



2009 PRODUCT SPECIFICATIONS

PRODUCT NAME	Max Zoom® 2552	Max Zoom® 2560	Zoom® 2042 XL	Zoom® 2548 XL
MODEL NUMBER	991065	991056	915137	915139
WARRANTY	2 Year	2 Year	2 Year	2 Year
ENGINE	Kohler® Courage V-Twin	Kohler® Courage V-Twin	Kohler® Courage V-Twin	Kohler® Courage V-Twin
HORSEPOWER	25	25	20	25
DRIVE SYSTEM	ZT2800 Transaxles	ZT2800 Transaxles	ZT2800 Transaxles	ZT2800 Transaxles
FUEL CAPACITY — Gallons (LITERS)	7 gallon (26.5L)	7 gallon (26.5L)	4.5 gallon (17L)	4.5 gallon (17L)
GROUND SPEED (APPX. Mph) (Forward/Reverse)	8 mph/4 mph	8 mph/4 mph	7 mph/3 mph	7 mph/3 mph
STARTER	Electric	Electric	Electric	Electric
DECK				
DECK MATERIAL	10 ga Steel w/ .25" Spindle Reinforcement	10 ga Steel w/ .25" Spindle Reinforcement	10 ga w/ Doubler Plate	10 ga w/ Doubler Plate
DECK CONSTRUCTION	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	17,000	16,800
SPINDLE MATERIAL	Ductile Cast Iron	Ductile Cast Iron	Aluminum	Aluminum
SPINDLE SHAFT	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel
SPINDLE BEARINGS	1" Sealed	1" Sealed	1" Sealed	1" Sealed
DECK DRIVE	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GT1A Electric Clutch	Ogura® GT1A Electric Clutch	Warner® Electric	Warner® Electric
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	52"	60"	42"	48"
CUTTING HEIGHTS	1"-5"	1"-5"	1.5"-4.5"	1.5"-4.5"
CUTTING POSITIONS	9	9	7	7
WHEELS				
FRONT AXLE	Fixed	Fixed	Fixed	Fixed
FRONT	13 x 5-6	13 x 5-6	11 x 4	11 x 4
REAR	20 x 10-10	20 x 10-10	20 x 10	20 x 8
FEATURES				
SAFETY	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant
HOOD	N/A	N/A	Standard	Standard
HEADLIGHTS	Optional	Optional	Optional	Optional
SEAT	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs
HOURLY METER	Standard	Standard	Standard	Standard
MACHINE DIMENSION				
WEIGHT (LBS)	810	830	615	630
LENGTH (INCHES)	74.5"	74.5"	69"	69"
WIDTH (INCHES) Dimensions are measured with the chute down unless otherwise noted	55.5" (w/o chute)	62.8" (w/o chute)	52"	58"
HEIGHT (INCHES)	42"	42"	42"	42"
OPTIONAL ATTACHMENTS/ACCESSORIES				
Bagger Kit, Mulching Kit, Striper Kit, Discharge Cover Kit, Trailer Hitch Kit, Suspension/Seat Kit, Roller, Aerator, Dethatcher, Sprayer			Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit, Headlight Kit, Sun Shade, Spreader, Cart, Snow Blade Snow Head	

Zoom® 34		Zoom® 2040		Zoom® 2350		Tractors			
915131		915133		915135		936039		936040	
2 Year		2 Year		2 Year		2 Year		2 Year	
Briggs & Stratton® I/C		Kohler® Courage Single		Kohler® Courage V-Twin		Kohler® Courage Single		Kohler® Courage V-Twin	
344cc		20		23		20		25	
EZT Transaxles with 1" Axle		EZT Transaxles with 1" Axle		EZT Transaxles with 1" Axle		Hydrostatic		Hydrostatic	
2.5 gallon (12.3L)		3.25 gallon (12.3L)		3.25 gallon (12.3L)		3.0 (11.4L)		3.0 (11.4L)	
6 mph/3mph		6 mph/3mph		6 mph/3mph		5.5 mph/2.5 mph		5.5 mph/2.5 mph	
Electric		Electric		Electric		Electric		Electric	
12 ga		12 ga w/ Doubler Plate		12 ga w/ Doubler Plate		12 ga		10 ga	
Stamped		Stamped		Stamped		Stamped		Stamped	
2		3		3		2		3	
17,100		15,000		16,600		19,000		19,000	
Steel		Aluminum		Aluminum		Steel		Steel	
1" Dia. Steel		1" Dia. Steel		1" Dia. Steel		Steel		Steel	
1" Sealed		1" Sealed		1" Sealed		Sealed		Greaseable	
Belt		Belt		Belt		Belt		Belt	
Soft Touch Electric		Electric Warner		Electric Warner		PTO Lever		PTO Electric	
Foot Operated		Foot Operated		Foot Operated		Manual, Spring Assist		Manual, Spring Assist	
34"		40"		50"		46"		54"	
1"-4"		1.5"-4.5"		1.5"-4.5"		1.5"-4"		1.5"-4"	
8		8		8		6		6	
Fixed		Fixed		Fixed		Stamped Steel		Cast Iron	
11 x 4		11 x 4		11 x 4		15 x 6.5		15 x 6.5	
18 x 6.5		18 x 8.5		18 x 9.5		18 x 9.5		20 x 8	
ANSI Compliant		ANSI Compliant		ANSI Compliant		ANSI Compliant		ANSI Compliant	
Standard		Optional		Optional		Standard-Tall		Standard-Tall	
N/A		Optional		Optional		Standard		Standard	
Low Back w/ Seat Springs		Mid Back w/ Seat Springs		Mid Back w/ Seat Springs		15" slide		15" slide	
N/A		N/A		N/A		N/A		N/A	
425		520		540		615		728	
64"		70"		70"		72.75"		72.75"	
42"		44"		57"		49.5"		52.5"	
37"		40"		40"		46"		46"	
Non-Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit, Spreader, Cart, Roller, Aerator, Dethatcher, Sprayer		Powered Bagger Kit, Mulching Kit, Headlight Kit, Sun Shade, Spreader, Cart, Roller, Aerator, Dethatcher, Sprayer				Bagger Kit, Mulching Kit			

PRODUCT NAME		Wide Area Walk 1034	Pro 21 SP	Blade Runner™ P	Blade Runner™ SP	Blade Runner™ SPE
MODEL NUMBER	911403	911252	911150	911152	911156	
WARRANTY	2 Year	2 Yr Consumer, 1 Yr Commercial	2 Year	2 Year	2 Year	
ENGINE	Briggs & Stratton® I/C	Kawasaki®	Kohler® XT-7	Kohler® XT-7	Kohler® XT-7	
ENGINE RATING	10.5 hp	6 hp	7 ft-lbs Net Torque	7 ft-lbs Net Torque	7 ft-lbs Net Torque	
DRIVE SYSTEM	Variable Speed Belt Drive	Variable Speed Belt Drive	Variable Speed Belt Drive	Variable Speed Belt Drive	Variable Speed Belt Drive	
FUEL CAPACITY — Gallons (LITERS)	0.75 gallon (2.83L)	0.53 gallon (2L)	0.37 gallon (1.4L)	0.37 gallon (1.4L)	0.37 gallon (1.4L)	
GROUND SPEED (APPX. Mph) (Forward/Reverse)	4 mph Forward/ 2 mph Reverse	3.75 mph	Push	2.75 mph	2.75 mph	
STARTER	Electric Start	Recoil	Recoil	Recoil	Recoil/E.S.	
DECK						
DECK MATERIAL	14 ga	14 ga	14 ga	14 ga	14 ga	
DECK CONSTRUCTION	Stamped	Stamped	Stamped	Stamped	Stamped	
NUMBER OF SPINDLES	2	1	1	1	1	
BLADE TIP SPEED (FPM)	17,500	17,500	18,000	18,000	18,000	
SPINDLE MATERIAL	Steel	Steel	Steel	Steel	Steel	
SPINDLE SHAFT	1"	7/8"	7/8"	7/8"	7/8"	
SPINDLE BEARINGS	Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball	
DECK DRIVE	Belt	Direct	Direct	Direct	Direct	
DECK ENGAGEMENT	PTO Lever	N/A	N/A	N/A	N/A	
DECK LIFT SYSTEM	Manual	Manual	Manual	Manual	Manual	
CUTTING WIDTH	34"	21"	21"	21"	21"	
CUTTING HEIGHTS	1.5"-3.5"	1"-4"	1"-4"	1"-4"	1"-4"	
CUTTING POSITIONS	6	13 (2 zones)	7	7	7	
WHEELS						
FRONT AXLE	Swivel	Yes	No	No	No	
FRONT	8	8.25	8.5	8.5	8.5	
REAR	13	8.25	8.5	8.5	8.5	
FEATURES						
SAFETY	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	
HOOD	No	No	No	No	No	
HEADLIGHTS	No	No	No	No	No	
SEAT	No	No	No	No	No	
HOUR METER	No	No	No	No	No	
MACHINE DIMENSION						
WEIGHT (LBS)	275	125	78	92	92	
LENGTH (INCHES)	67"	62.5"	70"	70"	70"	
WIDTH (INCHES)	44.5"	23.5"	21.5"	21.5"	21.5"	
HEIGHT (INCHES)	38"	40.6"	47"	47"	47"	
OPTIONAL ATTACHMENTS/ACCESSORIES						
Mulching Kit, Bagger, Discharge Plug		Mulching Kit	Bagger Kit, Height of Cut Extension Kit, High Lift Blade			

Classic LM 21	Classic LM 21S	Classic LM 21S	Classic LM 21SW	Classic LM 21SW
911160	911133	911162	911134	911164
2 Year	2 Year	2 Year	2 Year	2 Year
Kohler® XT-7	Kawasaki® FJ180V	Kohler® XT-7	Kawasaki® FJ180V	Kohler® XT-7
7 ft-lbs Net Torque	6 hp	7 ft-lbs Net Torque	6 hp	7 ft-lbs Net Torque
Push	Infi-Speed or Variable Speed Drive – Disc-O-Matic™	Infi-Speed or Variable Speed Drive – Disc-O-Matic™	Infi-Speed or Variable Speed Drive – Disc-O-Matic™	Infi-Speed or Variable Speed Drive – Disc-O-Matic™
0.37 gallon (1.4L)	0.53 gallon (2L)	0.37 gallon (1.4L)	0.53 gallon (2L)	0.37 gallon (1.4L)
N/A	4 mph	4 mph	4 mph	4 mph
Recoil	Recoil	Recoil	Recoil	Recoil
14 ga	14 ga	14 ga	14 ga	14 ga
Stamped	Stamped	Stamped	Stamped	Stamped
1	1	1	1	1
18,000	18,000	18,000	18,000	18,000
Steel	Steel	Steel	Steel	Steel
7/8"	7/8"	7/8"	7/8"	7/8"
Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball
Direct	Direct	Direct	Direct	Direct
N/A	N/A	N/A	N/A	N/A
Manual	Manual	Manual	Manual	Manual
21"	21"	21"	21"	21"
1"-3.25"	1"-3.25"	1"-3.25"	1"-3.25"	1"-3.25"
6	6	6	6	6
Yes	Yes	Yes	Swivel	Swivel
7.5	7.5	7.5	7.5	7.5
10.5	10.5	10.5	10.5	10.5
ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant
No	No	No	No	No
No	No	No	No	No
No	No	No	No	No
No	No	No	No	No
100	104	104	121	121
61.5"	61.5"	61.5"	61.5"	61.5"
23"	23"	23"	23"	23"
38"	38"	38"	38"	38"
Bagger Kit, Mulching Kit				



© Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kawasaki, Kohler, Honda, TecumsehPower and Quantum are registered trademarks for their respective companies. HP is a function of the engine manufacturer's rating. Mower features and specifications subject to change without notice.

