



CONQUERROAD

/// WHY DO WE RIDE?

IT'S BECAUSE NOTHING COMPARES TO THE FEELING OF THROWING A LEG OVER YOUR BIKE. IT'S LIVING, FEELING AND BREATHING THE OUTDOORS WHILE YOU ROLL ON THE THROTTLE. IT'S THE RUSH OF THE PAVEMENT FLYING MERE INCHES BENEATH YOUR FEET AS YOU LEAN INTO A CORNER. IT'S THE BUG-FILLED GRIN YOU CAN'T WIPE OFF YOUR FACE AS THE KILOMETRES ACCUMULATE ON THE ODOMETER. IT'S FOR THE REASON THAT SOMETIMES, YOU FIND YOURSELF IN THE MIDDLE OF NOWHERE; AND OTHER TIMES, IN THE MIDDLE OF NOWHERE, YOU FIND YOURSELF. IT'S BECAUSE YOU ARE A MOTORCYCLIST AND YAMAHA IS YOUR BIKE.

ON FOUR WHEELS, YOU'RE A PASSENGER OF THE PAVEMENT. ON TWO, YOU CONQUER ROAD.





BOLT









R-SPEC MATTE METALLIC GREY





LCD, digital speedometer.



Vintage-design LED taillight.



Clean, quiet belt drive system is extremely low-maintenance and simplifies customization.

SPECIFICATIONS	BOLT / BOLT R-SPEC
Engine Type	942 cc, air-cooled, SOHC, 8-valves, 60-degree, V-twin
Bore & Stroke	85 x 83 mm
Compression Ratio	9:1
Maximum Torque	8.2 kg-m (59.3 ft-lb) @ 3,000 rpm
Fuel Delivery	Dual 35 mm throttle body FI
Estimated Fuel Consumption*	20 kpl / 57 mpg (imp.)
Ignition	TCI / Electric
Transmission	5-speed
Final Drive	Belt
Suspension/Front	41-mm fork
Suspension/Rear	Preload adjustable dual shocks Preload adjustable dual premium gas shocks – <i>R-Spec</i>
Brakes/Front	298-mm disc / twin-piston caliper
Brakes/Rear	298-mm disc / single-piston caliper
Tire/Front	100/90 x 19
Tire/Rear	150/80 x 16
LxWxH	2,290 x 830 x 1,120 mm (90.2" x 37.2" x 44.1")
Seat Height	690 mm (27.2")
Wheelbase	1,570 mm (61.8")
Wet Weight	247 kg (545 lb)
Fuel Capacity	12 litres (2.6 imp. gal.)

* Fuel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your vehicle, accessories, cargo and operator/passenger weight.

STRATOLINER





S SILVER

DELUXE COCKTAIL RED



1,854 cc V-twin engine produces massive torque and class-leading acceleration.





Saddlebags provide ample storage.

Handlebar-mounted audio controller. (Deluxe)



The Stratoliner Deluxe is equipped with a Garmin zūmo® 665 GPS / navigation system.

SPECIFICATIONS	STRATOLINER S / STRATOLINER DELUXE
Engine Type	1,854 cc, air-cooled, OHV, 8-valves, 48-degree, V-twin
Bore & Stroke	100 x 118 mm
Compression Ratio	9.5:1
Maximum Torque	17 kg-m (123 ft-lb) @ 2,250 rpm
Fuel Delivery	Dual 43 mm cross bore downdraft throttle body Fl
Estimated Fuel Consumption*	18 kpl / 51 mpg (imp.) – <i>S</i> 16.5 kpl / 46 mpg (imp.) – <i>Deluxe</i>
Ignition	TCI / Electric
Transmission	5-speed
Final Drive	Belt
Suspension/Front	46-mm fork
Suspension/Rear	Adjustable link Monocross
Brakes/Front	Dual 298-mm discs / 4-piston calipers
Brakes/Rear	320-mm disc / single-piston caliper
Tire/Front	130/70R18
Tire/Rear	190/60R17
LxWxH	2,580 x 1,055 x 1,515 mm – S (101.6" x 41.5" x 59.6") 2,580 x 1,100 x 1,260 mm – <i>Deluxe</i> (101.6" x 43.3" x 49.6")
Seat Height	705 mm (27.8")
Wheelbase	1,715 mm (67.5")
Wet Weight	369 kg (813 lb) – <i>S</i> 370 kg (816 lb) – <i>Deluxe</i>
Fuel Capacity	17 litres (3.7 imp. gal.)

* Fuel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your vehicle, accessories, cargo and operator/passenger weight.



ROAD STAR






S DARK METALLIC VIOLE

SILVERADO S DARK METALLIC BLUISH GREY



"Police-style" windshield offers great wind and weather protection







2-into-2 exhaust system features beefy, staggered, dual shotgun pipes.

SPECIFICATIONS	ROAD STAR S / ROAD STAR SILVERADO S
Engine Type	1,670 cc, air-cooled, OHV, 8-valves, 48-degree, V-twin
Bore & Stroke	97 x 113 mm
Compression Ratio	8.4:1
Maximum Torque	13.9 kg-m (100.5 ft-lb) @ 2,500 rpm
Fuel Delivery	40 mm throttle body Fl
Estimated Fuel Consumption*	15 kpl / 43 mpg (imp.)
Ignition	TCI / Electric
Transmission	Wide ratio 5-speed
Final Drive	Belt
Suspension/Front	43-mm fork
Suspension/Rear	Adjustable link Monocross
Brakes/Front	Dual 298-mm discs / 4-piston calipers
Brakes/Rear	320-mm disc / 4-piston caliper
Tire/Front	130/90-16
Tire/Rear	150/80-16
LxWxH	2,500 x 980 x 1,140 mm — S (98.4" x 38.6" x 44.9") 2,500 x 980 x 1,500 mm — Silverado S (98.4" x 38.6" x 59.1")
Seat Height	710 mm (28")
Wheelbase	1,688 mm (66.5")
Wet Weight	337 kg (743 lb) – <i>S</i> 351 kg (774 lb) – <i>Silverado S</i>
Fuel Capacity	18 litres (4 imp. gal.)

uel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted o Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your licle, accessories, cargo and operator/passenger weight.



VMAX



MATTE METALLIC GRE



The iconic VMAX aluminum intaki



Dual floating 320-mm wave-style front rotors. Multi-function display panel.



Handlebar-mounted meter includes tachometer and digital speedo plus an adjustable shift light.

SPECIFICATIONS	VMAX
Engine Type	1,679 cc, liquid-cooled, DOHC, 16-valves, 65-degree, V-4
Bore & Stroke	90 x 66 mm
Compression Ratio	11.3:1
Maximum Torque	17 kg-m (123 ft-lb) @ 6,500 rpm
Fuel Delivery	Mikuni 48 mm Fl
Estimated Fuel Consumption*	11.4 kpl / 32 mpg (imp.)
Ignition	TCI / Electric
Transmission	5-speed (with slipper clutch)
Final Drive	Shaft
Suspension/Front	Fully adjustable 52-mm cartridge fork
Suspension/Rear	Fully adjustable link Monocross
Brakes/Front	Dual 320-mm discs with ABS & radial mount 6-piston caliper
Brakes/Rear	298-mm disc with ABS & single-piston calipers
Tire/Front	120/70R18
Tire/Rear	200/50R18
LxWxH	2,395 x 820 x 1,190 mm (94.3" x 32.3" x 46.9")
Seat Height	775 mm (30.5")
Wheelbase	1,700 mm (66.9")

* Fuel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted into Canadian measurements. Your actual milleage will wary depending on road condition, how you ride, maintain your vehicle, accessories, cargo and operator/passenger weight.

310 kg (684 lb) 15 litres (3.3 imp. gal.)



RADER







Classic fuel tank-mounted instrument panel.





5-spoke cast aluminium 21" front wheel.



Dual 298-mm floating front discs are squeezed by ultra-rigid, 4-piston, monoblock calipers.

SPECIFICATIONS	RAIDER / RAIDER S
Engine Type	1,854 cc, air-cooled, OHV, 8-valves, 48-degree, V-twin
Bore & Stroke	100 x 118 mm
Compression Ratio	9.5:1
Maximum Torque	17 kg-m (123 ft-lb) @ 2,500 rpm
Fuel Delivery	Dual 43 mm cross bore downdraft throttle body FI
Estimated Fuel Consumption*	18 kpl / 51 mpg (imp.)
Ignition	TCI / Electric
Transmission	5-speed
Final Drive	Belt
Suspension/Front	46-mm fork
Suspension/Rear	Adjustable link Monocross
Brakes/Front	Dual 298-mm discs / 4-piston calipers
Brakes/Rear	310-mm disc / single-piston caliper
Tire/Front	120/70-21
Tire/Rear	210/40R18
LxWxH	2,570 x 925 x 1,165 mm (101.2" x 36.4" x 45.9")
Seat Height	695 mm (27.4")
Wheelbase	1,800 mm (70.9")
Wet Weight	331 kg (730 lb)
Fuel Capacity	16 litres (3.5 imp. gal.)

^{*} Fuel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your vehicle, accessories, cargo and operator/passenger weight.

STRYKER







MATTE METALLIC GREY

VIVID PURPLISH BLUE







Lightweight 5-spoke cast aluminum wheels. Clean, quiet low-maintenance belt drive.





One-piece rider and passenger seat offers a low 670-mm (26.4") seat height and great styling.

000000000000000000000000000000000000000	
SPECIFICATIONS	STRYKER
Engine Type	1,304 cc, liquid-cooled, SOHC, 8-valves, 60 degree, V-twin
Bore & Stroke	100 x 83 mm
Compression Ratio	9.5:1
Maximum Torque	10.9 kg-m (78.8 ft-lb) @ 3,500 rpm
Fuel Delivery	Mikuni 40 mm dual bore throttle body Fl
Estimated Fuel Consumption*	17 kpl / 48 mpg (imp.)
Ignition	TCI / Electric
Transmission	5-speed
Final Drive	Belt
Suspension/Front	41-mm fork
Suspension/Rear	Adjustable link Monocross
Brakes/Front	320-mm disc / twin-piston caliper
Brakes/Rear	310-mm disc / single-piston caliper
Tire/Front	120/70-21
Tire/Rear	210/40R18
LxWxH	2,530 x 860 x 1,130 mm (99.6" x 33.9" x 44.5")
Seat Height	670 mm (26.4")
Wheelbase	1,750 mm (68.9")
Wet Weight	293 kg (646 lb)
Fuel Capacity	15 litres (3.3 imp. gal.)


Fuel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your vehicle, accessories, cargo and operator/passenger weight.



V-STAR 1300 DELUXE









iPod® / iPhone®-ready audio system features dual fairing-mounted speakers.

	-	
		1
		1
		H

14.1		
	1	
-		

PECIFICATIONS	V-STAR 1300 DELUXE
ngine Type	1,304 cc, liquid-cooled, SOHC , 8-valves, 60-degree, V-twin
ore & Stroke	100 x 83 mm
ompression Ratio	9.5:1
laximum Torque	11.3 kg-m (81.8 ft-lb) @ 4,000 rpm
uel Delivery	Mikuni dual bore 40 mm Fl
stimated Fuel onsumption*	18 kpl / 51 mpg (imp.)
nition	TCI / Electric
ransmission	5-speed
inal Drive	Belt
uspension/Front	41-mm fork
uspension/Rear	Adjustable link Monocross
rakes/Front	Dual 298-mm discs / twin-piston calipers
rakes/Rear	298-mm disc / single-piston caliper
ire/Front	130/90-16
ire/Rear	170/70-16
x W x H	2,490 x 1,060 x 1,475 mm (98" x 41.8" x 58.1")
eat Height	690 mm (27.2")
/heelbase	1,690 mm (66.5")
/et Weight	331 kg (729.7 lb)
uel Capacity	18.5 litres (4.1 imp. gal.)

into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain you

V-STAR 1300















Tourer model features backrest and hard leather-covered saddlebags.

SPECIFICATIONS	V-STAR 1300 / V-STAR 1300 TOURER
Engine Type	1,304 cc, liquid-cooled, SOHC , 8-valves, 60-degree, V-twin
Bore & Stroke	100 x 83 mm
Compression Ratio	9.5:1
Maximum Torque	11.3 kg-m (81.8 ft-lb) @ 4,000 rpm
Fuel Delivery	Mikuni dual bore 40 mm Fl
Estimated Fuel Consumption*	18 kpl / 51 mpg (imp.)
Ignition	TCI / Electric
Transmission	5-speed
Final Drive	Belt
Suspension/Front	41-mm fork
Suspension/Rear	Adjustable link Monocross
Brakes/Front	Dual 298-mm discs / twin-piston calipers
Brakes/Rear	298-mm disc / single-piston caliper
Tire/Front	130/90-16
Tire/Rear	170/70-16
LxWxH	2,490 x 1,000 x 1,145 mm (98" x 39.4" x 45.1") 2,490 x 1,000 x 1,520 mm – <i>Tourer</i> (98" x 39.4" x 59.8")
Seat Height	690 mm (27.2")
Wheelbase	1,690 mm (66.5")
Wet Weight	303 kg (668 lb) 323 kg (712 lb) – Tourer
Fuel Capacity	18.5 litres (4.1 imp. gal.)

into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your



U-STAR 950





DEEP METALLIC RED

TOURER METALLIC BLACK



942-cc engine produces outstanding low and mid-range torque.







Leather-covered hard shell saddlebags feature a stylish tapered design.

SPECIFICATIONS V-STAR 950 / V-STAR 950 TOURER Engine Type 942 cc, air-cooled, SOHC, 8-valves, 60-degree, V-twin Bore & Stroke 85 x 83 mm Compression Ratio 9:1 Maximum Torque 8 kg-m (57.9 ft-lb) @ 3,500 rpm Fuel Delivery 35 mm dual bore throttle body Fl Estimated Fuel Consumption* 20 kpl / 57 mpg (imp.) Ignition TCI / Electric Transmission 5-speed Final Drive Belt Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Fear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") (2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) (298 kg (657 lb) - Tourer Fuel Capacity 17 litres (3.7 imp. gal.)		
Bore & Stroke 85 x 83 mm 9:1	SPECIFICATIONS	V-STAR 950 / V-STAR 950 TOURER
Compression Ratio 9:1 Maximum Torque 8 kg-m (57.9 ft-lb) @ 3,500 rpm Fuel Delivery 35 mm dual bore throttle body Fl Estimated Fuel Consumption* 20 kpl / 57 mpg (imp.) Ignition TCI / Electric Transmission 5-speed Final Drive Belt Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Engine Type	
Maximum Torque 8 kg-m (57.9 ft-lb) @ 3,500 rpm Fuel Delivery 35 mm dual bore throttle body Fl Estimated Fuel Consumption* 20 kpl / 57 mpg (imp.) Ignition TCl / Electric Transmission 5-speed Final Drive Belt Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Bore & Stroke	85 x 83 mm
Fuel Delivery 35 mm dual bore throttle body FI Estimated Fuel Consumption* 20 kpl / 57 mpg (imp.) Ignition TCI / Electric Transmission 5-speed Final Drive Belt Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Compression Ratio	9:1
Estimated Fuel Consumption* Ignition TCI / Electric Transmission 5-speed Final Drive Belt Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Maximum Torque	8 kg-m (57.9 ft-lb) @ 3,500 rpm
Consumption* Ignition TCI / Electric Transmission 5-speed Final Drive Belt Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Fuel Delivery	35 mm dual bore throttle body Fl
Transmission 5-speed Final Drive Belt Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	201111010011001	20 kpl / 57 mpg (imp.)
Final Drive Belt Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm — Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) — Tourer	Ignition	TCI / Electric
Suspension/Front 41-mm fork Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Transmission	5-speed
Suspension/Rear Adjustable link Monocross Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Final Drive	Belt
Brakes/Front 320-mm disc / twin-piston caliper Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Suspension/Front	41-mm fork
Brakes/Rear 298-mm disc / single-piston caliper Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Suspension/Rear	Adjustable link Monocross
Tire/Front 130/70-18 Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm - Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) - Tourer	Brakes/Front	320-mm disc / twin-piston caliper
Tire/Rear 170/70-16 L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm — Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) — Tourer	Brakes/Rear	298-mm disc / single-piston caliper
L x W x H 2,435 x 1,000 x 1,080 mm (95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm – Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) – Tourer	Tire/Front	130/70-18
(95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm – Tourer (95.9" x 39.4" x 52.8") Seat Height 675 mm (26.6") Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) – Tourer	Tire/Rear	170/70-16
Wheelbase 1,685 mm (66.3") Wet Weight 278 kg (613 lb) 298 kg (657 lb) – Tourer	LxWxH	(95.9" x 39.4" x 42.5") 2,435 x 1,000 x 1,340 mm – <i>Tourer</i>
Wet Weight 278 kg (613 lb) 298 kg (657 lb) – <i>Tourer</i>	Seat Height	675 mm (26.6")
298 kg (657 lb) – Tourer	Wheelbase	1,685 mm (66.3")
Fuel Capacity 17 litres (3.7 imp. gal.)	Wet Weight	
	Fuel Capacity	17 litres (3.7 imp. gal.)

* Fuel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your vehicle, accessories, cargo and operator/passenger weight.

V-STAR 650





649-cc V-twin powerplant pumps out impressive power and torque.



Stylish chromed speedo sits atop the 16-litre tank.





CUSTOM SILVER

CLASSIC METALLIC BLACK

SPECIFICATIONS	V-STAR 650 CUSTOM / V-STAR 650 CLASSIC
Engine Type	649 cc, air-cooled, SOHC, 4-valves, 70-degree, V-twin
Bore & Stroke	81 x 63 mm
Compression Ratio	9:1
Maximum Torque	5.2 kg-m (37.6 ft-lb) @ 3,000 rpm
Fuel Delivery	Mikuni BDS28 x 2
Estimated Fuel Consumption*	21 kpl / 59 mpg (imp.)
Ignition	TCI / Electric
Transmission	5-speed
Final Drive	Shaft
Suspension/Front	41-mm fork
Suspension/Rear	Adjustable link Monocross
Brakes/Front	Single 298-mm disc / twin-piston caliper
Brakes/Rear	Drum
Tire/Front	100/90-19
Tire/Rear	170/80-15
LxWxH	2,340 x 880 x 1,075 mm — <i>Custom</i> (92.1" x 34.6" x 42.3") 2,450 x 930 x 1,110 mm — <i>Classic</i> (96.5" x 36.6" x 43.7")
Seat Height	695 mm (27.4") – <i>Custom</i> 710 mm (28") – <i>Classic</i>
Wheelbase	1,610 mm (63.4") – <i>Custom</i> 1,625 mm (64") – <i>Classic</i>
Wet Weight	233 kg (514 lb) - Custom, 247 kg (545 lb) - Class
Fuel Capacity	16 litres (3.5 imp. gal.)

* Fuel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your vehicle, accessories, cargo and operator/passenger weight.

V-STAR 250





Instrumentation includes a centrally located speedo with tripmeter and a full range of indicator lights.



Spoked, chrome wheels fitted with a narrow front and wide 130-series rear tire.





METALLIC RED

BLUISH WHIT

SPECIFICATIONS	V-STAR 250
Engine Type	249 cc, air-cooled, SOHC, 4-valves, 60-degree, V-twin
Bore & Stroke	49 x 66 mm
Compression Ratio	10:1
Maximum Torque	2.1 kg-m (15.2 ft-lb) @ 6,000 rpm
Fuel Delivery	Mikuni BDS26
Estimated Fuel Consumption*	32 kpl / 93 mpg (imp.)
Ignition	TCI / Electric
Transmission	5-speed
Final Drive	Chain
Suspension/Front	33-mm fork
Suspension/Rear	Adjustable dual shocks
Brakes/Front	282-mm disc / twin-piston caliper
Brakes/Rear	Drum
Tire/Front	3.00-18
Tire/Rear	130/90-15
LxWxH	2,190 x 710 x 1,060 mm (86.2" x 28" x 41.7")
Seat Height	685 mm (27")
Wheelbase	1,490 mm (58.7")
Wet Weight	147 kg (324 lb)
Fuel Capacity	9.5 litres (2.1 imp. gal.)

* Fuel economy estimates are based on US EPA exhaust emission certification data obtained by Yamaha and converted into Canadian measurements. Your actual mileage will vary depending on road condition, how you ride, maintain your vehicle, accessories, cargo and operator/passenger weight.

ACCESSORIES: ENDLESS COMBINATIONS









CUSTOMIZE YOUR RIDE WITH A GENUINE YAMAHA WINDSHIELD. FROM BOULEVARD TO QUICK-RELEASE, WE OFFER A VARIETY OF HEIGHTS AND STYLES TO SUIT ANY RIDER.

STARTING FROM \$125.95









ADD SOME STORAGE AND CONVENIENCE, AND YOU HAVE A WHOLE NEW RIDING EXPERIENCE. WHETHER YOU PREFER LEATHER, HARD, SMALL OR LARGE, WE HAVE THE SADDLEBAGS AND LUGGAGE TO SUIT YOUR TRAVELLING NEEDS.

STARTING FROM \$72.95









MAKE IT SHINE OR MAKE IT SUBTLE. WITH YAMAHA'S QUALITY FIT AND FINISH YOU CAN TRANSFORM YOUR VISION INTO REALITY.

STARTING FROM \$22.95

WANT TO SEE MORE? VISIT YAMAHA-MOTOR.CA/PNA









ENHANCE THE COMFORT AND STYLE OF YOUSELF AND YOUR PASSENGER WITH A LEATHER SEAT OR BACKREST.

STARTING FROM \$41.95

IES: ENDLESS COMBINATIONS










UPGRADE YOUR STOCK RIDER OR PASSENGER FLOORBOARDS WITH FINELY-CHROMED COVERS AND FLOORBOARDS.

STARTING FROM \$43.95

WANT TO SEE MORE? VISIT YAMAHA-MOTOR.CA/PNA











STARTING FROM \$54.95

III HELMETS & GOGGLES RIDE SAFE. WITH THE RIGHT PROTECTIVE GEAR AND HOTTEST STYLES EXCLUSIVELY FROM YAMAHA! STREET HELMET STARTING FROM \$159.95 THE ALL-NEW "RAW" HELMETS FROM SHARK
































GET STYLING, WITH THE LATEST FUNCTIONAL, HOT-LOOKING LEATHERS, TEXTILES AND CASUAL WEAR.

JACKETS STARTING FROM \$129.95









PROTECT YOUR INVESTMENT FROM THE ELEMENTS WITH A GENUINE YAMAHA COVER. **STARTING FROM \$59.95**

WANT TO SEE MORE? VISIT YAMAHA-MOTOR.CA/PNA







FULL-SYNTHETIC FOUR-STROKE SAE 15W-50

Blended from fully-synthetic base oils and fortified with synthetic esters to provide the absolute highest performance and protection you can buy for your Yamaha. Recommended for motorcycles, ATVs and side by side vehicles.



SEMI-SYNTHETIC FOUR-STROKE **SAE 20W-50**

Specially formulated for V-twin engines. Carefully balanced frictional properties guarantee stable clutch performance for long enjoyable rides.



PERFORMANCE FOUR-STROKE **SAE 10W-40 & SAE 20W-50**

Blended with premium-quality mineral base stocks for use in motorcycles, scooters, ATVs and side by sides vehicles.

THE STAR TREATMENT

/// YAMALUBE® PRODUCTS FOR STAR MOTORCYCLES



Yamaclean® Instant Detailer

This waterless wash and detailer cleans, shines and protects virtually any surface on your Yamaha. Its organic polymer leaves a natural shine with a protective anti-static finish.



Yamaclean Pro-Wash Spray

Biodegradable vehicle spray that removes grease and grime. Rinses clean and keeps your vehicle



Ring Free Plus

Removes carbon and protects fuel system metals from ethanol fuel corrosion, 100 ml travel size treats 19 L of gas.



Fuel Stabilizer & **Conditioner PLUS**

Helps resist phase separation, deters ethanol corrosion and keeps stored fuel fresh. 100 ml travel size treats 19 L of gas.





20W-50 Semi-Synthetic Oil

Specially blended for cruisers, this JASO MA-certified, semi-synthetic oil provides excellent lubricity, as well as smooth shifting and clutch engagement.



External Engine

This powerful engine degreaser and cleaner removes grease, mud and grime. Safe on most rubber, plastic and painted surfaces.



Brake & Contact

Use this product to quickly clean brake dust from critical brake components and quickly clean parts leaving them residue free.



DIY WITH A YAMALUBE OIL **CHANGE KIT**

Yamalube is formulated with assistance from the same team of engineers that design and test Yamaha engines. Our engineers have access to proprietary information and specifications; nobody knows Yamaha engines better than they do! For your convenience, we have developed a wide range of Yamalube "Do It Yourself" oil change kits. These kits are model-specific and include oil, oil filter, drain gaskets, gloves and general instructions.

Selected kits are available in 3 different oil grades for normal, hot or cold weather use. Check our website for more details.







Always wear an approved helmet, eye protection and proper riding apparel. Do not drink or take drugs and ride. Read your owner's manual. Always ride safely and defensively. Obey all provincial and federal laws and respect the environment. Every motorcyclist should be aware of the limits of his or her skill level and experience and ride accordingly. Novice riders should be extremely cautious and allow extra time and distance for manoeuvring and braking. All information, specifications and appearance of Yamaha products contained in the brochure are subject to change without notice. Yamaha encourages you to enroll in a recognized motorcycle safety training course. Some U.S. and European models shown. Canadian models may vary slightly. The VMAX model is not intended for novice or inexperienced riders.

Yamaha Motor Canada Ltd. reserves the right, at any time, to discontinue or change specifications, prices, designs, features, accessories or equipment without incurring any obligation or liability. Although the content of this brochure is believed to be accurate at time of printing, precision cannot be guaranteed. Some images depicted herein may include optional equipment or are sold separately. Prices are based on Manufacturer's Suggested Retail Prices. Dealers are at liberty to set their own pricing. Taxes and installation of accessories are not included in prices shown. See your Yamaha dealer for the most up-to-date and accurate information.

This document contains many of the valuable trademarks and service marks owned and used by Yamaha throughout the world. This document may also contain references to other company, brand, and product names that may be the trademarks/service marks of their respective owners. These company, brand, and product names are used herein for identification purposes only, and references to any names, marks, products or services of third parties do not constitute or imply endorsement, sponsorship or recommendation of the third party or the products or services.

Yamaha Motor Canada Ltd., 480 Gordon Baker Road, Toronto, ON M2H 3B4







