


8 Port 17" VGA LCD KVM Console (XL1708)




Date: 2017 / 01
Version: V3.1

Overview

The XL1708 VGA 17" LCD KVM console is a control unit that allows access to multiple computers from an USB or PS/2 KVM console. An extra console port is provided on the rear panel to manage the LCD KVM switch from an external console. It allows to access and control up to 8 computers from a single console (keyboard, mouse, and monitor). As many as 256 computers can be controlled from a single keyboard- monitor-mouse console by cascading to another 31 additional switches. The KVM switch supports USB or PS/2 connections for the console and computers, VGA connectors and VGA cable are used to link to the computers.



1 LCD Monitor	6 Touchpad
2 Rear Bracket Slot	7 Handle
3 Display Menu Buttons	8 Release Switch
4 Mounting Bracket	9 Display Panel
5 Keyboard	10 Port Selection Buttons



Features


- 17" LED TFT monitor, high brightness, high resolution
- 1U height, suitable height for standard 19" rack mount, metal structure
- Ultra slim 99 keys keyboard with small numeric keyboard
- High resolution and high flexibility with touchpad; with two function buttons and scroll wheel

Switch Functions

- A single USB console controls up to 8 computers
- By daisy chaining up to 31 additional Combo-KVM, as many as 256 computers can be controlled from the single KVM console which supports 8 ports KVM seamless mixed cascade connection
- Dual interface – supports computers with PS/2 and USB keyboard and mouse
- Auto PS/2 and USB interface detection

- Supports wireless keyboard and mouse from different suppliers
- Two level password security – only authorized users view and control computers; up to four users and an administrator with a separate profile for each
- Users can set up different hot keys(【Scroll Lock】/【Caps Lock】/【F12】/【Ctrl】), auto scanning time, port display time, log out time, buzzer on/off and mouse on/off according to their different needs
- Broadcast mode – operations simultaneously performed on all selected computers
- Multiplatform support – Windows, Linux, Mac and Sun
- Supports multimedia USB keyboard(PC, Mac and Sun)
- Superior video quality – up to 1280×1024; DDC2B
- USB or PS/2 keyboard emulation--computer boot even the console focus is else where
- Convenient computer switching via front panel pushbuttons, hotkeys, OSD menu
- Automatically shows the computer position on the front panel LED screen under daisy chaining connection without DIP set by hand
- Auto scan feature for monitoring user-selected computers
- Hot pluggable – add or remove computers without having to power down the switch
- Quickly select your computer by naming the server or inputting SN number of the server

Connection Diagram



Specifications (17" VGA LCD KVM Console)

Function		XL1708
Computer Connections	Direct	8
	Max	256
Port Emulation	Keyboard, Mouse	PS/2, USB
LED Monitor	LED model	SXGA TFT
	View area	17 "
	Optimum resolution	1280×1024@75Hz
	Display color	16.7 M
	Brightness	250cd/m ² (T y p)
	Contrast ratio	1000 : 1 (T y p)
	Pixel pitch(mm)	0.264(H) × 0.264(W)
Mouse	X/Y resolution	>1000 points /inch, (40 points/mm)
	Roll wheel	Supports scroll wheel function
Keyboard		99 keys (82 keys main keyboard +17 independent small numeric keyboard)
Port Selection		Pushbuttons, hotkeys, OSD menu
Input Power		100V – 240Vac, 50 ~ 60Hz, <1.5A
Power Consumption		17W
Operating Temperature		0 – 40 °C
Storage Temperature		-20 – 60 °C
Humidity		0 – 80% RH, non-condensing
Net Weight		13.3kg
Product Dimension (W × D × H)		448mm×581mm×42.5mm
Package Dimension (W × D × H)		765mm×615mm×185mm
Optional Power Input		-36V– -72V DC