

Discover more online!




Maintenance guides




Illustrated cleaning guides




Warranty forms



Literature



LEED forms



Installation guides



Installation quickfacts

Even more great resources!

- BIM components
- SpecWizard by Arcat
- SDS sheets
- Detail drawings and CAD files
- High resolution swatch downloads
- Photo galleries - www.altropics.com
- Solutions by area type - ORs, labs and cleanrooms, kitchens, senior living and more!

Follow us



📞 USA 800 377 5597

📞 CANADA 800 565 4658

✉️ support@altro.com

🌐 www.altro.com

Content was correct at time of print. Altro reserves the right to change any detail. Please consult www.altro.com or your local Sales Representative for the latest product information.



Designed for possibilities.
Made for people.



Altro Classic™ 25 product datasheet

Traditional and industrial, Altro Classic 25 has been trusted for over 60 years

discover [altro.com/classic](https://www.altro.com/classic)

Altro Classic 25

Classic by name, classic by nature – Altro Classic 25 was the first ever safety flooring. It has been tried and trusted for over 60 years, and its traditional, industrial look is still popular today.

Altro Classic 25 provides lasting slip resistance, durability and abrasion resistance, making it ideal for use in heavy traffic areas – particularly in commercial kitchens.

Altro Classic 25 is easy to clean and maintain and is available in practical, dirt-hiding shades. It achieves an R11 slip resistance rating. Altro Stronghold 30 and Altro Atlas 40 are also great flooring options for commercial kitchens depending on your individual needs.

It is frequently specified with Altro Puraguard wall protection to create safe and durable environments in commercial and industrial kitchens, and also looks great paired with Altro Walkway 20, Altro Wood or Altro Lavencia.

Typical applications

Commercial kitchens, food preparation, back-of-house service areas, walk-in coolers and freezers

Features + benefits

- Ideal for heavy traffic areas, particularly commercial kitchens
- Achieves R11 slip resistance rating and SCoF of .9 dry, 1.0 wet
- Easy to clean and maintain
- Lasting abrasion resistance and durability
- Practical, dirt-hiding shades available
- FloorScore Certified / Low VOCs

Slip resistance



It is designers, specifiers and end users' responsibility to ensure flooring is fit for purpose, and it's part of our role here at Altro to help make this process easy. Our flooring is separated into three categories: safety, slip-resistant and smooth.

Altro Classic 25 is safety flooring. It's a perfect choice when there are frequent spillages of water and other contaminants present. Altro Classic 25 achieves our second highest level of slip resistance and is commonly installed in kitchens and back-of-house areas. For areas with constant greasy spills, Altro Stronghold 30 offers our highest level of slip resistance and maintains 1 in a million slip resistance even with vegetable oil, greasy water and flour underfoot.



Altro Easyclean

Rather than using a superficial surface coat, Altro Easyclean Technology is incorporated into the flooring while it is manufactured. This allows Altro flooring to benefit from enhanced cleaning and maintenance while still allowing our products slip resistant properties to shine through.

Smooth flooring will have a higher level of Altro Easyclean than a slip-resistant or safety floor.

- Industry-leading ease of cleaning
- Enhanced long-term cleanability
- Cleaning and maintenance cost savings
- Sustained long-term slip resistance
- Exceptional long-term durability
- Low dirt pick-up qualities
- Improved color retention






Littlers Butchers chose Altro Classic 25 and Altro Whiterock Chameleon.




Anvil X2594R11
WR101 / A1M72 LRV 11



Graphite X2546R11
WR86 / A1M86 LRV 21




Truffle X2545R11
WR153 / A1M239 LRV 17




Pewter Gray X2539R11
WR81 / A1M81 LRV 26




Walnut X2586R11
WR62 / A1M62 LRV 10




Blackberry X2547R11
WR100 / A1M100 LRV 7




Mushroom X2542R11
WR24 / A1M27 LRV 32




Quarry Red X2560R11
WR42 / A1M42 LRV 17




Aster X2549R11
WR286 / A1M286 LRV 17



Blue X2541R11
WR71 / A1M71 LRV 20



Whisper X2548R11
WR354 / A1M84 LRV 24



Legend X2544R11
WR231 / A1M73 LRV 10



Light reflectance values (LRV)

Please keep LRVs in mind when selecting walling for areas with dementia and Alzheimer's patients, seniors or individuals with poor vision.



Color matched weldrods (WR) and mastic (AM) are available. You'll find their product codes under product SKUs.





Exhibition Centre Dusseldorf chose Altro Classic 25 in Anvil.

Type + class		ASTM F1303	Type I, Grade 1, Class A, safety flooring
Thickness and wear layer		2.5mm .10", homogenous construction	
Roll dimensions		6'7" x 65'5 2m x 20m	
Weight		5.89 lbs./yd ² 3.2 kg/m ²	
Warranty		12 years	
Cleaning technology		Altro Easyclean	
Static coefficient of friction		ASTM D2047	.9 dry, 1.0 wet
Dynamic coefficient of friction		ANSI/NFSI B101.3	.60 wet DCOF
Ramp test		DIN 51130	R11
TRRL pendulum test		BS 7976 ASTM E303	45+
Static load limit		ASTM F970	1000 psi
Indentation		EN 433	≤ 0.10mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		ASTM F137	Pass
Light fastness		EN 20105-B02	≥ 6
Sound insulation		ISO 140-8	5dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Minimum operating temperature		-4°F (-20°C)	
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Recycled content		This product contains 10% post-consumer recycled content.	
Composition	Silicon carbide, aluminum trioxide and colored quartz aggregate throughout thickness of PVC.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altrofloors.com/downloads , training clinic information at altrofloors.com/training . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altrofloors.com/downloads . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

LEED facts			
LEED v4		This product may help contribute to the following credits	
Altro Classic 25		6	
	Materials and resources Contains recycled content	1	
	Materials and resources Renewable bio-based content	1	
	Materials and resources - EPD Environmental product declaration Type III product specific	1	
	Materials and resources - HPD Health product declaration	1	
	Environmental quality Low emitting materials, flooring	1	
	Environmental quality Low emitting materials, adhesives	1	

Discover more of our sustainability story and credentials at altro.com/sustainability



Looking for samples?

Order samples 24 hours a day,
7 days a week at
www.altro.com/samples