

Environmental Protection and Growth Management Department

BUILDING CODE SERVICES DIVISION | BUILDING PERMITTING

2307 West Broward Boulevard, Suite #300 • Fort Lauderdale, Florida 33312 • 954-765-4400 • Broward.org/Building

APPLICATION INFORMATION FOR WINDOWS/DOORS REPLACEMENT SHUTTER INSTALLATION

- 1. You are required to have two (2) complete sets of building plans that include the following:
 - All appropriate **Notices of Acceptance** (product approval).
 - A **floor plan sketch** indicating the windows to be replaced or the shutters to be installed.
 - A completed **Permit Application** which must show the total job value for construction including labor and materials.
 - If you are a contractor applying for a permit you will be required to submit proof of **Worker's Compensation Insurance.** Such proof of compensation must be evidenced by a certificate of coverage issued by the carrier, a valid exemption certificate approved by the department, or a copy of the employer's authority to self-insure and shall be presented each time the employer applies for a building permit.
 - If you are a homeowner applying for a permit, you will be required to complete an **Owner/Builder Affidavit,** in the presence of Permitting Staff and provide state-issued identification (Example: Florida Driver License).
- 2. If your project meets the criteria in the attached document, you may submit your plans for review. If they do not meet the criteria your plans must be designed by a State of Florida Registered Architect/Engineer.
- 2. After your plans have been reviewed, which can take up to 15 business days, you will be contacted to either, pick up your plans and address the corrections/changes that are required, or you will be informed that your permit is ready to be issued.
- 3. If your job is valued at \$2500 or more, upon issuance of your permit you will be required to file a **Notice of Commencement.** The Notice of Commencement must be filed with **Records, Taxes and Treasury Division (RTT)** located at 115 South Andrews Avenue, Room #114, Ft. Lauderdale. A copy of the Notice of Commencement containing the filing stamp from RTT is to be submitted to Building Code Services Division, prior to the first inspection. For further information, please call (954)831-4000 or send an email to records@broward.org.

(See reverse for updated requirement information)

Retrofit of Windows, Doors, Garage Doors, Shutters, and Skylights FBC 2004 Existing Building, Alteration Level 1

At the Board of Rules and Appeals meeting of February 9, 2006, an interpretation was approved for Retrofit of Windows, Doors, Garage Doors, Shutters and Skylights, of the 2004 Florida Building Code as follows:

- 1. Window or door buck inspections are not required the buck shall comply with Section 1714.5.4.1 specifically, unless otherwise tested, buck shall extend beyond the entire face of the window of door frame such that full support of the frame is provided.
- 2. A Florida Professional Engineer or Architect may modify the buck with fasteners as specified in a Notice of Acceptance. Such modification must be documented with a signed and sealed letter or drawing.
- 3. To obtain the required design pressure for a specific opening at a specific site, an individual must utilize one of the following and submit documentation as indicated.
 - a. A site specific (signed and sealed) by a Florida Professional Engineer or Architect, indicating the location of all retro openings and the required design pressure.
 - b. A site-specific plan (not sealed) indicating the location of all openings accompanied by a worst-case design pressure chart (signed and sealed) prepared by a Florida P.E. or Architect.
 - c. A site-specific plan (not sealed) indicating the location of all openings and indicating the required design pressure based on FBC table 1609.6(b & d) FRC Table R301.2.2 (2 & 3) for windows, doors, shutters, and skylights and table 1609.6E for garage doors.

Note: FBC Table 1609.6 (b & d) and FRC Table 1609 R301.2.2 (2 & 3) and 1609.6E has been adopted for retrofit windows, doors, shutters and skylights (only with a permit application date preceding September 1, 1994*, and is limited to building with a roof mean height of 30'.

4. Required design pressure is required to meet FBC Table 1609.6 (b & d) FRC Table R301.2.2 (2 & 3) or ASCE-7-02 for windows, doors, shutters and skylights and 1609.6E for garage doors.

Note: FBC Table 1609.6 (b & d) FRC Table R301.2.2 (2 & 3) 1609.6E may be used to determine wind pressure for retrofit of windows, door, garage doors and skylights, but only on buildings with a permit application prior to September 1, 2004, * and shall be limited to buildings with a maximum roof mean height of 30'.

*Buildings with a permit application date on or after September 1, 1994, design measures were required to be shown on plans, should be used for retro.

EFFECTIVE DATE: JANUARY 20, 2020

Board of Rules & Appeals Policy 20-01

Subject: "Broward County Uniform Retrofit Window & Door Schedule"

POLICY


Each permit application for a window and door replacement "retrofit", shall be submitted to all jurisdictions in Broward County using the attached "Broward County Uniform Retrofit Window & Door Schedule"

This form does not relieve the permit holder, building owner or contractor from complying with all and any applicable local regulations or ordinances related to zoning, building, fire prevention, etc.; or prohibits a Broward County jurisdiction from requiring additional information to be provided in relation to applicable local regulations or ordinances related to zoning, building, fire prevention, etc.

Use of the "Broward County Uniform Retrofit Window & Door Schedule" is mandatory countywide starting July 1, 2020.

Uniform Retrofit Window & Door Schedule attached.

INSTRUCTION FLOWCHART



DESIGN CRITERIA REQUIREMENTS FOR PLANS


- 1. Unit sketch, generally to scale illustrating the unit and overall building (if multi-family).
- 2. Broward requires ASCE 7 calculations using Peak wind velocity Vult(min) = 170mph
- 3. Either Exposure C (inland) or D (coastal see description next page)
- 4. Mean (average) Roof height (see page 3)
- 5. Overall Building Width & Length (lessor dimension is used to determine width of zone 5)
- 6. Label each opening dimensions, wind zone (4 or 5) on the layout as shown in example on page 3
- 7. Each opening shall have a corresponding "mark" which ties into the window, door & mullion schedule provided within this packet

SITE SPECIFIC LAYOUT GUIDE INSTRUCTIONS - PAGE 2 of 3


Explanation of Terms

- 1: Exposure C: All of Broward County. The "Broward County Fenestration Voluntary Wind Load Chart" included within this packet can be used for all detached one & two story dwellings and multiple single-family dwellings (townhomes).
- 2: Exposure D: A structure that's within 600' or 20X building height of a flat area/body of water that's a mile long. Generally all areas east of the Intercoastal Waterway. Wind load pressures must be completed by a licensed design professional for all structures
- 3: Mean Roof Height ("h"): Average between the lowest and the highest roof point of a sloped roof, also the highest point of a flat roof (also see page 3).
- 4: Minimum Building Width: 10% of least horizontal dimension (W) or 0.4h, whichever is smaller, but not less than either 4% of least horizontal dimension or 3'ft minimum.


MIN. BUILDING WIDTH EXAMPLES (PLAN VIEW):



Mean Roof Height



ZONE EXAMPLES (PLAN VIEW)



- (INDICATES BUILDING CORNER DISCONTINUITY (ZONE 5)
- √ INDICATES AN OBSTRUCTED EXTERIOR CORNER (ZONE 4)
- () INDICATES A TYPICAL INTERIOR CORNER (ZONE 4)

NOTE: The corner designated by an * would not be considered a corner if dimension W is less than half the width of the corner zone and dimension X and Y are greater than the width of a corner zone

170 degree:

An unobstructed exterior corner with an interior angle of less than 170 degree would be considered a corner zone


See page 3 for example on how to calculate the zone dimensions of a building

SITE SPECIFIC LAYOUT GUIDE INSTRUCTIONS - PAGE 3 of 3

Minimum Sketch Requirement

Zone determinations:

- Zone 5 (corner zone) in this example is calculated as 5'ft in width, any opening within 5'ft of an outside unobstructed corner would be considered in zone 5.
- In this example, openings 1,
 3 & 10 are located in a
 zone 5 (corner zone).
- All other opening would be considered zone 4 (interior zone).




ZONE CALCULATIONS:

Zone 5 = .10 x least horizontal dimension (50ft x .10 = 5ft) or .4 x"h" (14ft x 0.4 = 5.6ft) whichever is smaller, but not less than either 4% of the least horizontal dimension (50ft x 4% = 2ft), or 3ft.

Zone 5 (corner zone) would be 5'ft wide.

All others would be zone 4.



Next Steps:

- Complete Window & Door Schedule included within this packet
- Submit all forms to your local building department according to their instructions.
- The local building department may require additional documentation

BROWARD COUNTY UNIFORM BUILDING PERMIT APPLICATION

Select One Trade: Building	☐ Electrical	□Pli	umbing		anical	Other_	
Application Number:					Applica	ation Date:	
Job Address:				Unit:	City:		
Tax Folio No.:	Flood Zn:	BFE:	FI	oor Area:		Job Value:	
Building Use:	· · · · · · · · · · · · · · · · · · ·	Col	nstructi	on Type:		Occupancy (Group:
1 Present Use:			posed				
Description of Work:							
New Addition Repair	Alteration	Dem	olition	Revision	Othe	er:	
Legal Description:							□Attachment
Property Owner:		P	hone:		Email:	***************************************	
Owner's Address:		•	none.	City:	Lilian.	State:	Zip:
				Oity.		Otato.	wib.
Contracting Co.:		P	hone:		Email:	<u></u>	
3 Company Address:				City:		State:	Zip:
Qualifier's Name:			Owne	er-Builder: 🗆	License	Number:	
Architect/Engineer's Name:		Pl	none:		Email:		
						Chatai	7:
Architect/Engineer's Address:				City:		State:	Zip:
Bonding Company: 4 Bonding Company Address:				City		State:	Zip:
Doriding Corripanty 7 Laureco.	ther then owner			City:		State.	Zip.
Fee Simple Titleholder's name (if of Fee Simple Titleholder's Address (City:	· · · · · · · · · · · · · · · · · · ·	State:	Zip:
Tee outspie Theriolder's Address (ii ouiei uieii owi	1161).		Oity.		Olulo.	p.
Mortgage Lender's Name:							
Mortgage Lender's Address:				City:		State:	Zip:
SIGNS, WELLS, POOLS, FURNACES OWNER'S AFFIDAVIT: I certify that a applicable laws regulating construction WARNING TO OWNER: YOUR PAYING TWICE FOR IMPROV RECORDED AND POSTED ON	all the foregoing in and zoning. FAILURE TO REEMENTS TO Y	nformation ECORD A OUR PRO	n is acco NOTIC OPERT	urate and that a E OF COMME Y. A NOTICE	all work w NCEMEN OF CO!	ill be done in NT MAY RES MMENCEMEI	ULT IN YOUR NT MUST BE
FINANCING, CONSULT WITH							
RECORDING YOUR NOTICE OF	COMMENCEM	ENT.					
X			¥				
	nature of Property Own	er or Agent	STATE	OF FLORIDA TY OF BROWAR			Signature of Qualifier
Sworn to (or affirmed) and subscribed before, 20	me this day	y of		to (or affirmed) ar			s day of
(Type / Pri	nt Property Owner or A	Agent Name)	(Type /	Print Qualifier's Nam	e)		
NOTARY'S SIGNATUR	_	•		Y'S SIGNATURE as			
Notary Name(Pr	int, Type or Stamp Not	tary's Name)	INULATY	Name (Print, T	ype or Stamp	Notary's Name)	
Personally Known or Produced	d Identification			Personally Know	n or	Produced identi	fication
APPROVED BY:	Permit Offic	er Issue	Date:			ode in Effect	•
A jurisdiction may use a supplement	ntal page reques	ting additi	ional in	formation and	citing oth	er conditions	, please inquire.
Note: If any development work as descrito the issuance of a building permit.	bed in FS 380.04	Sec. 2 a-g	is to be	performed, a d	evelopmei	nt permit must	be obtained prior 1.56

B	O	R	Α	P	ol	icy	٧.	2	0-	0:	L
---	---	---	---	---	----	-----	----	---	----	----	---

BROWARD COUNTY UNIFORM RETROFIT WINDOW & DOOR SCHEDULE

NAME:______ SITE ADDRESS:______ CONTACT #:_____

PAGE	OI	=
1770		

1	2		3	T	4	5		6		7		8		9)	10	
OPENING LOCATION ID	PRODUCT ACCEPTANCE NUMBER	APPR PRES	DUCT OVAL SURE TING	DES	JIRED SIGN SSURE	OPENING SIZES		ZONE LOCATION		Impact Glazing		OPENING HAS EXISTING SHUTTERS		NEW SHUTTERS REQUIRED		MULLION TUBES REQUIRED	
טו	NUIVIDEK	(+) PSF	(-) PSF	(+) PSF	(-) PSF	WIDTH X HEIGHT IN INCHES	AREA IN SQ FEET	4 INTER	5 END	YES	NO	YES	NO	YES	NO	YES	NO
						х	-										
						х											
						х											
						х											
	ı					х											
						х											
						х											
						х											
						х											
						х											
						х											

IDENTIFY OPENINGS ALPHABETICALLY OR NUMERICALLY ON ELEVATION SHEETS.

Broward County Fenestration Voluntary Wind Load Chart*


Per ASCE 7-16 Part 1 and FBC (2020) for Retrofitting in Accordance with Formal Interpretation #24

For Detached One-and Two family dwellings and Multiple Single-Family Dwellings (Townhouses) with Mean Roof Height ≤ 30 feet

Wind 170 mph (3-second gust) / Exposure C** / Kd = 0.85 / Kzt = 1.0 / Pressures are in PSF / Not for use in Coastal (Exposure 'D' areas)

* Using Allowable Stress Design methodology (P = 0.6w) / ** Exposure C or D shall be determined according to ASCE 7-16 Section 26.7 (Exposure Categories)

Roof and Wall Zone Chart Diagrams



Instructions on how to use these Charts: Determine Mean Roof Height, *h*, which is top of roof for flat roofs or the mean roof height for pitched roofs. Find your least horizontal dimension for your building, not including a overhang if it occurs. Calculate the value of, *a*, = 10% of least horizontal dimension or 0.4*h, whichever is smaller, but not less than either 4% of least horizontal dimension or 3 feet. If your roof height is less than 30 feet, but not exactly 15, 20, or 25 feet, you will need to go to the next higher roof height. If your Mean Foof Height is higher than 30 feet, these charts do not apply. Review the diagram which illustrate the wall and roof zones and determine the wind zone in which the component is located. Determine the tributary area of the component. If the tributary area falls in between values, use the value of the smaller tributary area. Select the positive and negative wind pressures corresponding to the wall or roof zone where your component is located. Door pressures shown are for the most common door sizes and are worst case for heights <= 30 Feet.

Wall Pressure For All Roof Types													Garage/Door Pressures					
Mean Roof Height	15 Ft							20 Ft						<= 30 Ft				
Tributary Area	10	20	35	50	100	500	10	20	35	50	100	500	Effective \	Wind Area	Positive	Negative		
Wall Positive Pressure	38.0	36.2	34.9	34.0	32.3	28.3	40.3	38.5	37.0	36.1	34.3	30.1	Width	Height	FUSILIVE	ivegative		
Zone 4 Negative Pressure	-41.2	-39.5	-38.1	-37.2	-35.5	-31.5	-43.7	-41.9	-40.5	-39.5	-37.7	-33.5	8	8	38.6	-48.2		
Zone 5 Negative Pressure	-50.8	-47.4	-44.6	-42.9	-39.5	-31.5	-54.0	-50.4	-47.4	-45.6	-41.9	-33.5	10	10	37.4	-45.7		
Mean Roof Height			25	Ft			30 Ft						14	14	35.4	-41.8		
Tributary Area	10	20	35	50	100	500	10	20	35	50	100	500	9	7	38.7	-48.3		
Wall Positive Pressure	42.3	40.4	38.8	37.8	35.9	31.5	43.9	41.9	40.3	39.3	37.3	32.8	16	7	37.0	-45.0		
Zone 4 Negative Pressure	-45.8	-43.9	-42.4	-41.4	-39.5	-35.1	-47.6	-45.7	-44.1	-43.1	-41.1	-36.5	3	7	41.8	-54.6		
Zone 5 Negative Pressure	-56.6	-52.8	-49.7	-47.8	-43.9	-35.1	-58.8	-54.7	-51.7	-49.6	-45.7	-36.5	6	7	39.8	-50.6		

SIMPLIFIED ROOF UPLIFT CHART FOR ROOFING APPLICATIONS

This simplified chart represents the worst case wind pressures for the various roof slopes and heights. This chart is based on a Tributary Area = 10 SF which is required for roofing applications. If the roof height is less than 30 feet, but not exactly 15, 20, or 25 feet, you will need to go to the next higher roof height. If your roof height is higher

	than 30 feet, these charts do not apply. Refer to Roof Chart Diagrams on Page 1 for Roof Zone Locations													
	Mean Roof Height = 15 Feet													
Flat Roof Gable Roof 1.51 to 4:12					Gable Ro	of 4.1 to 6:12	Gable Roof 6.	Hip	Roof 1.51	Hip Roof 4.1 to 6:12				
Positive*	15.4/38.0		Positive	23.2	Positive	23.2	Positive	34.7		Positive	28.3	Positive	28.3	
Zone		Zone	Roof	Overhang	Roof	Overhang	Roof	Overhang	Zone	Roof	Overhang	Roof	Overhang	
1	-60.5	1, 2e	-70.1	-80.4	-54.0	-64.3	-63.7	-83.6	1	-63.7	-74.0	-50.8	-60.8	
1'	-34.8	2n & 2r	-102	-113	-86.2	-96.5	-70.1	-90.1	2e	-89.4	-99.7	-70.1	-79.0	
2	-79.8	3e	-102	-132	-86.2	-116	-86.7	-107	2r	-83.0	-93.3	-70.1	-79.0	
3*	-109	3r	-122	-151	-102	-128	-70.1	-90.1	3	-89.4	-119	-70.1	-95.3	
Mean Roof Height = 20 Feet														
Flat I	Roof	Gable	Roof 1.51	to 4:12	Gable Ro	of 4.1 to 6:12	Gable Roof 6.	1: to 12:12	Hip	Roof 1.51	to 4:12	Hip Roof 4.1 to 6:12		
Positive*	16.4/40.3		Positive	24.6	Positive	24.6	Positive	36.9		Positive	30.1	Positive	30.1	
Zone		Zone	Roof	Overhang	Roof	Overhang	Roof	Overhang	Zone	Roof	Overhang	Roof	Overhang	
1	-64.2	1, 2e	-74.5	-85.4	-57.4	-68.3	-67.7	-88.9	1	-67.6	-78.6	-54.0	-64.6	
1'	-36.9	2n & 2r	-109	-120	-91.5	-102	-74.5	-95.7	2e	-95.0	-106	-74.5	-84.0	
2	-84.8	3e	-109	-140	-91.5	-123	-92.1	-113	2r	-88.1	-99.1	-74.5	-84.0	
3*	-116	3r	-129	-161	-108	-136	-74.5	-95.7	3	-95.0	-126	-74.5	-101	
					Mean	Roof Hei	ght = 25 Fe	et						
Flat I	Roof	Gable	e Roof 1.51	to 4:12	Gable Ro	of 4.1 to 6:12	Gable Roof 6.	Hip	Roof 1.51	Hip Roof 4.1 to 6:12				
Positive*	17.2/42.3		Positive	25.8	Positive	25.8	Positive	38.7		Positive	31.5	Positive	31.5	
Zone		Zone	Roof	Overhang	Roof	Overhang	Roof	Overhang	Zone	Roof	Overhang	Roof	Overhang	
1	-67.3	1, 2e	-78.1	-89.5	-60.2	-71.6	-70.9	-93.1	1	-70.9	-82.4	-58.6	-67.7	
1'	-38.7	2n & 2r	-114	-125	-96	-107	-78.1	-100	2e	-99.6	-111	-78.1	-88.0	
2	-88.8	3e	-114	-147	-96	-129	-96.6	-119	2r	-92.4	-104	-78.1	-88.0	
3*	-121	3r	-135	-168	-113	-143	-78.1	-100	3	-99.6	-133	-78.1	-106	
					Mean	Roof Hei	ght = 30 Fe	et						
Flat I	Roof	Gable	Roof 1.51	to 4:12	Gable Ro	of 4.1 to 6:12	Gable Roof 6.	1: to 12:12	Hip	Roof 1.51	to 4:12	Hip Roof	4.1 to 6:12	
Positive*	17.9/43.9		Positive	26.8	Positive	26.8	Positive	40.2		Positive	32.8	Positive	32.8	
Zone		Zone	Roof	Overhang	Roof	Overhang	Roof	Overhang	Zone	Roof	Overhang	Roof	Overhang	
1	-70.0	1, 2e	-81.1	-93.1	-62.6	-74.5	-73.7	-96.8	1	-73.7	-85.6	-58.8	-70.4	
1'	-40.2	2n & 2r	-118	-130	-99.8	-112	-81.1	-104	2e	-103	-115	-81.1	-91.4	
2	-92.3	3e	-118	-153	-99.8	-134	-100	-123	2r	-96.0	-108	-81.1	-91.4	
3*	-126	3r	-141	-175	-118	-148	-81.1	-104	3	-103	-138	-81.1	-110	

* If Parapet >= 3 Ft occurs around entire building use the same Zone 2 pressure for Zone 3 and use the higher positive pressure shown