

ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Storage: Not available Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international

regulations.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	>= 70 - < 90
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	>= 2.5 - < 10
bisphenol A - epoxy resins, number average MW >700 - <1100	25068-38-6	>= 1 - < 10



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of Bisphenol A and Epichlorhydrin

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: None known.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon oxides

Halogenated compounds

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and

contaminated fire extinguishing water must be disposed of in

accordance with local regulations.

Special protective equipment : Wear self-contained breathing apparatus for firefighting if



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

for firefighters necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

: 2 - 40 °C

Further information on

storage stability

: Stable under normal conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Filter type : Combined particulates and organic vapour type

Hand protection

Material : butyl-rubber

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : No data is available on the product itself.

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : ca. 6 (20 °C)

Concentration: 500 g/l

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

Boiling point : $> 200 \, ^{\circ}\text{C}$

Flash point : 210 °C

Method: Pensky-Martens closed cup, closed cup



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

260 °C

Method: Cleveland open cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : < 0.001 hPa (20 °C)

Relative vapour density : No data is available on the product itself.

Relative density : 1.14 - 1.19

Density : 1.15 g/cm3 (25 °C)

Solubility(ies)

Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Self-Accelerating

decomposition temperature

(SADT)

No data is available on the product itself.

Viscosity

Viscosity, dynamic : 30,000 - 50,000 mPa.s (25 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Particle size : No data is available on the product itself.

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

. Stable under normal conditions.

Possibility of hazardous : No hazards to be specially mentioned. reactions



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Conditions to avoid : None known.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents

None known.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of : No data is available on the product itself.

exposure

Acute toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Acute oral : LD50 (Rat, female): > 2,000 mg/kg
toxicityComponents Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral

toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Acute oral : LD50 (Rat, male and female): > 5,000 mg/kg

toxicityComponents Method: OECD Test Guideline 401

bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute oral : LD50 (Rat, female): > 2,000 mg/kg toxicityComponents Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity



ARALDITE® AW 106

Version Revision Date: SDS Number: Date of last issue: 28.02.2018 400001010251 1.1 22.08.2018 Date of first issue: 28.02.2018

bisphenol A - epoxy resins, number average MW >700 - <1100:

: LD50 (Rat, male and female): > 2,000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Acute toxicity (other routes of : No data available

administration)

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Mild skin irritant Method: OECD Test Guideline 404

Result: Irritating to skin.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Method: OECD Test Guideline 404

Result: Skin irritation

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Result: Irritating to eyes. Assessment: Mild eye irritant Method: OECD Test Guideline 405

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rabbit Result: Eye irritation

Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Exposure routes: Skin Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Result: Causes sensitisation.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Exposure routes: Skin Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Concentration: 0 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: Positive results were obtained in some in vitro tests.

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Cell type: Germ

Application Route: Oral



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Method: OECD Test Guideline 478

Result: negative

Cell type: Somatic Application Route: Oral Dose: 0 - 5000 mg/kg Method: OPPTS 870.5395

Result: negative

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Genotoxicity in vivo : Cell type: Somatic

Application Route: Oral Exposure time: 48 h Dose: 2000 mg/kg

Method: OECD Test Guideline 474

Result: negative

Cell type: Somatic Application Route: Oral Dose: 2000 mg/kg

Method: OECD Test Guideline 486

Result: negative

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vivo : Cell type: Germ

Application Route: Oral

Method: OECD Test Guideline 478

Result: negative

Cell type: Somatic Application Route: Oral Dose: 0 - 5000 mg/kg Method: OPPTS 870.5395

Result: negative

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

Application Route: Oral Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 days/week Method: OECD Test Guideline 453

Result: negative

Species: Mouse, male Application Route: Dermal Exposure time: 24 month(s)

Dose: 0.1 mg/kg

Frequency of Treatment: 3 days/week Method: OECD Test Guideline 453

Result: negative

Species: Rat, female



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Application Route: Dermal Exposure time: 24 month(s)

Dose: 1 mg/kg

Frequency of Treatment: 5 days/week Method: OECD Test Guideline 453

Result: negative

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female

Application Route: Oral Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 daily Method: OECD Test Guideline 453

Result: negative

Carcinogenicity - : No data available

Assessment

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: >750 milligram per kilogram

General Toxicity - Parent: No-observed-effect level: 540

mg/kg body weight

General Toxicity F1: No-observed-effect level: 540 mg/kg

body weight

Symptoms: No adverse effects Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female

Application Route: Oral

General Toxicity - Parent: No-observed-effect level: 750

mg/kg body weight

General Toxicity F1: No-observed-effect level: 750 mg/kg

body weight

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Components:



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal : Species: Rabbit, female development : Application Route: Dermal

General Toxicity Maternal: No observed adverse effect level:

30 mg/kg body weight Method: Other guidelines Result: No teratogenic effects

Species: Rabbit, female Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

60 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rat, female Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rabbit, female Application Route: Dermal

General Toxicity Maternal: No observed adverse effect level:

30 mg/kg body weight Result: No teratogenic effects

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rabbit, female Application Route: Dermal

General Toxicity Maternal: No observed adverse effect level:

30 mg/kg body weight Method: Other guidelines Result: No teratogenic effects

Species: Rabbit, female Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

60 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rat, female Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Reproductive toxicity -

Assessment

: No data available

STOT - single exposure

No data available



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion Exposure time: 14 Weeks Number of exposures: 7 d Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact Exposure time: 13 Weeks Number of exposures: 5 d Method: Subchronic toxicity

Species: Mouse, male NOAEL: 100 mg/kg

Application Route: Skin contact Exposure time: 13 Weeks Number of exposures: 3 d Method: Subchronic toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rat, male and female

NOAEL: 250 mg/kg

Application Route: Ingestion Exposure time: 13 Weeks Number of exposures: 7 d Method: Subchronic toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion Exposure time: 14 Weeks Number of exposures: 7 d Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact Exposure time: 13 Weeks Number of exposures: 5 d Method: Subchronic toxicity



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Repeated dose toxicity -

Assessment

: No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l

Exposure time: 96 h
Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 203

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Toxicity to fish : LC50 (Fish): 2.54 mg/l

Exposure time: 96 h Method: Calculation method

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 203

GLP: no

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2.7 mg/l

aquatic invertebrates Exposure time: 48 h

Test Type: static test
Test substance: Fresh water

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2.55 mg/l

aquatic invertebrates Exposure time: 48 h

Method: Calculation method

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

aquatic invertebrates Exposure time: 48 h

Test Type: static test
Test substance: Fresh water
Method: OFCD Test Cuidding 202

Method: OECD Test Guideline 202

GLP: yes

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l

Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: EPA-660/3-75-009

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 1.8 mg/l

Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to algae : EgC50 (Selenastrum capricornutum (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

GLP: no

Components:

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

M-Factor (Acute aquatic :

toxicity)

Toxicity to fish (Chronic : No data available

toxicity)



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.3 mg/l

aquatic invertebrates Exposure time: 21 d (Chronic toxicity) Test Type: semi-static test

Test substance: Fresh water Method: OECD Test Guideline 211

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.3 mg/l

aquatic invertebrates Exposure time: 21 d
(Chronic toxicity) Test Type: semi-static test

Test substance: Fresh water
Method: OECD Test Guideline 211

Remarks: Information given is based on data obtained from

similar substances.

M-Factor (Chronic aquatic

toxicity)

: No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane: Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h Test Type: static test

Test substance: Fresh water

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test

Test substance: Fresh water

Toxicity to soil dwelling

organisms

: No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial

organisms

: No data available

Ecotoxicology Assessment

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Biodegradability : Inoculum: Sewage (STP effluent)

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Biodegradability : Inoculum: activated sludge

Concentration: 3 mg/l Result: Not biodegradable Biodegradation: ca. 0 % Exposure time: 28 d

Method: Directive 67/548/EEC Annex V, C.4.E.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability : Test Type: aerobic

Inoculum: Sewage (STP effluent)

Concentration: 20 mg/l Result: Not biodegradable Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Biochemical Oxygen

Demand (BOD)

: No data available

Chemical Oxygen Demand

(COD)

: No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon

(DOC)

: No data available

Physico-chemical

removability

: No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Stability in water : Degradation half life(DT50): 4.83 d (25 °C) pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life(DT50): 7.1 d (25 °C) pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

Degradation half life(DT50): 3.58 d (25 °C) pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

bisphenol A - epoxy resins, number average MW >700 - <1100:

Stability in water : Degradation half life(DT50): 4.83 d (25 °C) pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life(DT50): 7.1 d (25 °C) pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life(DT50): 3.58 d (25 °C) pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage

Treatment

: No data available

Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Bioaccumulation
: Bioconcentration factor (BCF): 31

Remarks: Does not bioaccumulate.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 150 Remarks: Does not bioaccumulate.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 31 Remarks: Does not bioaccumulate.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Partition coefficient: n- : log Pow: 3.242 (25 °C)

octanol/water pH: 7.1

Method: OECD Test Guideline 117

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Partition coefficient: n- : log Pow: 2.7 - 3.6

octanol/water Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Components:



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among : Koc: 445

environmental compartments

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Distribution among : Koc: 4460

environmental compartments Method: OECD Test Guideline 121

bisphenol A - epoxy resins, number average MW >700 - <1100:

Distribution among : Koc: 445

environmental compartments

Stability in soil : No data available

Other adverse effects

Environmental fate and

pathways

: No data available

Results of PBT and vPvB

assessment

: No data available

Endocrine disrupting

potential

: No data available

Adsorbed organic bound

halogens (AOX)

: No data available

Hazardous to the ozone layer

Ozone-Depletion Potential Not applicable

Additional ecological

information - Product

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Global warming potential

(GWP)

: No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of contents/ container to an approved waste disposal

plant.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.



ARALDITE® AW 106

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.02.2018

 1.1
 22.08.2018
 400001010251
 Date of first issue: 28.02.2018

14. TRANSPORT INFORMATION

International Regulations

IATA

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

964

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction : 964

(passenger aircraft)

Environmentally hazardous : yes

IMDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

: Not applicable

RESIN)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and

Environmental Protection and Management

(Hazardous Substances) Regulations

The components of this product are reported in the following inventories:



۸D	ΛΙ	בוח	FR	. A \	N/ •	106
AK	ΔΙ		I I -(R)	Δν	V 1	lun

Version	Revision Date:	SDS Number:	Date of last issue: 28.02.2018
1.1	22.08.2018	400001010251	Date of first issue: 28.02.2018

CH INV : The formulation contains substances listed on the Swiss

Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

16. OTHER INFORMATION

Date format : dd.mm.yyyy

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.



ARALDITE® AW 106

Version Revision Date: SDS Number: Date of last issue: 28.02.2018
1.1 22.08.2018 400001010251 Date of first issue: 28.02.2018

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.