# **Fact sheet**

# **Approved Basic Trade Waste Pre-treatment Products**

#### Reviewed 05/02/2016

This list shows the basic pre-treatment devices approved by SA Water for connection to its sewerage system. Dischargers may choose from the various suppliers, but must install an approved device of the type and size, if that is specified on their trade waste discharge permit.

Equipment installations must allow adequate clearance for safe access during routine servicing and inspection. For example, the clearance above a grease arrestor or settling pit should be at least 1200mm.

Stands, walkways and steps associated with the device must meet Workplace Health and Safety guidelines.

Trade Waste Guideline *Approval of Basic Pre-treatment Products* sets out the process for adding new products to this list. If we have previously approved your product, but it is not listed, or the information is incorrect, please contact the SA Water Trade Waste Branch.

#### **Grease Arrestors**

Manufacturer/Product		
Name	<b>Supplier Contact</b>	Item/Model No.
Bianco Precast	(08) 8444 7555	Concrete. No.2 (1000 L/hr), No.3 (1750L/hr), No. 4(2400L/hr), No. 5 (5390L/hr)
Cooke Precast Concrete	(08) 8209 3093	Concrete. No.2 (1000 L/hr), No.3 (1750L/hr), No. 4(2400L/hr), No. 5 (5000L/hr)
		Passive Grease Arrestors (1000L, 1800L and 2400L) modified models (SA specific i.e. Changes to baffle's holes).
CV Plastics P/L	(03) 5442 8728	Above ground installations must be installed under cover. Not UV protected.
Eclipse Boat Shaped Grease Arrestor	Eclipse Environmental Australia 1300 272 650	Fibreglass. Models Eclipse GA1000F, GA1500F, GA1800F, GA2000F, GA2400F, GA3000F, GA4000F, GA5000F (Modified models as per Product's South Australia Manual dated June 2011)
Halgan MGT Modular Grease Trap	Halgan 1800 626 753 info@halgan.com.au	Polyethylene. Models MGT 1000, MGT 1000.2, MGT 1500, MGT 1500.2, MGT1500.3, MGT2000, MGT 2000.2, MGT 3000, MGT 3000.2, MGT 4000, MGT 4000.2, MGT 5000, MGT 5000.2



Halgan MGTA Modular Grease Trap A	Halgan 1800 626 753 info@halgan.com.au	Polyethylene. Models MGTA 1000, MGTA 1500, MGTA 2000, MGTA 3000, MGTA 4000, MGTA 5000. Above ground installations only.
Halgan MGT S Modular Grease Trap "S" Series	Halgan 1800 626 753 info@halgan.com.au	Polyethylene. Models MGTS 1000, MGTS 1500, MGTS 2000, MGTS 3000, MGTS 4000, MGT S 5000
Ri Industries	(08) 8445 7822	Concrete. No.2 (1000 L/hr), No.3 (1800L/hr), No. 4(2400L/hr), No. 5 (5000L/hr)
Stratco	(08)8349 5555	Stainless steel. GRAR1000SS (1000L/hr), GRAR1000SS (1800L/hr), GRARVBSS V-base in custom sizes minimum 1000L/hr.

# Filter Type Grease Removal Devices

Manufacturer/Product		
Name	<b>Supplier Contact</b>	Item/Model No.
		Delta 1 (1000L/hr) Delta 2 (1500L/hr)
	Eclipse	Only authorised when clear space restrictions can
	Environmental	be demonstrated and upon suitability assessment
Delta compact	1300 272 650	of the nature of the waste.
		Polyethylene/thermal plastics - 1000 L/hr
		Only authorised when clear space restrictions can
	Global Pumps	be demonstrated and upon suitability assessment
Grease Muncher	(08) 8275 8000	of the nature of the waste.
		Polyethylene - 1000 L/hr
	Halgan	Only authorised when clear space restrictions can
Halgan Ecotec S100 Grease	1800 626 753	be demonstrated and upon suitability assessment
Extractor	info@halgan.com.au	of the nature of the waste.

### **Grease Removal Devices**

Manufacturer/Product		
Name	Supplier Contact	Item/Model No.
		Models: W-150-IS, W-200-IS, W-250-IS, W-350-IS
		and W-500-IS.
	M.A.Griffith	Only for use upstream of an appropriate
Big Dipper Extractor	(03) 9399 8444	authorised grease arrestor, DAF unit etc.
		Stainless Steel - Models: D1, D2, D3, D4, D5
	<b>Eco Guardians</b>	Only for use upstream of an appropriate
Grease Guardian	1300 556 628	authorised grease arrestor, DAF unit etc.

# **Cooling Pits**

Manufacturer/Product		
Name	Supplier Contact	Item/Model No.
		Models HCP200, HCP400, HCP600, HCP800,
	Halgan	HCP1000, HCP1200, HAD1500 (polyethylene)
	1800 626 753	Only for use in minor applications / ad hock
Halgan Cooling Pit	info@halgan.com.au	discharges.
		Models HCPS1000, HCPS1500, HCPS2000,
Halg	Halgan	HCPS3000 (polyethylene)
	1800 626 753	Only for use in minor applications / ad hock
Halgan Cooling Pit S Series	info@halgan.com.au	discharges.





# Neutralising Tanks - Under Sink

Manufacturer/Product		
Name	Supplier Contact	Item/Model No.
Storm Plastics	(08) 8374 3277	PVC Neutraliser Tank NT50
Stratco	(08)8349 5555	Stainless steel. LNTKSS

#### Oil Water Separators

Manufacturer/Product		
Name	Supplier Contact	Item/Model No.
Baldwin Industrial Systems P/L	Baldwin (02) 4954 0440 Hydramet (SA) (08) 8374 7800	Coalescing Plate Separator - Polyethylene/polypropylene. Various models from 1000 L/hr upwards
MAK Industrial Water Solutions	(08) 8395 6122	Coalescing Plate Separator - Stainless steel. Various models from 720 L/hr upwards
Eclipse Hydroflow Oil Separators	Eclipse Environmental Australia 1300 272 650	Stainless steel. Models HYD1000S (1000L/hr), HYD3000S (3000L/hr), HYD5000S (5000L/hr)
EnviroSEP	Ovivo Australia (08) 8260 8111	Stainless steel. Various models from 1000L/hr upwards
Fox Environmental Systems	Fox Environmental Systems (03) 9338 6024	Mechanical Oil/ Water Separator models: FX 1000 (SS & SSD), FX 1500 (SS & SSD), FX 3000 (SS & SSD), FX 6000 (SS & SSD)
H2O Cleanawater, TS Series Oil Water Separators	1800 353 788	Stainless steel. Various models from 1000L/hr upwards
Hydro-Tec Engineering	(08) 8390 1565	Stainless steel. Various models from 1000L/hr upwards
Industrial Separation Systems (ISS), Vertical Gravity Separator (VGS)	Environmental Water Services (08) 8398 40 44. MRE Industries (08) 8352 6233. Ri Industries (08) 8445 7822. Tradelink 1800 228 476. Reece Plumbing Products - all stores.	Polyethylene or stainless steel. Various models 1000 - 3000 L/hr
Kwikflo Oil Water Separator	Global Pumps (08) 8275 8000. MRE Industries (08) 8352 6233	Polyethylene Various models from 1000 L/HR upwards





# Painting Tool Wash Water Treatment (water-based paints)

Manufacturer/Product		
Name	Supplier Contact	Item/Model No.
	Dulux Trade	
	Outlets	
EnviroWash system	132525	ES 160 and ES 450

## Plaster Traps – Under Sink

Manufacturer/Product		
Name	Supplier Contact	Item/Model No.
L W Gemmell Aust.	(08) 8340 9999	Stainless steel. PLAS - 316
Halgan Clay Plaster Trap	Halgan 1800 626 753 info@halgan.com.au	Model CPT/SS/5, manufactured from 304 grade stainless steel
Halgan Plaster Trap	Halgan 1800 626 753 info@halgan.com.au	Model PT/SS/5, manufactured from 316 grade stainless steel
Storm Plastics	(08) 8374 3277	PVC Plaster Traps PLTRAPBO and PLTRAPSO Models with PVC Plaster Trap Lid PLTRAP-Lid
Stratco	(08)8349 5555	Stainless steel PSTTSS

### Silt Traps/Strainers with Basket – In Floor, Sink or Trough

Note: As of 1<sup>st</sup> January 2014, the screening requirements includes the introduction of a fixed secondary strainer with a max 2mm hole size.

Manufacturer/Product		
Name	<b>Supplier Contact</b>	Item/Model No.
		ACO Wexel Floor Drain (141876, 141877, 141878,
		141879, 141880, 141881, 141882) fitted with
		removable strainer (142335, 142336) and fixed
		strainer 142334.
		ACO Gully 157 Floor Drain (142039, 142040,
		142041, 142042, 141976, 141977, 141978,
		141979, 141988, 141989, 141990, 141991,
		141980, 141981, 141982, 141983, 141984,
		141985, 141986, 141987) fitted with removable
		strainer (142326, 142327, 142328, 142329) and
ACO Polycrete Pty Ltd	(08) 8162 7800	fixed strainer 142337.
		ACO Gully 218 Floor Drain (142043, 142044,
		142045, 142046, 142047, 142048, 142049,
		142050, 141992, 141993, 141994, 141995,
		141996, 141997, 141998, 141999) fitted with
		removable strainer (142330, 142331, 142332,
		142333) and fixed strainer (142337, 142338.)
		Both a primary removable and secondary fixed
		strainer must be fitted to all above products with
		a maximum hole size of 2mm diameter.





Blucher Australia	(08) 8374 3426	316 Stainless Steel, 200mm Industrial Drains (760.402.110s, 766.402.110s, 760.502.110s, 766.502.110s or 760.602.110s) fitted with both a Filter Basket 2mm hole size (780.200.000.02s) and 2mm hole size Screw Fixed Secondary Strainer (788.110.000.02s).  316 Stainless Steel, 300mm Industrial Drains (760.403.110s, 760.403.160s, 766.403.110s, 760.503.110s, 760.503.160s, 766.503.110s or 760.603.110s) fitted with both a Filter Basket 2mm hole size (780.300.000.02s) and 2mm hole size Screw Fixed Secondary Strainer (788.110.000.02s or 788.160.000.02s).  Both a primary removable and secondary fixed strainer must be fitted to all above products with a maximum hole size of 2mm diameter.
SMC Stainless	(02) 4735 5666	Models ALDI-AT2HST-SA Solids Trap, ALDI-AT7-SA Solids Trap, AT6-YUM-SA Solids Trap All above products are only approved as the South Australia specific model fitted with a fixed tertiary strainer with maximum hole diameter of 2mm.
Storm Plastics	(08) 8374 3277	PVC Silt Trap 225 x 150mm. S225150 PVC Silt Trap 225 x 100mm. S225100 PVC Silt Trap 150 x 100mm. S150100 HDPE Silt Trap 160 x 110mm. S160110HDPE HDPE Silt Trap 250 x 110mm. S250110HDPE Both a primary removable and secondary fixed strainer must be fitted to all above products with a maximum hole size of 2mm diameter.
Stratco	(08)8349 5555	Stainless steel. Round Top Silt Trap. STRPROSS Stainless steel. SquareTop Silt Trap. STRPSQSS Both a primary removable and secondary fixed strainer must be fitted to all above products with a maximum hole size of 2mm diameter.

# Solids Settling/Neutralising Pits

Manufacturer/Product		
Name	Supplier Contact	Item/Model No.
Bianco Precast	(08) 8359 0666	Concrete. No.2 (1000 L/hr), No.3 (1750L/hr), No. 4(2400L/hr), No. 5 (5390L/hr)
	,	Concrete. No.2 (1000 L/hr), No.3 (1750L/hr), No. 4(2400L/hr), No. 5 (5000Lhr)
Cooke Precast Concrete	(08) 8209 3093	
Halgan Averaging Dilution Trap	Halgan 1800 626 753 info@halgan.com.au	Models HAD400, HAD600, HAD800. HAD1000, HAD1200 and HAD1500 (chemical grade polyethylene)
Halgan Averaging Dilution Trap S Series	Halgan 1800 626 753 info@halgan.com.au	Models HADS1000, HADS1500, HADS2000 and HADS3000 (chemical grade polyethylene)
Halgan Lint Trap	Halgan 1800 626 753 info@halgan.com.au	Models HLT600, HLT1100 and HLT1600 (chemical grade polyethylene)  Only for use in conjunction with a compliant





		upstream screening device.
		Models HLTS1000, HLTS1500, HLTS2000 and
	Halgan	HLTS3000 (chemical grade polyethylene)
	1800 626 753	Only for use in conjunction with a compliant
Halgan Lint Trap S Series	info@halgan.com.au	upstream screening device.
Halgan Settling Tank	Halgan 1800 626 753 info@halgan.com.au	Models HSTV1100 and HSTV1600 (chemical grade polyethylene)
	Halgan	
	1800 626 753	Silt Arrestor, Models HST550, HST1000 and
Halgan Silt Trap	info@halgan.com.au	HST1500 (chemical grade polyethylene)
	Halgan	Silt Arrestor, Models HSTS1000, HSTS1500,
	1800 626 753	HSTS2000 and HSTS3000 (chemical grade
Halgan Silt Trap S Series	info@halgan.com.au	polyethylene)
Ri Industries Developments		Concrete. No.2 (1000 L/hr), No.3 (1800L/hr), No.
P/L	(08) 8445 7822	4(2400L/hr), No. 5 (5000L/hr)

#### Note:

- The above devices have been approved in principle by SA Water's Trade Waste Branch only. Performance/ compliance of the device is the responsibility of the trade waste discharger (authorisation holder.)
- Wind driven turbine ventilators ('whirly bird' type vents) are required on all upstream
  trade waste vents. An induct vent of not less than DN80 has to be connected to the outlet
  chamber of the grease arrestor. A DN80 or larger high-level upstream vent (fitted with a
  wind driven turbine ventilator) has to be connected to the uppermost end of the drainage
  system gravitating to the arrestor.

The minimum venting size for all trade waste drains and pre-treatment devices is a DN80 or larger, however branch vent size is fixture unit dependent.

Approved Manufacturer: Edmonds Product Name: Sewer Vent Contact: 1300 858 674

Figure 1 illustrates the approved wind turbine ventilator required for grease arrestors.



Figure 1. Wind turbine ventilator (Sewer vent)



