


Data Center Storage Solutions

Powering the Data Revolution



For more than 50 years, Western Digital[®] has been enabling data at scale. Our data center SSDs, HDDs and platforms enable our customers to gain and leverage insights that they can extract from the zettabytes of data being generated by smart factories, connected endpoints, autonomous vehicles, IoT devices and more. Our robust portfolio and our outstanding customer service help companies and individuals transform their businesses with data.

Essential Data Infrastructure for the Zettabyte Age



Ultrastar[®] Data Center SSDs

- Portfolio breadth and depth for cloud computing to high-performance servers
- Industry-leading NAND
- Vertically integrated controllers and firmware



Ultrastar Data Center HDDs

- 1st with OptiNAND[™]-enabled 22TB CMR HDDs
- 1st with Energy-Assisted Magnetic Recording technology
- 1st with Triple Stage Actuator
- 1st with helium-filled HDDs



Ultrastar and OpenFlex[™] Platforms

- High-capacity disk storage platforms
- High-performance flash storage platforms
- Innovative ArcticFlow[™] & IsoVibe[™] technologies
- Open Composable Infrastructure Solutions

Trusted Storage Delivering Innovation Across All Technologies



NVMe™ SSDs

Low-latency, high-performance NVMe SSDs to accelerate your data center workloads



Helium-filled HDDs

Highest capacity HDDs for data center expansion and cost-efficient scale



Air-filled HDDs

Economical and reliable data access for traditional data center application




Platforms

Complete portfolio of storage platforms and servers for SATA, SAS, NVMe and NVMe-oF™





Optimize Your Data Center with Ultrastar SSDs

	Performance NVMe	Mainstream NVMe
	Ultrastar DC SN840	Ultrastar DC SN640
Compute Intensive/HPC	✓	
All Flash Array Primary Storage	✓	
Relational Databases	✓	
Artificial Intelligence/Machine Learning	✓	
Converged/Hyperconverged Infrastructure	✓	✓
OLTP	✓	✓
OLAP	✓	✓
Virtualization	✓	✓
noSQL Databases	✓	✓
Content Caching	✓	✓
File/Object Storage	✓	✓
Cloud Compute/Cloud Storage		✓







Ultrastar Data Center NVMe SSDs

	Performance NVMe	Mainstream NVMe
	 <p>Ultrastar DC SN840</p>	 <p>Ultrastar DC SN640</p>
Interface	PCIe 3.1 1x4, 2x2, NVMe 1.3c	PCIe 3.1 1x4, NVMe 1.3c
Form Factor	U.2. 15mm	U.2. 7mm
Endurance/Capacity (GB) ^{1,2}	3 DW/D: 1600, 3200, 6400 1 DW/D: 1920, 3840, 7680, 15360	2 DW/D: 800, 1600, 3200, 6400 0.8 DW/D: 960, 1920, 3840, 7680
NAND	3D TLC	
Seq R/W (MB/s), up to ³	3,470/3,300	3,340/2,190*
Random R/W (KIOPS), up to	780/257	515/161*
Reliability ⁴	Unrecoverable Bit Error Rate (UBER): 1 in 10 ¹⁷ MTBF (M hours): 2.5 AFR: 0.35%	Unrecoverable Bit Error Rate (UBER): 1 in 10 ¹⁷ MTBF (M hours): 2 AFR: 0.44%
Security	SE, ISE, TCG Ruby	SE, ISE, TCG Ruby





* TCG Ruby Performance Values





	CMR with HelioSeal®				
					
	Ultrastar DC HC570	Ultrastar DC HC560	Ultrastar DC HC550	Ultrastar DC HC530	Ultrastar DC HC520
					
Interface	SATA 6Gb/s, SAS 12Gb/s				
Rotational speed (RPM)	7200				
Form Factor	3.5-inch data center HDD				
Capacity (TB)	22	20	18, 16	14	12
Format	512e				
Sustained transfer rate (MB/s, max) ⁵	291	269	269 (18TB) 262 (16TB)	267	243
Idle_A (W), SATA/SAS ⁶	5.7/6.0	6.0/6.1	5.6/5.8	5.5/5.9	5.0/6.1
ArmorCache™	Yes				
Reliability ⁷	MTBF (M hours): 2.5, projected AFR: 0.35%, projected Workloads: up to 550TB/year			MTBF (M hours): 2.5 AFR: 0.35% Workloads: up to 550TB/year	
Security	Base (SE), SED			Base (SE), SED, SED-FIPS	





Ultrastar Data Center HDDs

	CMR, Air-filled			
				
	Ultrastar DC HC330	Ultrastar DC HC320	Ultrastar DC HC310	Ultrastar DC HA210
Interface	SATA 6Gb/s, SAS 12Gb/s			SATA 6Gb/s
Rotational speed (RPM)	7200			
Form Factor	3.5-inch data center HDD			
Capacity (TB)	10	8	6, 4	2, 1
Format	512e 512n available on 4TB capacity			512n
Sustained transfer rate (MB/s, max)	262	255	255 233 w/512n	200 (2TB) 184 (1TB)
Idle (W), SATA/SAS	8.0/9.0	7.4/8.4	5.9/7.0	5.9/NA
Reliability	MTBF (M hours): 2 AFR: 0.44% Workloads: up to 550TB/year			
Security	Base (SE), SED, SED-FIPS			SE

Ultrastar Data Center Platforms

	JBOD	
	 Ultrastar Data60	 Ultrastar Data102
Storage Type	HDD	
Interface	SATA/SAS	
# Drives (up to)	60	102
Capacity (up to)	1.3PB	2.2PB
Dimension	4U	
Features	IsoVibe ArcticFlow	

OpenFlex Data Center Platforms

	JBOD	
	  OpenFlex Data24 (Standard)	 OpenFlex Data24
Storage Type	SSD	SSD
Interface	NVMe (NVMe-oF) 2* RapidFlex NICs	NVMe (NVMe-oF) 6* RapidFlex NICs
# Drives (up to)	24	24
Capacity (up to)	368TB	368TB
Dimension	2U	2U
Features	Low Latency Ideal SAS replacement	Low Latency High Performance

¹ One gigabyte (GB) is equal to 1,000MB (one billion bytes) and one terabyte (TB) is equal to 1,000GB (one trillion bytes) when referring to solid-state capacity. Accessible capacity will vary from the stated capacity due to operating environment.² Endurance rating based on DW/D using 4KiB random write workload over 5 years.

³ Endurance rating based on DW/D using 4KiB 100% random write and JESD 219 workloads over 5 years.

⁴ Based on internal testing. Performance will vary by capacity point, changes in useable capacity, or security option. Consult product manual for further details. All performance measurements are in full sustained mode and are peak values. Subject to change.

⁵ MTBF and AFR specifications are based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions for this drive model. MTBF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

⁶ Idle specification is based on use of Idle_A

⁷ Based on internal testing; performance may vary depending on host environment, drive capacity, logical block address (LBA), and other factors. 1MiB = 1,048,576 bytes (2²⁰), 1MB = 1,000,000 bytes (10⁶)

⁸ Final MTBF and AFR specifications will be based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions, typical workload and 40°C device-reported temperature. Derating of MTBF and AFR will occur above these parameters, up to 550TB/year and 60°C (device reported temperature). MTBF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.



©2022 Western Digital Corporation or its affiliates. All rights reserved. Produced 7/20, Rev. 01/22. Western Digital, the Western Digital logo, ArticFlow, HelloSeal, IsoVibe, OpenFlex, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. The NVMe and NVMe-oF word marks are trademarks of NVM Express, Inc. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications that are subject to change and do not constitute a warranty. Pictures shown may vary from actual products. All other marks are the property of their respective owners.

5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.westerndigital.com/support