



Biotech

USD 3300

## Cadence™ Inline Concentrator with Delta Regenerated Cellulose and Omega™ Polyethersulfone Membranes



### *Single-Pass Tangential Flow Filtration Made Simpler*

Single-pass tangential flow filtration (SPTFF) is revolutionizing how tangential flow filtration (TFF) is implemented in biotech, vaccine, blood plasma and other applications. Pall has now made it even easier to implement this breakthrough patented technology into your process. As with the original Cadence SPTFF modules, the Cadence Inline Concentrator (ILC) allows direct flow through in-process volume reduction and can be implemented into a process system or operated as a stand alone unit.

This exciting new technology leads to economic and practical benefits, including:

- ▶ Ability to couple the concentration of product before or after other downstream processing (DSP) steps, consequently optimizing other steps and reducing in-process pool tank volumes
- ▶ Continuous processing in DSP
- ▶ Easy integration of the assembled module, allowing plug-and-play
- ▶ Potential reduction of product damage or aggregation due to reduced residence time and shear exposure

*Filtration. Separation. Solution.<sup>SM</sup>*

The preassembled Cadence ILC modules do not need a holder. Once the feed port is connected to a pressurized feed source, the module is ready for use. The built-in resistor in the retentate manifold eliminates the need for downstream instrumentation and allows volume reduction of 2 to 4X (or higher), depending on the application.

Similar to other Cadence SPTFF devices, the Cadence ILC utilizes standard Pall T-Series cassettes as the building blocks for the module. These modules are offered with either Delta regenerated cellulose or Omega polyethersulfone (PES) 10 kDa or 30 kDa membranes providing the high flux, high selectivity and low protein binding characteristics associated with these membranes. They are available in a range of size formats to accommodate various processing volumes.

These products utilize proprietary technology, as well as technology licensed from SPF Innovations, and may be covered by one or more patents. See [pall.com/patents](http://pall.com/patents).

### ***Optimize Economic and Operational Benefits***

#### **Enhance downstream processing to increase capacity and reduce costs**

Cadence ILC modules can help to eliminate or reduce the size of intermediate storage tanks and associated cleaning of tanks when used for in-process volume reduction before or after existing steps.

#### **Enable in-process volume reduction**

Depending on the initial concentration and product characteristics, a volume reduction of 2 to 4X (or higher) can be achieved with minimal instrumentation or system requirements.

#### **Optimize processing of highly shear-sensitive products**

Processing with the Cadence ILC results in only one pass through the pump and module, reducing shear exposure. For products sensitive to pumping, the pump can be completely eliminated by using pressurized vessels to flow the process fluid through the module. Further benefits are achieved by eliminating any mixing or foaming issues associated with the feed tank.

#### **No holder required**

Cadence ILC modules are provided assembled, and the cassettes and manifolds are pre-torqued between two end plates so that no extra holder is required.

Benefits include:

- ▶ Easy connection to a pressure source, like a pump or pressure vessel
- ▶ Simplified in-process volume reduction
- ▶ Continuous processing enabled by process coupling
- ▶ The module feed, retentate and permeate ports are easily connected to the appropriate outlets using clearly marked ports

### ***Product Platform***

Innovative SPTFF processing takes place within the Cadence ILC modules. The modules incorporate Pall's proven T-series cassettes with Delta or Omega membrane, and are available in different formats to accommodate various processing volumes (see ordering information).

### ***Applications***

The Cadence ILC is designed for continuous processing or for in-process volume reduction in various steps in a wide range of applications in the biopharmaceutical industry. These include recovery of antibodies or recombinant proteins, and preparation of samples (concentrating, desalting) before or after column chromatography, and can be implemented in existing facilities facing tank capacity issues or to other process optimization opportunities.

## Specifications

The operating conditions for any SPTFF process must be established by performing trials and analyzing results. Pall's technical service group is available to assist in conducting trials to develop operating conditions necessary to achieve the desired process objectives.

### Materials of Construction

Cassette	Delta regenerated cellulose or Omega PES membrane, 10 kDa or 30 kDa with polypropylene screens, polyurethane encapsulant with white pigment (TiO <sub>2</sub> ), and medical grade silicone for the permeate seals
Gaskets	Medical grade, platinum-cured silicone
Manifold plates	Ultra high molecular weight polyethylene (UHMWPE)
Tubing and connectors	<ul style="list-style-type: none"><li>• Tubing: pharmaceutical grade platinum-cured silicone</li><li>• T01/T02 - female Luer connection and cap: polypropylene (PP)</li><li>• T12 - MPC quick disconnect connector and plug: polysulfone (PS)</li><li>• T06 - MPX quick disconnect connector and plug: polysulfone</li></ul>

### Operating Limits

Maximum pressure	4.1 barg (60 psig)
Maximum transmembrane pressure (TMP)	4.1 barg (60 psig)
Processing temperature range	<ul style="list-style-type: none"><li>• 20 – 25 °C for extended use (freezing will damage module)</li><li>• Up to 40 °C for 4 hour cleaning</li></ul>
pH range	2 – 13

### Typical Feed Flow Rates

Cadence ILC Module Format	Membrane Area (m <sup>2</sup> )	Q <sub>FEED</sub> (L/min)
T01	0.065	0.05 – 0.3
T02	0.13	0.1 – 0.7
T12	0.7	0.6 – 3.5
T06	3.5	2.9 – 17.5

### Integrity Test

Delta membrane module	< 538 sccm/m <sup>2</sup> (<50 sccm/ft <sup>2</sup> ) at 4.1 barg (60 psig)
Omega membrane module	<1600 sccm/m <sup>2</sup> (<150 sccm/ft <sup>2</sup> ) at 2.1 barg (30 psig)

Each Cadence ILC module has a unique serial number for full traceability.

## Shelf Life

The shelf life of Cadence inline concentrator packaged in preservative is 1 year from the date of manufacture when the modules are stored unopened in the original packaging at temperature up to 25 °C and protected from direct light. Extended shelf life studies are ongoing. Please contact Pall for updated information.

## Biological Safety

The materials of construction for Cadence ILC modules have been tested and meet the requirements for the Biological Reactivity Tests listed in the United States Pharmacopeia (USP) under USP <88> for Class VI - 70 °C Plastics.

## Documentation

Each module is supplied with the following comprehensive documentation to ensure the Cadence ILC module is operated successfully. Visit [www.pall.com/biotech](http://www.pall.com/biotech) or contact your local Pall representative to obtain these documents.

- ▶ Certificate of quality
- ▶ Material and safety data sheet (MSDS) for the module preservative solution
- ▶ Care and use manual
- ▶ Validation guide
- ▶ Application notes

Additional services include:


- ▶ Validation service for your specific tests such as compatibility testing with your product fluid
- ▶ Training and technical support to optimize your process using Cadence ILC modules

Please contact Pall for further information.

## Performance

**Figure 1**

*Feed flux excursion test results: volume concentration factor (VCF), feed pressure as function of feed flux, 10 g/L human IgG feed solution, T01 (0.065 m<sup>2</sup>) Cadence ILC module*



*The range of operating VCF can be determined for a specific feed solution by doing a feed flux excursion.*

## Ordering Information

Identify and order Cadence inline concentrator modules using the table below.

### Guide to Cadence Inline Concentrator Module Part Numbers

IL	Inline concentrator
D or OS	Cassette with Delta regenerated cellulose membrane or Omega PES membrane
010 or 030	Nominal molecular weight cut-off (MWCO) in kDa
T01, T02, T12 or T06	Cassette format
04	Number in series
07	Number of cassettes

For example, a T01 module with 0.065 m<sup>2</sup> (0.7 ft<sup>2</sup>) of 10 kDa Delta regenerated cellulose membrane area is part number ILD010T010407.

### Cadence Inline Concentrator Part Numbers

Delta Membrane	Omega Membrane	Cassette Format	Membrane Area (m <sup>2</sup> )	MWCO (kDa)
ILD010T010407	ILOS010T010407	T01	0.065	10
ILD010T020407	ILOS010T020407	T02	0.13	
ILD010T120407	ILOS010T120407	T12	0.7	
ILD010T060407	ILOS010T060407	T06	3.5	
ILD030T010407	ILOS030T010407	T01	0.065	30
ILD030T020407	ILOS030T020407	T02	0.13	
ILD030T120407	ILOS030T120407	T12	0.7	
ILD030T060407	ILOS030T060407	T06	3.5	



**Corporate Headquarters**  
Port Washington, NY, USA  
+1 800 717 7255 toll free (USA)  
+1 516 484 5400 phone

**European Headquarters**  
Fribourg, Switzerland  
+41 (0)26 350 53 00 phone

**Asia-Pacific Headquarters**  
Singapore  
+65 6389 6500 phone


Visit us on the Web at [www.pall.com/biotech](http://www.pall.com/biotech)

Contact us at [www.pall.com/contact](http://www.pall.com/contact)

#### International Offices

Pall Corporation has offices and plants throughout the world in: Argentina, Australia, Austria, Belgium, Brazil, Canada, China, France, Germany, India, Indonesia, Ireland, Italy, Japan, Korea, Malaysia, New Zealand, Norway, Philippines, Poland, Russia, Singapore, South Africa, Spain, Sweden, Switzerland, Taiwan, Thailand, United Kingdom, and Vietnam. Distributors in all major industrial areas of the world. To locate the Pall office or distributor nearest you, visit [www.pall.com/contact](http://www.pall.com/contact).

The information provided in this literature was reviewed for accuracy at the time of publication. Product data may be subject to change without notice. For current information consult your local Pall distributor or contact Pall directly.

© 2018, Pall Corporation. Pall, , Cadence and Omega are trademarks of Pall Corporation. **Filtration.Separation.Solution** is a service mark of Pall Corporation. ® indicates a trademark registered in the USA and ™ indicates a common law trademark.