

CARBON STEEL BARS


Hot Rolled

Rounds	
Low Carbon.....	40
Medium Rounds.....	40
Strip	
Low Carbon.....	41
Squares	
Low Carbon (A36, 1045).....	41
Flats	
Low Carbon.....	42
Reinforcing Bars.....	43

Cold Finished


Rounds	
Low Carbon.....	44
Medium Carbon.....	44
Screw Stock.....	45
Shafting.....	45
Squares	
Screw Stock.....	45
Flats	
Low Carbon.....	46
Hexagons.....	48





Hot Rolled Rounds

Low Carbon
1020, ASTM A108
 ASTM 576 Special Bar Quality
 ASTM A36 Structural Quality
 Lengths: 20 Ft.



Hot Rolled Rounds

Medium Carbon
 ASTM 576, Special Bar Quality
 1045/1141
 Lengths: 20 Ft.


Size In Inches	Weight per Ft. in Lbs.
3/16	.094
1/4	.167
5/16	.216
3/8	.376
7/16	.511
1/2	.668
9/16	.845
5/8	1.043
11/16	1.262
3/4	1.502
13/16	1.763
7/8	2.045
15/16	2.347
1	2.670
1 1/16	3.015
1 1/8	3.380
1 3/16	3.766
1 1/4	4.172
1 5/16	4.600
1 3/8	5.049
1 7/16	5.518
1 1/2	6.008
1 9/16	6.519
1 5/8	7.051
1 11/16	7.604
1 3/4	8.178
1 13/16	8.733
1 7/8	9.388
1 15/16	10.02
2	10.68
2 1/16	11.58
2 1/8	12.06
2 1/4	13.52
2 3/8	15.06
2 1/2	16.69
2 5/8	18.40
2 3/4	20.19
2 7/8	22.07
2 15/16	23.04
Continued	

Size In Inches	Weight per Ft. in Lbs.
3	24.03
3 1/8	26.08
3 1/4	28.21
3 3/8	30.42
3 1/2	32.71
3 9/16	33.39
3 5/8	35.09
3 3/4	37.55
4	42.73
4 1/16	44.07
4 1/8	45.44
4 1/4	48.23
4 3/8	51.11
4 1/2	54.08
4 5/8	57.12
4 3/4	60.25
5	66.76
5 1/4	73.60
5 1/2	80.78
5 3/4	88.29
6	96.13
6 1/4	104.30
6 1/2	112.80
6 3/4	121.70
7	130.90
7 1/4	140.40
7 1/2	150.20
7 3/4	160.40
8	170.90
8 1/4	181.80
8 1/2	192.90
8 3/4	204.50
9	216.30
9 1/2	241.00
10	267.00
10 1/2	294.40
11	323.10
12	384.50

Size In Inches	Weight per Ft. in Lbs.
1/2	.668
5/8	1.043
3/4	1.502
7/8	2.045
1	2.670
1 1/16	3.015
1 1/8	3.380
1 3/16	3.766
1 1/4	4.172
1 5/16	4.600
1 3/8	5.049
1 7/16	5.518
1 1/2	6.008
1 9/16	6.519
1 5/8	7.051
1 11/16	7.604
1 3/4	8.178
1 13/16	8.773
1 7/8	9.388
1 15/16	10.02
2	10.68
2 1/16	11.36
2 1/8	12.06
2 3/16	12.78
2 1/4	13.52
2 5/16	14.28
2 3/8	15.06
2 7/16	15.87
2 1/2	16.69
2 9/16	17.53
2 5/8	18.40
2 11/16	19.29
2 3/4	20.19
2 13/16	21.12
2 7/8	22.07
2 15/16	23.04
3	24.03
3 1/8	26.08
3 1/4	28.21
Continued	

Size In Inches	Weight per Ft. in Lbs.
3 5/16	29.30
3 3/8	30.42
3 1/2	32.71
3 5/8	35.09
3 3/4	37.55
4	42.73
4 1/8	45.44
4 1/4	48.23
4 1/2	54.08
4 3/4	60.25
5	66.76
5 1/4	73.60
5 1/2	80.78
5 3/4	88.29
6	96.13
6 1/4	104.30
6 1/2	112.80
6 3/4	121.70
7	130.90
7 1/4	140.40
7 1/2	150.20
7 3/4	160.40
8	170.90
8 1/4	181.80
8 1/2	192.90
8 3/4	204.50
9	216.30
9 1/2	241.00
9 3/4	253.90
10	267.00
10 1/2	294.40
11	323.10
12	384.50

Forged and rough turned rounds available.




Hot Rolled Strip

Low Carbon A569 CQ
 .15 Max Carbon
 Lengths: 20 Ft.

Size In Inches	Weight per Ft. in Lbs.
1/8 x 1/2	.213
5/8	.266
3/4	.319
7/8	.372
1	.425
1 1/8	.478
1 1/4	.531
1 3/8	.584
1 1/2	.638
1 3/4	.744
2	.850
2 1/4	.956
2 1/2	1.063
Continued	

Size In Inches	Weight per Ft. in Lbs.
2 3/4	1.169
3	1.275
3 1/4	1.381
3 1/2	1.488
4	1.700
1/8 x 4 1/2	1.913
5	2.125
5 1/2	2.338
6	2.550
7	2.975
8	3.400
10	5.100
12	5.100
3/16 x 1/2	.319




Hot Rolled Squares

Low Carbon A36
 ASTM A36, Structural Quality
 Lengths: 20 Ft.

Size In Inches	Weight per Ft. in Lbs.
3/8	.478
1/2	.850
5/8	1.328
3/4	1.913
7/8	2.603
1	3.400
1 1/8	4.303
Continued	

Size In Inches	Weight per Ft. in Lbs.
1 1/4	5.313
1 1/2	7.650
1 3/4	10.41
2	13.60
2 1/4	17.21
2 1/2	21.25
2 3/4	25.71
3	30.60





Hot Rolled Flats

Low Carbon
A36, M1020
 Structural & Merchant Quality
 Lengths: 20 Ft.

Size In Inches	Weight per Ft. in Lbs.
3/16 X 1/2	.318
1	.637
1 1/2	.956
1 1/4	.797
1 3/4	1.115
2	1.275
3	1.913
3 1/2	2.231
4	2.550
5	3.188
3/16 x 6	3.83
1/4 X 1/2	.425
5/8	.531
3/4	.638
7/8	.744
1	.850
1 1/8	.956
1 1/4	1.063
1 3/8	1.169
1 1/2	1.275
1 5/8	1.381
1 3/4	1.488
2	1.700
2 1/4	1.913
2 1/2	2.125
2 3/4	2.338
3	2.550
3 1/4	2.763
3 1/2	2.975
3 3/4	3.188
4	3.400
4 1/4	36.130
4 1/2	3.825
5	4.250
5 1/2	4.675
6	5.100
7	5.950
7 1/2	6.375
8	6.800
9	7.650
10	8.500
11	9.350
12	10.200
5/16 X 3/4	.797
7/8	.930
1	1.063
1 1/8	1.195
1 1/4	1.328
1 3/8	1.461

Continued

Size In Inches	Weight per Ft. in Lbs.
5/16 X 1 1/2	1.594
1 3/4	1.859
2	2.125
2 1/4	2.391
2 1/2	2.656
2 3/4	2.922
3	3.188
3 1/4	3.453
3 1/2	3.719
4	4.250
4 1/2	4.781
5	5.313
5 1/2	5.844
6	6.375
7	7.438
8	8.500
9	9.563
10	10.630
12	12.750
3/8 X 1/2	.638
3/4	.956
7/8	1.116
1	1.275
1 1/8	1.434
1 1/4	1.594
1 3/8	1.753
1 1/2	1.913
1 5/8	2.072
1 3/4	2.231
2	2.550
2 1/4	2.869
2 1/2	3.188
2 3/4	3.506
3	3.825
3 1/4	4.144
3 1/2	4.463
3 5/8	4.622
3 3/4	4.781
4	5.100
4 1/2	5.738
5	6.375
5 1/2	7.013
6	7.650
6 1/2	8.288
7	8.925
8	10.200
9	11.480
10	12.750
11	14.030


Continued

Size In Inches	Weight per Ft. in Lbs.
3/8 X 12	15.300
7/16 X 1 1/4	1.859
1 1/2	2.231
2	2.975
2 1/2	3.719
3	4.463
5	7.438
1/2 X 3/4	1.275
1	1.700
1 1/8	1.913
1 1/4	2.125
1 3/8	2.338
1 1/2	2.550
1 5/8	2.763
1 3/4	2.975
2	3.400
2 1/4	3.825
2 1/2	4.122
2 3/4	4.675
3	5.100
3 1/4	5.525
3 1/2	5.950
3 3/4	6.375
4	6.800
4 1/2	7.650
5	8.500
5 1/2	9.350
6	10.200
7	11.900
7 1/4	12.330
8	13.600
8 1/2	14.450
9	15.300
9 1/2	16.150
10	17.000
11	18.700
12	20.400
5/8 X 3/4	1.594
1	2.125
1 1/4	2.656
1 3/8	2.922
1 1/2	3.188
1 3/4	3.719
2	4.250
2 1/4	4.781
2 1/2	5.313
2 3/4	5.844
3	6.375
3 1/4	6.906

Continued

Size In Inches	Weight per Ft. in Lbs.
5/8 X 3 1/2	7.438
4	8.500
4 1/2	9.563
5	10.630
5 1/2	11.690
6	12.750
7	14.880
8	17.000
9	19.130
10	21.250
11	23.380
12	25.500
3/4 X 7/16	1.116
1	2.550
1 1/8	2.869
1 1/4	3.188
1 1/2	3.825
1 5/8	4.144
1 3/4	4.463
1 7/8	4.781
2	5.100
2 1/4	5.738
2 1/2	6.375
2 3/4	7.013
3	7.650
3 1/4	8.288
3 1/2	8.925
4	10.200
4 1/2	11.480
5	12.750
5 1/2	14.030
6	15.300
7	17.850
8	20.400
9	22.950
10	25.500
11	28.050
12	30.600
7/8 X 1 1/4	3.719
1 1/2	4.463
1 3/4	5.206
2	5.950
2 1/4	6.694
2 1/2	7.438
3	8.925
3 1/2	10.410
4	11.900
4 1/2	13.390
5	14.880

Continued on Next Page



Reinforcing Bars


ASTM A615 - Billet Steel
Deformed Bars
Grades 40 & 60 – All Sizes
Lengths: 20 Ft.

Size In Inches	Weight per Ft. in Lbs.
7/8 x 5 1/2	16.360
6	17.850
7	20.830
8	23.800
1 x 1 1/4	4.250
1 1/2	5.100
1 3/4	5.950
2	6.800
2 1/4	7.650
2 1/2	8.500
2 3/4	9.350
3	10.200
3 1/4	11.050
3 1/2	11.900
4	13.600
4 1/2	15.300
5	17.000
5 1/2	18.700
6	20.400
7	23.800
8	27.200
9	30.600
10	34.000
12	40.800
1 1/8 x 2	7.650
2 1/2	9.563
3	11.480
4	15.300
5	19.130
6	22.950
8	30.600
1 1/4 x 1 1/2	6.375
1 3/4	7.440
2	8.500
2 1/4	9.560
2 1/2	10.630
2 3/4	11.690
3	12.750
3 1/4	13.810
3 1/2	14.880
4	17.000
4 1/2	19.130
5	21.250
5 1/2	23.380
6	25.500
7	29.750
8	34.000
1 3/8 x 4	18.700
1 1/2 x 1 3/4	8.930

Continued


Size In Inches	Weight per Ft. in Lbs.
1 1/2 x 2	10.200
2 1/4	11.480
2 1/2	12.750
2 3/4	14.030
3	15.300
3 1/2	17.850
4	20.400
4 1/2	22.950
5	25.500
5 1/2	28.050
6	30.600
7	35.700
8	40.800
1 3/4 x 2	11.900
2 1/2	14.880
3	17.850
3 1/2	20.830
4	23.800
4 1/2	26.780
5	29.750
5 1/2	32.730
6	35.700
2 x 2 1/4	15.300
2 1/2	17.000
3	20.400
3 1/2	23.800
4	27.200
4 1/2	30.600
5	34.000
5 1/2	37.400
6	40.800
7	47.600
8	54.400
2 1/4 x 2 1/2	19.130
3	22.950
3 1/2	26.775
4	30.600
2 1/2 x 3	25.550
3 1/2	29.750
4	34.000
4 1/2	38.250
5	42.500
6	51.000
3 x 4	40.800
4 1/2	45.900
5	51.000
6	61.200

Bar No.	Diameter In Inches	Nominal Dimension Area Sq. Inches	Nominal Dimension Perimeter In Inches	Weight per In Lbs.
# 3	.3750	.1100	1.1790	.376
# 4	.5000	.2000	1.5110	.668
# 5	.6250	.3100	1.9630	1.043
# 6	.7500	.4400	2.3560	1.502
# 7	.8750	.6000	2.7490	2.044
# 8	1.0000	.7900	3.1420	2.670
# 9	1.1250	1.0000	3.5440	3.380



Cold Finished Rounds

Low Carbon
1018, C1117, C11L17,
Lengths: 10 to 12 Ft. Random
ASTM A108



Cold Finished Rounds


Medium Carbon
1045, 1141, 11L41 and 1144
Stressproof®, sizes are cold drawn
Lengths: 10 to 12 Ft. Random
ASTM A108

Size In Inches	Weight per Ft. in Lbs.
1/8	.042
5/32	.065
3/16	.094
1/4	.167
5/16	.261
3/8	.376
7/16	.511
1/2	.668
9/16	.845
5/8	1.043
11/16	1.262
3/4	1.502
13/16	1.763
7/8	
2.045 15/16	
2.347	
1	2.670
1 1/16	3.015
1 1/8	3.380
1 3/16	3.766
1 1/4	4.172
1 5/16	4.600
1 3/8	5.049
1 7/16	5.518
1 1/2	6.008
1 9/16	6.519
1 5/8	7.051
1 11/16	7.604
1 3/4	8.178
1 13/16	8.773
1 7/8	9.388
1 15/16	10.02
2	10.68
2 1/16	11.36
2 1/8	12.06
2 3/16	12.78
2 1/4	13.52
2 5/16	14.28
2 3/8	15.06
2 7/16	15.87
2 1/2	16.69
2 9/16	17.53
2 5/8	18.40

Size In Inches	Weight per Ft. in Lbs.
Continued	
2 11/16	19.29
2 3/4	20.19
2 7/8	22.07
3	24.03
3 1/8	26.08
3 3/16	27.13
3 1/4	28.21
3 3/8	30.42
3 7/16	31.55
3 1/2	32.71
3 5/8	35.09
3 3/4	37.55
3 7/8	40.10
4	42.73
4 1/8	45.44
4 1/4	48.23
4 3/8	51.11
4 7/16	52.58
4 1/2	54.08
4 5/8	57.12
4 3/4	60.25
4 7/8	63.46
5	66.76
5 1/8	70.14
5 1/4	73.60
5 3/8	77.15
5 1/2	80.78
5 5/8	84.49
5 3/4	88.29
5 7/8	92.17
6	96.13
6 1/4	104.30
6 1/2	112.80
6 3/4	121.70
7	130.90
7 1/2	150.20
8	170.90
9	216.30
10	267.00
12	384.50

Size In Inches	Weight per Ft. in Lbs.
1/4	.167
5/16	.261
3/8	.376
7/16	.511
15/32	.587
1/2	.668
17/32	.754
9/16	.845
5/8	1.043
11/16	1.262
3/4	1.502
49/64	1.565
13/16	1.763
7/8	2.045
15/16	2.347
1	2.670
1 1/8	3.015
1 1/8	3.380
1 3/16	3.766
1 7/32	3.966
1 1/4	4.172
1 5/16	4.600
1 3/8	5.049
1 7/16	5.518
1 1/2	6.008
1 9/16	6.519
1 5/8	7.051
1 11/16	7.604
1 3/4	8.178
1 13/16	8.773
Continued	


Size In Inches	Weight per Ft. in Lbs.
1 7/8	9.388
1 15/16	10.02
2	10.68
2 1/16	11.36
2 1/8	12.06
2 3/16	12.78
2 1/4	13.52
2 5/16	14.28
2 3/8	15.06
2 7/16	15.86
2 1/2	16.69
2 9/16	17.53
2 5/8	18.40
2 11/16	19.29
2 3/4	20.19
2 7/8	22.07
2 15/16	23.04
3	24.03
3 1/8	26.08
3 1/4	28.21
3 3/8	30.42
3 1/2	32.71
3 5/8	35.09
3 3/4	37.55
3 7/8	40.10
4	42.73
4 1/8	45.44
4 1/4	48.23
4 3/8	51.11
4 1/2	54.08



Cold Drawn Rounds

Screw Stock
C1215, 12L14, 1214 + Bi,
12L14 + Se or Te, C12T14
 Lengths: 12 Ft. Random
ASTM A108


Size In Inches	Weight per Ft. in Lbs.	Size In Inches	Weight per Ft. in Lbs.
5/64	.016	1 1/8	3.380
3/32	.024	1 3/16	3.766
7/64	.032	1 1/4	4.172
1/8	.042	1 5/16	4.600
9/64	.053	1 3/8	5.049
5/32	.065	1 7/16	5.518
11/64	.079	1 1/2	6.008
3/16	.094	1 9/16	6.519
13/64	.110	1 5/8	7.051
7/32	.128	1 11/16	7.604
15/64	.147	1 3/4	8.178
1/4	.167	1 13/16	8.773
17/64	.188	1 7/8	9.388
9/32	.211	1 15/16	10.02
19/64	.235	2	10.68
5/16	.261	2 1/16	11.36
21/64	.288	2 1/8	12.06
11/32	.316	2 3/16	12.78
23/64	.345	2 1/4	13.52
3/8	.376	2 5/16	14.28
25/64	.408	2 3/8	15.06
13/32	.441	2 7/16	15.87
27/64	.475	2 1/2	16.69
7/16	.511	2 9/16	17.53
29/64	.548	2 5/8	18.40
15/32	.587	2 11/16	19.29
31/64	.627	2 3/4	20.19
1/2	.668	2 13/16	21.12
33/64	.710	2 7/8	22.07
17/32	.754	2 15/16	23.04
9/16	.845	3	24.03
37/64	.893	3 1/16	25.05
19/32	.941	3 1/8	26.08
39/64	.992	3 1/4	28.21
5/8	1.043	3 5/16	29.30
41/64	1.096	3 3/8	30.42
21/32	1.150	3 7/16	31.55
43/64	1.205	3 1/2	32.71
11/16	1.262	3 5/8	35.09
45/64	1.320	3 3/4	37.55
23/32	1.380	3 7/8	40.10
47/64	1.440	4	42.73
3/4	1.502	4 1/8	45.44
49/64	1.565	4 1/4	48.23
25/32	1.630	4 3/8	51.11
13/16	1.763	4 1/2	54.08
27/32	1.901	4 5/8	57.12
7/8	2.045	4 3/4	60.25
57/64	2.118	5	66.76
29/32	2.193	5 1/4	73.60
15/16	2.347	5 1/2	80.78
31/32	2.506	5 5/8	84.49
63/64	2.588	5 3/4	88.29
1	2.670	6	96.13
1 1/64	2.754	6 1/2	112.80
1 1/32	2.840	7	130.90
1 1/16	3.015	8	170.90
Continued		9	216.30



Shafting Rounds

Turned, Ground & Polished
1045, 1141 Stressproof®
 Lengths: 20 & 24 Ft.
 Niagara LaSalle Stressproof meets
ASTM A311 Class B. All other
 grades meet **ASTM A108**


Size In Inches	Weight per Ft. in Lbs.	Size In Inches	Weight per Ft. in Lbs.
5/16	.261	2 1/2	16.69
3/8	.376	2 5/8	18.40
7/16	.511	2 11/16	19.29
1/2	.668	2 3/4	20.19
9/16	.845	2 7/8	22.07
5/8	1.043	2 15/16	23.04
3/4	1.502	3	24.03
13/16	1.763	3 3/16	27.13
7/8	2.045	3 1/4	28.21
15/16	2.347	3 7/16	31.55
1	2.670	3 1/2	32.71
1 1/8	3.380	3 11/16	36.31
1 3/16	3.766	3 3/4	37.55
1 1/4	4.172	3 15/16	41.40
1 5/16	4.600	4	42.73
1 3/8	5.049	4 3/16	46.83
1 7/16	5.518	4 1/4	48.23
1 1/2	6.008	4 3/8	51.11
1 5/8	7.051	4 7/16	52.58
1 11/16	7.604	4 1/2	54.08
1 3/4	8.178	4 3/4	60.25
1 7/8	9.388	4 15/16	65.10
1 15/16	10.02	5	66.76
2	10.68	5 1/4	73.60
2 1/8	12.06	5 7/16	78.95
2 3/16	12.78	5 1/2	80.78
2 1/4	13.52	5 15/16	94.14
2 3/8	15.06	6	96.13
2 7/16	15.87	7	130.90
Continued		8	170.90



Cold Drawn Squares

Screw Stock
ASTM A108, C1018, C1215
& C12L14
 Lengths: 10 to 12 Ft. Random

Size In Inches	Weight per Ft. in Lbs.	Size In Inches	Weight per Ft. in Lbs.
1/8	.053	13/16	2.245
5/32	.083	7/8	2.603
3/16	.120	15/16	2.988
7/32	.163	1	3.400
1/4	.213	1 1/8	4.303
9/32	.269	1 1/4	5.313
5/16	.332	1 3/8	6.428
3/8	.478	1 1/2	7.650
7/16	.651	1 5/8	8.978
1/2	.850	1 3/4	10.41
9/16	1.076	2	13.60
5/8	1.328	2 1/4	17.21
11/16	1.607	2 1/2	21.25
3/4	1.913	2 3/4	25.71
Continued			



Cold Finished Flats

Low Carbon
 ASTM A108 & C1018
 Lengths: 10 to 12 Ft. Random

Size In Inches	Weight per Ft. in Lbs.
1/8 X 1/4	.106
3/8	.159
1/2	.213
5/8	.266
3/4	.319
7/8	.372
1	.425
1 1/4	.531
1 1/2	.638
1 3/4	.744
2	.850
2 1/2	1.063
3	1.275
3 1/2	1.488
4	1.700
5	2.125
6	2.550
3/16 X 1/4	.159
3/8	.239
1/2	.319
5/8	.398
3/4	.478
7/8	.558
1	.638
1 1/8	.717
1 3/8	.797
1 1/2	.956
1 3/4	1.116
1 7/8	1.195
2	1.275
2 1/4	1.434
2 1/2	1.594
2 3/4	1.753
3	1.913
3 1/2	2.231
4	2.550
5	3.188
6	3.825
10	6.375
1/4 X 5/16	.266
3/8	.319
7/16	.372
1/2	.425
5/8	.531
Continued	

Size In Inches	Weight per Ft. in Lbs.
1/4 X 3/4	.638
7/8	.744
1	.850
1 1/8	.956
1 1/4	1.063
1 3/8	1.169
1 1/2	1.275
1 5/8	1.381
1 3/4	1.488
2	1.700
2 1/4	1.913
2 1/2	2.125
2 3/4	2.338
3	2.550
3 1/4	2.763
3 1/2	2.975
3 3/4	3.188
4	3.400
4 1/2	3.825
5	4.250
5 1/2	4.675
6	5.100
7	5.950
8	6.800
9	7.650
10	8.500
12	10.200
5/16 X 3/8	.398
7/16	.465
1/2	.531
9/16	.598
5/8	.664
3/4	.797
7/8	.930
1	1.063
1 1/8	1.195
1 1/4	1.328
1 3/8	1.461
1 1/2	1.594
1 3/4	1.859
2	2.125
2 1/4	2.391
2 1/2	2.656
3	3.188
Continued	

Size In Inches	Weight per Ft. in Lbs.
5/16 X 3 1/2	3.719
4	4.250
5	5.313
6	6.375
3/8 X 7/16	.558
1/2	.638
5/8	.797
3/4	.956
7/8	1.116
1	1.275
1 1/8	1.434
1 1/2	1.913
1 3/8	1.753
1 1/2	1.913
1 5/8	2.072
1 3/4	2.231
2	2.550
2 1/4	2.869
2 1/2	3.188
2 3/4	3.506
3	3.825
3 1/4	4.144
3 1/2	4.463
3 3/4	4.781
4	5.100
4 1/2	5.738
5	6.375
5 1/2	7.013
6	7.650
7	8.925
8	10.20
9	11.48
10	12.75
12	15.30
7/16 X 1/2	.744
3/4	1.116
1	1.488
1 1/4	1.859
1 1/2	2.231
2	2.975
2 1/2	3.719
4	5.950
1/2 X 9/16	.956
5/8	1.063
Continued	


Size In Inches	Weight per Ft. in Lbs.
1/2 X 3/4	1.275
7/8	1.488
1	1.700
1 1/8	1.913
1 1/4	2.125
1 3/8	2.338
1 1/2	2.550
1 5/8	2.763
1 3/4	2.975
2	3.400
2 1/4	3.825
2 1/2	4.250
2 3/4	4.675
3	5.100
3 1/4	5.525
3 1/2	5.950
4	6.800
4 1/2	7.650
5	8.500
5 1/2	9.350
6	10.20
7	11.90
8	13.60
9	15.30
10	17.00
12	20.40
5/8 X 3/4	1.594
7/8	1.859
1	2.125
1 1/4	2.656
1 1/2	3.188
1 3/4	3.719
2	4.250
2 1/4	4.781
2 1/2	5.313
2 3/4	5.844
3	6.375
3 1/2	7.438
3 3/4	7.969
4	8.500
4 1/2	9.563
5	10.63
5 1/2	11.69
6	12.75
Continued on Next Page	

Size In Inches	Weight per Ft. in Lbs.
5/8 x 7	14.88
8	17.00
10	21.25
12	25.50
3/4 x 7/8	2.231
1	2.550
1 1/8	2.869
1 1/4	3.188
1 3/8	3.506
1 1/2	3.825
1 3/4	4.463
2	5.100
2 1/4	5.738
2 1/2	6.375
2 3/4	7.013
3	7.650
3 1/4	8.288
3 1/2	8.925
4	10.20
4 1/2	11.48
5	12.75
5 1/2	14.03
6	15.30
6 1/2	16.58
7	17.85
8	20.40
9	22.95
10	25.50
11	28.05
12	30.60
7/8 x 1	2.975
1 1/8	3.347
1 1/4	3.719
1 3/8	4.091
1 1/2	4.463
1 3/4	5.206
2	5.950
2 1/2	7.438
2 3/4	8.181
3	8.925
3 1/2	10.41
4	11.90
5	14.88
6	17.85
Continued	

Size In Inches	Weight per Ft. in Lbs.
7/8 x 8	23.80
1 x 1 1/8	3.825
1 1/4	4.250
1 3/8	4.675
1 1/2	5.100
1 5/8	5.525
1 3/4	5.950
2	6.800
2 1/4	7.650
2 1/2	8.500
2 3/4	9.350
3	10.20
3 1/2	11.90
4	13.60
4 1/2	15.30
5	17.00
5 1/2	18.70
6	20.40
6 1/2	22.12
7	23.80
8	27.20
9	30.60
10	34.00
12	40.80
1 1/8 x 1 1/4	4.781
2	7.650
2 1/2	9.563
3	11.48
4	15.30
1 1/4 x 1 3/8	5.844
1 1/2	6.375
1 5/8	6.906
1 3/4	7.438
2	8.500
2 1/4	9.563
2 1/2	10.63
2 3/4	11.69
3	12.75
3 1/4	13.81
3 1/2	14.88
3 3/4	15.94
4	17.00
4 1/2	19.13
5	21.25
Continued	

Size In Inches	Weight per Ft. in Lbs.
1 1/4 x 5 1/2	23.38
6	25.50
8	34.00
10	42.50
12	51.00
1 3/8 x 2	9.350
3	14.03
1 1/2 x 1 3/4	8.925
2	10.20
2 1/4	11.48
2 1/2	12.75
2 3/4	14.03
3	15.30
3 1/2	17.85
4	20.40
4 1/2	22.95
5	25.50
5 1/2	28.05
6	30.60
6 1/2	33.15
8	40.80
8 1/2	43.35
10	51.00
12	61.20
1 3/4 x 2	11.90
2 1/4	13.39
2 1/2	14.88
2 3/4	16.36
3	17.85
3 1/2	20.83
3 3/4	22.31
4	23.80
4 1/2	26.78
5	29.75
5 1/2	32.73
6	35.70
6 1/2	38.68
2 x 2 1/4	15.30
2 1/2	17.00
2 3/4	18.70
3	20.40
3 1/2	23.80
4	27.20
4 1/2	30.60
Continued	

Size In Inches	Weight per Ft. in Lbs.
2 x 5	34.00
5 1/2	37.40
6	40.80
6 1/2	44.20
7	47.60
8	54.40
10	68.00
12	81.60
2 1/4 x 2 1/2	19.13
2 3/4	21.04
3	22.95
3 1/4	24.86
3 1/2	26.78
4	30.60
5	38.25
6	45.90
2 1/2 x 3	25.50
3 1/2	29.75
4	34.00
4 1/2	38.25
5	42.50
6	51.00
8	68.00
10	85.00
3 x 3 1/2	35.70
4	40.80
4 1/2	45.90
5	51.00
6	61.20
8	81.60
10	102.00
4 x 5	68.00
6	81.60



Cold Drawn Hexagons

ASTM A108, C1018 & C12L14
Lengths: 10 to 12 Ft. Random

Size In Inches	Weight per Ft. in Lbs.	Size In Inches	Weight per Ft. in Lbs.
1/8	.046	1 1/4	4.601
5/32	.072	1 5/16	5.072
3/16	.104	1 3/8	5.567
7/32	.140	1 7/16	6.085
15/64	.162	1 1/2	6.625
1/4	.184	1 9/16	7.189
9/32	.233	1 5/8	7.775
5/16	.288	1 11/16	8.385
11/32	.348	1 3/4	9.018
3/8	.414	1 13/16	9.673
7/16	.564	1 7/8	10.35
1/2	.736	2	11.78
9/16	.932	2 1/8	13.30
5/8	1.150	2 3/16	14.09
11/16	1.392	2 1/4	14.91
3/4	1.656	2 3/8	16.61
13/16	1.944	2 1/2	18.40
7/8	2.254	2 5/8	20.30
15/16	2.588	2 3/4	22.27
1	2.945	2 7/8	24.34
1 1/16	3.324	3	26.50
1 1/8	3.727	3 1/4	31.10
1 3/16	4.152	3 1/2	36.08
Continued		4	47.12