



CATALOG





:: QUICKFINDER

→ A
Alu Spezial7
Booth Mask Stick
→ C
Car Grip 4 Carbo Spray 19 Carbo Spray Thinner 19 Carbo UV Clear 18 Cockpit-Spray 13
→ D
Dry Coat- black
→F
Flex
→ G
Glas white5
KS-50
→ L Liquid Putty6
Magnet for UV LED Lamp XL18 Magnetic Flat Strip12 Magnetic Sanding Protection12
Master Tape Green10
Multi Glas Green5 Multi Green4
Multi Silver Light7

→ N 1K NC Putty6	6
Plastic Pro	3
→ R Refinish Restorer	
→ S Silver wheel spray 13 Slim Tape 10 Soft 4 Speedmixer 3 Kg 9 Spray 6 Spray card 12 1K Spray Primer 8 Spray Thinner 8 Stand for UV LED Lamp XL 18 Steel 5	0 1 6 2 8 8 8
→ T Touch Up12	2
UV Clear	3 9 3 3
→ W WR-Lifting Tape Premium10)
→ Z Zink Spray13	3

The information is intended as aguide to application and is based on current information. The information is offered in good faith and without guarantee or liability. Product specifications subject to change availability.

:: REGISTER

Product#	Product	Page	Product#	Product	Page
123.892	DUALMATIC 3 KG 32 EXV AV	9	146.191	CS SPRAY CARD metal WHITE	12
124.315	CS SPRAY THINNER	8	146.608	CS SPRAY CARD DARK GREY	12
125.580	CS 1K Spray Primer	8	146.706	CS MULTI GREEN incl. hardener KG	4
126.020	CS Cockpit-SPRAY	13	146.707	CS MULTI GLAS GREEN incl.hardener	5
126.021	CS Silver-Wheel-SPRAY	13	147.337	CS MULTI GREEN H19 incl.hardener	4
126.023	CS KS-1050 StoneChipProtect. black	16	148.019	CS CARBO SPRAY incl. MEKP hardener	19
126.028	CS Rust Remover SPRAY	13	148.234	CS CARBO SPRAY THINNER	19
126.029	CS KS-550 Bitumen SPRAY black	16	148.524	CS ALU SPEZIAL INKL. HARDENER	7
126.030	CS Zinc-SPRAY	13	148.861	CS FOAM TAPE Classic 13MM BOX (oval)	10
126.032	CS KS-100 Bitumenbase brushable	14	149.221	CS MASTER TAPE GREEN 19 MM X 50 M	10
126.034	CS KS-500 Bitumen black	15	149.225	CS MASTER TAPE GREEN 38 MM X 50 M	10
126.040	CS KS - Dual Gun 1-2 UBS Gun	17	149.226	CS MASTER TAPE GREEN 50 MM X 50 M	10
126.048	CS Suction Pipe for KS Dual-Gun	17	149.265	CS KS-1000 Stone Chip Protection black	16
126.058	CS CAVITY PROTECTION TUBE for Dual Gun	17	149.338	CS Booth Mask Stick	11
126.061	CS KS-250 Cavity Protection	15	149.342	CS DUST KEEPER - Dust Binder	11
126.062	CS KS-200 Cavity Protection ML	14	149.613	CS PLASTIC PRO incl. hardener	7
127.972	CS SOFT incl.hardener	4	150.769	CS TOUCH UP BOTTLE transp. 25 pcs	12
127.978	CS SPRAY incl.hardener	6	150.801	CS KS-50 Brushable SEAM SEALER	14
128.366	CS DRY-COAT black	11	151.071	CS Refinish Restorer	13
130.992	CS Magnetic Sanding Protection 4x55cm	12	151.504	CS WR-LIFTING TAPE PREMIUM 9+11mmx10 m	10
132.116	CS SOFT H19 incl.hardener cartridge KG 2,6	4	152.088	CS Multi Green long incl. hardener for Speedmixer	9
132.413	BPO-HARDENER USA red Förster	8	152.112	CS CARBON UV Clear	18
133.827	CS SLIM TAPE 18mm x 50m	10	152.194	UV Clear applicator bottle	18
134.165	CS KS-300 Cavity Wax white-transp.	15	152.266	CS Nozzles Green for Speedmixer	9
134.374	CS KS-4000 water based black	17	152.719	CS Plastiksp. 115x77mm Box á 100 St	8
134.796	CS FLEX incl.hardener	7	152.804	CS KS-3000 Plus Stone Protect.grey	17
135.396	CS KS-Gun	18	152.823	SPEEDMIXER 3 KG	9
137.214	CS Magnetic Flat Strip 4x55cm Set	12	153.432	CS CarGrip USA incl. Hardener	4
137.435	CS PUTTY KNIFE Special Steel Spreader 60mm	9	153.777	CS UV Smart Lamp	18
137.436	CS PUTTY KNIFE Special Steel Spreader 80mm	9	154.093	CS IND 1K NC Putty	6
137.437	CS PUTTY KNIFE Special Steel Spreader 100mm	9	154.189	CS UV Filler	19
138.587	CS STEEL incl.hardener	5	154.190	CS UV Filler Spray	19
140.795	CS Multi Silver Light incl hardener	7	154.528	CS UV Clear	18
142.279	CS KS - Gun tube set	18	154.615	CS UV Gun Cleaner	18
142.889	CS Putty Board Set (10 pcs.)	9	154.646	CS Stand for UV LED Lamp XL	18
143.496	CS Liquid Putty incl.hardener	6	154.648	CS Magnet for UV LED Lamp XL	18
144.808	CS GLAS WHITE incl.BPO white	5	155.036	CS UV LED Lamp XL	18

Car Grip Lightweight Perfomance Body Filler



→ Area of application

Use for Dents to Small Scratches with the same Product. Works on the most Automotive Substrates.

→ Characteristics

- -Improves cycle time
- -High Standard of qualitly
- -No need for Body Filler & Putty, Car Grip is both in one

Art. No.	Specification	SP	MOQ
153.432	light blue / 8,82 lbs (4000g) tin (incl. hardener)	1	6
152.719	CS Plastic Spreader Box á 100 pcs.	1	1

Soft

polyester body putty



→ Area of application

For filling deep, uneven areas, particularly suitable for large areas.

Easily sandable, high viscosity, concentrated filling, pore-free surface.

Art. No.	Specification	SP	MOQ
127.972	beige / 3,97 lbs tin (incl. hardener)	1	6
132.116	beige / 5,73 lbs cartridge (incl. hardener)	1	6
152.719	CS Plastic Spreader Box á 100 pcs.	1	1
123.892	Putty dispenser- manual for 3kg cartridges	1	1

Multi Green

polyester multifunctional putty - green



→ Area of application

For universal use on all steel, aluminium and galvanised bodywork in car repairs as well as on GRP and wooden parts.

Multifunctional putty for a variety of surfaces.

This new multifunctional putty is a complete new developed putty with resins and fillers of the latest generation.

This high thixotropic putty is characterised by a high stability during application matched with a rapid drying time and a pore-free surface before sanding. VOC reduced.

Art. No.	Specification	SP	MOQ
146.706	green / 3.53 lbs tin (incl. hardener)	1	6
147.337	green 5.56 lbs cartridge (incl. hardener)	1	6
152.719	CS Plastic Spreader Box á 100 pcs.	1	1
123.892	Putty dispenser- manual for 3kg cartridges	1	1

Multi Glas Green polyester multifunctional fibreglass reinorced putty - green

→ Area of application

Reinforced fibreglass putty for steel-, aluminium- and galvanised carbodies as well as for GRP and wooden elements.

→ Characteristics

This new fibreglass putty has not only a wide range of surface applications but also enhanced improvements in spreading behaviour, sandability and an even more pore-free surface as conventional fibreglass putties. VOC reduced.

Art. No.	Specification	SP	MOQ
146.707	green / 3.64 lbs (1.650 g) tin (incl. hardner)	1	6
152.719	CS Plastic Spreader Box á 100 pcs.	1	1



Glas white

polyester fibreglass reinforced putty - white

→ Area of application

A fibreglass filler for repairing GRP components and for filling deeper uneven areas.

→ Characteristics

This white fibreglass putty has a direct adhesion on GRP components, steel and wood. The white neutral colour makes it versatile applicable on these various surfaces. It's modified fibre structure offers a better spreading behaviour and makes it easier to sand.

Art. No.	Specification	SP	MOQ
144.808	white / 3.97 lbs (1.800 g) tin (incl. hardener)	1	6
152.719	CS Plastic Spreader Box á	1	1



Steel

polyester body putty

→ Area of application

For filling bodywork edges, wing flanges and joints, as well as for repairs to tank supports and door edges.

Putty with a very high degree of hardness. Suitable for special repairs.

Art. No.	Specification	SP	MOQ
138.587	alu-grey / 1.98 lbs (900g) tin (incl. hardener)	1	6
152.719	CS Plastic Spreader Box á 100 pcs.	1	1





For all our polyester body pastes:

If there is resin floating on top, please don't mix but throw it away. Mixing causes air pockets in the paste and pinholes on the surface.

Liquid Putty

polyester finishing putty



→ Area of application

Liquid Putty is used for filling small surface imperfections like scratches and pinholes before applying the primer / filler. It can be used to fill up to approx. 3 mm deep imperfections.

→ Characteristics

Liquid Putty is a 2 component polyester finishing. Liquid Putty has been specially developed for the professional. It has excellent adhesion to metal, body filler, wood, fibreglass, catalysed primers and old / sanded OEM topcoats.

Art. No.	Specification	SP	MOQ
143.496	beige / 2.20 lbs (1.000 g) bottle (incl. hardener)	1	8
152.719	CS Plastic Spreader Box á 100 pcs.	1	1

1K NC Putty

kombi putty



→ Characteristics

The CS 1K NC Putty is 1-component nitrocellulose-based filler. The puty is ideal for spot repair of small uneveness, such as scratches, holes or stone damages. By application in thin layers, the filler dries very fast and forms an smooth surface. The 1K NC Putty is applicable on polyser fillers, acrylic fillers, metal, steel, aluminium and galvanized surfaces.

Art. No.	Specification	SP	MOQ
154.093	CS 1K NC Putty 7,05 oz. (200g)	1	24

Spray

polyester spray filler



→ Area of application

For filling uneven surfaces, sanding traces and pore bubbles on bodywork parts, both in the area of cars and lorries and also in vehicle construction and repair.

→ Characteristic

Spray is a 2 comp. polyester spray filler that is easy to sand. It has good adhesive properties to metal, wood, polyester puttied areas and GRP parts. It is for filling smaller and larger uneven areas. It dries up rapidly and produces a pore-free surface.

→ Processing equipment

All polyester products are porous and precautions should be taken to insure peak product performance. Once Spray is sanded, it must be topcoated immediately with a good quality 2K urethane primer such as CS Air Plus or 540 to properly seal the surface from moisture penetration.

→ Area of application

Gravity Spray Gun, jet size 2,5 diameter. Pressure: 2-2,5 bar.

Art. No.	Specification	SP	MOQ
127.978	grey / 3.31 lbs (1.500 g) tin (incl. hardener)	1	6

Plastic Pro

plastic putty

→ Area of application

To repair scratches and damages on plastic parts.

→ Characteristics

A specialized new developed plastic putty for the most common plastics available on the market. The putty has excellent properties such as adhesion, elasticity and sandability as well as fineness of the surface.

Art. No.	Specification	SP	MOQ
149.613	black / 2.20 lbs (1.000g) tin (incl. hardener)	1	6
152.719	CS Plastic Spreader Box á 100 pcs.	1	1



Flex

polyester contour putty for plastics

→ Area of application

For repairing small scratches and defects on plastic parts.

→ Characteristics

Plastic outline putty.

Art. No.	Specification	SP	MOQ
134.796	dark grey / 2.20 lbs (1.000) g tin (incl. hardener)	1	12
152.719	CS Plastic Spreader Box á 100 pcs.	1	1



Alu Spezial

aluminium & galvanized putty

→ Area of application

→ Area of application

A special putty for working on aluminium surfaces.

→ Characteristics

Alu Spezial is a special polyester hard putty for aluminium surfaces. It has a lower temperature expansion with less shrinking at a very high degree of hardness. This flexible repair putty absorbs vibrations and oscillations better. It is suitable for all special repairs on aluminium. Besides it offers perfect adhesion on steel-, zinc- and aluminium bases.

Art. No.	Specification	SP	MOQ
148.524	lightgrey / 3.97 lbs (1.800 g) tin (incl. hardener)	1	6
152.719	CS Plastic Spreader Box á 100 pcs.	1	1



Multi Silver Light

polyester multifunctional putty

Art. No. Specification SP MOQ silver / 140.795 3.31 lbs (1.500 g) tin 1 6 (incl. hardener) 1 52.719 CS Plastic Spreader Box á 1 1

For universal use as a filling and fine putty with excellent adhesion to all metallic surfaces, particularly aluminium and galvanized steel. Very lightweight (1.44g/ml) polyester multifunctional putty. Because of its

thixotropic processing properties, suitable even for difficult areas.



BPO Hardener

BPO Hardener



→ Area of application
BPO hardener for polyester putty.

Art. No.	Specification	SP	MOQ
132.413	red / BPO hardener tube / 1,41 oz (40 g)	10	10

1K Spray Primer spray filler



→ Area of application

Smoothes shallow uneven spots and serves as a blocking primer on polyester putty.

Fast-drying acrylic filler with excellent adhesion and very high filling performance.

Art. No.	Specification	SP	MOQ
125.580	grey / 13.53 oz (400 ml)	1	12

Spray Thinner spray putty thinner



→ Description

Thinner for polyester spray putty.

Art. No.	Specification	SP	MOQ
124.315	transparent / 33.81 oz (1 l) tin / spray putty thinner	1	6

Plastic Spreader plastic spreader



→ Characteristics

Unbreakable and solvent-resistant plastic spreader, width 12 cm.

Art. No.	Specification	SP	MOQ
152.719	115 mm x 77 mm	100	100

Dualmatic

putty dispenser - manual

→ Area of application

Precise measuring of polyester putty and hardener in order to ensure the correct mixing ratio. The amount of hardener to be added can be adjusted.

→ Characteristics

Mobile, handy device for 3 kg cartridges. Manual operation.

Art. No.	Specification	SP	MOQ
123.892	putty dispenser - manual for 3 kg cartridges	1	1
132.116	Soft beige / 5,73 lbs cartridge (incl. hardener)	1	6
147.337	Multi green 5.56 lbs cartridge (incl. hardener)	1	6
142.889	Putty Board 10 pcs. bag	1	1
152.719	CS Plastic Spreader Box á 100 pcs.	1	1



Speedmixer 3 kg putty mixing dispenser

→ Area of application

The Speedmixer produces a perfect ready mixed putty - homogenious and free of air bubbles.

→ Characteristics

For 3 kg cartridges.

Art. No.	Specification	SP	MOQ
152.823	Speedmixer 3 kg	1	1
152.088	Multi Green / slow / green / 5,56 lbs (2.523 kg) cartridge (incl. hardener) / Speedmixer	6	6
152.266	A bag of 90 nozzles for each carton of 6.	1	1
152.719	CS Plastic Spreader Box á 100 pcs.	1	1
142.889	Putty Board 10 pcs. bag	1	1



Putty Knife steel spreader

→ Characteristics

Steel spreader with a solvent-resistant plastic handle.

Art. No.	Specification	SP	MOQ
137.435	60 mm	1	12
137.436	80 mm	1	12
137.437	100 mm	1	12



Slim Tape

special masking tape



→ Area of application

High-performance masking tape for problematic materials, such as rubber and plastic parts.

→ Characteristics

Extremely thin, flexible and waterproof. High curve resistance, hardly any paint edges, temperature resistant up to 100 °C.

Art. No.	Specification	SP	MOQ
133.827	18 mm x 50 m	10	160

Master Tape Green

masking tape



→ Area of application

Professional masking tape for paint shops.


→ Characteristics

Waterproof, temperature resistant up to 110°C.

Art. No.	Specification	SP	MOQ
149.221	19 mm x 50 m	48	48
149.225	38 mm x 50 m	24	24
149.226	50 mm x 50 m	24	24

WR-Lifting Tape Premium

masking tape - perforated



→ Description

Special masking tape for protecting rubber profiles on bonded windscreens, as well as for covering headlamps, rear lights and direction indicators.

→ Characteristics

A masking tape which consists of a highly resistant, transparent, perforated plastics material strip.

Waterproof, temperature resistant up to 100°C. It offers two sizes in a band, 9 and 11 mm.

→ Processing equipment

For this masking tape a dispenser is not necessary because it is perforated.

Art. No.	Specification	SP	MOQ
151.504	perforated / 9 + 11 mm x 10 m	1	36

Foam Tape

foam sealing tape



→ Area of application

For professionally covering openings (doors, boot lids and engine bonnets). For perfectly sealing gaps and holes.

→ Characteristics

Silicone-free tape, temperature resistant up to 80 °C.

The rounded geometry ensures a very easy and universal application.

Art. No.	Specification	SP	MOQ
148.861	13 mm x 50 m	1	80