



Cisco 2900 Series Router Datasheet



Router-Switch.com
Leading Network Hardware Supplier

CONTENT

Overview	2
Appearance	2
Key Features and Benefits	3
Modularity Features and Benefits	4
Product Specifications	6
Basic Ordering Information	11
Additional Information	14
Where to Buy	14
Sources	14

Contact Us

Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166 /

Fax: +852-3050-1066 (Hong Kong)

Email: cisco@router-switch.com (Sales Inquiries)

ccie-support@router-switch.com (CCIE Technical Support)

OVERVIEW

Cisco 2900 Series builds on the best-in-class offering of the existing Cisco 2800 Series Integrated Services Routers by offering four platforms (Figure 1): the Cisco 2901, 2911, 2921, and 2951 Integrated Services Routers.

All Cisco 2900 Series Integrated Services Routers offer embedded hardware encryption acceleration, voice- and video-capable digital signal processor (DSP) slots, optional firewall, intrusion prevention, call processing, voicemail, and application services. In addition, the platforms support the industries widest range of wired and wireless connectivity options such as T1/E1, T3/E3, xDSL, copper and fiber GE.

APPEARANCE

Figure 1. Cisco 2900 Integrated Services Router



KEY FEATURES AND BENEFITS

Service integration

- The Cisco 2900 Series ISRs offer increased levels of services integration with voice, video, security, wireless, mobility, and data services, enabling greater efficiencies and cost savings.

Services on demand

- A single Cisco IOS® Software Universal image is installed on each ISR G2. The Universal image contains all of the Cisco IOS technology sets which can be activated with a software license. This allows your business to quickly deploy advanced features without downloading a new IOS image. Additionally, larger default memory is included to support the new capabilities.
- The Cisco Services Ready Engine (SRE) enables a new operational model which allows you to reduce capital expenditures (CapEx) and deploy a variety of application services as needed on a single integrated compute services module.

High performance with integrated services

- The Cisco 2900 Series enables deployment in high speed WAN environments with concurrent services enabled up to 75 Mbps.
- A multigigabit fabric (MGF) enables high-bandwidth module-to-module communication without compromising routing performance.

Network agility

- Designed to address customer business requirements, the Cisco 2900 Series modular architecture offers increased capacity and performance as your network needs grow.
- Modular interfaces offer increased bandwidth, a diversity of connection options, and network resiliency.

Energy efficiency

- The Cisco 2900 Series architecture provides energy-saving features that include the following:
 - The Cisco 2900 Series offers intelligent power management and allows the customer to control power to the modules based on the time of day. Cisco EnergyWise technology will be supported in the future.
 - Services integration and modularity on a single platform performing multiple functions, optimizes raw materials consumption and energy usage.
 - Platform flexibility and ongoing development of both hardware and software capabilities lead to a longer product lifecycle, lowering all aspects of the total cost of ownership, including materials and energy use.

- High efficiency power supplies are provided with each platform.

Investment protection

- The Cisco 2900 Series maximizes investment protection:
 - Reuse of a broad array of existing modules supported on the original Integrated Services Routers provides a lower cost of ownership.
 - A rich set of Cisco IOS Software features carried forward from the original Integrated Services Routers and delivered in a single universal image.
 - Flexibility to adapt as your business needs evolve.

MODULARITY FEATURES AND BENEFITS

ISR Modules	Benefits
<p>Cisco Service Module</p>	<ul style="list-style-type: none"> • Each service module slot offers high-data-throughput capability: <ul style="list-style-type: none"> Up to 4 Gbps aggregate toward the route processor. Up to 2 Gbps aggregate to other module slots over MGF. • Service module (SM) slots are highly flexible with support for double-wide service modules (SM-Ds), which are Service Modules that require two SM slots. SM-Ds in the Cisco 2921 and 2951 provide flexibility for higher-density modules. • A service module slot replaces the network module and the extension module for voice/fax (EVM) slots and is offered on Cisco 2911, 2921, and 2951 ISRs. • An adapter module enables backward compatibility with existing network modules, enhanced network modules (NMEs), and EVMs. • Service module slots provide twice the power capabilities relative to the network-module slots, allowing for flexibility for higher-scale and better-performance modules. • Power to service module slots can be managed by extensions similar to the Cisco EnergyWise framework, so your organization can reduce energy consumption in your network infrastructure. Full EnergyWise support will be available in future software releases.
<p>Cisco Enhanced High-Speed WAN Interface Card (EHWIC)</p>	<ul style="list-style-type: none"> • The EHWIC slot provides enhancements to the prior generation’s high-speed WAN interface card (HWIC) slots while provide maximum investment protection by natively supporting HWICs, WAN interface cards (WICs), voice

	<p>interface cards (VICs), and voice/WAN interface cards (VWICs).</p> <ul style="list-style-type: none"> • Four integrated EHWIC slots on the Cisco 2901, 2911, 2921, and 2951 allow for more flexible configurations. • Each HWIC slot offers high-data-throughput capability: Up to 1.6 Gbps aggregate toward the route processor. Up to 2 Gbps aggregate to other module slots over the MGF. • Flexibility to support double-wide modules is enabled by combining two EHWIC slots. Up to 2 doublewide HWIC (HWIC-D) modules are supported.
<p>Cisco Internal Services Module (ISM)</p>	<ul style="list-style-type: none"> • A single ISM slot provides flexibility to integrate intelligent service modules on an internal slot within the chassis • Each ISM slot offers high-data-throughput capability: Up to 4 Gbps aggregate toward the route processor. Up to 2 Gbps aggregate to other module slots over the MGF. • The ISM replaces the AIM slot; existing AIM modules are not supported in the ISM slot. • Power to ISM slots can be managed by extensions similar to the Cisco EnergyWise framework, so your organization can reduce energy consumption in your network infrastructure. Full EnergyWise support will be available in future software releases.
<p>Cisco High-Density Packet Voice Digital Signal Processor (DSP) Module (PVDM3) Slots on Motherboard</p>	<ul style="list-style-type: none"> • PVDM3 slots natively support PVDM3 modules, providing support for richer density for rich-media voice and video. • Each PVDM3 slot connects back to the system architecture through a 2 Gbps aggregate link through the MGF. • Investment protection for PVDM2 modules is supported through an adapter module. • Power to the PVDM slots can be managed by extensions similar to the Cisco EnergyWise framework, so your organization can reduce energy consumption in your network infrastructure. Full EnergyWise support will be available in future software releases.
<p>Compact Flash Slots</p>	<ul style="list-style-type: none"> • Two external Compact Flash slots are available on the Cisco 2900 Series Integrated Services Routers. Each slot

	can support high-speed storage densities upgradeable to 4 GB in density.
USB 2.0 Ports	<ul style="list-style-type: none"> Two high-speed USB 2.0 ports are supported. The USB ports enable secure token capabilities and storage.

CISCO 2900 INTEGRATED SERVICES ROUTER PRODUCT SPECIFICATIONS

Model	Cisco 2901	Cisco 2911	Cisco 2921	Cisco 2951
Services and Slot Density				
Embedded Hardware-Based Cryptography and Acceleration	Yes	Yes	Yes	Yes
Cisco Unified SRST Sessions	35	50	100	250
Cisco Unified CCME Sessions	35	50	100	150
Total Onboard WAN 10/100/1000 Ports	2	3	3	3
RJ-45-Based Ports	2	3	3	3
SFP-Based Ports (use of SFP port disables the corresponding RJ-45 port)	0	0	1	1
Service Module Slots	0	1	1	2
Double-Wide Service Module Slots (use of a double-wide slot will occupy all single-wide service module slots in a 2900)	0	0	1	1
EHWIC Slots	4	4	4	4
Double-Wide EHWIC Slots (use of a double-wide EHWIC slot will	2	2	2	2

consume two EHWIC slots)				
ISM Slots	1	1	1	1
Onboard DSP (PVDM) Slots	2	2	3	3
Memory DDR2 ECC DRAM - Default	512 MB	512 MB	512 MB	512 MB
Memory (DDR2 ECC DRAM) - Maximum	2 GB	2 GB	2 GB	2 GB
Compact Flash (External) - Default	slot 0: 256 MB slot 1: none	slot 0: 256 MB slot 1: none	slot 0: 256 MB slot 1: none	slot 0: 256 MB slot 1: none
Compact Flash (External) - Maximum	slot 0: 4 GB slot 1: 4 GB	slot 0: 4 GB slot 1: 4 GB	slot 0: 4 GB slot 1: 4 GB	slot 0: 4 GB slot 1: 4 GB
External USB 2.0 Flash Memory Slots (Type A)	2	2	2	2
USB Console Port (Type B) (up to 115.2 kbps)	1	1	1	1
Serial Console Port	1	1	1	1
Serial Auxiliary Port	1	1	1	1
Power-Supply Options	AC and PoE	AC, PoE, and DC	AC, PoE, and DC	AC, PoE, and DC
RPS Support (External)	No	Cisco RPS 2300	Cisco RPS 2300	Cisco RPS 2300
Power Specifications				
AC Input Voltage	100 to 240 VAC auto ranging	100 to 240 VAC auto ranging	100 to 240 VAC auto ranging	100 to 240 VAC auto ranging
AC Input Frequency	47 to 63 Hz	47 to 63 Hz	47 to 63 Hz	47 to 63 Hz
AC Input Current Range AC Power Supply (Maximum)	1.5 to 0.6A	2.2 to 1.0A	3.4 to 1.4A	3.4 to 1.4A
AC Input Surge Current	<50A	<50A	<50A	<50A

Typical Power (No Modules) (Watts)	40	50	60	70
Maximum Power with AC Power Supply (Watts)	150	210	320	340
Maximum Power with PoE Power Supply (Platform Only) (Watts)	175	250	370	405
Maximum Power with DC-PoE Power Supply (Platform Only) (Watts)	-	140	-	-
Maximum End-Point PoE Power Available from AC PoE Power Supply (Watts)	130	200	280	370
Maximum End-Point PoE Power Available from DC PoE Power Supply (Watts)	-	160	-	-
Maximum End-Point PoE Power Capacity with PoE Boost (Watts)	N/A	750	750	750
DC Input Voltage	N/A	24 to 60 Vdc, autoranging positive or negative	24 to 60 Vdc, autoranging positive or negative	24 to 60 Vdc, autoranging positive or negative
DC Input Current	N/A	(MAX) 8A (24V) 3.5A (60V)	(MAX) 12A (24V) 5A (60V)	(MAX) 12A (24V) 5A (60V)
Physical Specifications				
Dimensions (H x W x D)	1.75 x 17.25 x 17.3 in. (44.5 x 438.2 x 439.4 mm)	3.5 x 17.25 x 12 in. (88.9 x 438.2 x 304.8 mm)	3.5 x 17.25 x 18.5 in. (88.9 x 438.2 x 469.9 mm)	3.5 x 17.25 x 18.5 in. (88.9 x 438.2 x 469.9 mm)
Rack Height	1RU (rack unit)	2RU	2RU	2RU

Rack-Mount 19 in. (48.3 cm) EIA	Included	Included	Included	Included
Rack-Mount 23 in. (58.4 cm) EIA	Optional	Optional	Optional	Optional
Wall-Mount (refer to installation guide for approved orientation)	Yes	Yes	No	No
Weight with AC Power Supply (No Modules)	13.4 lb (6.1 kg)	18 lb (8.2 kg)	29 lb (13.2 kg)	29 lb (13.2 kg)
Weight with AC PoE Power Supply (No Modules)	14.3 lb (6.5 kg)	19 lb (8.6 kg)	30 lb (13.6 kg)	30 lb (13.6 kg)
Typical Weight Fully Configured	16 lb (7.3 kg)	21 lb (9.5 kg)	34 lb (15.5 kg)	34 lb (15.5 kg)
Airflow	Front to side	Side to side	Back and Side to Front	Back and Side to Front
Optional Airflow Kit	N/A	Front to back	N/A	N/A
Environmental Specifications				
Operating Conditions				
Temperature: 5,906 feet (1,800m) Maximum Altitude	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)
Temperature: 9,843 feet (3,000m) Maximum Altitude	32 to 77°F (0 to 25°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)
Temperature: 13,123 feet (4,000m) Maximum Altitude	N/A	32 to 86°F (0 to 30°C)	32 to 86°F (0 to 30°C)	32 to 86°F (0 to 30°C)
Temperature: Short-Term (per NEBS) 5906 feet (1,800m) Maximum Altitude	N/A	23°F to 122°F (-5 to 50°C)	N/A	23°F to 122°F (-5 to 50°C)
Altitude	10,000 ft (3,000m)	13,000 ft (4,000m)	10,000 ft (3,000m)	13,000 ft (4,000m)

Relative Humidity	10 to 85%	5 to 85%	10 to 85%	5 to 85%
Short-Term (per NEBS) Humidity	N/A	5% to 90%, but not to exceed 0.024 kg water/kg of dry air	N/A	N/A
Acoustic: Sound Pressure (Typical/Maximum)	41/53 dBA	51.8/62.9 dBA	54.4/67.4 dBA	54.4/67.4 dBA
Acoustic: Sound Power (Typical/Maximum)	49/61 dBA	58.5/70.3 dBA	62.6/74.5 dBA	62.6/74.5 dBA
Non-Operating Conditions				
Temperature	-40 to 158°F (-40 to 70°C)	-40 to 176°F (- 40 to 80°C)	-40 to 158°F (-40 to 70°C)	-40 to 158°F (-40 to 70°C)
Relative Humidity	5 to 95%	5 to 95%	5 to 95%	5 to 95%
Altitude	15,000 ft (4,570m)	15,000 ft (4,570m)	15,000 ft (4,570m)	15,000 ft (4,570m)
Regulatory Compliance				
Safety	UL 60950-1 CAN/CSA C22.2 No. 60950-1 EN 60950-1 AS/NZS 60950-1 IEC 60950-1	UL 60950-1 CAN/CSA C22.2 No. 60950-1 EN 60950-1 AS/NZS 60950-1 IEC 60950-1	UL 60950-1 CAN/CSA C22.2 No. 60950-1 EN 60950-1 AS/NZS 60950-1 IEC 60950-1	UL 60950-1 CAN/CSA C22.2 No. 60950-1 EN 60950-1 AS/NZS 60950-1 IEC 60950-1
EMC	47 CFR, Part 15 ICES-003 Class A EN55022 Class A CISPR22 Class A	47 CFR, Part 15 ICES-003 Class A EN55022 Class A CISPR22 Class A	47 CFR, Part 15 ICES-003 Class A EN55022 Class A CISPR22 Class A	47 CFR, Part 15 ICES-003 Class A EN55022 Class A CISPR22 Class A

	AS/NZS 3548 Class A VCCI V-3 CNS 13438 EN 300-386 EN 61000 (Immunity) EN 55024, CISPR 24 EN50082-1	AS/NZS 3548 Class A VCCI V-3 CNS 13438 EN 300-386 EN 61000 (Immunity) EN 55024, CISPR 24 EN50082-1	AS/NZS 3548 Class A VCCI V-3 CNS 13438 EN 300-386 EN 61000 (Immunity) EN 55024, CISPR 24 EN50082-1	AS/NZS 3548 Class A VCCI V-3 CNS 13438 EN 300-386 EN 61000 (Immunity) EN 55024, CISPR 24 EN50082-1
Telecom	TIA/EIA/IS-968 CS-03 ANSI T1.101 ITU-T G.823, G.824 IEEE 802.3 RTTE Directive	TIA/EIA/IS-968 CS-03 ANSI T1.101 ITU-T G.823, G.824 IEEE 802.3 RTTE Directive	TIA/EIA/IS-968 CS-03 ANSI T1.101 ITU-T G.823, G.824 IEEE 802.3 RTTE Directive	TIA/EIA/IS-968 CS-03 ANSI T1.101 ITU-T G.823, G.824 IEEE 802.3 RTTE Directive

CISCO 2900 SERIES BASIC ORDERING INFORMATION

Product Name	Product Description
CISCO2901/K9	Cisco 2901 with 2 onboard GE, 4 EHWIC slots, 2 DSP slots, 1 ISM slot, 256MB CF default, 512MB DRAM default, IP Base
CISCO2911/K9	Cisco 2911 with 3 onboard GE, 4 EHWIC slots, 2 DSP slots, 1 ISM slot, 256MB CF default, 512MB DRAM default, IP Base
CISCO2921/K9	Cisco 2921 with 3 onboard GE, 4 EHWIC slots, 3 DSP slots, 1 ISM slot, 256MB CF default, 512MB DRAM default, IP Base
CISCO2951/K9	Cisco 2951 with 3 onboard GE, 4 EHWIC slots, 3 DSP slots, 1 ISM slot, 256MB CF default, 512MB DRAM default, IP Base
CISCO2901-SEC/K9	Cisco 2901 Security Bundle w/SEC license PAK
CISCO2911-SEC/K9	Cisco 2911 Security Bundle w/SEC license PAK
CISCO2921-SEC/K9	Cisco 2921 Security Bundle w/SEC license PAK
CISCO2951-SEC/K9	Cisco 2951 Security Bundle w/SEC license PAK

CISCO2901-V/K9	Cisco 2901 Voice Bundle, PVDM3-16, UC License PAK
CISCO2911-V/K9	Cisco 2911 Voice Bundle, PVDM3-16, UC License PAK
CISCO2921-V/K9	Cisco 2921 Voice Bundle, PVDM3-32, UC License PAK
CISCO2951-V/K9	Cisco 2951 Voice Bundle, PVDM3-32, UC License PAK
C2901-VSEC/K9	Cisco 2901 Voice Sec. Bundle, PVDM3-16, UC and SEC License P
C2911-VSEC/K9	Cisco 2911 Voice Sec. Bundle, PVDM3-16, UC and SEC License P
C2921-VSEC/K9	Cisco 2921 Voice Sec. Bundle, PVDM3-32, UC and SEC License P
C2951-VSEC/K9	Cisco 2951 Voice Sec. Bundle, PVDM3-32, UC and SEC License P
C2901-CME-SRST/K9	2901 Voice Bundle w/ PVDM3-16,FL-CME-SRST-25, UC License PAK
C2911-CME-SRST/K9	2911 Voice Bundle w/PVDM3-16,FL-CME-SRST-25, UC License PAK
C2921-CME-SRST/K9	2921 Voice Bundle w/ PVDM3-32,FL-CME-SRST-25, UC License PAK
C2951-CME-SRST/K9	2951 Voice Bundle w/ PVDM3-32,FL-CME-SRST-25, UC License PAK
C2901-VSEC-SRE/K9	Cisco 2901 SRE Bundle, SRE 300, PVDM3-16, UC, SEC Lic. PAK
C2911-VSEC-SRE/K9	Cisco 2911 SRE Bundle, SRE 300, PVDM3-16, UC, SEC Lic. PAK
C2921-VSEC-SRE/K9	Cisco 2921 SRE Bundle, SRE 700, PVDM3-32, UC, SEC Lic. PAK
C2951-VSEC-SRE/K9	Cisco 2951 SRE Bundle, SRE 700, PVDM3-32, UC, SEC Lic. PAK
C2901-VSEC-CUBE/K9	C2901 VSEC CUBE Bundle, PVDM3-16, UC SEC Lic, FL-CUBEE-25
C2911-VSEC-CUBE/K9	C2911 VSEC CUBE Bundle, PVDM3-16, UC SEC Lic, FL-CUBEE-25
C2921-VSEC-CUBE/K9	C2921 VSEC CUBE Bundle, PVDM3-32, UC SEC Lic, FL-CUBEE-25
C2951-VSEC-CUBE/K9	C2951 VSEC CUBE Bundle, PVDM3-32, UC SEC Lic, FL-CUBEE-25
C2921-WAASX-SEC/K9	Router Bundle - C2921, WAASX F-License, Sec License, Max Mem
C2911-WAASX-SEC/K9	Router Bundle - C2911, WAASX F-License, Sec License, Max Mem
C2901-WAASX-SEC/K9	Router Bundle - C2901, WAASX F-License, Sec License, Max Mem
C2911-WAAS-SEC/K9	Cisco 2911, SRE 700, Sec PAK, WAAS Ent Small
C2921-WAAS-SEC/K9	Cisco 2921, SRE 700, Sec PAK, WAAS Ent Medium
C2951-WAAS-SEC/K9	Cisco 2951, SRE 900, Sec PAK, WAAS Ent Large
C2921-WAASX/K9	Router Bundle - C2921, WAASX Feature License, Max Mem
C2911-WAASX/K9	C2911-WAASX/K9 Cisco 2900 Series WAAS Express Bundle
C2901-WAASX/K9	Router Bundle - C2901, WAASX Feature License, Max Mem
C2951-S-SRE-WAE/K9	Cisco 2951, SRE 700 SM, NME WAE 502, WAAS Ent, IOS Sec PAK

CISCO2901-HSEC+/K9	VPN ISM module HSEC bundles for 2901 ISR platform
CISCO2911-HSEC+/K9	VPN ISM module HSEC bundles for 2911 ISR platform
CISCO2921-HSEC+/K9	VPN ISM module HSEC bundles for 2921 ISR platform
CISCO2951-HSEC+/K9	VPN ISM module HSEC bundles for 2951 ISR platform
CISCO2911-DC/K9	Cisco 2911 router w/3 GE,4 EHWIC,2 DSP,1 SM,256MB CF,512MB DRAM, IPB, DC-power supply
L-SL-29-DATA-K9=	Data License for Cisco 2901-2951
L-SL-29-UC-K9=	Unified Communications License for Cisco 2901-2951
L-SL-29-SEC-K9=	Security License for Cisco 2901-2951
MEM-2951-512MB=	512MB DRAM (1 DIMM) for Cisco 2951 ISR, Spare
MEM-2951-512U2.5GB	512MB to 2.5GB DRAM Upgrade (2GB+512MB) for Cisco 2951 ISR
MEM-2951-512U2GB	512MB to 2GB DRAM Upgrade (1 2GB DIMM) for Cisco 2951 ISR
MEM-2951-512U1.5GB	512MB to 1.5GB DRAM Upgrade (1GB+512MB) for Cisco 2951 ISR
MEM-2951-512U1GB	512MB to 1GB DRAM Upgrade (1 1GB DIMM) for Cisco 2951 ISR
MEM-2951-512U4GB	512MB to 4GB DRAM Upgrade (2 2GB DIMM) for Cisco 2951 ISR
MEM-2900-2GB=	2GB DRAM (1 DIMM) for Cisco 2901, 2911, 2921 ISR, Spare
MEM-2900-1GB=	1 GB DRAM (1 DIMM) for Cisco 2901, 2911, 2921 ISR, Spare
MEM-2900-512MB=	512MB DRAM (1 DIMM) for Cisco 2901, 2911, 2921 ISR, Spare
MEM-2900-512U1.5GB	512MB to 1.5GB DRAM Upgrade (1GB+512MB) for Cisco 2901-2921
MEM-2900-512U1GB	512MB to 1GB DRAM Upgrade (512MB+512MB) for Cisco 2901-2921
MEM-2900-512U2.5GB	512MB to 2.5GB DRAM Upgrade (2GB+512MB) for Cisco 2901-2921

ADDITIONAL INFORMATION

[Cisco ISR 4451-X vs. ISR 3900 vs. ISR 2900 vs. ISR 1900](#)

[Guide to Upgrade Your ISR G1 and ISR G2 Routers to ISR 4000](#)

WHERE TO BUY

Want to buy this series of products? please contact:

- Tel: +1-626-239-8066 (USA)/ +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com (Sales Inquiries)

Or visit: [Cisco ISR 2900 Series Routers](#)

About us

Router-switch.com, founded in 2002, is one of the biggest Global Network Hardware Supplier. We are a leading provider of network products with 14,500+ customers in over 200 countries. We provide original new and used network equipments (Cisco, Huawei, HPE, Dell, Hikvision, Juniper, EMC, etc.), including Routers, Switches, Servers, Storage, Telepresence and Videoconferencing, IP Phones, Firewalls, Wireless APs & Controllers, EHWIC/HWIC/VWIC Cards, SFPs, Memory & Flash, Hard Disk, Cables, and all kinds of network solutions related products.

SOURCES

https://www.cisco.com/c/en/us/products/collateral/routers/2900-series-integrated-services-routers-isr/data_sheet_c78_553896.html