

Comparison of hydrogen and battery electric trucks

Methodology and underlying assumptions

June 2020

Hydrogen vs battery electric trucks - Regional delivery

Trips up to 400 km represent 62% of EU truck activity

Parameters	Fuel cell electric truck		Battery electric truck	
	Today	2030	Today	2030
Total cost of ownership over first 5-year user period (based on France)	€ 437 k	€ 319 k	€ 353 k	€ 256 k
Vehicle purchase costs	€ 160 k	€ 115 k	€ 216 k	€ 122 k
Annual renewable fuel costs ¹	€ 39 k	€ 25 k	€ 21 k	€ 15 k
Cost parity with diesel without subsidies	Early 2040s		Mid 2020s	
Economies of scale with cars	Low		High	
Refuelling / recharging time (full)	3 - 8 minutes		8 hours (overnight) 60 minutes (opportunity)	
Net payload loss (weight) ²	None		None	

1: Renewable fuel costs are incl. taxes, levies and charges, transport and distribution costs for electricity and fuel; assuming renewable hydrogen cost for the end user of € 6.36/kg (2020) and € 5.40/kg (2030), and renewable electricity cost for the end user of €-cent 17.25/kWh (2020) and €-cent 15.26/kWh (2030).

2: Additional weight from the onboard battery pack (assumed energy density of 183 Wh/kg in 2020 and 318 Wh/kg in 2030) of 3.9 t (1.8 t in 2030) is compensated for by the additional ZEV weight allowance (2 t) under the EU Weights & Dimensions Directive and net savings from replacing a conventional with an electric drivetrain (2.4 t).




Hydrogen vs battery electric trucks - Long distance

Trips up to 400 km represent 62% of EU truck activity

Parameters	Fuel cell electric truck	Battery electric truck
Total cost of ownership over first 5-year user period (based on France)	€ 459 k	€ 393 k
Vehicle purchase costs	€ 139 k	€ 167 k
Annual renewable fuel costs ¹	€ 38 k	€ 22 k
Cost parity with diesel without subsidies	Mid 2040s	Early 2030s
Economies of scale with cars	Low	High
Max range without refuelling / recharging	1200 km	800 km
Refuelling / recharging time (full)	10-20 minutes	8 hours (overnight) 60 minutes (opportunity)
Net payload loss (weight) ²	None	None

1: Renewable fuel costs are incl. taxes, levies and charges, transport and distribution costs for electricity and fuel; assuming renewable hydrogen cost for the end user of € 5.40/kg (2030) and renewable electricity cost for the end user of €-cent 15.26/kWh (2030).

2: Additional weight from the onboard battery pack (assumed energy density of 318 Wh/kg in 2030) of 4.2 t is compensated for by the additional ZEV weight allowance (2 t) under the EU Weights & Dimensions Directive and net savings from replacing a conventional with an electric drivetrain (2.4 t).



1. Vehicle characteristics

The sample vehicle for both the regional delivery and long-haul duty cycle is a typical tractor-trailer under type-approval in the European Union. It has a gross combined vehicle weight (GCVW) of 40 tonnes, a vehicle curb weight of 14 tonnes and a resulting maximum payload of 26 tonnes. Both the fuel cell electric (FCEV) as well as the battery electric vehicle (BEV) have an electric drivetrain with a combined rated power output of 350 kW.

The FCEV features a fuel cell stack, compressed hydrogen storage tank and a smaller onboard battery pack to buffer for engine peak loads. The BEV has a large onboard battery pack whose usable capacity is capped at 80% to ensure long-term durability. The main criterion for determining the onboard energy storage for the FCEV and BEV is that the respective vehicle reaches the required operational range without the need for refuelling or recharging in between.

The energy consumption values are based on Earl et al.¹ They take into account vehicle efficiency improvements due to reduced rolling resistance and aerodynamic drag on a 40-tonnes tractor-trailer cruising at EU-specific highway speeds of 80 km/h (50 mph) and represent a reasonable mean value between industry announcements and various literature sources. Moultak et al. and Sharpe estimate an approximate energy demand at the wheels of 1.6 kWh/km in 2020 and 1.45 kWh/km in 2030 at a U.S.-specific highway speed of 65 mph (105 km/h).^{2, 3} Tesla has announced an energy consumption of its Semi truck of ‘less than 1.24 kWh/km’ (also at 65 mph).⁴ The energy demand at the wheels is identical for both the FCEV and BEV as they share the same vehicle characteristics and drivetrain components. The efficiency differences between them is solely due to the additional conversion loss when converting the hydrogen in the fuel cell to electricity (54% conversion efficiency rate in 2020 and 56% in 2030).⁵

Parameters	Regional delivery				Long-haul	
	FCEV		BEV		FCEV	BEV
	2020	2030	2020	2030	2030	
Annual mileage	80,000 km				120,000 km	
Energy consumption at the wheels in kWh/kmⁱ	2.53	1.95	1.44	1.15	1.95	1.15
Max. range without refuelling / recharging	400 km				1,200 km	800 km
H₂ fuel tank size (compressed at 700 bar)	30 kg H ₂	23 kg H ₂	-		70 kg H ₂	-
Battery size (usable capacity capped at 80%)	70 kWh		720 kWh	575 kWh	70 kWh	1,150 kWh

ⁱ Energy consumption at the wheels determines the onboard energy storage capacity which is required to reach the max. range without refuelling / recharging. To calculate the electricity consumption (i.e. fuel costs) of the BEV, additional charging losses need to be taken into account. The respective energy consumption values measured from the grid are 1.52 (2020) and 1.21 (2030).

2. Duty cycles

The **regional delivery** duty cycle is characterised by single trip lengths of up to 400 km and the vehicle's return to the depot overnight which is located outside of urban areas. 62% of EU truck activity measured (in tonne-kilometres) comprises trips of less than 400 km.⁶ The average annual mileage is set at 80,000 km based on the European Commission.⁷

The **long-haul** duty cycle involves multi-day intercity travel with maximum daily trip lengths of up to 800 km if the vehicle is equipped with one driver. The trip length is aligned with EU rules on driving times and rest periods which foresee maximum daily driving periods of 9 hours (which can go up to 10 hours).⁸ At an 80 km/h average vehicle speed, this amounts to 800 km per day. 78% of EU truck activity comprises trips of less than 800 km. The average annual mileage is set at 120,000 km also based on the European Commission.⁹

3. Total cost of ownership

The total cost of ownership (TCO) comprises all vehicle costs, fuel costs, infrastructure costs as well as all taxes, levies and road charges as they would occur if the vehicle was owned and operated in France. The taxation schemes are somewhat different among the EU Member States and France represents a good proxy among them in terms of tax and excise duty rates. In a broader sense, the TCO describes the total expenses for a haulier. The TCO comprises nominal prices for a first vehicle use period of 5 years (including the vehicle's residual value and excluding VAT and financing costs).

3.1. Vehicle costs

The vehicle costs are based on Kühnel et al. (except for battery costs) which undertook a bottom-up cost estimation for the different vehicle components and included a mark-up factor of 1.4 to determine the net retail price after manufacturing and distribution costs.¹⁰ The cost assumptions are based on the German cost level. Since the price level and purchase power in the two countries are broadly similar, the costs should be comparable.

The total net retail price (excl. VAT and financing costs) include the applicable costs due to the vehicle glider, electric motor, inverter, gearbox, fuel cell stack, hydrogen storage tank and battery pack. Maintenance and repair costs refer to costs due to general servicing over the first use period. The taxes on vehicle purchase and operation include the French-specific one-time registration tax and additional parafiscal charge as well as the annual special tax on certain motor vehicles.¹¹

Vehicle costs		Regional delivery		Long-haul
		2020	2030	2030
BEV	Retail price	€ 215,795	€ 122,432	€ 167,274
	Maintenance & repairs	€ 8,400 p.a.	€ 8,400 p.a.	€ 12,600 p.a.
	Vehicle taxes	€ 573 p.a.	€ 573 p.a.	€ 573 p.a.
FCEV	Retail price	€ 159,956	€ 114,651	€ 138,958
	Maintenance & repairs	€ 15,400 p.a.	€ 10,960 p.a.	€ 16,440 p.a.
	Vehicle taxes	€ 573 p.a.	€ 573 p.a.	€ 573 p.a.

The battery pack costs are based on BloombergNEF and include the same mark-up factor of 1.4 as for the vehicle costs to determine the pack's retail price after manufacturing and distribution costs.¹² The battery pack density values are the low assumptions on the potential for future technological improvement taken by Ricardo Energy & Environment.¹³

Battery pack costs	2020	2030
Net costs per kWh	€ 135	€ 56
Retail costs per kWh	€ 188	€ 78
Energy density (battery pack level)	183 Wh/kg	318 Wh/kg

3.2. Renewable electricity and fuel costs

It should be noted that both the FCEV and BEV are fuelled with renewable hydrogen and renewable electricity respectively. This has been a deliberate choice in order to provide for a level playing field and compare two technologies which can ensure zero well-to-wheel GHG emissions (though not lifecycle

GHG emissions). Depending on the electricity or fuel origin and production method, the TCO and the moment of cost parity with diesel can vary significantly (see also section 3.5 below).

The Agora PtG/PtL calculator was used to calculate the levelised cost of electricity (LCOE) and the levelised cost of hydrogen (LCOH) produced from additional renewable electricity capacity.¹⁴ The electricity generation and fuel production facilities are either based in the North Sea or in North Africa.

The calculated costs are based on the reference scenario of the Agora PtG/PtL calculator. The chosen weighted average cost of capital (WACC) is 6%. The renewable electricity for the BEV is produced from offshore wind in the North Sea. The load factor was set at 4,000 full-load hours per year. Resulting in a final renewable electricity price for the end user of €-cent 17.25/kWh (see table below) in 2020, this is higher than the current average grid electricity price for non-household consumers of €-cent 12.71/kWh in France.^{ii, 15}

The renewable hydrogen is produced from solar PV in North Africa. The MENA region is considered to provide for one of the most cost-effective means to produce hydrogen from renewable electricity through electrolysis. The load factor was set at 2,344 full-load hours. The same is the case for the high-temperature SOEC electrolysis (81% conversion efficiency rate in 2020 and 84% in 2030). Resulting in a final renewable hydrogen for the end user of € 6.36/kg in 2020 (see table below), this is considerably higher than today's fossil hydrogen final cost without CCUS (€ 1.83/kg) and with CCUS (€ 1.94/kg).^{iii, 16}

Grid connection fees are included in the LCOE for renewable electricity. In addition, it includes the *Tarif d'utilisation du réseau public d'électricité* (TURPE) to account for electricity network distribution costs in France. The renewable hydrogen takes into account costs due to liquefaction, transport via tanker from North Africa to France (Marseille) and domestic distribution via high-pressure tube trailer until the refuelling station. For the renewable electricity, the *Contribution tarifaire d'acheminement* (CTA), *Contribution au Service Public d'Electricité* (CSPE) and *Taxes sur la Consommation Finale d'Electricité* (TCFE) is added. The current tax exemption for hydrogen used as transport propellant in France is maintained.

ⁱⁱ The electricity price for non-household consumers refers to an annual consumption between 20 and 500 MWh and including taxes except for VAT and other recoverable levies as of the second half of 2019.

ⁱⁱⁱ Based on fossil hydrogen production costs using natural gas in Europe with and without CCUS and adding domestic distribution costs.

Electricity produced from offshore wind in the North Sea	€-cent/kWh _{el}		Hydrogen produced from solar PV in North Africa	€/kg _{H2}	
	2020	2030		2020	2030
LCOE	9.22	7.23	LCOH	3.39	2.73
-	-	-	Liquefaction	2.03	1.73
Transport to FR	<i>Grid connection fees included in LCOE</i>		Transport to FR	0.14	0.14
Distribution in FR	4.40	4.40	Distribution in FR	0.80	0.80
Total	13.62	11.63	Total	6.36	5.40
Total incl. taxes & levies	17.25	15.26	Total incl. taxes & levies	6.36	5.40

3.3. Infrastructure configurations and costs

The estimated infrastructure costs are also based on Kühnel et al.¹⁷ They take into account the size and power of the refuelling and charging stations, the utilisation rate, service life, capital expenditure (CAPEX), operational expenses (OPEX) and the number of supplied vehicles per refuelling / recharging station. It should be noted that refuelling and recharging cost estimations are to an extent speculative as the technologies are not yet (fully) commercialised or scaled up on the market.

Refuelling infrastructure for FCEVs		
Parameters	2020	2030
Specifications of a	Total refuelling capacity	5,468 kg _{H2}

hydrogen refuelling station	Mean refuelling quantity per vehicle (disregarding vehicle duty cycle)	33 kg _{H2}	
	Dispenser flow rate	3.6 - 7.2 kg _{H2} /min	
	Supplied vehicles per day	110	
	Service life	15 years	
	Capital expenditure	€ 7.0 million	€ 5.6 million
	Operational expenses per year	€ 69,652 p.a.	€ 56,128 p.a.
Total infrastructure costs per vehicle per year (full utilisation)		€ 4,855 p.a.	€ 3,912 p.a.

Charging infrastructure for BEVs			
Parameters		2020	2030
Specifications of a mega charger for long-haul (1.2 MW)	Charging time	60 minutes for 800 km range	
	Supplied vehicles per day	20	
	Service life	15 years	
	Capital expenditure	-	€ 364,000
	Operational expenses per year	-	€ 3,640 p.a.
Specifications of a rapid charger for regional delivery (600 kW)	Charging time	60 minutes for 400 km range	
	Supplied vehicles per day	20	

	Service life	15 years	
	Capital expenditure	€ 222,857	€ 193,143
	Operational expenses per year	€ 2,229 p.a.	€ 1,931 p.a.
Specifications of an overnight charger for long-haul (150 kW)	Charging time	8 hours for 800 km range	
	Supplied vehicles per night	0.91	
	Service life	15 years	
	Capital expenditure	-	€ 65,000
	Operational expenses per year	-	€ 650 p.a.
Specifications of an overnight charger for regional delivery (75 kW)	Charging time	8 hours for 400 km range	
	Supplied vehicles per day	0.91	
	Service life	15 years	
	Capital expenditure	€ 42,000	€ 35,000
	Operational expenses per year	€ 420 p.a.	€ 350 p.a.
Total infrastructure costs per vehicle per year for long-haul (full utilisation)		-	€ 5,691 p.a.
Total infrastructure costs per vehicle per year for regional delivery (full utilisation)		€ 3,670 p.a.	€ 3,063 p.a.

3.4. Road charges

In line with 2018 road charge estimations by the Comité National Routier, an average road toll cost of €-cent 10.64 per vehicle kilometre driven was assumed for the long-haul duty cycle. For the regional delivery cycle, a lower average road toll cost of €-cent 7.70 per vehicle kilometre driven was used.¹⁸ No reduced charges or toll exemptions were applied to the FCEV or BEV compared to diesel vehicles.

Annual road charges	Regional delivery		Long-haul
	2020	2030	2030
BEV	€ 6,160		€ 12,768
FCEV	€ 6,160		€ 12,768

3.5. Fuel cost sensitivity

The estimated cost parity with diesel takes into account the above TCO cost components and compares them to the equivalent vehicle with an internal combustion engine running on diesel in France. It should be noted that this comparison excludes any potential subsidies or policy incentives for the FCEV or BEV except for what is already provided for today (excise duty exemption for hydrogen). Today's level of taxes, levies and charges in France remain the same and are kept constant until 2030.

The calculated cost parity is subject to greater or lesser variability, depending on the assumed costs, their projections for the future and whether any potential subsidies are included. For example, carrying out a cost sensitivity analysis by using fossil hydrogen with or without CCUS instead of renewable hydrogen to fuel the vehicle would significantly improve the TCO and bring forward cost parity with fossil diesel of both the regional delivery and long-haul FCEV to the early 2020s.¹⁹ Potential reductions on road charges for ZEVs, as they are currently being discussed on EU-level or already implemented at national level, would also bring forward the date when FCEVs and BEVs will become cheaper to own and operate than diesel trucks.

4. Refuelling and recharging times

The refuelling and recharging times are based on the onboard storage configuration and the respective refuelling capacity or recharging power output.

Recharging times are aligned with EU rules on driving times and rest periods. They foresee maximum daily driving periods of 9 hours (10 hours in exceptional cases) and minimum resting periods of (at least) 9 hours.²⁰ At an 80 km/h average vehicle speed, this amounts to a maximum of 800 km per day. In addition, mandatory breaks of at least 30 minutes every four and a half hours are legally required. Based on the above, one driver can therefore perform a single distance of not more than 360 km between mandatory breaks. The high-power mega charger (1.2 MW) can charge a range of 400 km for the long-haul BEV in around 30 minutes. Likewise, the high-power rapid charger (600 kW) can charge a range of 200 km for the regional delivery BEV in around 30 minutes. The overnight chargers (150 kW and 75 kW) can fully charge the onboard battery of the regional and long-haul BEV in around 8 hours.

The range of the hydrogen dispenser flow rate is estimated to be between 3.6 and 7.2 kg_{H2} per minute which ensures refuelling times of no more than 20 minutes if the onboard tank of the FCEV is completely empty.²¹

5. Payload losses

It is often claimed that BEVs need to account for reduced payload capacity due to the significant weight of the onboard battery pack. Depending on the battery pack's gravimetric energy density and capacity, this can indeed be the case, particularly with respect to today's battery technology.

However, the additional weight due to the onboard battery pack (assumed energy density of 183 Wh/kg in 2020 and 318 Wh/kg in 2030) is compensated for by the additional ZEV weight allowance (2 t) under the EU Weights & Dimensions Directive and net savings from replacing a conventional with an electric drivetrain (2.4 t). The illustrative calculation below outlines this for the long-haul BEV in 2030.

	Parameter	Formula	Value	Source
A	Energy consumption at the wheels in 2030		1.15 kWh/km	Earl et al. (2018)
B	Nominal range		800 km	Kühnel et al. (2018)

C	Usable battery capacity		80%	Tesla (no date)
D	Required battery pack size in 2030	A x B / C	1,150 kWh	-
E	Battery pack energy density in 2030		0.318 kWh/kg	Ricardo Energy & Environment (2019)
F	Battery pack weight	D / E	3,616 kg	-
G	Weight of electric motor, inverter and gearbox		600 kg	Hall et al. (2019) ²²
H	Total weight of battery and electric engine	F + G	4,216 kg	-
I	Weight of conventional drivetrain and fluids in diesel tank		3,000 kg	Sharpe (2019)
J	Net additional weight of battery electric tractor-trailer	H - I	1,216 kg	-
K	Max. additional ZEV weight allowance under the EU Weights & Dimensions Directive		2,000 kg	European Union (2019) ²³
L	Net payload loss of battery electric tractor-trailer type-approved in the EU	J - K	- 784 kg	-

Illustration based on Sharpe (2019)

Further information

Fedor Unterlohner
 Freight & Investment Officer
 Transport & Environment
fedor.unterlohner@transportenvironment.org
 Mobile: +32 (0)485 63 94 92

References

- ¹ Earl et al. (2018). Analysis of long haul battery electric trucks in the EU. Marketplace and technology, economic, environmental, and policy perspectives. Amended paper originally presented at the 8th Commercial Vehicle Workshop in Graz, 17-18 May 2018. Retrieved from https://www.transportenvironment.org/sites/te/files/publications/20180725_T%26E_Battery_Electric_Trucks_EU_FINAL.pdf, page 7.
- ² Moultaq et al. (2017). Transitioning to zero-emission heavy-duty freight vehicles. Retrieved from https://theicct.org/sites/default/files/publications/Zero-emission-freight-trucks_ICCT-whitepaper_26092017_vF.pdf
- ³ Sharpe (2018). Zero-emission tractor-trailers in Canada. Retrieved from <https://theicct.org/sites/default/files/publications/ZETractorTrailers%20Working%20Paper042019.pdf>, page 3-4.
- ⁴ Tesla (no date). Tesla Semi. Retrieved from <https://www.tesla.com/semi>
- ⁵ National Research Council (2013). Transitions to Alternative Vehicles and Fuels, The National Academies Press, Washington, DC/US, page 33. Retrieved from <https://www.nap.edu/catalog/18264/transitions-to-alternative-vehicles-andfuels>, page 50.
- ⁶ Transport & Environment (forthcoming). T&E in-house analysis from an update of the ETISPLUS European project database.
- ⁷ European Commission (2018). Annexes to the Proposal for a Regulation of the European Parliament and of the Council setting CO2 emission performance standards for new heavy-duty vehicles. Retrieved from https://eur-lex.europa.eu/resource.html?uri=cellar:f38df734-59da-11e8-ab41-01aa75ed71a1.0001.02/DOC_2&format=PDF, page 6.
- ⁸ European Union (2019). Regulation (EU) 561/2006 of the European Parliament and of the Council. Retrieved from https://eur-lex.europa.eu/resource.html?uri=cellar:5cf5ebde-d494-40eb-86a7-2131294ccbd9.0005.02/DOC_1&format=PDF
- ⁹ European Commission (2018).
- ¹⁰ Kühnel et al. (2018). Oberleitungs-Lkw im Kontext weiterer Antriebs- und Energieversorgungsoptionen für den Straßengüterfernverkehr. Ein Technologie- und Wirtschaftsvergleich. Retrieved from <https://www.oeko.de/fileadmin/oekodoc/StratON-O-Lkw-Technologievergleich-2018.pdf>
- ¹¹ ACEA (2019). ACEA tax guide 2019 edition. Retrieved from https://www.acea.be/uploads/news_documents/ACEA_Tax_Guide_2019.pdf, page 86-97.
- ¹² BloombergNEF (2019). Battery pack prices fall as market ramps up with market average at \$ 156/kWh in 2019. Retrieved from <https://about.bnef.com/blog/battery-pack-prices-fall-as-market-ramps-up-with-market-average-at-156-kwh-in-2019/>
- ¹³ Ricardo Energy & Environment (2019). Circular economy perspectives for the management of batteries used in electric vehicles. Retrieved from https://publications.jrc.ec.europa.eu/repository/bitstream/JRC117790/jrc117790_jrc_circular_econ_for_e_v_batteries_ricardo2019_final_report_pubsy_online.pdf, page 248.
- ¹⁴ Agora Energiewende (2018). PtG/PtL calculator. Retrieved from <https://www.agora-energiewende.de/en/publications/ptgptl-calculator/>

-
- ¹⁵ Eurostat (2017). 'Electricity prices for non-household consumers - bi-annual data (from 2007 onwards)'. Retrieved from <https://ec.europa.eu/eurostat/web/energy/data/database>.
- ¹⁶ International Energy Agency (2019). The Future of Hydrogen. Seizing today's opportunities. Retrieved from <https://www.iea.org/reports/the-future-of-hydrogen>; 2018 currency exchange rate is taken from European Central Bank (2018). Euro reference exchange rate: US dollar (USD). Retrieved from https://www.ecb.europa.eu/stats/policy_and_exchange_rates/euro_reference_exchange_rates/html/euro_fxref-graph-usd.en.html
- ¹⁷ Kühnel et al. (2018).
- ¹⁸ Comité National Routier (2019). Enquête CNR longue Distance. Retrieved from <http://www.cnr.fr/fr/Publications-CNR/Enquete-CNR-longue-Distance-2018>, page 11.
- ¹⁹ International Energy Agency (2019).
- ²⁰ European Union (2006). Regulation (EU) 561/2006 of the European Parliament and of the Council. Retrieved from https://eur-lex.europa.eu/resource.html?uri=cellar:5cf5ebde-d494-40eb-86a7-2131294ccbd9.0005.02/DOC_1&format=PDF
- ²¹ U.S. Department of Energy (2018). Hydrogen Refueling Analysis of Fuel Cell Heavy-Duty Vehicles Fleet. Retrieved from <https://www.energy.gov/sites/prod/files/2018/08/f54/fcto-truck-workshop-2018-9-elgowainy.pdf>, page 7.
- ²² Hall et al. (2019). Estimating the infrastructure needs and costs for the launch of zero-emission trucks. Retrieved from https://theicct.org/sites/default/files/publications/ICCT_EV_HDVs_Infrastructure_20190809.pdf, page 19.
- ²³ European Union (2019). Regulation (EU) 2019/1242 of the European Parliament and of the Council. Retrieved from <https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32019R1242&from=EN>