



WCAG 2.1 Level AA Success Criteria

COMPLIANCE AUDIT

For sliquid.com | Verdict: **Compliant!**

accessiBe is the web accessibility **market leader**, powering the accessibility of **tens-of-thousands** of websites, from **small businesses** to industry-leading **enterprises**.

This audit evaluates the adherence level of **sliquid.com** as of Thu Sep 15 2022, to the "Web Content Accessibility Guidelines" (WCAG) 2.1 level AA success criteria.

Below you'll find the results for dozens of tests that focus mainly on 3 categories: **screen-reader** adjustments (for blind users), **keyboard navigation** adjustments (for the motor impaired) and **UI, design, and readability** adjustments (for the vision impaired).

#	Requirement	Relevant	Successes	Failures	Score
1	Elements that behave as buttons but are built using other tags such as span, div, a or others, should include a "role" attribute that equals to "button".	Yes	16	0	100%

Code snapshots of some successful elements

```
<button type="button" data-role="none" class="slick-prev slick-arrow acsb-bg-image " aria-label="Previous" role="button" style="display: inline-block;" >Previous</button>
```

```
<button type="button" data-role="none" class="slick-next slick-arrow acsb-bg-image " aria-label="Next" role="button" style="display: inline-block;" >Next</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-="true" " aria-label=" Next carousel slide 1" aria-hidden="false" >Next carousel slide</span>1</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-="true" " aria-label=" Next carousel slide 2" aria-hidden="false" >Next carousel slide</span>2</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-="true" " aria-label=" Next carousel slide 3" aria-hidden="false" >Next carousel slide</span>3</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-="true" " aria-label=" Next carousel slide 4" aria-hidden="false" >Next carousel slide</span>4</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-="true" " aria-label=" Next carousel slide 5" aria-hidden="false" >Next carousel slide</span>5</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-="true" " aria-label=" Next carousel slide 6" aria-hidden="false" >Next carousel slide</span>6</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-
carousel-paging="true"><span data-="true" " aria-label=" Next carousel sl
ide 7" aria-hidden="false" >Next carousel slide</span>7</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-
carousel-paging="true"><span data-="true" " aria-label=" Next carousel sl
ide 8" aria-hidden="false" >Next carousel slide</span>8</button>
```

- 2 Buttons should include text explaining their functionality, and if icons are used as buttons, a screen-reader only text or an "aria-label" attribute should be used for that description.

Yes

16

0

100%

Code snapshots of some successful elements

```
<button type="button" data-role="none" class="slick-prev slick-arrow acsb
-bg-image " aria-label="Previous" role="button" style="display: inline-bloc
k;" >Previous</button>
```

```
<button type="button" data-role="none" class="slick-next slick-arrow acsb
-bg-image " aria-label="Next" role="button" style="display: inline-bloc
k;" >Next</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-
carousel-paging="true"><span data-="true" " aria-label=" Next carousel sl
ide 1" aria-hidden="false" >Next carousel slide</span>1</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-
carousel-paging="true"><span data-="true" " aria-label=" Next carousel sl
ide 2" aria-hidden="false" >Next carousel slide</span>2</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-
carousel-paging="true"><span data-="true" " aria-label=" Next carousel sl
ide 3" aria-hidden="false" >Next carousel slide</span>3</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-
carousel-paging="true"><span data-="true" " aria-label=" Next carousel sl
ide 4" aria-hidden="false" >Next carousel slide</span>4</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 5" aria-hidden="false" >Next carousel slide</span>5</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 6" aria-hidden="false" >Next carousel slide</span>6</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 7" aria-hidden="false" >Next carousel slide</span>7</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 8" aria-hidden="false" >Next carousel slide</span>8</button>
```

- 3 [Links should include text that is setting expectations to what page they are leading to. If empty links are used as layout wrapping elements, a screen-reader only text or an "aria-label" attribute should be used for that description.](#)

Yes

36

0

100%

Code snapshots of some successful elements

```
<a class="skip-link screen-reader-text " href="#content" aria-hidden="false" data-=""true" ">Skip to content</a>
```

```
<a href="https://sliquid.com/" class="custom-logo-link" rel="home" aria-current="page" data-acsb-scrape-url="https://sliquid.com/"><span class="ubermen
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo
ut-text_only" href="https://sliquid.com/sliquid-news/" data-acsb-menu="a"
data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals
e"><span class="ubermenu-tar...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo
ut-text_only" href="https://sliquid.com/reviews/" data-acsb-menu="a" data
-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="false"><s
pan class="ubermenu-target-t...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo
ut-text_only" href="https://sliquid.com/sliquid-faq/" data-acsb-menu="a"
data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals
e"><span class="ubermenu-targ...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo
ut-text_only" title="The Sliquid Story" href="https://sliquid.com/about-s
liquid/" data-acsb-menu="a" data-acsb-menu-root-link="true" aria-haspopup
="true" aria-expanded="false..."
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo
ut-text_only" href="https://sliquid.com/contact-us/" data-acsb-menu="a" d
ata-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals
e"><span class="ubermenu-targe...
```

```
<a class="ubermenu-target ubermenu-target-with-icon ubermenu-item-layout-
default ubermenu-item-layout-icon_left ubermenu-item-notext" href="/my-ac
count/" ><span data-="true" " aria-label=" account " aria-hidden="false"
>account</span><i class="ube...
```

4	Links that open in a new tab or a new window should either have an "aria-label" attribute or a screen-reader only element explaining to screen-readers that this opens in a new tab.	No	0	0	-
---	--	----	---	---	---

5	An H1 title provides information to blind-users using screen-readers of what the main topic of the page is and each page should have exactly one H1 title.	Yes	Pass	-	100%
---	--	-----	------	---	------

```
<h1 class="has-text-align-center has-text-color has-large-font-size abueg z5rb85" id="h-a-collection-of-award-winning-spa-products" style="color:#1e3147" >A COLLECTION OF AWARD-WINNING SPA PRODUCTS</h1>
```

6	HTML title elements (H1-6) should have texts. If images or links are used, they should include an alternative or screen-reader only text.	Yes	12	0	100%
7	Elements that visually appear as titles but are coded with a non-heading HTML Tag should include a "role" attribute that equals to "heading" or have their tags fixed.	No	0	0	-
8	Title levels should not be skipped and should be built with consistent hierarchy. For example: you cannot have "h4" titles and "h2" titles without having "h3" titles.	No	0	0	-
9	Interactive elements such as links, buttons and form fields should all be navigable using the keyboard by either using a focusable element (a, button, input, etc.) or including the "tabindex" attribute that equals to "0".	Yes	Pass	-	100%
10	Interactive elements that can be navigated using the keyboard should be surrounded by a visual outline whenever they are focused.	Yes	Pass	-	100%
11	Active popups should include an "aria-modal" attribute that equals to "true", and a "role" attribute that equals to "dialog", so screen-reader users know how to navigate within it.	No	0	0	-
12	Every page should include hidden links that	Yes	Pass	-	100%

"skip" certain blocks directly to main

landmarks such as main content, menu or footer.

13	Elements that are hidden using CSS manipulations (opacity, height, text-indent, off-canvas, etc.) should be wrapped inside an element with an "aria-hidden" attribute that equals to "false", or include it directly, and have it dynamically changed to "true" when they become visible.	No	0	0	-
14	Elements that are hidden using CSS manipulations (opacity, height, text-indent, off-canvas, etc.) should include a "tabindex" attribute that is below 0, and have it dynamically changed to 0 when they become visible.	No	0	0	-
15	Menus should either be built using the HTML5 "nav" element or include a "role" attribute that equals to "menu" or "navigation" to indicate a navigation landmark for screen-readers.	Yes	3	0	100%

Code snapshots of some successful elements

```
<nav id="ubermenu-main-49-menu-1-2" class="ubermenu ubermenu-main ubermen  
u-menu-49 ubermenu-loc-menu-1 ubermenu-responsive ubermenu-responsive-def  
ault ubermenu-mobile-modal ubermenu-responsive-collapse ubermenu-horizont  
al ubermenu-transition-shift ub...
```

```
<ul id="menu-customer-service-menu" class="menu" data-acsb-menu="ul" ><li  
id="menu-item-270107" class="menu-item menu-item-type-post_type menu-item  
-object-page menu-item-270107" data-acsb-menu="li" data-acsb-menu-root="t  
rue"><a title="navigation" hre...
```

```
<ul id="menu-discover-menu" class="menu" data-acsb-menu="ul" ><li id="men  
u-item-270113" class="menu-item menu-item-type-post_type menu-item-object  
-page menu-item-270113" data-acsb-menu="li" data-acsb-menu-root="true"><a  
title="navigation" href="https...
```

16 Menu items that have a dropdown menu include an "aria-haspopup" attribute that equals to "true".

Yes

7

0

100%

Code snapshots of some successful elements

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/sliquid-products/" data-acsb-menu  
="a" data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded  
="false" data-acsb-tooltip="Us...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/sliquid-retailers/" data-acsb-men  
u="a" data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded  
="false"><span class="ubermen...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/sliquid-news/" data-acsb-menu="a"  
data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals  
e"><span class="ubermenu-tar...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/reviews/" data-acsb-menu="a" data  
-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="false"><s  
pan class="ubermenu-target-t...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/sliquid-faq/" data-acsb-menu="a"  
data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals  
e"><span class="ubermenu-targ...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" title="The Sliquid Story" href="https://sliquid.com/about-s  
liquid/" data-acsb-menu="a" data-acsb-menu-root-link="true" aria-haspopup  
="true" aria-expanded="false...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/contact-us/" data-acsb-menu="a" d  
ata-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals  
e"><span class="ubermenu-targe...
```

17 Menu items that have a dropdown menu

Yes

7

0

100%

back when opening or closing the dropdown.

Code snapshots of some successful elements

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/sliquid-products/" data-acsb-menu  
="a" data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded  
="false" data-acsb-tooltip="Us...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/sliquid-retailers/" data-acsb-men  
u="a" data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded  
="false"><span class="ubermen...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/sliquid-news/" data-acsb-menu="a"  
data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals  
e"><span class="ubermenu-tar...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/reviews/" data-acsb-menu="a" data  
-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="false"><s  
pan class="ubermenu-target-t...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/sliquid-faq/" data-acsb-menu="a"  
data-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals  
e"><span class="ubermenu-targ...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" title="The Sliquid Story" href="https://sliquid.com/about-s  
liquid/" data-acsb-menu="a" data-acsb-menu-root-link="true" aria-haspopup  
="true" aria-expanded="false...
```

```
<a class="ubermenu-target ubermenu-item-layout-default ubermenu-item-layo  
ut-text_only" href="https://sliquid.com/contact-us/" data-acsb-menu="a" d  
ata-acsb-menu-root-link="true" aria-haspopup="true" aria-expanded="fals  
e"><span class="ubermenu-targe...
```

Code snapshots of some successful elements

```
  
</i>
```

```
<i class="ubermenu-sub-indicator fas fa-angle-down" aria-hidden="true" da  
ta-acsb-force-hidden="true" ></i>
```

```
<span class="ubermenu-sub-indicator-close" aria-hidden="true" data-acsb-f  
orce-hidden="true" ><i class="fas fa-times" aria-hidden="true" data-acsb-  
force-hidden="true" ></i></span>
```

```
<i class="fas fa-times" aria-hidden="true" data-acsb-force-hidden="true"  
></i>
```

```
<i class="ubermenu-icon fas fa-user " aria-hidden="true" data-acsb-force-hidden="true" ></i>
```

```
<i class="ubermenu-icon fas fa-user" aria-hidden="true" data-acsb-force-hidden="true" ></i>
```

```
<i class="fab fa-instagram " aria-hidden="true" data-acsb-force-hidden="true" ></i>
```

```
<i class="fab fa-twitter " aria-hidden="true" data-acsb-force-hidden="true" ></i>
```

```
<i class="fab fa-facebook-f " aria-hidden="true" data-acsb-force-hidden="true" ></i>
```

```
<i class="fab fa-youtube " aria-hidden="true" data-acsb-force-hidden="true" ></i>
```

21	Figure elements that are used to display images should have a "role" attribute that equals to "none" and the image provide itself should provide the description using an "alt" attribute.	No	0	0	-
22	Every "area" element of a "map" tag should be regarded as a standard image and receive an alternative text description using an "alt" attribute.	No	0	0	-
23	Small or hidden tracker pixel images (often used for analytics or marketing purposes) should include a "role" attribute that equals to "none" or "presentation" so they are excluded from screen-readers.	No	0	0	-
24	Form fields should either include an "aria-label" attribute or a connected LABEL element describing the requirement of the	Yes	Pass	-	100%

Code snapshots of some successful elements

```
<input id="email" name="newsletter_email" type="email" placeholder="Email address" required="true" aria-hidden="false" data-acsb-validation-uuid="email" data-acsb-field-visible="true" aria-required="true" aria-invalid="true" data-acsb-label-text=...
```

25	Form elements cannot have the same ID, or else their corresponding label will provide false information.	No	0	0	-
26	Required form fields should include an "aria-required" attribute that equals to "true" so blind users using screen-readers know their validation.	No	0	0	-
27	The validity status of every form element must be represented in the code at all times using the "aria-invalid" attributes and the "true/false" values, and change dynamically when the status changes.	No	0	0	-
28	aria-describedby and aria-labeledby attributes should be connected by ID to an element that either has text description or an "aria-label" attribute.	Yes	12	0	100%

Code snapshots of some successful elements

```
<div class="wpls-logo-cnt slick-slide" data-slick-index="0" style="width: 344px;" aria-describedby="slick-slide00"> <div class="wpls-fix-box">  <div class="wpls-fix-box"> <img class="wp-post-image jetpack-lazy-image jetpack-lazy-image--handled" ...
```

```
<div class="wpls-logo-cnt slick-slide slick-active" data-slick-index="2" style="width: 344px;" aria-describedby="slick-slide02"> <div class="wpls-fix-box">  <div class="wpls-fix-box">  <div class="wpls-fix-box">  <div class="wpls-fix-box" aria-hidden="true" >  <div class="wpls-fix-box" >  <div class="wpls-fix-box" >  <div class="wpls-fix-box" >  <div class="wpls-fix-box" >  <input type="hidden" id="_wponce" name="_wponce" value="71f42e4484" aria-hidden="true" tabindex="-1" ><input type="hi...
```

30	Search forms should include a "role" tag that equals to "search" (or be wrapped by one) to indicate a search landmark for screen-readers.	No	0	0	-
31	The title tag of the HEAD section (also the title that appears in the browser tab and Search Engine result pages) should exist and describe the name of the current webpage for screen-reader users.	Yes	Pass	-	100%

Code snapshots of some successful elements

```
<title>Sliquid Natural Intimate Products</title>
```

32	The HTML tag should include a "lang" attribute that represents the main language of the webpage so screen-readers can calibrate on it for blind users.	Yes	Pass	-	100%
----	--	-----	------	---	------

Code snapshots of some successful elements

```
<html lang="en-US" class="jetpack-lazy-images-js-enabled acsb-light-contrast" id="acsb-light-contrast"><head> <base href="https://sliquid.com"><meta name="aceEmbedder" content="https://accessscan.accessible.com"><meta name="aceClient" content=...
```

double the standard scaling using the user-

scalable="yes" and maximum-scale={2 or higher} content strings.

Code snapshots of some successful elements

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

34 Landmarks such as main content and footer should be built using their corresponding HTML5 element or include a description using an "aria-label" attribute and a "role" tag that equals to "contentinfo" or "main". Landmarks such as search and navigation are tested in other sections.

Yes

3

0

100%

Code snapshots of some successful elements

```
<main id="main" class="site-main" role="presentation"> <article id="post-269365" class="post-269365 page type-page status-publish hentry"> <header class="entry-header" aria-hidden="true" > <h2 class="entry-title " >Sliqu id Natural Intima...
```

```
<div id="footer-widget-area" data-acsb-page-footer="true" role="contentinfo" aria-label="Footer"> <div class="container d-none d-sm-block"> <div class="inner-wrapper"> <aside class="footer-column foote...
```

35 Font sizes should be at least 11px in size in order to stay readable in the majority of font families. This should be verified also when using dynamic units such as REM or percents.

Yes

Pass

-

100%

36 Letter spacing should not be set to below -1px in order to stay readable in the majority of font families. This should be verified also when using dynamic units such as REM or percents.

Yes

Pass

-

100%

their foreground (usually text color) and background color.

Code snapshots of some successful elements

```
<span class="ubermenu-target-title ubermenu-target-text ">Products</span>
```

```
<span class="ubermenu-target-title ubermenu-target-text ">Retailers</span>  
>
```

```
<span class="ubermenu-target-title ubermenu-target-text ">News</span>
```

```
<span class="ubermenu-target-title ubermenu-target-text ">Reviews</span>
```

```
<span class="ubermenu-target-title ubermenu-target-text ">FAQ</span>
```

```
<span class="ubermenu-target-title ubermenu-target-text ">About Sliquid</span>  
>
```

```
<span class="ubermenu-target-title ubermenu-target-text ">Contact</span>
```

```
<span class="cart-value wishlist-cart-fragment ">0</span>
```

```
<h2 class="has-text-align-center best-sellers-header " id="h-customer-favorites">Customer Favorites</h2>
```

```
<h2 class="woocommerce-loop-product__title ">H2O – Sliquid Naturals</h2>
```

38	Carousels should include an "aria-label" attribute that equals to "carousel"/"slider" or something else that indicates the functionality, as well as be tagged as a landmark for screen-readers using a "role" tag that equals to "contentinfo".	No	0	0	-
39	Control elements such as next and	Yes	2	2	50%

that explains the functionality to screen-readers.

Code snapshots of some successful elements

```
<button type="button" data-role="none" class="slick-prev slick-arrow acsb -bg-image " aria-label="Previous" role="button" style="display: inline-block;" >Previous</button>
```

```
<button type="button" data-role="none" class="slick-next slick-arrow acsb -bg-image " aria-label="Next" role="button" style="display: inline-block;" >Next</button>
```

Code snapshots of some failed elements

```
<div class="jp-swiper-button-prev swiper-button-prev " > <svg width="25" height="24" viewBox="0 0 25 24" fill="none" xmlns="http://www.w3.org/2000/svg" aria-hidden="true" data-acsb-force-hidden="true" > <mask id="maskPrev" mask-type="..."
```

```
<div class="jp-swiper-button-next swiper-button-next " > <svg width="25" height="24" viewBox="0 0 25 24" fill="none" xmlns="http://www.w3.org/2000/svg" aria-hidden="true" data-acsb-force-hidden="true" > <mask id="maskNext" mask-type="..."
```

40	A common accessibility mistake is to treat carousels as live regions using the "aria-live" attribute and the "polite" or the "assertive" values. Using this practice will cause screen-readers to cut and skip announcements.	No	0	0	-
41	Carousel pagination items (usually used as small dots at the bottom of the carousel) should indicate their functionality and slide number they control using an "aria-label" and a screen-reader only text.	Yes	10	0	100%

Code snapshots of some successful elements

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 1" aria-hidden="false" >Next carousel slide</span>1</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 2" aria-hidden="false" >Next carousel slide</span>2</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 3" aria-hidden="false" >Next carousel slide</span>3</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 4" aria-hidden="false" >Next carousel slide</span>4</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 5" aria-hidden="false" >Next carousel slide</span>5</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 6" aria-hidden="false" >Next carousel slide</span>6</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 7" aria-hidden="false" >Next carousel slide</span>7</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 8" aria-hidden="false" >Next carousel slide</span>8</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 9" aria-hidden="false" >Next carousel slide</span>9</button>
```

```
<button type="button" data-role="none" role="button" class=" " data-acsb-carousel-paging="true"><span data-=""true" " aria-label=" Next carousel slide 10" aria-hidden="false" >Next carousel slide</span>10</button>
```

structures should include a "role" attribute

that equals to "presentation" to indicate to screen-readers that it is not really a table.

43	If nested tables are used (a table element within a table cell), set the nested tables "role" attribute to "presentation".	No	0	0	-
44	Tables that are missing a THEAD row with TH elements, should include a "role" attribute that equals to "rowheader" on the TD elements of the TR that represents the visual table headings.	No	0	0	-
45	Visually deleted texts (often used to show a previous price of a sale) should include an "aria-label" attribute or a screen-reader only text that explains this is deleted text.	No	0	0	-
46	Breadcrumbs main element should include a "role" attribute that equals to "navigation" and an "aria-label" attribute that describes the functionality."	No	0	0	-
47	Ratings/scores that are represented visually using stars, meters or other indicators should either have an "aria-label" attribute or a screen-reader only texts conveying the score/rate.	No	0	0	-
48	Making use of an accessibility interface helps to ensure that vision impaired users can adjust some of the UI and the design (font-size, colors, spacing, etc.) to their needs. It is not a compliance requirement, but can help to improve compliance.	Yes	Pass	-	100%
49	Iframe elements should include a "title" or an "aria-label" attribute explaining the	No	0	0	-

of the iframe, or be tagged hidden for screen-readers if irrelevant.