

s a u e

---

## CP Series 180

---

---

### Gear Pumps

---

### Technical Information

---

---


Available Configurations, Pumps	Available Configurations, Motors
 <b>TFP 50 Pump</b> DIN Flanges & Shaft 5 models 0.25-1.27 cm³ (0.015-0.074 in³) Speeds to 8000 rpm Pressures to 200 bar (2900 psi)	 <b>TFM 100 Motors</b> DIN Flanges & Shafts 6 models 2.60-7.8 cm³ (0.158-0.464 in³) Speeds to 3000 rpm Pressures to 200 bar (2900 psi)
 <b>TFP 100 Pumps</b> SAE "AA" & DIN Flanges & Shafts 7 models 1.20-7.8 cm³ (0.071-0.464 in³) Speeds to 5000 rpm Pressures to 230 bar (3300 psi)	 <b>SNM2 Motors</b> SAE "A" & DIN Flanges & Shafts 10 models 6-25.2 cm³ (0.366-1.54 in³) Speeds to 4000 rpm Pressures to 280 bar (4100 psi) NOTE: SNU2 Uni-directional motor available in 8.4-25.2 cm³ (0.513-1.54 in³)
 <b>SNP2 Pumps</b> SAE "A" & DIN Flanges & Shafts 11 models 3.4-25.2 cm³ (0.24-1.54 in³) Speeds to 4000 rpm Pressures to 260 bar (3800 psi)	 <b>TAM2290 Motors</b> SAE "B" & DIN Flanges & Shafts 9 models 22-90 cm³ (1.34-5.49 in³) Speeds to 3000 rpm Pressures to 230 bar (3300 psi) NOTE: TAU2290 Uni-directional motor available in the same displacements
 <b>SP2.5/250 Pumps</b> SAE "A" & "B" 2-Bolt Flanges SAE "A" & "B" 11T & 13T spline shafts SAE "A" & "B" .75" & .875" keyed shafts 8 models 20-45 cm³ (1.22-2.75 in³) Speeds to 3000 rpm Pressures to 275 bar (4000 psi) Priority Flow Divider Covers	<b>Fan Drive Systems</b>  Available in 5 to 36 HP configurations Fan speed modulated based temperature Options for additional inputs Contact Sauer-Sundstrand for details and specifications
 <b>SNP3 Pumps</b> SAE "B" & DIN Flanges & Shafts 10 models 22.1-88.2 cm³ (1.35-5.38 in³) Speeds to 3000 rpm Pressures to 270 bar (3910 psi) NOTE: The SEP3 is available in the 22.1-44.1cm³ (1.35-2.69 in³) displacements for applications not requiring the pressure capabilities of the SNP3 or CP180.	<b>Steering Pumps</b>  Available in 8-45 cm³ (0.49-2.75 in³) Special and or engine mount available (ie Perkins, Deutz, Kubota, etc.) Flanges and shafts for several engines Contact Sauer-Sundstrand for details and specifications
 <b>CP180 Pumps</b> SAE "B" Flanges & Shafts 11 models 31.79-95.7 cm³ (1.94-5.38 in³) Speeds to 3200 rpm Pressures to 310 bar (4500 psi) Priority Flow Divider Covers	
 <b>CP222 Pumps</b> SAE "C" 2 & 4-Bolt Flanges & Shafts 7 models 64.8-162.0 cm³ (3.95-9.89 in³) Speeds to 3000 rpm Pressures to 275 bar (4000 psi)	

**\*\*NOTE:** All pumps can be incorporated into multiple pump configurations. Contact Sauer-Sundstrand for details and specifications.

## Sauer-Sundstrand Gear Pump and Motor Features


- Worldwide sales and service capabilities from the industry leader is part of the package for every Sauer-Sundstrand gear product customer.
- Proven reliability with over 45 years of experience in gear product design for mobile and industrial applications.
- System pressures to 4500 psi (310 bar) and speeds to 8,000 rpm allow high performance in system design.
- Pressure balanced design for high efficiency and long life.
- Low cost design and manufacturing for the requirements of fixed displacement systems.
- Variety of flexible installation options available:
  - SAE, Metric, and European flanges, shafts and ports
  - Convenient side or rear porting options
  - Auxiliary through drive SAE mounting pads
  - Integral relief valve, priority flow control, and priority flow divider covers
  - High temperature viton seals optional
  - Multiple pump configurations (refer to the Quick Reference chart below)

### Quick Reference - Multiple Pump Configurations



## A Complete Family of Sauer-Sundstrand Gear Pumps and Motors

### Quick Reference - Displacement/Model



### Table of Contents


Sauer-Sundstrand Gear Pump and Motor Features .....	3
A Complete Family of Sauer-Sundstrand Gear Pumps and Motors .....	4
Technical Features .....	5
Pump Sizing Calculations .....	9
CP 180 Single Gear Pumps .....	10
CP 180 Gear Pumps with Priority Flow Divider (PFD) .....	10
CP 180 Gear Pump Specifications .....	11
CP 180 Single Gear Pump Dimensions .....	18
CP 180 Single Gear Pump Cover and Shaft Options .....	19
CP 180 Priority Flow Divider Pump Dimensions and Options .....	20
CP 180 Priority Flow Divider Pump Dimensions and Options, Continued .....	21
CPB (CP 180 Single, SAE "B" 2 Bolt Flange, Side Ports) Modular Ordering Code .....	22
CPC (CP 180 Single, SAE "B" 2 Bolt Flange, Rear Ports) Modular Ordering Code .....	23
CPD (CP 180 Single, SAE "B" 4 Bolt Flange, Side Ports) Modular Ordering Code .....	24
CPJ (CP 180 Single, SAE "B" 2 Bolt Flange and PFD Cover) Modular Ordering Code .....	25
CP 180 Tandem Gear Pumps .....	26
CP 180 Tandem Gear Pump Dimensions .....	27
CPE (CP 180 Tandem, SAE "B" 2-Bolt Flange, Side Ports) Modular Ordering Code .....	28
CPE (CP 180 Tandem, SAE "B" 2-Bolt Flange, Side Ports) Modular Ordering Code, cont. ....	29
CPF (CP 180 Tandem, SAE "B" 2 Bolt Flange, Rear Ports) Modular Ordering Code .....	30
CPF (CP 180 Tandem, SAE "B" 2 Bolt Flange, Rear Ports) Modular Ordering Code, cont. ....	31
CPG (CP 180 Tandem, SAE "B" 4 Bolt Flange, Side Ports), Modular Ordering Code .....	32
CPG (CP 180 Tandem, SAE "B" 4 Bolt Flange, Side Ports), Modular Ordering Code, cont. ....	33

## Technical Features

### DESIGN

Sauer-Sundstrand CP Series gear pumps utilize an external spur gear, positive displacement, and pressure balanced design, providing superior efficiency. These "heavy duty cycle" pumps are three-piece construction utilizing an aluminum flange and cover with Compacted Graphite Iron gear housings. This design offers superior resistance to contamination and excellent strength to survive in the harsh "construction type" environments but are light in weight. Oversized journal bearings (DU) are utilized to provide maximum life. By design, the gears of this pump on initial running track into the gear housing and create their own radial tip seal for high volumetric efficiency.

**Figure 1:**




### DELAYED INLET

All Sauer-Sundstrand CP Series pumps are manufactured to maximize efficiency and to enhance performance. The "Delayed Inlet" feature provides a number of advantages.

(1) Because more gear teeth are exposed to the inlet, the dwell time to fill the gear teeth is improved, thus allowing the pump to perform better

at low temperatures and with more viscous fluids. (2) The gears are directed to "track in" at a zone further up the circle from the inlet than in a conventional pump. This "Delayed Track" increases low speed efficiency by providing a better low pressure to high pressure area ratio than conventional designs.

**Figure 2:**



### LEAK PROTECTION

Various seals are available to meet specific applications. Standard are dual Buna seals to prevent leakage and migration of fluids from the hydraulic circuit to the gear box.

An optional weep hole between the seals is available to further protect the gear box and show leakage if any should occur. Section seal rings are exposed to inlet to reduce the risk of external leakage.

**Technical Features, Continued****INLET OIL BUSHING LUBRICATION**

The design of the CP Series is such that cooler inlet oil is routed to "flood" the DU Bushings with oil. This principle eliminates the need to force high pressure leakage to the journals. This allows the pump to run cooler, with higher volumetric efficiency.

**THERMAL EXPANSION OF ALUMINUM MEMBERS THERMAL EXPANSION OF IRON BODY**


As the oil temperature increases and oil viscosity goes down, the CP Series pump changes its tip clearance to compensate for this increased leakage. By using dissimilar materials (i.e., alumi-

num covers and iron gear housings), the difference in their coefficients of expansion causes the pump components to move in a manner which maintains volumetric efficiency as temperature increases.


**LESS DEBRIS IN THE EVENT OF BEARING FAILURE**

In the unlikely event of a bearing failure the CP pump offers, by design, release of less downstream contaminant to your systems than conventional pumps. Because the "track" is essentially tangent to the induced load, in the event of a failure, the gear (idler) tends to move into the pre-cut "delayed inlet slot." Failure detection is the same as a conventional pump but the volume of debris ingested is significantly less.

**Figure 3:**  
The DU® Bearing



**Figure 4:**



DU® is a trademark of the Garlock Bearing Company

**Technical Features, Continued****DRIVE CONDITIONS**

Most Sauer-Sundstrand gear products are available SAE standard spline or straight keyed drive shafts for direct or indirect drive applications. A three piece coupling is the preferred method of direct drives, thereby eliminating radial and axial loading.

Rigid splines may be used providing the mounting pilot should be aligned within .002 in. (.05 mm) on center [.004 (.10 mm) TIR].

Both concentricity and angular alignment of shafts are important to pump life. Misalignment can induce heavy side loads on bearing and seals, causing premature failure.

Overhung load drives (chain, belt, or gear) are permissible. Contact Sauer-Sundstrand for assistance.

**FILTRATION**

A full flow 10 micron filter should be used in the system return line to trap all contaminants before they enter the reservoir.

Since the filter must be changed at regular intervals, the filter housing should be located in an accessible area.

**OPERATING TEMPERATURES**

With Buna seals and normal operating conditions, the system temperature should not exceed 180° F (82°C) except for short periods to 200° F (93° C).

With optional Viton elastomers, the system may be operated at continuous temperatures up to 225° F (107° C) without damage to the pump.

**CAUTION: Operation in excess of 225° F may cause external leakage or premature unit failure.**

**FLUIDS**

A mineral based fluid is recommended with additives to resist corrosion, oxidation and foaming. The oil should have the maximum viscosity commensurate with system pressure drop and pump suction levels. The viscosity at any running condition must be between 45 SSU minimum and

250 SSU maximum continuous.

Since the fluid used serves as a system lubricant, as well as transmitting power, careful selection of the fluid is important for proper operation of the unit and satisfactory life of the pump and components.

**SUCTION**

For maximum pump life, the inlet vacuum should not exceed 4 inches (100 mm) Hg at the pump inlet. For cold start conditions, vacuum up to 12 inches (300 mm) Hg. is acceptable for short durations.

Both cavitation and the possibility of aeration increase with higher inlet vacuum. In addition, oil film lubrication is disrupted by high inlet vacuum. Both factors, either singularly or combined, may contribute to a decrease in pump life.

**CAUTION:** Continuous operation at vacuums in excess of 4 inches Hg. may cause premature unit failure.

**MAXIMUM SPEED**

Maximum speed is limited by gear tooth filling and surface speeds centrifugal gear teeth filling. Unless otherwise specified, maximum rated pump speeds listed in this manual are based on operation at sea level with SAE oil having a viscosity of 120 SSU at 122° (50° C). Speed limits for a particular application depend on inlet pressure and oil viscosity. Consult Sauer-Sundstrand for operation outside these limits.

**MINIMUM SPEED**

Minimum recommended operating speed at 2500 psi is 600 RPM. Minimum speed is limited by volumetric efficiency. If lower than recommended starting or operating speeds are required, contact Sauer-Sundstrand for assistance.

For motors, minimum speeds listed are for continuous operation at rated pressure. Motors may be started from zero speed on drives where torque typically increases with speed. Repeated starts under high load conditions are not recommended. No load start up pressures range from 300 to 600 PSI (20.7 to 41.4 BAR).

## Technical Features, Continued

### INPUT TORQUE RATINGS

The individual product dimensional configurations in this catalog list the maximum continuous input torques for various shaft options.

When applying pumps in tandem or multiple, observe that input torque limitations must be met for each section and cumulative sections.

Always insure that the rear pump on a tandem unit does not exceed its torque rating.

**CAUTION: Torques In excess of those shown may cause premature input shaft or unit failure.**

### MOUNTING

The pump mount / drive should be designed to minimize axial and radial loads on the shaft. When using indirect (chain, belt, or gear) drive, contact Sauer-Sundstrand to determine permissible load limits and direction of installation.

### PIPING

The choice of piping size and installation should always be consistent with maintaining minimum velocity. This will reduce system noise, pressure drops and overheating, thereby adding to cost savings for both the construction and operation of the system.

Inlet piping should be designed to prevent continuous pump inlet vacuums in excess of 4 in. (100 mm) Hg. or 12 in. (300 mm) Hg. during start-up when measured at the inlet port.

### RESERVOIR

The reservoir should be designed to accommodate maximum volume changes during all system operating modes and prevent aeration of the fluid as it passes through the tank. Return and inlet lines should be positioned below the reservoir low oil level and be located as far as possible from

each other. A baffle plate located between the pump inlet and return line is desirable to allow the oil to deaerate before it enters the pump.

Reservoirs are normally sized for at least one-half the maximum pump flow for adequate oil deaeration.

### COOLING

Depending on duty cycle and reservoir/line construction, an oil cooler may be required. This is sized based on typical power losses in the hydraulic circuit. The oil cooler is usually placed in the return line.

### CAVITATION

Hydraulic oil used in the majority of systems contains about 10% dissolved air by volume. This air under certain conditions of vacuum within the system is released from the oil causing air bubbles. These air bubbles collapse if subjected to pressure, and this collapse creates erosion of the adjacent metal. Because of this, it becomes obvious that the greater the air content within the oil, or the greater the vacuum in the inlet line, the more severe will be the resultant erosion.

The main causes of over-aeration of the oil are air leaks, particularly on the inlet side of the pump, and flow line restrictions such as inadequate pipe sizes, elbow fittings and sudden changes in flow line cross sectional area. Providing these defects are avoided; pump inlet pressure and rated speed requirements are maintained; and reservoir size and location is adequate, no cavitation problems should occur with Sauer-Sundstrand pumps and motors.

**Technical Features, Continued****PRESSURE PROTECTION & RATINGS**

The pump, as well as other system components, has pressure limitations. Thus a relief valve must be installed in the system, preferably as close to the pump as possible, to protect it from excessive pressure. If the relief valve is set at or near the maximum pressure rating for the pump, the operating characteristics of the valve should be known so that common relief valve overshoot does not allow system pressure to exceed the pump rating. Intermittent is defined as less than 15% of the duty cycle. Peak is defined as relief valve maximum overshoot. Contact Sauer-Sundstrand for pressures above those listed.

**CAUTION: Failure to install this relief valve may result in premature unit failure.**

**LIFE EXPECTANCY**

All Sauer-Sundstrand gear pumps utilize pressure balanced journal bearings which have an oil film maintained between the gear / shaft and bearing surfaces at all times. If this oil film is sufficiently sustained through proper system maintenance and operating limits are adhered to, a high life can be expected.

NOTE: A B-10 type life expectancy number is generally associated with anti-friction bearings and does not exist for journal bearings.

**Pump Sizing Calculations****SI System**

$$\text{Output flow } Q_e = \frac{Vg \cdot n \cdot \eta_v}{1000} \quad \text{l/min}$$

$$\text{Input torque } M_e = \frac{Vg \cdot \Delta p}{20 \cdot \pi \cdot \eta_{mh}} \quad \text{Nm}$$

$$\text{Input Power } P = \frac{M_e \cdot n}{9550} = \frac{Q_e \cdot \Delta p}{600 \cdot \eta_t} \quad \text{kW}$$

$Vg$  = Displacement per revolution in  $\text{cm}^3$

$p_{HD}$  = High pressure, in bar

$p_{ND}$  = Low pressure, in bar

$\Delta p$  =  $p_{HD} - p_{ND}$  bar (System pressure)

$n$  = Speed rpm ( $\text{min}^{-1}$ )

$\eta_v$  = Volumetric efficiency, (%)

$\eta_{mh}$  = Mechanic - hydraulic efficiency, (%)

$\eta_t$  = Overall efficiency, (%)

**English System**

$$\text{Output flow } Q_e = \frac{Vg \cdot n \cdot \eta_v}{231} \quad \text{gal/min}$$

$$\text{Input torque } M_e = \frac{Vg \cdot \Delta p}{2 \cdot \pi \cdot \eta_{mh}} \quad \text{in} \cdot \text{lb}$$

$$\text{Input Power } P = \frac{M_e \cdot n}{63025} = \frac{Q_e \cdot \Delta p}{1714 \cdot \eta_t} \quad \text{HP}$$

$Vg$  = Displacement per revolution in  $\text{in}^3$

$p_{HD}$  = High pressure, in psi

$p_{ND}$  = Low pressure, in psi

$\Delta p$  =  $p_{HD} - p_{ND}$  psi (System pressure)

$n$  = Speed rpm ( $\text{min}^{-1}$ )

$\eta_v$  = Volumetric efficiency, (%)

$\eta_{mh}$  = Mechanic - hydraulic efficiency, (%)

$\eta_t$  = Overall efficiency, (%)

**CP 180 Single Gear Pumps**

- 11 Sizes from 2.01 to 5.84 cu.in/rev.  
(32.94 to 95.70 cc/rev.)
- SAE 2-Bolt "B" Mounting Flange
- SAE 4-Bolt "B" Mounting Flange
- Spline or Keyed Shaft
- SAE 4-Bolt Split Flange Side Ported, Code 61
- SAE O-Ring Boss Ports - Side and Rear
- "Nitrile" Seals - Standard, "Viton" Seals - Optional
- Auxiliary Pad Rear Cover -  
SAE "A" & "B" Pad Mounts
- Clockwise or Counterclockwise Rotation
- Pressure - 3600 PSI Continuous (4500 PSI Peak)
- Speeds to 3000 RPM

**CP 180 Gear Pumps with Priority Flow Divider (PFD)**

- 7 Sizes from 2.01 to 3.88 cu.in/rev.  
(32.94 to 63.63 cc/rev.)
- SAE 2-Bolt "B" Mounting Flange Standard
- Spline or Keyed Shaft
- SAE 4-Bolt Split Flange Side Ported, Code 61
- SAE O-Ring Boss Ports - Side and Rear
- "Nitrile" Seals - Standard, "Viton" Seals - Optional
- 7 Standard Priority Flow Settings from 2 gpm to 8 gpm\*
- 5 Standard Pressure Options from 130 to 190 Bar  
(1885 to 2755 psi)\*\*



\*Nominal flow setting at 30 gpm (115 L/min) maximum  
pump flow and auxiliary supply 1000 psi (69 Bar) greater  
than priority pressure.

\*\*Nominal dead head pressure set at 1.0 gpm (3.85 L/min)  
flow

**Shaft and Port Option Prefix Codes for the CP series:**

CPB	=	CP 180 Single Pump with SAE "B" 2 Bolt flange and Side Ports
CPC	=	CP 180 Single Pump with SAE "B" 2 Bolt flange and Rear Ports
CPD	=	CP 180 Single Pump with SAE "B" 4 Bolt flange and Side Ports
CPE	=	CP 180 Tandem Pump with SAE "B" 2 Bolt flange and Side Ports
CPF	=	CP 180 Tandem Pump with SAE "B" 2 Bolt flange and Rear Ports (on rear section)
CPG	=	CP 180 Tandem Pump with SAE "B" 4 Bolt flange and Side Ports
CPJ	=	CP 180 Priority Flow Divider Single Pump with SAE "B" 2 Bolt flange

## CP 180 Gear Pump Specifications





Table 1:





CP 180	Dimension	Frame Size										
		020	023	026	030	032	035	040	045	050	055	060
Displacement	cu. in. / rev	2.01	2.24	2.54	2.92	3.14	3.40	3.88	4.37	4.85	5.36	5.84
	cc/rev	32.94	36.65	41.60	47.77	51.49	55.70	63.63	71.58	79.53	87.83	95.70
Continuous Pressure	psi	3600	3600	3600	3600	3600	3600	3600	3600	3300	3000	2700
	bar	250	250	250	250	250	250	250	250	230	210	185
	rpm	3000	3000	3000	3000	2800	2800	2800	2600	2600	2400	2400
Intermittent Pressure	psi	4000	4000	4000	4000	4000	4000	4000	4000	3650	3300	3000
	bar	275	275	275	275	275	275	275	275	255	230	210
	rpm	3000	3000	3000	3000	2800	2800	2800	2600	2600	2400	2400
Peak Pressure	psi	4500	4500	4500	4500	4500	4300	4100	4100	3800	3600	3400
	bar	310	310	310	310	310	295	280	280	260	250	235
Minimum Speed at 2500 psi	rpm	600	600	600	600	600	600	600	600	600	600	600
Weight	lbs	19.29	19.60	20.00	20.50	20.90	21.30	22.20	23.10	24.00	24.90	25.80
	kgs	8.75	8.89	9.07	9.32	9.48	9.68	10.09	10.50	10.91	11.30	11.70





Note: For applications requiring parameters beyond those listed above, contact Sauer-Sundstrand.





Table 2:





Frame Size	Speed	Theoretical Flow vs Speed, For Reference Only									
		Units	liters/min	GPM	liters/min	GPM	liters/min	GPM			
020	Flow	10.44	39.53	13.05	49.41	17.40	65.88	21.75	82.34	26.10	98.81
023		11.64	43.98	14.55	54.98	19.39	73.30	24.24	91.63	29.09	109.95
026		13.19	49.92	16.49	62.40	21.99	83.20	27.49	104.00	32.99	124.80
030		15.17	57.32	18.96	71.66	25.28	95.54	31.60	119.43	37.92	143.31
032		16.31	61.79	20.39	77.24	27.19	102.98	33.98	128.73	40.78	154.47
035		17.66	66.84	22.08	83.55	29.44	111.40	36.80	139.25	44.16	167.10
040		20.16	76.36	25.19	95.45	33.59	127.26	41.99	159.08	50.39	190.89
045		22.70	85.90	28.38	107.37	37.84	143.16	47.29	178.95	56.75	214.74
050		25.19	95.44	31.49	119.30	41.99	159.06	52.49	198.83	62.99	238.59
055		27.84	105.40	34.81	131.75	46.41	175.67	58.01	219.59	69.61	263.50
060		30.34	114.84	37.92	143.55	50.56	191.40	63.20	239.25	75.84	287.10



**CP 180 Performance Curves, (Continued)**[ $v = 34 \text{ mm}^2/\text{s}$  (160 SUS),  $\vartheta = 49^\circ \text{ C}$  (120°F)]**Figure 5:****Figure 6:****Figure 7:****Figure 8:**

**CP 180 Performance Curves, (Continued)**[ $v = 34 \text{ mm}^2/\text{s}$  (160 SUS),  $\vartheta = 49^\circ \text{ C}$  ( $120^\circ \text{ F}$ )]**Figure 9:****Figure 10:****Figure 11:****Figure 12:**

**CP 180 Performance Curves, (Continued)**[ $v = 34 \text{ mm}^2/\text{s}$  (160 SUS),  $\vartheta = 49^\circ \text{ C}$  (120°F)]**Figure 13:****Figure 14:****Figure 15:****Figure 16:**

**CP 180 Performance Curves, (Continued)**[ $v = 34 \text{ mm}^2/\text{s}$  (160 SUS),  $\vartheta = 49^\circ \text{ C}$  ( $120^\circ \text{ F}$ )]**Figure 17:****Figure 18:****Figure 19:****Figure 20:**

**CP 180 Performance Curves, (Continued)**[ $\nu = 34 \text{ mm}^2/\text{s}$  (160 SUS),  $\vartheta = 49^\circ \text{ C}$  (120°F)]**Figure 21:****Figure 22:****Figure 23:****Figure 24:**

**CP 180 Performance Curves, (Continued)**[ $v = 34 \text{ mm}^2/\text{s}$  (160 SUS),  $\vartheta = 49^\circ \text{ C}$  ( $120^\circ \text{ F}$ )]**Figure 25:****Figure 26:**

## CP 180 Single Gear Pump Dimensions

Figure 27:





Table 3:

DISPLACEMENT CODE	"A"		"B"	
	IN	MM	IN	MM
020	4.46	113.31	5.71	145.06
023	4.55	115.57	5.80	147.32
026	4.67	118.62	5.92	150.37
030	4.81	122.17	6.06	153.92
032	4.87	123.70	6.12	155.45
035	4.98	126.49	6.23	158.24
040	5.16	131.06	6.41	162.81
045	5.33	135.38	6.58	167.13
050	5.51	139.95	6.76	171.70
055	5.69	144.53	6.94	176.28
060	5.86	148.84	7.11	180.59

## CP 180 Single Gear Pump Cover and Shaft Options

Dimensions shown in inches xx.xx with metric dimensions (millimeters) shown in brackets (xx.xx).

**Figure 28:**




(REAR PORTED CONFIGURATION)  
(DRAWN FOR CLOCKWISE ROTATION)


**Figure 29:**

## MOUNTING SHAFTS AVAILABLE


SAE "B" SPLINE




SAE "B-B" SPLINE



SAE "B-B" STRAIGHT



SAE "B" STRAIGHT



TORQUE LIMIT: 2200 LB. IN.

TORQUE LIMIT: 4100 LB. IN.





TORQUE LIMIT: 4100 LB. IN.

TORQUE LIMIT: 2200 LB. IN.

## CP 180 Priority Flow Divider Pump Dimensions and Options

Dimensions shown in inches xx.xx with metric dimensions (millimeters) shown in brackets (xx.xx).

Figure 30:



Back Cover for CB and CD  
Option Code


Back Cover for CA Option  
Code

Table 4:


DISPLACEMENT CODE	MOUNTING DIMENSIONS			
	"A"		"B"	
	IN	MM	IN	MM
020	4.46	113.31	5.71	145.06
023	4.55	115.57	5.80	147.32
026	4.67	118.62	5.92	150.37
030	4.81	122.17	6.06	153.92
032	4.87	123.70	6.12	155.45
035	4.98	126.49	6.23	158.24
040	5.16	131.06	6.41	162.81

## CP 180 Priority Flow Divider Pump Dimensions and Options, Continued

**Figure 31:**




**Back Cover Secondary Outlet for CD Option Code (Primary is on Side as shown for all other options).**



**Back Cover Outlets for CA,CB and CC Option Code**

**Figure 32:**

### Priority Relief Valve Dead Head Pressure




\*Nominal flow setting at 30 gpm (115 L/min) maximum pump flow and auxiliary supply 1000 psi (69 Bar) greater than priority pressure.

\*\*Nominal dead head pressure set at 1.0 gpm (3.85 L/min) flow

**Figure 33:**

### Symbolic Schematic of PFD Option



**CPB (CP 180 Single, SAE "B" 2 Bolt Flange, Side Ports) Modular Ordering Code****A: CPB 180 Series Pump (SAE "B" 2-Bolt Flange and Side Ports)**   **E: Front Drive Gear (Continued)****B: Model**

020=	2.01 CIR (32.94 cc/rev)
023=	2.24 CIR (36.65 cc/rev)
026=	2.54 CIR (41.60 cc/rev)
030=	2.92 CIR (47.77 cc/rev)
032=	3.14 CIR (51.49 cc/rev)
035=	3.40 CIR (55.70 cc/rev)
040=	3.88 CIR (63.63 cc/rev)
045=	4.37 CIR (71.58 cc/rev)
050=	4.85 CIR (79.53 cc/rev)
055=	5.36 CIR (87.83 cc/rev)
060=	5.84 CIR (95.70 cc/rev)

**C: Rotation**

R=	Righthand (CW)
L=	Lefthand (CCW)

**D: Seal Kit**

2=	Buna
4=	Viton

**E: Front Drive Gear (Choose One)**

AU=	13T Spline 020	BA=	15T Spline 020
AR=	13T Spline 023	AS=	15T Spline 023
AV=	13T Spline 026	BB=	15T Spline 026
AA=	13T Spline 030	AF=	15T Spline 030
AX=	13T Spline 032	BC=	15T Spline 032
AB=	13T Spline 035	AG=	15T Spline 035
AC=	13T Spline 040	AH=	15T Spline 040
AD=	13T Spline 045	AJ=	15T Spline 045
AE=	13T Spline 050	AK=	15T Spline 050
AY=	13T Spline 055	BD=	15T Spline 055
AZ=	13T Spline 060	BE=	15T Spline 060
BF=	1" Straight Key Shaft 020		
AT=	1" Straight Key Shaft 023		
BG=	1" Straight Key Shaft 026		
AL=	1" Straight Key Shaft 030		
BH=	1" Straight Key Shaft 032		
AM=	1" Straight Key Shaft 035		
AN=	1" Straight Key Shaft 040		
AP=	1" Straight Key Shaft 045		
AQ=	1" Straight Key Shaft 050		
BI=	1" Straight Key Shaft 055		
BJ=	1" Straight Key Shaft 060		

BK=	.88" Straight Key Shaft 020
BL=	.88" Straight Key Shaft 023
BM=	.88" Straight Key Shaft 026
BN=	.88" Straight Key Shaft 030
BO=	.88" Straight Key Shaft 032
BP=	.88" Straight Key Shaft 035
BQ=	.88" Straight Key Shaft 040
BR=	.88" Straight Key Shaft 045
BS=	.88" Straight Key Shaft 050
BT=	.88" Straight Key Shaft 055
BU=	.88" Straight Key Shaft 060

**F: Rear Cover/Port Code****"O" Ring Boss, 1.25" In, 1.00" Out**

AL=	Plain Rear Cover
AM=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AN=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BM=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BN=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AP=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
AQ=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T
BP=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 15T
BQ=	RH (CW) Aux. W/ SAE "B" 2 Bolt 15T

**SAE Code 61 Split Flange, 1.25" In, 1.00" Out**

AR=	Plain Rear Cover
AS=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AT=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BR=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BS=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AU=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
AV=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T
BT=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 15T
BU=	RH (CW) Aux. W/ SAE "B" 2 Bolt 15T

**SAE Code 61 Split Flange, 1.50" In, 1.25" Out**

AW=	Plain Rear Cover
AX=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AY=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BV=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BW=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AZ=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
BA=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T
BX=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 15T
BY=	RH (CW) Aux. W/ SAE "B" 2 Bolt 15T

**Optional Aux Pad Ship Cover Kit**

SAE "A" pad = 20086-17  
 SAE "B" pad = 20086-18

**CPC (CP 180 Single, SAE "B" 2 Bolt Flange, Rear Ports) Modular Ordering Code****A: CPC 180 Series Pump (SAE "B" 2-Bolt Flange and Rear Ports)** **E: Front Drive Gear (Continued)****B: Model**

020= 2.01 CIR (32.94 cc/rev)  
 023= 2.24 CIR (36.65 cc/rev)  
 026= 2.54 CIR (41.60 cc/rev)  
 030= 2.92 CIR (47.77 cc/rev)  
 032= 3.14 CIR (51.49 cc/rev)  
 035= 3.40 CIR (55.70 cc/rev)  
 040= 3.88 CIR (63.63 cc/rev)  
 045= 4.37 CIR (71.58 cc/rev)  
 050= 4.85 CIR (79.53 cc/rev)  
 055= 5.36 CIR (87.83 cc/rev)  
 060= 5.84 CIR (95.70 cc/rev)

BK= .88" Straight Key Shaft 020  
 BL= .88" Straight Key Shaft 023  
 BM= .88" Straight Key Shaft 026  
 BN= .88" Straight Key Shaft 030  
 BO= .88" Straight Key Shaft 032  
 BP= .88" Straight Key Shaft 035  
 BQ= .88" Straight Key Shaft 040  
 BR= .88" Straight Key Shaft 045  
 BS= .88" Straight Key Shaft 050  
 BT= .88" Straight Key Shaft 055  
 BU= .88" Straight Key Shaft 060

**F: Rear Cover/Port Code****C: Rotation**

R= Righthand (CW)  
 L= Lefthand (CCW)

BB= "O" Ring Boss, 1.00" In, 0.75" Out  
 Plain Rear Cover

**D: Seal Kit**


2= Buna  
 4= Viton

BC= "O" Ring Boss, 1.25" In, 1.00" Out  
 Plain Rear Cover

**E: Front Drive Gear (Choose One)**

AU= 13T Spline 020      BA= 15T Spline 020  
 AR= 13T Spline 023      AS= 15T Spline 023  
 AV= 13T Spline 026      BB= 15T Spline 026  
 AA= 13T Spline 030      AF= 15T Spline 030  
 AX= 13T Spline 032      BC= 15T Spline 032  
 AB= 13T Spline 035      AG= 15T Spline 035  
 AC= 13T Spline 040      AH= 15T Spline 040  
 AD= 13T Spline 045      AJ= 15T Spline 045  
 AE= 13T Spline 050      AK= 15T Spline 050  
 AY= 13T Spline 055      BD= 15T Spline 055  
 AZ= 13T Spline 060      BE= 15T Spline 060

BF= 1" Straight Key Shaft 020  
 AT= 1" Straight Key Shaft 023  
 BG= 1" Straight Key Shaft 026  
 AL= 1" Straight Key Shaft 030  
 BH= 1" Straight Key Shaft 032  
 AM= 1" Straight Key Shaft 035  
 AN= 1" Straight Key Shaft 040  
 AP= 1" Straight Key Shaft 045  
 AQ= 1" Straight Key Shaft 050  
 BI= 1" Straight Key Shaft 055  
 BJ= 1" Straight Key Shaft 060

**CPD (CP 180 Single, SAE "B" 4 Bolt Flange, Side Ports) Modular Ordering Code****A: CPB 180 Series Pump (SAE "B" 2-Bolt Flange and Side Ports)**   **E: Front Drive Gear (Continued)****B: Model**

020=	2.01 CIR (32.94 cc/rev)
023=	2.24 CIR (36.65 cc/rev)
026=	2.54 CIR (41.60 cc/rev)
030=	2.92 CIR (47.77 cc/rev)
032=	3.14 CIR (51.49 cc/rev)
035=	3.40 CIR (55.70 cc/rev)
040=	3.88 CIR (63.63 cc/rev)
045=	4.37 CIR (71.58 cc/rev)
050=	4.85 CIR (79.53 cc/rev)
055=	5.36 CIR (87.83 cc/rev)
060=	5.84 CIR (95.70 cc/rev)

**C: Rotation**

R=	Righthand (CW)
L=	Lefthand (CCW)

**D: Seal Kit**

2=	Buna
4=	Viton

**E: Front Drive Gear (Choose One)**

AU=	13T Spline 020	BA=	15T Spline 020
AR=	13T Spline 023	AS=	15T Spline 023
AV=	13T Spline 026	BB=	15T Spline 026
AA=	13T Spline 030	AF=	15T Spline 030
AX=	13T Spline 032	BC=	15T Spline 032
AB=	13T Spline 035	AG=	15T Spline 035
AC=	13T Spline 040	AH=	15T Spline 040
AD=	13T Spline 045	AJ=	15T Spline 045
AE=	13T Spline 050	AK=	15T Spline 050
AY=	13T Spline 055	BD=	15T Spline 055
AZ=	13T Spline 060	BE=	15T Spline 060
BF=	1" Straight Key Shaft 020		
AT=	1" Straight Key Shaft 023		
BG=	1" Straight Key Shaft 026		
AL=	1" Straight Key Shaft 030		
BH=	1" Straight Key Shaft 032		
AM=	1" Straight Key Shaft 035		
AN=	1" Straight Key Shaft 040		
AP=	1" Straight Key Shaft 045		
AQ=	1" Straight Key Shaft 050		
BI=	1" Straight Key Shaft 055		
BJ=	1" Straight Key Shaft 060		

BK=	.88" Straight Key Shaft 020
BL=	.88" Straight Key Shaft 023
BM=	.88" Straight Key Shaft 026
BN=	.88" Straight Key Shaft 030
BO=	.88" Straight Key Shaft 032
BP=	.88" Straight Key Shaft 035
BQ=	.88" Straight Key Shaft 040
BR=	.88" Straight Key Shaft 045
BS=	.88" Straight Key Shaft 050
BT=	.88" Straight Key Shaft 055
BU=	.88" Straight Key Shaft 060

**F: Rear Cover/Port Code****"O" Ring Boss, 1.25" In, 1.00" Out**

AL=	Plain Rear Cover
AM=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AN=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BM=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BN=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AP=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
AQ=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T
BP=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 15T
BQ=	RH (CW) Aux. W/ SAE "B" 2 Bolt 15T

**SAE Code 61 Split Flange, 1.25" In, 1.00" Out**

AR=	Plain Rear Cover
AS=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AT=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BR=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BS=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AU=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
AV=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T
BT=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 15T
BU=	RH (CW) Aux. W/ SAE "B" 2 Bolt 15T

**SAE Code 61 Split Flange, 1.50" In, 1.25" Out**

AW=	Plain Rear Cover
AX=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AY=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BV=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BW=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AZ=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
BA=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T
BX=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 15T
BY=	RH (CW) Aux. W/ SAE "B" 2 Bolt 15T

**Optional Aux Pad Ship Cover Kit**

SAE "A" pad = 20086-17  
SAE "B" pad = 20086-18

## CPJ (CP 180 Single, SAE "B" 2 Bolt Flange and PFD Cover) Modular Ordering Code

**A: CPJ 180 Series Pump**

(SAE "B" 2-Bolt Flange and Priority Flow Divider Cover)

**F: Rear Cover/Port Code****B: Model**

020=	2.01 CIR (32.94 cc/rev)
023=	2.24 CIR (36.65 cc/rev)
026=	2.54 CIR (41.60 cc/rev)
030=	2.92 CIR (47.77 cc/rev)
032=	3.14 CIR (51.49 cc/rev)
035=	3.40 CIR (55.70 cc/rev)
040=	3.88 CIR (63.63 cc/rev)

**CA= Priority Flow Divider Rear Cover**1.25" Side Split Flange Inlet and Side "O" Ring  
Boss Outlets, .375" Priority & .75" Auxiliary**CB= Priority Flow Divider Rear Cover**Side "O" Ring Boss Ports, 1.25" Inlet, .375"  
Priority, & .75" Auxiliary**CC= Priority Flow Divider Rear Cover**1.25" Rear "O" Ring Boss Inlet and Side "O" Ring  
Boss Outlets, .375" Priority, & .75" Auxiliary**CD= Priority Flow Divider Rear Cover**1.25" Side "O" Ring Boss Inlet and .375" Side  
Priority Outlet, and .75" Top Auxiliary Outlet**C: Rotation**

R=	Righthand (CW)
L=	Lefthand (CCW)

**D: Seal Kit**

2=	Buna
4=	Viton

**E: Front Drive Gear (Choose One)**

AU=	13T Spline 020
AR=	13T Spline 023
AV=	13T Spline 026
AA=	13T Spline 030
AX=	13T Spline 032
AB=	13T Spline 035
AC=	13T Spline 040
BA=	15T Spline 020
AS=	15T Spline 023
BB=	15T Spline 026
AF=	15T Spline 030
BC=	15T Spline 032
AG=	15T Spline 035
AH=	15T Spline 040

BF=	1" Straight Key Shaft 020
AT=	1" Straight Key Shaft 023
BG=	1" Straight Key Shaft 026
AL=	1" Straight Key Shaft 030
BH=	1" Straight Key Shaft 032
AM=	1" Straight Key Shaft 035
AN=	1" Straight Key Shaft 040
BK=	.88" Straight Key Shaft 020
BL=	.88" Straight Key Shaft 023
BM=	.88" Straight Key Shaft 026
BN=	.88" Straight Key Shaft 030
BO=	.88" Straight Key Shaft 032
BP=	.88" Straight Key Shaft 035
BQ=	.88" Straight Key Shaft 040

**G: Priority Flow Setting Code (+/- 10%)\***

020=	2 GPM (7.7 L/Min)
040=	4 GPM (15.4 L/Min)
050=	5 GPM (19.2 L/Min)
060=	6 GPM (23.1 L/Min)
072=	7.2 GPM (27.7 L/Min)
080=	8 GPM (30.7 L/Min)


\*Nominal flow setting at 30 gpm (115 L/min) maximum pump flow and auxiliary supply 1000 psi (69 Bar) greater than priority pressure.

**H: Priority Pressure Setting Code (+/- 10%)\*\***

130=	130 Bar (1885 psi)
140=	140 Bar (2030 psi)
160=	160 Bar (2320 psi)
175=	175 Bar (2537 psi)
190=	190 Bar (2755 psi)

\*\*Nominal dead head pressure set at 1.0 gpm (3.85 L/min) flow. Refer to "Flow vs Pressure Curve" below.

Priority Relief Valve Dead Head Pressure  
Dead Head Flow Vs Pressure



\*Flow In Gallons Per Minute

**CP 180 Tandem Gear Pumps**

- 11 Sizes from 2.01 to 5.84 cu.in/rev.  
(32.94 to 95.70 cc/rev.)
- SAE 2-Bolt "B" Mounting Flange
- SAE 4-Bolt "B" Mounting Flange
- Spline or Keyed Shaft
- SAE 4-Bolt Split Flange Side Ported, Code 61
- "Nitrile" Seals - Standard, "Viton" Seals - Optional
- Single Inlet\*\*
- SAE 'O' Ring Boss Ports - Side and Rear
- Clockwise or Counterclockwise Rotation
- Pressure - 3600 PSI Continuous (4500 PSI Peak) Speeds to 3000 RPM
- Auxiliary Pad Rear Cover - SAE 2 Bolt "A" & "B" Pad Mounts



\* For combinations other than those shown, contact Sauer-Sundstrand.

\*\* For tandems requiring separate inlets, use CP180 single pump (rear) mounted to an optional SAE "B" pad on a front section CP180 single pump.

**★ AVAILABLE COMBINATIONS**


Figure 34:

REAR

		020	023	026	030	032	035	040
FRONT	REAR	020	★	★	★	★	★	★
		023	★	★	★	★	★	★
FRONT	REAR	026	★	★	★	★	★	★
		030	★	★	★	★	★	★
FRONT	REAR	032	★	★	★	★	★	★
		035	★	★	★	★	★	★
FRONT	REAR	040	★	★	★	★	★	★
		045	★	★	★	★	★	★
FRONT	REAR	050	★	★	★	★	★	★
		055	★	★	★	★	★	★
FRONT	REAR	060	★	★	★	★	★	★

**CP 180 Tandem Gear Pump Dimensions**

Dimensions shown in inches xx.xx with metric dimensions (millimeters) shown in brackets (xx.xx).

**Figure 35:**

**NOTE:** Please refer to page 19 for pump cover and shaft options.

**Table 5:**

DISPLACEMENT CODE	"A"		"B"		"C"	
	IN	MM	IN	MM	IN	MM
020-020	5.15	130.81	4.34	110.24	5.59	142.99
023-023	5.24	133.10	4.43	114.06	5.68	144.22
026-026	5.36	136.14	4.55	115.57	5.80	147.32
030-030	5.50	139.70	4.69	117.32	5.94	144.22
032-032	5.55	140.97	4.74	120.40	5.99	152.15
035-035	5.68	144.27	4.87	120.37	6.12	150.88
040-040	5.85	148.59	5.04	123.92	6.29	155.45
045-040	6.03	153.16	5.04	125.45	6.29	159.77
050-040	6.20	157.48	5.04	128.24	6.29	159.77
055-040	6.38	162.05	5.04	132.81	6.29	159.77
060-040	6.55	166.37	5.04	137.13	6.29	159.77

**CPE (CP 180 Tandem, SAE "B" 2-Bolt Flange, Side Ports) Modular Ordering Code**

**A:** CPE 180 Series Tandem Pump  
(SAE "B" 2-Bolt Flange and Side Ports)

**B:** Front Section Model

020= 2.01 CIR (32.94 cc/rev)  
023= 2.24 CIR (36.65 cc/rev)  
026= 2.54 CIR (41.60 cc/rev)  
030= 2.92 CIR (47.77 cc/rev)  
032= 3.14 CIR (51.49 cc/rev)  
035= 3.40 CIR (55.70 cc/rev)  
040= 3.88 CIR (63.63 cc/rev)  
045= 4.37 CIR (71.58 cc/rev)  
050= 4.85 CIR (79.53 cc/rev)  
055= 5.36 CIR (87.83 cc/rev)  
060= 5.84 CIR (95.70 cc/rev)

**C:** Rear Section Model

020= 2.01 CIR (32.94 cc/rev)  
023= 2.24 CIR (36.65 cc/rev)  
026= 2.54 CIR (41.60 cc/rev)  
030= 2.92 CIR (47.77 cc/rev)  
032= 3.14 CIR (51.49 cc/rev)  
035= 3.40 CIR (55.70 cc/rev)  
040= 3.88 CIR (63.63 cc/rev)

**D:** Rotation

R= Righthand (CW)  
L= Lefthand (CCW)

**E:** Seal Kit

2= Buna  
4= Viton

**F:** Front Drive Gear (Choose One)

AU= 13T Spline 020  
AR= 13T Spline 023  
AV= 13T Spline 026  
AA= 13T Spline 030  
AX= 13T Spline 032  
AB= 13T Spline 035  
AC= 13T Spline 040  
AD= 13T Spline 045  
AE= 13T Spline 050  
AY= 13T Spline 055  
AZ= 13T Spline 060

**F:** Front Drive Gear (Continued)

BA=	15T Spline 020
AS=	15T Spline 023
BB=	15T Spline 026
AF=	15T Spline 030
BC=	15T Spline 032
AG=	15T Spline 035
AH=	15T Spline 040
AJ=	15T Spline 045
AK=	15T Spline 050
BD=	15T Spline 055
BE=	15T Spline 060
BF=	1" Straight Key Shaft 020
AT=	1" Straight Key Shaft 023
BG=	1" Straight Key Shaft 026
AL=	1" Straight Key Shaft 030
BH=	1" Straight Key Shaft 032
AM=	1" Straight Key Shaft 035
AN=	1" Straight Key Shaft 040
AP=	1" Straight Key Shaft 045
AQ=	1" Straight Key Shaft 050
BI=	1" Straight Key Shaft 055
BJ=	1" Straight Key Shaft 060
BK=	.88" Straight Key Shaft 020
BL=	.88" Straight Key Shaft 023
BM=	.88" Straight Key Shaft 026
BN=	.88" Straight Key Shaft 030
BO=	.88" Straight Key Shaft 032
BP=	.88" Straight Key Shaft 035
BQ=	.88" Straight Key Shaft 040
BR=	.88" Straight Key Shaft 045
BS=	.88" Straight Key Shaft 050
BT=	.88" Straight Key Shaft 055
BU=	.88" Straight Key Shaft 060

**G:** Rear Drive Gear

B=	020 W/ Auxiliary Drive
C=	023 W/ Auxiliary Drive
D=	026 W/ Auxiliary Drive
1=	030 W/ Auxiliary Drive
E=	032 W/ Auxiliary Drive
2=	035 W/ Auxiliary Drive
3=	040 W/ Auxiliary Drive

**CPE (CP 180 Tandem, SAE "B" 2-Bolt Flange, Side Ports) Modular Ordering Code, cont.****H: Rear Cover/Port Code****SAE Code 61 Split Flange, No Inlet, 1.00" Out**

AA=	Plain Rear Cover
AB=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AC=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BD=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BE=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AD=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
AE=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T

**SAE Code 61 Split Flange, No Inlet, 1.25" Out**

AF=	Plain Rear Cover
AG=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AH=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BH=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BJ=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AJ=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
AK=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T

**I: Center Section Rotation/Port Code****SAE Code 61 Split Flange Ports**

1=	LH (CCW), 2.00" Common Inlet, 1.00" Outlet
2=	RH (CW), 2.00" Common Inlet, 1.00" Outlet
3=	LH (CCW), 2.00" Common Inlet, 1.25" Outlet
4=	RH (CW), 2.00" Common Inlet, 1.25" Outlet

**J: Assembly Stud Kit**

<b>Combined Displacement*</b>		<b>Combined Displacement*</b>	
BX=	040	AT=	070
BY=	043	AT=	071
BZ=	046	DH=	072
CD=	049	DH=	073
CA=	050	AU=	075
CB=	052	DJ=	076
CB=	053	DJ=	077
CC=	055	DJ=	078
CC=	056	AV=	080
CE=	058	AV=	081
AA=	060	DL=	082
AA=	061	DL=	083
CG=	062	AZ=	085
CG=	063	DM=	086
CG=	064	DM=	087
AB=	065	BC=	090
CF=	066	DN=	092
CH=	067	BE=	095
CH=	068	BF=	100

\*NOTE: "Combined Displacement" = Equals Sum of Front and Rear Model Codes  
 Examples: 020+020=040, 050+023=073, and 040+035=075

**CPF (CP 180 Tandem, SAE "B" 2 Bolt Flange, Rear Ports) Modular Ordering Code**

**A:** CPF 180 Series Tandem Pump  
(SAE "B" 2-Bolt Flange and Rear Ports)

**B: Front Section Model**

020=	2.01 CIR (32.94 cc/rev)
023=	2.24 CIR (36.65 cc/rev)
026=	2.54 CIR (41.60 cc/rev)
030=	2.92 CIR (47.77 cc/rev)
032=	3.14 CIR (51.49 cc/rev)
035=	3.40 CIR (55.70 cc/rev)
040=	3.88 CIR (63.63 cc/rev)
045=	4.37 CIR (71.58 cc/rev)
050=	4.85 CIR (79.53 cc/rev)
055=	5.36 CIR (87.83 cc/rev)
060=	5.84 CIR (95.70 cc/rev)

**C: Rear Section Model**

020=	2.01 CIR (32.94 cc/rev)
023=	2.24 CIR (36.65 cc/rev)
026=	2.54 CIR (41.60 cc/rev)
030=	2.92 CIR (47.77 cc/rev)
032=	3.14 CIR (51.49 cc/rev)
035=	3.40 CIR (55.70 cc/rev)
040=	3.88 CIR (63.63 cc/rev)

**D: Rotation**

R=	Righthand (CW)
L=	Lefthand (CCW)

**E: Seal Kit**

2=	Buna
4=	Viton

**F: Front Drive Gear (Choose One)**

AU=	13T Spline 020
AR=	13T Spline 023
AV=	13T Spline 026
AA=	13T Spline 030
AX=	13T Spline 032
AB=	13T Spline 035
AC=	13T Spline 040
AD=	13T Spline 045
AE=	13T Spline 050
AY=	13T Spline 055
AZ=	13T Spline 060

**F: Front Drive Gear (Continued)**

BA=	15T Spline 020
AS=	15T Spline 023
BB=	15T Spline 026
AF=	15T Spline 030
BC=	15T Spline 032
AG=	15T Spline 035
AH=	15T Spline 040
AJ=	15T Spline 045
AK=	15T Spline 050
BD=	15T Spline 055
BE=	15T Spline 060
BF=	1" Straight Key Shaft 020
AT=	1" Straight Key Shaft 023
BG=	1" Straight Key Shaft 026
AL=	1" Straight Key Shaft 030
BH=	1" Straight Key Shaft 032
AM=	1" Straight Key Shaft 035
AN=	1" Straight Key Shaft 040
AP=	1" Straight Key Shaft 045
AQ=	1" Straight Key Shaft 050
BI=	1" Straight Key Shaft 055
BJ=	1" Straight Key Shaft 060
BK=	.88" Straight Key Shaft 020
BL=	.88" Straight Key Shaft 023
BM=	.88" Straight Key Shaft 026
BN=	.88" Straight Key Shaft 030
BO=	.88" Straight Key Shaft 032
BP=	.88" Straight Key Shaft 035
BQ=	.88" Straight Key Shaft 040
BR=	.88" Straight Key Shaft 045
BS=	.88" Straight Key Shaft 050
BT=	.88" Straight Key Shaft 055
BU=	.88" Straight Key Shaft 060

**G: Rear Drive Gear**

B=	020 W/ Auxiliary Drive
C=	023 W/ Auxiliary Drive
D=	026 W/ Auxiliary Drive
1=	030 W/ Auxiliary Drive
E=	032 W/ Auxiliary Drive
2=	035 W/ Auxiliary Drive
3=	040 W/ Auxiliary Drive

**CPF (CP 180 Tandem, SAE "B" 2 Bolt Flange, Rear Ports) Modular Ordering Code, cont.****H: Rear Cover/Port Code**

BB= Rear "O" Ring Boss, 1.00" In, 0.75" Out  
Plain Rear Cover

BC= Rear "O" Ring Boss, 1.25" In, 1.00" Out  
Plain Rear Cover

**I: Center Section Rotation/Port Code****SAE Code 61 Split Flange Ports**

- 1= LH (CCW), 2.00" Common Inlet, 1.00" Outlet
- 2= RH (CW), 2.00" Common Inlet, 1.00" Outlet
- 3= LH (CCW), 2.00" Common Inlet, 1.25" Outlet
- 4= RH (CW), 2.00" Common Inlet, 1.25" Outlet

**J: Assembly Stud Kit**

<u>Combined Displacement*</u>	<u>Combined Displacement*</u>
CV= 040	AT= 070
CX= 043	AT= 071
CY= 046	DH= 072
DD= 049	DH= 073
CZ= 050	AU= 075
DA= 052	DJ= 076
DA= 053	DJ= 077
DB= 055	DJ= 078
DB= 056	AV= 080
DE= 058	AV= 081
AR= 060	DL= 082
AR= 061	DL= 083
DF= 062	AZ= 085
DF= 063	DM= 086
DF= 064	DM= 087
AS= 065	BC= 090
DK= 066	DN= 092
DK= 067	BE= 095
DG= 068	BF= 100

\*NOTE: "Combined Displacement" = Equals Sum of Front and Rear Model Codes

Examples: 020+020=040, 050+023=073, and 040+035=075

## CPK (CP 180 Tandem, SAE "B" 2 Bolt Flange with PFD) Modular Ordering Code



**A:** CPK 180 Series Tandem Pump  
(SAE "B" 2-Bolt Flange and Priority Flow Divider Rear Cover)

**B: Front Section Model**

020=	2.01 CIR (32.94 cc/rev)
023=	2.24 CIR (36.65 cc/rev)
026=	2.54 CIR (41.60 cc/rev)
030=	2.92 CIR (47.77 cc/rev)
032=	3.14 CIR (51.49 cc/rev)
035=	3.40 CIR (55.70 cc/rev)
040=	3.88 CIR (63.63 cc/rev)
045=	4.37 CIR (71.58 cc/rev)
050=	4.85 CIR (79.53 cc/rev)
055=	5.36 CIR (87.83 cc/rev)
060=	5.84 CIR (95.70 cc/rev)

**C: Rear Section Model**

020=	2.01 CIR (32.94 cc/rev)
023=	2.24 CIR (36.65 cc/rev)
026=	2.54 CIR (41.60 cc/rev)
030=	2.92 CIR (47.77 cc/rev)
032=	3.14 CIR (51.49 cc/rev)
035=	3.40 CIR (55.70 cc/rev)
040=	3.88 CIR (63.63 cc/rev)

**D: Rotation**

R=	Righthand (CW)
L=	Lefthand (CCW)

**E: Seal Kit**

2=	Buna
4=	Viton

**F: Front Drive Gear (Choose One)**

AU=	13T Spline 020
AR=	13T Spline 023
AV=	13T Spline 026
AA=	13T Spline 030
AX=	13T Spline 032
AB=	13T Spline 035
AC=	13T Spline 040
AD=	13T Spline 045
AE=	13T Spline 050
AY=	13T Spline 055
AZ=	13T Spline 060

**F: Front Drive Gear (Continued)**

BA=	15T Spline 020
AS=	15T Spline 023
BB=	15T Spline 026
AF=	15T Spline 030
BC=	15T Spline 032
AG=	15T Spline 035
AH=	15T Spline 040
AJ=	15T Spline 045
AK=	15T Spline 050
BD=	15T Spline 055
BE=	15T Spline 060
BF=	1" Straight Key Shaft 020
AT=	1" Straight Key Shaft 023
BG=	1" Straight Key Shaft 026
AL=	1" Straight Key Shaft 030
BH=	1" Straight Key Shaft 032
AM=	1" Straight Key Shaft 035
AN=	1" Straight Key Shaft 040
AP=	1" Straight Key Shaft 045
AQ=	1" Straight Key Shaft 050
BI=	1" Straight Key Shaft 055
BJ=	1" Straight Key Shaft 060
BK=	.88" Straight Key Shaft 020
BL=	.88" Straight Key Shaft 023
BM=	.88" Straight Key Shaft 026
BN=	.88" Straight Key Shaft 030
BO=	.88" Straight Key Shaft 032
BP=	.88" Straight Key Shaft 035
BQ=	.88" Straight Key Shaft 040
BR=	.88" Straight Key Shaft 045
BS=	.88" Straight Key Shaft 050
BT=	.88" Straight Key Shaft 055
BU=	.88" Straight Key Shaft 060

**G: Rear Drive Gear**

B=	020 W/ Auxiliary Drive
C=	023 W/ Auxiliary Drive
D=	026 W/ Auxiliary Drive
1=	030 W/ Auxiliary Drive
E=	032 W/ Auxiliary Drive
2=	035 W/ Auxiliary Drive
3=	040 W/ Auxiliary Drive

**CPK (CP 180 Tandem, SAE "B" 2 Bolt Flange with PFD) Modular Ordering Code****H: Rear Cover/Port Code****Cover**

- CA= Priority Flow Divider Rear Cover with  
1.25" Side Split Flange Inlet and Side "O" Ring  
Boss Outlets, .375" Priority & .75" Auxiliary
- CB= Priority Flow Divider Rear Cover with  
Side "O" Ring Boss Ports, 1.25" Inlet, .375"  
Priority, & .75" Auxiliary
- CC= Priority Flow Divider Rear Cover with  
1.25" Rear "O" Ring Boss Inlet and Side "O" Ring  
Boss Outlets, .375" Priority, & .75" Auxiliary
- CD= Priority Flow Divider Rear Cover with  
1.25" Side "O" Ring Boss Inlet and .375" Side  
Priority Outlet, and .75" Top Auxiliary Outlet
- CE= Auxiliary Priority Flow Divider Rear Cover,  
NON-Inlet and .375" Side Priority Outlet  
.75" Auxiliary Outlet

**I: Center Section Rotation/Port Code****SAE Code 61 Split Flange Ports**

- 1= LH (CCW), 2.00" Common Inlet, 1.00" Outlet
- 2= RH (CW), 2.00" Common Inlet, 1.00" Outlet
- 3= LH (CCW), 2.00" Common Inlet, 1.25" Outlet
- 4= RH (CW), 2.00" Common Inlet, 1.25" Outlet

**J: Assembly Stud Kit****Combined Displacement\***

CV= 040  
CX= 043  
CY= 046  
DD= 049  
CZ= 050  
DA= 052  
DA= 053  
DB= 055  
DB= 056  
DE= 058  
AR= 060  
AR= 061  
DF= 062  
DF= 063  
DF= 064  
AS= 065  
DK= 066  
DK= 067  
DG= 068

**Combined Displacement\***

AT= 070  
AT= 071  
DH= 072  
D= 073  
AU= 075  
DJ= 076  
DJ= 077  
DJ= 078  
AV= 080  
AV= 081  
DL= 082  
DL= 083  
AZ= 085  
DM= 086  
DM= 087  
BC= 090  
DN= 092  
BE= 095  
BF= 100

\*NOTE: "Combined Displacement" = Equals Sum of  
Front and Rear Model Codes  
Examples: 020+020=040, 050+023=073, and 040+035=075

**CPG (CP 180 Tandem, SAE "B" 4 Bolt Flange, Side Ports), Modular Ordering Code****A: CPG 180 Series Tandem Pump  
(SAE "B" 4-Bolt Flange and Side Ports)****B: Front Section Model**

020= 2.01 CIR (32.94 cc/rev)  
 023= 2.24 CIR (36.65 cc/rev)  
 026= 2.54 CIR (41.60 cc/rev)  
 030= 2.92 CIR (47.77 cc/rev)  
 032= 3.14 CIR (51.49 cc/rev)  
 035= 3.40 CIR (55.70 cc/rev)  
 040= 3.88 CIR (63.63 cc/rev)  
 045= 4.37 CIR (71.58 cc/rev)  
 050= 4.85 CIR (79.53 cc/rev)  
 055= 5.36 CIR (87.83 cc/rev)  
 060= 5.84 CIR (95.70 cc/rev)

**C: Rear Section Model**

020= 2.01 CIR (32.94 cc/rev)  
 023= 2.24 CIR (36.65 cc/rev)  
 026= 2.54 CIR (41.60 cc/rev)  
 030= 2.92 CIR (47.77 cc/rev)  
 032= 3.14 CIR (51.49 cc/rev)  
 035= 3.40 CIR (55.70 cc/rev)  
 040= 3.88 CIR (63.63 cc/rev)

**D: Rotation**

R= Righthand (CW)  
 L= Lefthand (CCW)

**E: Seal Kit**

2= Buna  
 4= Viton

**F: Front Drive Gear (Choose One)**

AU= 13T Spline 020  
 AR= 13T Spline 023  
 AV= 13T Spline 026  
 AA= 13T Spline 030  
 AX= 13T Spline 032  
 AB= 13T Spline 035  
 AC= 13T Spline 040  
 AD= 13T Spline 045  
 AE= 13T Spline 050  
 AY= 13T Spline 055  
 AZ= 13T Spline 060

**F: Front Drive Gear (Continued)**

BA=	15T Spline 020
AS=	15T Spline 023
BB=	15T Spline 026
AF=	15T Spline 030
BC=	15T Spline 032
AG=	15T Spline 035
AH=	15T Spline 040
AJ=	15T Spline 045
AK=	15T Spline 050
BD=	15T Spline 055
BE=	15T Spline 060
BF=	1" Straight Key Shaft 020
AT=	1" Straight Key Shaft 023
BG=	1" Straight Key Shaft 026
AL=	1" Straight Key Shaft 030
BH=	1" Straight Key Shaft 032
AM=	1" Straight Key Shaft 035
AN=	1" Straight Key Shaft 040
AP=	1" Straight Key Shaft 045
AQ=	1" Straight Key Shaft 050
BI=	1" Straight Key Shaft 055
BJ=	1" Straight Key Shaft 060
BK=	.88" Straight Key Shaft 020
BL=	.88" Straight Key Shaft 023
BM=	.88" Straight Key Shaft 026
BN=	.88" Straight Key Shaft 030
BO=	.88" Straight Key Shaft 032
BP=	.88" Straight Key Shaft 035
BQ=	.88" Straight Key Shaft 040
BR=	.88" Straight Key Shaft 045
BS=	.88" Straight Key Shaft 050
BT=	.88" Straight Key Shaft 055
BU=	.88" Straight Key Shaft 060

**G: Rear Drive Gear**

B=	020 W/ Auxiliary Drive
C=	023 W/ Auxiliary Drive
D=	026 W/ Auxiliary Drive
1=	030 W/ Auxiliary Drive
E=	032 W/ Auxiliary Drive
2=	035 W/ Auxiliary Drive
3=	040 W/ Auxiliary Drive

**CPG (CP 180 Tandem, SAE "B" 4 Bolt Flange, Side Ports), Modular Ordering Code, cont.****H: Rear Cover/Port Code****SAE Code 61 Split Flange, No Inlet, 1.00" Out**

AA=	Plain Rear Cover
AB=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AC=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BD=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BE=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AD=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
AE=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T

**SAE Code 61 Split Flange, No Inlet, 1.25" Out**

AF=	Plain Rear Cover
AG=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 9T
AH=	RH (CW) Aux. W/ SAE "A" 2 Bolt 9T
BH=	LH (CCW) Aux. W/ SAE "A" 2 Bolt 11T
BJ=	RH (CW) Aux. W/ SAE "A" 2 Bolt 11T
AJ=	LH (CCW) Aux. W/ SAE "B" 2 Bolt 13T
AK=	RH (CW) Aux. W/ SAE "B" 2 Bolt 13T

**I: Center Section Rotation/Port Code****SAE Code 61 Split Flange Ports**

1=	LH (CCW), 2.00" Common Inlet, 1.00" Outlet
2=	RH (CW), 2.00" Common Inlet, 1.00" Outlet
3=	LH (CCW), 2.00" Common Inlet, 1.25" Outlet
4=	RH (CW), 2.00" Common Inlet, 1.25" Outlet

**J: Assembly Stud Kit**

Combined Displacement*	Combined Displacement*
DT= 040	BJ= 070
DU= 043	BJ= 071
DV= 046	EK= 072
DZ= 049	ED= 073
DW= 050	BK= 075
DX= 052	EE= 076
DX= 053	EE= 077
DY= 055	EE= 078
DY= 056	BL= 080
EA= 058	BL= 081
BG= 060	EF= 082
BG= 061	EF= 083
EB= 062	BQ= 085
EB= 063	EH= 086
EB= 064	EH= 087
BH= 065	BT= 090
EG= 066	EL= 092
EJ= 067	BV= 095
EC= 068	BW= 100

\*NOTE: "Combined Displacement" = Equals Sum of Front and Rear Model Codes

Examples: 020+020=040, 050+023=073, and 040+035=075





## Hydraulic Power Systems

### SAUER-SUNDSTRAND Hydraulic Power Systems - Market Leaders Worldwide

SAUER-SUNDSTRAND is a world leader in the design and manufacture of Hydraulic Power Systems. Research and development resources in both North America and Europe enable SAUER-SUNDSTRAND to offer a wide range of design solutions utilizing hydraulic power system technology.

SAUER-SUNDSTRAND specializes in integrating a full range of system components to provide vehicle designers with the most advanced total-design system.

SAUER-SUNDSTRAND is Your World Source for Controlled Hydraulic Power Systems.

### Worldwide Service Support

SAUER-SUNDSTRAND provides comprehensive worldwide service for its products through an extensive network of Authorized Service Centers strategically located in all parts of the world.

Look to SAUER-SUNDSTRAND for the best in WORLDWIDE SERVICE.

