Fujitsu recommends Windows.



Data Sheet FUJITSU LIFEBOOK S935 Notebook

Your Stylish Marathon Runner

The FUJITSU Notebook LIFEBOOK S935 is a lightweight, touch-enabled notebook for frequent travelers. An ideal travel companion, it combines full functionality with an exceptional lightweight design starting at 1.24 kg and a battery runtime spanning over two working days. Its crystal clear 33.8 cm (13.3-inch) WQHD anti-glare display option enables best viewing comfort. Numerous features, such as Fujitsu's famous modular bay concept, optional 4*G*/LTE connectivity and a backlit keyboard help you to concentrate on your business while on the move. Moreover, a wide range of enterprise class security features and the unique palm vein sensor option guarantee ultimate protection of your company data. Choose the port replicator for best-in-class convenience in the office.

A stylish runner

Enjoy stylish design with no compromise on runtime

Sleek notebook design, up to two working days runtime with first and second battery, modular bay for optical disk drive, second hard disk drive or second battery

Superb mobility

Work and be online wherever you want

Exceptional lightweight starting at 1.24 kg, with a sturdy magnesium housing and aluminum palm rest, optional 4G/LTE connectivity, optional NFC

Ultimate security

Protect your notebook and company data against unauthorized access

■ Embedded palm vein sensor or fingerprint sensor option, integrated SmartCard reader, encrypted disk, ATP, TPM option

Best-in-class user experience

Combines business class productivity with a comfortable user experience

 High resolution (2560x1440) WQHD IGZO display with anti-glare, non-touch or glare, touch option, backlit keyboard, port replicator option









Page 1 / 7 www.fujitsu.com/fts/mobile

Components

Drococcor	Intel® Core™ i5-5200U processor (2.1 GHz, up to 2.7 GHz, 3 MB) *
Processor	Intel® Core™ i7-5600U processor (2.6 GHz, up to 3.2 GHz, 4 MB)
	Intel® Core™ i5-5300U processor (2.6 GHz, up to 3.2 GHz, 4 MB)
	*Processor only for retail, SMB, education and government Intel® Core™ vPro™ Processor - Best Platform for Businesses of all sizes
	IIITEL® COTE ANTO MOCESSOL - REST MATIOLIII IOL BRISILIESSES OL ALI SISES
Operating systems	
Operating system	Windows 8.1 Pro 64-bit Windows 8.1 64-bit
	Windows 7 Professional 64-bit
Memory modules	4 GB (1 module(s) 4 GB) DDR3 L, 1,600 MHz, PC3-12800, SO DIMM
	8 GB (1 module(s) 8 GB) DDR3 L, 1,600 MHz, PC3-12800, SO DIMM
Hard disk drives (internal)	SSHD, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch, OPAL capable
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SATA, 5,400 rpm, 1 TB, 2.5-inch, S.M.A.R.T.
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
	Accessible capacity may vary, also depending on used software.
	Up to 20 GB of HDD space is reserved for system recovery
	Internal HDD interface: S-ATA III (6GBit/s)
Modular bay options	2nd battery
	Blu-ray Disc™ Triple Writer
	DVD Super Multi
	Weight saver
Interface add on cards/components	
(optional)	
3G/4G (optional)	Sierra Wireless EM8805 (Downlink speed 42 Mbit/s, Uplink speed 5.76 Mbit/s)
	LTE Sierra Wireless EM7305 (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s)
WLAN (optional)	Intel® Wireless-N 7265 2x2 b/g/n with integrated Bluetooth 4.0
	Intel® Dual Band Wireless-N 7265 2x2 ac with integrated Bluetooth 4.0
Display	33.8 cm (13.3-inch), LED backlight, (WQHD), Glare IGZO touch display, magnesium, 2,560 x 1,440 pixel, 1,000:1, 350
	cd/m ²
	33.8 cm (13.3-inch), LED backlight, (WQHD), Anti-glare IGZO non-touch display, magnesium, 2,560 x 1,440 pixel,
	1,000:1, 350 cd/m ²
	33.8 cm (13.3-inch), LED backlight, (Full HD), Glare IGZO touch display, magnesium, 1,920 \times 1,080 pixel, 1,000:1, 350 cd/m ²
	33.8 cm (13.3-inch), LED backlight, (Full HD), Anti-glare IGZO non-touch display, magnesium, 1,920 x 1,080 pixel,
	33.0 cm (13.3-meth), EED backlight, (1 mil 110), Anti-glate 1020 hon-touch display, magnesium, 1,320 x 1,000 pixer, 1,000:1, 350 cd/m²
Multimedia	
Camera	Built-in webcam, HD (Microsoft® Lync™)

Base unit

Base unit	LIFFROOK \$935.13.3-inch black/silver
base unit	LII LUOON 3333 13.3 IIICII DIGCN3IIVCI

Integrated Int	General system information	
Supports And 11.00 Intel® Anomalia		Integrated
inicial* North Registration 1 DIAM (DIASTA) 1 DIAM (DIA	-	
Memory notes	Memory slots	1 DIMM (DDR3L)
A 4.60 enboard. 1 DMM slot with max. 8 (.08 AN Bull-in 10/10/21.000 MBbus Innel® 7 IBLM 8005 features BIOS based on Phoenix SecureCore varior features Stereo speakers Display Uniform Stereo Speakers Uniform Stereo Speakers Display Uniform Stereo Speakers Uni	Supported capacity RAM (max.)	12 GB
BIOS based on Phoenix SecureCore	Memory notes	
Nuclei type Undio code	LAN	Built-in 10/100/1,000 MBit/s Intel® 218LM
Nucleic code Realteck AI C283 (HD audio) Nucleic features Steroes peakers Sizylay Service of Sepakers Display notes 150 9241-307 - Pixel class II Siaphics Saace unit II FEBOOK \$935 13.3 inch black/silver FF resolution (MA) up to 1,920 x 1,200 FF resolution (MOA) up to 1,920 x 1,200 FF resolution (DisplayPort on Port up to 3,200 x 2,000 Replicator) up to 3,200 x 2,000 Explication (DisplayPort on Port up to 3,200 x 2,000 Explication (DisplayPort on Port up to 3,200 x 2,000 Explication (DisplayPort on Port up to 3,200 x 2,000 Explication (DisplayPort on Port up to 3,200 x 2,000 Explication (DisplayPort on Port up to 3,200 x 2,000 Explication (DisplayPort on Port up to 3,200 x 2,000 Explication (DisplayPort on Port up to 3,200 x 2,000 Explication (DisplayPort on Port up to 3,200 x 2,000 Medication (DisplayPort on Port (Display Port O	BIOS features	BIOS based on Phoenix SecureCore
	Audio type	On board
Display notes 150 9241-307 - Pixel class II	Audio codec	Realtek ALC283 (HD audio)
	Audio features	Stereo speakers
Sase unit LIFEBOOK S935 13.3-inch black/silver Fir resolution (MDMI) up to 4,096 × 2,160 Fir resolution (VGA) up to 1,920 x 1,200 Fir resolution (DVI on Port Replicator) Fir resolution (DVI on Port Replicator) Intel® HID Graphics 5500 Sarphics features 3 bisplay Support Sarphics features 3 bisplay Support Traphics notes Shared memory depending on main memory size and operating system Interfaces V-Cin 1 (combo port with Audio line-in) Audio: line-in / microphone 1 (combo port with Audio line-enu) Intelment (R)-45) 1 Statement (R)-45) 1 Statement (R)-45) 1 Microphics on switch 1 (soli up to 268, SDHC up to 3268, SDXC up to 12868) Simulaticard slot 1 (only for models with integrated 3G/UMTS or 4G/LTE module) V-Cin 1 (199V) Over replicator interfaces (optional) V-Cin 1 (up to 1920 x 1200) VI (up to 1920 x 1200) VI (up to 1920 x 1200) VI (up to 1920 x 1200) Vicebenet (R)-45) 1 (up to 1920 x 1200) Vicebenet (R)-45) 8 1 (up to 1920 x 1200) Vicebenet (R)-45) 8 1 (up to 1920 x 1200) Vicebenet (R)-45) 8 1 (up to 1920 x 1200) Vicebenet (R)-45) 8 1 (up to 1920 x 1200) Vicebenet (R)-45) 8 8 (kilt isolation keyboard Mumber of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality Ecolution Control	Display	
Base unit LIFEBOOK S935 13.3-inch black/sliver FT resolution (HDMI) up to 1,906 × 2,160 FT resolution (VCA) up to 1,920 x 1,200 FT resolution (DisplayPort on Port Replicator) up to 1,920 x 2,000 FT resolution (DisplayPort on Port Replicator) up to 3,200 x 2,000 Graphics brand name Intel® HD Graphics 5500 Graphics features 3 Display Support Targetist and the control of the properties of of	Display notes	ISO 9241-307 - Pixel class II
Base unit LIFEBOOK S935 13.3-inch black/sliver FT resolution (HDMI) up to 1,906 × 2,160 FT resolution (VCA) up to 1,920 x 1,200 FT resolution (DisplayPort on Port Replicator) up to 1,920 x 2,000 FT resolution (DisplayPort on Port Replicator) up to 3,200 x 2,000 Graphics brand name Intel® HD Graphics 5500 Graphics features 3 Display Support Targetist and the control of the properties of of	Graphics	
FT resolution (DMI)	Base unit	LIFEBOOK S935 13.3-inch black/silver
FFT resolution (VGA) up to 1,920 x 1,200 FFT resolution (DWI on Port Replicator) up to 1,920 x 1,200 Treplicator) up to 3,200 x 2,000 Traphics brand name intel® HD Graphics 5500 Traphics brand name interfaces Traphics notes Shared memory depending on main memory size and operating system Traphics notes Interfaces DC-in I (combo port with Audio line-in) Audio: line-in / microphone I (combo port with Audio line-out) Traphics notes I (digital) SDS 3,0 total I (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) TransmartCard Slot I (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) TransmartCard Slot I (19V) Towns on switch I (19V)	TFT resolution (HDMI)	
IFT resolution (DisplayPort on Port Replicator) up to 3,200 x 2,000 IFT resolution (DisplayPort on Port Replicator) up to 3,200 x 2,000 Graphics brand name Intel® HD Graphics 5500 Graphics features 3 bisplay Support Graphics features 3 bisplay Support Transcriptions notes 2 bisplay Support Interfaces 4 combo port with Audio Inne-in/ Undio: Inne-in / Incrophone 1 (combo port with Audio Inne-out) Using Inne-in / microphones 2 (digital) USB 3.0 total 3 (1 with Anytime USB Charge functionality) UGA 1 Ethernet (R)-45) 1 Memory and slots 1 (50 up to 2GB, SDHC up to 32GB, SDXC up to 128GB) StartCard slot 1 (19V) Obver on switch 1 (19V) Obver on switch 1 (19V) Obver on switch 1 (up to 3200 x 2000) UGA 1 (up to 1920 x 1200) UGA 1 (up to 1920 x 1200) Celement (R)-45) 1 (up to 1920 x 1200) Celement (R)-45) 1 (up to 1920 x 1200) Celement (R)-45) 1 (up to 1920 x 1200)	TFT resolution (VGA)	
Replicator) Finaphics brand name Finaphics notes Shared memory depending on main memory size and operating system Interfaces OC-in I (combo port with Audio line-out) Audio: line-in / microphone I (combo port with Audio line-out) Audio: line-in / microphone I (combo port with Audio line-out) Audio: line-in / microphone I (combo port with Audio line-out) Audio: line-in / microphone I (digital) SSB 3.0 total I (digital) SSB 3.0 total I (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) Memory card slots I (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) Memory card slots I (solly for models with integrated 3G/UMTS or 4G/LTE module) Port Replicator interfaces (optional) FOC-in I (19V) Power on switch I (19V) Power on switch I (up to 3200 x 2000) AUGA I (up to 3200 x 2000) AUGA I (up to 1920 x 1200) Ethernet (R)-45) I (up to 1920 x 1200) Augustian Lock support Augustian Lock support of replicator supports 0-Watts functionality Ecophoral Augustian Lock support Augustian Lock support of Lock supports 0-Watts functionality Ecophoral Augustian Lock support of Lock and pointing devices Backlit isolation keyboard Augustian Lock support of Lock uncouchad with integrated mouse button functionality Ecophoral Augustian Lock support of Lock uncouchad with integrated mouse button functionality Ecophoral Lock uncounted and pointing devices Backlit isolation keyboard Augustian Lock support of Lock uncouchad with integrated mouse button functionality Ecophoral Lock uncounted and pointing devices Backlit isolation keyboard Augustian Lock support of Lock uncouchad with integrated mouse button functionality Ecophoral Lock uncounted and pointing devices Backlit isolation keyboard Augustian Lock uncounted and with integrated mouse button functionality Ecophoral Lock uncounted and pointing devices Augustian Lock uncoun	TFT resolution (DVI on Port Replicator)	·
Traphics brand name Intel® HD Graphics 5500 Traphics features 3 Display Support Shared memory depending on main memory size and operating system Interfaces TOC in 1 (combo port with Audio line-in) Audio: line-in / microphone 1 (combo port with Audio line-in) Audio: line-in / microphone 1 (combo port with Audio line-out) Audio: line-in / microphone 2 (digital) AUSB 3.0 total 3 (1 with Anytime USB Charge functionality) AUGA 1 (CA 1 (C	TFT resolution (DisplayPort on Port	up to 3,200 x 2,000
Traphics features 3 Display Support Shared memory depending on main memory size and operating system Interfaces Oct-in 1 (combo port with Audio line-in) Audio: line-out / headphone 1 (combo port with Audio line-out) Audio: line-in / microphone 1 (combo port with Audio line-out) Audio: line-in / microphone 1 (combo port with Audio line-out) Audio: line-in / microphone 2 (digital) ISB 3.0 total 3 (1 with Anytime USB Charge functionality) IGA 1 (Audio: line-in / microphone 2 (digital) I (SU pub to 2GB, SDHC up to 32GB, SDXC up to 128GB) I (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) I (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) I (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) I (I (up) for models with integrated 3G/UMTS or 4G/LTE module) Port Replicator interfaces (optional) Port Replicator interfaces (optional) I (up to 3200 x 2000) I (up to 1920 x 1200) Molti gesture touchpad with integrated mouse button functionality Everboard and pointing devices Backlit isolation keyboard Multi gesture touchpad with integrated mouse button functionality EcoButton	Replicator)	
Interfaces DC-in 1 (combo port with Audio line-in) Audio: line-in / microphone 1 (combo port with Audio line-in) Audio: line-in / microphone 1 (combo port with Audio line-out) Audio: line-in / microphone 1 (combo port with Audio line-out) Audio: line-in / microphone 2 (digital) JSB 3.0 total 3 (1 with Anytime USB Charge functionality) JSB 3.0 total 3 (1 with Anytime USB Charge functionality) JSB 3.0 total 1 (SD up to 2GB, SDHC up to 3ZGB, SDXC up to 128GB) JSB 3.0 total 1 (SD up to 2GB, SDHC up to 3ZGB, SDXC up to 128GB) JSB 3.0 total 1 (Inply for models with integrated 3G/UMTS or 4G/LTE module) Power on switch 1 (199V) JSB 3.0 total 4 (199V) JSB 3.0 total 4 (1990 to 3200 x 2000) JSB 3.0 total 4 (1990 to 3200 x 2000) JSB 3.0 total 1 (up to 1920 x 1200) JSB 3.0 total 1 (up to 1920 x 1200) JSB 3.0 total 1 (up to 1920 x 1200) JSB 3.0 total 2 (1990 to 1900 x 1200) JSB 3.0 total 3 (1990 to 1900 x 1200) JSB 3.0 total 4 (1990 to 1900 x 1200) JSB 3.0 total 4 (1990 to 1900 x 1200) JSB 3.0 total 5 (1990 to 1900 x 1200) JSB 3.0 total 6 (1990 to 1900 x 1200) JSB 3.0 total 7 (1990 to 1900 x 1200) JSB 3.0 total 8 (1990 to 1900 x 1200) JSB 3.0 total 9 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 to 1900 x 1200) JSB 3.0 total 1 (1990 x 1200 x 1200) JSB 3.0 total 1 (1990 x	Graphics brand name	Intel® HD Graphics 5500
Interfaces OC-in 1 (combo port with Audio line-in) Audio: line-out / headphone 1 (combo port with Audio line-in) Audio: line-in / microphone 1 (combo port with Audio line-out) Internal microphone 2 (digital) ISB 3.0 total 3 (1 with Anytime USB Charge functionality) IGA 1 IOMI 1 ICOMINI	Graphics features	· / · · ·
Audio: line-out / headphone Audio: line-out / headphone Audio: line-in / microphone 1 (combo port with Audio line-out) Audio: line-in / microphone 1 (combo port with Audio line-out) Audio: line-in / microphone 2 (digital) JSB 3.0 total 3 (1 with Anytime USB Charge functionality) JGA 1 The statement (RJ-45) 1 The statement (RJ-45) 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) JGM Card slots 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) JGM Card slots 1 (only for models with integrated 3G/UMTS or 4G/LTE module) PORT Replicator interfaces (optional) PORT Replicator interfaces (optional) JGA 1 (up to 3200 x 2000) JGA 1 (up to 3200 x 2000) JGA 1 (up to 1920 x 1200) JGA 1 (up to 1920 x 1200) JGA 1 (up to 1920 x 1200) JGA Audio: Au	Graphics notes	Shared memory depending on main memory size and operating system
Audio: line-out / headphone 1 (combo port with Audio line-in) Audio: line-in / microphone 1 (combo port with Audio line-out) Audio: line-in / microphone 1 (combo port with Audio line-out) 2 (digital) 3 (1 with Anytime USB Charge functionality) AUGA 1 AUDIO 1 A	Interfaces	
Audio: line-in / microphone 1 (combo port with Audio line-out) Internal microphones 2 (digital) ISB 3.0 total 3 (1 with Anytime USB Charge functionality) IGA 1 IDMI 1 ICHIENTER (RJ-45) 1 IMMEMORY card slots 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) IMMEMORY card slots 1 (only for models with integrated 3G/UMTS or 4G/LTE module) FORT Replicator interfaces (optional) IOSB 3.0 total 4 IOSB 3.0 total 5 IOSB 3.0 total 6 IOSB 3.0 total 7 IOSB 3.0 total 7 IOSB 3.0 total 8 IOSB 3.0 total 9 IOSB 3.0 total 9 IOSB 3.0 total 1 IOSB 3.0 total 1 IOSB 3.0 total 1 IOSB 3.0 total 3 IOSB 3.0 total 4 IOSB 3.0 total 4 IOSB 3.0 total 5 IOSB 3.0 total 6 IOSB 3.0 total 7 IOSB 3.0 total 7 IOSB 3.0 total 8 IOSB 3.0 total 9 IOS	DC-in	1
ISB 3.0 total 3 (1 with Anytime USB Charge functionality) ISB 3.0 total 3 (1 with Anytime USB Charge functionality) ISB 3.0 total 1 1 ISB 3.0 total 1 1 ISB 3.0 total 1 1 ISB 4.0 total 1 1 ISB 6.0 total 1 1 ISB 6.0 total 1 1 ISB 6.0 total 1 1 ISB 3.0 total 1 1 ISB 4.0 total 1 1 ISB 5.0 total 1 1 ISB 5.0 total 1 1 ISB 6.0 total	Audio: line-out / headphone	1 (combo port with Audio line-in)
3 (1 with Anytime USB Charge functionality) (GA 1 10MI 1 1 1 10thernet (RJ-45) 1 Memory card slots 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) isinartCard slot 1 (only for models with integrated 3G/UMTS or 4G/LTE module) cort Replicator interfaces (optional) Cort Replicator interfaces (optional) Cover on switch 1 1 (19V) Cover on switch 1 1 (up to 3200 x 2000) (GA 1 (up to 1920 x 1200) OVI 1 (up to 1920 x 1200) Cotter (RJ-45) 1 (10/100/1000) Cotter (RJ-45)	Audio: line-in / microphone	1 (combo port with Audio line-out)
In the state of th	Internal microphones	2 (digital)
HDMI 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) Memory card slots 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) MinartCard slot 1 (only for models with integrated 3G/UMTS or 4G/LTE module) Port Replicator interfaces (optional) Port Replicator interfaces (optional) Power on switch 1 (19V) Power on switch 1 (up to 3200 x 2000) MGA 1 (up to 3200 x 2000) MGA 1 (up to 1920 x 1200) Port Replicator interfaces (RJ-45) 1 (10/100/1000) Retermet (RJ-45) 1 (10/100/1000) Retermet (RJ-45) 1 (10/100/1000) Retermet (RJ-45) 1 (10/100/1000) Retermination Lock support 1 x (Port rep only) Notes Port replicator supports 0-Watts functionality Reyboard and pointing devices Multi gesture touchpad with integrated mouse button functionality EcoButton	USB 3.0 total	3 (1 with Anytime USB Charge functionality)
Ethernet (R)-45) Memory card slots I (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) FinartCard slot I (only for models with integrated 3G/UMTS or 4G/LTE module) Port Replicator interfaces (optional) Port Repl	VGA	1
Memory card slots 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB) finartCard slot 1 (only for models with integrated 3G/UMTS or 4G/LTE module) Port Replicator interfaces (optional) Port Replicator interfaces (optional) Power on switch 1 (199) Power on switch 1 (up to 3200 x 2000) POGA 1 (up to 1920 x 1200) POGA 1 (up to 1920 x 1200) POGA 1 (up to 1920 x 1200) Potenter (RJ-45) 1 (10/100/1000) Rensington Lock support 1x (Port rep only) Rotes Port replicator supports 0-Watts functionality Reyboard and pointing devices Residut isolation keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton	HDMI	
Sind card slot 1 (only for models with integrated 3G/UMTS or 4G/LTE module) Port Replicator interfaces (optional) Power on switch 1 (19V) Power on switch 1 (up to 3200 x 2000) JOSB 3.0 total 4 (up to 3200 x 2000) JOSB 3.0 total 1 (up to 1920 x 1200) JOSB 3.0 total 1 (up to 1920 x 1200) JOSB 3.0 total 1 (up to 1920 x 1200) JOSB 3.0 total 1 (up to 1920 x 1200) JOSB 3.0 total 2 (up to 1920 x 1200) JOSB 3.0 total 3 (up to 1920 x 1200) JOSB 3.0 total 4 (up to 1920 x 1200) JOSB 3.0 total 5 (up to 1920 x 1200) JOSB 3.0 total 6 (up to 1920 x 1200) JOSB 3.0 total 7 (up to 1920 x 1200) JOSB 3.0 total 7 (up to 3200 x 2000) JOSB		'
Soft Replicator interfaces (optional) OC-in 1 (19V) Ower on switch 1 USB 3.0 total 4 OisplayPort 1 (up to 3200 x 2000) OVI 1 (up to 1920 x 1200) OVI 1 (up to 1920 x 1200) Other in (Rj-45) 1 (10/100/1000) Kensington Lock support 1x (Port rep only) Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Backlit isolation keyboard Multi gesture touchpad with integrated mouse button functionality EcoButton 1 (only for models with integrated a Gr/UMTS or 4G/LTE module) 1 (19V) 1 (19V) 1 (up to 3200 x 2000) 1 (up to 1920 x 1200)		1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB)
Port Replicator interfaces (optional) OC-in 1 (19V) Power on switch 1 JSB 3.0 total 4 OisplayPort 1 (up to 3200 × 2000) JGA 1 (up to 1920 x 1200) OVI 1 (up to 1920 x 1200) Ethernet (RJ-45) 1 (10/100/1000) Kensington Lock support 1x (Port rep only) Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton		1 / b. (d-l
Power on switch 1 USB 3.0 total 4 DisplayPort 1 (up to 3200 x 2000) VGA 1 (up to 1920 x 1200) Ethernet (RJ-45) 1 (10/100/1000) Kensington Lock support 1x (Port rep only) Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Multi gesture touchpad with integrated mouse button functionality EcoButton 1 (19V) 1 (19V) 1 (up to 3200 x 2000) 1 (up to 1920 x 1200) 1 (10/100/1000) 1 (10/100/1000) 1 (Port rep only) 1 (Port rep only) Multi gesture touchpad with integrated mouse button functionality EcoButton		(only for models with integrated 30/0MTS of 40/LTE module)
Power on switch JSB 3.0 total 4 DisplayPort 1 (up to 3200 x 2000) JGA 1 (up to 1920 x 1200) DVI 1 (up to 1920 x 1200) Ethernet (RJ-45) 1 (10/100/1000) Kensington Lock support 1x (Port rep only) Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton		
JSB 3.0 total Ji (up to 3200 x 2000) JGA 1 (up to 1920 x 1200) July to 1920 x 1200 July		
DisplayPort 1 (up to 3200 x 2000) (GA 1 (up to 1920 x 1200) 2 (up to 1920 x 1200) 2 (thernet (RJ-45) 1 (10/100/1000) 3 (Port rep only) 4 (Port rep only) 5 (ensington Lock support) 7 (Port rep only) 8 (eyboard and pointing devices 8 (eyboard and pointing devices 8 (Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton		
I (up to 1920 x 1200) I (up to 1920 x 1200) I (up to 1920 x 1200) I (10/100/1000) Kensington Lock support		
DVI 1 (up to 1920 x 1200) Ethernet (RJ-45) 1 (10/100/1000) Kensington Lock support 1x (Port rep only) Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton	<u> </u>	
Ethernet (RJ-45) 1 (10/100/1000) Kensington Lock support 1x (Port rep only) Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton		
Kensington Lock support Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton		
Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton	· · · · · · · · · · · · · · · · · · ·	
Keyboard and pointing devices Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton	Notes	
Backlit isolation keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton		1
Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.2 mm Multi gesture touchpad with integrated mouse button functionality EcoButton	reyouard and politting devices	Backlit isolation keyboard
Multi gesture touchpad with integrated mouse button functionality EcoButton		
EcoButton		
Status LED		
		Status LED

Page 3 / 7

Wireless technologies	
Antennas	2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional, 1 Bluetooth antenna shared with WLAN
WLAN notes	Import and usage according to country-specific regulations.
NFC	optional
Power supply	
AC Adapter	19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter
·	19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology
	19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter
Notes	65W AC Adapter for usage with system/ min. 80W AC Adapter for usage with Port Replicator
1st battery options	Li-lon battery 4-cell, 3,550 mAh, 51 Wh
	Li-lon battery 6-cell, 7,100 mAh, 77 Wh
2nd battery (optional)	Li-lon battery 6-cell, 2,600, mAh, 28 Wh
Runtime 1st battery	Up to 37:00 h (MM2007), Up to 16:30 h (MM2012) (tbc)
Runtime 1st + 2nd battery	Up to 50:30 h (MM2007), Up to 22:30 h (MM2012) (tbc)
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2007 (readers mode) and BAPCo® MobileMark® 2012 (office productivity) see www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.
Noise emission	
Noise emission	Please refer to the Eco Declaration
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	319 mm (12.56 inch) x 215 mm (8.46 inch) x 26.5 mm (1.04 inch)
Weight	1.24 kg (2.73 lb) with non-touch display, 1.37 kg (3.02 lb) with touch display
Weight notes	Weight may vary depending on actual configuration
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	20 - 85 %
Compliance	
Europe	CE
	СВ
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.0 EPEAT® Gold (dedicated regions) (planned)
Compliance notes	Above mentioned compliances are planned but not available at preliminary stage.
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Fujitsu LIFEBOOK Application Panel Fujitsu Display Manager ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Win8.1: Microsoft Push Button Recovery (hard disk based recovery) Win7: Fujitsu Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Connection manager (optional with 4G/LTE or 3G/UMTS) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Recovery DVD for Windows®

Page 4 / 7 www.fujitsu.com/fts/mobile

. Late	
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intel® vPro™ technology WoL (Wake on LAN) iAMT 10.0 (depending on CPU)
Manageability software	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI PXE BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/solutions/business-technology/manageability/feature-finder.html
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Computrace® ready BIOS Advanced Theft Protection (Computrace® only) Optional: Trusted platform module (TPM 1.2) EraseDisk (optional)
User Security	Hard disk password User and supervisor BIOS password Embedded fingerprint sensor (optional) Workplace Protect (secure authentication solution) Smartcard reader (integrated) SystemLock BIOS SmartCard security Embedded palm vein sensor (optional)
Warranty	
Standard Warranty	2 years (depending on country)
Service level	Collect & Return Service / Bring-in Service (depending on country specific requirements)
Warranty Terms & Conditions Product Support Services - the per	http://support.ts.fujitsu.com/warranty fect extension
Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	htttp://ts.fujitsu.com/Supportservice

Recommended Accessories

Page 5 / 7 www.fujitsu.com/fts/mobile

Port Replicator



Flexibility, expandability, desktop replacement and investment protection are just a few benefits of Fujitsu docking options. It takes just a second to attach your notebook to the Port Replicator and get connected to your external display, keyboard and mouse. Your workplace is simple and tidy while you are instantly ready to work with your notebook.

Order Code: S26391-F1307-L100

LIFEBOOK Bundle (Port Replicator, AC Adapter, EU Cable Kit)



The combination of a Fujitsu Port Replicator and AC Adapter (with EU cable) Order Code: is the perfect docking solution for your LIFEBOOK. Simplify your mobile life. S26391-F1307-L110 In the office or at home it takes just a second to attach your notebook to the port replicator and get connected to your peripherals.

AC Adapter LIFEBOOK



Power your notebook at work, at home or on the road with a second power Order Code: source. You can easily recharge your notebook everywhere. Depending on your notebook you can choose from various AC Adapters ranging from a slim stick type adapter to standard adapters, or even the innovative 0-Watt AC Adapter.

S26391-F1246-L500

Second Battery for Modular Bay



Modern business demands that busy professionals be ready to meet customers, make presentations, and work wherever is necessary to get the job done. With a Second Battery for your Fujitsu LIFEBOOK you will be more flexible than ever. Installation is effortless. Just slide the Second Battery into your Fujitsu LIFEBOOK's modular bay.

Order Code: S26391-F1304-L500

Privacy filter



Privacy filters help block the screen view from anyone viewing the computer Order Code: from a side view. 3M's unique microlouver privacy technology allows persons directly in front of the computer to see on-screen data clearly

S26391-F6097-L361

Sleeve Case M



The Fujitsu Sleeve Case M is the ideal notebook companion for easy transportation and protection. The slim construction makes it extremely portable, whilst the combination of exterior Twill PU and interior suede protects your notebook from any potential damage. It incorporates a hidden magnet to keep the lid closed and the angular cut shape means that the compartment inside is easily accessed.

Order Code: S26391-F1192-L312

UC&C USB Headset Stereo H650e



The UC&C USB Headset Stereo H650e is the ultimate in style and functionality. Long, uncomfortable work calls are a thing of the past thanks to the cushioned ear pads and crystal clear sound. Adjustable headband and microphone provides the perfect fit for everyone. Optimized for Microsoft® Lync™ the headset displays a red 'in-call' LED to let your co-workers know when you're available, thus helping to boost office productivity.

Order Code: S26391-F7139-L10

Wireless Keyboard Set LX901



The Wireless Keyboard LX901 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K565-L4** (**: Country specific variation)

Page 6 / 7 www.fujitsu.com/fts/mobile

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU LIFEBOOK S935, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU LIFEBOOK S935, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions Website: www.fujitsu.com/fts 2015-01-22 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions