Fujitsu recommends Windows.



Data Sheet FUJITSU LIFEBOOK U745 Notebook

Business Elegance meets Premium Security

The FUJITSU Notebook LIFEBOOK U745 is a slim and light Ultrabook™ for professionals supporting optimum mobility for business trips and ergonomics in the office. Its low weight from 1.55 kg combined with a 35.6 cm (14-inch) anti-glare display with touch panel and backlit keyboard options offers you mobile comfort. The 4G/LTE or 3G/UMTS option and the pull-out LAN connector grant you added connectivity. Moreover, an embedded palm vein sensor option guarantees ultimate protection of your data. The common port replicator with the LIFEBOOK E family facilitates workplace sharing; the VGA port allows you to present on demand.



Elegance in combination with ergonomics

Elegant design and comfortable working in every situation

A slim 19 mm and lightweight notebook from 1.55 kg, HD+ anti-glare display with touch panel option, magnesium housing with aluminum palm rest



Convenient working anywhere with a variety of features for the most demanding mobile user

■ Ultrabook™ with VGA port, display port, common port replicator with LIFEBOOK E family, Anytime USB Charge to charge phones, media devices even when the system is turned off, backlit keyboard option



Premium security

Guarantee protection of your notebook and company data from unauthorized access

■ Embedded palm vein sensor or fingerprint sensor option, Advanced Theft Protection, Full Disk Encryption, SmartCard reader option, Trusted Platform Module option

Ultimate connectivity

Flexibility and increased availability through a variety of options

■ Pull-out LAN connector, embedded 4G/LTE or 3G/UMTS option, WLAN and Bluetooth



Direct access to key components reduces upgrade time and costs

■ Door to exchange the battery, memory and internal storage





Page 1 / 7 www.fujitsu.com/fts/mobile

Components

Processor	Intel® Core™ i5-5200U processor (2.2 GHz, up to 2.7 GHz, 3 MB) *
	Intel® Core™ i3-5010U processor (2.1 GHz, 3 MB) *
	Intel® Core™ i7-5600U processor (2.6 GHz, up to 3.2 GHz, 4 MB)
	Intel® Core™ i5-5300U processor (2.3 GHz, up to 2.9 GHz, 3 MB)
	*Processor only for retail, SMB, education and government
	Intel® Core™ vPro™ Processor - Best Platform for Businesses of all sizes
Operating systems	
Operating system	Windows 8.1 Pro 64-bit
	Windows 8.1 64-bit
	Windows 7 Professional 64-bit
Operating system compatible	Windows 8 64-bit
	Windows 8 32-bit
	Windows 7 Professional 32-bit
Memory modules	4 GB (1 module(s) 4 GB) DDR3 L, 1,600 MHz, PC3-12800, SO DIMM
	8 GB (1 module(s) 8 GB) DDR3 L, 1,600 MHz, PC3-12800, SO DIMM
Hard disk drives (internal)	SSHD, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
	SSD SATA III, 512 GB, 2.5-inch, OPAL capable
	SSD SATA III, 256 GB, 2.5-inch, OPAL capable
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
	Accessible capacity may vary, also depending on used software.
	Up to 20 GB of HDD space is reserved for system recovery
	Internal HDD interface: S-ATA III (6GBit/s)
Interface add on cards/components (optional)	
3G/4G (optional)	Sierra Wireless EM8805 (Downlink speed 42 Mbit/s, Uplink speed 5.76 Mbit/s)
. 1	LTE Sierra Wireless EM7305 (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s)
WLAN (optional)	Intel® Wireless-N 7265 2x2 b/g/n with integrated Bluetooth 4.0
	Intel® Dual Band Wireless-N 7265 2x2 ac with integrated Bluetooth 4.0
Display	35.6 cm (14-inch), LED backlight, (HD+), Anti-glare touchscreen, magnesium, 1,600 x 900 pixel, 400:1, 250 cd/m²
	35.6 cm (14-inch), LED backlight, (HD+), Anti-glare display, magnesium, 1,600 x 900 pixel, 400:1, 250 cd/m²
Multimedia	
Camera	Built-in webcam (HD) with Status LED

Base unit

Base unit	LIFEBOOK U745 14.0-inch
General system information	
Chipset	Integrated
Chipset notes	Supports iAMT 10.0
	Intel® vPro™ requires Core i5-53xx & i7-56xx CPU, Intel WLAN 7265 ac, TPM module
Memory slots	1 DIMM (DDR3L)

Page 2 / 7 www.fujitsu.com/fts/mobile

BB 3L - 1,600 MHz 3 onboard, 1 DIMM slot with max. 8 GB t-in 10/100/1,000 MBit/s Intel® 218LM 5 based on Phoenix SecureCore board tek ALC3233 eo speakers 2241-307 - Pixel class II ying angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200
3L – 1,600 MHz 3 onboard, 1 DIMM slot with max. 8 GB t-in 10/100/1,000 MBit/s Intel® 218LM 5 based on Phoenix SecureCore coard tek ALC3233 eo speakers 9241-307 - Pixel class II ving angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200 to 1,920 x 1,200 to 1,920 x 1,200 to 1,920 x 1,200
3 onboard, 1 DIMM slot with max. 8 GB t-in 10/100/1,000 MBit/s Intel® 218LM 5 based on Phoenix SecureCore coard tek ALC3233 eo speakers 9241-307 - Pixel class II ving angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200
t-in 10/100/1,000 MBit/s Intel® 218LM based on Phoenix SecureCore board tek ALC3233 eo speakers 9241-307 - Pixel class II ving angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200
based on Phoenix SecureCore coard tek ALC3233 eo speakers 9241-307 - Pixel class II ving angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch o 2,560 x 1,600 o 1,920 x 1,200 o 1,920 x 1,200 left HD Graphics 5500
board tek ALC3233 eo speakers 9241-307 - Pixel class II ving angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200 to 1,920 x 1,200 IP HD Graphics 5500
tek ALC3233 eo speakers 9241-307 - Pixel class II ving angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch o 2,560 x 1,600 o 1,920 x 1,200 o 1,920 x 1,200 left HD Graphics 5500
2241-307 - Pixel class II 241-307 - Pixel class II 241-307 - Pixel class II 241-307 - Pixel class II 251-300
9241-307 - Pixel class II ying angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200 to 1,920 x 1,200 IP HD Graphics 5500
wing angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200 to 1,920 x 1,200 The HD Graphics 5500
wing angle: Left/Right 40°, Top 10°, Bottom 30°; 16ms response time; Color Gammut: 45% BOOK U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200 to 1,920 x 1,200 The HD Graphics 5500
B00K U745 14.0-inch to 2,560 x 1,600 to 1,920 x 1,200 to 1,920 x 1,200 le HD Graphics 5500
o 2,560 x 1,600 o 1,920 x 1,200 o 1,920 x 1,200 l® HD Graphics 5500
o 2,560 x 1,600 o 1,920 x 1,200 o 1,920 x 1,200 l® HD Graphics 5500
o 1,920 x 1,200 o 1,920 x 1,200 [®] HD Graphics 5500
o 1,920 x 1,200 [®] HD Graphics 5500
® HD Graphics 5500
splay Support
red memory depending on main memory size and operating system
igital microphones (array)
with Anytime USB Charge functionality)
with ruly time 055 charge ranetarionally
ull-out connector)
D up to 2GB, SDHC up to 32GB, SDXC up to 128GB)
ptional)
nly for models with integrated 3G/UMTS or 4G/LTE module)
9V)
יין אכ
p to 2560 x 1600) - 1 DP (next to DVI) is shared with DVI, works when DVI not connected
p to 1920 x 1200)
p to 1920 x 1200) p to 1920 x 1200) - shared with DP (next to DVI) - works when DP (next to DVI) not connected
0/100/1000)
ortrep & System)
ordep & Systems
replicator supports 0-Watts functionality
Tephedol 30pports o Mates fairctionality
k colored key caps for backlight keyboard#Black colored key caps with red frame for regular keyboard#Isolation board#Spill-resistant standard keyboard aber of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm chpad with two mouse buttons Button us LED
i CFF

Page 3 / 7 www.fujitsu.com/fts/mobile

Wireless technologies	
Antennas	2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional, Bluetooth antenna shared with WLAN
WLAN notes	Import and usage according to country-specific regulations.
Power supply	
AC Adapter	19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter
	19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology
	19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter
Notes	65W AC Adapter for usage with system/ min. 80W AC Adapter for usage with Port Replicator
1st battery options	Lithium polymer battery 4-cell, 45 Wh
Runtime 1st battery	Up to 14:00 h (MM2007), Up to 7:30 h (MM2012) (tbc)
Battery charging time	~120 min
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2007 (readers mode) and BAPCo® MobileMark® 2012 (office productivity) see www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.
Noise emission	
Noise emission	Please refer to the Eco Declaration
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	332.6 mm (13.09 inch) x 234.0 mm (9.21 inch) x 19.0 mm (0.75 inch)
Weight	From 1.55 kg (3.42 lbs) with non-touch display, from 1.70 kg (3.75 lbs) with touch display
Weight notes	Weight may vary depending on actual configuration
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	20 - 85 %
Compliance	
Europe	CE CB
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.0 EPEAT® Gold (dedicated regions) (planned)
Compliance notes	Above mentioned compliances are planned but not available at preliminary stage.
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Fujitsu LIFEBOOK Application Panel Fujitsu Display Manager ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (buy license to activate the pre-installed Microsoft Office) Win8: Microsoft Push Button Recovery (hard disk based recovery) Win7: Fujitsu Recovery (hard disk based recovery)
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows® Connection manager (optional with 4G/LTE or 3G/UMTS) CyberLink YouCam (webcam software)

Page 4 / 7 www.fujitsu.com/fts/mobile

Managoahility	
Manageability	Darkilladata Drivas magazamast
Manageability technology Manageability software	DeskUpdate Driver management PXE 2.1 Boot code
	Wake up from S5 (off mode)
	wake up nom 55 (on mode) Intel® vPro™ technology
	WoL (Wake on LAN)
	iAMT 10.0 (depending on CPU)
	DeskView Client
	DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform
DeskView components	Inventory Management
	BIOS Management
	Driver Management
	Security Management
	Alarm Management
Supported standards	WMI
	PXE
	BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/solutions/business-technology/manageability/feature-finder.html
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Computrace® ready BIOS
	Advanced Theft Protection (Computrace® only)
	Optional: Trusted platform module (TPM 1.2)
User Security	Access protection via internal SmartCard reader (optional)
,	SystemLock BIOS SmartCard security
	Embedded palm vein sensor (optional)
	Embedded fingerprint sensor (optional)
	Hard disk password
	User and supervisor BIOS password
	Workplace Protect (secure authentication solution)
Warranty	
Standard Warranty	2 years (depending on country)
Service level	Collect & Return Service / Bring-in Service (for countries within region FTS CEMEA&I, for all other countries depending
	on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the per	
Recommended Service	9x5, Response Time: Next Business Day

Recommended Accessories

Port Replicator for LIFEBOOK (U745, T725, E754, E744, E734, E554 and E544) and CELSIUS H730

Spare Parts availability Service Weblink



5 years after end of product life

http://ts.fujitsu.com/Supportservice

Flexibility, expandability, desktop replacement, investment protection – to Order Code: name just a few benefits of Fujitsu's docking options.

S26391-F1337-L100

AC Adapter LIFEBOOK



Power your notebook at work, at home or on the road with a second power Order Code: source. You can easily recharge your notebook everywhere. Depending on your notebook you can choose from various AC Adapters ranging from a slim stick type adapter to standard adapters, or even the innovative 0-Watt AC Adapter.

S26391-F1246-L500

Prestige Pro Case Midi 14



The Fujitsu Prestige Pro Case Midi 14 offers you a stylish high-quality leather and nylon combination which will impress everyone who sees it. It S26391-F1191-L80 protects your 35.6 cm (14-inch) notebook plus your essential accessories in padded compartments. Everything will be safe but accessible in dedicated front, document, and identification pockets.

Order Code:

Sleeve Case M



The Fujitsu Sleeve Case M is the ideal notebook companion for easy transportation and protection. The slim construction makes it extremely portable, whilst the combination of exterior Twill PU and interior suede protects your notebook from any potential damage. It incorporates a hidden magnet to keep the lid closed and the angular cut shape means that the compartment inside is easily accessed.

Order Code: S26391-F1192-L312

Wireless Notebook Mouse WI610



The Wireless Notebook Mouse WI610 uses the latest wireless 2.4 GHz technology, and an ultra-high resolution switchable sensor to give you the precision and reliability you need (1000/1500/2000 dpi). Sporting a stylish silver-black finish, the WI610 wireless mouse is well suited to all environments.

Order Code: S26381-K460-L100

www.fujitsu.com/fts/mobile Page 6 / 7

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU LIFEBOOK U745, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU LIFEBOOK U745, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions Website: www.fujitsu.com/fts 2015-01-19 CE-EN All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions