

Hunter®

DESIGN GUIDE

MP Rotator®: High Efficiency Multi-Stream Nozzle



Matched Precipitation

The MP Rotator maintains its matched precipitation rate at any arc or radius setting, simplifying landscape irrigation designs while maximizing efficiency.

Reliable Operation

Patented double-pop nozzle keeps the sprinkler free from external debris.

Efficient Application

Multiple rotating streams provide even coverage and wind resistance, eliminating dry spots.

Pressure Regulation

For best results, use the pressure-regulated Hunter PRS40.

Accurate Adjustments

Arc and radius can be adjusted while maintaining matched precipitation. Radius can be reduced up to 25%.

Durable

Removable inlet filter keeps sprinkler free from internal debris.

Easy Installation

Compatible with all Hunter spray bodies—perfect for retrofits. Use the MP-HT for female-threaded spray bodies.



MP ROTATOR DESIGN GUIDE

APPLICATION

1 MP Rotator Application



Specify the MP Rotator as the desired nozzle in a spray head body.

Retrofit spray systems by installing the MP Rotator onto any conventional spray head or shrub adapter.

2 Radius Adjustment

All models of the MP Rotator allow for easy radius adjustment of up to 25% while maintaining automatic matched precipitation.

Turn the nozzle adjustment screw clockwise to reduce the radius or counter clockwise to increase the radius. Four full rotations will maximize the effect. Additional rotations will not affect the performance of the nozzle.



3 Arc Setting

The MP Rotator has a fixed left edge on all 90-210 models and 210-270 models. Turn the adjustment ring clockwise to increase the arc, and turn the adjustment ring counter-clockwise to decrease the arc.



4 Pressure

Optimal performance and uniformity are reached at 40 PSI operating pressure. Use the Pro-Spray PRS40 to achieve pressure regulation of 40 PSI.

To reach the minimum radius, use the Pro-Spray PRS30 for pressure regulation to 30 PSI. To achieve maximum radius, increase the pressure over 40 PSI.

MP ROTATOR FACTORY SETTINGS

New MP Rotators are shipped from the factory at the maximum radius setting and with the following arc settings:

| MP MODEL | FACTORY SET ARC |
|-----------------------|-----------------|
| 90-210 | 180 ° |
| 210-270 | 210 ° |
| 360 | full circle |
| MP Corner | 45 ° |
| MP Side Strip | 180 ° |
| MP Left & Right Strip | 90 ° |

MP ROTATOR NOZZLE HEIGHT AND TRAJECTORY

| Nozzle No. | Pressure (PSI) | Degrees of Trajectory | Max. Height of Spray |
|---------------|----------------|-----------------------|----------------------|
| MP800SR | 40 | 18 | 18" |
| 1000 | 40 | 20 | 20" |
| 2000 | 40 | 26 | 45" |
| 3000 | 40 | 26 | 79" |
| 3500 | 40 | 26 | 79" |
| Corner | 40 | 14 | 14" |
| MP Side Strip | 40 | 16 | 19" |
| MP Left Strip | 40 | 16 | 18" |

LAYOUT AND PLACEMENT

Run Times

Because the MP Rotator applies less water with increased uniformity, simply doubling the run time used for traditional spray nozzles may supply sufficient water to the landscape while using less water overall.

Or you can calculate the run time based on the lower precipitation rate.

Visit www.hunterindustries.com/tools/runtime for more information on run time calculations.

Precipitation Rate Calculations


MP Rotators are recommended for use with head-to-head coverage in either square or triangular layouts.

Square Spacing Application Rate

$$\frac{96.25 \times GPM \text{ of } 360^\circ \text{ sprinkler}}{\text{Head spacing} \times \text{Row spacing}}$$

Example:

$$\frac{96.25 \times 1.47 \text{ GPM}}{19' \times 19'} = \frac{141.49}{361} = 0.39 \text{ in/hr}$$



19' Square Spacing


MP2000-360
40 PSI
19' Radius
1.47 GPM
19' Head x 19' Row,
Square Spacing

Equilateral Triangular Spacing Application Rate

$$\frac{96.25 \times GPM \text{ of } 360^\circ \text{ sprinkler}}{(\text{Head spacing} \times \text{Head spacing}) 0.866}$$

Example:

$$\frac{96.25 \times 3.64 \text{ GPM}}{(30 \times 30) 0.866} = \frac{350.35}{(900) 0.866} = \frac{350.35}{779.4} = 0.45 \text{ in/hr}$$



30' Triangular Spacing

MP3000-360
40 PSI
30' Radius
3.64 GPM
30' Head x 26' Row,
Triangular Spacing


Note: Equilateral triangular spacing has a higher application rate than square spacing due to less area per sprinkler.

Zoning with the MP Rotator

The standard MP Rotators have a matched precipitation rate of approximately 0.4 in/hr. This means any standard MP Rotator at any arc or radius can be placed on the same zone.

The MP800SR can be configured to work well in head-to-head coverage in either square or triangular layouts. When square spacing is used, the resulting precipitation rate will be approximately 0.8 in/hr.

Since this precipitation rate differs from the standard line of MP Rotators, it is strongly suggested to zone the MP800SR separately to maintain matched precipitation within each zone.




MP ROTATOR DESIGN GUIDE

MP800SR

Matched Precipitation

Realize water savings for tight spaces with the MP800SR. The SR series offers the benefits of multi-stream multi-trajectory technology in smaller areas than ever before. The MP800SR delivers water to distances as small as 6' at a matched precipitation rate of approximately **0.8 in/hr**, less than half that of traditional spray nozzles.

Radius



Pressure Ratings

The MP800SR, just like its larger family of MP Rotators, prefers 40 PSI for optimal performance. This pressure yields the best results for coverage and distribution uniformity. **However, to achieve the lowest radius setting of 6', it will be necessary to regulate the inlet pressure to 30 PSI.** Use a PRS30 to achieve a consistent inlet pressure of 30 PSI.

PRS30

Pair with Pro-Spray®
PRS30 to achieve
minimum 6 ft radius.



PRS40

Pair with Pro-Spray®
PRS40 for optimal
performance.



MP ROTATOR DESIGN GUIDE

MP1000, MP2000, MP3000, MP35000

Matched Precipitation

All standard MP Rotators have a matched precipitation rate of approximately **0.4 in/hr.**

Radius

Arc



90° to 210°



210° to 270°



360°

MP1000



8' ← 15'



MP100090



MP1000210



MP1000360

MP2000



13' ← 21'



MP200090



MP2000210



MP2000360

MP3000



22' ← 30'



MP300090



MP3000210



MP3000360

MP3500



31' ← 35'




MP350090

SIDE STRIP AND CORNER MODELS

Side Strip Precipitation Example

The precipitation rate of the MP Strips is dependent on the layout of the system. The following is an example of a potential design and associated precipitation rate:



Precipitation Rate Using Total Area Method

$$P = \frac{96.25 \times \text{Total Flow (GPM)}}{\text{Total Area (ft)}}$$

$$P = \frac{96.25 \times (0.22 + 0.44 + 0.44 + 0.44 + 0.22)}{5 \times 60}$$

$$P = 0.56 \text{ in/hr}$$





MP Corner

The MP Corner is specially designed to provide extra coverage in tight corners so that neighboring heads do not need to reach into the corner to provide head-to-head coverage, avoiding unnecessary overspray onto non-target areas.



MPCorner



MP ROTATOR DESIGN GUIDE



UNIFORMITY

Uniformity Samples



The various streams of the MP Rotator allow it to target all areas of the landscape evenly when properly installed, yielding superior uniformity over traditional spray nozzles. Several independent studies demonstrate this difference and other efficiency benefits of the MP Rotator. Read more at hunterindustries.com/site-studies.

Below is a sampling of MP Rotator profiles and associated uniformities. These uniformity examples result from tests performed indoors in controlled conditions. On-site conditions will affect actual uniformity, and the uniformity data may change due to continuing product development.



MP1000 90-210 180° at 40 PSI



MP2000 90-210 180° at 40 PSI



MP3000 90-210 180° at 40 PSI



COST AND WATER SAVINGS


Lower System Cost

A design with MP Rotators uses far less material and equipment than a traditional spray design, resulting in an overall reduced project cost. Due to the lower flow rates, more heads can be run at once, reducing the number of valves needed.


Learn more about how the MP Rotator provides material and labor savings in this residential site study:

hunterindustries.com/site-study/mp-rotator-creates-material-and-labor-savings.

Design Using Traditional Sprays



Design Using MP Rotators



IRRIGATION SYSTEM COST SAVING COMPARISON

| Materials Needed | With Sprays | With MP Rotator |
|---------------------|-----------------|-----------------|
| Valves | 6 | 2 |
| Mainline | 150 ft | 15 ft |
| Laterals | 800 ft | 600 ft |
| Sprinklers | 55 | 34 |
| Controller | 6-Station | 4-Station |
| Wire | 175 ft | 20 ft |
| OVERALL COST | \$\$\$\$ | \$\$ |

FILTRATION RECOMMENDATIONS AND WASTE WATER APPLICATION

Filtration Guidelines

It is recommended to use primary filtration when operating with dirty water.

A general rule is to use primary filtration that is five times the mesh rating of the nozzle filter. For example, if the nozzle filter is 20 mesh, the primary filter should be 100 mesh.

Field testing has shown that the MP800SR runs well in dirty water conditions with the use of a 150 mesh primary filtration system.

NOZZLE FILTER SIZES

| Nozzle | Screen Size (mesh) |
|----------------------|--------------------|
| MP1000 | 40 |
| MP2000 | 40 |
| MP3000 | 20 |
| MP3500 | 20 |
| MP Strips and Corner | 40 |
| MP800SR90 | 60 |
| MP800SR360 | 40 |

HY-100, HY-100-75, HY-075

Height: 6"

Width: 3"

Depth: 5"



Hunter's HY filters with 150 mesh size are a great solution for zone-specific MP800SR arrangements.

Reclaimed Waste Water

The MP Rotator is an excellent choice when using reclaimed waste water. The materials used in the MP Rotator are chemical-resistant polypropylene, polyurethane, acetal plastics, stainless steel, and EPDM rubber. These materials are designed to withstand the chemicals and conditions commonly used in waste water irrigation.

MP ROTATOR DESIGN GUIDE

| MP ROTATOR PERFORMANCE DATA | | | | | | | | | | | | | | | | | | |
|---|-----------------|---------------|-------------|--------------|--------------|--|---------------|-------------|--------------|--------------|-------------|--|---------------|--------------|--------------|--------------|-------------|-------------|
| MP1000 | | | | MP2000 | | | | MP3000 | | | | | | | | | | |
| Arc | Pressure PSI | Radius ft. | Flow GPM | Flow GPH | Precip in/hr | | Radius ft. | Flow GPM | Flow GPH | Precip in/hr | | Radius ft. | Flow GPM | Flow GPH | Precip in/hr | | | |
| | | | | | ■ | ▲ | | | | ■ | ▲ | | | | ■ | ▲ | | |
| 90° | 25 | -- | -- | -- | -- | -- | 17 | 0.31 | 18.6 | 0.41 | 0.48 | 25 | 0.69 | 41.4 | 0.43 | 0.49 | | |
| | 30 | 12 | 0.16 | 9.60 | 0.43 | 0.50 | 18 | 0.33 | 19.8 | 0.39 | 0.45 | 27 | 0.74 | 44.4 | 0.39 | 0.45 | | |
| | 35 | 13 | 0.18 | 10.8 | 0.40 | 0.46 | 19 | 0.37 | 22.2 | 0.39 | 0.46 | 28 | 0.80 | 48.0 | 0.39 | 0.45 | | |
| | 40 | 14 | 0.19 | 11.4 | 0.39 | 0.45 | 20 | 0.40 | 24.0 | 0.39 | 0.44 | 30 | 0.86 | 51.6 | 0.37 | 0.43 | | |
| | 45 | 14 | 0.20 | 12.0 | 0.39 | 0.45 | 21 | 0.42 | 25.2 | 0.37 | 0.42 | 30 | 0.91 | 54.6 | 0.39 | 0.45 | | |
| | 50 | 14 | 0.21 | 12.6 | 0.38 | 0.43 | 21 | 0.44 | 26.4 | 0.35 | 0.40 | 30 | 0.96 | 57.6 | 0.41 | 0.47 | | |
| | 55 | 15 | 0.22 | 13.2 | 0.37 | 0.43 | 21 | 0.47 | 28.2 | 0.37 | 0.43 | 30 | 1.01 | 60.6 | 0.43 | 0.50 | | |
| 180° | 25 | -- | -- | -- | -- | -- | 16 | 0.58 | 34.8 | 0.44 | 0.50 | 25 | 1.44 | 86.4 | 0.44 | 0.51 | | |
| | 30 | 12 | 0.32 | 19.2 | 0.43 | 0.50 | 17 | 0.63 | 37.8 | 0.42 | 0.49 | 27 | 1.58 | 94.8 | 0.42 | 0.48 | | |
| | 35 | 13 | 0.35 | 21.0 | 0.40 | 0.46 | 18 | 0.69 | 41.4 | 0.41 | 0.47 | 28 | 1.70 | 1.02 | 0.42 | 0.48 | | |
| | 40 | 14 | 0.37 | 22.2 | 0.39 | 0.45 | 19 | 0.74 | 44.4 | 0.39 | 0.45 | 30 | 1.82 | 109.2 | 0.39 | 0.45 | | |
| | 45 | 14 | 0.40 | 24.0 | 0.39 | 0.45 | 20 | 0.78 | 46.8 | 0.38 | 0.43 | 30 | 1.93 | 115.8 | 0.41 | 0.48 | | |
| | 50 | 14 | 0.41 | 24.6 | 0.38 | 0.43 | 21 | 0.83 | 49.8 | 0.36 | 0.41 | 30 | 2.04 | 122.4 | 0.44 | 0.50 | | |
| | 55 | 15 | 0.43 | 25.8 | 0.37 | 0.43 | 21 | 0.85 | 51.0 | 0.37 | 0.43 | 30 | 2.13 | 127.8 | 0.46 | 0.53 | | |
| 210° | 25 | -- | -- | -- | -- | -- | 16 | 0.68 | 40.8 | 0.44 | 0.50 | 25 | 1.68 | 100.8 | 0.44 | 0.51 | | |
| | 30 | 12 | 0.37 | 22.2 | 0.43 | 0.50 | 17 | 0.74 | 44.4 | 0.42 | 0.49 | 27 | 1.84 | 110.4 | 0.42 | 0.48 | | |
| | 35 | 13 | 0.41 | 24.6 | 0.40 | 0.46 | 18 | 0.80 | 48.0 | 0.41 | 0.47 | 28 | 1.99 | 119.4 | 0.42 | 0.48 | | |
| | 40 | 14 | 0.43 | 25.8 | 0.39 | 0.45 | 19 | 0.86 | 51.6 | 0.39 | 0.45 | 30 | 2.12 | 127.2 | 0.39 | 0.45 | | |
| | 45 | 14 | 0.46 | 27.6 | 0.39 | 0.45 | 20 | 0.91 | 55.2 | 0.38 | 0.43 | 30 | 2.25 | 135.0 | 0.41 | 0.48 | | |
| | 50 | 14 | 0.48 | 28.8 | 0.38 | 0.43 | 21 | 0.97 | 58.2 | 0.36 | 0.41 | 30 | 2.37 | 142.2 | 0.43 | 0.50 | | |
| | 55 | 15 | 0.50 | 30.0 | 0.37 | 0.43 | 21 | 1.01 | 60.6 | 0.37 | 0.43 | 30 | 2.49 | 149.4 | 0.46 | 0.53 | | |
| 270° | 25 | -- | -- | -- | -- | -- | 16 | 0.87 | 52.2 | 0.44 | 0.50 | 25 | 2.19 | 131.4 | 0.45 | 0.52 | | |
| | 30 | 12 | 0.48 | 29.0 | 0.43 | 0.50 | 17 | 0.95 | 57.0 | 0.42 | 0.49 | 27 | 2.37 | 142.2 | 0.42 | 0.48 | | |
| | 35 | 13 | 0.54 | 32.0 | 0.40 | 0.46 | 18 | 1.03 | 61.8 | 0.41 | 0.47 | 28 | 2.55 | 153.0 | 0.42 | 0.48 | | |
| | 40 | 14 | 0.57 | 34.0 | 0.39 | 0.45 | 19 | 1.10 | 66.0 | 0.39 | 0.45 | 30 | 2.73 | 163.8 | 0.39 | 0.45 | | |
| | 45 | 14 | 0.60 | 36.0 | 0.39 | 0.45 | 20 | 1.17 | 70.2 | 0.38 | 0.43 | 30 | 2.89 | 173.4 | 0.41 | 0.48 | | |
| | 50 | 14 | 0.63 | 38.0 | 0.38 | 0.43 | 21 | 1.23 | 73.8 | 0.36 | 0.41 | 30 | 3.06 | 183.6 | 0.44 | 0.50 | | |
| | 55 | 15 | 0.66 | 40.0 | 0.37 | 0.43 | 21 | 1.30 | 78.0 | 0.37 | 0.43 | 30 | 3.22 | 193.2 | 0.46 | 0.53 | | |
| 360° | 25 | -- | -- | -- | -- | -- | 16 | 1.16 | 69.6 | 0.44 | 0.50 | 25 | 2.88 | 172.8 | 0.44 | 0.51 | | |
| | 30 | 12 | 0.65 | 39.0 | 0.43 | 0.50 | 17 | 1.27 | 76.2 | 0.42 | 0.49 | 27 | 3.15 | 189.0 | 0.42 | 0.48 | | |
| | 35 | 13 | 0.71 | 42.6 | 0.40 | 0.47 | 18 | 1.37 | 82.2 | 0.41 | 0.47 | 28 | 3.40 | 204.0 | 0.42 | 0.48 | | |
| | 40 | 14 | 0.75 | 45.0 | 0.39 | 0.46 | 19 | 1.47 | 88.2 | 0.39 | 0.45 | 30 | 3.64 | 218.4 | 0.39 | 0.45 | | |
| | 45 | 14 | 0.80 | 48.0 | 0.39 | 0.45 | 20 | 1.56 | 93.6 | 0.38 | 0.43 | 30 | 3.86 | 231.6 | 0.41 | 0.48 | | |
| | 50 | 14 | 0.84 | 50.4 | 0.38 | 0.44 | 21 | 1.64 | 98.4 | 0.36 | 0.41 | 30 | 4.07 | 244.2 | 0.44 | 0.50 | | |
| | 55 | 15 | 0.87 | 52.2 | 0.37 | 0.43 | 21 | 1.70 | 102.0 | 0.37 | 0.43 | 30 | 4.27 | 256.2 | 0.46 | 0.53 | | |
| MP3500 Radius: 31' to 35' Adjustable Arc ● Light Brown: 90° | | | | 90° | | MP3500 Radius: 31' to 35' Adjustable Arc ● Light Brown: 180° | | | | 180° | | MP3500 Radius: 31' to 35' Adjustable Arc ● Light Brown: 210° | | | | | | |
| Pressure PSI | Radius ft. | Flow GPM | Flow GPH | Precip in/hr | ■ | ▲ | Radius ft. | Flow GPM | Flow GPH | Precip in/hr | ■ | ▲ | Radius ft. | Flow GPM | Flow GPH | Precip in/hr | ■ | ▲ |
| 25 | 33 | 1.04 | 62.4 | 0.37 | 0.42 | | 33 | 2.21 | 132.6 | 0.39 | 0.45 | | | 33 | 2.59 | 155.4 | 0.39 | 0.45 |
| 30 | 34 | 1.13 | 67.8 | 0.38 | 0.43 | | 34 | 2.24 | 134.4 | 0.37 | 0.43 | | | 34 | 2.84 | 170.4 | 0.41 | 0.47 |
| 35 | 34 | 1.21 | 72.6 | 0.40 | 0.47 | | 34 | 2.65 | 159.0 | 0.44 | 0.51 | | | 34 | 3.08 | 184.8 | 0.44 | 0.51 |
| 40 | 35 | 1.28 | 76.8 | 0.40 | 0.46 | | 35 | 2.86 | 171.6 | 0.45 | 0.52 | | | 35 | 3.29 | 197.4 | 0.44 | 0.51 |
| 45 | 35 | 1.38 | 82.8 | 0.43 | 0.50 | | 35 | 3.10 | 186.0 | 0.49 | 0.56 | | | 35 | 3.54 | 212.4 | 0.48 | 0.55 |
| 50 | 35 | 1.43 | 85.8 | 0.45 | 0.52 | | 35 | 3.21 | 192.6 | 0.50 | 0.58 | | | 35 | 3.76 | 225.6 | 0.51 | 0.59 |
| 55 | 35 | 1.50 | 90.0 | 0.47 | 0.54 | | 35 | 3.28 | 196.8 | 0.52 | 0.60 | | | 35 | 3.94 | 236.4 | 0.53 | 0.61 |

Bold = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Hunter PRS40 Spray Body, pressure regulated at 40 PSI.

MP ROTATOR DESIGN GUIDE

| MP ROTATOR PERFORMANCE DATA | | | | | | | | |
|--|-----------------|-----------------|---------------|-------------|---------------------|---------------|--|-------------|
| MP800SR | | | | | | | MP ROTATOR PERFORMANCE DATA | |
| Radius: 6' to 12' Adjustable Arc and Full-Circle ● Orange and Gray: 90° to 210° ● Lime Green and Gray: 360° | | | | | | | MP Corner Radius: 8' to 15' Adjustable Arc ● Turquoise: 45° to 105° | |
| MAX RADIUS | | | | MIN RADIUS | | | | |
| Arc | Pressure PSI | Radius ft. | Flow GPM | Flow GPH | Precip in/hr ■ ▲ | Radius ft. | Flow GPM | Flow GPH |
| 90° | | | | | | | 45° | |
| ● | 30 | 8 | 0.17 | 9.6 | 0.90 | 1.04 | 6 | 0.13 |
| | 35 | 9 | 0.21 | 11.4 | 0.89 | 1.03 | 7 | 0.15 |
| | 40 | 10 | 0.23 | 13.8 | 0.83 | 0.96 | 8 | 0.16 |
| | 45 | 11 | 0.25 | 15.0 | 0.80 | 0.92 | 8 | 0.18 |
| | 50 | 11 | 0.27 | 16.2 | 0.79 | 0.92 | 9 | 0.19 |
| | 55 | 12 | 0.28 | 16.8 | 0.80 | 0.93 | 10 | 0.20 |
| 180° | | | | | | | 90° | |
| ● | 30 | 8 | 0.33 | 19.2 | 0.88 | 1.02 | 6 | 0.26 |
| | 35 | 9 | 0.38 | 22.2 | 0.85 | 0.99 | 7 | 0.29 |
| | 40 | 10 | 0.42 | 25.2 | 0.81 | 0.93 | 8 | 0.32 |
| | 45 | 11 | 0.46 | 27.6 | 0.77 | 0.88 | 8 | 0.36 |
| | 50 | 11 | 0.48 | 28.8 | 0.76 | 0.88 | 9 | 0.38 |
| | 55 | 12 | 0.50 | 30.0 | 0.73 | 0.84 | 10 | 0.40 |
| 210° | | | | | | | 105° | |
| ● | 30 | 8 | 0.35 | 22.2 | 0.80 | 0.93 | 6 | 0.30 |
| | 35 | 9 | 0.38 | 26.4 | 0.77 | 0.89 | 7 | 0.34 |
| | 40 | 10 | 0.43 | 29.4 | 0.81 | 0.91 | 8 | 0.37 |
| | 45 | 10 | 0.45 | 31.8 | 0.82 | 0.95 | 8 | 0.42 |
| | 50 | 11 | 0.49 | 33.6 | 0.73 | 0.85 | 9 | 0.44 |
| | 55 | 12 | 0.56 | 34.8 | 0.70 | 0.81 | 10 | 0.47 |
| 360° | | | | | | | MPLCS515: Ivory, MP Left Corner Strip MPRCS515: Copper, MP Right Corner Strip MPSS530: Brown, MP Side Strip | |
| ● | 30 | 8 | 0.66 | 37.8 | 0.89 | 1.03 | 6 | 0.47 |
| | 35 | 9 | 0.71 | 42.0 | 0.80 | 0.92 | 7 | 0.52 |
| | 40 | 10 | 0.78 | 46.8 | 0.79 | 0.91 | 8 | 0.56 |
| | 45 | 10 | 0.85 | 51.0 | 0.78 | 0.90 | 8 | 0.59 |
| | 50 | 11 | 0.88 | 52.8 | 0.73 | 0.85 | 9 | 0.63 |
| | 55 | 12 | 0.98 | 58.8 | 0.70 | 0.81 | 10 | 0.70 |
| PERFORMANCE DATA NOTE FOR ALL CHARTS: Bold = Recommended Pressure. The MP Rotator is designed to maintain matched precipitation after radius adjustment. Optimal pressure for the MP Rotator is 40 PSI. This can be achieved easily by using the MP Rotator with the Hunter PRS40 Spray Body, pressure regulated at 40 PSI. | | | | | | | | |
| MP ROTATOR PERFORMANCE DATA | | | | | | | | |
| MP Left Corner Strip | | Pressure PSI | Radius ft. | | Flow GPM | Flow GPH | | |
| MP Left Corner Strip | | 30 | 4 x 14 | | 0.19 | 11.4 | | |
| | | 35 | 5 x 15 | | 0.21 | 12.6 | | |
| | | 40 | 5 x 15 | | 0.22 | 13.2 | | |
| | | 45 | 5 x 15 | | 0.23 | 13.8 | | |
| | | 50 | 6 x 16 | | 0.25 | 15.0 | | |
| | | 55 | 6 x 16 | | 0.26 | 15.6 | | |
| MP Right Corner Strip | | 30 | 4 x 14 | | 0.19 | 11.4 | | |
| | | 35 | 5 x 15 | | 0.21 | 12.6 | | |
| | | 40 | 5 x 15 | | 0.22 | 13.2 | | |
| | | 45 | 5 x 15 | | 0.23 | 13.8 | | |
| | | 50 | 6 x 16 | | 0.25 | 15.0 | | |
| | | 55 | 6 x 16 | | 0.26 | 15.6 | | |
| MP Side Strip | | 30 | 4 x 28 | | 0.38 | 22.8 | | |
| | | 35 | 5 x 30 | | 0.41 | 24.6 | | |
| | | 40 | 5 x 30 | | 0.44 | 26.4 | | |
| | | 45 | 5 x 30 | | 0.47 | 28.2 | | |
| | | 50 | 6 x 32 | | 0.49 | 29.4 | | |
| | | 55 | 6 x 32 | | 0.51 | 30.6 | | |

Strip pattern radius can be adjusted by 25%.

MP ROTATOR DESIGN GUIDE

FIELD IDENTIFICATION

MP Rotator models are color-coded for easy field identification.

| | MP1000 | MP2000 | MP3000 | MP3500 | | MP Strip |
|--------------|------------|------------|------------|------------|--|----------------------------------|
| Radius | 8' to 15' | 13' to 21' | 22' to 30' | 31' to 35' | | |
| Arc | | | | | | |
| 90° to 210° | MP1000-90 | MP2000-90 | MP3000-90 | MP3500-90 | | MPLCS515 5' x 15' Left Corner |
| | | | | | | MPRC515 5' x 15' Right Corner |
| 210° to 270° | MP1000-210 | MP2000-210 | MP3000-210 | | | |
| | | | | | | MPSS530 5' x 30' Side Strip |
| 360° | MP1000-360 | MP2000-360 | MP3000-360 | | | |

MP800SR

| | |
|-------------|------------------|
| Radius | 6' to 12' |
| Arc | |
| 90° to 210° | Short Radius |
| 360° | Short Radius |

With a precipitation rate of approximately 0.8 in/hr, it is strongly suggested to zone the MP800SR separately to maintain matched precipitation within each zone.

MP Corner



MPCORNER
8' x 15'

MP Male Threaded



Available in all MP Rotator models, except MP1000-210, MP3500-90, and MP800SR models

MP-HT
Male-Threaded

Website hunterindustries.com | **Customer Support** 1-800-383-4747 | **Technical Service** 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Gregory R. Hunter, President of Hunter Industries