

# ECHO SOUNDER

<p><b>KF-667</b></p>		<p><b>ONWA® 5.6-INCH COLOR DISPLAY FISH FINDER</b></p> <p><b>Model:</b> KF-667</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* 5.6-inch TFT LCD display with 8-color or multi-level amber presentation</li> <li>* Dual-frequency: 50 and 200 KHz</li> <li>* 300W Plastic / Bronze Transducer for option</li> <li>* Auto Mode for hands-off operation</li> <li>* Display modes: A-scope, bottom-lock expansion, marker zoom and unique bottom zoom displays</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Main Unit of KF-667</li> <li>* Plastic / Bronze Transducer with 10m Cable</li> <li>* Standard Installation Material and Spare parts</li> <li>* Operator Manual</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>4.95 kgs</td> <td>4 sets/CTN</td> <td>51x33x51(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	4.95 kgs	4 sets/CTN	51x33x51(cm3)
	Weight	Volume per CTN	Dimension of CTN					
4.95 kgs	4 sets/CTN	51x33x51(cm3)						
<p><b>KF-868</b></p>		<p><b>ONWA® 8" COLOR DISPLAY FISH FINDER</b></p> <p><b>Model:</b> KF-868</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* 8" Color LCD display with 7-color presentation</li> <li>* 600W RMS output power standard, 1KW RMS output power(option)</li> <li>* Single Frequency Transducer 50KHz or 200 KHz</li> <li>* Auto Mode for hands-off operation</li> <li>* Bottom expansion and mid-water expansion, Depth alarm</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Main Unit of KF-868</li> <li>* Bronze Transducer with 10m cable</li> <li>* Installation material and standard spare parts</li> <li>* Operator Manual</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>8.82 kgs</td> <td>2 sets/CTN</td> <td>46x43x40(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	8.82 kgs	2 sets/CTN	46x43x40(cm3)
	Weight	Volume per CTN	Dimension of CTN					
8.82 kgs	2 sets/CTN	46x43x40(cm3)						



# ECHO SOUNDER

KF-1067



## ONWA® 10.4" BIG OUTPUT POWER FISH FINDER



**Model:** KF-1067

### Feature:

- \* 10.4" TFT LCD display with 8-color or multi-level amber presentation
- \* Choice of Frequency: 50KHz, 200KHz or 50&200KHz (Dual Frequency), specify when ordering
- \* Choice of Output Power: 1KW or 2KW, specify when ordering
- \* Auto Mode for hands-off operation
- \* Display modes: A-scope, bottom-lock expansion, marker zoom and unique bottom zoom displays



### In the box:

- \* Main Unit of KF-1067
- \* Rubber Transducer with 12m cable
- \* Installation material and standard spare parts
- \* Operator Manual

### Packing:

Weight	Volume per CTN	Dimension of CTN
12.30 kgs/17.3 kgs	2 sets/CTN	54x50x40(cm3)


# MARINE RADAR

<p>KR-1338C</p>	 <p>The image shows the ONWA KR-1338C marine radar. It consists of a white radome antenna unit on top of a grey LCD display unit. The display unit has a circular screen showing a radar scan and several control buttons on the right side. The ONWA logo is visible on the radome.</p>	<p><b>ONWA® 36NM, Color LCD Marine Radar With AIS Function</b>  <b>Model:</b> KR-1338C</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* 4KW output, 36nm range</li> <li>* AIS Display Function</li> <li>* 3 NEMA 0183 ports</li> <li>* Rugged die-cast, waterproof housing</li> <li>* Automatic optimization of radar picture</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* LCD Display Unit</li> <li>* Radome Antenna Unit</li> <li>* Antenna Cable, 10/15/20/30 m (Specify when ordering)</li> <li>* Power Cable/3m, Standard Spare Parts and Installation Materials</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>12.25 kgs &amp; 13.00 kgs</td> <td>2 Cartons</td> <td>42x39x37 &amp; 72x70x39(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	12.25 kgs & 13.00 kgs	2 Cartons	42x39x37 & 72x70x39(cm3)
Weight	Volume per CTN	Dimension of CTN						
12.25 kgs & 13.00 kgs	2 Cartons	42x39x37 & 72x70x39(cm3)						
<p>KR-1668C</p>	 <p>The image shows the ONWA KR-1668C marine radar. It features a white open array antenna unit mounted on a grey LCD display unit. The display unit has a circular screen and control buttons. The ONWA logo is on the antenna unit.</p>	<p><b>ONWA® 64NM, Color LCD Marine Radar With AIS Function</b>  <b>Model:</b> KR-1668C</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* 6KW output, 64nm range</li> <li>* AIS Display Function</li> <li>* 3 NEMA 0183 ports</li> <li>* Rugged die-cast, waterproof housing</li> <li>* Automatic optimization of radar picture</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* LCD Display Unit</li> <li>* Open Array Antenna Unit</li> <li>* Antenna Cable, 10/15/20/30 m (Specify when ordering)</li> <li>* Power Cable/3m, Standard Spare Parts and Installation Materials</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>22.25 kgs &amp; 13.00 kgs</td> <td>2 Cartons</td> <td>42x39x37 &amp; 72x70x39(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	22.25 kgs & 13.00 kgs	2 Cartons	42x39x37 & 72x70x39(cm3)
Weight	Volume per CTN	Dimension of CTN						
22.25 kgs & 13.00 kgs	2 Cartons	42x39x37 & 72x70x39(cm3)						



# GPS CHART PLOTTER

<p>KP-32</p>	 <p>The image shows the ONWA KP-32 Marine GPS/SBAS Navigator. It features a 4.5-inch silver LCD display showing coordinates: 22°46.792'N and 115°21.280'E. Other data on the screen includes SOG: 0.00 kt, COG: 0°, and the date 17-APR-07 at 14:29:18. The device has a control panel with buttons for MENU, ENT, DISP, GOTO, MARK, MOB, and a DMR PWR button. The ONWA logo and 'GPS NAVIGATOR' text are visible at the bottom of the unit.</p>	<p><b>ONWA® MARINE GPS/SBAS NAVIGATOR</b></p> <p><b>Model:</b> KP-32</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* 4.5" Silver Bright LCD display</li> <li>* Multiple display modes to suit a variety of navigational requirements</li> <li>* Up to 999 waypoint, 50 routes and 2,500 track points</li> <li>* One-touch waypoint entry, Customizable Nav Data screens</li> <li>* Improved accuracy with built-in SBAS receiver and Galileo receiver</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Display Unit</li> <li>* GPS Antenna Unit</li> <li>* Installation materials and spare parts</li> <li>* Operator Manual</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>2.20 kgs</td> <td>6 sets/CTN</td> <td>53x37x48(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	2.20 kgs	6 sets/CTN	53x37x48(cm3)
	Weight	Volume per CTN	Dimension of CTN					
2.20 kgs	6 sets/CTN	53x37x48(cm3)						
<p>KP-6288</p>	 <p>The image shows the ONWA KP-6288 Marine GPS Chart Plotter. It features a 5.6-inch day-view LCD display showing a map with coordinates 28°10.668'N and 114°39.838'E. The device has a control panel with buttons for MENU, CLR, MARK, GOTO, MARK, MOB, and a DMR PWR button. The ONWA logo and 'KP-6288 GPS PLOTTER' text are visible at the bottom of the unit.</p>	<p><b>ONWA® Marine GPS Chart Plotter</b></p> <p><b>Model:</b> KP-6288</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* High resolution 5.6 inches day-view LCD display</li> <li>* Works with C-map Max NT Chart (SD) and Onwa K-Chart</li> <li>* High performance GPS receiver</li> <li>* Versatile display modes including: Course Plot, Nav Data, Steering Display, Highway</li> <li>* User SD card to save and transfer waypoint, track, route memory</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Display unit of KP-6288</li> <li>* Antenna unit with 10m cable</li> <li>* Installation materials and Standard spare parts.</li> <li>* Operator manual</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>3.28 kgs</td> <td>6 sets/CTN</td> <td>37x44x39(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	3.28 kgs	6 sets/CTN	37x44x39(cm3)
	Weight	Volume per CTN	Dimension of CTN					
3.28 kgs	6 sets/CTN	37x44x39(cm3)						







<b>KP-623MKII / KP-823MKII / KP-1223MKII</b>		<b>ONWA® 6" , 8" , 12" Color TFT LCD GPS Plotter</b>						
		<b>Model:</b> KP-623 MKII / KP-823 MKII / KP-1223 MKII <b>Feature:</b> <ul style="list-style-type: none"> <li>* High Resolution Day-View TFT LCD</li> <li>* Detail map data that buildin K-Chart already</li> <li>* Tide table and Sunrise Sundown</li> <li>* 260MHz High Speed Microprocessor, quick map redraw speed</li> <li>* Multi-Interface connection to Radar and AIS</li> </ul> <b>In the box:</b> <ul style="list-style-type: none"> <li>* Display unit</li> <li>* Antenna unit with 10m cable</li> <li>* Installation materials and Standard spare parts.</li> <li>* Operator manual</li> </ul> <b>Packing:</b> <table style="width: 100%; border: none;"> <tr> <td style="width: 33%;">KP-623MKII</td> <td style="width: 33%;">6 Sets / Carton</td> <td style="width: 33%;">KP-823MKII</td> <td style="width: 33%;">2 Sets / Carton</td> </tr> <tr> <td>KP-1223MKII</td> <td>2 Sets / Carton</td> <td></td> <td></td> </tr> </table>	KP-623MKII	6 Sets / Carton	KP-823MKII	2 Sets / Carton	KP-1223MKII	2 Sets / Carton
KP-623MKII	6 Sets / Carton	KP-823MKII	2 Sets / Carton					
KP-1223MKII	2 Sets / Carton							





## GPS Chartplotter/AIS SERIES

<b>KP-62A,62B / KP-82A,82B / KP-122A , 122B</b>		<b>ONWA® 6" Color GPS/AIS Chart Plotter</b>						
		<b>Model:</b> KP-62A/62B , KP-82A / 82B , KP-122A / 122B <b>Feature:</b> <ul style="list-style-type: none"> <li>* Built-in Class B AIS Transponder (62A, 82A, 122A ) or Receiver only (62B , 82B , 122B)</li> <li>* 6" , 8" , 12" Color TFT Day View LCD</li> <li>* Improved accuracy with built-in SBAS receiver</li> <li>* Multiple display modes to suit a variety of navigational requirements</li> <li>* Up to 18,000 waypoints, 50 routes and 84,000 track points</li> </ul> <b>In the box:</b> <ul style="list-style-type: none"> <li>* Display unit accommodating GPS/SBAS receiver and Class B AIS module</li> <li>* Antenna unit KA-07 with 10m cable</li> <li>* Installation materials and Standard spare parts.</li> <li>* Operator manual</li> </ul> <b>Packing:</b> <table style="width: 100%; border: none;"> <tr> <td style="width: 33%;">KP-62A</td> <td style="width: 33%;">2 Sets/ Carton</td> <td style="width: 33%;">KP-82A</td> <td style="width: 33%;">2 Sets / Carton</td> </tr> <tr> <td>KP-122A</td> <td>2 Sets / Carton</td> <td></td> <td></td> </tr> </table>	KP-62A	2 Sets/ Carton	KP-82A	2 Sets / Carton	KP-122A	2 Sets / Carton
KP-62A	2 Sets/ Carton	KP-82A	2 Sets / Carton					
KP-122A	2 Sets / Carton							



# GPS PLOTTER SOUNDER

<b>KP-636 / 838 / 1038</b>	 	<b>ONWA® COLOR LCD GPS PLOTTER SOUNDER</b>		 
		<b>Model:</b> KP-KP-636 / KP-838 / KP-1038		
		<b>Feature:</b>		
		<ul style="list-style-type: none"> <li>* 6" , 8" , 10.4" TFT Color LCD Display,</li> <li>* Built-in Large memory electronic chart</li> <li>* Versatile display modes</li> <li>* Display of vessel tracks, waypoints</li> <li>* NMEA 0183 data I/O</li> </ul>	<ul style="list-style-type: none"> <li>* 50KHz or 200KHz Transducer choice</li> <li>* Depth data display on plotter screen</li> <li>* Auto mode for hand-off operation</li> <li>* 7 color targets presentation</li> </ul>	
		<b>In the box:</b>		
<ul style="list-style-type: none"> <li>* Display unit</li> <li>* Antenna unit with 10m cable</li> <li>* Installation materials and spare parts.</li> </ul>	Transducer:636 With NBM 300W , 838 NMM 600W 1038 With NMM 600W * Operator manual			
<b>Packing:</b>				
Weight	Volume per CTN	Dimension of CTN		
3.90 kgs / 4.55 kgs	4 sets/CTN	49x34x45(cm3)		

# Satellite phone Isatdock Pro

<b>Isatdock Pro ISD- 190</b>	 	<b>Isatphone Pro Dock Station for Marine</b>		 
		<b>Model:</b> ISD-190		
		<b>Feature:</b>		
		Work with Inmarsat Satellite phone Isatphone Pro Global satellite coverage , Call , message , visit internet . Receive call , and message free charge With Marine Antenna and 10 meter Cable , Satellite signal good , install in the boat . Hand-Free Function . Power Charge manage by in-built MCU .		
		<b>In the box:</b>		
ISD-190 Maine unit Marine Antenna 10 meter Cable x 2	Accessory part for install antenna			
<b>Packing:</b>				
4 Sets / Carton For the Isatdock Pro , 5 Sets / Carton for the Isatphone pro				

# AUTOPILOT AND COMPASS

<p>KAP-833</p>		<p><b>ONWA® Marine Autopilot</b></p> <p>Model: KAP-833</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* Locks onto current course when auto is engaged</li> <li>* Pre-set course select enables easy</li> <li>* Rudder and counter rudder controls enable autopilot to be customized to a vessel's specific steering characteristics</li> <li>* Off course alarm warns when vessel is not responding to autopilot control</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* KAP-833 control unit</li> <li>* Heavy duty rudder feedback unit</li> <li>* Magnetic compass pick up coil</li> <li>* Standard installation kit</li> <li>* Operator manual</li> <li>* Standard accessories</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>6.95 kgs</td> <td>4 sets/CTN</td> <td>62x36x36(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	6.95 kgs	4 sets/CTN	62x36x36(cm3)
Weight	Volume per CTN	Dimension of CTN						
6.95 kgs	4 sets/CTN	62x36x36(cm3)						
<p>KEC-30</p>		<p><b>ONWA® LCD Display Electronic Fluxgate Compass</b></p> <p>Model: KEC-30</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* Fluxgate heading sensor with high accuracy and stability</li> <li>* Automatic correction for local magnetic variation</li> <li>* NMEA heading data output for other navigation equipment</li> <li>* 4.5 silver bright LCD display</li> <li>* Multiple display mode</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Fluxgate Sensor KFG-25</li> <li>* Display unit KEC-30</li> <li>* Installation Materials</li> <li>* Operator Manual</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>2.40 kgs</td> <td>6 sets/CTN</td> <td>53x37x48(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	2.40 kgs	6 sets/CTN	53x37x48(cm3)
Weight	Volume per CTN	Dimension of CTN						
2.40 kgs	6 sets/CTN	53x37x48(cm3)						



# CB RADIO AND ANTENNA TUNER

<p>KC-480</p>		<p><b>ONWA® 27 MHZ, AM CB TRANSCEIVER</b></p> <p><b>Model:</b> KC-480</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* AM modulation</li> <li>* 480 Channels</li> <li>* Frequency Coverage, 24.265 to 29.655 MHz</li> <li>* 12W transmit power (with modulation)</li> <li>* Built-in voltage converter (option)</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Main Unit of CB Transceiver</li> <li>* Microphone</li> <li>* Standard Installaion Material</li> <li>* Operator manual</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>3.25 kgs</td> <td>6 sets/CTN</td> <td>48x24x24(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	3.25 kgs	6 sets/CTN	48x24x24(cm3)
Weight	Volume per CTN	Dimension of CTN						
3.25 kgs	6 sets/CTN	48x24x24(cm3)						
<p>K-6124</p>		<p><b>ONWA® 27 MHZ, AM CB TRANSCEIVER</b></p> <p><b>Model:</b> K-6124</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* AM modulation</li> <li>* 6 bands 240 channels</li> <li>* Frequency Coverage, 26.065 to 28.755 MHz</li> <li>* 4W of transmit power, 5W Max.</li> <li>* Economical</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Main Unit of CB Transceiver</li> <li>* Dynamic Microphone</li> <li>* Standard Installaion Material</li> <li>* Operator manual</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>1.38 kgs</td> <td>10 sets/CTN</td> <td>57*39*28(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	1.38 kgs	10 sets/CTN	57*39*28(cm3)
Weight	Volume per CTN	Dimension of CTN						
1.38 kgs	10 sets/CTN	57*39*28(cm3)						







# CB RADIO AND ANTENNA TUNER

<p>Argo-300</p>		<p><b>ONWA® 27 MHZ, AM/FM CB TRANSCEIVER</b></p> <p><b>Model:</b> Argo-300</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* 6 Bands 240 channels</li> <li>* AM/FM dual mode</li> <li>* High/Low transmit power selection</li> <li>* LED signal Level Display</li> <li>* Noise blanker function to eliminate the external noise</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Main Unit of CB Transceiver</li> <li>* Dynamic Microphone</li> <li>* Standard Installaion Material</li> <li>* Operator manual</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>2.42 kgs</td> <td>8 sets/CTN</td> <td>43*33*47(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	2.42 kgs	8 sets/CTN	43*33*47(cm3)
Weight	Volume per CTN	Dimension of CTN						
2.42 kgs	8 sets/CTN	43*33*47(cm3)						
<p>KAT-130</p>		<p><b>ONWA® HF AUTOMATIC ANTENNA TUNER</b></p> <p><b>Model:</b> KAT-130</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* Suitable for icom , Kenwood , Yatsu etc different HF Radio</li> <li>* Automatic tuning</li> <li>* Frequency Coverage: 1.6 ~ 30 MHz</li> <li>* For varies HF marine transceivers</li> <li>* Quick tune-up</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Automatic Antenna Tuner</li> <li>* Operator manual</li> <li>* Standard Installaion Material</li> </ul> <p><b>Packing:</b></p> <table border="1"> <thead> <tr> <th>Weight</th> <th>Volume per CTN</th> <th>Dimension of CTN</th> </tr> </thead> <tbody> <tr> <td>3.2 kgs</td> <td>4 sets/CTN</td> <td>53x47x33(cm3)</td> </tr> </tbody> </table>	Weight	Volume per CTN	Dimension of CTN	3.2 kgs	4 sets/CTN	53x47x33(cm3)
Weight	Volume per CTN	Dimension of CTN						
3.2 kgs	4 sets/CTN	53x47x33(cm3)						



# GPS ANTENNA

<p>KA-5M</p>		<p><b>ONWA® GPS ANTENNA WITH BUILT-IN GPS MODULE</b></p> <p><b>Model:</b> KA-5M</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* High compact, corrosion-proof PC resin, Fully waterproof</li> <li>* 50 channels GPS L1 frequency C/A code</li> <li>* Hot start &lt; 1s</li> <li>* SBAS &lt; 2m</li> <li>* NMEA 0183 v2.0 @ 4800 baud</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Main Unit of Antenna</li> </ul> <p><b>Packing:</b></p> <table border="0"> <tr> <td>Weight</td> <td>Dimensions</td> </tr> <tr> <td>0.065 kgs</td> <td>09mm(D) * 110mm(H)</td> </tr> </table>	Weight	Dimensions	0.065 kgs	09mm(D) * 110mm(H)
Weight	Dimensions					
0.065 kgs	09mm(D) * 110mm(H)					
<p>KA-07 /KA-08</p>		<p><b>ONWA® GPS ANTENNA</b></p> <p><b>Model:</b> KA-07 / KA-08</p> <p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>* High compact, corrosion-proof PC resin, Fully waterproof</li> <li>* BNC connector</li> <li>* RF Cable: 10m RG-59</li> <li>* Output impedance: 50ohm</li> <li>* Center frequency:1575.42MHz, Band width 2MHz min</li> </ul> <p><b>In the box:</b></p> <ul style="list-style-type: none"> <li>* Main Unit of Antenna</li> </ul> <p><b>Packing:</b></p> <table border="0"> <tr> <td>Weight</td> <td>Dimensions</td> </tr> <tr> <td>0.065 kgs</td> <td>09mm(D) * 110mm(H)</td> </tr> </table>	Weight	Dimensions	0.065 kgs	09mm(D) * 110mm(H)
Weight	Dimensions					
0.065 kgs	09mm(D) * 110mm(H)					

