

EIDW AD 2.1 AERODROME LOCATION INDICATOR AND NAME

EIDW – DUBLIN/International

EIDW AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP and its site	532517N 0061612W Midpoint RWY 10R/28L
2	Direction and distance from (city)	10 KM (5.4 NM) N of Dublin
3	AD Elevation, Reference Temperature & Mean Low Temperature	243 ft AMSL / 19.7°C (Max Temp) 0.1°C (MNM Temp)
4	Geoid undulation at AD ELEV PSN	184 ft
5	MAG VAR/Annual change	2° W (2022) / 11' decreasing
6	AD Operator, address, telephone, telefax, email, AFS, Website	Post: daa plc. Dublin Airport Co Dublin Phone:+ 353 1 944 1111 Fax: + 353 1 944 4715, AVBL H24 SITA: DUBRN7X, Airport Administration AFS: EIDWYDYX
7	Types of traffic permitted (IFR/VFR)	IFR/VFR
8	Contact Details	Post: Resource Allocation Unit (for stand allocation) Phone: +353 1 944 5228 Email: ops.aoso@daa.ie Post: Airside Operations and Safety Officers (AOSO) Phone: + 353 87 2892277 Email: AMU@daa.ie Post: Airport Duty Manager Phone: + 353 87 2892222 Email: Airportdmdublin@daa.ie
9	Remarks	Nil

EIDW AD 2.3 OPERATIONAL HOURS

1	AD Operator	H24
2	Customs and immigration	Customs/Irish Immigration: H24 Department of Agriculture, Food and the Marine: H24 US Customs and Border Protection: By prior negotiation with Dublin US Embassy, USCBP 0700 - 1700

3	Health and sanitation	H24
4	AIS Briefing Office	See Remarks
5	ATS Reporting Office (ARO)	H24
6	MET Briefing Office	H24
7	ATS	H24
8	Fuelling	H24
9	Handling	H24
10	Security	H24
11	De-icing	H24
12	Remarks	Airport closed on 25th December. Exact hours advised by NOTAM. PIB AVBL from AIS, Shannon see GEN 3.1.5

EIDW AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo handling facilities:	Available from IAG Cargo, Swissport Cargo and WFS
2	Fuel/oil types	JET A1Fuel Oil Grades 100, 100W, 100U, 100E, 120, W80, E80. Turbo Oils 750, 390, 2380
3	Fuelling facilities/capacity	JET A1 H24 No limitations. Hydrant fuelling available on Pier 1 and Pier 4 stands. Fuelling by bowser available on all other stands.
4	De-icing facilities	On request from Signature and Swissport.
5	Hangar space available for visiting aircraft	On request from Dublin Aerospace and Aer Lingus.
6	Repair facilities for visiting aircraft	Repair facilities from Dublin Aerospace.
7	Remarks	Passenger Handling: Available from Swissport, Sky Handling, Signature Flight Support (Corporate), Universal Aviation (Corporate). Catering: Available from Gate Gourmet and Dnata Catering. General Aviation Handling: Signature Flight Support, Universal Aviation, (Other ground handlers listed above on request). Fixed ground power: Pier 1: Stands 121 to 127 inclusive, Stands 108L to 111R inclusive Pier 3: Stands 311C/311R, 312, 313C, 314, 315C, 316, 317, 318L, 318C and 318R Pier 4: Stands 400L to 409R inclusive Aircraft Power Plant Test Runs: See EIDW AD 2.20

EIDW AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of AD	Hotels At Airport and in Dublin area. See www.booking.com Link in doc
2	Restaurant(s) at or in the vicinity of AD	See www.dublinairport.com
3	Transportation possibilities	Buses, taxis, car hire AVBL at Airport
4	Medical facilities	First aid treatment, All Airport Police are trained Emergency first Responders (ERFs), Rescue and Fire Fighting Services Personnel (RFFS) Paramedics with 1 domestic ambulance. Hospitals in Dublin, 8km.
5	Bank and Post Office at or in the vicinity of AD	ATM and Bureau De Change available at Airport No Post Office at Airport
6	Tourist Office	At Airport
7	Remarks	Short term Car Parking - 3750 spaces Long term Car Parking - 18600 spaces Executive lounges - See www.dublinairport.com

EIDW AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	Required CAT 9 Available CAT 9
2	Rescue equipment	Emergency lighting and other equipment adequate to meet Category 9 requirements
3	Capability for removal of disabled aircraft	Aircraft Recovery Coordinator Mr Odhran McCann - Airfield Delivery Manager Phone:+353 (0)87 203 5950 Capability Up to Code C aircraft (nosewheel recovery up to Code E) Details available from Coordinator (Utilising equipment available at Dublin Airport)
4	Remarks	Communication with Rescue and Fire Fighting Service: Frequency 121.600 MHz AVBL for direct communication between ACFT and Rescue and Fire Fighting Service. 121.600 MHz should be requested initially via ATC. Call sign for the Rescue and Fire Fighting Service is 'Dublin Fire'. It is mandatory for both ACFT and Rescue and Fire Fighting Service to maintain contact with ATC at all times. ATC do not have access to 121.600 MHz. Frequency 121.600 MHz is H24 and AVBL within 10 NM radius of Dublin Airport

EIDW AD 2.7 SEASONAL AVAILABILITY - CLEARING RUNWAY SURFACE CONDITION ASSESSMENT AND REPORTING AND SNOW PLAN

1	Type(s) of clearing equipment	Snow clearing and anti-icing equipment including: Sweeper-blowers Tractors equipped with ploughs or brushes Sprayers of de-icing fluid Snow blowers Ramp ploughs/brushes Motorised brushes
2	Clearance priorities	1. Duty runway(s) and associated taxiways, aircraft stands, together with apron areas. 2. Other areas.
3	Use of material for movement area surface treatment	De/anti-icing of aircraft movement areas carried out as required using potassium acetate fluids (KAC) and potassium formate (KFOR) See also AD 1.2 .
4	Specially prepared winter runways	Nil
5	Remarks	Annual snow plan available from the Aerodrome Operator on request. AD Operator H24, Airport closed on 25th December. Exact hours advised by NOTAM.

EIDW AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATION DATA

1	Apron surface and strength	Surface: CONC Strength: PCN 70/R/C/W/U			
2	Taxiway width, surface and strength	TAXIWAY	WIDTH	SURFACE	STRENGTH
		A	23 M	ASPH	PCN 97/R/C/W/T
		B1	24 M	CONC	PCN 108/R/B/W/T
		B2	24 M	CONC	PCN 97/R/B/W/T
		C	23 M	CONC	PCN 107/R/C/W/T
		DN	15 M	CONC	PCN 107/R/C/W/T
		DS	15 M	CONC	PCN 107/R/C/W/T
		E1	23 M	CONC/ASPH	PCN 120/F/B/W/T
		F-Inner	15 M	CONC	PCN 100/R/B/W/T
		F-Outer	23 M	CONC	PCN 109/R/B/W/T
		F1	25 M	CONC/ASPH	PCN 88/R/C/W/T
		F2	23 M	CONC	PCN 98/R/B/W/T
		F3	23 M	CONC	PCN 98/R/B/W/T
		H1	23 M	CONC/ASPH	PCN 84/R/B/W/T
K	23 M	CONC	PCN 114/R/C/W/T		
M	23 M	CONC	PCN 114/R/C/W/T		
M1	25 M	CONC/ASPH	PCN 120/R/A/W/T		

	N	23 M	CONC	PCN 114/R/C/W/T
	N1	24 M	CONC	PCN 114/R/C/W/T
	N2	27 M	CONC	PCN 114/R/C/W/T
	N3	23 M	CONC	PCN 114/R/C/W/T
	N4	23 M	CONC/ASPH	PCN 98/F/C/W/T
	N5	23 M	CONC	PCN 114/R/C/W/T
	N6	26 M	CONC	PCN 114/R/C/W/T
	N7	25 M	CONC	PCN 114/R/C/W/T
	P1	23 M	CONC/ASPH	PCN 68/R/B/W/T
	S	23 M	CONC/ASPH	PCN 95/R/B/W/T
	S1	23 M	CONC	PCN 60/R/B/W/T
	S2	23 M	ASPH	PCN 70/R/C/W/U
	S3	23 M	ASPH	PCN 48/R/B/W/T
	S4	23 M	CONC	PCN 60/R/B/W/T
	S5	30 M	CONC	PCN 55/R/B/W/T
	S6	23 M	CONC	PCN 59/R/B/W/T
	S7	23 M	ASPH	PCN 95/R/B/W/T
	W1	25 M	ASPH	PCN 120/R/A/W/T
	W2	23 M	ASPH	PCN 120/F/A/W/T
	W3	23 M	CONC	PCN 73/R/A/W/T
	W4	15 M	ASPH	PCN 52/R/B/W/T
	Z	23 M	ASPH	PCN 114/R/C/W/T
	LINK 1	33 M	CONC	PCN 110/R/C/W/T
	LINK 2	65 M	CONC/ASPH	PCN 70/R/C/W/U
	LINK 3	42 M	CONC	PCN 79/R/B/W/T
	LINK 4	73 M	CONC	PCN 84/R/A/W/T
	LINK 5	23 M	CONC/ASPH	PCN 108/R/B/W/T
	LINK 6	23 M	CONC	PCN 109/R/C/W/T
	LINK 7	23 M	CONC	PCN 114/R/C/W/T
	AT 1	47 M	CONC	PCN 70/R/C/W/U

		AT 2	47 M	CONC	PCN 70/R/C/W/U
		AT 3	61 M	CONC	PCN 70/R/C/W/U
		AT 4	59 M	CONC	PCN 70/R/C/W/U
		AT 5	81 M	CONC/ASPH	PCN 70/R/C/W/U
		AT 6	58 M	CONC	PCN 70/R/C/W/U
		West Apron	86 M	CONC	PCN 70/R/C/W/U
		North Apron	48 M	CONC	PCN 70/R/C/W/U
		South Apron	30 M	CONC	PCN 70/R/C/W/U
3	Altimeter checkpoint location and elevation	Location: South Apron / Elevation: 201ft AMSL			
4	VOR checkpoint	Nil			
5	INS checkpoint	EIDW AD 2.24-2			
6	Remarks	Nil			

EIDW AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	<p>Taxiing guidance signs at all intersections and at holding points. Mandatory signs lighted. Guidelines on aprons and taxiways. Taxiway information markings. AVDGS is installed on majority of stands. Where AVDGS is available and operational, it is mandatory for it to be used. On stands where AVDGS is not available or not operational Marshalls must be provided. No aircraft should enter a stand without guidance.</p> <p>If AVDGS is not operational on the stands listed below, the aircraft listed cannot taxi onto stand due to reduced clearances. Aircraft will be allocated an alternative stand or must shut down engines and tow on.</p> <p>Stand Restrictions: Stand 313C - B777-300. Stand 314 - B787-900, A330-200 and A330-300. Stand 316 - All A/C types. Stand 409C - All A/C types.</p>
2	RWY/TWY markings and LGT	<p>RWY 10R/28L Designation, THR, TDZ, centreline, side stripe, aiming point. Rapid exit taxiway indicator markings for TWY S5 located on RWY 28L.</p> <p>RWY 10L/28R Designation, THR, TDZ, centreline, side stripe, aiming point. Rapid exit taxiway indicator markings for TWY N3 on RWY 10L & N5 for RWY 28R.</p> <p>RWY 16/34 Designation, THR, TDZ, centreline, side stripe, aiming point. For the purposes of Taxiing Intermediate holding positions.</p> <p>Taxiways Centreline, edge stripes, holding positions, intersection markings except TWY S1.</p> <p>Intermediate holding position lights on TWY H1, M1, W2, Link 1, Link 2, Link 3, Apron Taxiway 6 and RWY 16/34 at 16-1 and 34-2, 16-2, K, N, M, F-Outer.</p>

3	Stop bars	<p>Switchable Stop bars at CAT II/III Runway Holding Position on TWY E1, S7, N2. Switchable Stop bars at CAT I Runway Holding Position on TWY A, B2, E1, H1, M1, N, N2, N4, P1, S, S1, S2, S3, S4, S5, S6, S7, W1, W2, W3, W4, RWY 34.</p> <p>Switchable Stop bars at co-located CAT I/II/III Runway Holding Position on N1, N4, N6, N7. Switchable Stop bars at RWY 28L.</p> <p>Fixed Stop bars on TWY A, H1, S1, S2, S3, S4, S5, S6, RWY 34.</p> <p>No Entry bars on RWY 34, RET N3, RET N5.</p> <p>Runway Guard lights on TWY A, B2, E1, H1, N, N1, N2, N3, N4, N5, N6, N7, M, M1, P1, S, S1, S2, S3, S4, S5, S6, S7, W1, W3, W4.</p>
4	Other RWY Protection measures	-
5	Remarks	See also EIDW AD 2.14 and 2.15 for lighting

EIDW AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		
RWY/Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
10R/APCH 28L/TKOF	Localizer 28L 79.5 M / 261 ft LGTD	532521.59N 0061739.60W	ESB Pylon 132.2 M / 434 ft Nil	532435.44N 0062032.45W	
	TV Aerial 96.8 M / 318 ft Nil	532531.16N 0061820.91W	ESB Pylon 131.8 M / 433 ft Nil	532451.14N 0062101.37W	
	TV Aerial 105.0 M / 344 ft Nil	532515.01N 0061832.98W	ESB Pylon 127.2 M / 418 ft Nil	532424.91N 0062002.20W	
10L/APCH 28R/TKOF	Localizer 28R 74.4 M / 244 ft	532615.51N 0061721.57W	ESB Pylon 120.5 M / 396 ft Nil	532426.46N 0062021.07W	
16/APCH 34/TKOF	Approach Light 71.5 M / 235 ft LGTD	532621.26N 0061549.01W	ESB Pylon 119.6 M / 393 ft Nil	532419.76N 0061858.91W	
	Approach Light 72.0 M / 237 ft LGTD	532622.47N 0061548.99W	ESB Pylon 118.3 M / 389 ft Nil	532423.49N 0061944.31W	
	Approach Light 72.0 M / 237 ft LGTD	532622.08N 0061550.49W	ESB Pylon 120.5 M / 396 ft Nil	532422.17N 0061928.25W	

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY/Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
	Approach Light 72.5 M / 238 ft LGTD	532623.14N 0061550.37W	ESB Pylon 131.8 M / 433 ft Nil	532443.18N 0062041.84W	
	Approach Light 73.0 M / 240 ft LGTD	532624.00N 0061551.00W	Mast on 3 Rock 590.7 M / 1938 ft LGTD	531440.15N 0061417.75W	
	Approach Light 70.9 M / 233 ft Nil	532613.09N 0061552.93W	Mast on Kippure 880.8 M / 2890 ft LGTD	531040.98N 0061953.71W	
	Approach Light 72.0 M / 237 ft Nil	532613.15N 0061556.45W	Mast on Knockbrack 224.1 M / 735 ft LGTD	533432.68N 0061543.45W	
	Tree 77.0 M / 253 ft Nil	532612.35N 0061602.74W	Atlantic 252 Mast 355.7 M / 1167 ft LGTD	532745.68N 0064039.11W	
28L/APCH 10R/TKOF	Nil		ESB Pylon 120.5 M / 396 ft Nil	532422.17N 0061928.25W	
28R/APCH 10L/TKOF	Localizer 10L 68.4 M / 225 ft	532604.50N 0061401.35W	ESB Pylon 132.2 M / 434 ft Nil	532435.44N 0062032.45W	
34/APCH 16/TKOF	Mobile Obstacle 62.0 M / 204 ft Nil	532504.95N 0061458.51W	Mast 124.0 M / 407 ft Nil	532607.55N 0062340.13W	
	Localizer 16 63.3 M / 208 ft LGTD	532505.75N 0061454.26W	Chimneys 211.5 M / 694 ft LGTD	532024.88N 0061123.83W	
	Approach Light 64.0 M / 210 ft Nil	532503.79N 0061452.85W	ESB Pylon 119.9 M / 394 ft Nil	532420.89N 0061912.69W	
	Tree 65.3 M / 215 ft Nil	532503.82N 0061452.43W	Glide Antenna 10R 89.5 M / 294 ft LGTD	532515.50N 0061705.49W	
	Tree 68.4 M / 225 ft Nil	532503.34N 0061450.21W	Surface Radar 111.8 M / 367 ft Nil	532543.75N 0061548.24W	
	Tree 68.6 M / 225 ft Nil	532458.63N 0061452.01W	Glide Antenna 16 85.3 M / 280 ft LGTD	532602.68N 0061543.21W	
	Tree 68.8 M / 226 ft Nil	532456.57N 0061452.88W	Glide Antenna 28L 78.9 M / 259 ft LGTD	532509.62N 0061518.42W	

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY/Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
			Chimney 113.5 M / 373 ft Nil	532350.68N 0061547.05W	
			DME Antenna 72.9 M / 240 ft LGTD	532512.24N 0061613.89W	

EIDW AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	Dublin Airport
2	Hours of service	H24
3	Office responsible for TAF preparation Periods of validity	MET Eireann Central Aviation Office, Shannon 24 HR 6 HR
4	Type of landing forecast Interval of issuance	METAR TREND 30 MIN
5	Briefing/consultation provided	Computer-based self-briefing facility Personal briefing by telephone from Central Aviation Office, Shannon
6	Flight documentation Language(s) used	Charts and tabular English
7	Charts and other information available for briefing or consultation	6-hourly synoptic chart, 6-hourly prognostic chart (surface), prognostic chart of significant weather, prognostic chart of wind/temperature at upper levels, prognostic chart of tropopause levels
8	Supplementary equipment available for providing information	Weather RADAR, satellite cloud picture receiver, IRVR RWYs 10R and 28L (touchdown, midpoint, stop-end) IRVR RWYs 10L and 28R (touchdowns & midpoint) IRVR RWY 16 (touchdown, midpoint) Satellite Display available.
9	ATS units provided with information	Dublin TWR
10	Additional information (limitation of service, etc.)	GEN 3.5.4.2 to request additional information.

EIDW AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR Geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
10R	095.24°	2637 M x45 M	92/R/B/W/T ASPH ASPH	532520.75N 0061724.27W 532512.94N 0061502.08W 184 ft	THR 242ft
28L	275.27°	2637 M x45 M	92/R/B/W/T ASPH ASPH	532512.94N 0061502.08W 532520.75N 0061724.27W 184 ft	THR 202ft
10L	095.25°	3109 M x45 M	114/R/C/W/T CONC	532613.79N 0061650.22W 532605.39N 0061417.60W 184 ft	THR 235ft
28R	275.28°	3109 M x45 M	114/R/C/W/T CONC	532606.73N 0061441.87W 532614.62N 0061705.32W 183 ft	THR 213ft
16	156.59°	2072 M x45 M	84/R/B/W/T ASPH -	532613.16N 0061543.12W 532511.66N 0061458.54W 184 ft	THR 217ft
34	336.60°	2072 M x45 M	84/R/B/W/T ASPH -	532511.66N 0061458.54W 532613.16N 0061543.12W 184 ft	THR 202ft

Slope of RWY-SWY	SWY dimensions	CWY dimensions	Strip dimensions	RWY End Safety Area dimensions	Location and description of Arresting System	OFZ	Remarks
7	8	9	10	11	12	13	14
Slope of 0.47% Refer to Aerodrome Obstacle Chart Type A EIDW AD 2.24-3	91 M x 45 M	213 M x 150 M	2904 M x 280 M	240M long x 150M wide at both ends of RWY Strip	Nil		RWY 10R/28L, pavement surface is grooved asphalt. RWY 10R/28L is provided with 7.5 M wide asphalt shoulders.
	56 M x 45 M	213 M x 150 M	2904 M x 280 M	240M long x 150M wide at both ends of RWY Strip	Nil		Periodic closure for maintenance - Approximately every eight weeks, RWY 10R/28L will be closed for essential maintenance, including rubber removal, grass cutting, painting of day markings etc. The RWY will be closed for approximately four nights between 2230 HR and 0530 HR (local). These closures for maintenance will be promulgated by NOTAM.
Slope of 0.18% Refer to Aerodrome Obstacle Chart Type A EIDW AD 2.24-3	Nil	60 M x 150 M	3229 M x 280 M	240M long x 150M wide at both ends of RWY Strip	Nil		RWY 10L/28R pavement surface is grooved. RWY 10L/28R is provided with 7.5M wide concrete shoulders.
	Nil	60 M x 150 M	3229 M x 280 M	240M long x 150M wide at both ends of RWY Strip	Nil		CWY starts at end of RWY surface.
<p>a) The parallel runways (10R-28L and 10L-28R) shall be used in preference to the cross runway, 16-34,</p> <p>b) When winds are westerly, Runway 28L shall be preferred for arriving aircraft. Either Runway 28L or 28R shall be used for departing aircraft as determined by air traffic control,</p> <p>c) When winds are easterly, either Runway 10L or 10R as determined by air traffic control shall be preferred for arriving aircraft. Runway 10R shall be preferred for departing aircraft, and</p> <p>d) Runway 10L-28R shall not be used for take-off or landing between 2300 hours and 0700 hours, except in cases of safety, maintenance considerations, exceptional air traffic conditions, adverse weather, technical faults in air traffic control systems or declared emergencies at other airports.</p>							

Slope of RWY-SWY	SWY dimensions	CWY dimensions	Strip dimensions	RWY End Safety Area dimensions	Location and description of Arresting System	OFZ	Remarks
7	8	9	10	11	12	13	14
Slope of 0.24% Refer to Aerodrome Obstacle Chart Type A EIDW AD 2.24-5	Nil	183 M x 150 M	2192 M x 280 M	RWY16 THR (north end of RWY strip) 140M long x 150M wide. RWY16 END (south end of RWY strip) 138M long x 150M wide.	Nil		RWY 16/34, pavement surface is grooved asphalt. RWY 16/34 is provided with 8M wide asphalt shoulders. Runway Slope - Sharp slope change approximately 100m south of RWY 16 THR/ RWY 34 END, and runway slope of up to 1.1%. See EIDW AD 2.23.
	Nil	61 M x 150 M	2192 M x 280 M	RWY34 THR (south end of RWY strip) 138M long x 150M wide. RWY34 END (north end of RWY strip) 140M long x 150M wide.	Nil		

EIDW AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
10R	2637 M	2850 M	2728 M	2637 M	
28L	2637 M	2850 M	2693 M	2637 M	
10L	3109 M	3169 M	3109 M	2829 M	
28R	3109 M	3169 M	3109 M	2659 M	
16	2072 M*	2255 M	2072 M	2072 M	*Departures from RWY 16 are only available from intersection take off Twys N4 and N.
34	2072 M	2133 M	2072 M	2072 M	

INTERSECTION TAKE-OFF					
RWY Designator	TWY	TORA	TODA	ASDA	Remarks
10R	S6	2156 M	2369 M	2247 M	see EIDW AD 2.20
10R	S4	1352 M	1565 M	1443 M	
28L	S1	2415 M	2628 M	2471 M	
10L	N6	2860 M	2920 M	2860 M	
28R	N2	2641 M	2701 M	2641 M	
16	N4	2026 M	2209 M	2026 M	
16	N	1653 M	1836 M	1653 M	
34	A	1815 M	1876 M	1815 M	
34	B2	1815 M	1876 M	1815 M	
34	S1	1815 M	1876 M	1815 M	

EIDW AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ Length	RWY Centre Line LGT Length, spacing, colour, INTST	RWY edge LGT LEN, spacing, colour, INTST	RWY End LGT colour WBAR	SWY LGT LEN (M) colour	Remarks
1	2	3	4	5	6	7	8	9	10
10R	CAT II/III 900M LIH	Green LIH Green LIH	PAPI Both sides/ 3° MEHT 20M (439M)	900M 30M LIH	2637M 15M coded 0-1737M White, 1737M-2337M Red/White, 2337M-2637M Red LIH	2637M 60M nom White (last 600M Yellow) LIH	Red LIH -	Red LIH	Nil
28L	CAT II/III 900M LIH	Green LIH Green LIH	PAPI Both sides/3° MEHT 21M (374M)	900M 30M LIH	2637M 15M coded 0-1737M White, 1737M-2337M Red/White, 2337M-2637M Red LIH	2637M 60M nom White (last 600M Yellow) LIH	Red LIH -	Red LIH	RETILs (yellow) Prior to exit to TWY S5
10L	CAT II/III 900M LIH	Green LIH Green LIH	PAPI Both sides/3° MEHT 17.6M (398M)	900M 30M LIH	3109M 15M coded 0-2220M White, 2220M-2820M Red/White, 2820M-3109M Red LIH	3109M 60M nom White (last 600M Yellow) LIH	Red LIH	n/a	RETILs (yellow) Prior to exit to TWY N3
28R	CAT II/III 900M LIH	Green LIH Green LIH	PAPI Right side only 3° MEHT 16.8M (398M)	900M 30M LIH	3109M 15M coded 0-2205M White, 2205M-2805M Red/White, 2805M-3109M	3109M 60M nom White (last 600M Yellow) LIH	Red LIH	n/a	RETILs (yellow) Prior to exit to TWY N5
16	CAT I 910M LIH	Green LIH Green LIH	PAPI Both sides/3° MEHT 19M (380M)	Nil	Nil	2073M 60M nom White (last 600M Yellow) LIH	Red LIH -	Nil	Nil
34	SALS 426M LIL	Green LIH	PAPI Both sides/3° MEHT 20M (380M)	Nil	Nil	2073M 60M nom White (last 600M Yellow) LIH	Red LIH -	Nil	For small aircraft (A & B) Runway 34 end lights may not be sighted until the last 400 metres.

Note: All runway lighting with the exception of the PAPI's on Runway 10R/28L are LED.

EIDW AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	Nil
2	LDI location and LGT Anemometer location and LGT	Nil 2 Nr.
3	TWY edge and centre line lighting	Edge; blue all TWY and intersections except M1, S3, W2, W4. Edge, blue, RWY 16/34 from TWY A to THR 34 and TWY N to THR 16. Edge, blue, retroreflective markers TWY W4. Centreline, green (green/yellow on exit TWYs) TWY B1, B2, E1, F1, F2, F3, F-inner, F-outer, H1, M1, S, S1, S2, S5, S7, W1, W2 Link 2, Link 3, Link 4, K, N, N1, N2, N3, N4, N5, N6, N7, M. Note: All Taxiway Centreline lights are LED, all Stopbars are LED with the exception of S1 CAT III stopbar. Taxiway edge lights are a mixture of LED (circa 90%) and Halogen.
4	Secondary power supply/switch-over time	Secondary power supply provided, switch-over time 15 SEC (1 SEC in Low Visibility Procedures). Electric battery lamps.
5	Remarks	Apron - Floodlights Apron edge - Blue, omni-directional (mixture of LED & Halogen). Apron centreline lighting - Green bi-directional on all apron taxiways and taxilanes except Apron TWY 6 and West Apron (all LED). Obstacles: Fixed red (mixture of Neon & LED lights). WDIs 4-6 Nr. (2-4 lighted). See Aerodrome Chart EIDW AD 2.24-1

EIDW AD 2.16 HELICOPTER LANDING AREA

NIL

EIDW AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	533445N 0055420W, arc 15NM radius centre 532621N 0061508W, 531152N 0062130W, 531439N 0062130W, 531437N 0063707W, 532202N 0064237W, 532127N 0063758W, arc 5NM radius centre 532110N 0062938W, 532403N 0063626W, 532347N 0063117W, arc 10NM radius centre 532621N 0061508W, 533445N 0062411W.
2	Vertical limits	5000 ft
3	Airspace classification	C
4	ATS unit call sign Language(s)	Dublin Tower - English
5	Transition altitude	5000 ft

6	Hours of applicability	-
7	Remarks	Nil

EIDW AD 2.18 ATS COMMUNICATIONS FACILITIES

Service designation	Call sign	Channel(s)	SAT VOICE No	Logon Address	Hours of Operation	Remarks
1	2	3	4	5	6	7
Clearance Delivery Frequency	Dublin Delivery	122.985 MHz			0600-1800 local time	Aircraft Contact Minimum 15 Min before start-up. 8.33kHz Channel.
GND	Dublin Ground	121.800 MHz			0600-2400 local time	Non-8.33kHz equipped aircraft shall contact 121.8 MHz for ATC Clearance minimum 15 minutes prior to requested start up.
		125.885 MHz				GND NTH.
		130.790 MHz			H24	
TWR	Dublin Tower	118.600 MHz			H24	Primary TWR Frequency. Note: TWR STH when segregated runway mode in use (Monitor NOTAM for further information).
		124.680 MHz			H24	TWR NTH. Note: TWR NTH when segregated runway mode in use (Monitor NOTAM for further information).
		128.800 MHz			H24	Non 8.33kHz TWR NTH Frequency.
		119.805 MHz			H24	Dublin Tower Backup Channel. When instructed by ATC.
APP	Dublin Approach	121.100 MHz			H24	
		119.555 MHz			06:00 to 24:00L	
		133.280 MHz			06:00 to 24:00L	
		119.930 MHz			H24	Final Controller
ACC	Dublin Control	129.180 MHz			All H24	Upper North
		135.655 MHz				Upper South
		132.580 MHz				Lower North
		120.755 MHz				Lower South
		124.650 MHz				H24
	126.250 MHz					
Dublin Departure	127.865 MHz			H24	Dublin Departure NTH when segregated runway mode in use (Monitor NOTAM for further information).	
	123.990 MHz			H24	Dublin Departure STH when segregated runway mode in use (Monitor NOTAM for further information).	

Service designation	Call sign	Channel(s)	SAT VOICE No	Logon Address	Hours of Operation	Remarks
1	2	3	4	5	6	7
FIS	Dublin Flight Information Service	118.500 MHz			As promulgated on ATIS	As required.
ATIS	Dublin Information Arrival	124.530 MHz			0515-2200 Local time	
	(Dublin Information Departure)	129.640 MHz			0515-2200 Local time	Not notified as yet operationally available (Monitor NOTAM for further information).
VOLMET	Dublin VOLMET	127.005 MHz			H24	
D-ATIS	Dublin Information				0515-2200 Local time	Operators equipped with AEEC623 compliant ACARS-MU can interface with the service through ARINC and SITA service provider's network.

EIDW AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OP (for VOR/ILS/MLS/GNSS/SBAS and GBAS, give declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna or SBAS: ellipsoid height of LTP/FTP	Service Volume Radius from the GBAS Reference Point	Remarks
1	2	3	4	5	6	7	8
DVOR/DME 2° W (2021)	DUB	114.9MHz CH 96X	H24	532957.8N 0061825.6W	200ft		100/500, 300/700 (180° T-360° T) with purpose A,T,E
DVOR/DME 2° W (2021)	DAP	111.20MHz CH 49X	H24	532525.0N 0061810.0W	300ft		Designated Operational Coverage 150NM
DVOR/DME 2° W (2020)	BAL	115.8MHz CH105X	H24	531759.6N 0062652.0W	300ft		Designated Operational Coverage 60 NM Operating Authority Minister for Defence. BAL DVOR unusable in sector R150 to R170 below 5500 ft AMSL outside 20 NM due to terrain. Due to rising terrain to the south of facility, aircrew may observe BAL DME unlocks in sectors R150 to R175 and R195 to R205 below 4500 ft AMSL outside 20 NM.

Type of aid, MAG VAR, Type of supported OP (for VOR/ILS/ MLS/GNSS/ SBAS and GBAS, give declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna or SBAS: ellipsoid height of LTP/ FTP	Service Volume Radius from the GBAS Reference Point	Remarks
1	2	3	4	5	6	7	8
NDB	KLY	378kHz	H24	531610.4N 0060623.2W			Designated Operational Coverage 50NM ACFT may not obtain guidance beyond 45NM below 8,000ft, in the sector between bearings 180° T and 270° T.
NDB	GMN	334kHz	H24	533853.2N 0061336.0W			Designated Operational Coverage 30NM Operating Authority Minister for Defence.
DME	GMN	76X 112.9MHz	H24	533848.5N 0061405.7W	100ft		Designated Operational Coverage 30NM. Operating Authority Minister for Defence.
ILS LOC RWY 10R CAT IIIa 2° W (2020)	IDE	108.9MHz	H24	532511.8N 0061440.8W *			Coverage restricted to 35° either side of course line. Signals received outside the coverage sector including back beam radiation should be ignored * Data whose accuracy has not been quality assured
ILS GP RWY 10R		329.3MHz	H24	532515.5N 0061705.5W			GP angle 3° RDH 54ft
ILS DME RWY 10R	IDE	CH 26X (108.9MHz)	H24	532515.5N 0061705.5W	290ft		DME zero range is indicated at THR RWY 10R
LO RWY 10R	OE	316kHz	H24	532548.6N 0062543.7W			
OM RWY 10R	2 dashes per sec.	75MHz	H24	532547.8N 0062543.5W			
MM RWY 10R	Dots and dashes	75MHz	H24	532523.6N 0061816.8W			
ILS LOC RWY 28L CAT IIIa 2° W (2020)	IDW	111.35MHz	H24	532521.8N 0061743.7W *			Coverage restricted to 35° either side of course line. Signals received outside the coverage sector including back beam radiation should be ignored * Data whose accuracy has not been quality assured
ILS GP RWY 28L		332.15MHz	H24	532509.6N 0061518.4W			GP angle 3° RDH 54ft
ILS DME RWY 28L	IDW	CH 50Y (111.35MHz)	H24	532509.6N 0061518.4W	260ft		DME zero range is indicated at THR RWY 28L
LO RWY 28L	OP	397kHz	H24	532449.7N 0060818.1W			

Type of aid, MAG VAR, Type of supported OP (for VOR/ILS/ MLS/GNSS/ SBAS and GBAS, give declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna or SBAS: ellipsoid height of LTP/ FTP	Service Volume Radius from the GBAS Reference Point	Remarks
1	2	3	4	5	6	7	8
OM RWY 28L	2 dashes per sec	75MHz	H24	532450.5N 0060818.4W			
MM RWY 28L	Dots and dashes	75MHz	H24	532510.0N 0061409.2W			
ILS LOC RWY 10L CAT IIIb 2° W (2022)	INDL	109.55MHz	H24	532604.5N 0061401.4W			Coverage restricted to 35° either side of course line. Signals received outside the coverage sector including back beam radiation should be ignored.
ILS GP RWY 10L		332.45MHz	H24	532616.9N 0061630.2W			GP angle 3° RDH 51ft.
ILS DME RWY 10L	INDL	CH 32Y (109.55MHz)	H24	532616.9N 0061630.2W	250ft		DME zero range is indicated at THR RWY 10L
ILS LOC RWY 28R CAT IIIb 2° W (2022)	INDR	110.15MHz	H24	532615.5N 0061721.6W			Coverage restricted to 35° either side of course line. Signals received outside the coverage sector including back beam radiation should be ignored.
ILS GP RWY 28R		334.25MHz	H24	532611.9N 0061458.7W			GP angle 3° RDH 51ft.
ILS DME RWY 28R	INDR	CH 38Y (110.15MHz)	H24	532611.9N 0061458.7W	230ft		DME zero range is indicated at THR RWY 28R
ILS LOC RWY 16 CAT I 2° W (2020)	IAC	111.5MHz	H24	532505.7N 0061454.2W *			Coverage restricted to 35° either side of course line. Signals received outside the coverage sector including back beam radiation should be ignored. * Data whose accuracy has not been quality assured
ILS GP RWY 16		332.9MHz	H24	532602.7N 0061543.2W			GP angle 3°
ILS DME RWY 16	IAC	CH 52X	H24	532602.7N 0061543.2W	280ft		DME zero range is indicated at THR RWY 16.
SBAS (LPV, LNAV/VNAV, LNAV RWY28L)	GPS & EGNOS E28A	1575.42 MHz CH 59277	H24	N/A	LTP/FTP Ellipsoid Height 117.1 M	N/A	Transmitting antennas are satellite based.
SBAS (LPV, LNAV/VNAV, LNAV RWY 10R)	GPS & EGNOS E10A	1575.42 MHz CH 41225	H24	N/A	LTP/FTP Ellipsoid Height 130.3 M	N/A	Transmitting antennas are satellite based.

Type of aid, MAG VAR, Type of supported OP (for VOR/ILS/ MLS/GNSS/ SBAS and GBAS, give declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna or SBAS: ellipsoid height of LTP/ FTP	Service Volume Radius from the GBAS Reference Point	Remarks
1	2	3	4	5	6	7	8
SBAS (LPV, LNAV/VNAV, LNAV RWY 28R)	GPS & EGNOS E28B	1575.42 MHz CH 74379	H24	N/A	LTP/FTP Ellipsoid Height TBC	N/A	Transmitting antennas are satellite based.
SBAS (LPV, LNAV/VNAV, LNAV RWY 10L)	GPS & EGNOS E10B	1575.42 MHz CH 52341	H24	N/A	LTP/FTP Ellipsoid Height TBC	N/A	Transmitting antennas are satellite based.
SBAS (LPV, LNAV/VNAV, LNAV RWY16)	GPS & EGNOS E16A	1575.42 MHz CH 44282	H24	N/A	LTP/FTP Ellipsoid Height 122.6 M	N/A	Transmitting antennas are satellite based.
SBAS (LPV, LNAV/VNAV, LNAV RWY34)	GPS & EGNOS E34A	1575.42 MHz CH 86156	H24	N/A	LTP/FTP Ellipsoid Height 117.9 M	N/A	Transmitting antennas are satellite based.

EIDW AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Ground Movement

1.1 General

- i. Stop-bars are provided at all runway entry/exit points and are illuminated to protect active runways. When a runway is inactive the associated stop-bar is normally not illuminated. However, specific clearance from ATC must still be obtained before entering or crossing an inactive runway.
- ii. Pilots should use the minimum power necessary while taxiing. In apron areas, pilots should operate at the minimum power commensurate with the intended manoeuvre, due to the effect of jet blast on personnel, equipment and buildings.
- iii. Flight crew are responsible for wing tip clearance and are reminded of the importance of maintaining a careful lookout at all times, regardless of location and visibility conditions.
- iv. ATC may require aircraft to manoeuvre in close proximity to other aircraft. Avoidance of other aircraft is the responsibility of the flight crew involved. If doubt exists as to whether an aircraft can be passed safely, the flight crew should stop, advise ATC, and request alternative instructions if available.
- v. In order to assist in the maintenance of safe separation of aircraft, when flight crew are instructed to stop at any runway-holding or intermediate holding position they should position the aircraft as close as possible to the relevant pavement marking while ensuring that the marking remains visible from the cockpit.

1.2 Turning

No turns should be made at the following runway/taxiway intersections:

- No turns should be made by aircraft from RWY 28R to TWY N3 or vice versa.
- No turns should be made by aircraft from RWY 28R to TWY N4 or vice versa.
- No turns should be made by aircraft from RWY 28R to RWY 16 or vice versa.

- No turns should be made by aircraft from RWY 10L to TWY N5 or vice versa.
- No turns should be made by aircraft from RWY 10L to RWY 16 or vice versa.
- No left turns should be made by aircraft from TWY M to RWY 34 or vice versa.

No turns should be made at taxiway/taxiway intersections where taxi centreline markings are not provided.

Particular attention is drawn to the following:

- No turns should be made by aircraft from TWY W1 to TWY S East of TWY W1 or vice versa.
- No turns should be made by aircraft from TWY F1 to TWY B2 or vice versa.
- No turns should be made by aircraft from TWY B2 to TWY E1 or vice versa.
- No turns should be made by aircraft from TWY A to TWY F1 or vice versa.
- No turns should be made by aircraft from TWY W1 to TWY W2 or vice versa at intersection with TWY S.
- No turns should be made by aircraft from TWY M to TWY N5.
- No turns should be made by aircraft from TWY N to TWY N3.

1.3 Taxiing Restrictions

Location	Situation	Restriction
TWY A	Outbound aircraft holding on TWY A	Aircraft movement not permitted between TWY F1 and Link 2 / TWY F2 or vice versa
TWY B1	Aircraft with wingspan 36m or greater operating on TWY B1	Aircraft not permitted on TWY Z
TWY B2	Outbound aircraft (wingspan less than 36m) holding on TWY B2	Aircraft movement not permitted between TWY F1 and TWY E1 / TWY B1 or vice versa
TWY B2	Outbound aircraft (wingspan 36m or greater) holding on TWY B2	Aircraft movement not permitted between TWY F1 and TWY E1 / TWY B1 or vice versa and Aircraft are not permitted to taxi between TWY E1 and TWY B1 / TWY Z or vice versa
TWY B2	Inbound aircraft (wingspan less than 36m) holding on TWY B2	Movement between TWY A and RWY16-34 / TWY S / TWY S1 or vice versa restricted to aircraft with wingspan less than 36m
TWY B2	Inbound aircraft with wingspan 36m or greater holding on TWY B2	Aircraft movement not permitted between TWY A and RWY16-34 / TWY S / TWY S1 or vice versa
APRON TAXIWAY C	Aircraft operating on Apron Taxiway C	Aircraft not permitted on Apron Taxiway DN or Apron Taxiway DS
APRON TAXIWAY DN	All operations	Restricted to aircraft with wingspan less than 36m
APRON TAXIWAY DN	Aircraft operating on Apron Taxiway DN	Aircraft not permitted on Apron Taxiway C
APRON TAXIWAY DS	All operations	Restricted to aircraft with wingspan less than 36m
APRON TAXIWAY DS	Aircraft operating on Apron Taxiway DS	Aircraft not permitted on Apron Taxiway C
TWY E1	Outbound aircraft (wingspan less than 36m) holding on TWY E1	Movement between TWY B1 and TWY B2 / TWY F1 or vice versa restricted to aircraft with wingspan less than 36m
TWY E1	Outbound aircraft (wingspan 36m or greater) holding on TWY E1	Aircraft movement not permitted between TWY B1 and TWY B2 / TWY F1 or vice versa
TWY F1	Aircraft travelling towards LINK1 / TWY B1 / TWY E1 holding on TWY F1	Aircraft movement not permitted between TWY A and LINK 2 / TWY F2 or vice versa
TWY F1	Aircraft travelling towards LINK 2 / TWY F2 holding on TWY F1	Aircraft movement not permitted between TWYs B1 and B2 or vice versa or between TWY E1 and TWY B1 / TWY Z or vice versa

Location	Situation	Restriction
APRON TAXIWAY F-INNER	All operations	Restricted to aircraft with wingspan less than 36m
TWY K	All operations	Restricted to Code E aircraft (less than 65m wingspan) Note A340 operations are prohibited on TWY K
TWY K	All operations	Aircraft movement not permitted on to TWY N behind holding aircraft on N1
TWY K	All operations	Aircraft movement not permitted on to TWY N if aircraft holding on N2
TWY N	All operations	Aircraft movement not permitted to pass behind aircraft holding on TWY N awaiting intersection take-off on RWY 16
TWY N	All operations	Aircraft movement not permitted to pass behind aircraft holding on TWY N1 onto TWY K
TWY N1	All operations	Aircraft movement not permitted on to TWY N2 behind holding outbound aircraft
TWY N1	All operations	Aircraft movement not permitted on to TWY N behind holding aircraft on TWY K
TWY N2	All operations	Aircraft movement not permitted on to TWY N1 behind holding aircraft
TWY N2	All operations	Aircraft movement not permitted on to TWY N2 if aircraft holding on TWY N1
TWY N3	All operations	No Entry allowed for aircraft from TWY N
TWY N3	All operations	No Entry allowed for aircraft towing or taxiing on R28R from a westerly direction
TWY N4	All operations	Restricted to code E aircraft (less than 65m wingspan)
TWY N4	All operations	No Entry allowed for aircraft on to TWY N4 when 28R is the active runway
TWY N4	All operations	No Entry allowed for aircraft towing or taxiing on RWY 28R in a westerly direction from
TWY N5	All operations	No Entry allowed for aircraft from TWY M
TWY N5	All operations	No Entry allowed for aircraft towing or taxiing on RWY10L in an easterly direction
TWY N6	All operations	Aircraft movement not permitted from TWY M on to TWY N7 behind holding aircraft
TWY N7	All operations	Aircraft movement not permitted from TWY M on to TWY N6 behind holding aircraft
TWY S3	All operations	Restricted to daylight hours only and aircraft with wingspan 30m or less
TWY S5	Outbound aircraft (wingspan less than 36m) holding on TWY S5	Movement on TWY S behind holding aircraft restricted to aircraft with wingspan less than 36m
TWY S5	Outbound aircraft (wingspan 36m or greater) holding on TWY S5	Aircraft movement not permitted on TWY S behind holding aircraft
TWY S6	Outbound aircraft (wingspan less than 36m) holding on TWY S6	Movement on TWY S behind holding aircraft restricted to aircraft with wingspan less than 36m
TWY S6	Outbound aircraft (wingspan 36m or greater) holding on TWY S6	Aircraft movement not permitted on TWY S behind holding aircraft
TWY Z	Aircraft operating on TWY Z	TWY B1 restricted to aircraft with wingspan less than 36m

Location	Situation	Restriction
RWY 16-34 CAT I Runway Holding position for RWY 10R- 28L	Outbound aircraft (wingspan less than 36m) holding on RWY 16-34 for entry to RWY 10R-28L	Movement through the intersection of RWY 34 and TWYs A, B2, S, S1 restricted to aircraft with wingspan less than 36m
RWY 16-34 CAT I Runway Holding position for RWY 10R- 28L	Outbound aircraft (wingspan 36m or greater) holding on RWY 16-34 for entry to RWY 10R-28L	Aircraft movement not permitted through the intersection of RWY 34 and TWYs A, B2, S, S1.

1.4 Apron Operations

Apron Taxiway 1 and Apron Taxiway 2, the aircraft stand taxilanes serving Stands 121L-127, 130-131S, and 200L-203L are restricted to aircraft with a maximum wingspan of 36m.

Apron Taxiway 3, the aircraft stand taxilane serving Stands 205R-207T and 311L-313L, is restricted to aircraft with a maximum wingspan of 41.10m.

The aircraft stand taxilane serving Stands 412-418 is restricted to aircraft with a maximum wingspan of 36m.

1.5 Use of Runways (General)

1.5.1 The parallel runways (10R-28L and 10L-28R) shall be used in preference to the crosswind runway, 16-34,

1.5.2 When winds are westerly, Runway 28L shall be preferred for arriving aircraft. Either Runway 28L or 28R shall be used for departing aircraft as determined by air traffic control,

1.5.3 When winds are easterly, either Runway 10L or 10R as determined by air traffic control shall be preferred for arriving aircraft. Runway 10R shall be preferred for departing aircraft, and

1.5.4 Runway 10L-28R shall not be used for take-off or landing between 2300 hours and 0700 hours, except in cases of safety, maintenance considerations, exceptional air traffic conditions, adverse weather, technical faults in air traffic control systems or declared emergencies at other airports.

1.6 Runway 16-34 Operations

Unless otherwise instructed by ATC, aircraft vacating the runway must not stop on any of the following adjoining taxiways: E1, B2, A, H1, M1, P1 or N. Aircraft vacating the runway and stopping in any of these taxiways are not clear of the runway.

Aircraft exiting the runway via TWY N4 must continue on to the section of taxiway parallel to the runway to clear the runway. Aircraft on the adjacent parallel taxiways must give way to aircraft vacating the runway.

1.7 Runway 28L Operations

Unless otherwise instructed by ATC, aircraft vacating the runway must not stop on any of the following taxiways: S3, S4, S5, S6. Aircraft vacating the runway and stopping on any of these taxiways are not clear of the runway. Aircraft exiting onto TWY S7 must continue on to the section of TWY S parallel to the runway to clear the runway. Aircraft on the adjacent parallel taxiways must give way to aircraft vacating the runway.

1.8 Runway 10R Operations

Unless otherwise instructed by ATC, aircraft vacating the runway must not stop on any of the following taxiways: S2, S3 and S4. ATC may instruct arrivals to stop on taxiways E1 or S1 on a tactical basis. Aircraft vacating the runway and stopping on any of these taxiways are not clear of the runway. Aircraft on the adjacent parallel taxiways must give way to aircraft vacating the runway.

1.9 Runway 28R Operations

Unless otherwise instructed by ATC, aircraft vacating the runway must not stop on any of the following taxiways: N5, N6 and N7. Aircraft vacating the runway and stopping on any of these taxiways are not clear of the runway. Aircraft

exiting these taxiways must continue on to the section of TWY M parallel to the runway to clear the runway. Aircraft on the adjacent parallel taxiways must give way to aircraft vacating the runway.

1.10 Runway 10L Operations

Unless otherwise instructed by ATC, aircraft vacating the runway must not stop on any of the following taxiways: N4, N3, N2 and N1. Aircraft vacating the runway and stopping on any of these taxiways are not clear of the runway. Aircraft exiting these taxiways must continue on to the section of TWY N parallel to the runway to clear the runway. Aircraft on the adjacent parallel taxiways must give way to aircraft vacating the runway.

2. Availability of Intersection Take-Off

Take-offs using less than the full length of the runway are available (except during Low Visibility Operations) from TWY/RWY intersections as listed in [EIDW AD 2.13](#)

During Low Visibility Operations, intersection take-offs using less than the full length are NOT permitted from RWY10R/28L.

The datum from which the reduced declared distances on RWY10R/28L, RWY 10L/28R and RWY16 are measured is the downwind edge of the specific taxiway projected perpendicular to the runway centreline as per section III-3 of the European Air Navigation Plan

The datum from which the reduced declared distances on RWY34 are measured is the intersection of the extended downwind edge of Taxiway S with the runway edge projected perpendicular to the runway centreline.

The take-off run available (TORA) is displayed on an illuminated sign adjacent to the taxiway.

2.1 RWY10R/28L and RWY 16/34

Intersection take-offs are subject at all times to pilots' discretion and aircraft operational requirements. Pilots should advise as early as possible of their ability to accept intersection take-offs.

Approval for intersection take-offs is subject to the air traffic situation.

2.2 RWY 10L/28R

Intersection take-offs from N2 and N6 are considered the primary line up points for RWY28R and RWY10L respectively in normal operations and also in Low Visibility Operations. Taxiways N1 and N7 are NOT available for departure in LVOs. Pilots should advise as early as possible if unable to accept departure from these points. Further information refer to 3.3 HIRO Departures.

Intersection take-offs are not available during Low Visibility Operations.

3 High Intensity Runway Operations (HIRO)

High Intensity Runway Operations (HIRO) are valid from 0600 to 2400HR (local time) unless otherwise advised by ATC (e.g. via ATIS). The HIRO system optimises separation of aircraft on final approach in order to minimise runway occupancy time for both arriving and departing aircraft, thereby maximising runway utilisation and minimising "go-around".

3.1 Arrivals

Pilots are reminded that by leaving the runway at the fastest speed commensurate with safety and standard operating procedures, ATC will be able to guide aircraft on final approach using minimum radar separation or separation minimum according to wake vortex category. Extended runway occupancy may result in a missed approach.

In order to reduce runway occupancy times, pilots shall apply the following procedure:

Pilots should pre-plan their landing and roll out to target the appropriate exit taxiway, weather permitting, that provides for a safe and expeditious exit from the runway to reduce delays and maximise utilisation at all times

Pilots are to ensure runway fully vacated before stopping i.e. aircraft are not to stop on any runway exit awaiting instructions from ATC but should continue on to the next available taxiway (unless instructed to do so by ATC)

Tactical requests to extend the landing roll to reduce ground taxi/exit nearer to parking stands are not to be made to ATC

Aircraft unable to vacate the runway via the preferred taxiways should notify ATC when the aircraft is between 8 and 4 NM from touchdown, or at the earliest opportunity after which it has been determined that it is unable to comply.

The preferred exit taxiways for RWY10R and RWY28L are:

RWY	Aircraft Type	Preferred exit TWY	Distance from threshold to exit point (m)
10R	Wingspan less than 36m and B757	TWY S2	1690
	All other aircraft	TWY S1	2240
28L	Wingspan less than 24m and all turboprops	TWY S4*	1240
	All other aircraft	RET S5	1597
10L	Up to Code E aircraft type	TWY N4	1469
	All other aircraft	RET N3	1700
28R	All aircraft	RET N5	1600

* TWY S4 and N4 are not available as a runway exit during Low Visibility Operations

Pilots may plan their arrival using the threshold-to-exit-point distances set out in the table above. The distances are measured from the landing threshold to the point of the intersection of the runway centreline and the extended exit taxiway centreline pavement marking.

If the pilot of a landing aircraft cannot contact ATC due to RTF congestion, the pilot should fully vacate the runway and taxi into the next available taxiway. The pilot should then hold position until contact with ATC can be established.

3.2 Departures

ATC will consider every ACFT at the runway holding point as able to commence line-up and take-off roll immediately after clearance is issued, unless otherwise instructed. Pilots not ready when reaching the holding point (no ACFT in front on the same taxiway) shall advise ATC on Tower frequency as early as possible before entering the RWY.

When cleared for take-off, ATC will expect and has planned on seeing movement within 10 seconds (of take-off clearance being issued). Wake vortex separation is applied by ATC in accordance with the published requirements. If more separation than the prescribed minima is requested, pilots shall notify ATC before entering the RWY.

Where possible, cockpit checks and cabin readiness should be completed before line-up and any checks needing completion on the runway should be kept to the minimum required. Pilots should not back-track when entering the runway unless specifically requested at the runway holding position.

Note: Pilots shall not cross the runway-holding position until the illuminated red stop bar has been extinguished. ATC do not issue conditional line-up clearances where stop bars are operational at line-up points.

3.3 Preferred Use of Intersection Take-Offs

Based on aircraft type and performance characteristics, ATC may issue instructions for aircraft to depart from runway intersections from which adequate take-off run is available. Intersection take-offs are subject at all times to pilots' discretion and aircraft operational requirements. Pilots unable to accept departure from an intersection point may request an alternate take-off position from ATC. Pilots requiring departure from the beginning of the runway should request it at the time of push-back/start-up, and such requests will be considered by ATC subject to delay.

The preferred use of intersection take-offs are set out in the table below.

Aircraft Type	RWY	Preferred TWY Intersection
All aircraft	10L	TWY N6
	28R	TWY N2
RJ85 type and all turboprops	10R	TWY S6*
	28L	TWY S1*

Aircraft Type	RWY	Preferred TWY Intersection
* Intersection take-offs RWY 10R/28L are not available during Low Visibility Operations		

3.4 Additional information on runway usage is available [EIDW AD 2.21 NOISE ABATEMENT PROCEDURES](#) Section 5

4. Mandatory ground handling of aircraft at Dublin Airport
All aircraft must avail of ground handling. All aircraft of less than 2 tonnes maximum certified AUW must avail of minimum handling i.e. ramp transport to/from departures and the aircraft

5. Aircraft Engine Test Runs

Permission for all test runs must be obtained from the Aerodrome Operator.

LOCATION	NOTES
ENGINE TEST SITE 1 (Adjacent to TWY W1)	Up to full power engine runs. Available for aircraft up to Code C plus Boeing 757 (max wingspan 42M). Operational hours 0730 - 2000HR Local Time Monday to Friday 0900 - 2000 HR Local Time Saturday, Sunday and Bank Holidays Lighting and movable jet blast fence available. Movable jet blast fence allows for engine runs to be carried out on the following heading range: 230° - 280°. Positioning outside the headings is not permitted for any aircraft type, other than ATR.
ENGINE TEST SITE 2 (Forecourt Cityjet Hangar)	Check starts, idle engine runs, running one engine at idle, for maintenance and post engine wash run are permissible. Ground engine runs WILL NOT exceed thirty minutes in duration and not above idle power. If a new engine is to be run for the first time, the Airside Operations and Safety Officers (AOSO) must be informed of this fact at the time of the request.
ENGINE TEST SITE 3	Withdrawn from service.
ENGINE TEST SITE 4 (Apron Taxiway 6)	Available for all aircraft. Check starts, idle engine runs, running two engines at idle, for maintenance and post engine wash run are permissible. <i>Caution: No lighting or acoustic/safety barriers available.</i>
ENGINE TEST SITE 5 (Adjacent to Hangar 1)	Idle engine runs at Engine Test Site 5 are permitted for operators, running two engines, at idle, for maintenance and post engine wash runs. Permission required from the Resource Allocation Unit. <i>Caution: No acoustic/safety barriers available.</i>
Aircraft Stands	Aircraft engine test runs at idle speed not exceeding five minutes duration are permitted on all stands. Permission required from the Resource Allocation Unit. If greater than 5mins up to 30mins permission is required from the AOSO. Only one engine is permitted to be running at any stage during the engine run. <i>Caution: No acoustic/safety barriers available.</i>
Location to be agreed	For aircraft larger than code C/B757 contact Resource Allocation Unit for agreed location and available times. Code C aircraft: 0800 - 2000HR local Monday to Friday, 0900 - 2000HR, Saturday, Sunday and Bank Holidays. Code D aircraft: 0900 - 2000HR local, Monday to Sunday, but not outside daylight hours. <i>Caution: No lighting or acoustic/safety barriers available.</i>

6. Apron Parking and Marshalling of Aircraft

6.1 Aircraft are prohibited from entering any stand without the guidance of a marshaller, or the Advanced Visual Docking Guidance System (AVDGS) where provided. For availability of AVDGS, see [EIDW AD 2.9.1](#)

6.2 In order to prevent dazzling the marshaller or the push-back crew, pilots are requested to switch off the aircraft landing lights when reaching or leaving the parking position and, when equipped with both a conventional red anti-

collision light and a sequenced white strobe light system, to switch off the latter system as well.

7. Building Served Stands
Aircraft using building served stands are required to vacate stand immediately at scheduled departure time.
8. Rapid Exit Taxiway – S5, N3, N5
Rapid Exit Taxiways (RETs) at Dublin Airport are designed for a maximum exit speed of 50 KT. However it is expected that aircraft using the RET will normally exit the runway at circa 35KT.
Rapid Exit Taxiway Indicator Lights (RETILs) are provided.
9. Aerodrome Hotspot Facilities in the vicinity of thresholds Runways 28L and 34
 - 9.1 The following details and associated diagram are provided for ease of familiarity with the aerodrome hotspot on this complex area of the aerodrome. The attention of all aircrews is drawn to the layout of taxiways, the location of holding positions, and the proximity of the thresholds of Runway 28L and Runway 34. Close attention must be paid to visual aids (markings, lighting, signage).
 - 9.2 All taxiways are provided with location signs (yellow inscription on black background) and direction signs (black on yellow). Centreline markings and edge markings are also provided.
 - 9.3 Mandatory signs, (white inscription on red background), are provided to identify locations which aircraft shall not pass unless authorised by ATC. These signs include runway designation signs, runway-holding position signs etc.
 - 9.4 For normal visibility conditions, CAT I runway-holding positions are established on all taxiways which intersect with runways. The CAT I runway-holding position on Taxiway E1 is a combined position for Runway 10R/28L and Runway 16/34. CAT I runway-holding positions are also established on Runway 16/34, for aircraft taxiing along Runway 16/34 towards Runway 10R/28L, and on Runway 10R/28L for aircraft taxiing along Runway 10R/28L towards Runway 16/34. These holding positions are denoted by:
 - i. Yellow painted holding-position markings;
 - ii. Red mandatory markings, Indicating the Designation of the runway ahead;
 - iii. Red mandatory signs, including the designation of the runway ahead;
 - iv. Red controllable stop bar lights (where shown on Aerodrome Chart);
 - v. Yellow flashing runway guard lights (ICAO Configuration A);
 - vi. Location sign indicating the taxiway designation in yellow on a black background;For low visibility conditions, a CAT II/III runway-holding position is established on Taxiway E1. This holding position is denoted by:
 - i. Yellow painted markings;
 - ii. Red mandatory signs with the inscription 28L CAT II/III;
 - iii. Red controllable stopbar lights;
 - iv. Yellow flashing runway guard lights (ICAO Configuration A);
 - v. Location sign indicating E1 in yellow on a black background;
 - 9.5 Runway-holding positions cannot be passed without permission from ATC.
 - 9.6 Aircrews are advised that should they become unsure of their position while taxiing, they should contact ATC immediately and request assistance.
 - 9.7 Due to the close proximity of the two runways Runway 28L and Runway 34, aircrews taking off from Runway 28L or Runway 34 are advised to ensure that they are lined up on the correct runway before commencing take-off run.

10 Stop bars

Pilots shall not cross illuminated stop bars. A pilot receiving instructions which imply that an illuminated stop bar should be crossed shall wait until the stop bar is extinguished. If the stop bar remains illuminated, the pilot shall request confirmation from ATC that the stop bar is to be crossed. Instructions to cross illuminated stop bars will only be given in exceptional circumstances.

In the event of failure of the stop bar control mechanism, only TWY E1 (Runways 28L and 34), TWY S7 (Runway 10R) and TWY N4 (Runway 16) shall be used as line-up points.

In the event of failure of the stop bar control mechanism, the following line up points shall be used:

Runway	Line up Points
28L	E1 and RWY 16
10R	S7
16	N4
34	E1
28R	N2 and N1
10L	N6 and N7

The following phraseology shall be used by ATC to instruct pilots or vehicle drivers to cross an illuminated stop bar:
ATC: “[Callsign] Due to a failure of the control system, the stop bar will remain illuminated. Taxi/proceed across the stop bar on taxiway [designator] / runway [designator] Echo 1/Sierra 7/November 4 and line up RWY [designator] 34,28L,10R,16”

Reply: “[Call-sign] Lining up Runway [10R/28L/34/16 Designator] crossing stop bar” shall not cross illuminated stop bars. A pilot receiving instructions which imply that an illuminated stop bar should be crossed shall wait until the stop bar is extinguished. If the stop bar remains illuminated, the pilot shall request confirmation from ATC that the stop bar is to be crossed. Instructions to cross illuminated stop bars will only be given in exceptional circumstances. In the event of failure of the stop bar control mechanism, only TWY E1 (Runways 28L and 34), TWY S7 (Runway 10R) and TWY N4 (Runway 16) shall be used as line-up points.

11 **Airport Collaborative Decision Making (A-CDM)**11.1 **Flight Plan Validation**

Three hours prior to the Estimated Off-Block Time (EOBT) of a flight, checks will be performed to verify the consistency between the ATC Flight Plan, Airport Slot and Airport Flight Data.

If the Scheduled Off-Block Time (SOBT) deviates from the EOBT, the relevant contact person will be informed and advised to adjust the times accordingly. Aircraft Operator (AO) or their Handling Agent (HA) is responsible for timely update of aircraft registration in the A-CDM portal (AOS).

11.2 **Target Off-Block Time (TOBT)**

This is the time that an Aircraft Operator or their Handling Agent estimates that an aircraft will be ready, all doors closed, boarding bridge removed, push back vehicle available, de-icing completed, and ready to start up/push back immediately upon reception of clearance from the Tower.

TOBT= Prediction of “Aircraft Ready”

11.3 **Automated TOBT**

120 minutes prior to the Estimated Off-Block Time (EOBT), the A-CDM portal (AOS) system will automatically generate a default Target Off-Block Time (TOBT).

11.4 **Person Responsible for TOBT**

The Aircraft Operator or their agent is responsible for entry, update and if necessary deletion of TOBT's. It is the responsibility of the AO/HA to communicate and ensure the pilot of a flight has the correct TOBT prior to calling for

clearance. TSAT will also be included in DCL messages. If it becomes obvious that the TOBT cannot be respected, it shall be corrected or re-entered by the person responsible for the TOBT. Since the TOBT is used for various ground processes, it shall be updated by the person responsible for the TOBT when deviations of more than 5minutes occur.

For deviations of 15minutes or more from the EOBT, it will still be mandatory to send a delay message (DLA) to the Network Manager.

11.5 **TOBT Update/Deletion**

Until the TSAT has been issued (TOBT minus 40 minutes) the TOBT can be updated as often as desired. After the TSAT has been issued, the TOBT can be updated up to three times. If a sixth TOBT update is required the flights TSAT will be removed and the flight will get re-sequenced. It is important to recognise that once sequenced, changes to TOBT are likely to impact the aircraft's position in the Pre-Departure Sequence (PDS). TOBTs require updating if they differ by 5mins from the previous declared TOBT.

If a flight is to be taken out of the TOBT/TSAT calculation, the TOBT shall be deleted. The TOBT shall be re-entered by the person responsible for the TOBT.

11.6 **TOBT Reporting Routines**

The TOBT is viewed and or adjusted in one of the following ways:

- A-CDM Portal (AOS)
- AOS Mobile Application
- Internal system of the Airline/Handling Agent (via interface)
- By telephone via the Dublin Airport Control Centre (ACC), Phone + 353 (0) 1 814 4352
- Advanced Visual Docking Guidance System (A-VDGS) (specific stands)

11.7 **Target Start-up Approval Time (TSAT)**

The TSAT is the target time for start-up approval according to the Dublin A-CDM Operational procedures, taking into account TOBT, Calculated Take Off Time (CTOT), and/or the traffic situation. The earliest time for the TSAT calculation (by the PDS) is 40 minutes prior to TOBT.

TOBT is the time at which an Aircraft Operator, or his duly accredited representative expect the flight will be ready to commence movement; whereas the TSAT is the time at which Ground will grant the start-up.

It is the responsibility of the AO/HA to communicate the most up to date TSAT to the pilot, prior to doors closing.

The "Pre-Departure Sequence" is a result of the calculated TSATs.

11.8 **TSAT Reporting Routines**

The TSAT is transmitted in one of the following ways, via:

- A-CDM Portal (AOS)
- AOS Mobile application
- Internal system of the airline/Handling agent (via interface)
- Datalink Clearance (DCL). If a TSAT changes post clearance, ATC will communicate the revised TSAT verbally to the pilot. A revised DCL message will not be issued, post ATC clearance.
- Advanced Visual Docking Guidance System (A-VDGS) (specific stands)

11.9 **Start-up and Push-back**

The sequence of push and start is based on the TSAT sequence. The following rules apply:

- The Pilot shall report ready to push and start at TOBT (+/-) 5 minutes. (ATC clearance (including DCL) shall be requested any time prior to TOBT from delivery)
- The aircraft has to be ready for start-up at TOBT
- Ground will issue push and start approval at TSAT (+/-) 5 minutes
- If pilots have received their ATC clearance and called at TOBT and Ground has not called to give push and start approval by TSAT + 5minutes, pilots are requested to call Ground requesting push and start approval.

In case of delays (>5 minutes) after ATC clearance has been received and/or a call ready at TOBT has been made, pilot shall inform clearance of the delay and a new TOBT must be sent by the AO/HA.

11.10 **Datalink Clearances (DCL)**

For datalink departure clearance (DCL), the published procedures and the time parameters published in the AIP will remain valid. The TSAT will also be transmitted in DCL messages.

11.11 **De-icing**

De-icing must be completed before an aircraft can report ready for push and start. De-icing times shall be taken into account, to calculate the TOBT.

11.12 **Coordination with the Network Manager (NMOC)**

A permanent and fully automatic data exchange with the Network Operations will be established. This data transfer will enable highly accurate early predictions of landing and departure times. Furthermore, this will allow for more accurate and efficient calculation of the CTOT (when applicable) due to the use of local target take-off times. The following messages are used:

- Flight Update Message (FUM)
- Early Departure Planning Information Message (E-DPI)
- Target Departure Planning Information Message (T-DPI)
- ATC Departure Planning Information Message (A-DPI)

The basic Network Operations procedures continue to apply. The Network operations will generally take those local Target Take -Off Times (TTOT) into consideration, when updating the flights' profiles in its system. In some cases Clearance Delivery position will offer to coordinate a new CTOT (if applicable) in agreement with the pilot.

11.13 **Remote Holding**

In the event of a contact stand not being available, Dublin Airport will request a remote hold stand position from ATC. The Pre-departure Sequencer (PDS) will recalculate the variable taxi time from this new remote hold location.

11.14 **Contact and Information**

For the TOBT dialogue and the TSAT submission, all Aircraft Operators/Handling Agents have to appoint a person responsible for TOBT and give the details to the airport company.

VFR flights are not part of the A-CDM process and therefore do not require TOBTs to be entered.

11.15 **Contact Details**

For additional information and support documents on Dublin A-CDM, see link:

<https://www.dublinairport.com/regulation-and-planning/regulatory/airport-cdm>

Contact persons for the A-CDM procedure at Dublin Airport, are as follows:

Dublin Airport

Resource Allocation Unit
Phone: + 353 (0) 1 944 5228
Email: POD@dublinairport.com

Irish Aviation Authority

ATC Duty Station Manager
Phone: + 353 (0) 1 8445962
Email: atcdub@iaa.ie

EIDW AD 2.21 NOISE ABATEMENT PROCEDURES

1. Aircraft operators shall ensure at all times that aircraft are operated in a manner calculated to cause the least disturbance practicable in areas surrounding the airport.
2. Standard Instrument Departures
Strict compliance with SID is mandatory.
3. Other Instrument Departures
 - 3.1 Cat A, B Aircraft
 - 3.1.1 Cat A, B Aircraft (Non Jet)
After take-off, pilots should ensure that they are at a minimum altitude of 750ft QNH before initiating any turn. No take-off turn shall be commenced before the departure end of the runway.
 - 3.1.2 Cat A, B Aircraft (Jet)
Departures must track the runway extended centreline after take-off until passing 750QNH before commencing turn. No take-off turn shall be commenced before the departure end of the runway.
 - 3.2 Cat C, D Aircraft
 - 3.2.1 Departures from all runways except Runway 10R, must track the runway extended centreline after take-off until passing 750feet and then proceed in accordance with the relevant Instrument Flight Procedure published departure track and adhere to published altitude/level restrictions unless otherwise cleared by ATC.
 - 3.2.2 Departures from Runway 10R must track the runway extended centreline to 5NM before commencing turn to the north, or to 6NM before commencing turn to the south.
 - 3.2.3 Take-off climb shall comply with the procedure detailed below, which is based on noise abatement departure climb guidance contained in PANS OPS Doc 8168 Vol 1 - Appendix to Chapter 3 - NADP2.
 - 3.2.4 Take-off thrust, speed $V^2 + 20$ to 40 km/h ($V^2 + 10$ to 20kt).
 - 3.2.4.1 At 240m (800ft) and while maintaining a positive rate of climb, body angle is reduced and flaps/slats are retracted on schedule as the aircraft is accelerated towards V_{zf} .
 - 3.2.4.2 Power/thrust is reduced during the flap/slat retraction sequence at a point that ensures satisfactory acceleration performance.
 - 3.2.4.3 (3000ft) Transition smoothly to en-route climb speed.
 - 3.2.4.4 Cat C and D aircraft operating from Runway 28L directly to Weston or Baldonnel aerodromes are exempt from Sections 3.2.1, 3.2.2 and 3.2.3. These aircraft must not leave the environmental corridor below 1,500ft QNH.
4. Jet aircraft (Cat C/D) on visual approach to all runways must join final approach no closer than 6NM from touchdown. Aircraft must follow a descent path which will not result in being at any time lower than the approach path which would otherwise be followed using the ILS glide-path.

5. Runway 10L/R or 28L/R are the required Runways between 0600 and 2300HR Local Time when the crosswind component is 20KT or less. Runway 28L/R will be the preferential Runways when the tailwind component is 10KT or less and braking action is assessed as good. Aircraft will be required to use these Runways except when operational reasons dictate otherwise.
If the crosswind component on Runway 10L/R or Runway 28L/R is greater than 20KT Runway 16 or Runway 34 may become the active Runway. If the forecast crosswind component on Runway 10L/R or 28L/R is greater than 20KT Runway 16 or 34 may become the active Runway.
The use of Runway 16/34 will be kept to an absolute minimum subject to operational conditions.
6. Runways will be prioritised for noise abatement purposes between 2300 and 0600HR Local Time, subject to the same wind calculation method and values as used between 0600 and 2300HR Local time (see Section 5).
7. Reverse thrust should not be used during landing operations on any runway between 2300-0600HR Local Time, except where operational or safety reasons dictate otherwise.
8. Cat C and D aircraft using Runways 28L, 28R, 10L, 16 and 34 shall operate within environmental corridors which are based on runway take-off flight path areas. The corridors have a width of 180 M at the departure end of the clearway, diverging at 12.5% on each side to a maximum width of 1800 M, and extending in length to 5 NM from the point of origin. The corridors extend vertically from surface to 3000 ft AMSL.

Cat C and D aircraft using Runway 10R shall operate within an environmental corridor which is based on the runway take-off flight path area. The corridor has a width of 180 M at the departure end of the clearway, diverging at 12.5% on each side to a maximum width of 1800 M, and extending in length from the point of origin to 5 NM for the northern boundary of the corridor and 6 NM for the southern boundary of the corridor. There is no upper vertical limit to this corridor

The corridors apply for departures from each runway and also for approaches to the reciprocal runway, except for circling approaches.

EIDW AD 2.22 FLIGHT PROCEDURES

1. Holding Areas

Protected airspace is provided for Holding Areas in accordance with the criteria contained in PANS-OPS ICAO Doc 8168, Volume II for basic holding areas.

For RNAV procedures, holding basic areas are based on aircraft having RNAV holding system functionality.
2. SID and STAR and IAP's
- 2.1 **RNAV Equipped Aircraft**

SIDs and STARs and initial and Missed Approach segments of IAPs for all runways have been developed in accordance with ICAO Doc 8168 (PANS OPS).

The RNAV Specification is RNAV 1.

The supporting navigation infrastructure provided is DME/DME or GNSS.

Operators which have obtained operational and airworthiness approval, from their regulatory authority, may operate the RNAV SID and STAR procedures in accordance with the conditions of approval.

If the RNAV equipment fails, or navigation accuracy of +/-1 NM can not be maintained, inform ATC as soon as possible. Radar vectoring will be provided.
- 2.2 **RTF Phraseology**

Phraseology used will be as provided in the European Regional Supplementary Procedures (ICAO Doc 7030) and outlined in Eurocontrol Guidance material for RNAV SIDs and STARs.

Examples of phraseology for ATC are:
 - {CALLSIGN} CLEARED {STAR designator} ARRIVAL, RUNWAY {designator}*Note:* On such a clearance flight crew shall continue on route until reaching start point of the STAR.
 - {CALLSIGN} ADVISE IF ABLE {designator} DEPARTURE [or ARRIVAL].

If ATC are unable to issue a requested SID or STAR:

- {CALLSIGN} UNABLE TO ISSUE (designator) DEPARTURE [or ARRIVAL] DUE [Reason]

Examples of pilot phraseology in the event of being unable to accept SID or STAR:

- UNABLE (designator) DEPARTURE [or ARRIVAL] DUE TO RNAV TYPE
- UNABLE RNAV DUE EQUIPMENT

2.3 Non RNAV Equipped aircraft

Non RNAV equipped aircraft will be assigned a clearance based on conventional navigation aids and/or vectoring.

2.4 Expected Approach Distance RWY 10L/R and RWY 28L/R

The expected approach distances are listed for all runways in ENR 1.10. The Lateral Holding/Point Merge STAR procedures (Chart AD 2.24-23.1 and AD 2.24-22.1) must be available in the aircraft navigation database.

3. Speed Control

Speed Restrictions

General	STAR	Holds	Initial Approach Segment (BTN HLDG Fix and IF)	Intermediate Approach Segment (BTN IF and FAP)	Final Approach Segment	Remarks
Below FL100, Max IAS 250KT or less.	As specified waypoints.	As specified on chart	IAS 210KT	IAS 180KT	BTN FAP and 4NM from THR IAS 160KT	1. ATC may request specific speeds for accurate spacing. Comply with speed adjustments as promptly as feasible within operational constraints. 2. If unable to comply with the above, advise ATC as soon as possible.
					4NM to THR IAS as performance requires.	
<p>Warning</p> <p>Operators are advised of the probability of encountering a GPWS Terrain alert, for aircraft which are exceeding the standard speed restrictions, while at or below 5,000FT and which are in the vicinity of the high terrain to the south of Dublin Airport.</p>						

4. Recommended Flight Planning for Peak Arrival Periods

For further information refer to [ENR 1.10.7.1](#)

5. Arrival Procedures

5.1 Clearance to enter the CTA and CTR

Aircraft flying the ATS Route system will be cleared into the CTA/CTR without having to request a specific entry clearance.

Arriving Aircraft will normally be cleared on a STAR appropriate to the route by ATC. On occasions ATC may radar vector aircraft for arrival (Due traffic or technical reasons).

5.2 Initial Approach Procedures

5.2.1 With radar control

In order to expedite the flow of traffic, aircraft may receive radar vectors on to final approach from the STAR.

For RWYs 16 & 34 pilots should plan their flight profile in such a manner as to be able to achieve 6000ft QNH at the appropriate hold.

For RWY 28L/R & 10L/R pilots should plan their flight profile on the sequencing leg to achieve level constraints.
ACTUAL DESCENT CLEARANCE WILL BE AS DIRECTED BY ATC.

5.2.2 Without radar control

When arriving traffic cannot be sequenced by radar, aircraft will be cleared to join the Instrument Approach Procedure appropriate to the landing from the hold.

5.3 Communications failure procedures for arriving aircraft

5.3.1 RWY16 & 34

Aircraft experiencing communications failure in the Dublin CTA/CTR shall set transponder code A7600 and comply with standard ICAO procedures.

5.3.2 RWY 28L/R and 10L/R

RWY 28L/R

5.3.2.1 Aircraft prior to Sequence Leg Entry

- a. Squawk 7600.
- b. Proceed via the STAR to enter the appropriate Sequence Leg Entry Hold (i.e. KERAV or SORIN) at the last cleared Flight Level.
- c. Commence descent in the Hold to the Sequence Leg entry Flight Level (FL080 or FL070 as appropriate) specified on the chart at, or as close as possible to the expected approach time (EAT). If no EAT has been received and acknowledged descend at, or as close as possible to the estimated time of arrival resulting from the current flight plan.
- d. Proceed onto the appropriate Sequence Leg, complete the full STAR as filed or last cleared by Dublin ATC, to LAPMO. After turning off the Sequence Leg descend to 3000ft QNH and complete the approach for landing on RWY28L.
- e. **Aircraft flying the ABLIN(L) STAR losing R/T contact should squawk A7600 and should continue to fly the STAR (including the sequence leg from SIVNA onwards) and complete the approach.**
- f. **ABLIN(X) STAR: in the event of radio communication failure aircraft flying the ABLIN2X STAR should squawk A7600, continue on the procedure maintaining required altitude and speed constraints and complete the approach.**

5.3.2.2 Aircraft on Sequence Leg

- a. Squawk 7600.
- b. Complete the full STAR to LAPMO or ABIVU, depending on the runway in use.
- c. After turning off the Sequence Leg descend to 3000ft QNH and complete the approach for landing on RWY28L/R, depending on the runway in use.

5.3.2.3 Aircraft turned off the Sequence Leg

- a. Squawk 7600
- b. Descend to 3000ft QNH
- c. In the most expeditious manner route to LAPMO/ABIVU to complete the instrument approach procedure for RWY28L/R, depending on the runway in use.

RWY 10L/R

5.3.2.4 Aircraft prior to sequence Leg Hold (ADNAL or BABON as appropriate) Squawk 7600

1. Proceed via the STAR to enter the appropriate Sequence Leg Hold (ie ADNAL or BABON) at the last cleared

Flight Level

2. Commence descent in the Hold to the Sequence Leg Flight
3. Level (FL080 or FL070 as appropriate) specified on the chart at, or as close as possible to the expected approach time (EAT). If not EAT has been received and acknowledge descend at, or as close as possible to the estimated time of arrival resulting from the current flight plan.
4. Continue on the appropriate STAR Sequence Leg, complete the full STAR as filed or last cleared by Dublin ATC, to IFBAP or OSLEX as appropriate. After turning off the Sequence Leg descend to comply with the constraint altitude at IFBAP or OSLEX and complete the approach for landing on RWY10L/R, depending on the runway in use.

5.3.2.5 Aircraft on Sequence Leg.

- a. Squawk 7600
- b. Complete the full STAR and approach for RWY 10L/R, depending on the runway in use.
- c. After turning off the Sequencing leg descend to comply with the constraint altitude at IFBAP or OSLEX and complete the approach on RWY 10L/R, depending on the runway in use.

5.3.2.6 Aircraft turned off the Sequence Leg

- a. Squawk 7600
- b. Descend to comply with the constraint altitude at IFBAP or OSLEX and complete the approach for landing on RWY 10L/R, depending on the runway in use.

5.3.3 Non RNAV capable Cat C/D aircraft.

Non RNAV capable Cat C/D aircraft should route, in the most expeditious manner, to the appropriate hold for the runway in use and hold using best navigation means available. From the hold proceed to, and complete in the most expeditious manner, the IAP for the runway in use.

6. Departure Procedures

6.1 Departure Clearance Service using Datalink (DCL)

6.1.1 Introduction

6.1.1.1 The DCL service uses the Aircraft Communications Addressing and Reporting System (ACARS). DCL messages are described in EUROCAE ED-85A Appendix A and ARINC 623-2.

6.1.1.2 DCL departure clearances are provided solely to those flights departing Dublin Airport.

6.1.1.3 Clearance Delivery Procedures via RT (voice) will be utilised in the event of datalink transaction failure.

6.1.1.4 Oceanic traffic can receive domestic clearances via ACARS.

6.1.2 Datalink procedure

6.1.2.1 The pilot will send a departure clearance request utilising the on-board datalink interface. Minimum 15 minutes before start-up. **Any slot times will be taken into account by the pilot in the request if appropriate.**

6.1.2.2 If the clearance is not received by the pilot within 3 minutes of the request the pilot will contact ATC through the normal RT communication channels and obtain a clearance on RT.

6.1.2.3 Where the pilot receives a Datalink reply and cannot accept the clearance he will contact ATC through the normal RT channels to obtain, an alternate clearance on RT.

6.1.2.4 If the pilot is satisfied with the Datalink clearance an acknowledgement message will be sent to the ground system.

6.1.2.4.1 If the ground system does not receive the acknowledgement message within 3 minutes after the clearance has been

transmitted, or if an invalid message is received, ATC will contact the pilot through the normal VHF channels and issue the clearance via RT (voice).

6.1.2.5 All departure clearances issued through the normal VHF RT voice channels will cancel the DCL service.

6.2 RWY 28L, 28R, 10L, 10R, 16 and 34 - Standard Instrument Departures (SID)

Aircraft on IFR flights departing from RWY 28L, 28R, 10L, 10R, 16 and 34 will proceed in accordance with Standard Instrument Departures (SID) WHICH ALSO INCLUDE MANDATORY NOISE ABATEMENT ELEMENTS for jet aircraft.

Category C and D departures shall remain on DUBLIN TOWER frequency until passing 2,000ft, then contact DUBLIN ACC Lower North/DUBLIN ACC Lower South as appropriate.

Where ICAO obstacle clearance criteria require minimum climb gradient greater than 3.3% the required values will be included in the SID.

As a cross check to confirm the correct SID has been selected in the FMS, Category C and D departures will be requested by CDS to confirm the first waypoint on the SID e.g. RWY 10R "DW553".

Non-Standard Departure Instructions - Pilots who cannot comply with any of the Standard Instrument Departure procedures must inform ATC in good time so that alternative clearances can be issued. A minimum climb gradient of 4.1 per cent applies to all alternate clearances.

Note: CAT A, B aircraft may be assigned a SID appropriate to CAT C, D aircraft at the discretion of ATC.

Note: CAT E aircraft will be assigned a SID appropriate to CAT C, D aircraft at the discretion of ATC

6.3 Communications failure procedures for departing aircraft

Aircraft experiencing communications failure in the Dublin CTA/CTR shall set transponder code A7600 and comply with standard ICAO procedures,

Supplemented by the following:

- i. For aircraft departing on a SID where no cruising level has been specified in the enroute clearance (and therefore no level specified in the Current Flight Plan) the climb, after the appropriate time interval, shall be to the level contained in the Filed Flight Plan.
- ii. Aircraft routeing on a ROTEV SID expecting transition to BOYNE
Aircraft routeing on a ROTEV SID experiencing communications failure, and expecting transition to BOYNE, should continue to ROTEV, then, in the most expeditious manner, route to BOYNE to join the Current Flight Plan route. Maintain the last assigned level for a period of three minutes, and then climb to the level specified in the Current Flight Plan.

7. Low Visibility Procedures

7.1. Low Visibility Procedures

Low Visibility Procedures apply when the cloud ceiling is below 200 ft (60M) and/or the IRVR is less than 550M or the meteorological visibility is less than 800M.

When Low Visibility Procedures are in force the following standard taxi route system applies:

Table 1: Single Runway Operations Runway 28L

RUNWAY	TO/FROM	ARRIVAL TAXI ROUTE	DEPARTURE TAXI ROUTE	APRON TAXI ROUTES
28L	South and Main Apron (South of Link 4)	S5 or S7 to S, W2, M1	B1 to E1 or Link 2, F1 to E1 or Link 3, F2, F1 to E1	All except Z
28L	Main Apron (Link 4 to Link 6)	S5 or S7 to S, W2, RWY34, N, F-Outer	F3, F2, F1 to E1	All except Z

Table 1: Single Runway Operations Runway 28L

RUNWAY	TO/FROM	ARRIVAL TAXI ROUTE	DEPARTURE TAXI ROUTE	APRON TAXI ROUTES
28L	North Apron	S5 or S7 to S, W2, RWY34, N, K	AT6, DN/DS/C, F-Outer/Inner, F3, F2, F1 to E1	All except Z
28L	West Apron (Northern stands)	S5 or S7 to S, W2, W3	W3, W2, M1, F3, F2, F1 to E1	All except Z
28L	West Apron (Southern stands)	S5 or S7 to S, W2	W2, M1, F3, F2, F1 to E1	All except Z
28L	Main Apron If Holding for a stand	S5 or S7 to S, W1	N/A	All except Z

Table 2: Single Runway Operations Runway 10R

RUNWAY	TO/FROM	ARRIVAL TAXI ROUTE	DEPARTURE TAXI ROUTE	APRON TAXI ROUTES
10R	South and Main Apron (South of Link 4)	E1, B1/F1 or S2, W1, H1	B1, F1, F2, F3, M1, W2, S to S7 or Link 2, F2, F3, M1, W2, S to S7 or Link 3, F3, M1, W2, S to S7	All except Z
10R	To South Apron if Holding for a stand	S1, B2	N/A	B1
10R	Main Apron (Link 4 to Link 6)	E1, F1, F2, F3 or S2, W1, H1	F-Outer/Inner, N, RWY16, W2, S to S7	All except Z
10R	North Apron	E1, F1, F2, F3, F-Outer/Inner or S2, W1, H1, F-Outer/Inner	AT6 or DN/DS/C, K, N, RWY16, W2, S to S7	All except Z
10R	West Apron (Northern stands)	E1, Link 4, M1, W2, W3 or S2, W1, H1, M1, W2, W3	W3, W2, S to S7	All except Z
10R	West Apron (Southern stands)	E1, Link 4, M1, W2 or S2, W1, H1, M1, W2	W2, S to S7	All except Z

Table 3: Single Runway Operations Runway 28R

RUNWAY	TO/FROM	ARRIVAL TAXI ROUTE	DEPARTURE TAXI ROUTE	APRON TAXI ROUTES
28R	South and Main Apron (South of Link 4)	N5 or N7 to M, RWY16-M1	B1, F1, F2, F3, F-Outer-N to N2 or Link 2, F2, F3, F-Outer-N to N2 or Link 3, F3, F-Outer-N to N2	All except Z
28R	Main Apron (Link 4 to Link 6)	N5 or N7 to M, RWY16, M1	F-Inner, F-Outer, N, N2	All except Z
28R	North Apron	N5 or N7 to M, RWY16-M1	AT6, DN/DS/C, F-Outer, N, N2	All except Z

Table 3: Single Runway Operations Runway 28R

RUNWAY	TO/FROM	ARRIVAL TAXI ROUTE	DEPARTURE TAXI ROUTE	APRON TAXI ROUTES
28R	West Apron (Northern stands)	N5 or N7 to M, RWY16, W2, W3	W3, W2, M1, F-Outer, N, N2	All except Z
28R	West Apron (Southern stands)	N5 or N7 to M, RWY16, W2	W2, M1, F-Outer, N, N2	All except Z

Table 4: Single Runway Operations Runway 10L

RUNWAY	TO/FROM	ARRIVAL TAXI ROUTE	DEPARTURE TAXI ROUTE	APRON TAXI ROUTES
10L	South and Main Apron (South of Link 4)	N3 or N1 to N, F-Outer	B1, F1, F2, F3, M1, RWY34, M, N6 or Link 2, F2, F3, M1, RWY34, M, N6 or Link 3, F3, M1, RWY34, M, N6	All except Z
10L	Main Apron (Link 4 to Link 6)	N3 or N1 to N, F-Outer	F-Outer/Inner, M1, RWY34, M, N6	All except Z
10L	North Apron	N3, N, F-Outer or N1, K	AT6, DN/DS/C, F-Outer/Inner, M1, RWY34, M, N6	All except Z
10L	West Apron (Northern stands)	N3 or N1 to N, F-Outer M1, W2, W3	W3, W2, RWY34, M, N6	All except Z
10L	West Apron (Southern stands)	N3 or N1 to N, F-Outer M1, W2	W2, RWY34, M, N6	All except Z

Table 5: Segregated Parallel Runway Operations Runway 28

RUNWAY	TO/FROM	ARRIVAL TAXI ROUTE RWY 28L	DEPARTURE TAXI ROUTE RWY 28R	APRON TAXI ROUTES
28	South and Main Apron (South of Link 4)	S5 or S7 to S, W2, M1	B1, F1, F2, F3, H1, RWY34, N to N2 or Link 2, F2, F3, H1, RWY34, N to N2 or Link 3, F3, H1, RWY34, N to N2	All except Z
28	Main Apron (Link 4 to Link 6)	S5 or S7 to S, W2, M1	F-Outer, N to N2	All except Z
28	North Apron	S5 or S7 to S, W2, M1	AT6, DN/DS/C, F-Outer, N to N2	All except Z
28	West Apron (Northern stands)	S5 or S7 to S, W2, W3	W3, W2, RWY34, N to N2	All except Z
28	West Apron (Southern stands)	S5 or S7 to S, W2	W2, RWY34, N to N2	All except Z
28	Main Apron If Holding for a stand	S5 or S7 to S, W1	N/A	All except Z

Table 6: Segregated Parallel Runway Operations Runway 10

RUNWAY	TO/FROM	ARRIVAL TAXI ROUTE RWY 10L	DEPARTURE TAXI ROUTE RWY 10R	APRON TAXI ROUTES
10	South and Main Apron (South of Link 4)	N3 or N1 to N, RWY16, M1	B1, F1, F2, F3, H1, W1, S to S7 or Link 2, F2, F3, H1, W1, S to S7 or Link 3, F3, H1, W1, S to S7	All except Z
10	Main Apron (Link 4 to Link 6)	N3 or N1, F-Outer	H1, W1, S to S7	All except Z
10	North Apron	N3, N, F-Outer or N1, K, ATC or AT6	AT6 or DN/DS/C, F-Outer, H1, W1, S to S7	All except Z
10	West Apron (Northern stands)	N3 or N1 to N, RWY16, W2, W3	W3, W2, S to S7	All except Z
10	West Apron (Southern stands)	N3 or N1 to N, RWY16, W2	W2, S to S7	All except Z

Note: Code C aircraft shall not be instructed to push back onto Taxiway Foxtrot Outer during Low Visibility Operations.

CAT II/III holding positions will apply as follows:

Departure Runway	CAT II/III Holding Position
RWY 28L	TWY E1
RWY 10R	TWY S7
RWY 28R	TWY N2
RWY 10L	TWY N6

TWY/stopbar/centreline lighting will be in use.

Pilots will be informed by ATIS broadcast or RTF when Low Visibility Procedures have been initiated.

Full details of low visibility operations are available on request from AD Administration (EIDW AD 2.2)

A maximum taxiing speed limit of 15KT applies to all aircraft during the periods when Low Visibility Procedures are in force.

7.2. Low Visibility Take Offs (LVTOs)

During LVP Operations, LVTOs are permitted from Runway 10R/28L and Runway 10L/28R.

It is the at the discretion of the PIC to depart based on their airline operating procedures in LVP conditions.

Take-offs are not available when IRVR values fall below 125m for the runway in use.

All IRVR readings for the departure runway in use must show 125m or greater.

ATC shall inform departing pilots when any IRVR values for the departure runway falls below 125m.

8. Holding Procedures

A standard rate of descent of between 500ft and 1000ft per min in holding patterns will be used unless otherwise instructed by ATC.

9. Operation of Mode S transponders on the Movement Area.

Mode S transponders shall be operated on the Movement Area in accordance with the following provisions:

-
- 9.1 Departing aircraft:
- i. Set aircraft identification and, when received, set assigned Mode A code.
 - ii. Immediately prior to request for push back or taxi, or when advising Clearance Delivery that you are ready for push and start, whichever is earlier, select: "Automatic mode" (e.g.: AUTO) or, if automatic mode is not available, select "on" (e.g. ON or XPDR),
 - iii. Only when approaching the holding position of the departure runway, select "TCAS" (e.g.: TA/RA).
- 9.2 Arriving aircraft:
- i. As soon as practicable after landing de-select "TCAS" (e.g.: deselect TA/RA),
 - ii. Select "automatic mode" (e.g.: AUTO) or, if automatic mode is not available, select "on" (e.g. ON or XPDR),
 - iii. Continue to squawk last assigned Mode A code until fully parked, When fully parked, select "standby" (e.g.: STBY).
10. VFR Procedures, Dublin CTR/CTA and environs
- 10.1 Flight Plan
- Flight Plans are mandatory for flights within Dublin CTR/CTA. Flights planned to transit EIR23, EIR15, EIR16 should include this information in field 15 of the Flight Plan
- Flights planning to enter or leave Dublin CTR should, when practicable, indicate in item 16 of the Flight Plan, an alternate aerodrome situated outside Dublin CTR.
- Where the flight destination is not an aerodrome licensed for public use, the address of the place of intended landing together with the name and telephone number of the property owner should be indicated in field 18 of the Flight Plan.
- 10.2 Special VFR is available within Dublin CTR in accordance with the provisions of EU Reg. No 923/2012 - SERA.5010 Special VFR in control zones.
- 10.3 Flight Information Service is provided H24. When required and as promulgated by ATIS, a discrete frequency (118.500 MHz) is allocated to the provision of FIS for aircraft in class G airspace.
- 10.4 Landing Lights should be shown at all times during flight within Dublin CTR.
- 10.5 ATC Clearances for flights departing from within Dublin CTR.
- Prior to departure
- i. From Dublin Airport by request for start up to Dublin Ground, 122.985MHz or 121.800 MHz if non 8.33kHz equipped.
 - ii. Other than Dublin Airport
 - Contact Dublin ATC by telephone for prior approval
 - Request for start/lift to Dublin Tower from frequency issued in prior approval
 - If no RTF two-way communication can be established, contact Dublin ATC by telephone and request a time for take off / Lift off.
- Take off / Lift without prior two-way communications with Dublin ATC is not permitted.*
- 10.6 **ATC Clearances for flights arriving to destinations within Dublin CTA/CTR**
- Prior to penetration of Dublin CTA/CTR, by submitting a request at least 10 minutes before ETA at the airspace boundary to the relevant ATSU as follows:
- a. Dublin Tower:
 - 118.600 MHz for entry to the Dublin CTR **South** of Dublin Airport
 - 124.680 MHz for entry to the Dublin CTR **North** of Dublin Airport (non 8.33kHz equipped aircraft contact 128.800);

- b. Dublin ACC Lower North, Channel 132.580 for entry to the Dublin CTA, North Sector;
- c. Dublin ACC Lower South, 120.755 for entry to the Dublin CTA, South Sector.
- d. Dublin ACC, for entry to the Dublin CTA, non 8.33 kHz equipped, 124.650 MHz or 126.250 MHz

Note: Dublin ACC Lower North Sector is divided from Dublin South Sector by a boundary line extending along the extended centreline of *RWY 10R/28L*.

10.7 VFR Routes

10.7.1 Flights departing/arriving at Dublin Airport are normally cleared as follows:

- i. North arrivals/departures: via Skerries VFR Route or Naul Town VRP
- ii. West arrivals/departures: via Skerries VFR Route, Dunshaughlin VFR Route or Naul Town VRP
- iii. South arrivals: As instructed by Dublin Tower
- iv. South West arrivals
 - Fixed wing flights to enter the Dublin CTR at The Square, Tallaght, Dunshaughlin VRP, Naul Town VRP or Skerries VRP
 - Helicopter flights to enter Dublin CTR at Redcow Roundabout or The Square, Tallaght
- v. South departures
 - As instructed by Dublin Tower,
or
 - Flights intending to transit EIR15 are cleared to either Palmerston Roundabout Hold or Marley Park Hold to await onwards clearance from Baldonnel Tower.

10.7.2 Flights with departure/destination other than Dublin Airport are normally cleared as follows:

- i. North arrivals/departures
 - As directed by Dublin ATC, or
 - Skerries VFR route or Naul Town VRP.
- ii. West arrivals/departures
 - As instructed by Dublin ATC, or
 - Skerries VFR Route, Dunshaughlin VFR route or Naul Town VRP.
- iii. South west arrivals
 - As instructed by Dublin ATC, or
 - Helicopter VFR flights to enter Dublin CTR at Red Cow Roundabout or The Square, Tallaght. or
 - Fixed-wing VFR flights to enter the Control Zone at Dunshaughlin VRP, Naul Town VRP or Skerries VRP.
- iv. South arrivals as instructed by Dublin ATC.
- v. South departures
 - As instructed by Dublin ATC, or
 - Flights intending to transit EIR15 route to either the Palmerston Roundabout Hold or the Marley Park Hold to await onwards clearance from Baldonnel Tower
- vi. Weston arrivals from the East
 - As instructed by Dublin ATC, or
 - Weston VFR Route

10.8 Visual Holding Patterns

Visual Holding Patterns for category A aircraft are established as follows:

10.8.1 Broad Meadow Bridge (532756.45N 0061125.11W (WGS-84))

Left-hand pattern, based on the M1 motorway bridge, which crosses the Broad Meadow estuary.

Outbound leg is 1 minute, flown at 90KT IAS. Inbound track 187° M. Minimum holding altitude is 1000ft QNH.

The following criteria also apply:

On arriving overhead the Fix, left turn onto the outbound leg should be initiated before the southern shore of the Broad Meadow estuary.

Left turn onto the inbound leg to the Fix should be completed to the east of the M1/N1 road.

The inbound leg to the fix should remain east of the M1/N1 road at all times.

Broad Meadow Bridge Holding Pattern is not available when Runway 10L is in use.

10.8.2 Palmerston Roundabout (532124.26N 0062303.57W (WGS-84))

Left-hand pattern, based on the Palmerston roundabout, which intersects the M50 motorway and the M4/N4 road.

Outbound leg is 1 minute, flown at 90 KT IAS. Inbound track 277° M. Minimum holding altitude is 1700ft QNH.

10.8.3 Marley Park House (531636.19N 0061601.09W (WGS-84))

Right hand pattern, based on Marley Park House, a large manor house inside the grounds of Marley Public Park.

Outbound leg is 1 minute, flown at 90KT IAS. Inbound track 284° M. Minimum holding altitude is 1700ft QNH.

10.8.4 Other Visual Reporting Points (VRPs) (WGS-84)

• VRP Ashbourne Town	533043.95N 0062354.93W
• VRP Baily Lighthouse	532141.65N 0060308.76W
• VRP Ballymun Centre	532339.93N 0061554.74W
• VRP Bray Head	531119.49N 0060503.83W
• VRP Cellbridge Town	532020.42N 0063222.16W
• VRP Donadea Wood	532021.28N 0064449.03W
• VRP Dunboyne Town	532517.22N 0062836.15W
• VRP Dunshaughlin Town	533051.04N 0063228.82W
• VRP Dunsoghly Castle	532537.48N 0061910.36W
• VRP Garristown Village	533400.27N 0062258.13W
• VRP Heuston Station	532046.18N 0061746.66W
• VRP Kilcock Town	532358.13N 0064005.43W
• VRP Killiney Hill	531555.09N 0060714.33W
• VRP Kiltel Village	531410.34N 0063128.07W
• VRP Lambay Island	532929.64N 0060057.65W
• VRP Malahide Town	532704.80N 0060859.56W

10.9 Circuit Operation,

Dublin Airport Circuit training is not permitted at Dublin Airport.

10.10 Radio Communications Failure Procedures – VFR Traffic

10.10.1 Departure Traffic

Proceed in accordance with the ATC clearance last received and acknowledged and land at the most suitable aerodrome located outside Dublin Control Zone. Report arrival to an appropriate ATC unit by the most expeditious means.

10.10.2 Arrival Traffic

If outside the control Zone, proceed with the flight plan route, remaining clear of the Control Zone and comply with flight plan closure procedures, or

If within the Control Zone, EXIT, ensuring that the aircraft remains clear of Dublin Aerodrome and the approach and Take off path of the Runway(s) in use.

EIDW AD 2.23 ADDITIONAL INFORMATION

Refer to ENR 5.6 for bird hazard information.

[Refer to ENR 1.6 2.8 Monitoring Codes](#)

Variation from EASA Certification Specifications - Runway Slope, Runway 16/34

The longitudinal slope in the first and last quarter of a Code 4 runway should not exceed 0.8% (CS ADR-DSN.B.060(c)(1)). In the vicinity of the intersection 10L/28R runway, due to the relative slopes of the two runways, the longitudinal slope provided on RWY 16/34 is up to 1.1%, south of 10L/28R centreline.

In addition, a slope change between two consecutive longitudinal slopes on a Code 4 runway should not exceed 1.5%, and the transition between one slope and another should be a curved surface (CS ADR-DSN.B.065 (b)(1) and (c)(1)). Where RWY 16/34 crosses the centreline of 10L/28R, the slope change is 1.7%, and the transition is immediate, ie without a curved surface.

The Competent Authority has accepted that the safety intent of the Certification Specifications has been met, and that the resulting level of safety can be deemed an Equivalent Level of Safety (ELOS).

Dublin Airport has a minimal capacity to handle code F aircraft for diversions, exceptional and planned movements. Operators should give as much advance notice as possible to ensure sufficient resources are in place.

Dublin Airport is available for B777-800 and B777-900 aircraft operation. If the wing tips fail to fold after the landing at Dublin Airport, pilot is required to inform ATC and request a follow-me service to stand. Pilots must proceed with caution and follow all the instructions from the follow-me provider.

Provision of information to the IATA Standard for AOS:

1. daa requires that airlines and handling agents submit messages for inbound and outbound Dublin Flights, in the standard format described in the IATA Airport Handling Manual.
2. The address that all the SITA messages shall be sent to is DUBRN7X.
3. The following are the three principal message types to be submitted to daa:
 - a. Load messages (AHM 583).
 - b. Statistical load summary (AHM 588).
 - c. Aircraft movement message (AHM 780).
4. Passenger Services Messages (PSMs) and Passenger Transfer Messages (PTMs) are also processed by the AOS. A standard format is required. Examples of the appropriate formats for these and other message types, including those related to passengers are available on the Dublin Airport Operations Library.

EIDW AD 2.24 CHARTS RELATED TO AERODROME

Name	Page
Aerodrome Chart - ICAO	EIDW AD 2.24-1
Aircraft Parking/Docking Chart - ICAO	EIDW AD 2.24-2
Aerodrome Obstacle Chart RWY 10R/28L - ICAO	EIDW AD 2.24-3
Aerodrome Obstacle Chart RWY 10L/28R - ICAO	EIDW AD 2.24-4
Aerodrome Obstacle Chart RWY 16/34 - ICAO	EIDW AD 2.24-5
Precision Approach Terrain Chart RWY 28L - ICAO	EIDW AD 2.24-6
Precision Approach Terrain Chart RWY 28R - ICAO	EIDW AD 2.24-7
Precision Approach Terrain Chart RWY 10L - ICAO	EIDW AD 2.24-8
Precision Approach Terrain Chart RWY 10R - ICAO	EIDW AD 2.24-9
Standard Departure Chart – Instrument RNAV RWY 28L CAT A, B - ICAO	EIDW AD 2.24-10
Standard Departure Chart – Instrument RNAV RWY 28L CAT C, D - ICAO	EIDW AD 2.24-11
Standard Departure Chart – Instrument RNAV RWY 28R CAT A, B - ICAO	EIDW AD 2.24-12
Standard Departure Chart – Instrument RNAV RWY 28R CAT C, D - ICAO	EIDW AD 2.24-13
Standard Departure Chart - Instrument RNAV RWY 10L CAT A,B - ICAO	EIDW AD 2.24-14
Standard Departure Chart - Instrument RNAV RWY 10L CAT C,D - ICAO	EIDW AD 2.24-15
Standard Departure Chart – Instrument RNAV RWY 10R CAT A, B - ICAO	EIDW AD 2.24-16
Standard Departure Chart – Instrument RNAV RWY 10R CAT C, D - ICAO	EIDW AD 2.24-17
Standard Departure Chart – Instrument RNAV RWY 16 CAT A, B - ICAO	EIDW AD 2.24-18
Standard Departure Chart – Instrument RNAV RWY 16 CAT C, D - ICAO	EIDW AD 2.24-19
Standard Departure Chart – Instrument RNAV RWY 34 CAT A, B - ICAO	EIDW AD 2.24-20
Standard Departure Chart – Instrument RNAV RWY 34 CAT C, D - ICAO	EIDW AD 2.24-21
Standard Arrival Chart - Instrument RNAV RWY 28L/R (With Lateral Holding/Point Merge) - ICAO	EIDW AD 2.24-22.1
Standard Arrival Chart - Instrument RNAV RWY 28L/R (Without Lateral Holding/Point Merge) - ICAO	EIDW AD 2.24-22.4
Standard Arrival Chart - Instrument RNAV RWY 10L/R (With Lateral Holding/Point Merge) - ICAO	EIDW AD 2.24-23.1
Standard Arrival Chart - Instrument RNAV RWY 10L/R (Without Lateral Holding/Point Merge) - ICAO	EIDW AD 2.24-23.5
Standard Arrival Chart - Instrument RNAV RWY 16 - ICAO	EIDW AD 2.24-24
Standard Arrival Chart - Instrument RNAV RWY 34 - ICAO	EIDW AD 2.24-25
Instrument Approach Chart RNP RWY 28L - ICAO	EIDW AD 2.24-26
Instrument Approach Chart - ILS CAT I & II or LOC RWY 28L - ICAO	EIDW AD 2.24-27
Instrument Approach Chart VOR RWY 28L - ICAO	EIDW AD 2.24-28
Instrument Approach Chart RNP RWY 28R CAT A,B,C,D - ICAO	EIDW AD 2.24-29
Instrument Approach Chart ILS CAT I and II or LOC RWY 28R CAT A,B,C,D - ICAO	EIDW AD 2.24-30

Name	Page
Instrument Approach Chart RNP RWY 10L - ICAO	EIDW AD 2.24-32
Instrument Approach Chart - ILS CAT I & II or LOC RWY 10L - ICAO	EIDW AD 2.24-33
Instrument Approach Chart RNP RWY 10R - ICAO	EIDW AD 2.24-35
Instrument Approach Chart - ILS CAT I & II or LOC RWY 10R - ICAO	EIDW AD 2.24-36
Instrument Approach Chart VOR RWY 10R - ICAO	EIDW AD 2.24-37
Instrument Approach Chart RNP RWY 16 - ICAO	EIDW AD 2.24-38
Instrument Approach Chart - ILS CAT I or LOC RWY 16 - ICAO	EIDW AD 2.24-39
Instrument Approach Chart VOR RWY 16 - ICAO	EIDW AD 2.24-40
Instrument Approach Chart RNP RWY 34 - ICAO	EIDW AD 2.24-41
Instrument Approach Chart VOR RWY 34 - ICAO	EIDW AD 2.24-42
ATC Surveillance Minimum Altitude Chart - ICAO	EIDW AD 2.24-43
Visual Approach Chart - ICAO	EIDW AD 2.24-44
Instrument Approach Chart VOR T RWY 28L - ICAO	EIDW AD 2.24-45