Services & Support



Agenda







Introduction

- EMBRAER
- SHM applications on maintenance programs


Maintenance Program Development

Status of SHM on the MSG-3 Methodology

- MRB process / MSG-3 Methodology Familiarization
- Scheduled SHM (S-SHM) applications
- S-SHM Ground Support Equipment
- S-SHM as provisions for initial Automated SHM applications



Embraer – Business Areas



Defense Systems



Executive Aviation Market





Introduction - Embraer Defense Systems

Super Tucano











EMB 145 Multi Intel
Airborne Ground Surveillance and
Strategic Intelligence

EMB 145 MP Maritime Patrol

EMB 145 AEW&C
Airborne Early Warning & Control

Introduction - Embraer Executive Aviation

Phenom 100



Phenom 300



Legacy 450/500



Legacy 600/650



Lineage 1000



Introduction - Embraer Commercial Aircraft





ERJ 145 Family (37 to 50 Pax)

E-Jets Family (70 to 122 Pax)



Introduction - Embraer

E-Jets Program Status: 60 Airlines from 40 Countries

Introduction - Embraer



Commercial Aviation Backlog	Firm Orders	Options	Total	Deliveries	Firm Backlog
ERJ 145 Family	890		890	890	
EMBRAER 170	190	32	222	182	8
EMBRAER 175	189	285	474	136	53
EMBRAER 190	519	305	824	349	170
EMBRAER 195	105	36	141	75	30
E-JETS Family	1.003	658	1.661	742	261
TOTAL	1.893	658	2.551	1.632	261



Introduction









WHAT DO WE NEED?

Technical Feasibility

Consistent Business Case

Approved in a Certification Process

Compatible with Continued Airworthiness Requirements


Acceptability by Operators



[1] Derriso, M.M., S.E. Olson, M.P. DeSimio, D.H. Pratt, "Why are there few fielded SHM for Structural. Health Monitoring" 6th International Workshop on Structural Health Monitoring, Stanford CA, Sept 11, p55, 2007 [2] Munns, Thomas E., R.E. Beard, A.M. culp, D.A. Murphy, R.M. Kent, 2000. Analysis of Regulatory Guidance for Health Monitoring. NASA / CR-2000-210643, 6: 56.



Maintenance Program Development



Maintenance Program Development

Section 1


System & Powerplant Mainten. Requirem.

Section 2

Structural Mainten. Requirem.

Section 3

Zonal Mainten. Requirem.



Section 4

Corrosion Prev. & Control Mtx Req.

Appendix 2

Airworth. Limitation Items (ALI)

Other Sections & Appendixes

Status of SHM on the MSG-3 Methodology



ATA SHM Working Group Meeting

> Sep 29th to Oct 1st, 2009 Toronto, Canada

Detail P/C-SHM Methodology Proposal Maintenance Programs Industry Group (MPIG) Meeting

> Nov 3rd to 5th, 2009 Bordeaux, France

Present A-SHM and System MSG-3 Revision Proposals

International MRB Policy Board Meeting

> April 2010 Singapore

Final review and acceptance of A-SHM and System MSG-3 Proposals

MSG-3 2009.1 Approval International MRB Policy Board Meeting

Mar 31st to Apr 03rd, 2009 São José dos Campos, Brazil

Review and final acceptance S-SHM Proposal Maintenance Programs Industry Group (MPIG)

Nov 18th to 20th, 2008 Washington, USA

> Conclusion of S-SHM Methodology Proposal

ATA SHM Working Group meeting

Sep 16th to 18th, 2008 Hamburg, Germany

Detailing of S-SHM proposal and Introduction of P/C-SHM general concepts

ATA SHM Working Group activity kick off meeting

Sep 12th to 13th, 2007 Stanford - USA

Initial MSG-3 Revision Proposal for S-SHM

Maintenance Programs Industry Group (MPIG) Meeting

Jan 8th to 10th, 2008 Memphis – USA

Defined Industry accepted Methodology

International MRB Policy Board Meeting

Apr 22nd to 25th, 2008 Cologne – Germany

Requested further review of MSG-3 structure procedure steps



Status of SHM on the MSG-3 Methodology

MSG-3 Methodology Revision 2009.1 (current)


- Scheduled SHM (S-SHM) "the act to use/run/read out a SHM device at an interval set at a fixed schedule".
- S-SHM as new maintenance task category: alternative for current inspections

International MRB Police Board Issue Paper 105

- Automated SHM (A-SHM) any SHM technology, which does not have a pre-determined interval at which maintenance action much takes place, but instead relies on the system to inform maintenance personnel that action must take place.
- SHM technology types
 - i. Damage Monitoring System It uses sensors to directly monitor the structure for deterioration conditions.
 - ii. Operation Monitoring System It uses sensors, which do not directly check the structure for damage, but instead correlate various measurements (e.g. environment conditions, loads) to make an inference to the probability or likelihood of damage.
- Once a SHM system design is demonstrated to be applicable and effective, it may be used to ensure inherent airworthiness of the item being monitored and traditional inspection task selection may not be appropriate.
- When an A-SHM system is used to monitor structure which has maintenance/inspection requirements, appropriate transfer policies should be used to show that the intent of the damage detection (ED/AD/FD) requirement is being satisfied by the monitoring system. This process takes place after the development of the Structures Requirements described previously in this section.



Status of SHM on the MSG-3 Methodology



Introduction of SHM on Scheduled Maintenance

EMBRAER 190

MAINTENANCE REVIEW BOARD REPORT

MRBR Task Number	Zones	Type Description Cat- egory Access Panels		Applicability	Interval (I: Interval, T: Threshold)	
55-20-001-0407	337 347	S-SHM	ELEVATOR STRUCTURE - INTERNAL Inspection of Elevator Structure, LH/RH, by using Structures Health Monitoring equipment – Internal Side of Elevator	ALL	T: XX MO I: YY MO	
55-20-002-1000	337 347	DET	ELEVATOR HINGE AND ACTUATOR FITTINGS - INTERNAL Detailed Inspection of Elevator Hinge and Actuator Fittings, LH/RH - Internal Side at Rear Spar and Elevator Area.	ALL	T: FC I: FC	
55-20-004-0406	337 347	GVI	ELEVATOR FRONT SPAR FORWARD FACE, LH/RH - INTERNAL General Visual Inspection of Elevator Front Spar Foward Face, LH/RH - Internal	ALL	T: FC I: FC	

Introduction of SHM on Scheduled Maintenance - Example 1


Internal Visual Inspections of rear passenger and service doors cutout structures

What is the issue with current maintenance requirements for this region?

Galley, Lavatory and linings removal

Current Mtx Requirement

To inspect every 5000 FC for fatigue damage (threshold of 20000 FC) & every 12000 FC for corrosion



With SHM (fatigue)

To inspect every 12000 FC for corrosion

BENEFITS

Reduction of 120 Man-hours (MH) every 12000 FC

If SHM also covers corrosion, MH reduction every 12000 FC would be >250 hours

Elimination of maintenance induced problems

Higher aircraft availability (lower downtime means more revenue flights)



Introduction of SHM on Scheduled Maintenance - Example 1

