

General

Applications and Accessories, Cryo Pumps

Cryo pumps											
	COOLVAC 800 BL	COOLVAC 800 CL	COOLVAC 1.500 CL	COOLVAC 2.000 CL	COOLVAC 3.000 CL	COOLVAC 5.000 CL	COOLVAC 10.000 CL	COOLVAC 18.000 CL	COOLVAC 30.000	COOLVAC 60.000	
Application											
UHV systems	■	■	■	■							
Beam tubes in particle accelerators	■										
Transfer chambers / Loadlock	■	■	■	■	■						
General research	■	■	■	■	■	■	■	■	■	■	■
Evaporation coating systems		■	■	■	■	■	■	■	■	■	■
Sputtering systems		■	■	■	■						
Ion implanters		■	■	■	■	■					
Metallization systems	■	■	■	■	■	■	■	■	■	■	■
Space simulation chambers	■	■	■	■	■	■	■	■	■	■	■
Electron beam welding systems	■	■	■	■	■	■	■	■			

Accessories

Page

Compressor unit COOLPAK 2000 (A)/2200 (A)	184/186	■	■	■	■	■					
Compressor unit COOLPAK 6000 H/6200 H/6000 HD	188	[■]	[■]	[■]	[■]	[■]	■	■	■	■	■
Low temperature controller MODEL 9700	202	■									
Temperature sensor	204	■									
Gas manifold GD 2	192	■	■	■	■	■	■				
Gas manifold GD 4	192	■	■	■	■						

[■] = For dual and multiple operation only

Applications and Accessories, Cryogenics

Cold heads						
	COOLPOWER 50	COOLPOWER 140 T	COOLPOWER 7/25	COOLPOWER 5/100	COOLPOWER 5/100 T	COOLPOWER 10 MD
Application						
Cooling of samples and detectors	■	■	■	■	■	■
Cooling of superconductors	(■)	(■)	■	■	■	■
Cooling of cryopanel	■	■	■	■	■	■
Cleaning of gases	■	■	■	■	■	■
Calibration of sensors			■	■	■	■
Optical spectroscopy			■	■	■	■
Infrared spectroscopy			■	■	■	■
Matrix spectroscopy			■	■	■	■
Testing of superconductors			■			
Cooling of superconducting magnets, coils and components HT _C + LT _C	(■)	(■)		■	■	

Accessories

	Page	COOLPOWER 50	COOLPOWER 140 T	COOLPOWER 7/25	COOLPOWER 5/100	COOLPOWER 5/100 T	COOLPOWER 10 MD
Compressor unit COOLPAK 2000 (A)/2200 (A)	184/186	■		■			
Compressor unit COOLPAK 6000 H/6200 H	188		■		■	■	
Compressor unit COOLPAK 6000 HMD/6200 HMD	190						■
Low temperature controller MODEL 9700	202			■	■	■	
Low temperature measurement instrument MODEL 211S	203	■	■	■	■	■	
Temperature sensor	204	■	■	■	■	■	

(■) = Only high T_C superconductors

Conversion of Units

Celsius, Fahrenheit, Kelvin

Kelvin (abbreviated as K) is the unit of temperature.

Temperatures on the Kelvin scale are converted into temperatures on the Celsius scale as follows:

$$n \text{ } ^\circ\text{C} = (n + 273.15) \text{ K.}$$

Since the following equation applies between Celsius scale and Fahrenheit scale

$$n \text{ } ^\circ\text{F} = 5/9 (n - 32) \text{ } ^\circ\text{C}$$

it follows that

$$n \text{ } ^\circ\text{F} = 5/9 (n + 459.67) \text{ K.}$$

The inverse equations are as follows:

$$m \text{ K} = (m - 273.15) \text{ } ^\circ\text{C}$$

$$m \text{ } ^\circ\text{C} = (1.8 m + 32) \text{ } ^\circ\text{F}$$

$$m \text{ K} = (1.8 m - 459.67) \text{ } ^\circ\text{F.}$$

The following applies in particular to absolute zero:

$$0 \text{ K} = -273.15 \text{ } ^\circ\text{C} ; -459.67 \text{ } ^\circ\text{F.}$$

bar, psi

$$1 \text{ bar} = 14.5 \text{ psi}$$

$$1 \text{ MPa} = 10 \text{ bar}$$

Cryo Pumps

Cryo pumps are gas entrapment vacuum pumps for the pressure range from 10^{-3} to $\leq 10^{-11}$ mbar (0.75×10^{-3} to $\leq 0.75 \times 10^{-11}$ Torr). The principle of operation is that gaseous substances are bound to the cold surfaces within the pump by means of cryocondensation, cryosorption or cryotrapping.

In order to be able to produce a high or ultra-high vacuum the cold surfaces (cryopanel) must be cooled to a sufficiently low temperature. Depending on the type of cooling system used a difference is made between refrigerator cryo pumps, bath cryo pumps and evaporator cryo pumps.

Oerlikon Leybold Vacuum manufactures only cryo pumps which are cooled by means of a refrigerator.

Advantages to the User

Advantages offered by the Pumping Principle

- High effective pumping speed for all gases
- Extremely high pumping speed for water vapor

For a given diameter of the high vacuum flange, the cryopump offers the highest pumping speed of all high vacuum pumps.

Advantages offered by Design

In contrast to gas transfer high vacuum pumps (mechanically suspended turbomolecular pumps, for example), cryo pumps do not have any mechanically moving, oil, or grease lubricated parts on the vacuum side.

The following advantages are a direct result of this design characteristic:

- Hydrocarbon-free vacuum in the pressure range from 10^{-3} to $\leq 10^{-11}$ mbar (0.75×10^{-3} to $\leq 0.75 \times 10^{-11}$ Torr).
- Insensitivity to mechanical disturbances from particles coming from the process or external vibrations.

Further Advantages

- Much more compact than comparable pump systems offering a pumping speed of over 1500 l x s^{-1}
- Backing pump is only required during start-up and during regeneration
- Easy process control and pump control via computer
- Favorable price-to-performance ratio and low running costs especially at higher pumping speeds

The cryo pumps are cooled by the well-proven two-stage cold heads from Oerlikon Leybold Vacuum's COOLPOWER line (Gifford/McMahon principle).

The design of a refrigerator cryopump from the COOLVAC range is shown schematically in the figure below.

The first stage of the cold head (9) cools the thermal radiation shield (5) and the baffle (6) of the pump.

Depending on the type of pump and the operating conditions operating temperatures of 45 to 80 K are attained. Correspondingly water vapor condenses at this temperature.


The thermal shield and baffle are made of copper which conducts heat very well so as to optimally utilize the refrigerating capacity which is available.

Moreover, the thermal shield is metalized so that reflective losses will be minimal.

The second stage of the cold head (7) is used to cool the cryopanel (8). Depending on the operating conditions, operating temperatures of 10 to 20 K are attained.

Here the process of cryocondensation of N_2 , O_2 and argon will take place.

The active pumping surfaces are made of copper of high thermal conductivity and they are tightly linked thermally to the second stage of the cold head. H_2 , Ne and He are also adsorbed on to these surfaces which are partly covered with activated charcoal.



COOLVAC refrigerator cryopump

All cryo pumps from the COOLVAC range are equipped with a safety valve (respectively with a bursting disk in the case of the UHV variants) which is set in the factory so that it will open at an overpressure of 150 mbar (113 Torr).

Multiple Operation of Refrigerator Cryo Pumps

The powerful Oerlikon Leybold Vacuum compressor units COOLPAK 6000 HD open up the possibility of operating two cold heads or refrigerator cryo pumps simultaneously.

Regenerating Cryo Pumps

An important aspect in the operation of cryo pumps is that of regeneration. Since a cryopump is a gas entrapment pump, the gasses which have accumulated in the pump during the "pumping" mode must from time to time be removed from the pump. This is done by switching the compressor unit off and by warming up the cryopanel to room temperature or slightly higher so that the released substances can be pumped out by a forevacuum pump.

Cryo Pumps without Electric Regeneration System

The cryopump is warmed up to room temperature by purging the inside of the pump with a dry, pre-warmed inert gas (such as nitrogen). In this case it is not possible to set up defined and controlled temperatures within the cryopump. Thus the simultaneous presence of gases such as hydrogen and oxygen in the pump can not be entirely excluded. The formation of ignitable gas mixtures is only prevented by the diluting effect of the dry inert gas.

Cryo Pumps with Fully Automatic Electric Regeneration System from Oerlikon Leybold Vacuum

The cryopump is warmed up to room temperature by heating the 1st and 2nd stages of the cold head with elec-

In order to be able to safely remove any gases which may present a health hazard when the safety valve responds, the valve is equipped with an additional DN 40 KF flange where an exhaust line is connected.

Advantages to the User

- Significantly reduced investment and operating costs
- Small footprint

tric heaters. In this case, a defined and controlled temperature distribution within the cryopump can be set up. This controlled warming process ensures that the pumped gases are removed sequentially, i.e. the pumped gases are released one after the other in the following sequence:

- Gases adsorbed at the cryopanel (e.g. hydrogen, helium, neon),
- Gases condensed at the cryopanel (e.g. nitrogen, oxygen, argon),
- Gases and vapors which have condensed on to the baffle and thermal radiation shield (e.g. water vapor).

The electric method of regeneration from Oerlikon Leybold Vacuum prevents gases such as hydrogen and oxygen from being present in the pump at the same time. This excludes the formation of ignitable gas mixtures right from the start.

Cryo pumps without fully automatic control and without electric regeneration system belong to the BasicLine (BL), like the COOLVAC 800 BL, for example.

The warming up process is fully automatic. Pressure and temperature distribution within the pump are set up and controlled by the control system at all times. The sequential regeneration of pumped gases prevents the formation

The pump's body, all flanges and the safety valve are made of high-quality stainless steel.

of ignitable gases right from the start. This ensures the utmost safety during the regeneration of cryo pumps from Oerlikon Leybold Vacuum.

In the case of cryogenic pumps with fully automatic control there exist two cryopump lines.


1. The COOLVAC BasicLine (COOLVAC BL) offering the following pumping speed class for Nitrogen in l/s: 800; COOLVAC 800 BL, for example. Other pumping speed classes from 1 500 to 18 000 l/s are available on request. For more information please contact your local Oerlikon Leybold Vacuum representative.
2. The COOLVAC ClassicLine (COOLVAC CL) offering the following pumping speed classes for nitrogen in l/s: 800, 1 500, 2 000, 3 000, 5 000, 10 000 and 18 000; COOLVAC 1500 CL, for example.

In the price list the designators "V" appears in connection with the pump designations.


"V":

The high vacuum flange is located at the top and the cold head below, as is the case for the COOLVAC 1500 CL-V, DN 200 CF.


Refrigerating Capacity of Cryogenic Cold Heads




Typical refrigerating capacity of the cold head COOLPOWER 50




Typical refrigerating capacity of the cold head COOLPOWER 140 T




Typical refrigerating capacity of the cold head COOLPOWER 7/25



Typical refrigerating capacity of the cold head COOLPOWER 5/100



Typical refrigerating capacity of the cold head COOLPOWER 5/100 T



Typical refrigerating capacity of the cold head COOLPOWER 10 MD

The refrigerating capacities stated apply to vertical operation with the cold end at the bottom.

Cold Heads

A refrigerator (cold head) is a gas cooling machine which operates on the basis of a thermodynamic cycle to produce cryogenic temperatures ($T \leq 120$ K).

Refrigerators operating according to the Gifford/McMahon principle have succeeded over other methods of cooling cryo pumps and cryostats. It is thus employed exclusively by Oerlikon Leybold Vacuum.

In order to account for individual requirements from customers, Oerlikon Leybold Vacuum offers customized cryostats as well.

Gifford/McMahon-Refrigerators

Advantages to the User


- Low temperatures on a single key press
- No liquid helium and no liquid nitrogen are required
- Very simple to operate
- High refrigerating capacity from a small volume
- Easy process control and temperature control via a computer

Advantages by Design

- No space problems since cold head and compressor unit can be installed and operated apart
- Installation of the cold head basically in any orientation
- High reliability
- Long periods of operation without maintenance
- Cooling of superconducting magnets; in magnetic resonance tomographs, for example
- Cooling of samples and detectors; especially for cooling of
 - samples for spectroscopic analysis in the areas of solid state and surface physics
 - high temperature superconductors
 - superconductors and semiconductors
 - infrared and gamma detectors
- Calibration of sensors

Typical Applications

- Cooling of cryopanel in cryo pumps thereby producing high or ultra-high vacuum



Dual-stage Gifford/McMahon cold head (schematic diagram)


Cold Heads from the COOLPOWER Range

The standard range of single-stage and two-stage cold heads matches a wide range of applications.


Oerlikon Leybold Vacuum is offering refrigerators with usable refrigerating powers of 140 W at 80 K (COOLPOWER 140 T, single-stage) and down to 3.5 W at 10 K (COOLPOWER 5/100 T; dual-stage).

The cold heads basically consist of three subassemblies:

- Drive and control unit for the displacer
- Displacer
- First stage of the cold head (and second stage in the case of two-stage cold heads).



Refrigerating capacity as a function of temperature; operation in connection with the recommended compressor unit at 50 Hz; measured under standard acceptance conditions: Refrigerating capacity \dot{Q}_1 of the first stage as a function of temperature T_1 of the first stage (2nd stage: $\dot{Q}_2 = 0$).



Refrigerating capacity \dot{Q}_2 of the second stage as a function of temperature T_2 , of the second stage (1st stage: $T_1 = 80$ K = constant). Standard acceptance conditions: Cold head in a vacuum, 2nd cold stage thermally shielded by a radiation shield (high-gloss nickel-plated) attached to the 1st stage, thermal loading \dot{Q} simulated by electrical heating.

Pneumatically driven Cold Heads

Advantages

- Simple Design

The pneumatic drive system for the displacer of these cold heads from Oerlikon Leybold Vacuum consists of only two mechanically moving components: the rotating control valve and the synchronous motor driving the control valve.

- Easy and quick maintenance

All Oerlikon Leybold Vacuum cryo pumps from the COOLVAC range are equipped with pneumatically driven Oerlikon Leybold Vacuum cold heads.

Owing to the simple design of the built-in cold heads, maintenance is easy. Maintenance can be performed in place without detaching the cryopump from the vacuum chamber.

Mechanically driven Cold Heads

Advantages

In the case of the mechanically driven Oerlikon Leybold Vacuum cold heads, the displacer is moved through the so-called "Scotch yoke" directly by the drive motor. This elaborate mechanism allows the gas flow and the movement of the displacer to be precisely controlled through which it is possible to attain with two-stage cold heads especially high refrigerating capacities in the range of lowest temperatures (refrigerators of the COOLPOWER 10 MD line).

Advantages Through High Reliability

As to reliability, Oerlikon Leybold Vacuum cold heads are top performers.

Especially high reliability is required for medical instrumentation, specifically in connection with nuclear spin tomographs. In this application cold heads are used to cool superconducting magnets and they are thus exposed to strong magnetic fields.

The leading manufacturers of nuclear spin tomographs have therefore decided to use Oerlikon Leybold Vacuum cold heads to cool the superconducting magnets.

Refrigerator Cryostats (Basic Units)

Advantages to the User

- Can be installed basically in any orientation thereby offering a high degree of flexibility in experimental arrangements
- Can be set to any temperature within 6.5 and 320 K
- High refrigerating capacity, constant temperatures
- No liquid refrigerants are required
- Very simple to operate
- Temperature control without problems through standardized control and connecting components
- Possible high throughput of samples due to short cooldown and warming-up periods

Typical Applications

- Cooling of
 - high temperature superconductors
 - superconductors and semiconductors
 - infrared and gamma detectors
- Measurement of electric and thermal transport quantities, as a function of the temperature, such as
 - electric and thermal conductance
 - electromotive force

Especially in connection with:

- Spectroscopic investigations in the infrared, visible and ultraviolet spectral ranges
- Matrix spectroscopy
- Moessbauer spectroscopy
- Magneto-optic experiments

Compressor Units

COOLPAK 2000 to 6000 compressors are available for single operation of the remaining cold heads from the COOLPOWER line as well as for multiple operation of cryo pumps and cryostats.

The period during which no maintenance will be required on the Oerlikon Leybold Vacuum compressor units depends on the service life of the adsorber. If the values for the ambient temperature and the cooling water

entry temperature remain within the specified range, Oerlikon Leybold Vacuum guarantees a service life for the adsorber - and thus a period during which no maintenance will be required - of 18 000 operating hours.

The possibilities for single and multiple operation of refrigerator cryo pumps are given in the following table:

Compressor Unit	Cold Heads	Cryo Pumps
COOLPAK 2000/2200	1 x COOLPOWER 50 and 7/25	1 x COOLVAC 800/1500/2000/3000
COOLPAK 2000 (A)/2200 (A)	1 x COOLPOWER 50 and 7/25	1 x COOLVAC 800/1500/2000/3000
COOLPAK 6000 HD	2 x COOLPOWER 50 and 7/25 up to 2 x COOLPOWER 5/100 ¹⁾	2 x COOLVAC 800/1500/2000/3000 2 x COOLVAC 5000 ¹⁾
COOLPAK 6000 H/6200 H	1 x COOLPOWER 140 T 1 x COOLPOWER 5/100	3 x COOLVAC 800/1500/2000 2 x COOLVAC 3000 (5000 ¹⁾) 1 x COOLVAC 5000/10000
COOLPAK 6000 HMD/6200 HMD	1 x COOLPOWER 10 MD	

¹⁾ At reduced power

Approval

The Oerlikon Leybold Vacuum refrigerators in this catalog part (consisting of compressor unit COOLPAK 6000/6200, flexlines FL and the cold head COOLPOWER ²⁾) meet – as complete systems – the requirements of the NRTL (Nationally Recognized Testing

Laboratory) approval for the North American continent.

Oerlikon Leybold Vacuum refrigerators are listed under the reference number UL 471 : 2006 R3.06.

²⁾ Resp. formerly RGD

CE Approval

The Oerlikon Leybold Vacuum compressor units RW and COOLPAK meet the basic requirements regarding safety and health of the relevant EC directives.

Products Cryo Pumps

Standard Cryo Pumps, BasicLine COOLVAC 800 BL

Advantages to the User

- Hydrocarbon-free high vacuum
- High capacity for argon and hydrogen
- High pumping speed for water vapor, argon and hydrogen

Typical Applications

- Lamps and tubes manufacture
- Transfer chambers / Loadlock
- General research

Advantages to the User

- Hydrocarbon-free ultra-high vacuum
- High pumping speed for water vapor, nitrogen and hydrogen

Typical Applications


- Beam tubes in particle accelerators
- General research

Advantages to the User


- Hydrocarbon-free ultra-high vacuum
- High pumping speed for water vapor, nitrogen and hydrogen

Typical Applications


- Beam tubes in particle accelerators
- UHV systems



Dimensional drawing for the
COOLVAC 800 BL (160 ISO-K)



Dimensional drawing for the
COOLVAC 800 BL (160 CF)



Dimensional drawing for the
COOLVAC 800 BL UHV (160 CF)

Technical Data

		800 BL (ISO-K)	COOLVAC 800 BL (CF)	800 BL UHV (CF)
High vacuum flange	DN	160 ISO-K	160 CF	160 CF
Fore vacuum flange	DN	25 KF	25 KF	40 CF
Flange for other purposes	DN	16 KF (2x)	16 KF (2x)	16 CF (1x), 40 CF (1x)
Safety valve with DN 40 KF flange connection for gas exhaust line		welded-in	welded-in	burst disk mounted on DN 16 CF
Pumping speed				
H ₂ O	l x s ⁻¹	2600	2600	2600
Ar / N ₂	l x s ⁻¹	640 / 800	640 / 800	640 / 800
H ₂ / He	l x s ⁻¹	1000 / 300	1000 / 300	1000 / 300
Capacity				
Ar / N ₂	bar x l (Torr x l)	300 (225 000) / 300 (225 000)	300 (225 000) / 300 (225 000)	300 (225 000) / 300 (225 000)
H ₂ at 10 ⁻⁶ mbar	bar x l (Torr x l)	4.5 (3375)	4.5 (3375)	4.5 (3375)
He	bar x l (Torr x l)	0.5 (375)	0.5 (375)	0.5 (375)
Built-in cold head	COOLPOWER	7/25	7/25	7/25
Max. throughput				
Ar / N ₂	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	4 (3) / 4 (3)	4 (3) / 4 (3)	4 (3) / 4 (3)
H ₂	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	2 (1.5)	2 (1.5)	2 (1.5)
Crossover value	mbar x l (Torr x l)	150 (112)	150 (112)	150 (112)
Cool down time to 20 K	min	50	50	50
Overall height	mm (in.)	535 (21.06)	538 (21.18)	538 (21.18)
Weight	kg (lbs)	12 (26.5)	12 (26.5)	12 (26.5)
Silicon diode for temperature measurements at second stage of the cold head		built-in to a DN 16 KF with 4-way HV current feedthrough	built-in to a DN 16 KF with 4-way HV current feedthrough	built-in to a DN 16 CF with 4-way UHV feedthrough

Ordering Information

	800 BL (ISO-K)	COOLVAC 800 BL (CF)	800 BL UHV (CF)
	Part No.	Part No.	Part No.
COOLVAC	844160V1006	844160V1002	844160V9002
Compressor unit			
COOLPAK 2000	840000V2000	840000V2000	840000V2000
COOLPAK 2200	840000V2200	840000V2200	840000V2200
COOLPAK 2000 A	840000V2010	840000V2010	840000V2010
COOLPAK 2200 A	840000V2210	840000V2210	840000V2210
Connecting cable			
Compressor – cold head, 4.5 m (15.75 ft)	E 400000323	E 400000323	E 400000323
Electric extension cable EL 4.5	893 74	893 74	893 74
Flexlines			
FL 4.5 (1/2", 1/2")	892 87	892 87	892 87
or FL 9.0 (1/2", 1/2")	892 88	892 88	892 88
Low temperature measuring instrument	upon request	upon request	upon request
Cable for the silicon diode, 10 m (35.0 ft) long	upon request	upon request	upon request

Cryo Pumps with Fully Automatic Control, ClassicLine

COOLVAC 800 CL

COOLVAC 1.500 CL



COOLVAC 1.500 CL

Advantages to the User

- Hydrocarbon-free high vacuum
- High capacity for argon and hydrogen
- High crossover value
- Simple operation
- Trouble-free integration into complex systems
- Fully automatic regeneration through Cryo Compact Control
- Easy servicing

Typical Applications


- Evaporators
- Sputtering systems
- Ion implanters
- Optical coating systems
- Metallization systems

Advantages to the User


- Hydrocarbon-free high vacuum
- High capacity for argon and hydrogen
- High crossover value
- Simple operation
- Trouble-free integration into complex systems
- Fully automatic regeneration through Cryo Compact Control
- Easy servicing

Typical Applications

- Evaporators
- Sputtering systems
- Ion implanters
- Optical coating systems
- Metallization systems



Dimensional drawing for the COOLVAC 800 CL (DN 160 ISO-K)



Dimensional drawing for the COOLVAC 1.500 CL (DN 200 ISO-K)

Technical Data

COOLVAC

		800 CL	1.500 CL
High vacuum (HV) flange	DN	160 ISO-K / 160 CF	200 ISO-K / 200 CF / 6" ANSI
Fore vacuum flange	DN	25 KF	25 KF
Flange for connection a gauge head	DN	16 KF	16 KF
Flange for the electrical connection	DN	16 KF	16 KF
Safety valve with flange connection for gas exhaust line	DN	40 KF	40 KF
4-way current feedthrough for Si diode on a flange	DN	16 KF	16 KF
Heaters			
1st stage	W	160	160
	V AC	42	42
2nd stage	W	90	90
	V AC	42	42
Temperature sensor			
1st stage		Pt100	Pt100
2nd stage		Si diode	Si diode
Built-in cold head	COOLPOWER	7/25	7/25
Weight	kg (lbs)	15 (33.1)	25 (55.2)
Cooldown time to $T_2 = 20$ K	min	50	60
Crossover value	mbar x l (Torr x l)	150 (112)	210 (157)
Pumping speed			
H ₂ O	l x s ⁻¹	2600	4600
Ar / N ₂	l x s ⁻¹	640 / 800	1200 / 1500
H ₂	l x s ⁻¹	1000	2500
Capacity			
Ar / N ₂	bar x l	300 / 300	1000 / 1000
H ₂ at 10 ⁻⁶ mbar	bar x l	4.5	12.0
Max. throughput			
Ar / N ₂	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	4 (3) / 4 (3)	12 (9) / 12 (9)
H ₂ O	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	2 (1.5)	6 (4.5)
Helium connections (Self-sealing couplings: outside thread, type 5400-S2-8)	DN	1/2"	1/2"

Ordering Information

COOLVAC 800 CL

	Single Operation		Dual operation			Multiple Operation	
	Europe	USA/Japan	Europe	Europe	USA/Japan	Europe	USA/Japan
	Part No.		Part No.			Part No.	
COOLVAC 800 CL DN 160 CF DN 160 ISO-K	844160V0002 844160V0006		844160V0002 (2x) 844160V0006 (2x)			844160V0002 (3x) 844160V0006 (3x)	
Electronics and Cables							
System controller SC	844 230		844 230	844 230	844 230	844 230	
Power supply PS (50/60 Hz) 230 V, 1-ph. (switchable to 115 V) 200 V, 3-ph. (switchable to 400 V)	844 135 -		844 135 -	- 844 235	- 844 235	- 844 235	
Network communication cable – System controller to the pump(s) 10 m (35.0 ft) 20 m (70.0 ft)	844 261 844 262		844 261 844 262	844 261 844 262	844 261 844 262	844 261 844 262	
Network PM cable for the link between the pumps 3 m (10.5 ft) 10 m (35.0 ft)	- -		844 256 844 258	844 256 844 258	844 256 844 258	844 256 (2x) 844 258 (2x)	
Power supply cable from power supply to pump 10 m (35.0 ft) 20 m (70.0 ft)	- -		- -	844 251 (2x) 844 252 (2x)	844 251 (2x) 844 252 (2x)	844 251 (3x) 844 252 (3x)	
Remote control cable CP, 1 m (3.5 ft)	-		-	844 265	844 265	844 265	
Cable compressor – Power supply 10 m (35.0 ft) 20 m (70.0 ft)	844 129 844 139		844 129 844 139	- -	- -	- -	
Cable system controller – Power supply 1 m (3.5 ft)	844 141		844 141	-	-	-	
Cable pump module PM – Power supply 10 m (35.0 ft) 20 m (70.0 ft)	844 128 844 138		844 128 (2x) 844 138 (2x)	- -	- -	- -	
Connecting cable compressor – pump, 4.5 m (15.75 ft)	E 400 000 323		E 400 000 323 (2x)	-	-	-	
Electric extension cable EL 4.5	893 74		893 74 (2x)	-	-	-	
Compressors and Flexlines							
Compressor							
CP 2000	840000V2000	-	-	-	-	-	-
CP 2000 A	840000V2010	-	-	-	-	-	-
CP 2200	-	840000V2200	-	-	-	-	-
CP 2200 A	-	840000V2210	-	-	-	-	-
CP 6000 HD	-	-	840000V6004	-	-	-	-
CP 6000 H	-	-	-	840000V6001	-	840000V6001	-
CP 6200 H	-	-	-	-	840000V6201	-	840000V6201
Accessories							
Water cooling discharge throttle	-	-	E 840000 133	-	-	-	-
Power supply cable for compressor	1)		1)	1)	1)	1)	
Set of flexlines FL 4.5 (1/2", 1/2") or FL 9.0 (1/2", 1/2")	892 87 892 88		892 87 (2x) 892 88 (2x)	892 87 (2x) 892 88 (2x)	892 87 (2x) 892 88 (2x)	892 87 (3x) 892 88 (3x)	
Gas manifold (1 piece each) GD 2 GD 4	- -		840 253 (2x) -	840 253 (2x) -	840 253 (2x) -	- 840 254 (2x)	

The arrangement of the components is shown in the chapter "Accessories" under the heading "COOLVAC ClassicLine, System Components"

1) See Ordering Information for the compressor units COOLPAK

Ordering Information

COOLVAC 1.500 CL

	Single Operation		Dual operation			Multiple Operation	
	Europe	USA/Japan	Europe	Europe	USA/Japan	Europe	USA/Japan
	Part No.		Part No.			Part No.	
COOLVAC 1.500 CL							
DN 200 CF	844200V0002		844200V0002 (2x)			844200V0002 (3x)	
DN 6" ANSI	844200V0004		844200V0004 (2x)			844200V0004 (3x)	
DN 200 ISO-K	844200V0006		844200V0006 (2x)			844200V0006 (3x)	
Electronics and Cables							
System controller SC	844 230		844 230	844 230	844 230	844 230	
Power supply PS (50/60 Hz)							
230 V, 1-ph. (switchable to 115 V)	844 135		844 135	-	-	-	
200 V, 3-ph. (switchable to 400 V)	-		-	844 235	844 235	844 235	
Network communication cable – System controller to the pump(s)							
10 m (35.0 ft)	844 261		844 261	844 261	844 261	844 261	
20 m (70.0 ft)	844 262		844 262	844 262	844 262	844 262	
Network PM cable for the link between the pumps							
3 m (10.5 ft)	-		844 256	844 256	844 256	844 256 (2x)	
10 m (35.0 ft)	-		844 258	844 258	844 258	844 258 (2x)	
Power supply cable from power supply to pump							
10 m (35.0 ft)	-		-	844 251 (2x)	844 251 (2x)	844 251 (3x)	
20 m (70.0 ft)	-		-	844 252 (2x)	844 252 (2x)	844 252 (3x)	
Remote control cable CP, 1 m (3.5 ft)	-		-	844 265	844 265	844 265	
Cable compressor – Power supply							
10 m (35.0 ft)	844 129		844 129	-	-	-	
20 m (70.0 ft)	844 139		844 139	-	-	-	
Cable system controller – Power supply							
1 m (3.5 ft)	844 141		844 141	-	-	-	
Cable pump module PM – Power supply							
10 m (35.0 ft)	844 128		844 128 (2x)	-	-	-	
20 m (70.0 ft)	844 138		844 138 (2x)	-	-	-	
Connecting cable compressor – pump, 4.5 m (15.75 ft)	E 400 000 323		E 400 000 323				
			(2x)	-	-	-	
Electric extension cable EL 4.5	893 74		893 74 (2x)	-	-	-	
Compressors and Flexlines							
Compressor							
CP 2000	840000V2000	-	-	-	-	-	-
CP 2000 A	840000V2010	-	-	-	-	-	-
CP 2200	-	840000V2200	-	-	-	-	-
CP 2200 A	-	840000V2210	-	-	-	-	-
CP 6000 HD	-	-	840000V6004	-	-	-	-
CP 6000 H	-	-	-	840000V6001	-	840000V6001	-
CP 6200 H	-	-	-	-	840000V6201	-	840000V6201
Accessories							
Water cooling discharge throttle	-	-	E 840000 133	-	-	-	-
Power supply cable for compressor	1)		1)	1)	1)	1)	
Set of FLEXLINES							
FL 4.5 (1/2", 1/2")	892 87		892 87 (2x)	892 87 (2x)	892 87 (2x)	892 87 (3x)	
or FL 9.0 (1/2", 1/2")	892 88		892 88 (2x)	892 88 (2x)	892 88 (2x)	892 88 (3x)	
Gas manifold (1 piece each)							
GD 2	-		840 253 (2x)	840 253 (2x)	840 253 (2x)	-	
GD 4	-		-	-	-	840 254 (2x)	

The arrangement of the components is shown in the chapter "Accessories" under the heading "COOLVAC ClassicLine, System Components".

¹⁾ See Ordering Information for the compressor units COOLPAK

COOLVAC 2.000 CL




COOLVAC 2.000 CL

Advantages to the User

- Hydrocarbon-free high vacuum
- High capacity for argon and hydrogen
- High crossover value
- Simple operation
- Trouble-free integration into complex systems
- Fully automatic regeneration through Cryo Compact Control
- Easy servicing

Typical Applications

- Evaporators
- Sputtering systems
- Ion implanters
- Optical coating systems
- Metallization systems



Dimensional drawing for the COOLVAC 2.000 CL (DN 250 CF)

COOLVAC 3.000 CL




COOLVAC 3.000 CL

Advantages to the User

- Hydrocarbon-free high vacuum
- High capacity for argon and hydrogen
- High crossover value
- Simple operation
- Trouble-free integration into complex systems
- Fully automatic regeneration through Cryo Compact Control
- Easy servicing

Typical Applications

- Evaporators
- Sputtering systems
- Ion implanters
- Optical coating systems
- Metallization systems



Dimensional drawing for the COOLVAC 3.000 CL (DN 320 ISO-K / 10" ANSI)

Technical Data

COOLVAC

		2.000 CL	3.000 CL
High vacuum (HV) flange	DN	250 ISO-K / 250 CF / 8" ANSI	320 ISO-K / 10" ANSI
Fore vacuum flange	DN	25 KF	25 KF
Flange for connection a gauge head	DN	16 KF	16 KF
Flange for the electrical connection	DN	16 CF	16 CF
Safety valve with flange connection for gas exhaust line	DN	40 KF	40 KF
4-way current feedthrough for Si diode on a flange	DN	16 KF	16 KF
Heaters			
1st stage	W	160	160
	V AC	42	42
2nd stage	W	90	90
	V AC	42	42
Temperature sensor			
1st stage		Pt100	Pt100
2nd stage		Si diode	Si diode
Built-in cold head	COOLPOWER	7/25	7/25
Weight	kg (lbs)	25 (55.2)	35 (77.3)
Cooldown time to T ₂ = 20 K	min	70	80
Crossover value	mbar x l (Torr x l)	250 (187)	500 (375)
Pumping speed			
H ₂ O	l x s ⁻¹	7000	10500
Ar / N ₂	l x s ⁻¹	1600 / 2100	2500 / 3000
H ₂	l x s ⁻¹	3200	6000
Capacity			
Ar / N ₂	bar x l	1600 / 1600	2500 / 2500
H ₂ at 10 ⁻⁶ mbar	bar x l	15	28
Max. throughput			
Ar / N ₂	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	12 (9) / 12 (9)	15 (11.2) / 15 (11.2)
H ₂ O	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	6 (4.5)	10 (7.5)
Helium connections (Self-sealing couplings: outside thread, type 5400-S2-8)	DN	1/2"	1/2"

Ordering Information

COOLVAC 2.000 CL

	Single Operation		Dual operation			Multiple Operation	
	Europe	USA/Japan	Europe	Europe	USA/Japan	Europe	USA/Japan
	Part No.		Part No.			Part No.	
COOLVAC 2.000 CL							
DN 250 CF	844250V0002		844250V0002 (2x)			844250V0002 (3x)	
DN 8" ANSI	844250V0004		844250V0004 (2x)			844250V0004 (3x)	
DN 250 ISO-K	844250V0006		844250V0006 (2x)			844250V0006 (3x)	
Electronics and Cables							
System controller SC	844 230		844 230	844 230	844 230	844 230	
Power supply PS (50/60 Hz)							
230 V, 1-ph. (switchable to 115 V)	844 135		844 135	-	-	-	
200 V, 3-ph. (switchable to 400 V)	-		-	844 235	844 235	844 235	
Network communication cable – System controller to the pump(s)							
10 m (35.0 ft)	844 261		844 261	844 261	844 261	844 261	
20 m (70.0 ft)	844 262		844 262	844 262	844 262	844 262	
Network PM cable for the link between the pumps							
3 m (10.5 ft)	-		844 256	844 256	844 256	844 256 (2x)	
10 m (35.0 ft)	-		844 258	844 258	844 258	844 258 (2x)	
Power supply cable from power supply to pump							
10 m (35.0 ft)	-		-	844 251 (2x)	844 251 (2x)	844 251 (3x)	
20 m (70.0 ft)	-		-	844 252 (2x)	844 252 (2x)	844 252 (3x)	
Remote control cable CP, 1 m (3.5 ft)	-		-	844 265	844 265	844 265	
Cable compressor – Power supply							
10 m (35.0 ft)	844 129		844 129	-	-	-	
20 m (70.0 ft)	844 139		844 139	-	-	-	
Cable System Controller – Power Supply							
1 m (3.5 ft)	844 141		844 141	-	-	-	
Cable pump module PM – Power supply							
10 m (35.0 ft)	844 128		844 128 (2x)	-	-	-	
20 m (70.0 ft)	844 138		844 138 (2x)	-	-	-	
Connecting cable compressor – pump, 4.5 m (15.75 ft)	E 400 000 323		E 400 000 323				
			(2x)	-	-	-	
Electric extension cable EL 4.5	893 74		893 74 (2x)	-	-	-	
Compressors and Flexlines							
Compressor							
CP 2000	840000V2000	-	-	-	-	-	-
CP 2000 A	840000V2010	-	-	-	-	-	-
CP 2200	-	840000V2200	-	-	-	-	-
CP 2200 A	-	840000V2210	-	-	-	-	-
CP 6000 HD	-	-	840000V6004	-	-	-	-
CP 6000 H	-	-	-	840000V6001	-	840000V6001	-
CP 6200 H	-	-	-	-	840000V6201	-	840000V6201
Accessories							
Water cooling discharge throttle	-	-	E 840 000 133	-	-	-	-
Power supply cable for compressor	1)		1)	1)	1)	1)	
Set of flexlines							
FL 4.5 (1/2", 1/2")	892 87		892 87 (2x)	892 87 (2x)	892 87 (2x)	892 87 (3x)	
or FL 9.0 (1/2", 1/2")	892 88		892 88 (2x)	892 88 (2x)	892 88 (2x)	892 88 (3x)	
Gas manifold (1 piece each)							
GD 2	-		840 253 (2x)	840 253 (2x)	840 253 (2x)	-	
GD 4	-		-	-	-	840 254 (2x)	

The arrangement of the components is shown in the chapter "Accessories" under the heading "COOLVAC ClassicLine, System Components".

1) See Ordering Information for the compressor units COOLPAK

Ordering Information

COOLVAC 3.000 CL

	Single operation		Dual operation		
	Europe	USA/Japan	Europe	Europe	USA/Japan
	Part No.		Part No.		
COOLVAC 3.000 CL DN 10" ANSI DN 320 ISO-K	844320V0004 844320V0006		844320V0004 (2x) 844320V0006 (2x)		
Electronics and Cables					
System controller SC	844 230	844 230	844 230	844 230	844 230
Power supply PS (50/60 Hz) 230 V, 1-ph. (switchable to 115 V) 200 V, 3-ph. (switchable to 400 V)	844 135 -	844 135 -	844 135 -	- 844 235	- 844 235
Network communication cable – System controller to the pump(s) 10 m (35.0 ft) 20 m (70.0 ft)	844 261 844 262	844 261 844 262	844 261 844 262	844 261 844 262	844 261 844 262
Network PM cable for the link between the pumps 3 m (10.5 ft) 10 m (35.0 ft)	- -	- -	844 256 844 258	844 256 844 258	844 256 844 258
Power supply cable from power supply to pump 10 m (35.0 ft) 20 m (70.0 ft)	- -	- -	- -	844 251 (2x) 844 252 (2x)	844 251 (2x) 844 252 (2x)
Remote control cable CP, 1 m (3.5 ft)	-	-	-	844 265	844 265
Cable compressor – Power supply 10 m (35.0 ft) 20 m (70.0 ft)	844 129 844 139	844 129 844 139	844 129 844 139	- -	- -
Cable system controller – Power supply 1 m (3.5 ft)	844 141	844 141	844 141	-	-
Cable pump module PM – Power supply 10 m (35.0 ft) 20 m (70.0 ft)	844 128 844 138	844 128 844 138	844 128 (2x) 844 138 (2x)	- -	- -
Connecting cable compressor – pump, 4.5 m (15.75 ft)	E 400000323	E 400000323	E 400000323 (2x)	-	-
Electric extension cable EL 4.5	893 74	893 74	893 74 (2x)	-	-
Compressors and Flexlines					
Compressor					
CP 2000	840000V2000	-	-	-	-
CP 2000 A	840000V2010	-	-	-	-
CP 2200	-	840000V2200	-	-	-
CP 2200 A	-	840000V2210	-	-	-
CP 6000 HD	-	-	840000V6004	-	-
CP 6000 H	-	-	-	840000V6001	-
CP 6200 H	-	-	-	-	840000V6201
Accessories					
Water cooling discharge throttle	-	-	E 840000133	-	-
Power supply cable for compressor	1)		1)	1)	1)
Set of flexlines FL 4.5 (1/2", 1/2") or FL 9.0 (1/2", 1/2")	892 87 892 88	892 87 892 88	892 87 (2x) 892 88 (2x)	892 87 (2x) 892 88 (2x)	892 87 (2x) 892 88 (2x)
Gas manifold (1 piece each) GD 2	-	-	840 253 (2x)	840 253 (2x)	840 253 (2x)

The arrangement of the components is shown in the chapter "Accessories" under the heading "COOLVAC ClassicLine, System Components".

1) See Ordering Information for the compressor units COOLPAK

COOLVAC 5.000 CL




COOLVAC 5.000 CL

Advantages to the User

- Hydrocarbon-free high vacuum
- High capacity for argon and hydrogen
- High crossover value
- Simple operation
- Trouble-free integration into complex systems
- Fully automatic regeneration through Cryo Compact Control
- Easy servicing

Typical Applications

- Evaporators
- Ion implanters
- Electron beam welding systems
- Optical coating systems
- Metallization systems



Dimensional drawing for the COOLVAC 5.000 CL

COOLVAC 10.000 CL




COOLVAC 10.000 CL

Advantages to the User

- Hydrocarbon-free high vacuum
- High capacity for argon and hydrogen
- High crossover value
- Simple operation
- Trouble-free integration into complex systems
- Fully automatic regeneration through Cryo Compact Control
- Easy servicing

Typical Applications

- Evaporators
- Space simulation chambers
- Electron beam welding systems
- Optical coating systems
- Metallization systems



Dimensional drawing for the COOLVAC 10.000 CL

Technical Data

COOLVAC

		5.000 CL	10.000 CL
High vacuum (HV) flange	DN	400 ISO-K	500 ISO-K
Fore vacuum flange	DN	40 KF	40 KF
Flange for connection of a gauge head	DN	16 KF	16 KF
Flange for the electrical connection	DN	40 KF	40 KF
Safety valve with flange connection for gas exhaust line	DN	40 KF	40 KF
4-way current feedthrough for Si diode on a flange	DN	16 KF	16 KF
Heaters			
1st stage	W	160	160
	V AC	42	42
2nd stage	W	90	90
	V AC	42	42
Temperature sensor			
1st stage		Pt100	Pt100
2nd stage		Si diode	Si diode
Built-in cold head	COOLPOWER	5/100	5/100
Weight	kg (lbs)	42 (92.7)	50 (110.4)
Cooldown time to T ₂ = 20 K	min	100	150
Crossover value	mbar x l (Torr x l)	700 (525)	800 (600)
Pumping speed			
H ₂ O	l x s ⁻¹	18000	30000
Ar / N ₂	l x s ⁻¹	4000 / 5200	8400 / 10000
H ₂	l x s ⁻¹	6200	12000
Capacity			
Ar / N ₂	bar x l	3000 / 3000	5500 / 5500
H ₂ at 10 ⁻⁶ mbar	bar x l	32	45
Max. throughput			
Ar / N ₂	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	10 (7.5) / 10 (7.5)	10 (7.5) / 10 (7.5)
H ₂	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	7 (5.3)	7 (5.3)
Helium connection (Self-sealing couplings: outside thread, types 5400-S2-8)	DN	1/2"	1/2"

Ordering Information

COOLVAC 5.000 CL

COOLVAC 10.000 CL

	Europe	USA/Japan	Europe	USA/Japan
	Part No.	Part No.	Part No.	Part No.
COOLVAC				
5.000 CL, DN 400 ISO-K	844 410	844 410	-	-
10.000 CL, DN 500 ISO-K	-	-	844 610V0006	844 610V0006
Electronics and Cables				
System controller SC	Part No. 844 230	Part No. 844 230	Part No. 844 230	Part No. 844 230
Power supply PS 230 V, 1-ph.	844 135	844 135	844 135	844 135
Network communication cable – System controller to the pump(s)				
10 m (35.0 ft)	844 261	844 261	844 261	844 261
20 m (70.0 ft)	844 262	844 262	844 262	844 262
Cable compressor – Power supply PS				
10 m (35.0 ft)	844 129	844 129	844 129	844 129
20 m (70.0 ft)	844 139	844 139	844 139	844 139
Cable system controller – Power supply 1 m (3.5 ft)	844 141	844 141	844 141	844 141
Cable pump module PM – Power supply				
10 m (35.0 ft)	844 128	844 128	844 128	844 128
20 m (70.0 ft)	844 138	P844 138	844 138	844 138
Compressors and Flexlines				
Compressor				
CP 6000 H	840000V6001	-	840000V6001	-
CP 6200 H	-	840000V6201	-	840000V6201
Power supply cable for compressor	see Ordering Information for the Compressor Units COOLPAK	see Ordering Information for the Compressor Units COOLPAK	see Ordering Information for the Compressor Units COOLPAK	see Ordering Information for the Compressor Units COOLPAK
Set of flexlines				
FL 4.5 (1/2", 1/2")	892 87	892 87	892 87	892 87
or FL 9.0 (1/2", 1/2")	892 88	892 88	892 88	892 88
and EL 4.5 (electric extension cable)	893 74	893 74	893 74	893 74

The arrangement of the components is shown in the chapter "Accessories" under the heading "COOLVAC ClassicLine, System Components"

COOLVAC 18.000 CL




COOLVAC 18.000 CL with special flanges

Advantages to the User

- Hydrocarbon-free high vacuum
- High pumping speed for water vapor and nitrogen
- Fast, safe and efficient regeneration with the electric regeneration system
- Simple operation

Typical Applications

- Space simulation chambers
- Evaporators
- Electron beam welding systems
- Optical coating systems
- Metallization systems



Dimensional drawing for the COOLVAC 18.000 CL

COOLVAC 30.000




COOLVAC 30.000 with special flanges

Advantages to the User

- Hydrocarbon-free high vacuum
- High pumping speed for water vapor and nitrogen
- Fast, safe and efficient regeneration with the electric regeneration system
- Simple operation

Typical Applications

- Space simulation chambers
- Evaporators
- Electron beam welding systems
- Optical coating systems
- Metallization systems



Dimensional drawing for the COOLVAC 30.000

COOLVAC 60.000

COOLVAC 60.000 LN₂ cooled upon request




COOLVAC 60.000 with special flanges

Advantages to the User

- Hydrocarbon-free high vacuum
- High pumping speed for water vapor and nitrogen
- Fast, safe and efficient regeneration with the electric regeneration system
- Simple operation

Typical Applications

- Space simulation chambers
- Evaporators
- Electron beam welding systems
- Optical coating systems
- Metallization systems



Dimensional drawing for the COOLVAC 60.000

Technical Data

COOLVAC 18.000 CL

COOLVAC 30.000

COOLVAC 60.000

High vacuum flange	DN	630 ISO-F	35" ANSI	1250 ISO-F
Fore vacuum flange	DN	63 ISO-K	63 ISO-K	63 ISO-K
Flange with current feedthrough for silicon diode	DN	25 KF (2x)	16 KF (2x)	16 KF (2x)
Flange for other purposes	DN	40 KF	40 KF	40 KF
Safety valve with DN 40 KF flange connection for gas exhaust line (opening pressure)	DN mbar	40 KF 1100	40 KF 1100	40 KF 1100
Pumping speed				
H ₂ O	l x s ⁻¹	46000	93000	180000
Ar / N ₂	l x s ⁻¹	13500 / 18000	25000 / 30000	47000 / 57000
H ₂ / He	l x s ⁻¹	14000 / 4000	30000 / 7000	60000 / 15000
Capacity				
Ar / N ₂	bar x l	5000 / 5000	6500 / 6500	9000 / 9000
H ₂ at 10 ⁻⁶ mbar	bar x l	65	100	150
H ₂ O	bar x l	945		
Built-in cold head	COOLPOWER	5/100 (2x)	5/100 (2x) and 140T (1x)	5/100 (2x) and 140T (2x)
Max. throughput				
Ar / N ₂	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	14 / 14	14 / 14	25 / 25
H ₂	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	7	7	12
Crossover value at 20 K	mbar x l (Torr x l)	850	1200	1000
Cool down time to 20 K	min	180	260	330
Overall height	min	606	see drawing	see drawing
Weight	kg (lbs)	65	245	450
Silicon diode for temperature measurements at the second stage of the cold head		built-in (2x)	built-in (2x)	built-in (2x)
Regeneration heaters at the first and second stage of the cold head		built-in (2x)	-	-

Ordering Information

COOLVAC 18.000 CL


COOLVAC 30.000

COOLVAC 60.000


	Part No.	Part No.	Part No.
Cryopump			
COOLVAC 18.000 CL, 630 ISO-F	844630V0006	-	-
COOLVAC 30.000, 35" ANSI	-	upon request	-
COOLVAC 60.000, 1250 ISO-F	-	-	upon request
Compressor unit			
COOLPAK 6000 H	upon request (2x)	upon request (3x)	upon request (4x)
COOLPAK 6200 H	upon request (2x)	upon request (3x)	upon request (4x)
Power supply cable	see Ordering Information for the compressor units COOLPAK		
Set of flexlines			
FL 4.5 (1/2", 1/2")	Part No. 892 87 (2x)	Part No. 892 87 (3x)	Part No. 892 87 (4x)
or FL 9.0 (1/2", 1/2")	Part No. 892 88 (2x)	Part No. 892 88 (3x)	Part No. 892 88 (4x)
and EL 4.5 (electric extension cable)	Part No. 893 74 (2x)	Part No. 893 74 (3x)	Part No. 893 74 (4x)
Compact controller and cable kit	upon request	upon request	upon request

Products Cryogenics

Cold Heads, Pneumatically Driven Single-Stage Cold Heads COOLPOWER 50 and 140 T



Single-stage cold head's COOLPOWER 50 (left) and 140 T (right)



Dimensional drawing for the COOLPOWER 50 (left) and COOLPOWER 140 T (right)

Advantages to the User

- For installation mostly in any orientation
- High refrigerating capacity
- No liquid refrigerants are required
- Very simple to operate
- Short cooldown time

Typical Applications

- Cooling of cryopanel in cryo pumps and thus generation of high vacuum and ultra-high vacuum pressures
- Calibration of sensors
- Cooling of samples and detectors; especially for cooling of
 - samples for spectroscopic investigations in solid state and surface physics
 - high temperature superconductor and semiconductor conditions
 - infrared and gamma detectors

Technical Data

COOLPOWER 50

COOLPOWER 140 T

Refrigeration capacity at 50/60 Hz ¹⁾ at 80 K, approx.	W	50	140
at 20 K, approx.	W	-	20
Lowest attainable temperature ¹⁾	K	≤ 26	≤ 15
Cooldown time down to 20 K	min	-	≤ 55
to 20 K, approx.	min	20	-
Permissible ambient temperature	°C (°F)	+10 to +40 (+50 to +104)	+10 to +40 (+50 to +104)
He filling pressure at room temperature	bar	16	16
He connections Self-sealing screwed connections			
High pressure connection		1/2" ²⁾	1/2" ³⁾
Low pressure connection		1/2" ²⁾	1/2" ³⁾
Weight	kg (lbs)	8 (17.7)	12 (26.5)
Length of the electrical connection line to the compressor unit	m (ft)	-	4.5 (15.75)

Ordering Information

COOLPOWER 50

COOLPOWER 140 T

	Part No.	Part No.
Cold head		
with DN 100 CF-R	842050V0001	-
with DN 160 ISO-K	-	842 030
with weld-on pipe	842050V0000	-
other flanges	upon request	upon request
Accessories		
Connecting cable compressor – cold head, 4.5 m (15.75 ft)	E 400000323	included with the cold head
Compressor unit (for operation of one cold head)		
COOLPAK 2000	840000V2000	-
COOLPAK 2000 A	840000V2010	-
COOLPAK 2200	840000V2200	-
COOLPAK 2200 A	840000V2210	-
COOLPAK 6000 H		
400 V/50 Hz; 470 V/60 Hz	-	840000V6001
COOLPAK 6200 H		
200 V/50 Hz; 200 V, 230 V/60 Hz	-	840000V6201
Power supply cable	see Ordering Information for the compressor units COOLPAK	see Ordering Information for the compressor units COOLPAK
Set of flexlines FL 4.5 (1/2", 1/2") or FL 9.0 (1/2", 1/2") and EL 4.5 (electric extension cable)	892 87 892 88 893 74	892 87 892 88 893 74
Options		
Temperature measurement Silicon diode Low temperature measuring instrument Measuring cable	890 89 upon request upon request	890 89 upon request upon request

¹⁾ The refrigerating capacities and temperatures stated apply only to vertical operation with the cold end at the bottom

²⁾ Series 5400 from Aeroquip or compatible types

³⁾ Series 8 from Aeroquip

Dual-Stage Cold Heads

COOLPOWER 7/25, 5/100 and 5/100 T



Dual-stage cold head COOLPOWER 7/25




Dual-stage cold heads COOLPOWER 5/100 and COOLPOWER 5/100 T

Advantages to the User


- For installation in any orientation
- High refrigerating capacity
- No liquid refrigerants are required
- Very simple to operate
- Short cooldown time

Typical Applications

- Cooling of cryopanel in cryo pumps and thus generation of high vacuum and ultra-high vacuum pressures
- Cooling of samples and detectors; especially for cooling of
 - high temperature superconductors
 - superconductors and semi-conductors
 - infrared and gamma detectors
- samples for spectroscopic investigations in solid state and surface physics
- Calibration of sensors
- Cooling of accelerator components in the area of high energy physics
- Cooling of superconducting magnets; in nuclear magnetic resonance tomographs, for example (only COOLPOWER 5/100 and 5/100 T)



Dimensional drawing for the COOLPOWER 7/25



Dimensional drawing for the COOLPOWER 5/100 and COOLPOWER 5/100 T

Technical Data

COOLPOWER

		7/25	5/100	5/100 T
Refrigeration capacity at 50/60 Hz ¹⁾				
1st stage at 80 K, approx.	W	25	100	100
2st stage at 20 K, approx.	W	7	5	7.5
2st stage at 10 K, approx.	W	-	-	3.5
2st stage at 40 K, approx.	W	-	-	35
Lowest attainable temperature ¹⁾				
1st stage, approx.	K	≤ 35	≤ 35	≤ 35
2nd stage, approx.	K	≤ 10	≤ 10	6
Cooldown time of the				
2nd stage to 20 K, approx.	min	20	20	20
1st stage to 80 K, approx.	min	20	20	20
2nd stage to 10 K, approx.	min	-	-	35
1st stage to 40 K, approx.	min	-	-	30
2nd stage to 6 K, approx.	min	-	-	45
1st stage to 30 K, approx.	min	-	-	40
Permissible ambient temperature	°C (°F)	+5 to +40 (+41 to +104)	+5 to +40 (+41 to +104)	+5 to +40 (+41 to +104)
He filling pressure at room temperature	bar	16	16	16
He connections				
Self-sealing screwed connections				
High pressure connection		1/2" (#8 ²⁾)	1/2" (#8 ²⁾)	1/2" (#8 ²⁾)
Low pressure connection		1/2" (#8)	1/2" (#8)	1/2" (#8)
Weight	kg (lbs)	11 (24.3)	11 (24.3)	11 (24.3)
Length of the electrical connection line to the compressor unit (included with cold head)	m (ft)	4.5 (15.75)	4.5 (15.75)	4.5 (15.75)

Ordering Information

COOLPOWER

	7/25	5/100	5/100 T
	Part No.	Part No.	Part No.
Cold head			
COOLPOWER 7/25	842 040	-	-
COOLPOWER 5/100 with weld-on pipe	-	893 05	-
COOLPOWER 5/100 T	-	-	129 78
Accessories			
Connecting cable compressor – cold head, 4.5 m (15.75 ft)	E 400000323	included with the cold head	included with the cold head
Compressor unit (for operation of one cold head)			
COOLPAK 2000	840000V2000	-	-
COOLPAK 2000 A	840000V2010	-	-
COOLPAK 2200	840000V2200	-	-
COOLPAK 2200 A	840000V2210	-	-
COOLPAK 6000 H	-	840000V6001	840000V6001
COOLPAK 6200 H	-	840000V6201	840000V6201
Power supply cable	3)	3)	3)
Set of flexlines			
FL 4.5 (1/2", 1/2")	892 87	892 87	892 87
or FL 9.0 (1/2", 1/2")	892 88	892 88	892 88
and EL 4.5 (electric extension cable)	893 74	893 74	893 74
Options			
Temperature measurement / control			
Silicon diode	890 89	890 89	890 89
Low temperature measuring instrument	upon request	upon request	upon request
Measuring cable	upon request	upon request	upon request
Electrical heaters	upon request	upon request	upon request
Low temperature controller MODEL 9700	842 400	842 400	842 400
Measuring cable, 3 m (10.5 ft) long	842 401	842 401	842 401

¹⁾ The refrigerating capacities and temperatures stated apply to vertical operation with the cold end at the bottom

²⁾ Series 8 from Aeroquip

³⁾ See Ordering Information for the compressor units COOLPAK

Cold Heads, Mechanically Driven

Dual-Stage Cold Head COOLPOWER 10 MD



Dual-stage Cold Head COOLPOWER 10 MD

COOLPOWER 10 MD - the strongest 10 K GM cooler available on the market:

- High 2nd stage cooling capacity of > 18 W at 20 K
- High 1st stage cooling capacity of > 25 W at 40 K and ~ 110 W at 80 K


Advantages to the User

- Excellent cooling performance
- 18 W at 20 K by press-button operation
- High reliability
- Design optimized for MTBF 100,000 h
- Long and maintenance-free operation
- Low vibration due to directly driven displacer
- No liquid refrigerants are required
- Very simple to operate
- Short cooldown time
- Easy operation
 - Plug & Cool - as usual for all Oerlikon Leybold Vacuum GM coolers
 - Simple variation of motor speed via the COOLPAK MD compressor unit

Typical Applications

The COOLPOWER 10 MD is a mechanically driven double-stage Gifford McMahon (GM) cryo cooler and ideally suited for

- Cooling of cryo probes in NMR spectrometers
- Shield cooling of superconducting magnets in MRI
- Cooling of cryopanel in special Cryo pumps and thus generation of high vacuum and ultra-high vacuum pressures
- Cooling of larger samples and devices; especially
 - High temperature superconductor coils, wires and bulk materials
 - Recondensation of liquid refrigerants such as H₂, Ne
 - Samples for spectroscopic investigations in solid state and surface physics
 - Infrared and gamma detectors
- Calibration of sensors



Dimensional drawing for the COOLPOWER 10 MD

Technical Data

COOLPOWER 10 MD

Refrigeration capacity at 50/60 Hz ¹⁾		
1st stage at 80 K, approx.	W	110
2nd stage at 20 K, approx.	W	18
Lowest attainable temperature ¹⁾		
1st stage, approx.	K	≤ 28
2nd stage, approx.	K	≤ 8
Cooldown time of the 2nd stage to 20 K, approx.		min
		25
Permissible ambient temperature		°C (°F)
		+5 to +40 (+41 to +104)
He filling pressure at room temperature		bar
		16
He connections		
Self-sealing screwed connections		
High pressure connection		1/2" (#8 ²⁾)
Low pressure connection		1/2" (#8)
Weight	kg (lbs)	20 (44.15)

Ordering Information

COOLPOWER 10 MD

	Part No.
Cold head COOLPOWER 10 MD	842 010
Accessories	see Ordering Information for the compressor unit COOLPAK 6000 HMD/6200 HMD, connecting cable and flexline

¹⁾ The refrigerating capacities and temperatures stated apply to vertical operation with the cold end at the bottom

²⁾ Series 8 from Aeroquip

Compressor Units for Pneumatically Driven Cold Heads and Pumps, Air Cooling


COOLPAK 2000 A/2200 A



Compressor unit COOLPAK 2000 A (2200 A is similar)

Advantages to the User

- High efficiency and increased performance for cryogenic pumps and refrigerators
- High long-term reliability due to long-life and highly efficient components and improved oil management
- Very quiet and low vibration operation through the innovative horizontally suspended scroll compressor
- Simple installation and operation
- Global mains voltage compatibility
- Perfect integration within complex systems due to the 24 V Sub-D interface
- Simple adsorber replacement, otherwise maintenance-free
- Small footprint
- Low cost of ownership



Dimensional drawing of the COOLPAK 2000 A/2200 A

Technical Data

COOLPAK

		2000 A (50 Hz)	2200 A (60 Hz)
Number of electrical connections for cold heads		1	1
Helium system filling pressure at room temperature	bar	15	14
Ambient temperature	°C (°F)	+5 to +30 (+41 to +86)	+5 to +30 (+41 to +86)
Mains voltage (single phase)	V	230 ± 10%	208 ± 10%
Operating current			
with cooled down cold head	A	9.5 to 10.5	11.5 to 12.5
with warmed up cold head	A	12.0	13.0
Electric power consumption			
with cooled down cold head	kW	2.2	2.3
with warmed up cold head	kW	2.4	2.5
Remote control through interface		24 V DC	24 V DC
Helium connections self-sealing fittings			
high-pressure side (outside thread)		1/2"	1/2"
low-pressure side (outside thread)		1/2"	1/2"
Noise level (at a distance of 1 m (3.5 ft))	dB(A)	< 55	< 55
Dimensions (W x H x D)	mm (in.)	445 x 607 x 400 (17.52 x 23.90 x 15.74)	445 x 607 x 400 (17.52 x 23.90 x 15.74)
Weight	kg (lbs)	69 (152.32)	69 (152.32)

Ordering Information

COOLPAK

	2000 A (50 Hz)	2200 A (60 Hz)
	Part No.	Part No.
Compressor unit	840000V2010	840000V2210
Accessories, optional		
19" installation kit	840 022	840 022
RC adapter box (for operating older cold heads of type RGD, RGS or COOLPOWER 20 / 210 / 30 / 510)	840 910	840 910
Spare parts		
Absorber CPS-V8	E 840001973	E 840001973

Compressor Units for Pneumatically Driven Cold Heads and Pumps, Water Cooling


COOLPAK 2000/2200



Compressor unit COOLPAK 2000 (2200 is similar)

Advantages to the User

- High efficiency and increased performance for cryogenic pumps and refrigerators
- High long-term reliability due to long-life and highly efficient components and improved oil management
- Very quiet and low vibration operation through the innovative horizontally suspended scroll compressor
- Simple installation and operation
- Global mains voltage compatibility
- Perfect integration within complex systems due to the 24 V Sub-D interface
- Simple adsorber replacement, otherwise maintenance-free
- Small footprint
- Low cost of ownership



Dimensional drawing of the COOLPAK 2000/2200

Technical Data

COOLPAK

		2000 (50 Hz)	2200 (60 Hz)
Number of electrical connections for cold heads		1	1
Helium system filling pressure at room temperature	bar	15	14
Ambient temperature	°C (°F)	+5 to +40 (+41 to +104)	+5 to +40 (+41 to +104)
Cooling water consumption		< 5	< 5
Cooling water feed temperature	°C (°F)	+5 to +25 (+41 to +77)	+5 to +25 (+41 to +77)
Mains voltage (single phase)	V	230 ± 10%	208 ± 10%
Operating current			
with cooled down cold head	A	9.5 to 10.5	11.5 to 12.5
with warmed up cold head	A	12.0	13.0
Electric power consumption			
with cooled down cold head	kW	2.2	2.3
with warmed up cold head	kW	2.4	2.5
Remote control through interface	V DC	24	24
Helium connections			
self-sealing fittings			
high-pressure side (outside thread)		1/2"	1/2"
low-pressure side (outside thread)		1/2"	1/2"
Water connections	DN	10	10
Noise level (at a distance of 1 m (3.5 ft))	dB(A)	< 55	< 55
Dimensions (W x H x D)	mm (in.)	445 x 395 x 400 (17.52 x 15.55 x 15.74)	445 x 395 x 400 (17.52 x 15.55 x 15.74)
Weight	kg (lbs)	69 (152.32)	69 (152.32)

Ordering Information

COOLPAK

	2000 (50 Hz)	2200 (60 Hz)
	Part No.	Part No.
Compressor unit	840000V2000	840000V2200
Accessories, optional		
19" installation kit	840 022	840 022
RC adapter box (for operating older cold heads of type RGD, RGS or COOLPOWER 20 / 210 / 30 / 510)	840 910	840 910
Spare parts		
Absorber CPS-V8	E 840001973	E 840001973

Compressor Units for Pneumatically Driven Cold Heads and Pumps, Water Cooling


COOLPAK 6000 H/6200 H/6000 HD



Compressor units COOLPAK 6000 H/6200 H/6000 HD

Advantages to the User

- Highly effective and even more powerful when connected with Oerlikon Leybold Vacuum cryo pumps and refrigerators
- Excellent long-term reliability owing to the modular design and the long life components
- Silent and low vibration operation through scroll compressors
- Simple installation and operation
- Global power supply compatibility
- Easy integration in complex systems due to 24 V DC or RS 232 C interfaces
- Almost maintenance-free
- Small footprint
- Low cost of ownership



Dimensional drawing for the COOLPAK 6000 H/6200 H/6000 HD

Technical Data

COOLPAK

	6000 H / 6000 HD		6200 H	
	50 Hz	60 Hz	50 Hz	60 Hz
Number of electrical connections for cold heads	1	1	1	1
Helium system filling pressure at room temperature	17 bar	16	15	14
Ambient temperature	°C (°F) +5 to +40 (+41 to +104)	+5 to +40 (+41 to +104)	+5 to +40 (+41 to +104)	+5 to +40 (+41 to +104)
Cooling-water consumption ¹⁾	l/min 5.0	5.0	5.0	5.0
Cooling-water entry temperature	°C (°F) +5 to +25 (+41 to +77)	+5 to +25 (+41 to +77)	+5 to +25 (+41 to +77)	+5 to +25 (+41 to +77)
Main voltage (3 phase) upon delivery	V 380 - 400 ± 10%	–	230 ²⁾ + 1% / - 10%	230 ± 10%
alternative setting	V –	470 ± 10%	200 ± 10%	200 ± 10%
Operating currents with the cold head cool	A 10 to 12	–	20 to 22	–
with the cold head warm	A 11 to 13	–	22 to 25	–
Electrical power consumption with the cold head cool	kW 6.5 to 7.5	7.0 to 8.0	6.5 to 7.5	7.0 to 8.0
with the cold head warm	kW 7.0 to 8.0	7.5 to 8.5	7.0 to 8.0	7.5 to 8.5
Remote control via interface	24 V DC or RS 232 C	24 V DC or RS 232 C	24 V DC or RS 232 C	24 V DC or RS 232 C
Helium connections				
Self-sealing couplings				
High pressure connection (outside thread)	1/2"	1/2"	1/2"	1/2"
Low pressure connection (outside thread)	1/2"	1/2"	1/2"	1/2"
Water connections	Hose nozzle DN 12 / G 1/2" outside thread	Hose nozzle DN 12 / G 1/2" outside thread	Hose nozzle DN 12 / G 1/2" outside thread	Hose nozzle DN 12 / G 1/2" outside thread
Sound level (at 1 m (3.5 ft) distance)	dB(A) 60	60	60	60
Dimensions (W x H x D)	mm 440 x 589 x 558 (in.) (17.32 x 23.19 x 21.97)	440 x 589 x 558 (17.32 x 23.19 x 21.97)	440 x 589 x 558 (17.32 x 23.19 x 21.97)	440 x 589 x 558 (17.32 x 23.19 x 21.97)
Weight	kg (lbs) 104 (230)	104 (230)	104 (230)	104 (230)

Ordering Information

COOLPAK

	6000 H / 6000 HD		6200 H	
	50 Hz	60 Hz	50 Hz	60 Hz
	Part No.	Part No.	Part No.	Part No.
Compressor unit				
without power supply cable				
Connection for 1 cold head (CP ... H)	840000V6001	840000V6001	840000V6201	840000V6201
Connection for 2 cold heads (CP ... HD)	840000V6004	840000V6004	–	–
Power supply cable				
3.5 m (12.25 ft)				
CEE plug, 32 A/6h, 3-pol +N+PE	893 95	–	–	–
NEMA plug, L 16-20 P, 20 A/480 V, 3-pol +PE (AWG 12)	–	893 96	–	–
10 m (35.0 ft)				
with end splice (AWG 10)	–	–	840 111 ³⁾	840 111 ³⁾
20 m (70.0 ft)				
with end splice (AWG 10)	–	–	840 112 ³⁾	840 112 ³⁾
Accessories				
Water cooling discharge throttle	E 840 000 133 ⁴⁾	E 840 000 133 ⁴⁾	–	–
Spare parts				
Adsorber CACP 4000/6000	E 840 002 863	E 840 002 863	E 840 002 863	E 840 002 863

¹⁾ At a cooling water entry temperature of 25 °C (77 °F)

²⁾ At 14 bar filling pressure

³⁾ Also suitable for COOLPAK 6000 H(D)

⁴⁾ Only for COOLPAK 6000 HD

Compressor Units for Mechanically Driven Cold Heads and Pumps, Water Cooling COOLPAK 6000 HMD/6200 HMD




Compressor unit COOLPAK 6000 HMD/6200 HMD

Serves the purpose of individually driving the cold heads with mechanically driven displacers; i.e. COOLPOWER 10 MD, but also older cold heads like COOLPOWER 150, 130, 4.2 GM, 0.5 WATT and 4.2 ONE WATT.

Advantages to the User

- Compact
- Simple to operate
- Can be controlled remotely
- Selectable voltages
- Low noise
- UL approved
- Long maintenance-free period of operation
- Variable cold head motor speed



Dimensional drawing for the COOLPAK 6000 HMD/6200 HMD

Technical Data

COOLPAK

	6000 HMD	6200 HMD
Mains voltage	50 Hz, 400 ± 10% 60 Hz, 460 ± 10%	50 Hz, 200 ± 10% 60 Hz, 200 - 230 ± 10%
	For all other Technical Data, see COOLPAK 6000 H and 6200 H	

Ordering Information

COOLPAK

	6000 HMD	6200 HMD
	Part No.	Part No.
Compressor type		
400 V/3-ph. 50 Hz or 460 V/3-ph. 60 Hz ± 10%	840000V6002	-
200 V/3-ph. 50 Hz or 200-230 V/3-ph. 60 Hz ± 10%	-	840000V6202
Flexible pressure line (for operating mechanically driven cold heads)		
6 m (21.0 ft) (High-pressure) FL6 HP-DN 20 (8f/8f)	840 210	840 210
6 m (21.0 ft) (Low-pressure) FL6 LP-DN 16 (8f/8f)	840 211	840 211
9 m (31.5 ft) (High-pressure) FL9 HP-DN 20 (8f/8f)	840 217	840 217
9 m (31.5 ft) (Low-pressure) FL9 LP-DN 16 (8f/8f)	840 218	840 218
20 m (75.0 ft) (High-pressure) FL20 HP-DN 16 (8f/8f)	840 230	840 230
20 m (75.0 ft) (Low-pressure) FL20 LP-DN 16 (8f/8f)	840 231	840 231
Connection cable for the cold heads COOLPOWER 10 MD, 150, 130, 4.2 GM, 0.5 WATT and 4.2 ONE WATT		
9.0 m (31.5 ft)	842 110	842 110
20.0 m (75.0 ft)	842 112	842 112
30.0 m (105.0 ft)	842 114	842 114
Power supply cable		
3.5 m (12.25 ft) CEE plug, 32 A/6h, 3-pol +N+PE	893 95	-
NEMA plug, L 16-20 P, 20 A/480 V, 3-pol +PE (AWG 12)	893 96	-
10 m (35.0 ft) with end splice (AWG 10)	-	840 111 ¹⁾
20 m (75.0 ft) with end splice (AWG 10)	-	840 112 ¹⁾
Accessories		
Water cooling discharge throttle	E 840000133	E 840000133

¹⁾ Also suitable for COOLPAK 4000(D)/6000(D)

General Accessories for Compressor Units COOLPAK

Technical Data	Length	Connections on both sides (inside thread)	
		High pressure line (HD)	Low pressure line (ND)
Flexlines ^{1), 2)} FL 4.5 (1/2", 1/2") FL 9.0 (1/2", 1/2")	4.5 m (15.75 ft) 9.0 m (31.50 ft)	1/2" 1/2"	1/2" 1/2"
Accessories for Flexlines	Adaptor Outside thread (m)	Adaptor Inside thread (f)	
Adaptor for flexlines AD (1/2" m, 3/4" f) AD (1/2" f, 3/4" m)	1/2" 3/4"	3/4" 1/2"	
	Connections Outside thread (m)	Connections Inside thread (f)	
Elbow 1/2" for flexlines Isolating piece 1/2" for flexlines	1/2" 1/2"	1/2" 1/2"	
	Connections on both sides Outside thread (m)		
Coupling 1/2" for interconnecting two 1/2" flexlines	1/2"		
	Gas Distributors required quantity	Gas Manifold - Connections At the compressor (inside thread)	At the cold head (outside thread)
Gas manifold (1 piece each) GD 2 (for dual operation) ²⁾ GD 4 (for up to quad operation) ²⁾	2 2	1/2" 1/2"	2 x 1/2" 4 x 1/2"
	Length		
EL 4.5 extension cable for linking cold head and compressor unit	4.5 m (15.75 ft)		

Ordering Information

General Accessories


	Part No.
Flexlines ^{1), 2)} FL 4.5 (1/2", 1/2") FL 9.0 (1/2", 1/2")	892 87 892 88
Adaptor AD (1/2" m, 3/4" f) AD (1/2" f, 3/4" m)	892 89 892 90
Elbow 1/2"	891 73
Coupling 1/2"	891 71
Gas manifold (1 piece each) GD 2 (for dual operation) ²⁾ GD 4 (for up to quad operation) ²⁾	840 253 (2x) 840 254 (2x)
EL 25 extension cable for linking cold head and compressor unit ²⁾	200 20 900
EL 4.5 extension cable for linking cold head and compressor unit ²⁾	893 74

All flexible pressure lines, adaptor pieces, bends, isolating pieces, line couplings and gas manifolds are equipped with self-sealing Aeroquip fittings and filled in the factory with high-purity helium gas (purity: 99.999%). The filling pressure is 16 bar

¹⁾ Minimum bending radius: 30 cm (11.81 in.)

²⁾ Only suited for pneumatically driven cold heads and cryo pumps

Refrigerator Cryostat based on the RDK 6-320



Basic unit RDK 6-320

The RDK 6-320 basic unit includes the COOLPOWER 5/100 T two-stage cold head. Its high refrigerating capacity at low temperatures permits experiments which previously could not be performed by relying on refrigerators and which required the use of liquid helium.

The RDK 6-320 basic unit is a complete system for measurements in the temperature range between 6 and 320 K.

The COOLPOWER 5/100 T cold head is augmented by:

- Silicon diode for measuring the temperatures at the second stage of the cold head
- Heater at the second stage of the cold head provided with overheating protection
- 11-way current feedthrough with matching external connector
- DN 25 KF pumpdown port
- DN 160 ISO-K vacuum flange

Advantages to the User

- Compact
- Very reliable
- Comprehensive range of accessories from one source
- For installation in any orientation
- Simple to operate
- Short cooldown time
- Cost-effective in long-term experiments since no liquid helium is required
- Simple and rapid servicing through the use of the standard COOLPOWER 5/100 T cold head with pneumatic drive system for the displacer

Typical Applications

- Cooling of samples and detectors
- Material research and testing
- Spectroscopic applications
- Matrix isolation spectroscopy with neon and argon

General Remarks on Refrigerator Cryostats

Isolating Vacuum

A two-stage rotary vacuum pump will normally be adequate to produce an isolating vacuum. However, this pump should be equipped on the suction side with an adsorption trap and a isolation valve.

If the application requires that the cold surfaces remain free of hydrocarbons, we recommend the use of our small turbomolecular pump system PT 50 (see Catalog Part "Vacuum Pump Systems" Section "High Vacuum Pump Systems").

Temperature Measurement

In order to avoid measurement errors due to thermal resistances, the temperature at the sample should preferably be measured by a second optional silicon diode which is installed as close to the sample as possible. If possible it should be maintained at the same temperature level as that of the probe.

Temperature Control

The temperature at the second stage of the cold head (or that of the probe) is controlled by heating against the cooling effect produced by the refrigerator (while the cold head is running).

Optical Refrigerator Cryostat based on the RDK 6-320




Optical refrigerator cryostat RDK 6-320


Upgraded as an optical cryostat (option) the RDK 6-320 is tailor-made for experiments involving temperatures down to about 7 K.

Supplied Equipment

- Basic unit RDK 6-320
- Temperature attenuation disk out of Pb Sn
- Sample holder out of Al 99.5
- Thermal radiation shield out of E-Cu
- Vacuum jacket out of aluminum / stainless steel
- Five exchangeable windows (four windows on the sides, one window in the longitudinal axis of the cryostat); two windows on the sides and the window in the longitudinal axis are made of SUPRASIL I, the two other windows are blanked off and are made of brass



Dimensional drawing for the optical refrigerator cryostat



Section through the window area

Technical Data

RDK 6-320

Temperature range		
2nd stage of the cold head	K	6 to 320
1st stage of the cold head	K	28 to 320
Silicon diode for temperature measurements at the 2nd stage of the cold head		built-in
Heater at the 2nd stage of the cold head		built-in
Heating power	W	50
Heating current	A	1
Heating voltage	V DC	50
Permissible ambient temperature	°C (°F)	+5 to +40 (+41 to +104)
He filling pressure at room temperature	bar	16
He connections		
Self-sealing screwed connections		
High pressure connection (outside thread)		1/2"
Low pressure connection (outside thread)		1/2"
Length of the connection cable to the compressor unit	m (ft)	4.5 (15.75) [included]
Weight	kg (lbs)	13 (28.7)

Ordering Information

RDK 6-320

	Part No.
Basic unit RDK 6-320	842 403
Optical cryostat consisting of RDK 6-320 and Expansion Kit ROK	842 404
Compressor unit	
COOLPAK 6000 H 400 V/50 Hz; 470 V/60 Hz	840000V6001
COOLPAK 6200 H 200 V/50 Hz; 200 V, 230 V/60 Hz	840000V6201
Power supply cable	see Ordering Information for the compressor units COOLPAK
Flexlines	
FL 4.5 (1/2", 1/2")	892 87
Temperature measurement at 2nd stage with low temperature controller MODEL 9700	842 400
Sensor cable, 3 m (10.5 ft) long	842 401

Accessories for Cryo Pumps / Cryogenics

Controllers and Monitoring Units for Cryo Pumps

Advantages to the User

- Interface to external system controller
- For easy integration with external system controllers
- For safe pumping of hydrogen

Typical Applications

- For automated operation of the COOLVAC cryo pumps of the ClassicLine

System Controller COOLVAC SC



System controller COOLVAC SC

The intelligent COOLVAC system controller SC automatically controls and monitors up to 30 COOLVAC pumps. Online monitoring, help functions and a service interface for easy diagnostic are just a few user friendly features. It can be installed as a “stand alone system” or remote controlled via an interface.

Design Features

- 1/4 19" rack module
- 3 height units (HU)
- Dimensions (W x H x D)
106 x 129 x 178 mm
(4.17 x 5.08 x 7.01)
- Operation through pushbuttons

Supplied equipment

- Network terminator (Part No. 400 000 114)
- Hardware interlock plug (Part No. 400 000 133)
- O modem adapter for connection to the PC

Technical Data

COOLVAC SC


Operating voltage	Supply through RS 485 C cable from COOLVAC PM
Dimensions (W x H x D) mm (in.)	106 x 129 x 178 (4.17 x 5.08 x 7.01) [1/4 19", 3 HU]

Ordering Information

COOLVAC SC

	Part No.
System controller COOLVAC SC	844 230
System controller COOLVAC SC with Profibus interface	844230V0004

Power Supply PS for up to Two Cryo Pumps



Power supply PS

The COOLVAC power supply PS provides the power for the cold head motor, the electrical heaters and the supplies voltage to the electronics for up to 2 COOLVAC pumps. Controlled via the system controller SC the PS turns the compressor unit on and off if required by the connected pumps.

The system controller COOLVAC SC (not included) will fit into the empty space.

Design Features

- 19" rack module
- 3 height units (HU)
- Dimensions (W x H x D)
483 x 135 x 320 mm
(19.02 x 5.31 x 12.60)

Supplied equipment

- Approximately 3 m (10.5 ft) long mains cord

Technical Data

PS for double connection

Power consumption, approx.	VA	900
Supply voltage, factory preset (optional 115 V AC is possible ¹⁾)	V AC	230 ± 10%, 1 phase
Output power	W	2 x 250
Rack mounting		Through 19" installation frame
Dimensions (W x H x D)	mm (in.)	483 x 135 x 320 (19.02 x 5.31 x 12.60) [3/4 19", 3 HU]
Weight	kg (lbs)	10 (22.1)

Ordering Information

PS for double connection

	Part No.
Power supply PS for up to 2 cryo pumps	844 135

¹⁾ Please contact Oerlikon Leybold Vacuum

Power supply PS for up to Three Cryo Pumps



Power supply PS

The COOLVAC power supply PS provides the power for the cold head motor, the electrical heaters and the supplies voltage to the electronics for up to 3 COOLVAC pumps. Controlled via the system controller SC the PS turns the compressor unit on and off if required by the connected pumps.

Design Features

- 19" rack module
- 4 height units (HU)
- Dimensions (W x H x D)
483 x 177 x 440 mm
(19.02 x 6.97 x 17.32)
- Single LED indicates correct direction of rotation for the rotating field

Supplied equipment

- 20 m (70 ft) long mains cord, fitted, without plug
- 19" mounting brackets for rack mounting

Technical Data

PS

for multiple connection

Nominal voltage (3 phase) factory default	V AC	3 x 200 + PE
switchable to	V AC	3 x 400 + PE 3 x 460 to 480 + PE
Voltage tolerance		± 10%
Frequency range	Hz	47 to 63
Fusing		Power switch
Ambient temperature range	°C (°F)	0 to +40 (+32 to +104)
Protection type	IP	20
Dimensions (W x H x D) [without handles]	mm (in.)	483 x 177 x 440 (19.02 x 6.97 x 17.32) [19", 4 HU]
Weight (including cord)	kg (lbs)	38.8 (85.65)


Ordering Information

PS

for multiple connection

	Part No.
Power supply PS for up to 3 cryo pumps	844 235


COOLVAC ClassicLine, Single System Configuration



Single System Configuration


COOLVAC ClassicLine, Dual System Configuration

Only for European mains voltages and for compressors suited for dual operation



Dual System Configuration

COOLVAC ClassicLine, Dual and Multiple System Configuration



Dual and Multiple System Configuration

Low Temperature Controller MODEL 9700



Low temperature controller MODEL 9700

Advantages to the User

- Microprocessor controlled PID controller
- Digital temperature readout in Kelvin
- Control by means of counter heating
- High control accuracy over the entire temperature range (1.5 to 450 K)
- Electric heating power up to 50 W
- Programmable heater power limit
- Generation of linear temperature ramps
- Up to 50 program steps are programmable
- Standard interface RS 232 C and IEEE-488
- Data from two sensors can be displayed
- Analogue temperature outputs for both channels
- Can be used in three operating modes
 - Manual
 - Program
 - External computer control

Typical Applications

- Temperature control at refrigerator cryostats

Technical Data

MODEL 9700

Mains connection, 50/60 Hz	V AC	85 to 240
Power consumption, max.	W	150
Entry of data		3 x 4 membrane key pad
Data memory		EPROM
Display		Two line, 20 digit LED digital display
Temperature measurement		
Sensors		2 x silicon diodes type D or 2 x silicon diodes with standard temperature resistance characteristics
Measurement current	µA	10
Measurement range	K	1.5 to 450
Measurement range of the silicon diode type D	K	1.4 to 325 K
Number of channels		2
Resolution		Simultaneous display of both channels
A/D converter resolution	bit	24
Switching outputs		2 relays (n.o. and n.c. contacts)
Temperature resolution	K	0.1
Temperature control		PID controller
Heating power, max.	W	50
Heating current, max.	A	1
Heating voltage, max.	V DC	0 to 50
Computer interface		RS 232 C and IEEE-488
Permissible ambient temperature °C (°F)		+10 to +30 (+50 to +86)
Mechanical design/cabinet		Table-top unit (8.5" x 3.5" x 12")
Dimensions (W x H x D) [high H without feet]	mm (in.)	215.9 x 88 x 304.8 (8.5 x 3.5 x 12.0)
Weight	kg (lbs)	2.3 (5)
Dimensions of the packaging (W x H x D)	mm (in.)	360 x 230 x 450 (14.17 x 9.06 x 17.72)
Weight (inc. packaging, approx.)	kg (lbs)	4.2 (9.3)
Length of mains cord	m (ft)	2.5 (8.75)

Ordering Information

MODEL 9700

	Part No.
Low temperature controller MODEL 9700	842 400
Sensor cable, 3 m (10.5 ft) long	842 401
Silicon diode type D with connection cable and miniature plugs	890 89

Low Temperature Measuring Instrument MODEL 211S



Low temperature measuring instrument MODEL 211S

Advantages to the User

- Supports one silicon diode
- 3-digit LED display
- Temperature readout between 1 and 450 Kelvin
- Two trigger thresholds
- RS 232 C interface

Typical Applications

- Temperature measurements on cryostats
- Temperature measurements on cryo pumps for monitoring their operation and to control pump systems

Technical Data

Measurement current	μA	10
Display		LED, 5-digits
Temperature range	K	1.4 to 475
Resolution		0.001 K from 1.4 to 99.9 K 0.01 K from 100 to 475 K
Accuracy		± 0.05 K from 1.5 to 99.9 K ± 0.05 K from 100 to 475 K
Power supply voltage		5 V DC at 1 A through the supplied 100-240 V AC power adaptor
Trigger thresholds		2
Switched output		2 relays (n.c. and n.o.) 30 V DC at 1 A
Analog output		
Voltage	V	0 to 10
Current	mA	4 to 20
RS 232 C interface		a) Temperature output b) External adjustment of switching thresholds
Admissible ambient temperature	$^{\circ}\text{C}$ ($^{\circ}\text{F}$)	+15 to +35 (+59 to +95)
Mechanical design/housing		Benchtop unit
Dimensions (W x H x D)	mm (in.)	96 x 48 x 166 (3.78 x 1.89 x 6.54)
Weight (including packaging), approx.	kg (lbs)	0.45 (1.0)

MODEL 211S


Ordering Information

MODEL 211S


	Part No.
Low temperature measuring instrument MODEL 211S	844 110
HV cable 2-way with plug, 10 m (35.0 ft) long ¹⁾	844 112
HV cable 4-way with plug, 10 m (35.0 ft) long ¹⁾	844 113
UHV cable 4-way with plug, 10 m (35.0 ft) long ¹⁾	844 114
Silicon diode, type D, with connecting cable and micro plugs - without current feedthrough	890 89
HV current feedthrough on a flange DN 25 KF, 2-way	200 19 256
UHV current feedthrough on a flange DN 16 CF, 4-way	500 217

¹⁾ For COOLPOWER and COOLVAC pumps

Temperature Sensor



Dimensional drawing for the silicon diode, type D



Standard characteristic of the silicon diode

In contrast to vapor pressure thermometers, electric temperature sensors can be used for continuous measurements within a wide range of temperatures.

Silicon diodes offer a negative temperature coefficient of resistance, i.e. their resistance drops as the temperature increases. The slope of the temperature/resistance characteristic and the absolute resistance are decisive regarding the suitability of these diodes. The slope determines the sensitivity of the sensor and a high electrical resistance permits accurate measurements while keeping the thermal load small (microwatts).

In systems which are degassed at high temperatures, silicon diodes can only be fitted after degassing has been completed.

The silicon diode type D matches the low temperature display unit and the low temperature control unit MODEL 9700.

Technical Data

Silicon Diode Type D


Temperature range	K	1.4 to 325
Temperature coefficient (dR/dT) qualitative		Negative in the entire temperature range
quantitative	Ω/K	Non-linear characteristic
Measurement current	μA	10
Bakeable to	$^{\circ}C$ ($^{\circ}F$)	+60 (+140)

Ordering Information

Silicon Diode Type D

	Part No.
Temperature sensor	890 89
Silicon diode with 4-way electrical feedthrough	200 20 694
Flange DN 16 ISO-KF	200 20 616

Safety Valve



Dimensional drawing for the safety valve

Typical Applications

- Protecting sealed vacuum systems like cryo pumps, cryostats, lifting devices, for example against internal overpressures
- Mandatory for systems which are separated when cold, as a means of protection against overpressures

Technical Data

Safety Valve

Responding pressure	mbar	150 ± 40, over-pressure
Flow at 140 mbar	l x h ⁻¹	500
Valve disk		Spring loaded, with O-ring seal
Leak rate in the closed state	mbar x l x s ⁻¹ (Torr x l x s ⁻¹)	< 1 x 10 ⁻⁸ (< 0.75 x 10 ⁻⁸)
Connection	DN	16 KF
Diameter	mm (in.)	32 (1.26)
Material		Steel 1.4305
Overall height	mm (in.)	28 (1.10)
Weight	kg (lbs)	0.3 (0.7)

Ordering Information

Safety Valve

	Part No.
Safety valve on DN 16 KF flange	890 39

Sales and Service

Germany

Oerlikon
Leybold Vacuum GmbH
Bonner Strasse 498
D-50968 Cologne
Phone: +49-(0)221-347 1234
Fax: +49-(0)221-347 1245
sales.vacuum@oerlikon.com
www.oerlikon.com

Oerlikon
Leybold Vacuum GmbH
Sales Area North/Northeast
Branch Office Berlin
Industriestrasse 10b
D-12099 Berlin
Phone: +49-(0)30-435 609 0
Fax: +49-(0)30-435 609 10
sales.vacuum.bn@oerlikon.com

Oerlikon
Leybold Vacuum GmbH
Sales Area South/Southwest
Branch Office Munich
Karl-Hammerschmidt-Strasse 34
D-85609 Aschheim-Dornach
Phone: +49-(0)89-357 33 9-10
Fax: +49-(0)89-357 33 9-33
sales.vacuum.mn@oerlikon.com
service.vacuum.mn@oerlikon.com

Oerlikon
Leybold Vacuum GmbH
Sales Area West & Benelux
Branch Office Cologne
Bonner Strasse 498
D-50968 Cologne
Phone: +49-(0)221-347 1270
Fax: +49-(0)221-347 1291
sales.vacuum.kn@oerlikon.com

Oerlikon
Leybold Vacuum GmbH
Service Competence Center
Emil-Hoffmann-Strasse 43
D-50996 Cologne-Suerth
Phone: +49-(0)221-347 1538
Fax: +49-(0)221-347 1945
service.vacuum.kn@oerlikon.com

Oerlikon
Leybold Vacuum GmbH
Mobil Customer Service
Emil-Hoffmann-Strasse 43
D-50996 Cologne-Suerth
Phone: +49-(0)221-347 2001
Fax: +49-(0)221-347 1944
service.vacuum.kn@oerlikon.com

Oerlikon
Leybold Vacuum
Dresden GmbH
Service Competence Center
Zur Wetterwarte 50, Haus 304
D-01109 Dresden
Service:
Phone: +49-(0)351-88 55 00
Fax: +49-(0)351-88 55 041
info.vacuum.dr@oerlikon.com

Europe

Belgium
Oerlikon
Leybold Vacuum Nederland B.V.
Belgisch bijkantoor
Leuvensesteenweg 542-9A
B-1930 Zaventem
Sales:
Phone: +32-2-711 00 83
Fax: +32-2-720 83 38
sales.vacuum.zv@oerlikon.com
Service:
Phone: +32-2-711 00 82
Fax: +32-2-720 83 38
service.vacuum.zv@oerlikon.com

France
Oerlikon
Leybold Vacuum France S.A.S.
7, Avenue du Québec
Z.A. de Courtaboeuf
F-91140 Villebon-sur-yvette
Sales and Service:
Phone: +33-1-69 82 48 00
Fax: +33-1-69 07 57 38
info.vacuum.ctb@oerlikon.com
sales.vacuum.ctb@oerlikon.com

Oerlikon
Leybold Vacuum France S.A.S.
Valence Factory
640, Rue A. Bergès
B.P. 107
F-26501 Bourg-lès-Valence Cedex
Service:
Phone: +33-4-75 82 33 00
Fax: +33-4-75 82 92 69
marketing.vacuum.vc@oerlikon.com

Great Britain

Oerlikon
Leybold Vacuum UK LTD.
Silverglade Business Park
Leatherhead Road Unit 2
KT9 2QL Chessington, Surrey
(London)
Sales:
Phone: +44-13-7273 7300
Fax: +44-13-7273 7301
sales.vacuum.ln@oerlikon.com
Service:
Phone: +44-20-8971 7030
Fax: +44-20-8971 7003
service.vacuum.ln@oerlikon.com

Italy

Oerlikon
Leybold Vacuum Italia S.r.l.
Via Trasimeno 8
I-20128 Milano
Sales:
Phone: +39-02-27 22 31
Fax: +39-02-27 20 96 41
sales.vacuum.mi@oerlikon.com
Service:
Phone: +39-02-27 22 31
Fax: +39-02-27 22 32 17
service.vacuum.mi@oerlikon.com

Netherlands

Oerlikon
Leybold Vacuum Nederland B.V.
Proostwetering 24N
NL-3543 AE Utrecht
Sales and Service:
Phone: +31-(30) 242 6330
Fax: +31-(30) 242 6331
sales.vacuum.ut@oerlikon.com
service.vacuum.ut@oerlikon.com

Spain

Oerlikon
Leybold Vacuum Spain, S.A.
C/ Huelva 7
E-08940 Cornellà de Llobregat
(Barcelona)
Sales:
Phone: +34-93-666 43 11
Fax: +34-93-666 43 70
sales.vacuum.ba@oerlikon.com
Service:
Phone: +34-93-666 46 16
Fax: +34-93-685 43 70
service.vacuum.ba@oerlikon.com

Switzerland

Oerlikon
Leybold Vacuum Schweiz AG
Leutschenbachstrasse 55
CH-8050 Zürich
Sales:
Phone: +41-44-308 40 50
Fax: +41-44-302 43 73
sales.vacuum.zh@oerlikon.com
Service:
Phone: +41-44-308 40 62
Fax: +41-44-308 40 60
service.vacuum.zh@oerlikon.com

America

Oerlikon
Leybold Vacuum USA Inc.
5700 Mellon Road
USA-Export, PA 15632
Phone: +1-724-327-5700
Fax: +1-724-325-3577
info.vacuum.ex@oerlikon.com
Sales:
Phone: +1-724-327-5700
Fax: +1-724-333-1217
Service:
Phone: +1-724-327-5700
Fax: +1-724-325-3577

Asia

P.R. China

Oerlikon
Leybold Vacuum (Tianjin)
International Trade Co. Ltd.
Beichen Economic
Development Area (BEDA),
No.8 Western Shuangchen Road
Tianjin 300400
China
Sales and Service:
Phone: +86-22-2697 0808
Fax: +86-22-2697 4061
Fax: +86-22-2697 2017
info.vacuum.tj@oerlikon.com
sales.vacuum.tj@oerlikon.com
service.vacuum.tj@oerlikon.com

Oerlikon
Leybold Vacuum
(Tianjin) Co. Ltd.
Beichen Economic
Development Area (BEDA),
No.8 Western Shuangchen Road
Tianjin 300400
China
Sales and Service:
Phone: +86-22-2697 0808
Fax: +86-22-2697 4061
info.vacuum.tj@oerlikon.com
sales.vacuum.tj@oerlikon.com
service.vacuum.tj@oerlikon.com

Oerlikon
Leybold Vacuum GmbH
Bonner Strasse 498
D-50968 Cologne
Phone: +49-(0)221-347 0
Fax: +49-(0)221-347 1250
info.vacuum@oerlikon.com

P.R. China

Oerlikon
Leybold Vacuum (Tianjin)
International Trade Co. Ltd.
Shanghai Branch:
No. 10 Building
816 Ronghua Road
Songjiang District
Shanghai 201611
China
Sales and Service:
Phone: +86-21-5288-5863
Fax: +86-21-5288-5836
info.vacuum.sh@oerlikon.com
sales.vacuum.sh@oerlikon.com
service.vacuum.sh@oerlikon.com

Oerlikon
Leybold Vacuum (Tianjin)
International Trade Co. Ltd.
Guangzhou Office and
Service Center
1st F, Main Building
Science City Plaza,
No.111 Science Revenue,
Guangzhou Science City
(GZSC) 510663, Guangzhou,
China
Sales:
Phone: +86-20-223 23 980
Fax: +86-20-223 23 990
info.vacuum.gz@oerlikon.com
sales.vacuum.gz@oerlikon.com
service.vacuum.gz@oerlikon.com

Oerlikon
Leybold Vacuum (Tianjin)
International Trade Co. Ltd.
Beijing Branch:
1-908, Beijing Landmark Towers
8 North Dongsanhuan Road
Beijing 100004
China
Sales:
Phone: +86-10-6590-7622
Fax: +86-10-6590-7607
sales.vacuum.bj@oerlikon.com
service.vacuum.bj@oerlikon.com

India

Oerlikon
Leybold Vacuum India Pvt Ltd.
EL 22, J-Block
MIDC Bhosari
Pune 411026
India
Sales and Service:
Phone: +91-20-3061 6000
Fax: +91-20-2712 1571
sales.vacuum.pu@oerlikon.com
service.vacuum.pu@oerlikon.com

Japan

Oerlikon
Leybold Vacuum
Japan Co., Ltd.
Headquarter
23-3, Shin-Yokohama
3-chome
Tobu A.K. Bldg. 4th Floor
Kohoku-ku
Yokohama-shi 222-0033
Sales:
Phone: +81-45-471-3330
Fax: +81-45-471-3323
info.vacuum.yh@oerlikon.com
sales.vacuum.yh@oerlikon.com

Oerlikon
Leybold Vacuum
Japan Co., Ltd.
Osaka Sales Office
3F, Shin-Osaka Terasaki
No.3 Bldg.
1-5-28 Nishi-Miyahara
Yodogawa-ku, Osaka-shi
Osaka 532-0004
Phone: +81-6-6399-6271
Fax: +81-6-6399-6273
info.vacuum.os@oerlikon.com
sales.vacuum.os@oerlikon.com

Japan

Oerlikon
Leybold Vacuum
Japan Co., Ltd.
Tsukuba Technical Service Center
1959, Kamiyokoba
Tsukuba, Ibaraki
305-0854 Japan
Service:
Phone: +81-29 839 5480
Fax: +81-29 839 5485
service.vacuum.iik@oerlikon.com

Malaysia

Oerlikon Leybold Malaysia
Oerlikon Leybold Vacuum
Singapore Pte. Ltd.
No. 1 Jalan Hi-Tech 2/6
Kulim Hi-Tech Park
Kulim, Kedah Darul
Aman 09000
Malaysia
Sales and Service:
Phone: +604 4020 222
Fax: +604 4020 221
info.vacuum.ku@oerlikon.com
sales.vacuum.ku@oerlikon.com
service.vacuum.ku@oerlikon.com

South Korea

Oerlikon
Leybold Vacuum Korea Ltd.
3F, Jellzone 2 Tower
Jeongja-dong 159-4
Bundang-gu Sungnam-si
Gyeonggi-do
Bundang 463-384, Korea
Sales:
Phone: +82-31 785 1367
Fax: +82-31 785 1359
sales.vacuum.bd@oerlikon.com

Service:
623-7, Upsung-Dong
Cheonan-Si
Chungcheongnam-Do
Korea 330-290
Phone: +82-41 589 3035
Fax: +82-41 588 0166
service.vacuum.cn@oerlikon.com

Singapore

Oerlikon
Leybold Vacuum
Singapore Pte. Ltd.
8 Commonwealth Lane
#01-01, Singapore 149555
Sales and Service:
Phone: +65-6303 7030
Fax: +65-6773 0039
sales.vacuum.sg@oerlikon.com
service.vacuum.sg@oerlikon.com

Taiwan

Oerlikon
Leybold Vacuum Taiwan Ltd.
No 416-1, Sec. 3
Chunghsin Road., Chutung
Hsinchu County 310
Taiwan, R.O.C.
Sales and Service:
Phone: +886-3-500 1688
Fax: +886-3-583 3999
sales.vacuum.hc@oerlikon.com
service.vacuum.hc@oerlikon.com