

GENERAL CONSTRUCTION TOOLS

2021 PRODUCT LINE CARD



RAMMERS		
MAKE	MODEL	SPECS
Husqvarna	LT6005	4-stroke, Honda GXR120, 11" shoe
MQ Mikasa	MTX60HD	4-stroke, Honda GX100 gas engine, 141 lbs., 2.8 hp, 10.4" shoe, 3,064 force/blow
MQ Mikasa	MTX70HD	4-stroke, Honda GX100 gas engine, 165 lbs., 2.8 hp, 11.2" shoe, 3,350 force/blow



VIBRATORY PLATES		
MAKE	MODEL	SPECS
MQ Mikasa	MVC82VHW	Honda GX160 gas engine, 181 lbs., 17.7" x 22.4" plate, 3,080 force, water tank
MQ Mikasa	MVC88VTHW	Honda GX160 gas engine, 229 lbs., 19.7" x 20.7" plate, 3,372 force, water tank
Husqvarna	LF100UA	Honda GX160, 20" plate



REVERSIBLE VIBRATORY PLATES		
MAKE	MODEL	SPECS
MQ Mikasa	MVH208GH	Honda GX-240 gas engine, 463 lbs., 20" x 20" plate, 8,318 centrifugal force
MQ Mikasa	MVH508DZ	Hatz 1D81S diesel engine, 1,182 lbs., 26" x 35" plate, 14,613 centrifugal force



PUMPS		
MAKE	MODEL	SPECS
Multiquip	QP2TH	2" Trash Pump, 96 lbs., Honda GX160 gas engine, 4.8 hp, 211 GPM
Multiquip	QP3TH	3" Trash Pump, 163 lbs., Honda GX240 gas engine, 7.1 hp, 396 GPM
Multiquip	QP4TH	4" Trash Pump, 216 lbs., Honda GX340 gas engine, 9.5 hp, 555 GPM
Multiquip	QP4TK	4" Trash Pump, 265 lbs., Kubota Diesel engine, 9.9 hp, 526 GPM
Multiquip	ST2037	2" Discharge, 115V, 1.0 hp, 73 GPM
Multiquip	ST2047	2" Discharge, 115V, 1.0 hp, 87 GPM



PUMP HOSE		
TYPE	MODEL	SPECS
Intake	2" / 25 feet	With strainer & camlock fitting (hose with camlock - \$100 / strainer - \$28)
Intake	3" / 25 feet	With strainer & camlock fitting (hose with camlock - \$300 / strainer - \$33)
Intake	4" / 25 feet	With strainer & camlock fitting (hose with camlock - \$500 / strainer - \$45)
Intake	6" / 20 feet	With strainer & camlock fitting (hose with camlock - \$875 / strainer - \$80)
Discharge	2" / 50 feet	With camlock quick couplers
Discharge	3" / 50 feet	With camlock quick couplers
Discharge	4" / 50 feet	With camlock quick couplers
Discharge	6" / 50 feet	With camlock quick couplers



CUT-OFF SAWS		
MAKE	MODEL	SPECS
Husqvarna	K770	Cutting depth 5", blade diameter 14", output power 5 hp
Husqvarna	K970	Cylinder displacement 93.6 cm, blade diameter max 14", output power 6.5 hp



FLAT SAWS

MAKE	MODEL	SPECS
Husqvarna	FS309	8 hp, 117 lbs.
Husqvarna	FS400	11 hp, 219 lbs.
Husqvarna	FS413	11 hp, 306 lbs.
Husqvarna	FS513	11 hp, 424 - 502 lbs.
Husqvarna	FS520	20.8 hp, 424 lbs.
Husqvarna	FS524	20.8 hp, 502 lbs.
Husqvarna	FS5000D	47.6 hp, 1,700 lbs.
Husqvarna	FS7000D	74.3 hp, 2,275 lbs.

SOFF-CUT SAWS – We stock and offer a full line of all demo saw blades, core bits and Soff-Cut blades.



CONCRETE VIBRATORS – Price on request. Wacker and Multiquip available.



POWER TROWELS (WALK-BEHIND)



POWER TROWELS (RIDE-ON)



CONCRETE HAND-HELD POWER SCREEDS – Price on request. PT, Hand Held, Ride-on, Mixers available



CONCRETE & MORTAR MIXERS

LIGHT TOWERS

MAKE	MODEL	SPECS
Allmand	Night-Lite Pro II	V-Series, 4x1250 watt lamps, 7.5 kW single-phase 120/240V
Allmand	Mine Spec I	V-Series, 4 - LED lights, 8kw single-phase 12/240V
MQ	GB8LED	Glo Bug, 13.2 max heigh, 48 lbs., 800 w/amp



TRENCH ROLLERS

MAKE	MODEL	SPECS
MQ Rammax	RX1575-CI33	Walk-behind, articulating, Lombardini diesel engine, 3,373 lbs., 33" dbl drum pad, 15,543 centrifugal force
Husqvarna	LP9505	Walk-behind, articulating, Kubota D1105 engine, 3,693 lbs., 33.5" drum width, 16,186 centrifugal force



AIR COMPRESSORS – *Offering full range of tools.

MAKE	MODEL	SPECS
Sullivan Palatek	D185PIZ4	



DUMP TRUCKS		
MAKE	MODEL	SPECS
Valew	6 yd dump	10' standard dump body, 5 to 7 yd
Valew	10 yd dump	15' standard dump body, 10 yd

WATER TRUCKS		
MAKE	MODEL	SPECS
Valew	2,000 gallon	2,000 gallon tank, standard or auto
Valew	4,000 gallon	4,000 gallon tank, standard or auto
Custom Truck	4,000 gallon	Freightliner 4,000 gallon tank, auto

WATER TRAILER		
MAKE	MODEL	SPECS
MQ	WT5C	Dry weight 1,428 lbs., Multiquip 2" pump (158 gpm), Honda GX-120 Engine



WATER TOWER		
MAKE	MODEL	SPECS
Valew	12,000 gallon	12,000 gallon water tower



BROOMS		
MAKE	MODEL	SPECS
Broce	BW260	(3 wheeler) OROPS / 8' Broom / Towable
Broce	CR350	(4 wheel) Cab / AC / 8' Broom / Water Kit



TRAIL KING TRAILERS		
MAKE	MODEL	SPECS
Trail King	TKT16U	(Wheeler Spec) 16,000 lbs capacity, 16' tilt, 4' stationary, Electric Brakes
Trail King	TK24LP	24,000 lbs capacity, 24' deck (19' flat with 5' beavertail), Air Brakes, Ramp
Trail King	TKT24	24,000 lbs capacity, 24' deck, 8' 6" wide, tilt deck
Trail King	*TK40LP	40,000 lbs capacity, 26' deck (21' flat with 5' beavertail), Air Brakes, 5' Ramp
Trail King	*TKT50	(Wheeler Spec) 50,000 lbs. capacity, 24' tilt, 4' stationary, Air Brakes
Trail King	*TK80SA	80,000 lbs. capacity, 48' Sliding Axle, Air Brakes, 20,000 lbs. winch
Trail King	*TK110SA	110,000 lbs. capacity, 50' Sliding Axle, Air Brakes
Trail King	*TK110HDG	(Wheeler Spec) 110,000 lbs. capacity, 24' deck 4S2M, hyd. Detatch, Air Brakes
Trail King	*TK120HDG	(Wheeler Spec) 120,000 lbs. capacity, 26' deck No ABS, hyd. Detatch, Air Brakes, 3+1 configuration
Trail King	*TK40SSD	Side Dump Train, Dolly
Trail King	*TKBD	Belly Dump Train, Dolly

*Models subject to 12% Federal Excise Tax. For more information, please contact: Glen Scooter Barney 801-440-8129



THUNDER CREEK EQUIPMENT		
MAKE	MODEL	SPECS
Thunder Creek	MTT460	4 tanks, 460 gal. total, 10 guage, dual 5,000 lbs. axle, 6-bolt hubs, 13' x 7' x 6', 3,426 lbs / 10,000 lbs.
Thunder Creek	MTT690	6 tanks, 690 gal. total, 10 guage, dual 6,000 lbs. axle, 8-bolt hubs, 15' x 7' x 6', 4,054 lbs / 12,000 lbs.
Thunder Creek	MTT920	8 tanks, 690 gal. total, 10 guage, dual 7,000 lbs. axle, 8-bolt hubs, 17' x 7' x 6', 4,682 lbs / 14,000 lbs.
Thunder Creek	SLT440	Up to 8, 25, 55 or 110 gal. tanks, 440 gal. total, Dual 7,000 lbs., 8 bolt hubs, 20'1" x 6'9" x 5'9" / 6,800 lbs.

TRENCH BOXES		
MAKE	SIZE	SPECS
Pro-Tec	8' x 12'	8" Tall x 12' Long, Foam Filled, 5,864 lbs.
Pro-Tec	4' x 12'	4' Tall x 12' Long, Foam Filled, 3,749 lbs.
Pro-Tec	8' x 16'	8' Tall x 16' Long, Foam Filled; 7,328 lbs.
Pro-Tec	4' x 16'	4' Tall x 16' Long, Foam Filled; 4,613 lbs.
Pro-Tec	8' x 20'	8' Tall X 20' Long, Foam Filled; 8,822 lbs.
Pro-Tec	4' x 20'	4' Tall x 20' Long, Foam Filled; 5,447 lbs.
Pro-Tec	8' x 24'	8' Tall x 24' Long, Foam Filled; 10,486 lbs.
Pro-Tec	4' x 24'	4' Tall x 24' Long, Foam Filled; 6,321 lbs.

Stacking pins \$55 each. Extra pins & keepers \$60 each.

TRENCH BOX SPREADERS		
MAKE	SIZE	SPECS
RhinoBilt	36"	Includes 1 set of 4 pins & keepers, 650 lbs.
RhinoBilt	42"	Includes 1 set of 4 pins & keepers, 740 lbs.
RhinoBilt	48"	Includes 1 set of 4 pins & keepers, 820 lbs.
RhinoBilt	54"	Includes 1 set of 4 pins & keepers, 915 lbs.
RhinoBilt	60"	Includes 1 set of 4 pins & keepers, 1,010 lbs.
RhinoBilt	72"	Includes 1 set of 4 pins & keepers, 1,170 lbs.

MANHOLE BOXES		
MAKE	SIZE	SPECS
Pro-Tec	4' x 8'	4" Double Wall, Foam Filled, 3,260 lbs.
Pro-Tec	4' x 10'	4" Double Wall, Foam Filled, 3,760 lbs.
Pro-Tec	8' x 8'	4" Double Wall, Foam Filled, 5,070 lbs.
Pro-Tec	8' x 10'	4" Double Wall, Foam Filled, 5,970 lbs.

Note: Manhole shields require 5" diameter spreaders. For width of manhole shield, add 4' to spreader size due to 2' warp-around ends. Example: 36" spreaders + 4' (wrap around ends) = 7' box width.

MANHOLE SPREADERS		
MAKE	SIZE	SPECS
Pro-Tec	48"	Includes 1 set of 4 pins & keepers, 390 lbs.
Pro-Tec	72"	Includes 1 set of 4 pins & keepers, 560 lbs.

ALUMINUM BOXES		
MAKE	SIZE	SPECS
Pro-Tec	6' x 6'	2.75" Sidewall, 690 lbs.
Pro-Tec	8' x 10'	2.75" Sidewall, 1,360 lbs.
Pro-Tec	8' x 12'	2.75" Sidewall, 1,590 lbs.

ALUMINUM SPREADERS		
MAKE	SIZE	SPECS
Pro-Tec	34" to 54"	Adjustable Spreader Sets (Set of 4), 183 lbs.
Pro-Tec	42" to 66"	Adjustable Spreader Sets (Set of 4), 223 lbs.

TRENCH PLATES

MAKE	SIZE	SPECS
RhinoBilt	5' x 10'	1" thick
RhinoBilt	5' x 12'	1" thick
RhinoBilt	8' x 12'	1" thick
RhinoBilt	8' x 16'	1" thick
RhinoBilt	8' x 20'	1" thick

MATERIAL SEPARATORS & SCREENS

MAKE	SIZE	SPECS
RhinoBilt	SG12-6	Built-In 6" Minus Screen
RhinoBilt	2"	Laser-cut screen, 1" W x 2" L
RhinoBilt	3"	Laser-cut screen, 2" W x 3" L
RhinoBilt	4"	Laser-cut screen, 3" W x 4" L
RhinoBilt	5"	Laser-cut screen, 4" W x 5" L

HEAVY-DUTY GRAVEL BOXES

MAKE	SIZE
RhinoBilt	5.5 cubic yd.
RhinoBilt	7.5 cubic yd.
RhinoBilt	9 cubic yd.
RhinoBilt	12 cubic yd. (7' Wide)