Hazard Communication



Introduction


- About 32 million workers work with and are potentially exposed to one or more chemical hazards
- There are approximately 650,000 existing chemical products, and hundreds of new ones being introduced annually
- Chemical exposure may cause or contribute to many serious health effects such as heart ailments, central nervous system damage, kidney and lung damage, sterility, cancer, burns, and rashes
- Some chemicals may also be safety hazards and have the potential to cause fires and explosions and other serious accidents


Purpose of OSHA's Hazard Communication Standard

To ensure that employers and employees know about work hazards and how to protect themselves so that the incidence of illnesses and injuries due to hazardous chemicals is reduced.

Hazard Communication Program

Program





Who is covered?

OSHA's Hazard Communication (HazCom) standard applies to general industry, shipyard, marine terminals, longshoring, and construction employment and covers chemical manufacturers, importers, employers, and employees exposed to chemical hazards.

Employer Responsibilities

- Identify and list hazardous chemicals in their workplaces
- Obtain Material Safety Data Sheets (MSDSs) and labels for each hazardous chemical, if not provided by the manufacturer, importer, or distributor
- Implement a written HazCom program, including labels, MSDSs, and employee training
- Communicate hazard information to employees through labels, MSDSs, and formal training programs

How can workplace hazards be minimized?

- The first step in minimizing workplace hazards is to perform a thorough hazard assessment
- Employers can rely on the evaluations performed by the manufacturers or importers to establish the hazards of the chemicals they use
 - This information is obtained from MSDSs and labels

Why is a written program required?

- Ensures that all employers receive the information they need to inform and train their employees
- Provides necessary hazard information to employees



Written HazCom Program Requirements

- Describes container labeling, MSDSs, and employee training for each workplace
- List of the hazardous chemicals
- Make information regarding hazards and protective measures available to other employers onsite

How must chemicals be labeled?

Each container of hazardous chemicals entering the workplace must be labeled or marked with:

- Identity of the chemical
- Appropriate hazard warnings
- Name and address of the responsible party



Container Labeling in the Workplace

- The hazard warning can be any type of message, picture, or symbol that provides information on the hazards of the chemical(s) and the targeted organs affected, if applicable
- Labels must be legible, in English (plus other languages, if desired), and prominently displayed



Material Safety Data Sheets

Prepared by the chemical manufacturer or importer and describe:

- Physical hazards, such as fire and explosion
- Health hazards, such as signs of exposure
- Routes of exposure
- Precautions for safe handling and use
- Emergency and first-aid procedures
- Control measures

Material Safety Data Sheets (cont'd)

- Must be in English and include information regarding the specific chemical identity and common names
- Must provide information about the:
 - Physical and chemical characteristics
 - Health effects
 - Exposure limits
 - Carcinogenicity (cancer-causing)
 - Identification (name, address, and telephone number) of the organization responsible for preparing the sheet
- Must be readily accessible to employees in their work area

Material Safety Data Sheets (cont'd)

- MSDSs have no prescribed format
- If no MSDS has been received for a hazardous chemical, employer must contact the supplier, manufacturer, or importer to obtain one and maintain a record of the contact

Material Safety Data Sheet May be used to comply with DSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be					<i>\(\lambda\)</i>
consulted for specific requirements.		OMB No. 1218			
ENTITY (As Used on Label and List)		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that:			
Section I					
Manufacturer's Name		Emergency Telep	phone Number		
Address (Number, Street, City, State, and ZIP Code)		Telephone Number for Information			
		Date Prepared			
		Signature of Pre	parer (optional)		
Section II Hazardous Ingredients/Identi	ity Information				
Hazardous Components (Specific Chemical Identity; Co	ommon Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (option
Section III — Physical/Chemical Character	ristics				
Section III — Physical/Chemical Character Boling Point	ristics	Specific Gravity	(H ₂ O = 1)		
	ristics	Specific Gravity Melting Point	(H ₂ O = 1)		
Boiling Point	ristics	Melting Point Evaporation Rat	0		
Bolling Point Vapor Pressure (mm Hg.) Vapor Density (AIR = 1)	ristics	Melting Point	0		
Boiling Point Vapor Pressure (mm Hg.)	ristics	Melting Point Evaporation Rat	0		
Bolling Point Vapor Pressure (mm Hg.) Vapor Density (AIR = 1)	ristics	Melting Point Evaporation Rat	0		
Bolling Point Vapor Pressure (mm Hig.) Vapor Density (AIR = 1) Solubility in Water		Melting Point Evaporation Rat	0		
Boiling Point Vapor Pressure (mm Hg.) Vapor Density (AR = 1) Solubility in Water Appearance and Odor		Melting Point Evaporation Rat	9 1)	l LEL	UEL
Boiling Point Vapor Pressure (mm Hg.) Vapor Density (AIR = 1) Solubility in Water Appearance and Odor Section IV — Fire and Explosion Hazard I		Metting Point Evaporation Rat (Butyl Acetate =	9 1)	LEL	UEL
Boiling Point Vapor Pressure (mm Hg.) Vapor Denshy (AIR = 1) Solubility in Water Appearance and Odor Section IV — Fire and Explosion Hazard I Flash Point (Method Used)		Metting Point Evaporation Rat (Butyl Acetate =	9 1)	LEL	UEL
Boiling Point Vapor Pressure (mm Hg.) Vapor Density (AR = 1) Solubility in Water Appearance and Odor Section IV — Fire and Explosion Hazard I Flash Point (Method Used) Entinguishing Media		Metting Point Evaporation Rat (Butyl Acetate =	9 1)	LEL	UEL.
Boiling Point Vapor Pressure (mm Hg.) Vapor Density (AR = 1) Solubility in Water Appearance and Odor Section IV — Fire and Explosion Hazard I Flash Point (Method Used) Entinguishing Media		Metting Point Evaporation Rat (Butyl Acetate =	9 1)	LEL	UEL.
Bolling Point Vapor Pressure (mm Hg.) Vapor Density (ARR = 1) Solubility in Water Appearance and Odor Section IV — Fire and Explosion Hazard I Flash Point (Method Used) Estinguishing Media Special Fire Fighting Procedures		Metting Point Evaporation Rat (Butyl Acetate =	9 1)	LEL	UEL

Training

Training is required for employees who are exposed to hazardous chemicals in their work area:

- ★ At the time of initial assignment
- Whenever a new hazard is introduced into their work area



What training is needed to protect workers?

- Explanation of the HazCom program, including information on labels, MSDSs, and how to obtain and use available hazard information
- Hazards of chemicals
- Protective measures such as engineering controls, work practices, and the use of PPE
- How to detect the presence or release of a hazardous chemical (using monitoring devices, observation, or smell)

What information must be provided to workers?

Employees must be informed of:

- The HazCom standard and its requirements
- Operations in their work areas where hazardous chemicals are present
- Location and availability of the written hazard evaluation procedures, communications program, lists of hazardous chemicals, and the required MSDSs

Summary

- OSHA's Hazard Communication Standard is based on a simple concept - that employees have both a need and a right to know the hazards and identities of the chemicals they are exposed to when working
- Employees also need to know what protective measures are available to prevent adverse effects from occurring