



- 3-Point Chinstrap with 150N Break-Off Anchors.
- Optional: Logo
- Conforms to: DME, EN397, ESKOM WFH Work Group time/date stamp.
- CATIV 600 V safety rating
- · Colors Available: Red/White/Blue/Green/Yellow
- Code: FHLXX (add color)



# **Helmet Sunflap FHFLAP**

- Fits over peak of Helmet.
- Water Resistant.
- Lightweight and compact.
- Available Colors: Orange/Navy/Lime
- Code: FHFLAPXX (add color)



# Safety Spectacle FSS

- Stylish state of the art safety spectacle with indigo blue polycarbonate frames.
- Conforms to ANSI Z87.1-2010.
- Single piece clear Polycarbonate lens with a 9-based curve for maximum peripheral vision.
- Unparalleled lens strength and impact resistance.
- A patented, soft, pivoting universal-fit nose bridge.
- Lightweight 22grams.
- Smoke lens protected by exclusive coatings antiscratch, anti-static and anti-UV 99.9%.
- Code: FSS



# Safety Goggle FSG

- Panoramic lens shape allows 180 Deg lateral vision.
- Medium energy impact (B) 120m/s.
- Integrated, indirect ventilation allows air movement directly across lens.
- Fits comfortably over most spectacles.
- Simple lens replacement
- High quality, easy adjustable headband.
- Conforms to EN166-349NB
- Code: FSG







# Respirator mask without valve FRM

- The exhalation valve offers lower breathing resistance for easier breathing which increases workers acceptance.
- Activated carbon offers the additional protection against organic gas at nuisance levels.
- A low profile mask offers a better fit with glasses and goggle.
- A soft inner lining offers more comfort and less irritation.
- NRCS AZ2011/43
- Code: FRM

# **Hearing Protector FEP**

- The ergonomic design of the band keeps the pads suspended so they don't become contaminated when set down.
- It has softly styled foam pads shaped for supra-aural protection that fit easily inside the ear canal opening.
- Replacement pads
- Reusable
- Code: FEP

#### Conti Suite Flame & Acid Resistant FCS

- A flame retardant and coated acid resistant fabric
- · Reflective tape for increased visibility
- The natural fibres add comfort and breathability
- Protection in the event of a Flash Fire, Accidental Chemical Spillage, Petro Chemical flash fire protection potential.
- 100% Cotton 300/310gsm fabric.
- YKK concealed metal zip on jackets and pants.
- Fully triple stitched shoulders, arm holes, side seams, in-leg & back rise.
- 50mm silver flame retardant double needle stitched reflective tape on arms & legs.
- Elasticated cuffs and side slits on jacket.
- Mitred laid on jacket pockets, mitred breast pocket with flap, mitred hip pocket and tool pocket on pants.









• Sizes Available: Small - 3XL

• Code: FCSXX (add size)

#### **Reflective Vest FPRV**

- Anti Static & Flame Retardant vest made with 100% Polyester fluorescent yellow open weave fabric with 50mm silver Flame Retardant tape which is 100% cotton woven fabric with microglass bead coating, 520g/m2.
- The reflective material is compliant with ANSI/ISEA 107-1999 retroflective material specifications.
- Garments are available which performance meet the EN 471 requirements (European Norm for High Visibility Warning Clothing).

• Tape: EN ISO 20471:2013 & EN 469:2005+A1+AC • Fabric: ISO 6330:2012, EN ISO 14116:2008

• Sizes Available: Small - 3XL

• Code: FPRVXX (add size)



## **Hand Protection Ninja FHN**

- Excellent general purpose handling glove that provides good abrasion and tear resistance.
- Can be utilised in the agriculture, recycling, shipping and durable goods industries
- 15 Gauge Nylon shell with ultra light natural Rubber Latex coating.
- High density crinkle coating provides powerful grip and superb flexibility.
- Excellent dexterity
- Blue Ninja Lite Light Duty
- Black MaxiFLEX Medium Duty
- Red Ninja Flex Heavy Duty
- Code: FHNXX (add color)





### **Hand Protection Mechanical Gloves FHC**

- Candy-Striped Reinforced Leather Glove.
- Excellent general purpose handling glove that provides good abrasion and tear resistance.
- Cow hide Leather reinforced palm glove with striped canvas backing .
- Abrasion /Cut /Puncture suitable for general application.
- According to EN 388-2122 and EN 420 standards.
- Glove leather Candy Srtipe Brown or Grey
- Code: FHCXX (add color)





#### **Hand Protection Mechanical Gloves FHP**

- Excellent general purpose handling glove that provides good abrasion and tear resistance.
- Can be utilised in the agriculture, recycling, shipping and durable goods industries
- Excellent dexterity
- Abrasion EN Level 4 Cut EN Level 2 Tear EN Level 3 Puncture EN Level 3
- According to EN 388-2122 and EN 420 standards.
- Glove leather Nappa Brown or Grey
- Code: FHPXX (add color)



### Storage Bag SG-35 / SG-36

- This accessory is made from water proof PVC canvas, with a reinforced edge, equipped with a clasp and loop so that it can be fixed to a belt
- The bag is ideal for carrying gloves during work on site
- Dimensions: 160x39x50 (in mm)
- Code: SG-35XX (add Class0/Class1)
   Code: SG-36XX (add Class2/Class3)



Regeltex - Beige

# Insulated Gloves (1000V-36500V) LG01 / LG02 • Full range of insulating gloves for live working complies with the

specifications of the European standard EN 60903:2003 and the international standard IEC 60903:2002.

• See table below for voltage selection & hand size

• Length - 360mm ( Class 0 - Class 2)

• Code: LG01XX (add size) (Beige) LG02XX (add size) (Black)

• Glove Kits- (Pair of gloves & protector/ inner mitten/ carry bag & talc powder)

• Code: GloveKTXX (add class & size)



Novax- Black

Class	Lengths available	Operating Voltage	Thickness in mm *	Sizes available	
00	28/36 cm	500V	0.5	8-9-10-11	
0	36/41 cm	1000V	1.0	7-8-9-10-11	
1	36/41 cm	7500V	1.5	8-9-10-11	
2	36/41 cm	17000V	2.3	8-9-10-11	
3	36/41 cm	26500V	2.9	8-9-10-11	
4	41 cm	36500V	3.6	9-10-11	



#### **Glove Inner Mitten LGM**

Knitwrist Cotton Inner Glove

• 100% cotton glove with straight thumb 8oz weight

• Use only for general handling or as an inner

• Code: LGM



# **Leather Overglove Protector LGP02**

- · Goat skin leather overgloves
- To worn over insulating gloves to prolect against mechanical risk and, when necessary, against electric arc risks
- Length 250mm
- Thickness: 0.9mm
- Can be used over Class0 Class2 insulated gloves
- According to EN 388-2122 and EN 420 standards.
- Sizes Available: 8/9/10/11
- Code: LGP02XX (add size)







# **GLOVES MV**





## Insulated Gloves MV - ASTM / IEC Class 3-4 MG34

- Class 3 & 4 gloves are available in the industry standard color black, or in contrasting two-color combinations.
- The contrast between the thin outer color against the inner color makes inspecting for cuts and tears easier when the glove is inflated or stretched.
- Insulating gloves for live working complies with the specifications of the European standard EN 60903:2003 and the international standard IEC 60903:2002.
- Length 410mm ( Class 3 Class 4)
- · Available sizes: 8/9/10/11
- Code: MGXX (add class & size)



# **Leather Overglove Protector MGP34**

- · Cowskin leather overgloves
- · Manufactured from top grain cowhide
- Tough leather on palm size and grey vinyl on back.
- To worn over insulating gloves to prolect against mechanical risk and, when necessary, against electric arc risks
- Length 280mm
- Thickness: 1.2mm
- Can be used over Class2 Class3 insulated gloves
- According to EN 388-2122 and EN 420 standards.
- · Available sizes: 8/9/10/11
- · Code: MGPXX (add size)



#### **Pneumatic Tester GTLM 117**

- Before using insulated gloves for live working, the EN 60903 and EC 60903 standards recommend a visual inspection by inflating the gloves with air to detect any possible leakages.
- The pneumatic tester is a pump system optimizing inflation and thus allowing visual inspection at cuff level
- Code: GTLM 117



#### **Talc Powder TALCPM**

- Talc makes the insulating glove more comfortable to wear by limiting the effects of sweating
- Code: TALCPM











# SALISBURY

# ARC Shield Kits 12cal/26cal ARCKT12 / ARCKT26

- The ARCSHIELD Kits make your Personal Protective Equipment purchasing easier.
- New generation of face protection against the thermal hazards of arc flash.
- Realistic colour reproduction >95%.
- Protection against high-speed particles: medium energy impact (B).
- Extended length visor and transparent chinguard.
- Fitted with a universal bracket for use with front brim arc rated hard hats according to EN50365 or EN 397 standards.
- These convenient kits contain an AS1000HAT, a10cal/cm2, 15 cal/cm2, or 20 cal/cm2 ATPV rated AFHOOD, safety glasses and an ASBAG.
- Available Rating: ARC01- 12cal/cm2 ARC02- 26cal/cm2
- Code: ARCKTXX (add AFP rating)

#### **ARC Flash Nomex Balaclava ARC02**

- Cal Rating 13cal/cm2
- Double layered
- Can be worn under helmet & Shield to increase ATPV
- Meet NFPA 70E Hazard risk Category 2.
- Code: ARC02

#### Arc Resistant Conti-Suite 12.4 Cal/cm2 ARCCS12

- ATPV 12.4 cal/cm2
- 305gsm Dromex A.P.T Fabric
- 88% Cotton, 12% Nylon
- Flame Retardant Thread
- YKK concealed brass zips on jackets and pants
- Flame Retardant Velcro closures
- Triple needle side seams
- Flame Retardant knitted rib cuffing
- Three jacket pockets with mitred flap & FR Velcro closure & side swing pockets on pants
- 12.4 cal/cm2 rating embroidery on jacket and pants
- 50mm Flame Retardant reflective tape on arms and legs
- Conforms to SANS 434 IEC 61482-1-1, IEC 61482-1-2, NFPA 2112,
- SANS 724, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014
- Sizes Available: Jackets: 32-60 Pants: 28-56
- Code: ARCCSXX (add size)

# Arc Resistant DenimSuite 21 Cal/cm2

- ATPV 9.6cal/cm2 Shirt
- ATPV 21 cal/cm2 Pants
- Two mitred breast pockets with double needle stitching and mitred flap
- 9.6 cal/cm2 rating embroidery on right breast
- 100% Cotton, 14oz (475 asm) Arc Denim
- Flame Retardant Corespun 40 Thread
- Double needle top stitching at inleg & back rise
- Swing pockets with double needle topstitch21 cal/cm2 rating embroidery on right back pocket
- Five Belt Loops
- · Back yoke with double needle top stitching
- Two back pockets with double needle top stitching
- Sizes Available: Shirt: Small-3XL
  - Pants: 28-44



#### Arc Flash Boiler Suite 12.4cal/cm2 ARCBS

- ATPV 12.4 cal/cm2
- 305gsm Dromex A.P.T Fabric
- 88% Cotton, 12% Nylon
- Flame Retardant Thread throughout
- YKK concealed brass zips on jackets and pants
- Flame Retardant Velcro closures
- Triple needle side seams
- Flame Retardant knitted rib cuffing
- Three jacket pockets with mitred flap & FR Velcro closure & side swing pockets on pants
- 12.4 cal/cm2 rating embroidery on jacket and pants
- 50mm Flame Retardant reflective tape on arms and legs
- Conforms to SANS 434 IEC 61482-1-1, IEC 61482-1-2, NFPA 2112,
- SANS 724, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014

• Sizes Available: 32-60

• Code: ARCBSXX (add size)



#### Arc Flash Suite 25cal/cm2 - 51cal/cm2

- ATPV 25cal or 51 cal/cm2
- Dromex A.P.T Fabric 88% Cotton, 12% Nylon
- Double layer construction: 14oz outer and 9oz inner
- Flame Retardant Thread throughout
- YKK concealed brass zip on jacket
- Flame Retardant velcro closures
- Triple needle top stitching on shoulders, side seams & inleg
- Flame Retardant knitted rib cuffing
- 51 cal/cm2 rating embroidery on jacket and pants
- Hood Includes 40 cal/cm2 BSD Arc Visor with Real View Technology
- Back flap with velcro closure
- Conforms to SANS 434 IEC 61482-1-1, IEC 61482-1-2, NFPA 2112,
- SANS 724, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014

• Sizes Available: Jackets: 32-60 Pants: 28-56

Code: ARC25KTXX- (add size) 25cal/cm2
 ARC51KTXX- (add size) 51cal/cm2



# Arc Glove 51cal/cm2 ARCGLV51

- Leather glove lined with Aramid fibre
- Kevlar stitching
- Shirred extended 16cm cuff
- Tan split cow leather palm 1.0 to 1.2mm with equivalent reinforcing.
- Tan split cow leather back 1.0 to 1.2mm, shirred.
- Yellow aramid knitted wrist cuff with tan split cow leather 0.8 to 1.0mm
- leather continuous pull
- 380g per pair (size L)
- 51 CAL/CM² arc rated leather gloves
- High cut level D
- High Abrasion Resistance
- High resistance to snatch, tear, cut and heat
- Waterproof
- Multi-layer protection provides flexibility, comfort and excellent insulation.
- Size: 8/9/10/11
- Code: ARCGL51XX (add size)- 51cal/cm2



Style 01

Style 01



Style 02

Style 02



- Brand JIM GREEN
- Available in tan or brown oily leather.
- These boots boast lightweight imported rubber/polyurethane soles from Italy.
- The Stockman & Adventure boot is lined with goat leather and the latest generation lining for extra waterproof, anti-bacterial and anti-odor properties providing comfort, coolness and breath ability.
- This easy slip on boot is a favorite amongst outdoor enthusiasts who like to get going early with no fuss
- Sizes Available: 8/9/10/11
- · Code: SBXX (add style & size)

# Safety Shoes / Boots Male SBH

- Brand: LEMAITRE
- Shoe Explorer (SSX)
- Boot- Hunter (SBH)
- · Sex: Male
- Category: Industrial Steel Toe Cap
- Purpose: General Industry / Agriculture / Mining
- · Resistance: Acid / Oil Fuel / Water
- Upper Material: Buffalo Leather
- Sole Material: Double Density PU
- Sole Construction: Direct Injected Moulded
- Toecap: Steel Resistant 200J
- · Colors: Black/Silver
- Sizes Available: 8/9/10/11
- Code: SBHXX (add style & size)



Style 02

# Safety Shoes / Boots Male SBZ

- Shoe Eros (SSE)
- Boot Zeus (SBZ)
- Category: Industrial Non Steel Toe Cap
- Purpose: General Industry / Agriculture / Mining
- Resistance: Acid / Oil Fuel / Water
- Upper Material: Safety Boot
- Lining: Vamp Non-Woven
- Sole Material: Double Density PU
- Sole Construction: Direct Injected Moulded
- Toecap: Steel Resistant 200J
- Colors: Black / Brown
- Sizes Available: 8/9/10/11
- Code: SBZXX (add style & size)

### Safety Shoes / Boots Female SBP

- Brand: LEMAITRE
- Shoe Pisces (SSP)
- Boot Tugela (SBT)
- Category: Industrial Non Steel Toe Cap
- Purpose: General Industry / Agriculture / Mining
- Resistance: Acid / Oil Fuel / Water
- Upper Material: Safety Boot
- Lining: Vamp Non-Woven
- Sole Material: Double Density PU
- Sole Construction: Direct Injected Moulded
- Toecap: Steel Resistant 200J
- Colors: Black / Brown
- Sizes Available: 5/6/7/8/9
- Code: SBPXX (add style & size)



Style 01

Style 02



#### **Fall Arrest Kit Powerline FASPL**

- Full body harness with Dorsal D-rings, Sternal D-rings and Lateral D-rings
- Padded waistbelt for comfort.
- Flame Resistant/ Anti static webbing.
- Aluminum buckles and D-rings
- Adjustable webbing lanyard 1.75m for work positioning attachment straps
- · Includes all accessories listed below
- Carry bag
- SANS50361 /SANS50358/SANS50355/SANS50354
- Sizes Available: SML/MED/LRG/XL/2XL/3XL
- Code: FASPLXX (add size)



#### **Fall Arrest Kit Live Work FASLW**

- Full body harness with Dorsal D-rings, Sternal D-rings and Lateral D-rings
- Padded waistbelt for comfort.
- Flame Resistant/ Anti static webbing.
- Aluminum buckles and D-rings
- Adjustable webbing lanyard 1.75m for work positioning attachment straps
- Includes all accessories listed below
- Carry bag
- SANS50361 /SANS50358/SANS50355/SANS50354
- Sizes Available: SML/MED/LRG/XL/2XL/3XL
- · Code: FASLWXX (add size)



#### Fall Arrest Kit Sub & Aux Kit FASMUN

- Full body harness with Dorsal D-rings, Sternal D-rings and Lateral D-rings
- Padded waistbelt for comfort.
- Flame Resistant/ Anti static webbing.
- Aluminum buckles and D-rings
- Adjustable webbing lanyard 1.75m for work positioning attachment straps
- Includes all accessories listed below
- Carry bag
- SANS50361 /SANS50358/SANS50355/SANS50354
- Sizes Available: SML/MED/LRG/XL/2XL/3XL
- Code: FASMUNXX (add size)

### Standard Accessories for all FAS Kits

Double Adjustable Lanyard QSSA/DAL
Complete with a shock
absorber, aluminium pylon
hooks and one tri-lock/
captive eye karabiner

Webbing Pole Strap QSSA/WAWP
complete with 2 aluminium snap
hooks

Nylon Rope Pole Strap QSSA/NAWP Complete with a rope grab and an aluminium tri-lock captive eye karabiner with a snap hook on one end

1,5m Attachment Strap QSSA/AS





# First Man Up Rope Access Fall Arrest Kit FPFMU



#### **FAS Post Fall Arrest Rescue Kit FPRES**



• Length Available: 20M/30M

• Code: FPRESXX (add Length)

# **Telescopic Rescue Pole Kit FPRESTP**



• Code: FPRESTPXX



#### **Insulation Stool-IST**

- Made of high impact copolymer polypropylene.
- The platform surface is rough and non-slip.
- Rubber tips are place under the legs to give it greater adherence to the floor and protection from wear
- Platform: 525x525mmSurface: 575x575mm
- According to UNE 204001 standard
- Class 5
- Voltage Rating Available: 36kV/45kV/66kV
- Code: ISTXX (add voltage rating)



# Insulated Wire Cutter - SZ-57

- Insulated wire cutter for cutting cables up to 25mm.
- Incorporates metallic blades and two handles made of polyester rere-inforced with fiberglass of 32mm diameter
- Voltage Rating Available: 25kV / 36kV
- · Code: SZ-57XX (add voltage rating)



# Rescue Panoplies Kit - SZ-51M

- In the event of an electrical accident, fast intervention is essential.
- The panel contains all the rescue tools in a single place making it accessible to all users when an intervention is necessary .

# Contains the following elements

- 1 x Rescue pole
- 1 x 5-36kV voltage detector with pole
- 1 x Metallic case for gloves
- 1 x Pair of dielectric gloves (class3)
- 1 x Insulated wire cutter
- 1 x Pipette
- 1 x Insulated stool 45kV
- 1 x Jar of salts
- 1 x Pair of insulated shoes
- 1x First aid plate
- 1 x Instruction plate
- Code: SZ-51M