

ShenZhen Foscam Intelligent Technology Co., Ltd.


Address: 9/F, Block F5, TCL International E City, No.1001 Zhongshanvuan Road, NanShan District, Shenzhen, PRC.

Tel: +86-755-26745668

Fax: +86-755-26745168

HOME NETWORK VIDEO SURVEILLANCE LEADING BRAND

2018 Product Brochure









CATALOGUE

01

About Foscam

05

Home Security

07

Business Security

80

Foscam Cloud Service

09

Foscam APP



Battery-powered Camera (NEW) Foscam E1

13

- 13 Indoor Wireless Pan/Tilt IP Camera R4/R2/FI9821P
- L5 Indoor Wireless Cube IP camera c2/c1
- 7 Outdoor Waterproof Bullet IP camera
- 19 Outdoor Dome IP Camera FI9928P/FI9961EP/FI9853EP
- 21 Network Video Recorder Kits FN7108E-B4-2T/FN3104W-B4/FN3108XE-B4-1T



Accessories



Aftersales Support



Product Specification

About Foscam

Our Mission

Dedicated to security technology, create a secure life.

Company Vision

Become the world's top brand of intelligent security field.

Core Value

Strive, Self-realizing, Service-focused, Customer success.



ShenZhen Foscam Intelligent Technology Co.,Ltd. is a professional company which designs, manufactures and provides IP video camera and solutions.

Founded in 2007, Foscam is headquartered in Shenzhen, China, with its operations all over the world. Foscam has established distribution channels in more than 80 countries and regions, including Germany, the United States, Britain, Italy, Singapore, India, France and Canada. Millions of Foscam products, which have been approved by ISO9001:2008 and RoHS, have been sold via various online store channels and retailers.

Foscam has a domestic R&D team with professional experience of many years for video, voice and communication products. The team possesses best technology integration and development capabilities.

As a leading firm for network video solutions in China, Foscam is committed to offering the public the safest network camera series of high quality and cost-effective comprehensive equipment solutions. Thanks to all the great channels with our top-class resellers, Foscam has gained high reputation for its cost-effectiveness. We sincerely welcome worldwide partners to join us to expand Foscam brand value together.



Subsidiary Foscam Inc. was established in the USA in 2016. Its origination was based on the concept of the manufacture being closer to the front lines in the worlds largest consumer market for IP Cameras. As a manufacture of IP cameras, it is critical we understand what consumers want so that we can go back to the drawing board and build the products that meet their needs.

Foscam Milestone 2007-2018

2018	Start home security system de Start Foscam AI project
2017	Foscam's 10th anniversary Int is commercially available. Products advance toward hig
2016	Build up subsidiary Foscam, Ir
2015	Set up the Global Service Cent Released the first-phase proje Built up Subsidiary in the UK.
2014	Acquired ISO9001 quality cert Released the first network bal
2013	Joined ONVIF Alliance.
2012	Released the first 1.0 Megapix network camera.
2011	Sales volume ranked No.1 in C annual growth rate.
2010	Released FI8918W with desigr Became top three network ca
2009	Entered into the USA, Europe
2008	Released patented product-FI
2007	Foscam is founded in Shenzhe

design

ntelligent algorithm V1.0

gher resolution and intelligentization

Inc. in the USA.

nter in the headquarter. ject of Cloud platform.

rtificate aby monitor-FosBaby.

xel Foscam independent R & D

China with 200%

n patent, sales volume reached 130,000USD. amera providers in China.

market. Released FI8904W, FI8905W and etc.

18908W.

nen.

Foscam Milestone (02)



Foscam **RESELLERS**



North America

United States Mexico

Europe

Belgium Poland Russia Hungary Ukraine Italy Netherlands United Kingdom

South America

Bolivia Peru Venezuela

China (HK/TW) Japan

Asia

Kuwait

Malaysia Saudi Arabia Singapore Vietnam

Oceania

Australia New Zealand

Africa

South Africa

Foscam has established distribution channels in more than 80 countries and regions, including the United States, United Kingdom, Germany, Britain, Italy, Singapore, Spain, Netherlands, France, Canada, Australia, etc. In these countries, millions of Foscam products have been sold via various online store channels and local retailers.



Stores









Home Security





Monitor your home in the palm of your hand.



Replay multi-channel synchronously on PC.



Find the record accurately by motion alarm and auto recording.



Plug in external hard disk in a second.



Business Security








Store

Office





Warehouse Factory

Protect your business day and night

With night vision and motion detection, it's easy for you to know whether your business is safe and secure anytime.



View your chain stores on one computer

If you have several stores in different places, you may have trouble in managing them simultaneously. Now add each store video on Foscam VMS to follow them all at once.



Foscam Cloud Service Simple · Smart · Secure

Foscam Cloud adds a simple, smart and secure way to store video recordings from your Foscam cameras. With Foscam Cloud, you'll never miss an event!



Cloud Recording Cloud storage protects recordings against any footage loss that could result from damage such as fire, flood, vandalism, or theft of the camera.

myfoscam



Real-time viewing and multi camera management



0

0



Cloud Playback Quickly see the important moments you missed, and enjoy viewing the fun moments anywhere.

Trusted by more than 2 MILLION users!

Foscam 10th anniversary 2008-2018





```
www.myfoscam.com
```





Cloud Push

Ò

Smart motion and sound detection technology will notify your smartphone of meaningful events.



Cloud Upgrade

Enjoy the latest features for your camera through free over-the-air updates

Ó



Foscam APP Be There, From Anywhere

Foscam Cloud adds a simple, smart and secure way to store video recordings from your Foscam cameras. With Foscam Cloud Service. never miss an event!

Foscam APP

One APP for multiple Foscam cameras



One APP for home security

- Alert notifications and Alert Linkage.
- Sharing cameras with your family.
- Foscam cameras can be remotely voice controlled via **amazon** alexa



Control your camera from your smartphone

Two way audio Control the pan/tilt rotation of camera Remote Camera Setting

ι, Ö

New look in 2018




Foscam App is free and available for download in the App Store and Google Play store.



Search "Foscam App" in the App Store or Google Play store.

When you see the blue and white Foscam App logo, select download and install.

Alternatively, you can simply scan the QR code above to download Foscam App directly.



Foscam	10^{th}	anniversar	y 2008-2018
--------	------------------	------------	-------------


(

How to get Foscam app?

•**	Foscam APP 10

Foscam E1 **HD Smart Security** Wire free, Hassle free





Dimensions (Unit: mm)



Monitoring Various Locations House



100% Wire-Free Camera

required.

Thanks to its magnetic base, you can install your camera anywhere.

No angle is missed when monitoring your home right from your smartphone.

7 days of history.

Foscam Cloud Plan

Long Lasting **Rechargeable Battery**

Long-lasting battery life allows you to keep an eye on what matters most anytime, even if you're away for extended periods.

You can check the Foscam E1's battery status conveniently right from the Foscam App.

Rest assured knowing that when the battery needs to be charged, notifications will be sent right to your smartphone.

Note: Foscam E1 uses 5000mAh rechargeable battery. Battery life varies depending on camera settings, usage and operating temperature.




Leave the unsightly wires behind. The Foscam E1 camera is 100% Wire-Free and is easy to setup - no invasive drilling or wiring

Free Foscam Cloud Plan with the Foscam E1

Free Foscam Cloud Plan includes up to 6 cameras per account.

- Access triggered video recordings from your Foscam Cloud for up to
- Enjoy up to 1 GB of Cloud storage with the Free Foscam Cloud plan.
- Free Foscam Cloud Plan never expires for the Foscam E1.

Note: We reserve all the right for the final explanation about Free



4.0MP IndoorPan/Tilt WirelessIP Camera

Key Features

- 4.0 Megapixels wireless IP camera
- IR range up to 26 feet (8 meters)
- Magic Zoom provides detailed view
- EZLink and PnP setup feature bring easy setup experience
- · H.264 video compression
- Enhanced 2 Way Audio with integrated mic and speaker ·WDR technology
- · Low Bit Rate feature brings smooth video experience
- Supports up to 128GB Micro SD Card Storage
- · Supports Pan/Tilt function (H=300°/ V=100°)


·Works with free Foscam iOS and Android Colud APP

· Supports IEEE 802.11n Wireless Connection





Dimensions (Unit: mm)



Monitoring Various Locations House, small shops, school, warehouse

Indoor 1080P Full HD Wireless Pan/Tilt IP Camera

Key Features

- 2.0 megapixels 1080P full HD wireless pan & tilt camera
- Supports pan & tilt control from phone (H:300°; V: 100°)
- Detect human motions with Smartcam Technology to reduce irrelevant alerts
- · Enhanced two way audio with integrated mic and speaker
- IR range up to 26 feet (8 meters)
- · 2X magic Zoom and 6X digital zoom for closer view
- WDR technology for clearer image in backlight scene
- · Low Bit Rate (Ambarella chip set)
- Supports up to 128G micro SD card storage
- All motion detection and alert push to email, FTP and mobile app



Monitoring Various Locations House, small shops, school, warehouse

720P HD PnP Wireless IP Camera

Key Features

- ·720P HD Pan/Tilt wireless IP camera
- · H.264 video compression
- · Day/Night surveillance, IR LEDs On/Off auto switch
- Motion detection alerts push to email, FTP and mobile app · Supports 32G micro SD card storage
- · Plug & Play connection by simply scanning QR code
- Compatible with free Foscam central management software · Compatible with free Foscam iOS and Android APP
- · Supports WPS secure wireless connection
- · Supports 6X digital zoom



Foscam 10th anniversary 2008-2018






Dimensions (Unit: mm)







Dimensions (Unit: mm)



Monitoring Various Locations

House, small shops, school, warehouse

Pan/Tilt IP Camera (14)



2.0 Megapixel 1080P Full HD PIR Wireless IP Camera

Key Features

- · 2.0 Megapixels 1080P Full HD Images and Videos · Passive Infrared Detection & Intelligent Alerts for
- Accurate Monitoring
- Enhanced 2 Way Audio with integrated mic and speaker
- \cdot 2X Magic Zoom and 6X Digital Zoom provide detailed View \cdot Ultra-wide 110° viewing angle
- ·128GB Micro SD card & Foscam Cloud Storage



Monitoring Various Locations

House, Garden, Factory, Shop, Office



Dimensions (Unit: mm)





720P HD Indoor PnP Wireless IP Camera

Key Features


- •720P HD wireless IP camera
- $\cdot\,\mathsf{Plug}\,\&\,\mathsf{Play}\,\mathsf{connection}$ by simply scanning QR code
- \cdot H.264 video compression
- ·Day & Night surveillance, IR LEDs On/Off auto switch
- $\cdot \operatorname{Accurate}$ action detection alarm with Infrared Human Body Sensor
- · Supports 360° monitor with functional bracket
- Supports 32G micro SD card storage
- · Supports two-way audio
- $\cdot\, {\rm Works}$ with free iOS and Android APP
- \cdot Supports 6X digital zoom



Monitoring Various Locations

House, Garden, Factory, Shop, Office





Cube IP Camera (16)

4.0 MP Outdoor IP66 Waterproof **PoE IP Camera**

Key Features

- 4.0 megapixel IP66 waterproof IP camera
- · IR range up to 66 feet (20 meters) with 30pcs IR-LEDs
- · WDR 2.0 for better image in backlight situations
- · IP66 rating against all types of bad weather
- · Supports two-way audio with external mic and speaker
- Motion detection alert to mobile app, email and FTP
- · Compatible with free Foscam iOS and Android app
- · Supports cloud service and real-time captured image push
- · Supports 6X digital zoom




Monitoring Various Locations

House, Garden, Factory, Shop, Office

FI9901EP





2.0 MP Outdoor IP66 Waterproof **PoE IP Camera**

Key Features

- · 2.0 Megapixel full HD IP66 waterproof IP camera
- Plug & Play connection by simply scanning QR code
- · With 30pcs IR-LED, IR range up to 66 feet (20 meters)
- Motion detection alerts push to email, FTP and mobile app
- · Compatible with free Foscam iOS and Android APP
- Supports WDR, LBR and Magic Zoom
- · Supports 6X digital zoom




Monitoring Various Locations

House, Garden, Factory, Shop, Office

FI9900EP



Dimensions (Unit: mm)





1080P HD Outdoor IP66 Waterproof Wireless Bullet IP Camera

Key Features

- 2.0 Megapixel HD IP66 Waterproof IP Camera
- · With 30pcs IR-LED, IR range up to 66 feet (20 meters)
- · Plug & Play Feature by scanning OR code for easy remote access
- Motion detection alerts push to email, FTP and mobile app
- · Compatible with free Foscam iOS and Android APP
- · Supports WDR, LBR and Magic Zoom
- Supports IEEE 802.11n Wireless Connection
- Supports WEP, WPA and WPA2 Encryption
- · Supports Two-way Audio
- Supports 6X digital zoom



Monitoring Various Locations

House, Garden, Factory, Shop, Office

720P HD Outdoor IP66 Waterproof Wireless IP Camera

Key Features

- · 1.0 MP HD IP66 waterproof IP camera
- · H.264 video compression
- · Plug & Play connection by simply scanning QR code · IR range up to 66 feet (20 meters)
- Motion detection alerts push to email, FTP and mobile app
- Compatible with free Foscam Video Management Software
- Compatible with free Foscam iOS and Android APP
- Supports IEEE 802.11n wireless connection
- Supports WEP, WPA and WPA2 encryption
- Supports 6X digital zoom




Monitoring Various Locations House, Garden, Factory, Shop, Office











Dimensions (Unit: mm)







1080P Full HD Pan/Tilt/Zoom Waterproof Wireless Starvis Dome Camera

Key Features

- 2.0 megapixel full HD Pan/Tilt/Zoom wireless dome IP camera
- 4x optical zoom for more detailed view
- Supports pan & tilt function (H=355°; V=90°)
- Day & night surveillance, IR LEDs On/Off auto switch
- With 6pcs IR-array lights, IR range up to 196 feet (60 meters)
- Motion detection alert push to email, FTP and mobile app
- Supports auto focus
- Compatible with free Foscam iOS and Android app
- Supports IEEE 802.11n wireless connection
- Supports WEP, WPA and WPA2 encryption
- Supports two-way audio with external mic and speaker
- Supports I/O interfaces



Monitoring Various Locations

House, Garden, Factory, Shop, Office

Luxury hardware for most powerful camera

Professional SONY CMOS sensor, the low light imaging sensor, supports low lux color night vision and shows you more details with full color image in near darkness. Reliable Ambarella chip provides smooth video feed at low bit rate. 4X optical zoom dual-motor lens is equipped for superb magnification effect.

Artful 4+2 grouping of infrared lamps for clearer night vision

To provide clearer night vision image, six highly efficient infrared lamps are divided into two groups for wide angle viewing and narrow angle viewing respectively. The switch of lamp group corresponds automatically to the focus of lens.

Super wide pan & tilt range and 4X optical zoom


Control the pan & tilt rotation of camera from your phone to see your space without blind spots. Never leave anything to doubt with 4X optical zoom and 6X digital zoom. Auto focus works well with zoom to provide clear image for you.

External Micro SD card slot for easy operation

Insert Micro SD card for local storage is not tricky any longer. You don't need to disassemble the camera, but just remove the two screws on a small cover to see the Micro SD card slot. The best part is, both the cover and other parts of camera are waterproof for the outdoor use.

FI9928P

Dimensions (Unit: mm)





1080P FHD Vandal-proof PoE **Dome IP Camera**

Key Features

- IK10 vandal-proof cover against devastating impacts
- 2.0 megapixel full HD streaming video
- WDR 2.0 for better image in backlight situations
- IR range up to 66 feet (20 meters) with infrared lamp arrays
- IP66 rating against all types of bad weather
- PoE for easier wiring and smaller through-wall hole
- Quick QR code access and free iOS and Android Foscam APP
- Superior two-way audio with external mic and speaker
- Supports recording and alert push triggered by motion detection
- Supports cloud service and real-time captured image push
- Supports SD card up to 128G
- Supports 6X digital zoom



Monitoring Various Locations

Hospital, School, Metro Station, Factory

720P HD PnP Fixed Dome **IP** Camera

Key Features

- 1.0 Megapixel HD waterproof IP camera
- H.264 video compression
- Plug & Play connection by simply scanning QR code
- IR range up to 66 feet (20 meters)
- Motion detection alerts push to email, FTP and mobile app
- Compatible with free Foscam iOS and Android APP



Monitoring Various Locations House, Factory, Shop, Office

FI9961EP



Dimensions (Unit: mm)





FI9853EP



Dimensions (Unit: mm)







Dome IP Camera (20)



1080P Professional PoE NVR Security System

Key Features

- 8-channel live viewing, 4-channel synchronous playback
- 1080P high definition images for day and night
- Standard PoE for easy wiring and small through-wall hole
- Access via Foscam NVR APP, browsers, or monitor
- Pre-installed 2TB hard drive (up to 4TB)
- Motion detection alert push to email and FTP
- · 30 IR LEDs for 66 feet (20 meters) IR range
- · IP66 rating against all types of bad weather
- · USB 3.0 data transfer, 10 times faster than USB2.0
- HD-OUT: connect via HD cable to HDTV



Monitoring Various Locations

House, Garden, Factory, Shop, Office

FN7108E-B4-2T



Dimensions (Unit: mm)	1
	234



720P WiFi NVR Security System

Enjoy all the advantages of wireless connection

Key Features

- WIFI NVR Kits, connect camera with NVR wirelessly
- Supports IEEE 802.11n wireless connection
- 4-channel live viewing and synchronous playback
- · 720P high definition images for day and night
- Access cameras via IE, Safari
- Remote viewing on smartphone via free Foscam NVR APP
- Motion detection alert push to email and FTP
- Pre-installed 1TB hard drive (up to 4TB)
- · 30 IR LEDs for 66 feet (20 meters) IR range
- · IP66 rating against all types of bad weather
- · HD-OUT: connect via HD cable to HDTV



Monitoring Various Locations

House, Factory, Store, Office, Warehouse, Hotel

NVR and Camera Auto Pairing

Four cameras automatically connect to the NVR in the same security system when all of them are powered, no Ethernet cable is required. Only for remote viewing access you need connect the NVR to network.

Automatic Channel Picking for Sustained WiFi Speeds

WiFi speeds are a vexing problem in a lot of situations. This security system can automatically select the best channel to get you more stable network connection and boost your WiFi speed.

Mount It Wherever You'd Like

Enjoy all the advantage of wireless security system, such as flexible mounting position selection, much easier wiring works, less damages to your decoration and so on. This portable system can be taken anywhere.

Foscam 10th anniversary 2008-2018



FN3104W-B4



Dimensions (Unit: mm)





720P HD Simplified PoE NVR **Security System**

Key Features

- · 8 Channel Live Preview & Record
- · 4 Channel Synchronous Playback
- · High Definition 720P Live View & Playback
- Pre-installed 1TB/2TB Hard HDD
- xPoE Simplified Power Over Ethernet for IP Cameras
- · Access Device Via Mobile APP or IE & Safari & Firefox
- Remote Viewing- View Remotely on your Smartphone
- Motion Detection Alarm Via E-mail and FTP
- 66 feet (20 meters) IR range
- 75° Viewing Angle
- Outdoor Cameras with IP66 Weather-resistant Rating
- · HD-OUT- Connect Via HD cable to HDTV

00 C HD 2.0 MP IE & Safari Night Vision Simplified Power Motion

Monitoring Various Locations

House, Factory, Store, Office, Warehouse, Hotel

FN3108XE-B4-1T



Dimensions (Unit: mm)







PoE Injector



Waterproof Junction Box



Wireless Antenna

9-channel 960P HD **Network Video Recorder**


Key Features

- ·9-ch 960P HD IP camera access
- · H.264 main profile video compression
- · Supports HD output and VGA local display
- ·9-ch video synchronous playback
- Compatible with Foscam HD and MJPEG cameras
- · Supports ONVIF protocol
- · Supports USB external storage (flashdisk,HDD)



Monitoring Various Locations House, Convenience Store, Warehouse, Hotel

FN3109H





Foscam 10th anniversary 2008-2018



Ethernet Cable



HD Out Connector



PoE Switch



Extension Cord




Power Adapter



Wall Mount for Bullet Camera



www.foscam.com



Global Technical Support Email: tech@foscam.com







Call us 1-844-344-1113 (U.S.A)

Live Chat on

www.foscam.com







Online Foscam Community Support http://community.foscam.com

Free Instructional How-To Videos available on Youtube and official website

Battery-p IP camera	owered	
Ctation	Model	61
Station Video Input	Model	S1
video input	IP Video Input	up to 8Channels
Decending	Recording Resolution	720P &1080P
Recording	Record Mode	Manual /alarm Record
Dlauback	Compression Format	H.264
Playback	Synchronous Playback	1 channel 720P&1080P synchronous
	Ethernet	One 10/100Mbps RJ45 port
Network	Wireless Standard	IEEE802.11b/g/n
	Wireless Security	WEP, WPA, WPA2
	Network Protocol	IP、TCP、UDP、HTTP、HTTPS、DF
	Network Interface	1× 10/100 Mbps RJ45 port
External Interface	USB	1×External USB storage port
	Button	1× Power on/off button,1× Reset b
Software	Smart phone	iOS, Android, 3G/4G Smartphones
Language	Language	English
	Power Supply	DC 12V/1A
	Dimension(LxWxH)	167mm*65mm*117mm
Physical and Environmental	Operating Temperature	0°C~55°C (32°F~131°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temperature	-20°C~60°C (-4°F~140°F)
	Storage Humidity	0% ~ 90% non-condensing
Camera	Model	B1
	Sensor Type	1/2.9" CMOS
	Video Quality	1080P(1920*1080)&720p (1280*720)
Image Sensor		
Image Sensor	Backlight Compensation	\checkmark
Image Sensor	Backlight Compensation Lens Type	√ f:2.8mm, F:2.0
Image Sensor Lens		
-	Lens Type	f:2.8mm, F:2.0
-	Lens Type Infrared Mode	f:2.8mm, F:2.0 Automatic
Lens	Lens Type Infrared Mode View Angle	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n
-	Lens Type Infrared Mode View Angle Wireless Standard	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80
Lens	Lens Type Infrared Mode View Angle Wireless Standard Data Rate	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80
Lens Connectivity Software	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80 IP、TCP、UDP、HTTP、HTTPS、DH
Lens	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE800 IP、TCP、UDP、HTTP、HTTPS、DF H.264
Lens Connectivity Software	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format Multi-Stream	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80 IP、TCP、UDP、HTTP、HTTPS、DH H.264 A single stream
Lens Connectivity Software	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format Multi-Stream Motion Detection Waterproof	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE800 IP、TCP、UDP、HTTP、HTTPS、DF H.264 A single stream √ IP65
Lens Connectivity Software	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format Multi-Stream Motion Detection Waterproof Battery capacity	 f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80 IP、TCP、UDP、HTTP、HTTPS、DH H.264 A single stream ✓ IP65 5000mAh
Lens Connectivity Software Features	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format Multi-Stream Motion Detection Waterproof Battery capacity Standby	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80 IP、TCP、UDP、HTTP、HTTPS、DF H.264 A single stream √ IP65 5000mAh Battery life varies based on settings,
Lens Connectivity Software Features Physical	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format Multi-Stream Motion Detection Waterproof Battery capacity Standby Dimension(LxWxH)	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80 IP、TCP、UDP、HTTP、HTTPS、DH H.264 A single stream ✓ IP65 5000mAh Battery life varies based on settings, 78(L)x53.5(W)x100 (H)
Lens Connectivity Software Features	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format Multi-Stream Motion Detection Waterproof Battery capacity Standby Dimension(LxWxH) Warranty	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80 IP、TCP、UDP、HTTP、HTTPS、DH H.264 A single stream √ IP65 5000mAh Battery life varies based on settings, 78(L)x53.5(W)x100 (H) Limited 1-year warranty
Lens Connectivity Software Features Physical and	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format Multi-Stream Motion Detection Waterproof Battery capacity Standby Dimension(LxWxH) Warranty Operating Temperature	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80 IP、TCP、UDP、HTTP、HTTPS、DF H.264 A single stream ✓ IP65 5000mAh Battery life varies based on settings, 78(L)x53.5(W)x100 (H) Limited 1-year warranty -20°C~ 50°C (-4°F ~ 122°F)
Lens Connectivity Software Features Physical and	Lens Type Infrared Mode View Angle Wireless Standard Data Rate Network Protocol Video Format Multi-Stream Motion Detection Waterproof Battery capacity Standby Dimension(LxWxH) Warranty	f:2.8mm, F:2.0 Automatic 110° IEEE802.11b/g/n "IEEE802.11b: 11Mbps(Max.); IEEE80 IP、TCP、UDP、HTTP、HTTPS、DH H.264 A single stream √ IP65 5000mAh Battery life varies based on settings, 78(L)x53.5(W)x100 (H) Limited 1-year warranty

	Foscam E1	
s video playl	back	
НСР		
outton		
	N	200
	Net Weight (g)	290g
	IR Range	25ft(8m)
2.11g: 54Mb	ps(Max.); IEEE802.11n: 150N	/bps(Max.)."
НСР		
	Day/Night	\checkmark
	Net Weight	290g
110000 0 +	aporaturo	
usage & ten	Certification	FCC、IC、CE、IP65
	Certification	
	Operating Humidity	10% ~ 80% non-condensing

Indoo IP Car		R 4	R2	FI9821P		
	Sensor Type	1/3" CMOS	1/2.7" CMOS	1/4" CMOS		
-						
	Display Resolution	4.0 Megapixels (2560x1440),	2.0 Megapixels (1920x1080)	1.0 MegaPixels (1280x720)		
Sensor	Frame Rate (Max.)	25fps	25fps	30fps		
	IR-cut		√	√		
	Minimum Illumination	0 Lux (With IR Illuminator)				
	Lens Type	f:4.0mm,F:2.1	f:2.8mm,F:2.6	f:2.8mm, F:2.4		
	Angle of View	74°	101°	64°		
Lens	Pan & Tilt Angle	H=300°,V=100°	H=300°,V=100°	H=300°, V=120°		
	IR Range	8m (26.2ft)	8m (26.2ft)	8m (26.2ft)		
	Ethernet	\checkmark	√	\checkmark		
	WPS	\checkmark	\checkmark	\checkmark		
	Wireless	IEEE 802.11b/g/n				
	Wireless Security	WEP, WPA, WPA2				
Connectivity	P2P	\checkmark	\checkmark	\checkmark		
	External I/O	N/A	N/A	N/A		
	SD Card Slot	128G micro SD card	128G micro SD card	32G micro SD card		
	Video Format	H.264				
	Multi-Stream	Dual streams				
	Motion Detection	\checkmark	\checkmark	\checkmark		
	Sound Detection	\checkmark	\checkmark	\checkmark		
	Scheduled Recording	\checkmark	√	\checkmark		
Software Features	Built-in DDNS Server	√	\checkmark	\checkmark		
realures	Browser Supported	IE; Chrome; Safari.				
	OS Supported	Windows, MAC, Android, iOS				
	Infrared Mode	Automatic or manual				
	Day/Night	\checkmark	\checkmark	√		
	Firewall	Supports IP Filtering				
	2-way Audio	√	\checkmark	√		
	Built-in Microphone	\checkmark	√	√		
Audio	External Microphone I		N/A	√		
	Built-in Speaker	√ 	\checkmark	√		
	External Speaker Outp		N/A	 √		
	Dimensions (mm)	74(L)×74(W)×119(H)	74(L)x74(W)x119 (H)	117(L)x114(W)x129(H)		
	Power Adapter	5V/2A	() ()	() ()))))))))))))))))))))))))))))))))))		
Physical	Power Consumption	<6W	<6W	<8.2W		
and Environ	Operating Temper	-10°C ~ 55° (14°F ~ 131°F)	-10°C ~ 50° (14°F ~ 122°F)	0.2.11		
-mental	Operating Humidity					
	Certification	20% ~ 85% non-condensing				
	arranty	IC, CE, RoHS, FCC, CCPSA Limited 2-year warranty				

Indoor IP Carr		C2
	Sensor Type	1/3" CMOS
Image	Display Resolution	2.0 MegaPixels (1920x1080)
Sensor	Frame Rate (Max.)	30fps
	IR-cut	
	Minimum Illumination	0 Lux (With IR Illuminator)
	Lens Type	f:2.8mm, F:2.4
	Angle of View	110°
Lens	Pan & Tilt Angle	N/A
	IR Range	8m (26.2ft)
	Ethernet	
	WPS	
Connectivity	Wireless	IEEE 802.11b/g/n
	Wireless Security	WEP, WPA, WPA2
	P2P	
	External I/O	N/A
	SD Card Slot	128G micro SD card
	Video Format	H.264
	Multi-Stream	Dual streams
	Motion Detection	
	Scheduled Recording	
	Built-in DDNS Server	
Software Features	Browser Supported	IE; Chrome; Safari.
i catal es	OS Supported	Windows, MAC, Android, iOS
	Infrared Mode	Automatic or manual
	Day/Night	
	Firewall	Supports IP Filtering
	2-way Audio	
	Built-in Microphone	
Audio	External Microphone Input	N/A
	Built-in Speaker	
	External Speaker Output	N/A
	Dimensions (mm)	70(L)×70(W)×120(H)
Physical	Power Adapter	5V/1A
and	Power Consumption	<4.8W
Environ-	Operating Temper	-10°C ~ 50° (14°F ~ 122°F)
mental	Operating Humidity	20% ~ 85% non-condensing
	Certification	IC, CE, RoHS, FCC, CCPSAA
Other Featur	es	PIR, Sound detection

ę
<u> </u>
C1
1/4" CMOS
1.0 Megapixels (1280x720)
25fps VGA 23fps(720P)
\checkmark
f:2.8mm, F:2.4
100°
N/A
8m (26.2ft)
\checkmark
\checkmark
\checkmark
N/A
32G micro SD card
\checkmark
\checkmark
\checkmark
\checkmark
N/A
\checkmark
N/A
70(L)x70(W)x120(H)
5V/1A
<3W





Outdoo IP Cam					(g) 1 "		
		FI9901EP	FI9900EP	FI9900P	FI9803P		
	Sensor Type	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/4" CMOS		
lmage Sensor	Display Resolution	4.0 Megapixels (2560x1440)	2.0 Megapixels (1920x1080)	2.0 Megapixels (1920x1080)	1.0 MegaPixels(1280x720)		
	Frame Rate (Max.)	25fps	25fps	25fps	25fps(VGA) 23fps(720P)		
5611501	IR-cut	\checkmark	\checkmark	\checkmark	\checkmark		
	Min. Illumination	0 Lux (With IR Illuminator)	•				
	Lens Type	f:4mm, F:2.1	f:2.8mm,F:2.6	f:2.8mm,F:2.6	f:2.8mm, F:2.6		
	Angle of View	75°	91°	91°	76°		
Lens	Pan & Tilt Angle	N/A	N/A	N/A	N/A		
	Infrared Mode	Automatic or manual					
	IR Range	66 feet (20 meters)	66 feet (20 meters)	66 feet (20 meters)	66 feet (20 meters)		
	Ethernet	√	√	√	√		
	Wireless	N/A	N/A	IEEE 802.11b/g/n	IEEE 802.11b/g/n		
	Wireless Security	N/A	N/A	WEP, WPA, WPA2	WEP, WPA, WPA2		
	P2P	√	\checkmark	\checkmark	√		
Connectivity	External I/O	N/A	N/A	N/A	N/A		
	802.3af PoE	\checkmark	\checkmark	N/A	N/A		
	SD Card Slot	Internal 128G micro SD card			N/A		
	Power Adapter	12V/1A	12V/1A	12V/1A	12V/1A		
	Video Format	H.264	H.264	H.264	H.264		
	Multi Stream	Dual streams	Dual streams	Dual streams	Dual streams		
	Motion Detection	√	\checkmark	√	√		
	Scheduled Recording	√	\checkmark	√	√		
Software	Bulit-in DDNS Server	√	\checkmark	√	√		
Features	Browser Supported	IE; Chrome; Safari					
	OS Supported	Windows, MAC, Android, iOS					
	Day/Night	\checkmark	\checkmark	\checkmark	\checkmark		
	Firewall	Supports IP Filtering					
	User Accounts	Three levels user role					
	2-way Audio	√	√	\checkmark	N/A		
	Bulit-in Microphone	N/A	N/A	N/A	N/A		
Audio	External	\checkmark	\checkmark	\checkmark	N/A		
	Microphone Input						
	Built-in Speaker	N/A	N/A	N/A	N/A		
	External Speaker Output	√	\checkmark	\checkmark	N/A		
	Waterproof	IP66	IP66	IP66	IP66		
	Dimensions (mm)	165(L)x67(W)x64 (H)			153(L)x 92(W)x 86(H)		
Physical	Power Consumption	<5W	<5W	<5W	<4.2W		
and nvironmental	Operate Temper	-20°C ~ 60°C (-4°F ~ 140°F)					
	Operate Humidity	10% ~ 80% non-condensing					
	Certification	IC, CE, RoHS, FCC, IP66					
	Warranty	Limited 2-year warranty					

Outdoo IP Cam		6		00		
		FI9928P	FI9961EP	FI9853EP		
	Sensor Type	1/3" CMOS	1/2.7" CMOSS	1/4" CMOS		
	Display Resolution	2.0 Megapixels (1920x1280)		1.0 Megapixels (1280x720)		
Image Sensor	Frame Rate (Max.)	25fps	30fps	30fps		
	IR-cut	\checkmark	\checkmark	\checkmark		
	Min. Illumination	0 Lux (With IR Illuminator)				
	Lens Type	f:2.8mm~12mm, F:1.4	f.2.8mm, F=2.6	f.2.8mm, F=2.6		
	Angle of View	45°~125°	76°	74°		
Lens	Pan & Tilt Angle	H=355°, V=90°	N/A	N/A		
	Infrared Mode	Automatic or manual				
	IR Range	196 feet (60 meters)	66 feet (20 meters)	66 feet (20 meters)		
	Ethernet	√	\checkmark	\checkmark		
	Wireless	IEEE 802.11b/g/n	N/A	N/A		
	Wireless Security	WEP, WPA, WPA2	N/A	N/A		
Connectivity	P2P	\checkmark	\checkmark	\checkmark		
Connectivity	External I/O	√	N/A	N/A		
	802.3af PoE	N/A	\checkmark	\checkmark		
	SD Card Slot	External128G micro SD card	Internal 128G micro SD card	N/A		
	Power Adapter	12V/2A	12V/1A	12V/1A		
	Video Format	H.264				
	Multi Stream	Dual streams				
	Motion Detection	\checkmark	\checkmark	\checkmark		
	Scheduled Recording	\checkmark	\checkmark	\checkmark		
Software	Bulit-in DDNS Server	\checkmark	\checkmark	\checkmark		
Features	Browser Supported	IE; Chrome; Safari	IE; Safari; Chrome	IE; Safari; Chrome		
	OS Supported	Windows, MAC, Android, iOS				
	Day/Night	\checkmark	\checkmark	\checkmark		
	Firewall	Supports IP Filtering				
	User Accounts	Three levels user role				
	2-way Audio	\checkmark	\checkmark	N/A		
	Bulit-in Microphone	N/A	N/A	N/A		
Audio	External	\checkmark	\checkmark	N/A		
	Microphone Input					
	Built-in Speaker	N/A	N/A	N/A		
	External Speaker Output	\checkmark	\checkmark	N/A		
	Waterproof	√	IP66	\checkmark		
	Dimensions (mm)	234(L)×209W)×138H)	112.5(L)x112.5(W)x88(H)	135(L)x135(W)x98(H)		
Physical and	Power Consumption	<10W	<4.5W	<4.2W		
Environmental	Operate Temper	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C~60°C (4°F~140°F)	-20°C ~ 60°C (-4°F ~ 140°F)		
	Operate Humidity	20% ~ 85% non-condensing	10%~80% non-condensing	20% ~ 85% non-condensing		
	Certification	CE, FCC, RoHS	IC, CE, RoHS, FCC, IP66, IK10	IC CE, RoHS, FCC, IP66		
	Warranty	Limited 2-year warranty				



NVR Kits					0000	
		FN3108>	(E-B4-1T	FN7108E-B4-2T	FN3104W-B4	
Video Input	IP Video Input	8 Channels HD IP	camera		4 Channels HD IP camera input	
	HD Output	1×HD-Out				
Video Output	VGA Output	1×VGA				
	Display Resolution	1920 × 1080 /60Hz, 1280 × 720 /60Hz,1440 × 900 /60Hz,1024 × 768 /60Hz			1280x720/60Hz, 1280x1024/60Hz, 1280x720/50Hz, 1280x720/50Hz, 1280x1024/50Hz	
Recording	Recording Resolution	720P per channel (8ch@720P) 1080P per channel (8ch@1080P)			720P per channel (4ch@720P)	
	Record Mode	Manual / Time Scheduled / Motion Detect				
	Compression Format	H.264				
Playback	Synchronous Playback	4 channel 720P synchronous video playback 4 channel 1080P synchronous video playback			4 channel 720P synchronous video playbac	
	Playback Mode	Fast forward / Fast backward / Frame forward / Slow Play				
	HDD	1TB security hard drive (pre-installed) 2TB security grade hard drive (pre-installed)			1TB security hard drive (pre-installed)	
HDD	Capacity	Up to 4TB	1			
External Interface	Network Interface	1× 10/100 Mbps RJ	45 port	1×10/100/1000 Mbps RJ45 port	1×10/100 Mbps RJ45 port	
	USB Interface	2×USB2.0 interface for mouse and external storage 1×USB2.0/1×USB3.0 interface for			1×USB2.0 interface for mouse and	
	Button	1× Power on/off button,1× Reset button			external storage	
	Wireless Standard	1			IEEE802.11b/g/n	
Network	Wireless Security				WEP, WPA, WPA2	
	Computer Operating System	tem Microsoft Windows XP, 7, 8, 8.1, 10, Mac OS				
Software	Internet Viewing	IE, Safari				
boltmare	Smart phone	iOS, Android, 3G/4G Smartphones				
	Power Supply	DC 19V/4.75A DC 48V/1.87A			DC 12V/2A	
Physical and	Dimension(LxWxH)	234mm*234mm*52mm				
Environmental	Net Weight (g)	1200g		1100g		
Camera	Model	FI9800XE	FI9800E	FI9900E	FI9800W	
	Sensor Type	1/4" CMOS		1/2.7" CMOS	1/4" CMOS	
	Video Quality	720p (1280*720) 1080P (1920×1080)			720p (1280*720)	
Image Sensor	Wide Dynamic Range	√			1	
	Backlight Compensation	\checkmark				
	Lens Type	f:2.8mm, F:1.2	f:4mm, F:2.0	f:2.8mm, F:1.2	f:4mm, F:2.0	
Lens	IR Range	66 feet (20 meters)			
	Angle of View	75°	70°	90°	62°	
	Video Format	H.264				
	Multi-Stream	Dual streams				
Software Features	Motion Detection	\checkmark				
	UPnP	\checkmark			1	
	Day/Night	\checkmark				
Physical and Environmental	Waterproof	IP66				
	Net Weight	360g				
	Power	DC12V/1A				
	Power Consumption	<5W				
	Dimensions (LxWxH)	165(L)x67 (W)x64 (H)				
		IC, CE, RoHS, FCC, IP66				
	Certification	IC, CE, ROHS, FCC,	1200	Limited 2-year warranty		

NVRs			
		FN3109H	
Video Input	IP Video Input	9-ch HD IP cameras input	
	Comptible Camera	Foscam HD and MJPEG IP Cameras and other brand ONVIF cameras	
	Decoding Resolution	1080P(1920×1080), 960P(1280 × 960), 720P(1280 × 720), VGA(640 × 480), VGA(1280 × 1080 640 × 360), QVGA(320 × 240)	
Video Output	VGA Output	1-ch, resolution: 1920 × 1080 , 1280 × 720 ,1440 × 900 ,1024 × 768	
	HD Output	1-ch, resolution: 1920 × 1080 , 1280 × 720 ,1440 × 900 ,1024 × 768	
Hard Disk	Туре	One SATA interface for one 3.5 inch disk	
	Capacity	Up to 4TB, compatible with Seagate, Western Digital hard disk	
	Network	One 10/100 Mbps RJ45 port	
	USB 2 USB 2.0 interfaces for mouse and external storage		
External	Video Output	One HD-Out, and one VGA	
Interface	Power Input	Input One DC power supply jack	
	Button	One power on/off button, and one reset button	
	Alarm in/out	4 channel sensor inputs / 1 channel alarm output	
	Control Method	Mouse/Internet Browser	
	Display Switch	1-ch 1080P or 4-ch 720P/960P or 9-ch VGA display switch	
	Record Mode	Manual / Time Scheduled / Alarm Triggered / Motion Detect	
	Video Playback	1-ch 1080P or 4-ch 720P/960P,Fast forward / Rewind / Slow Play	
Software	PTZ	Supports Pan/Tilt/Zoom control,Optical Zoom supported	
Features	Camera Search/Management	Search camera in LAN, add camera and manage a camera list	
	Application support	Remote configuration, video browse, local recording, local and remote playback	
	Disk Management	Set the video coverage strategy, format disk	
	Motion Detection	Alarm area and schedule settings	
	User Accounts	User account management	
System	Operating System	Microsoft windows XP, 7, 8, 8.1, 10	
Requirements	Browser	IE or compatible browser;	
	Power Supply	12V/2A	
Power	Power Consumption	<12W (Without hard disks)	
	Dimensions (mm)	220 × 209 × 40mm (L x W x H)	
Physical	Net Weight	700g	
	Operating Temperature	-10°C ~ 50° (14°F ~ 122°F)	
	Operating Humidity	10% ~ 90% non-condensing	
Environmental	Storage Temperature	-20° ~ 60° C(-4°F ~ 140°F)	



