

ICSV6 99 - 6th International Congress on Sound and Vibration, 5 - 8 July 1999, Lyngby, Denmark

“Efficiency of a ballastless mass-spring-system with discrete elastic Sylodyn® bearings and of dynamically soft Sylodyn® ballast mats in a railway tunnel in Cologne”

by

R. G. Wettschureck ¹⁾, F. Breuer ²⁾, M. Tecklenburg ³⁾ and H. Widmann ⁴⁾

¹⁾ Getzner Werkstoffe GmbH, D-82031 Grünwald

²⁾ Peutz Consult GmbH, D-40599 Düsseldorf

³⁾ Getzner Werkstoffe GmbH, A-6706 Bürs/Bludenz

⁴⁾ Ed. Züblin AG, D-70567 Stuttgart

presented by

Rüdiger G. Wettschureck

ICSV6 - July 1999 • Copenhagen, Denmark

Vibration mitigation measures in a railway tunnel in Cologne

TABLE OF CONTENTS

➤ INTRODUCTION

➤ INSTALLED VIBRATION MITIGATION MEASURES

- Area 1: 170-meter section, **very high demands**: ballast mat 1, Sylodyn® DN 335,
- Area 2: 230-meter section, **extremely high demands**: mass-spring-system,
- Area 3: 570-meter section, **high demands**: ballast mat 2, Sylodyn® DN 325,

➤ STRUCTURE-BORNE NOISE MEASUREMENTS

- Procedure
- Results

➤ EFFICIENCY OF THE INSTALLED VIBRATION MITIGATION MEASURES

- Measured **INSERTION LOSS** compared with
- **CALCULATIONS** using lumped-parameter models → **SDOF systems**


➤ SUMMARY

ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne


Description of track sections and installed vibration mitigation measures

Area No.	Track position Demands	Vibration mitigation measure, Elastic element	Specification of elastic element
1	km 11.80 - 11.97 Very high	Ballast mat 1, Sylodyn® DN 335	Thickness: 35 mm Spec. static stiffness: 0.030 N/mm³ Spec. dynamic stiffness: 0.035 N/mm³
2	km 11.90 - 12.20 Extremely high	Ballastless mass-spring-system, constructed by ZÜBLIN, with discrete elastic bearings Sylodyn® N 70690/50	Thickness: 50 mm Static stiffness: 14 MN/m Dynamic stiffness: 17 MN/m
3	km 12.20 - 12.77 High	Ballast mat 2, Sylodyn® DN 325	Thickness: 25 mm Spec. static stiffness: 0.030 N/mm³ Spec. dynamic stiffness: 0.045 N/mm³

ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne



ICSV6 - July 1999 • Copenhagen, Denmark
Vibration mitigation measures in a railway tunnel in Cologne



Lyngby, July 1999

Rüdiger G. Wettschureck

5

ICSV6 - July 1999 • Copenhagen, Denmark
Vibration mitigation measures in a railway tunnel in Cologne




Lyngby, July 1999

Rüdiger G. Wettschureck


6

ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne




Top view of the Ballastless Mass-Spring-System, constructed by ZÜBLIN

ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne



Cross Section of the Ballastless Mass-Spring-System, constructed by ZÜBLIN


ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne



Load deflection curve of the elastic bearing, type Sylodyn® N 70690/50 for the ballastless mass-spring-system in area 2.

◆◆ Static secant stiffness:
 $c_{stat} \approx 14 \text{ MN/m}$

ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne



Static and dynamic stiffness of the elastic bearing, type Sylodyn® N 70690/50 for the mass-spring-system as a function load:

— Static tangential stiffness;
 — Dynamic stiffness at 10 Hz.

ICSV6 - July 1999 • Copenhagen, Denmark
Vibration mitigation measures in a railway tunnel in Cologne



Lyngby, July 1999

Rüdiger G. Wettschureck

11

ICSV6 - July 1999 • Copenhagen, Denmark
Vibration mitigation measures in a railway tunnel in Cologne



Lyngby, July 1999

Rüdiger G. Wettschureck

12

ICSV6 - July 1999 • Copenhagen, Denmark
Vibration mitigation measures in a railway tunnel in Cologne



Lyngby, July 1999

Rüdiger G. Wettschureck

13

ICSV6 - July 1999 • Copenhagen, Denmark
Vibration mitigation measures in a railway tunnel in Cologne




Lyngby, July 1999

Rüdiger G. Wettschureck

14

ICSV6 - July 1999 • Copenhagen, Denmark

Vibration mitigation measures in a railway tunnel in Cologne



Static tangential stiffness and dynamic stiffness at different frequencies of the Syldyn® DN 335 ballast mat as a function of specific load *).

*) According to Müller-BBM Report No. 32.242/12, July 1996.

— Value of the dynamic stiffness which is used for calculation of the insertion loss:

$$c_{\text{dyn}} \approx 0.035 \text{ N/mm}^3$$

ICSV6 - July 1999 • Copenhagen, Denmark

Vibration mitigation measures in a railway tunnel in Cologne



ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne




Lyngby, July 1999

Rüdiger G. Wettschureck

17

ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne



Static tangential stiffness and dynamic stiffness at different frequencies of the Syldyn® DN 325 ballast mat as a function of specific load *).

*) According to Müller-BBM Report No. 32.242/9, July 1996.

— Value of the dynamic stiffness which is used for calculation of the insertion loss:


$$c_{dyn} \approx 0.045 \text{ N/mm}^3$$

Lyngby, July 1999

Rüdiger G. Wettschureck

18


ICSV6 - July 1999 • Copenhagen, Denmark
Vibration mitigation measures in a railway tunnel in Cologne



1/3-octave-band spectra of the velocity level, measured at the tunnel wall during train passages, before and after modification of the track: Average track 1 + 2.

- Before modification: Average of all 24 measuring points;
- After modification: 6 measuring points in areas 1, 2 and 3 at a time;
- △-△** 3: Ballast mat Sylodyn® DN 325;
- 1: Ballast mat Sylodyn® DN 335;
- 2: Mass-spring-system.

ICSV6 - July 1999 • Copenhagen, Denmark
Vibration mitigation measures in a railway tunnel in Cologne



Measured and calculated insertion loss of the vibration mitigation measure in area 1: Ballast mat Sylodyn® DN 335.

— Measurement: average track 1+2;


Calculation *): Dynamic stiffness of ballast mat $s'' \approx 0.035 \text{ N/mm}^3$;

Parameter:
 unsprung mass M of wheel set.

*) According to Wettschureck, R. and Kurze, U. J., Acustica 58 (1985), pp. 177-182

ICSV6 - July 1999 • Copenhagen, Denmark

Vibration mitigation measures in a railway tunnel in Cologne




Measured and calculated insertion loss of the vibration mitigation measure in area 2: mass-spring-system (MSS).

- Measurement: average track 1+2;
- Calculation, Mass of MSS-slab per meter of track: 4000 kg/m; Dynamic stiffness of elastic bearing: Approx. 17 MN/mm at 10 – 20 Hz;
- Restriction because of the validity limits of the used SDOF model.

ICSV6 - July 1999 • Copenhagen, Denmark

Vibration mitigation measures in a railway tunnel in Cologne




Measured and calculated insertion loss of the vibration mitigation measure in area 1: Ballast mat Syloydyn® DN 325.

- Measurement: average track 1+2;
- Calculation^{*)}: Dynamic stiffness of ballast mat $s'' \approx 0.045 \text{ N/mm}^2$;
- Parameter: unsprung mass M of wheel set.

^{*)} According to Wettschureck, R. and Kurze, U. J., Acustica 58 (1985), pp. 177-182


ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne



Measured insertion loss of the installed vibration mitigation measures in areas 1, 2 and 3;

- Area 2:
Mass-spring-system;
- ◇—◇ Area 1: ballast mat 1,
Sylodyn® DN 335;
- △—△ Area 3: ballast mat 2,
Sylodyn® DN 325.

ICSV6 - July 1999 • Copenhagen, Denmark
 Vibration mitigation measures in a railway tunnel in Cologne



Peak of KB-values according to DIN 4150, part 2, measured in a house situated diagonally across the railway tunnel during train passages, before and after installation of the mass-spring-system.

ICSV6 - July 1999 • Copenhagen, Denmark

Vibration mitigation measures in a railway tunnel in Cologne

SUMMARY

- Two types of **highly-effective ballast mats and a mass-spring-system** were installed over a total length of 970 meters in both tracks of a railway tunnel in Cologne in order to reduce the vibrations caused by the rail traffic.
- The mitigation measures, in particular **the elastic components** applied for vibration mitigation **are described**.
- **The efficiency of the vibration mitigation measures, i.e. their insertion loss, was determined by means of structure-borne noise measurements** carried out in the tunnel during train passages before and after installation, as well as in a residential unit which was seriously affected.
- **The insertion loss** of the installed vibration mitigation measures **was also calculated** using lumped-parameter models ⇒ **SDOF systems**.
- **The measurement results show a very good consistency with the calculation** and completely confirm the high expectations placed in the vibration mitigation measures.

ICSV6 99 - 6th International Congress on Sound and Vibration, 5 - 8 July 1999, Lyngby, Denmark

End of Presentation