

AD-A269 500



2

DODPOPHM/USA/DOD/NADTR92108
REVISION A

PERFORMANCE ORIENTED PACKAGING TESTING
OF
MK 635 MOD 0 SHIPPING AND STORAGE CONTAINER
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS

Author:
Kerry J. Libbert
Mechanical Engineer

Performing Activity:
Naval Surface Warfare Center
Code 4045
Crane, Indiana 47522-5001

Date
August 1993

FINAL

DTIC
ELECTE
SEP. 20. 1993
S B D

DISTRIBUTION STATEMENT A
Approved for public release
Distribution Unlimited

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Surface Warfare Center
Code 4024
Crane, Indiana 47522-5001

93 9 16 081


93-21716
[Barcode]

46

Prepared by:


K. J. Libbert

Reviewed by:


R. F. Sanders

Reviewed by:


J. W. Puckett

Approved by:


D. N. Montgomery

**Form Approved
OMB No 0704-0188**

Public reporting burden of this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE August 1993	3. REPORT TYPE AND DATES COVERED POP Test, Revision A	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of MK 635 Mod 0 Shipping and Storage Container for Packing Group II Solid Hazardous Materials			5. FUNDING NUMBERS	
6. AUTHOR(S) Kerry J. Libbert				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center Plastics and Packaging Applications Branch (Code 4045) 300 Highway 361 Crane IN 47522-5001			8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR92108 Revision A	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center Countermeasures Branch (Code 4027) 300 Highway 361 Crane IN 47522-5001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above	
11. SUPPLEMENTARY NOTES N/A				
12a. DISTRIBUTION/AVAILABILITY STATEMENT			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Qualification tests were performed to determine whether the in-service MK 635 Mod 0 Shipping and Storage Container could be utilized to contain properly dunnaged solid type hazardous materials weighing up to a gross weight of 32 kg (70.5 pounds). The tests were conducted in accordance with Performance Oriented Packaging (POP) requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178. The MK 635 has conformed to the POP performance requirements; i.e., the container successfully retained its contents throughout the specified tests.				
14. SUBJECT TERMS POP Test of MK 635 Mod 0 Shipping and Storage Container			15. NUMBER OF PAGES 6	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UL	19. SECURITY CLASSIFICATION OF ABSTRACT UL	20. LIMITATION OF ABSTRACT UL	

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the MK 635 Mod 0 Shipping and Storage Container meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The objectives were to evaluate the adequacy of the container in protecting the hazardous materials.

The MK635 Mod 0 Shipping and Storage Container is a steel drum with a removeable lid. Each container lid was secured with a V-retainer and a lead seal during the testing.

TESTS PERFORMED

1. Drop Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Six containers were used during the test series, one for each drop. Three drops were conducted at each orientation listed below from a height of 1.2 meters:

- a. 45° from vertical on V-retainer closure
- b. Horizontal on container seam (closure of V-retainer positioned 180° from seam)

The tests were performed at ambient temperature (70° ± 20°F). The contents of the container should be retained within its packaging and exhibit no damage liable to affect safety during transport.

2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. Three different containers were used, each with a stack weight of 1000 pounds. This represents the weight imposed on the bottom container of a ten-foot stack of like containers weighing 70.5 pounds each. The test was performed for 24 hours. After the allowed time, the weight was removed and the container examined. Any leakage, deterioration, or distortion which could adversely affect transport or reduce its strength or cause instability in stacks of packages is cause for rejection.

3. Base Level Vibration Test

One sample container was loaded with live Flexible Linear Shaped Charges and closed as for shipment. The container was subjected to standard transportation vibration testing for a period of six hours. The test was performed for two hours in each of the three principal axes.



Figure 1. MK 635 Mod 0 containers
after stack test.

PASS/FAIL (UN CRITERIA)

The criteria for passing the drop test is outlined in Title 49 CFR, Part 178, Subpart M, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, the entire contents are retained by an inner packaging (e.g. a plastic bag) even if the closure on the top head of the drum is no longer sift proof.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Part 178, Subpart M, Sec. 178.606: No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Vibration Test

The criteria for passing the Vibration Test is outlined Title 49 CFR, Part 178, Subpart M, Sec. 178.608: Immediately following the period of vibration, each package must be removed from the platform, turned on its side and observed for any evidence of leakage. A packaging passes the vibration test if there is no rupture or leakage from any of the packages. No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

TEST RESULTS

1. Drop Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Vibration Test

Satisfactory.

DISCUSSION

DTIC QUALITY INSPECTED 3

1. Drop Test

After each drop the container was inspected for any damage which would be cause for rejection. The containers were slightly damaged during the tests, but all V-retainers and lead seals remained fastened securely.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification _____	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

2. Stacking Test

Three containers were individually tested. Each container was visibly inspected after the 24-hour period was over. There was no leakage, distortion, or deterioration to the container as a result of this test. The containers are shown in figure 1.

3. Vibration Test

Immediately following the vibration test, each container was removed from the platform, turned on its side and observed for any evidence of leakage. There was no evidence of leakage of contents.

REFERENCE MATERIAL

Code of Federal Regulations Title 49 CFR, Parts 107-178.

DISTRIBUTION LIST

Commander
Crane Division
Naval Surface Warfare Center
Code 4045 and Code 4024
Crane, IN 4 22-5000

Commanding Officer
Naval Weapons Station Earle
Code 50 and Code 50232
Colts Neck, NJ 07722-5000

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDAC (Virginia Guidi)
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Commander
U.S. Army Armament, Research, Development and Engineering
Center
SMCAR-ESK
Rock Island, IL 61299-7300

Defense General Supply Center
DDRV-TMPA (Dave Gay)
Richmond, VA 23297-5000

DATA SHEET

CONTAINER: MK635 Shipping and Storage Container	POP MARKING: <table border="1"><tr><td>u</td><td>1A2/Y32/S/**</td></tr><tr><td>n</td><td>USA/DOD/NAD</td></tr></table>	u	1A2/Y32/S/**	n	USA/DOD/NAD
u	1A2/Y32/S/**				
n	USA/DOD/NAD				
Type: 1A2	UN Code: See Table I				
Drawing Number: 53711-3193400	Material: Steel				
Gross Weight: 32.0 kg (70.5 pounds)	Dimensions: 1.31 m L x .20 m DIA (51.56" L x 8.0" DIA)				
Closure (Method/type): Screw-on cap	Tare Weight: 4.6 kg (10.1 pounds)				
Additional Description: Lid secured with V-retainer and lead seal (MS51938-5) during tests. Alternate container nomenclature "CONTAINER, SHIPPING AND STORAGE, FOR NATO SEA GNAT", Drawing 53711-6133117.					

PRODUCTS: See Table I					
Proper Shipping Name: See Table II					
United Nations Number: See Table I					
United Nations Packing Group: II					
Physical State: Solid					
Amount Per Container: See Table I					
Net Weight: Varies					

TEST PRODUCT: Name: Sand Physical State: Solid					
Size: N/A					
Quantity: N/A					
Dunnage: None Gross Weight: 32.0 kg (70.5 lbs.)					

TABLE I

NALC/ DODIC	NSN	ITEM	PACKING DRAWING	HAZ. CL.	UN NO.	# CNTR.	PER GROSS	WT.
3W80	1320-01-247-0627	MK216-0 RF CTG.	6348315	1.3C	0186	1	65.0	
3W80	1320-01-352-3678	MK216-1 RF CTG.	6813901			1	65.0	
4W35	1320-01-258-0290	MK186-0/E 5.125 CTG.	5186484	1.3J	0247	1	60.0	
4W61	1320-01-263-2854	MK229-0 PRAC. CTG.	5177715	1.4S	0173	1		
4W61	1320-01-301-5651	MK229-0 PRAC. CTG.	6375535	1.4S	0173	1	62.0	
5W59	1320-01-264-5441	MK186-2 5.125 CTG.	5388289			1		
7W69	1320-01-158-4113	MK182-2 5.125 CTG.	3193399	1.4S	0173	1	60.0	
9W22	1320-01-185-8157	MK214-0 RF CTG.	6133075	1.4S	0173	1	62.0	
9W22	1320-01-328-5098	MK214-1 RF CTG.	6775105			1	62.0	
EW75	1320-01-074-7046	MK186-0 5.125 CRG.	5186484	1.3G	0010	1	60.0	
EW75	1320-01-217-8724	MK186-1 5.125 CTG.	5388257	1.3G	0054	1	60.0	
EW76	1320-01-045-7859	MK182-1 5.125 CTG.	3193399	1.4S	0173	1	60.0	
EW77	1320-01-045-7860	MK193-0 5.125 CTG.	*3193399	1.4S	0173	1	60.0	
EW77	1320-01-095-9772	MK193-1 5.125 CTG.	5177715	1.4S	0173	1	62.0	
ML09	1375-01-079-3899	20 GR/FT FLEX CHG.	5206261	1.1D	0288	18	19.7	
ML10	1375-01-079-3900	30 GR/FT FLEX CHG.	5206262	1.1D	0288	18	21.3	
ML11	1375-01-079-3901	40 GR/FT FLEX CHG.	5206263	1.1D	0288	18	22.8	
ML12	1375-01-079-3902	60 GR/FT FLEX CHG.	5206264	1.1D	0288	18	26.0	
ML13	1375-01-079-3903	75 GR/FT FLEX CHG.	5206265	1.1D	0288	18	28.4	
ML14	1375-01-079-3904	125 GR/FT FLEX CHG.	5206266	1.1D	0288	15	33.0	
ML15	1375-01-079-3905	225 GR/FT FLEX CHG.	5206267	1.1D	0288	15	46.3	
ML16	1375-01-079-3906	300 GR/FT FLEX CHG.	5206268	1.1D	0288	15	54.2	
ML17	1375-01-079-3907	400 GR/FT FLEX CHG.	5206269	1.1D	0288	9	48.2	
ML18	1375-01-079-3908	500 GR/FT FLEX CHG.	5206270	1.1D	0288	9	56.2	
ML19	1375-01-079-3909	600 GR/FT FLEX CHG.	5206271	1.1D	0288	9	64.1	
N/A	**	5.125 CRG.	5388375	1.2G	0171	1	57.0	
N/A		EX237-0 5.125 CRG.	***	1.3J	0247	1	60.0	

* ALTERNATE PACKING DRAWING 53711-5177715

** NATO NUMBER 1320-12-323-1479

*** PACKING SKETCH (53711) 90-D-1536

TABLE II

UN NO.	PROPER SHIPPING NAME
-----------	-------------------------

0010 AMMUNITION, INCENDIARY

0054 CARTRIDGES, SIGNAL

0171 AMMUNITION, INCENDIARY

0173 RELEASE DEVICES, EXPLOSIVE

0186 ROCKET MOTORS

0247 AMMUNITION, INCENDIARY

0288 CHARGES, SHAPED, FLEXIBLE, LINEAR