## Instrument Hire Catalogue



"the complete engineering and process solution" ®

January 2017

Phone: 02920 815 000 Fax: 02920 813 051 Email: sales@mjwilsongroup.com

**DELIVERY / COLLECTION OPTIONS** 

DELIVER & PICK UP VIA COURIER: £25

**COLLECTION AVAILABLE FROM WALES OFFICE** 

Pressure	£	per week
	Digital Test Gauge Druck DPI 104 0-10Bar, 0-200 Bar & 0-700 Bar	£60.00
Y	0-10Bar, 0-200 Bar & 0-700 Bar 0-10Bar, 0-200 Bar & 0-700 Bar	£65.00
Ø	Mechanical High accuracy (0.25% F.S) Test Gauges Wide selection of ranges	£45.00
	DPI 601 0-2 Bar Vac DPI 601 0-7 Bar DPI 601 0-20 Bar DPI 601 0-10 Bar	£80.00
DPI 610	IS Versions         DPI 601 IS 0-20 Bar         DPI601 IS 0-7 Bar           DPI 601 IS 0-200 mBar         DPI610 IS -1-20 Bar           DPI 601 IS 0-10 Bar Vac         DPI615 IS 0-400 Bar           DPI 615 IS -1-20 Bar	£97.00
<b>L</b>	<b>Druck DPI 611</b> -1-1 BarG -1-7 BarG -1-20BarG	£125.00
	DPI 620	£130.00
- " " " " " " " " " " " " " " " " " " "	IS Versions DPI 620 IS	£150.00
	PV623	£70.00
20 20	IS Versions PV622IS	£85.00
	0-2 BarG 0-20 BarG 0-100 BarG 0-700 BarA	£60.00
	IS Versions0-20BarG0-100BarG	£65.00
	Hand Pumps -1 -0 Bar 0-2 Bar 0-700Bar	£35.00 £35.00 £45.00
	DPI 705 0-70mBarG	£40.00
Edwards Speedware	<b>Edwards Speedivac Vacuum Pump</b> Maximum vacuum approx. 50mbarA Supply 230 VAC.	£60.00
	Wide selection of Pressure transmitters Which can be hired individually or attached to our recorders/loggers	£20.00

Thermal Cameras         InfraCam       £80.00         Filr T       £120.00         Filr T       £120.00         Filr E40BX       £220.00         Filr E40BX       £250.00         Filr E40BX       £350.00         POP 811 RTD Calibrator       £50.00         Measures or simulates RTD sensors       £50.00         Probe Sizes 6mm,5mm, 4mm       £60.00         Probe Sizes 6mm,5mm, 4mm       £140.00         130m, 10mm, 8mm, 5mm and 3.5mm dia. Holes       £140.00         All 157mm deep       Also includes         Stirred Liquid Mode with Liquid Container Kit       £80.00         Image: Stirred Liquid Mode with Liquid Container Kit       £150.00         Resolution: -0.0001°C       Sensor Calibration: -200°C to +300°C         Sensor Calibration: -200°C to +300°C       £150.00         Reference Probes       For use with the TT1-22 Indicator -70 to 450C         -70 to 450C       £20.00         Wireless temperature and humidity Logging (see recording and logging section         Wireless temperate and humidity Logging (see recording and logging section	Temperature an	d Humidity	£ per week
Fir IZ       É120.00         Fir E40BX       É220.00         Fir E8       É250.00         Fir T440       É350.00         POIDE 811 RTD Calibrator       É50.00         Measures or simulates RTD sensors       É60.00         Probe Sizes 6mm,5mm, 4mm       É60.00         Probe Sizes 6mm,5mm, 4mm       É140.00         Ali I57mm deep Also includes       Stirred Liquid Mode with Liquid Container Kit         Calibration sand Bath       £80.00         TTI-22 True Temperature Indicator Accuracy: - 0.001 °C Resolution: - 0.0001°C Sensor Calibration: - 0.0001°C Sensor Calibration: - 0.0001°C       £150.00         Reference Probes For use with the TTI-22 Indicator -70 to 450C       £45.00         Mide selection of with Transmitters, which can be hired individually or attached to our recorders/loggers.       £20.00         Wireless temperate and humidity Logging (see recording and       £20.00			-
Flir E406X       £220.00         Flir IF E8       £250.00         Flir T440       £350.00         DPI 811 RTD Calibrator       £50.00         Measures or simulates RTD sensors       £60.00         Probe Sizes 6mm,5mm,4mm       £140.00         SiSO Tech Hot Blocks       £140.00         13mm, 10mm, 8mm, 5mm and 3.5mm dia. Holes       £140.00         All 157mm deep       Also includes         Stirred Liquid Mode with Liquid Container Kit       £80.00         Image: Calibration = 0.0001°C       Reference Probes         Reference Probes       For use with the TT1-22 Indicator       £150.00         Image: Calibration = 0.0001°C       Sensor Calibration: -0.0001°C       £150.00         Reference Probes       For use with the TT1-22 Indicator       £150.00         Image: Calibration of with Transmitters, which can be hired individually or attached to our recorders/loggers.       £20.00         Wireless temperate and humidity Logging (see recording and       £20.00	¢FLIR ¢FLIR	InfraCam	£80.00
Flir E406X       £220.00         Flir IF E8       £250.00         Flir T440       £350.00         DPI 811 RTD Calibrator       £50.00         Measures or simulates RTD sensors       £60.00         Probe Sizes 6mm,5mm,4mm       £140.00         SiSO Tech Hot Blocks       £140.00         13mm, 10mm, 8mm, 5mm and 3.5mm dia. Holes       £140.00         All 157mm deep       Also includes         Stirred Liquid Mode with Liquid Container Kit       £80.00         Image: Calibration = 0.0001°C       Reference Probes         Reference Probes       For use with the TT1-22 Indicator       £150.00         Image: Calibration = 0.0001°C       Sensor Calibration: -0.0001°C       £150.00         Reference Probes       For use with the TT1-22 Indicator       £150.00         Image: Calibration of with Transmitters, which can be hired individually or attached to our recorders/loggers.       £20.00         Wireless temperate and humidity Logging (see recording and       £20.00		Flir I7	£120.00
Flir E8       £250.00         Flir T440       £350.00         DPI 811 RTD Calibrator       £50.00         Measures or simulates RTD sensors       £60.00         Probe Sizes 6mm,5mm, 4mm       £60.00         Probe Sizes 6mm,5mm, 4mm       £60.00         Probe Sizes 6mm,5mm, 4mm       £140.00         ISO Tech Hot Blocks       13mm, 10mm, 8mm, 5mm and 3.5mm dia. Holes         All 157mm deep       Also includes         Stirred Liquid Mode with Liquid Container Kit       £80.00         Image: Calibration sand Bath       £80.00         Image: Calibration: - 0.001 °C       Resolution: - 0.001 °C         Sensor Calibration: - 200°C to +300°C       £150.00         Image: Calibration: - 0.001 °C       Sensor Calibration: - 200°C to +300°C         Image: Calibration: - 0.001 °C       Sensor Calibration: - 200°C to +300°C         Image: Calibration: - 0.001 °C       Sensor Calibration: - 200°C to +300°C         Image: Calibration: - 0.001 °C       Sensor Calibration: - 200°C to +300°C         Image: Calibration: - 0.001 °C       Sensor Calibration: - 200°C to +300°C         Image: Calibration: - 0.001 °C       Sensor Calibration: - 200°C to +300°C         Image: Calibration: - 0.001 °C       Sensor Calibration: - 200°C to +300°C         Image: Calibration: - 0.001 °C       Sensor Calibration: - 20			
Flir T440       £350.00         Image: Problem in the series of simulates RTD sensors       £50.00         Image: Problem in the sensors       \$250.00         Image: Problem in the sensors       \$260.00         Image: Problem in the sensor in the senset in the sensor in the sensor in the senso			
DPI 811 RTD Calibrator Measures or simulates RTD sensors       £50.00         Image: Construction of the sensor			
Measures or simulates RTD sensors       £60.00         Probe Sizes 6mm,5mm, 4mm       £60.00         Probe Sizes 6mm,5mm, 4mm       £140.00         ISO Tech Hot Blocks       £140.00         I3mm, 10mm, 8mm, 5mm and 3.5mm dia. Holes       £140.00         All 157mm deep       Also includes         Stirred Liquid Mode with Liquid Container Kit       £80.00         ISO Tech Hot Blocks       £150.00         ISO Tech Hot Blocks       £150.00         ISO Tech Hot Blocks       £			
Probe Sizes 6mm,5mm, 4mm       ISO Tech Hot Blocks       £140.00         ISO Tech Hot Blocks       13mm, 10mm, 8mm, 5mm and 3.5mm dia. Holes       £140.00         All 157mm deep       Also includes       Stirred Liquid Mode with Liquid Container Kit         Image: Calibration sand Bath       £80.00         Image: Calibration: -0.001 °C       Resolution: - 0.0001 °C         Sensor Calibration: -200°C to +300°C       £150.00         Image: Calibration: -200°C to +300°C       £45.00         Image: Calibration: -200°C to +300°C       £45.00         Image: Calibration of with Transmitters, which can be hired individually or attached to our recorders/loggers.       £20.00         Image: Calibration of with Transmitters, which can be hired individually or attached to our recorders/loggers.       £20.00			230.00
13mm, 10mm, 8mm, 5mm and 3.5mm dia. Holes         All 157mm deep         Also includes         Stirred Liquid Mode with Liquid Container Kit         Calibration sand Bath       £80.00         Image: Calibration sand Bath       £150.00         Resolution: - 0.001 °C       Sensor Calibration: -200°C to +300°C         Sensor Calibration: -200°C to +300°C       £150.00         Image: Calibration: -200°C to +300°C       £45.00         Image: Calibration sand Bath       £20.00         Image: Calibration sand Bat	1978, Million HDRC		£60.00
13mm, 10mm, 8mm, 5mm and 3.5mm dia. Holes         All 157mm deep         Also includes         Stirred Liquid Mode with Liquid Container Kit         Calibration sand Bath       £80.00         Image: Calibration sand Bath       £150.00         Resolution: - 0.001 °C       Sensor Calibration: -200°C to +300°C         Sensor Calibration: -200°C to +300°C       £150.00         Image: Calibration: -200°C to +300°C       £45.00         Image: Calibration sand Bath       £20.00         Image: Calibration sand Bat		ISO Tech Hot Blocks	£140.00
Calibration sand Bath       £80.00         Image: Comparison of the second stress of the s	ISOCAL-6	All 157mm deep Also includes	
Image:		Stirred Liquid Mode with Liquid Container Kit	
Accuracy: - 0.001 °C         Resolution: - 0.0001°C         Sensor Calibration: -200°C to +300°C         Sensor Calibration: -200°C to +300°C         Reference Probes         For use with the TTI-22 Indicator         -70 to 450C         Endote         Wide selection of with Transmitters, which can be hired individually or attached to our recorders/loggers.         Wireless temperate and humidity Logging (see recording and		Calibration sand Bath	£80.00
Accuracy: - 0.001 °C         Resolution: - 0.0001°C         Sensor Calibration: -200°C to +300°C         Sensor Calibration: -200°C to +300°C         Reference Probes         For use with the TTI-22 Indicator         -70 to 450C         Endote         Wide selection of with Transmitters, which can be hired individually or attached to our recorders/loggers.         Wireless temperate and humidity Logging (see recording and		TTI-22 True Temperature Indicator	£150.00
Resolution: - 0.0001°C         Sensor Calibration: -200°C to +300°C         Reference Probes         For use with the TTI-22 Indicator         -70 to 450C         Emperature Probes         Wide selection of with Transmitters, which can be hired individually or attached to our recorders/loggers.         Wireless temperate and humidity Logging (see recording and	Surger State		
Sensor Calibration: -200°C to +300°C         Reference Probes         For use with the TTI-22 Indicator         -70 to 450C         É20.00         Wide selection of with Transmitters, which can be hired individually or attached to our recorders/loggers.         Wireless temperate and humidity Logging (see recording and	22.712*	1	
For use with the TTI-22 Indicator       £45.00         -70 to 450C       -70 to 450C         Image: Constraint of the selection of with Transmitters, which can be hired individually or attached to our recorders/loggers.       £20.00         Image: Wireless temperate and humidity Logging (see recording and second process)       Wireless temperate and humidity Logging (see recording and second process)	ee	Sensor Calibration: -200°C to +300°C	
-70 to 450C Temperature Probes Wide selection of with Transmitters, which can be hired individually or attached to our recorders/loggers. Wireless temperate and humidity Logging (see recording and			
Wide selection of with Transmitters, which can be hired individually or attached to our recorders/loggers.         Wireless temperate and humidity Logging (see recording and	00.000		£45.00
		Wide selection of with Transmitters, which can be hire	
			nd

<b>Electronic Test</b>	Equipment	£ per week
475	Instrument Communicators	
	Emerson 475 Communicator with Foundation Fieldbus	£150.00
	Emerson 375 Communicator with Foundation Fieldbus	£130.00
	Emerson 375 Communicator	£100.00
	Honeywell STS 102	£150.00
	Oscilloscopes	
	Bench mounted	£35.00
	Portable	£40.00
C.A.6334B	Power Analysis	
	Chauvin Arnoux CA 8334B Mains-analysis device	£180.00
	Chauvin Arnoux CA 8335 Mains-analysis device	£240.00
	PEL 103 one, two (split phase) and three phase (Y, $\Delta$ ) power/energy data logger	£150.00
	Fluke 771 milliamp clamp meter	£40.00
	EX623 - 400A Dual Input AC/DC Clamp Meter + NCV + IR	£40.00
01WLerze	Thermometer	210.00
	EX845 - 1000A AC/DC True RMS Clamp/DMM with IR	£40.00
	Thermometer	210100
-		
	Meters	
	Fluke 87 III	£40.00
	Fluke 725 Ex	£120.00
	Capacitance meters	£35.00
	METRIX MTX3281-BT Digital Multimeter	£30.00
Construction of the second sec	Druck UPS 3 IS	£25.00
	The UPS III IS is a rugged and extremely compact loop Calibrator.	
	CA 7041/2 LAN Network Tester	£200.00
	The CA7041/2 is a Cat 5 LAN tester used to certify compliance	
	of the network. With its simple easy to use features such as	
	pass or fail lights, battery indicator and voltage presence	
	warning indicator the CA 7042 can be used with little training	
	needed.	
	Megger BM80 Insulation Tester	£40.00
	50V 100V 250V 500V 1000V	
	The Bicotest T511 "Faultman" is a Cable Fault Locator,	а
1	small handheld pulse-echo instrument which provides a visu	
	indication of cable faults. Full cable trace and measurement u	р

Recording and I	oaaina £	per week
	Circular mechanical chart recorders Range of pressure options Range of temperature ranges	£60.00
	Honeywell DPR250mm Chart Recorder Records up to 32 inputs. Chart 180mm/250mm. Media Roll or fanfold. Input types T/C, RTD, mV, mA. Power supply 110 or 240Vac. Ranges fully user configurable. Prints user defined messages, date and time. 60 assignable alarms.	£150.00
	<b>Honeywell SX/QX/QXe Eztrend</b> USB ports for keyboard and mouse. Up to 48 analogue inputs. Industrial rugged touch screen with rapid navigation. Independent chart and logging speeds. Remote access – advanced software data analysis at your PC. Screen sizes: 12" / 5.5" / 5".	£140.00
	<b>Nanodac</b> Recorder/controller offers the ultimate in graphical recording combined with PID control for a box of its size. The compact ¼ DIN panel mount unit offers four high accuracy universal inputs for data recording and PID control. This secure data recording device with accurate control is enhanced by a full colour, ¼ VGA display to bring a crystal clear operator interface to even the smallest of machines.	£70.00
	<b>The SL7000</b> data loggers have a very flexible combination of inputs from a single temperature up to 4 universal inputs each of which can be individually configured to accept any combination of the following input types: RTD / Pt100, Thermocouple (Types J, K, T, R, S, B, N) (isolated tip), mA (4-20mA 4/20mA), Volts, mV, Thermistors, Slidewire, Cu, Ni	£40.00
	<b>Button Loggers</b> Hire a kit of five SL52T data loggers, USB interface and TempIT-Pro software. The SL52T loggers are single channel, temperature data logggers that record the time, date and precise temperature for later retrieval and analysis. The data loggers are used in food, pharmaceutical, building management and other industries for temperature monitoring.	£35.00
	<b>Wireless data logging</b> Wirelessly log and recorded temperature, humidity, mA (4-20mA 4/20mA), Volts, mV to a laptop in a central location, on which the data and be displayed in graphical form and printed out on PDF's	

Measurement	£p	er week
Provide Anticology Provide Antic	<b>Micromotion CMF100-2700 Coriolis Mass Flowmeter</b> Flow and Density, Size 1", Liquid and Gas, High Accuracy Applications. Outputs: 4 – 20mA, Modbus, HART®.	£290.00
	<b>KATflow 200 Ultrasonic Flowmeter</b> Transit-time correlation measurement. Light-weight, hand-held unit, graphic display, easy to install clamp-on sensors with no process interruption. Suitable for all commonly used pipe materials. Ranging from 10mm to 3m diameters. Fully charged battery giving 24 hr operation. Internal data logger, operating system windows 2000, NT, XP, and Vista	£280.00
	PT878 - Portable Ultrasonic Liquid Flow Meter The PT878 is one of the most powerful portable ultrasonic liquid flow meters available. It measures flow from outside plastic, metal or concrete-lined pipes nonintrusively, so there's no pressure drop, leaks or contamination. Patented correlation algorithms resolve transit-time signals like no other flow meter	£280.00
	<b>ETI8601 pH/mV Meter</b> The ETI 8601 is a microprocessor based digital pH meter measuring pH over the range of 0 to 14pH with a resolution of 0.01pH	£92.00
	<b>AQUACal 2000</b> water conductivity Meter Pure Water Conductivity and Resistivity Portable Kit	£92.00
	Light meter, dual range 500/2000 lux analogue display	£25.00
Autom P	Autofim 2 - Intrinsically safe detector for hydrocarbon gases	£420.00
	<b>HI 9828 Multiparameter meter</b> Measurement of dissolved oxygen, pH, ORP, conductivity and related parameters, temperature, atmospheric pressure and seawater specific gravity	£185.00

## **DELIVERY / COLLECTION OPTIONS**

## **DELIVER & PICK UP VIA COURIER: £25**

## **COLLECTION AVAILABLE FROM WALES OFFICE**