

Intelect® Electrotherapy



2009



Engineered to meet your electrotherapy and ultrasound needs, the Intelect Legend XT delivers a comprehensive range of therapies in a single, award-winning, state-of-the-art unit.

Intelect® Legend XT System

- 2763 – 2-Channel Electrotherapy
- 2786K – 4-Channel Electrotherapy
- 2760K – 2-Channel Combination
- 2788K – 4-Channel Combination

Standard Accessories:

- 27465 – Patient Data Cards (1x)
- 27383 – 5 cm² Soundhead Applicator
- 27312 – Electrotherapy Leadwire Channel 1
- 27313 – Electrotherapy Leadwire Channel 2
- 42044 – DURA-STICK® II 2.75" (7 cm) Electrodes (4x)
- 4248 – Conductor™ Ultrasound Gel - 8.5 oz (250 ml) Bottle (1x) (Combination Systems only)

Intelect Legend XT System with Cart

- 2793K – 2-Channel Electrotherapy
- 2797K – 4-Channel Electrotherapy
- 2791K – 2-Channel Combination
- 2795K – 4-Channel Combination

Optional Accessories

- 2758 – Light Therapy Module
- 2781 – Channel 3 and 4 Electrotherapy Module
- 2780ASY – Therapy Cart (assembled)
- 2767 – Battery Module
(Self-contained Nickel Metal Hydride battery automatically and continually charges when unit is plugged into mains power supply.)
- 27469 – Patient Interrupt Switch (Ch 1 & 2)
- 27470 – Patient Interrupt Switch (Ch 3 & 4)
- 72852 – Black Rubber Carbon 3" (8 cm) Electrodes (2x)
- 72853 – Red Rubber Carbon 3" (8 cm) Electrodes (2x)
- 1264 – Nylatex® Wrap, 2.5" x 24" (3x)
- 27465 – Patient Data Cards (25/pack)
- 27508 – Operator Remote Channels 1 and 2
- 27079 – Operator Remote Channels 3 and 4
- 27381 – 1 cm² Sound Head Applicator
- 27382 – 2 cm² Sound Head Applicator
- 27384 – 10 cm² Sound Head Applicator
- 27133 – Intelect Legend XT Carry Bag
- 28205 – 19 Diode Cluster Applicator, 325mW
Total: no Lasers, 6 x 670nm 10mW LED, 7 x 880nm 25mW LED, 6 x 950nm 15mW LED
- 28206 – 33 Diode Cluster Applicator, 565mW
Total: no Lasers, 12 x 670nm 10mW LED, 13 x 880nm 25mW LED, 8 x 950nm 15mW LED

Standard Features

- Patented award-winning, ergonomic modular design
- Easy-to-add-to modularity allows the addition of two additional Channels of Electrotherapy or a Battery Module
- High contrast 5" (13 cm) FSTN LCD monochromatic user interface
- Two independent electrotherapy channels, expandable to four independent channels
- Multiple waveform electrotherapy - six clinical waveforms: Interferential, Premodulated, High Volt, Russian, Microcurrent, and Symmetrical Biphasic
- Documentation of treatment data with Patient Data Cards
- User Defined Protocols for your specific needs
- Dual frequency Ultrasound at 1 or 3.3 MHz
 - » Pulsed or Continuous Duty Cycles (10%, 20%, 50% & 100%)
 - » Four ergonomically designed sound head applicator sizes: 1 cm², 2 cm², 5 cm² & 10 cm²
 - » Sound heads are watertight for use in underwater therapy
- Therapy Cart also provides storage for clinical supplies and organizes cables
- Optional operator remotes allow treatment stop, start and pause, as well as change in amplitude, at any time during a treatment session. Each remote is color-coded for designation between channels





User Defined Protocols

Customize waveforms to your specific needs and organize alphabetically by patient name for easy recall.



Patient Documentation

Patient Data Cards allows you to capture and record accurate patient information using programs such as pain map profile, modality records and electrode placement diagrams; and to view session notes.



Multiple Waveforms

Six essential clinical waveforms let you manage a broad spectrum of clinical conditions: Interferential, Premodulated, High Volt, Russian, Microcurrent and Symmetrical Biphasic.



Light Therapy Module

Adds fully functional light therapy modality with independent control over all parameters. Includes protective eyewear.

Waveforms

Interferential • Continuous • Manual Vector Scan	
Premodulated • Continuous • Cycle Timed	
High Volt • Twin peak	
Russian • Continuous • Cycle Timed	
Microcurrent Polarity Based	
Symmetrical Biphasic • Continuous • Cycle Timed	

TECH SPECS

Mains Power: 100-240 VAC-50/60 Hz
Weight: 7 lb. (3.2 kg)
Shipping Weight: 16 lb. (7.3 kg)
Dimensions: 12.75" L x 11.4" W x 8.75" H
 (32.4 cm x 28.9 cm x 22.2 cm)
Electrical Safety Class: Class 1,
 Electrotherapy Type BF, Ultrasound Type B
Safety Tests: UL/IEC/EN 60601-1,
 IEC/EN 60601-1-2, IEC 60601-2-5,
 IEC 60601-2-10



**INTELECT® TRANSPORT
LIGHT THERAPY
REF: 2920K**

Standard Accessories:

27525 – Laser Protection Eyewear (2x)

Light Applicators *(choose one)*

28205 – 19 Diode Cluster Applicator,
325mW Total: 6 x 670nm
10mW LED, 7 x 880nm 25mW LED,
6 x 950nm 15mW LED

28206 – 33 Diode Cluster Applicator,
565mW Total: 12 x 670nm
10mW LED, 13 x 880nm 25mW LED,
8 x 950nm 15mW LED

Optional Accessories

27478 – Intelect Transport Nickel
Metal Hydride Battery Pack

27467 – Intelect Transport Carry Bag

2780ASY – Therapy Cart (assembled)

2891K – Therapy Cart with
Cart Adapter (Gray)

2884 – Cart Adapter (Gray)
Allows the Intelect Transport
unit to attach securely to the
Therapy Cart.

27525 – Laser Protective Eyewear

TECH SPECS

Mains Power: 120-240VAC, 50-60Hz
Weight: 5 lb (2.3 kg)
Shipping Weight: 16 lb (7.3 kg)
Dimensions: 12.9" L x 11.3" W x 6.4" H
(32.8 cm x 28.8 cm x 16.3 cm)
Electrical Safety Class: Class 1, Type B
Safety Tests: 21CFR 1040.10 & 1040.11,
UL/IEC/EN 60601-1, IEC/EN 60601-1-2,
IEC/EN 60601-1-22, IEC 60825-1:2001



Standard Features

- Independent control over all parameters
- Display of energy in choice of joules or joules/cm²
- Pulsed and continuous treatment operation (90% and 100%)
- Fully variable pulse frequency range of 8Hz-10,000Hz and continuous
- Real time feedback of dosage delivered
- Ten user-defined memory positions for user protocols
- Two interchangeable light therapy applicators with wavelengths ranging from 670nm to 950nm and output power ranging from 325mW-565mW (dependent upon applicator)
- Applicators are interchangeable due to Electronic Signature™ recognition residing on each applicator
- Unit uniquely designed for table top, wall mount, therapy cart, or mobile use
- Available as module for Intelect Legend XT™ Therapy Systems
- Two pair of laser protective eyewear included
- Two-year warranty



Intelect® TRANSPORT COMBO

Ordering Information



INTELECT® TRANSPORT COMBO THERAPY UNIT
REF: 2738K

Standard Accessories:

- 27383 – 5 cm² Sound Head Applicator
- 4248 – Conductor™ Ultrasound Gel - 8.5 oz (250 ml) Bottle (1x)
- 27312 – Electrotherapy Leadwire Channel 1
- 27313 – Electrotherapy Leadwire Channel 2
- 42044 – DURA-STICK® II 2.75" (7 cm) Round Electrodes (4x)

Optional Accessories

- 27478 – Intelect Transport Nickel Metal Hydride Battery Pack
- 72852 – Black Rubber Carbon 3" (8 cm) Electrodes (2x)
- 72853 – Red Rubber Carbon 3" (8 cm) Electrodes (2x)
- 1264 – Nylatex® Wrap 2.5" x 24" (3x)
- 27381 – 1 cm² Sound Head Applicator
- 27382 – 2 cm² Sound Head Applicator
- 27384 – 10 cm² Sound Head Applicator
- 27467 – Intelect Transport Carry Bag
- 2780ASY – Therapy Cart (assembled)
- 2891K – Therapy Cart with Cart Adapter (Gray)
- 2884 – Cart Adapter (Gray)
Allows the Intelect Transport unit to attach securely to the Therapy Cart.

Electrotherapy Waveforms

Interferential • Continuous • Manual Vector Scan	
Premodulated • Continuous • Cycle Timed	
High Volt • Twin peak	
Russian • Continuous • Cycle Timed	

Standard Features

- Fully functional 1 and 3.3 MHz frequencies
- Two channels of electrical stimulation output
- Ten user-defined memory positions for User Protocols
- Four standard waveforms on board: Interferential, Premodulated, High Volt, and Russian
- Pulsed and continuous therapy operation (10%, 20%, 50% and 100%)
- Independent intensity and parameter controls for each channel
- Ergonomically designed Sound Head Applicators in a variety of sizes (1 cm², 2 cm², 5 cm² and 10 cm²)
- All Sound Head Applicators are interchangeable with Electronic Signature™ residing on all transducers
- Watertight sound heads for use in underwater therapy
- Head-warming feature on all Sound Head Applicators
- Unit uniquely designed for tabletop, wall mount, therapy cart or mobile use
- 110V or battery powered option
- Optional Therapy Cart integrates with the unit to maximize storage of clinical supplies
- Two-year warranty



TECH SPECS

Mains Power: 120-240VAC, 50-60Hz
Weight: 5 lb (2.5 kg)
Shipping Weight: 16 lb (7.3 kg)
Dimensions: 12.9"L x 11.3"W x 10.1"H
 (32.8 cm x 28.8 cm x 25.7 cm)
Electrical Safety Class: Class 1, Electrotherapy Type BF, Ultrasound Type B
Safety Tests: UL/IEC/EN 60601-1, IEC/EN 60601-1-2, IEC 60601-2-5, IEC 60601-2-10

INTELECT® TRANSPORT ULTRASOUND REF: 2782K

Standard Accessories:

- 27383 – 5 cm² Sound Head Applicator
- 4248 – Conductor™ Ultrasound Gel
8.5 oz (250 ml) Bottle (1x)

Optional Accessories

- 27478 – Intelect Transport Nickel
Metal Hydride Battery Pack
- 27381 – 1 cm² Sound Head Applicator
- 27382 – 2 cm² Sound Head Applicator
- 27384 – 10 cm² Sound Head Applicator
- 27467 – Intelect Transport Carry Bag
- 2780ASY – Therapy Cart (assembled)
- 2891K – Therapy Cart with
Cart Adapter (Gray)
- 2884 – Cart Adapter (Gray)
Allows the Intelect Transport
unit to attach securely to the
Therapy Cart.



TECH SPECS

Mains Power: 100-240 VAC-50/60 Hz, 1.0 A
Weight: 5 lb (2.3 kg)
Shipping Weight: 9 lb (4 kg)
Dimensions: 12.9"L x 11.3"W x 6.4"H
 (32.8 cm x 28.8 cm x 16.3 cm)
Electrical Safety Class: Class 1, Type B
Safety Tests: UL/IEC/EN 60601-1,
 IEC/EN 60601-1-2, IEC 60601-2-5

Standard Features

- Fully functional 1 and 3.3 MHz frequencies
- Ten user-defined memory positions for User Protocols
- Pulsed and continuous therapy operation (10%, 20%, 50% and 100%)
- Ergonomically designed Sound Head Applicators in variety of sizes (1 cm², 2 cm², 5 cm² and 10 cm²)
- Sound heads are watertight for use in underwater therapy
- All Sound Head Applicators are interchangeable due to Electronic Signature™ residing on all transducers
- Head-warming feature on all Sound Head Applicators
- Unit uniquely designed for tabletop, wall mount, therapy cart or mobile use
- 110V or battery powered option
- Optional Therapy Cart integrates with the unit to maximize storage of clinical supplies
- Two-year warranty



Cart Adapter



Optional Battery Pack







Applicators



Standard Features

- Two channels of electrical stimulation output
- Logical control system and a large easy-to-read graphical LCD display
- Four standard waveforms on board: Interferential, Premodulated, High Volt, and Russian
- Ten user-defined memory positions for User Protocols
- Independent intensity and parameter controls for each channel
- Unit uniquely designed for tabletop, wall mount, therapy cart or mobile use
- 110V or battery-powered option
- Optional Therapy Cart integrates with the unit to maximize storage of clinical supplies
- Two-year warranty

Electrotherapy Waveforms

Interferential • Continuous • Manual Vector Scan	
Premodulated • Continuous • Cycle Timed	
High Volt • Twin peak	
Russian • Continuous • Cycle Timed	



The custom designed carrying bag (optional) is lightweight. Protect and transport the unit and accessories for therapy on the go.



INTELECT® TRANSPORT 2-CHANNEL ELECTROTHERAPY REF: 2783K

Standard Accessories:

- 27312 – Electrotherapy Leadwire Channel 1
- 27313 – Electrotherapy Leadwire Channel 2
- 42044 – DURA-STICK® II 2.75" (7 cm) Round Electrodes (4x)

Optional Accessories

- 27478 – Intellect Transport Nickel Metal Hydride Battery Pack
- 72852 – Black Rubber Carbon 3" (8 cm) Electrodes (2x)
- 72853 – Red Rubber Carbon 3" (8 cm) Electrodes (2x)
- 1264 – Nylatex® Wrap 2.5" x 24" (23x)
- 27467 – Intellect Transport Carry Bag
- 2780ASY – Therapy Cart (assembled)
- 2891K – Therapy Cart with Cart Adapter (Gray)
- 2884 – Cart Adapter (Gray)
Allows the Intellect Transport unit to attach securely to the Therapy Cart.

TECH SPECS

Mains Power: 100-240 VAC-50/60 Hz
 Weight: 5 lb (2.3 kg)
 Shipping Weight: 9 lb (4 kg)
 Dimensions: 12.9"L x 11.3"W x 6.4"H
 (32.8 cm x 28.8 cm x 16.3 cm)
 Electrical Safety Class: Class 1, Type BF
 Safety Tests: UL/IEC/EN 60601-1,
 IEC/EN 60601-1-2, IEC 60601-2-10

Intelect® PORTABLE ELECTROTHERAPY

Long known for innovative clinical electrotherapy, Chattanooga Group offers you a full line of portable electrotherapy products with Intelect® TENS units, Intelect NMES (Neuromuscular Electrical Stimulation) and Intelect IFC (Interferential Current) units. Treat multiple patient needs from pain management to the prevention or retardation of disuse muscle atrophy. All devices come with lead wires, 9-volt battery, DURA-STICK® II Self-Adhesive Electrodes and a convenient carrying case.

Intelect TENS

- Dual Independent Channels
- Adjustable Timer on Standard and Digital units
- Adjustable Frequency and Pulse Duration parameters
- Basic and Standard units feature three modes: Burst, Normal and Modulation
- Digital unit features five modes: Burst, Normal, Modulated Rate and Width, Strength Duration and Bi-Pulse
- Digital unit has easy-to-read LCD display and convenient digital controls



77710 – Intelect TENS Basic

77600 – Intelect TENS Standard



77712 – Intelect TENS Digital



Intelect NMES

- Dual Independent Channels
- Adjustable Pulse Amplitude, Pulse Frequency and Contraction/Relaxation Time parameters
- Digital unit features
 - » Adjustable Pulse Width and Timer parameters
 - » Three stim modes: Synchronous, Constant and Alternate
 - » Easy-to-read LCD display and convenient digital controls



77715 – Intelect NMES Standard



77717 – Intelect NMES Digital

Intelect IFC

- Dual Channel, Manual Selection for two or four Electrodes
- Adjustable Pulse Amplitude, Interference Frequency and Difference Frequency parameters
- Four stimulation modes (frequency shifts): Continuous, 1/1, 8/8 and 10/10 Ramped
- Includes 120V AC line cord adapter
- Sliding cover for controls and battery

77719 – Intelect IFC Portable



Portable Electrotherapy Accessories

Batteries (not shown)

- 77734 – 9-volt battery (each)
- 77735 – 9-volt battery (12-pack)
- 77609 – Rechargeable NiCd 9-volt Battery
- 77610 – Battery Recharger

Lead Wires (not shown)

- 77593 – Lead Wire, TENS 360° Pivot, Unshielded Connector (Pair)
- 77594 – Lead Wire, TENS 360° Pivot, Shielded Connector (Pair)
- 77595 – Lead Wire, TENS Non-Pivot, Shielded Connector (Pair)

TECH SPECS

TENS Basic & TENS Standard

Channel: Dual, isolated
 Waveform: Asymmetric biphasic square pulse
 Pulse Amplitude: 0-80 mA each channel adjustable (500 ohm load)
 Pulse Width: 60-250µ sec. adjustable
 Pulse Frequency: 2-150 Hz adjustable
 Dimensions: 1.2" x 2.4" x 3.6" (30 x 62 x 91 mm)
 Weight: 4.4 oz (126 g)
 Safety Tests: EN 60601-1, EN 60601-1-2, EN 60601-2-10

TENS Digital

Channel: Dual, isolated
 Waveform: Asymmetric biphasic square pulse
 Pulse Amplitude: 0-80 mA each channel adjustable (500 ohm load)
 Pulse Width: 50-300µ sec. adjustable
 Pulse Frequency: 2-150 Hz adjustable
 Dimensions: 1.2" x 2.4" x 4" (30 x 62 x 101 mm)
 Weight: 4.4 oz (126 g)
 Safety Tests: EN 60601-1, EN 60601-1-2, EN 60601-2-10

NMES Standard

Channel: Dual, isolated
 Waveform: Asymmetric biphasic square pulse
 Pulse Amplitude: 0-80 mA each channel adjustable (500 ohm load)
 Pulse Width: Fixed 250µ sec.
 Pulse Frequency: 5, 30, 100 Hz
 Dimensions: 1" x 2.4" x 3.6" (26 x 62 x 91 mm)
 Weight: 4.4 oz (126 g)
 Safety Tests: EN 60601-1, EN 60601-2, EN 60601-2-10

NMES Digital

Channel: Dual, isolated
 Waveform: Asymmetric biphasic square pulse
 Pulse Amplitude: 0-80 mA each channel adjustable (500 ohm load)
 Pulse Width: 50-300µ sec. adjustable
 Pulse Frequency: 2-120 Hz, adjustable
 Dimensions: 1.2" x 2.3" x 4" (30 x 59 x 101 mm)
 Weight: 4.4 oz (124 g)
 Safety Tests: EN 60601-1, EN 60601-1-2, EN 60601-2-10

IFC

Channel: Single for 2 pole or Dual for 4 pole
 Waveform: Symmetric biphasic square
 Pulse Amplitude: 0-32 mA, adjustable (at 500 ohm load)
 Pulse Width: 125µ sec/phase
 Pulse Frequency: 4000+/-10% Hz fixed
 Dimensions: 1.3" x 2.5" x 3.7" (33 x 64 x 94 mm)
 Weight: 5.2 oz (140 g)
 Safety Tests: EN 60601-1, EN 60601-1-2, EN 60601-2-10

Intelect® HVP High Volt Portable Stimulator

- Single channel with continuous or alternating modes
- Protective cover for controls



Intelect D-HVP Digital High Volt Portable Stimulator

- Single channel
- Accurate one-touch digital programming access
- 20 custom and standard presets
- Unique pause feature
- Ergonomic case design



Dura-Stick® High Volt Accessory Kits

- Each includes one 5" x 8" (13 cm x 20 cm) self-adhesive dispersive pad
- Packaged 10 kits per case
- Single patient use

REF: 42068

- Includes two round self-adhesive electrodes
- For use in High Volt treatments for:
 - » Relaxation of muscle spasms
 - » Prevention or retardation of disuse atrophy
 - » Muscle re-education
 - » Maintaining or increasing range of motion



REF: 42070

- Includes two 12" (30 cm) alligator clips
- For use in High Volt treatment techniques to increase localized blood circulation, utilizing gauze and hydrogel (not included) as electrodes



High Volt Probe Kit

The High Volt Probe Kit includes a lightweight High Volt Probe and two sponge-covered applicator tips (15 mm and 18 mm).

Intelect Low Volt Stimulators

- Available with one or two channels of stimulation
- Easy-to-use, transport and store, with easily accessible channels
- Includes a Patient Interrupt Switch to discontinue stimulator output
- Includes Nylatex® wraps, both red and black 3" (8 cm) round electrodes, patient switch and wall mounting bracket as standard equipment
- Two-year Warranty
- ETL and cETL listed



Ordering Information

Low Volt Stimulators

- 7410 – LV-110 One Channel Unit
- 7420 – LV-120 Two Channel Unit

Intelect D-HVP Portable Stimulator

- 7570 – Intelect D-HVP

Intelect HVP Portable Stimulator

- INT005 – Intelect HVP

High Volt Probe Kit

- 79977 – High Volt Probe Kit

DURA-STICK High Volt Accessory Kit

- 42068 – 10 kits per case.
- 42070 – 10 kits per case
- 42046 – Rectangular Dispersive Electrode 5" x 8" (15 cm x 28 cm)

Accessories



DURA-STICK® Supreme Self-Adhesive Electrodes (40/CASE)

- Pure conductive silver layer
- Choice wire and molded connectors
- Provides optimal current dispersion with low impedance

- 42048 – 2" (5 cm) Round
 42049 – 2.75" (7 cm) Round
 42050 – 2" (5 cm) Square
 42051 – 2" x 3.5" (5 cm x 9 cm) Rectangle
 42053 – 1.5" x 2.5" (4 cm x 6 cm) Oval
 42055 – 1.5" x 2.3" (4 cm x 6 cm) Rectangle



DURA-STICK Supreme Blue Gel Self-Adhesive Electrodes (40/CASE)

- Non-irritating conductive gel for superior conformability

- 42057 – Blue Gel 2" (5 cm) Square
 42059 – Blue Gel 1.75" x 3.75" (4 cm x 10 cm) Rectangle



DURA-STICK II Self-Adhesive Electrodes (40/CASE)

Our most popular electrode.

- Unique silver printed conductive layer
- Flexible and sturdy design for durability and ease of use


- 42061 – 1.25" (3 cm) Round
 42041 – 2" (5 cm) Square
 42042 – 2" (5 cm) Round
 42043 – 2" x 3.5" (5 cm x 9 cm) Rectangle
 42044 – 2.75" (7 cm) Round
 42045 – 2.75" x 5" (7 cm x 13 cm) Rectangle



DURA-STICK Self-Adhesive Electrodes (40/CASE)

- Carbon silver film layer incorporated into a low profile design
- White foam backing for increased "stretchability" and memory
- Innovative polymer for improved adhesion and durability

- 42005 – 2" x 2" (5 cm x 5 cm) Square
 42004 – 2" x 3.5" (5 cm x 9 cm) Rectangle
 42006 – 2.75" x 5" (7 cm x 13 cm) Rectangle
 42011 – 2" (5 cm) Round
 42009 – 2.75" (7 cm) Round
 42046 – 5" x 8" (13 cm x 20 cm) Rectangle
 Dispersive Electrode (10/case)



DURA-STIM™ Self-Adhesive Electrodes (40/CASE)

Our most economical electrode.

- Carbon conductive film incorporated into a flexible spun lace backing
- Permagem™ Hydrogel for superior conformability to body contours

- 42066 – 2" (5 cm) Square
 42067 – 2" (5 cm) Round
 42063 – 2.75" (7 cm) Round
 42065 – 2" x 3.5" (5 cm x 9 cm)

DURA-STICK TENS Electrodes – Single Use (40/CASE) (not shown)

- Polymer gel layer
- Pin-connector design ideal for TENS, NMES and small muscle group applications
- Single use

- 11842 – TENS Electrodes 2" x 2.5" (5 cm x 6 cm)

Conductive Rubber Electrodes (not shown)

- 71486 – 1-5/8" x 2" (4 cm x 5 cm) Rectangle Red
 71487 – 1-5/8" x 2" (4 cm x 5 cm) Rectangle Black
 72853 – 3" (8 cm) Round Red
 72852 – 3" (8 cm) Round Black



Nylatex® Assortment (1 pack of 9 rolls)

Ideal for holding carbon rubber electrodes in place. Several sizes available. Good for hundreds of uses.

- 1200 – Nylatex Assortment
 One of each size listed below except 1213 and 1264.

Nylatex Individual (3 rolls per package)

- 1202 – 2.5" x 18" (6 cm x 46 cm)
 1264 – 2.5" x 24" (6 cm x 61 cm)
 1204 – 2.5" x 36" (6 cm x 91 cm)
 1206 – 2.5" x 48" (6 cm x 122 cm)
 1208 – 4" x 18" (10 cm x 46 cm)
 1210 – 4" x 36" (10 cm x 91 cm)
 1212 – 4" x 48" (10 cm x 122 cm)
 1213 – 4" x 60" (10 cm x 152 cm)
 1214 – 6" x 18" (15 cm x 46 cm)
 1216 – 6" x 36" (15 cm x 91 cm)
 1218 – 6" x 48" (15 cm x 122 cm)
 1219 – 6" x 60" (15 cm x 152 cm)



Ultra-Myossage® Lotion

Formulated with aloe vera, this top quality lotion is ideal for massage or as an ultrasound coupling agent. No menthol, hexachlorophene or polysorbates. Hypoallergenic, water-soluble and greaseless.

- 4262 – 1 Gallon (3.8 liter) Bottle
 4260 – 8.5 oz. (250 ml) Bottle



Myossage Lotion®

Soothing, effective alcohol-free, non-greasy and non-staining lotion.

- 4210 – 1 Gallon (3.8 liter) Bottle
 4208 – 8.5 oz. (250 ml) Bottle (12/case)
 4212 – Plastic Measuring Pump



Conductor™ Transmission Gel

Water-soluble, non-greasy ultrasound and electrical coupling gel.

- 4238 – 1.3 Gallon (5 Liter) Container
 Includes one 8.5 oz. container for refill
 4248 – 8.5 oz. (250 ml) Bottle (24/case)



Intellect® Ultrasound Gel

Water-soluble, non-greasy, non-staining and hypoallergenic gel enhances conductivity.

- 4266 – 1.3 Gallon (5 Liter) Container
 Includes one 8.5 oz. container for refill



TM-1 Electric Lotion Warmer

Easily attaches to any treatment table or wall to keep massage lotion or ultrasound gel at a comfortable temperature and within reach. Bottles not included.

- 4012 – TM-1 Electric Lotion Warmer (110V only)

1.800.592.7329 USA
1.800.242.8329 Fax
1.800.361.6661 Canada
ChattGroup.com