

Vendor Name: NIEBUR TRACTOR AND EQUIPMENT  
Contact Person: DAN BEISSEL  
Street Address: 14380 EAST 240TH STREET  
P.O. Box: \_\_\_\_\_  
City, State, Zip: HASTINGS MN 55033  
Phone #: 651-437-3531  
Toll Free #: 888-559-9492  
Fax #: 651-437-9161  
Email Address: d.beissel@nieburtractor.com

Spec #	Information Requested	Answer
1.0	Tractor Catalog Section Price List Title:	<u>B ,GRAND L, AND M SERIES</u>
	Date & I.D. of Price List	<u>MARCH 1, 2012</u>
	Percentage Discount to be applied to Price List	<u>20</u>
1.1	Price for manuals, (service, parts, repair, and operations)	<u>60</u>
1.2	Price for set of fluid and air filters	<u>165</u>
2.0	<b>PERFORMANCE/EXTENDED WARRANTY OPTIONS</b> Offer performance/warranty options. Numbers starting with 2.1, 2.2, etc. (Specify years, miles or hours extended term covers.)	
2.1	_____	<u>\$ _____</u>
2.2	_____	<u>\$ _____</u>
3.0	<b>INSTALLATION - PER HOUR -See Special Terms and Conditions</b>	<u>\$ _____</u>
4.0	<b>NEW EQUIPMENT RENTAL PROGRAM</b> If rental programs are available on the new equipment offered, with the option to purchase, list the hourly/weekly/monthly rental rate. Indicate the percent of rental fee paid by the purchaser that will be applied to the purchase price. See Solicitation Special Terms & Conditions.  Hourly Rental Rate: _____ Weekly Rental Rate: \$ _____ Monthly Rental Rate: \$ _____ Percent (%) of Rental Fee applied to purchase price: \$ _____  If the new rental equipment is purchased and finance charges are applicable for the actual rental term only, state the actual interest rate here: _____	
5.0	<b>VENDOR OWNED RENTAL RETURN OR DEMO EQUIPMENT PROGRAM</b> See Special Terms and Conditions. DEDUCT cost per Used Hour from the original Contract Price	<u>\$ _____</u>
6.0	<b>DISCOUNT OFF LIST PRICE FOR RELATED PARTS &amp; ACCESSORIES</b> See Special Terms and Conditions	<u>12</u>
7.0	DELIVERY STARTING POINT - _____ City, State, Zip	<u>HASTINGS MN 55033</u>
8.0	<b>DELIVERY CHARGES -- SEE ADDENDUM 1</b> Cost per loaded Mile (includes overhead but not fuel cost) _____ Fuel Cost per loaded mile _____	<u>2.5</u> Confirm at the time order is placed
9.0	<b>MINIMUM DELIVERY CHARGE - SEE ADDENDUM 1</b>	<u>75</u>

### WHOLEGOODS PRICE LIST EFFECTIVE MARCH 1, 2012

NOTE: Tire prices appear per piece.

## L SERIES

	PAGE NUMBER	MODEL	PTO HP	SUGGESTED LIST PRICE	
STANDARD L SERIES	6-5	L3200F	26.7	\$12,839.00	
	6-6	L3200DT	26.7	\$14,893.00	
	6-7	L3200HST	25.2	\$16,092.00	
	6-8	L3800F	31.5	\$14,879.00	
	6-9	L3800DT	31.5	\$16,782.00	
	6-10	L3800HST	30.0	\$17,982.00	
	6-11	L4600F	38.3	\$15,222.00	
	6-12	L4600DT	38.3	\$21,198.00	
	6-13	L4600HST	36.8	\$22,799.00	
	6-15	L2800F-1*	25	\$12,257.00	
	6-16	L2800DT-1*	25	\$13,982.00	
	6-17	L2800HST-1*	23.5	\$15,316.00	
	6-18	L3400F-1*	30	\$14,257.00	
	6-19	L3400DT-1*	30	\$15,800.00	
	6-20	L3400HST-1*	28.5	\$16,954.00	
	6-21	L3700SUⓄ	30.0	\$16,002.00	
	6-22	L4400F-1*	37.5	\$14,556.00	
	6-23	L4400DT-1*	37.5	\$20,050.00	
	6-24	L4400HST-1*	36	\$21,890.00	
	6-25	Standard L Series Attachment Chart			
	6-27	Standard L Series Dealer Installed Options			
	GRAND L40 SERIES	6-33	L3240F-1*/-2/-3	26.5	\$18,201.00
		6-34	L3240DT-1*/-2/-3	26.5	\$19,948.00
		6-35	L3240GST-1*/-2/-3	26.5	\$21,091.00
		6-36	L3240HST-1*/-2/-3	25	\$21,586.00
6-37		L3240HSTC-1/-3	25	\$28,951.00	
6-38		L3540GST-1*/-2/-3	29.5	\$22,410.00	
6-39		L3540HST-1*/-2/-3	28	\$22,904.00	
6-40		L3540HSTC-1/-3	28	\$30,270.00	
6-41		L3940DT-1*/-2/-3	33	\$23,441.00	
6-42		L3940GST-1*/-2/-3	33	\$24,584.00	
6-43		L3940HST-1*/-2/-3	31.5	\$25,078.00	
6-44		L3940HSTC-1/-3	31.5	\$32,444.00	

\*\*\*

□ \*\* based off of dealer orders

## L SERIES

	PAGE NUMBER	MODEL	PTO HP	SUGGESTED LIST PRICE	
GRAND L40 SERIES (CONT.)	6-45	L4240DT-1*/-2/-3	36.5	\$25,284.00	
	6-46	L4240GST-1*/-2/-3	36.5	\$26,428.00	
	6-47	L4240HST-1*/-2/-3	35	\$26,922.00	
	6-48	L4240HSTC-1/-3	35	\$34,288.00	
	6-49	L4740GST-1*/-2/-3	41.5	\$28,694.00	
	6-50	L4740HST-1*/-2/-3	40	\$29,188.00	
	6-51	L4740HSTC-1/-3	40	\$36,554.00	
	6-52	L5040GST-1*/-2/-3	44	\$30,537.00	
	6-53	L5240HST-1*/-2/-3	45	\$31,274.00	
	6-54	L5240HSTC-1/-3	45	\$38,639.00	
	6-55	L5740HST-1*/-2/-3	50	\$32,520.00	
	6-56	L5740HSTC-1/-3	50	\$39,886.00	
	6-57	Grand L-40 Series Attachment Chart			
	6-58	Grand L-40 Series Dealer Installed Options			
L SERIES IMPLEMENTS	6-62	Std. L Series Implement Matching Chart			
	6-62	Grand L-40 Implement Matching Chart			
	6-63	Std. L-Series Loader Matching Chart			
	6-63	Grand L-40 Loader Matching Chart			
	6-64	Std. L-Series Loaders			
	6-64	L-Series Loaders			
	6-65	Std. L-Series Replacement Loader Attachments			
	6-69	L-Series Loader Attachments			
	6-70	Grand L-40 Loaders			
	6-75	L-Series Backhoes			
	6-80	L-Series Mowers			
	6-81	L-Series Rotary Tillers			
	6-83	L-Series Blades			
	6-85	L-Series Snowblowers			
6-89	L-Series Rotary Sweeper				
6-92	L-Series Replacement Engines				
6-97	Prior Models				

This page intentionally left blank.

# KUBOTA

## L3200F

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model #D1503  
 3 Cyl. 91.5 cu. in.  
 + 30.4 Net Eng. HP  
 + 26.7 F/DT PTO HP  
 @ 2800 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V - 490 CCA Battery  
 Charging Output 40 Amps  
 Electric Key Shut-off

### HYDRAULICS

Open Center Gear Type  
 6.5 gpm Remote/3 Pt. Hitch  
 4.0 gpm Power Steering  
 10.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 1998 lbs.  
 24" Behind 1435 lbs.

### FRONT AXLE

Integral Power Steering, 2WD  
 Tubular Steel Beam  
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

### DRIVE TRAIN

Sliding Gear Constant Mesh  
 8 Forward Speeds  
 4 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

### FLUID CAPACITY

Fuel Tank 10.0 gal  
 Cooling System 6.3 qts  
 Crankcase 6.0 qts  
 Transmission and  
 Hydraulics 7.1 gal

### POWER TAKE OFF

Transmission Driven with  
 Overrunning Clutch  
 Rear PTO - 1 Speed  
 Speed - 540 @ 2430 Eng. rpm  
 SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

ROPS w/Retractable Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 SMV Sign

### OPERATOR STATION

Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable  
 Suspension  
 Operator Presence Control

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3200F	2WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2158	\$ 12,839.00

L3200F		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8865**	F-TIRE 5-15 F2 Steel Bias CA	28	\$ 123.00	\$12,839.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8852A	F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION	64	\$ 194.00	\$12,981.00
ALR9494	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8890A	F-TIRE 23x8.5-12 R3 TF Steel Bias AA	32	\$ 165.00	\$12,909.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

# KUBOTA

## L3200DT

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model #D1503  
 3 Cyl. 91.5 cu. in.  
 + 30.4 Net Eng. HP  
 + 26.7 PTO HP  
 @ 2800 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V - 490 CCA Battery  
 Charging Output 40 Amps  
 Electric Key Shut-off

#### HYDRAULICS

Open Center — Gear Type Single Pump  
 6.5 gpm Remote/3 Pt. Hitch  
 4.0 gpm for Power Steering  
 10.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 1998 lbs.  
 24" Behind 1435 lbs.

#### FRONT AXLE

Integral Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

#### DRIVE TRAIN

Sliding Gear Constant Mesh  
 8 Forward Speeds  
 4 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch – Single Dry Plate  
 Differential Lock

#### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

#### FLUID CAPACITY

Fuel Tank 10.0 gal.  
 Cooling System 6.3 qts.  
 Crankcase 6.0 qts.  
 Transmission and Hydraulics 7.3 gal.

#### POWER TAKE OFF

Transmission Driven with Over-running Clutch  
 540 Rear PTO – 1 Speed  
 Speed - 540 @ 2430 Eng. rpm  
 SAE Std 1 3/8" Six Spline

#### SAFETY EQUIPMENT

ROPS w/Retractable Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 SMV Sign

#### OPERATOR STATION

Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control System

#### TIRES AND WHEELS

Front 7.00 x 16 R1  
 Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3200DT	4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2308	\$ 14,893.00

L3200DT		Price with Tire Option		
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$14,893.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$14,769.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$15,547.00
ALR8809 ①	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

# KUBOTA

## L3200HST

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model #D1503  
 3 Cyl. 91.5 cu. in.  
 + 30.4 Net Eng. HP  
 + 25.2 PTO HP  
 @ 2800 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V - 490 CCA Battery  
 Charging Output 40 Amps  
 Electric Key Shut-off

### HYDRAULICS

Open Center — Gear Type Single Pump  
 6.5 gpm Remote/3 Pt. Hitch  
 4.0 gpm for Power Steering  
 10.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 1998 lbs.  
 24" Behind 1435 lbs.

### FRONT AXLE

Integral Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

### DRIVE TRAIN

Hydrostatic Drive  
 3 Speed L-M-H  
 Multiple Wet Disc Brakes  
 Clutch – Dry Type / Single Stage  
 Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

### FLUID CAPACITY

Fuel Tank 10.0 gal  
 Cooling System 6.3 qts  
 Crankcase 6.0 qts  
 Transmission and Hydraulics 6.2 gal

### POWER TAKE OFF

Live Continuous Running  
 540 Rear PTO – 1 Speed  
 Speed - 540 @ 2430 Eng. rpm  
 SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

ROPS w/Retractable Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 SMV Sign  
 Turn Signals / Hazard Lights

### OPERATOR STATION

Color Coded Controls  
 Wide Platform Step  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control System  
 Cruise Control (Optional)  
 Cup Holder

### TIRES AND WHEELS

Front 7.00 x 16 R1  
 Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3200HST	4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2322	\$ 16,092.00

L3200HST		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$16,092.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$15,968.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$16,746.00
ALR8809 ①	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.



# KUBOTA

## L3800F

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model #D1803  
 3 Cyl. 111.4 cu. in.  
 + 35.9 Net Eng. HP  
 + 31.5 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V – 490 CCA Battery  
 Charging Output 40 Amps  
 Electric Key Shut-off

#### HYDRAULICS

Open Center Gear Type  
 6.3 gpm Remote/3 Pt. Hitch  
 3.8 gpm for Power Steering  
 10.1 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 1998 lbs.  
 24" Behind 1435 lbs.

#### FRONT AXLE

Integral Power Steering, 2WD  
 Tubular Steel Beam  
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

#### DRIVE TRAIN

Sliding Gear Constant Mesh  
 8 Forward Speeds  
 4 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch – Dual Clutch, Dry Plates  
 Differential Lock

#### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

#### FLUID CAPACITY

Fuel Tank 10.0 gal  
 Cooling System 6.3 qts  
 Crankcase 7.5 qts  
 Transmission and Hydraulics 7.1 gal

#### POWER TAKE OFF

Live-Continuous Running (Dual Clutch)  
 540 rpm Rear PTO – 1 Speed  
 Speed - 540 @ 2425 Eng. rpm  
 SAE Std 1 3/8" Six Spline

#### SAFETY EQUIPMENT

ROPS w / Retractable Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 SMV Sign

#### OPERATOR STATION

Color coded controls  
 Wide platform steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control

#### TIRES AND WHEELS

Front 5.00 x 15 F2  
 Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3800F	2WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2198	\$ 14,879.00

L3800F		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8865**	F-TIRE 5-15 F2 Steel Bias CA	28	\$ 123.00	\$14,879.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8852A	F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION	64	\$ 194.00	\$15,021.00
ALR9494	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8890A	F-TIRE 23x8.5-12 R3 TF Steel Bias AA	32	\$ 165.00	\$14,949.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

# KUBOTA

## L3800DT

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model #D1803  
 3 Cyl. 111.4 cu. In.  
 + 35.9 Net Eng. HP  
 + 31.5 PTO HP  
 @ 2700 Eng. Rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V – 490 CCA Battery  
 Charging Output 40 Amps  
 Electric Key Shut-off

#### HYDRAULICS

Open Center — Gear Type  
 6.3 gpm Remote/3 Pt. Hitch  
 3.8 gpm for Power Steering  
 10.1 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 1998 lbs.  
 24" Behind 1435 lbs.

#### FRONT AXLE

Integral Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing,  
 Nonadjustable

+ Manufacturer Estimate

#### DRIVE TRAIN

Sliding Gear Constant Mesh  
 8 Forward Speeds  
 4 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch – Dual Clutch, Dry Plates  
 Differential Lock

#### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

#### FLUID CAPACITY

Fuel Tank 10.0 gal  
 Cooling System 6.3 qts  
 Crankcase 7.5 qts  
 Transmission and 7.3 gal  
 Hydraulics

#### POWER TAKE OFF

Live-Continuous Running (Dual Clutch)  
 Speed - 540 @ 2425 Eng. rpm  
 540 rpm Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline

#### SAFETY EQUIPMENT

ROPS w / Retractable Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 SMV Sign

#### OPERATOR STATION

Color coded controls  
 Wide platform steps  
 High Back Seat with Adjustable Suspens  
 Operator Presence Control System

#### TIRES AND WHEELS

Front 7.00 x 16 R1  
 Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3800DT	4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2343	\$ 16,782.00

L3800DT		Price with Tire Option		
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$16,782.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$16,658.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$17,436.00
ALR8809 ①	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

# KUBOTA

## L3800HST

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model #D1803  
3 Cyl. 111.4 cu. In.  
+ 35.9 Net Eng. HP  
+ 30.0 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
12V – 490 CCA Battery  
Charging Output 40 Amps  
Electric Key Shut-off

#### HYDRAULICS

Open Center — Gear Pump  
6.3 gpm Remote/3 Pt. Hitch  
3.8 gpm for Power Steering  
10.1 Total gpm  
Cat I 3-point Hitch  
At lift Point 1998 lbs.  
24" Behind 1435 lbs.

#### FRONT AXLE

Integral Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing,  
Nonadjustable

+ Manufacturer Estimate

#### DRIVE TRAIN

Hydrostatic Drive  
3 Speeds L-M-H  
Multiple Wet Disc Brakes  
Clutch – Dry Type / Single Stage  
Differential Lock

#### DASH INSTRUMENTS

Tachometer w/Hour Meter  
Fuel Gauge  
Temperature Gauge

#### FLUID CAPACITY

Fuel Tank 10.0 gal  
Cooling System 6.3 qts  
Crankcase 7.5 qts  
Transmission and  
Hydraulics 6.2 gal

#### POWER TAKE OFF

Live-Continuous Running  
Speed - 540 @ 2425 Eng. rpm  
540 rpm Rear PTO – 1 Speed  
SAE Std 1 3/8" Six Spline

#### SAFETY EQUIPMENT

ROPS w / Retractable Seat Belt  
PTO Shield  
Safety Start Switches  
Mechanical Wet Disc Brakes  
Parking Brakes  
SMV Sign  
Turn Signals / Hazard Lights

#### OPERATOR STATION

Color coded controls  
Wide platform steps  
High Back Seat with Adjustable Suspension  
Operator Presence Control System  
Optional Cruise Control  
Cup Holder

#### TIRES AND WHEELS

Front 7.00 x 16 R1  
Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3800HST	4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2381	\$ 17,982.00

L3800HST		Price with Tire Option		
TIRES AND WHEELS (priced per piece)				SUGG. LIST
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$17,982.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$17,858.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$18,636.00
ALR8809 ①	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

# KUBOTA

## L4600F

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V-2203  
 4 Cyl. 134.1 cu. in.  
 + 43.8 Net Eng. HP  
 + 38.3 PTO HP  
 @ 2600 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Radial Air Flow Cooling  
 12V, 582A CCA  
 Charging Output 40 Amps  
 Electric Key Shutoff

### HYDRAULICS

Open Center — Gear Type  
 Dual Pumps  
 8.4 gpm Remote/3 Pt. Hitch  
 5.1 gpm for Power Steering  
 13.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 2870 lbs.  
 24" Behind 2320 lbs.

+ Manufacturer Estimate

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, Cast Iron  
 Tread Spacing, nonadjustable

### DRIVE TRAIN

Synchro Shuttle with Constant  
 Mesh Gear Shift Transmission  
 8 Forward Speeds  
 8 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch – Dry Type Single Stage  
 Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

### FLUID CAPACITY

Fuel Tank 12.7 gal.  
 Cooling System 6.9 qts.  
 Crankcase 8.0 qts.  
 Transmission and  
 Hydraulics 42.4 qts.

### POWER TAKE OFF

Live Independent Hydraulic PTO w/PTO brake  
 540 rpm Rear PTO – 1 Speed  
 Speed - 540 @ 2475 Eng. rpm  
 SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

Foldable ROPS w / Retractable  
 Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 Turn Signals  
 SMV Sign  
 Hazard Lights

### OPERATOR STATION

Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control System  
 Cup Holder

### TIRES AND WHEELS

Front 7.5L - 15 F2  
 Rear 14.9 - 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4600F	2WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt		\$ 15,222.00

L4600F		Price with Tire Option		
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8852A**	F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION	64	\$ 194.00	\$15,222.00
ALR6811A**	R-TIRE 14.9-24 R1BIAS SAT II	207	\$ 637.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$15,640.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	

\*\* Standard tires.

## L4600DT

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V-2203  
 4 Cyl. 134.1 cu. in.  
 + 43.8 Net Eng. HP  
 + 38.3 PTO HP  
 @ 2600 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Radial Air Flow Cooling  
 12V, 582A CCA  
 Charging Output 40 Amps  
 Electric Key Shutoff

### HYDRAULICS

Open Center — Gear Type  
 Dual Pumps  
 8.4 gpm Remote/3 Pt. Hitch  
 5.1 gpm for Power Steering  
 13.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 2870 lbs.  
 24" Behind 2320 lbs.

+ Manufacturer Estimate

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, Cast Iron  
 Tread Spacing, nonadjustable

### DRIVE TRAIN

Synchro Shuttle with Constant Mesh  
 Gear Shift Transmission  
 8 Forward Speeds  
 8 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch – Dry Type Single Stage  
 Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

### FLUID CAPACITY

Fuel Tank 12.7 gal.  
 Cooling System 6.9 qts.  
 Crankcase 8.0 qts.  
 Transmission and  
 Hydraulics 42.4 qts.

### POWER TAKE OFF

Live Independent Hydraulic PTO w/ PTO  
 brake  
 540 rpm Rear PTO – 1 Speed  
 Speed - 540 @ 2475 Eng. rpm  
 SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

Foldable ROPS w / Retractable  
 Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 Turn Signals  
 SMV Sign  
 Hazard Lights

### OPERATOR STATION

Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable  
 Suspension  
 Operator Presence Control System  
 Cup Holder

### TIRES AND WHEELS

Front 8.3 - 16 R1  
 Rear 14.9 - 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	------------------	----------------------

\*\*\* STANDARD MACHINE \*\*\*

L4600DT	4WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt		\$ 21,198.00
---------	--	--	--------------

L4600DT		Price with Tire Option		
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$21,198.00
ALR6811A**	R-TIRE 14.9-24 R1BIAS SAT II	207	\$ 637.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$21,512.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$21,786.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$21,712.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	

\*\* Standard tires.

# KUBOTA

## L4600HST

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

**DIESEL ENGINE**  
 Model # V-2203  
 4 Cyl. 134.1 cu. in. Tier III  
 + 43.8 Net Eng. HP  
 + 36.8 PTO HP  
 @ 2600 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Radial Air Flow Cooling  
 12V, 582A CCA  
 Charging Output 40 Amps  
 Electric Key Shutoff

**HYDRAULICS**  
 Open Center — Gear Type  
 Dual Pumps  
 8.4 gpm Remote/3 Pt. Hitch  
 5.1 gpm for Power Steering  
 13.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 2870 lbs.  
 24" Behind 2320 lbs.

+ Manufacturer Estimate

**FRONT AXLE**  
 Hydrostatic Power Steering  
 Bevel Gear, Cast Iron  
 Tread Spacing, nonadjustable

**DRIVE TRAIN**  
 Feather Step HST  
 Hydraulic Pedal Assist  
 Cruise Control  
 Maximum Travel Speed 14.2 mph  
 Multiple Wet Disc Brakes  
 Clutch – Dry Type Single Stage  
 Differential Lock

**DASH INSTRUMENTS**  
 Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

**FLUID CAPACITY**  
 Fuel Tank 12.7 gal.  
 Cooling System 6.9 qts.  
 Crankcase 8.0 qts.  
 Transmission and  
 Hydraulics 47.5 qts.

**POWER TAKE OFF**  
 Live Independent Hydraulic PTO, w/ PTO  
 Brake  
 540 rpm Rear PTO – 1 Speed  
 Speed - 540 @ 2475 Eng. rpm  
 SAE Std 1 3/8" Six Spline

**SAFETY EQUIPMENT**  
 Foldable ROPS w / Retractable  
 Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 Turn Signals  
 SMV Sign  
 Hazard Lights

**OPERATOR STATION**  
 Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control System  
 Cup Holder

**TIRES AND WHEELS**  
 Front 8.3 - 16 R1  
 Rear 14.9 - 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	------------------	----------------------

\*\*\* STANDARD MACHINE \*\*\*

L4600HST	4WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt	\$ 22,799.00
----------	--	--------------

L4600HST		Price with Tire Option		
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$22,799.00
ALR6811A**	R-TIRE 14.9-24 R1BIAS SAT II	207	\$ 637.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$23,113.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$23,387.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$23,313.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	

\*\* Standard tires.

This page intentionally left blank.

# KUBOTA

## L2800F-1

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model #D1503  
 3 Cyl. 91.5 cu. in.  
 + 28.6 Net Eng. HP  
 + 25 PTO HP  
 @ 2800 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V - 490 CCA Battery  
 Charging Output 40 Amps  
 Electric Key Shut-off

### HYDRAULICS

Open Center Gear Type  
 6.8 gpm Remote/3 Pt. Hitch  
 4.3 gpm Power Steering  
 11.1 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 1985 lbs.  
 24" Behind 1433 lbs.

### FRONT AXLE

Integral Power Steering, 2WD  
 Tubular Steel Beam  
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

### DRIVE TRAIN

Sliding Gear Constant Mesh  
 8 Forward Speeds  
 4 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

### FLUID CAPACITY

Fuel Tank 9.0 gal.  
 Cooling System 6.3 qts.  
 Crankcase 6.0 qts.  
 Transmission and 7.1 gal.  
 Hydraulics

### POWER TAKE OFF

Transmission Driven with Overrunning Clutch  
 Rear PTO - 1 Speed  
 Speed - 540 @ 2430 Eng. rpm  
 SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

ROPS w/Retractable Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 SMV Sign

### OPERATOR STATION

Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control

### TIRES AND WHEELS

Front 5.00 x 15 R1  
 Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L2800F-1R	* 2WD TRACTOR with 2 Post Rigid ROPS w/Retractable Seat Belt	2152	\$ 12,257.00
L2800F-1F	* 2WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2158	\$ 12,305.00

L2800F-1R		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8865**	F-TIRE 5-15 F2 Steel Bias CA	28	\$ 123.00	\$12,257.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8890A	F-TIRE 23x8.5-12 R3 TF Steel Bias AA	32	\$ 165.00	\$12,327.00
ALR8804A	① R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	

L2800F-1F		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8865**	F-TIRE 5-15 F2 Steel Bias CA	28	\$ 123.00	\$12,305.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8890A	F-TIRE 23x8.5-12 R3 TF Steel Bias AA	32	\$ 165.00	\$12,375.00
ALR8804A	① R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.



# KUBOTA

## L2800DT-1

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model #D1503  
3 Cyl. 91.5 cu. in.  
+ 28.6 Net Eng. HP  
+ 25 PTO HP  
@ 2800 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
12V - 490 CCA Battery  
Charging Output 40 Amps  
Electric Key Shut-off

### HYDRAULICS

Open Center — Gear Type Single Pump  
6.8 gpm Remote/3 Pt. Hitch  
4.3 gpm for Power Steering  
11.1 Total gpm  
Cat I 3-point Hitch  
At lift Point 1985 lbs.  
24" Behind 1433 lbs.

### FRONT AXLE

Integral Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

### DRIVE TRAIN

Sliding Gear Constant Mesh  
8 Forward Speeds  
4 Reverse Speeds  
Multiple Wet Disc Brakes  
Clutch – Single Dry Plate  
Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
Fuel Gauge  
Temperature Gauge

### FLUID CAPACITY

Fuel Tank 9.0 gal.  
Cooling System 6.3 qts.  
Crankcase 6.0 qts.  
Transmission and 7.3 gal  
Hydraulics  
Front Axle 4.8 qts.

### POWER TAKE OFF

Transmission Driven with Over-  
running Clutch  
540 Rear PTO – 1 Speed  
Speed - 540 @ 2430 Eng. rpm  
SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

ROPS w/Retractable Seat Belt  
PTO Shield  
Safety Start Switches  
Mechanical Wet Disc Brakes  
Parking Brakes  
SMV Sign

### OPERATOR STATION

Color Coded Controls  
Wide Platform Steps  
High Back Seat with Adjustable Suspension  
Operator Presence Control System

### TIRES AND WHEELS

Front 7.00 x 16 R1  
Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L2800DT-1R	* 4WD TRACTOR with 2 Post Rigid ROPS w/Retractable Seat Belt	2302	\$ 13,982.00
L2800DT-1F	* 4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2308	\$ 14,031.00

L2800DT-1R		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$13,982.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$13,858.00
ALR8804A	① R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$14,636.00
ALR8809	① R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

L2800DT-1F		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$14,031.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$13,907.00
ALR8804A	① R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$14,685.00
ALR8809	① R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

F.O.B. KTC designated shipping point.  
Complete revision March 1, 2012.

## L2800HST-1

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model #D1503  
3 Cyl. 91.5 cu. in.  
+ 28.6 Net Eng. HP  
+ 23.5 PTO HP  
@ 2800 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
12V - 490 CCA Battery  
Charging Output 40 Amps  
Electric Key Shut-off

### HYDRAULICS

Open Center — Gear Type Single Pump  
7.0 gpm Remote/3 Pt. Hitch  
4.3 gpm for Power Steering  
11.3 Total gpm  
Cat I 3-point Hitch  
At lift Point 1985 lbs.  
24" Behind 1433 lbs.

### FRONT AXLE

Integral Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

### DRIVE TRAIN

Hydrostatic Drive  
3 Speed L-M-H  
Multiple Wet Disc Brakes  
Clutch — Dry Type / Single Stage  
Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
Fuel Gauge  
Temperature Gauge

### FLUID CAPACITY

Fuel Tank 9.0 gal.  
Cooling System 6.3 qts.  
Crankcase 6.0 qts.  
Transmission and Hydraulics 7.3 gal.  
Front Axle 4.8 qts.

### POWER TAKE OFF

Live Continuous Running  
540 Rear PTO — 1 Speed  
Speed - 540 @ 2430 Eng. rpm  
SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

ROPS w/Retractable Seat Belt  
PTO Shield  
Safety Start Switches  
Mechanical Wet Disc Brakes  
Parking Brakes  
SMV Sign  
Turn Signals / Hazard Lights

### OPERATOR STATION

Color Coded Controls  
Wide Platform Step  
High Back Seat with Adjustable Suspension  
Operator Presence Control System  
Cruise Control  
Cup Holder

### TIRES AND WHEELS

Front 7.00 x 16 R1  
Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L2800HST-1R	* 4WD TRACTOR with 2 Post Rigid ROPS w/Retractable Seat Belt	2374	\$ 15,136.00
L2800HST-1F	* 4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt	2322	\$ 15,184.00

L2800HST-1R		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$15,136.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$15,012.00
ALR8804A	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$15,790.00
ALR8809	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

L2800HST-1F		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$15,184.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$15,060.00
ALR8804A	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$15,838.00
ALR8809	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

Ⓢ Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

# KUBOTA

## L3400F-1

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model #D1803  
3 Cyl. 111.4 cu. in.  
+ 34.2 Net Eng. HP  
+ 30 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
12V – 490 CCA Battery  
Charging Output 40 Amps  
Electric Key Shut-off

#### HYDRAULICS

Open Center Gear Type  
6.8 gpm Remote/3 Pt. Hitch  
4.1 gpm for Power Steering  
10.9 Total gpm  
Cat I 3-point Hitch  
At lift Point 1985 lbs.  
24" Behind 1433 lbs.

#### FRONT AXLE

Integral Power Steering, 2WD  
Tubular Steel Beam  
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

#### DRIVE TRAIN

Sliding Gear Constant Mesh  
8 Forward Speeds  
4 Reverse Speeds  
Multiple Wet Disc Brakes  
Clutch – Dual Clutch, Dry Plates  
Differential Lock

#### DASH INSTRUMENTS

Tachometer w/Hour Meter  
Fuel Gauge  
Temperature Gauge

#### FLUID CAPACITY

Fuel Tank 9.0 gal.  
Cooling System 6.3 qts.  
Crankcase 6.0 qts.  
Transmission and Hydraulics 7.1 gal.

#### POWER TAKE OFF

Live-Continuous Running (Dual Clutch)  
540 rpm Rear PTO – 1 Speed  
Speed - 540 @ 2425 Eng. rpm  
SAE Std 1 3/8" Six Spline

#### SAFETY EQUIPMENT

ROPS w/ Retractable Seat Belt  
PTO Shield  
Safety Start Switches  
Mechanical Wet Disc Brakes  
Parking Brakes  
SMV Sign

#### OPERATOR STATION

Color coded controls  
Wide platform steps  
High Back Seat with Adjustable Suspension  
Operator Presence Control

#### TIRES AND WHEELS

Front 5.00 x 15 F2  
Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3400F-1R	* 2WD TRACTOR with 2 Post Rigid ROPS w/ Retractable Seat Belt	2191	\$ 14,257.00
L3400F-1F	* 2WD TRACTOR with 2 Post Foldable ROPS w/ Retractable Seat Belt	2198	\$ 14,305.00

L3400F-1R		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8865**	F-TIRE 5-15 F2 Steel Bias CA	28	\$ 123.00	\$14,257.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8890A	F-TIRE 23x8.5-12 R3 TF Steel Bias AA	32	\$ 165.00	\$14,327.00
ALR8804A	① R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	

L3400F-1F		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8865**	F-TIRE 5-15 F2 Steel Bias CA	28	\$ 123.00	\$14,305.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8890A	F-TIRE 23x8.5-12 R3 TF Steel Bias AA	32	\$ 165.00	\$14,375.00
ALR8804A	① R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

## L3400DT-1

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model #D1803  
3 Cyl. 111.4 cu. In.  
+ 34.2 Net Eng. HP  
+ 30 PTO HP  
@ 2700 Eng. Rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
12V – 490 CCA Battery  
Charging Output 40 Amps  
Electric Key Shut-off

### HYDRAULICS

Open Center — Gear Type  
6.8 gpm Remote/3 Pt. Hitch  
4.1 gpm for Power Steering  
10.9 Total gpm  
Cat I 3-point Hitch  
At lift Point 1985 lbs.  
24" Behind 1433 lbs.

### FRONT AXLE

Integral Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable  
+ Manufacturer Estimate

### DRIVE TRAIN

Sliding Gear Constant Mesh  
8 Forward Speeds  
4 Reverse Speeds  
Multiple Wet Disc Brakes  
Clutch – Dual Clutch, Dry Plates  
Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
Fuel Gauge  
Temperature Gauge

### FLUID CAPACITY

Fuel Tank 9.0 gal.  
Cooling System 6.3 qts.  
Crankcase 6.0 qts.  
Transmission and 7.3 gal.  
Hydraulics  
Front Axle 4.8 qts.

### POWER TAKE OFF

Live-Continuous Running (Dual Clutch)  
Speed - 540 @ 2425 Eng. rpm  
540 rpm Rear PTO – 1 Speed  
SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

ROPS w / Retractable Seat Belt  
PTO Shield  
Safety Start Switches  
Mechanical Wet Disc Brakes  
Parking Brakes  
SMV Sign

### OPERATOR STATION

Color coded controls  
Wide platform steps  
High Back Seat with Adjustable Suspension  
Operator Presence Control System

### TIRES AND WHEELS

Front 7.00 x 16 R1  
Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3400DT-1R	* 4WD TRACTOR with 2 Post Rigid ROPS w/ Retractable Seat Belt	2337	\$ 15,800.00
L3400DT-1F	* 4WD TRACTOR with 2 Post Foldable ROPS w/ Retractable Seat Belt	2343	\$ 15,848.00

L3400DT-1R		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$15,800.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$15,676.00
ALR8804A	① R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$16,454.00
ALR8809	① R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

L3400DT-1F		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$15,848.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$15,724.00
ALR8804A	① R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$16,502.00
ALR8809	① R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

## L3400HST-1

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

**DIESEL ENGINE**  
 Model #D1803  
 3 Cyl. 111.4 cu. In.  
 + 34.2 Net Eng. HP  
 + 28.5 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V – 490 CCA Battery  
 Charging Output 40 Amps  
 Electric Key Shut-off

**HYDRAULICS**  
 Open Center — Gear Pump  
 6.8 gpm Remote/3 Pt. Hitch  
 4.1 gpm for Power Steering  
 10.9 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 1985 lbs.  
 24" Behind 1433 lbs.

**FRONT AXLE**  
 Integral Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable  
 + Manufacturer Estimate

**DRIVE TRAIN**  
 Hydrostatic Drive  
 3 Speeds L-M-H  
 Multiple Wet Disc Brakes  
 Clutch – Dry Type / Single Stage  
 Differential Lock

**DASH INSTRUMENTS**  
 Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

**FLUID CAPACITY**  
 Fuel Tank 9.0 gal.  
 Cooling System 6.3 qts.  
 Crankcase 6.0 qts.  
 Transmission and Hydraulics 7.3 gal.  
 Front Axle 4.8 qts.

**POWER TAKE OFF**  
 Live-Continuous Running  
 Speed - 540 @ 2425 Eng. rpm  
 540 rpm Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline

**SAFETY EQUIPMENT**  
 ROPS w / Retractable Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 SMV Sign  
 Turn Signals / Hazard Lights

**OPERATOR STATION**  
 Color coded controls  
 Wide platform steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control System  
 Cruise Control  
 Cup Holder

**TIRES AND WHEELS**  
 Front 7.00 x 16 R1  
 Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3400HST-1R	* 4WD TRACTOR with 2 Post Rigid ROPS w/ Retractable Seat Belt	2440	\$ 16,954.00
L3400HST-1F	* 4WD TRACTOR with 2 Post Foldable ROPS w/ Retractable Seat Belt	2381	\$ 17,002.00

L3400HST-1R		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$16,954.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$16,830.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$17,608.00
ALR8809 ①	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

L3400HST-1F		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$17,002.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$16,878.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$17,656.00
ALR8809 ①	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

# KUBOTA

## L3700SUHSTP

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model #D1803  
3 Cyl. 111.4 cu. In.  
+ 35.7 Net Eng. HP  
+ 30.0 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
12V – 490 CCA Battery  
Charging Output 40 Amps  
Electric Key Shut-off

### HYDRAULICS

Open Center — Gear Pump  
6.8 gpm Remote/3 Pt. Hitch  
4.1 gpm for Power Steering  
10.9 Total gpm  
Cat I 3-point Hitch  
At lift Point 1998 lbs.  
24" Behind 1435 lbs.

### FRONT AXLE

Integral Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

### DRIVE TRAIN

Hydrostatic Drive  
3 Speeds L-M-H  
Multiple Wet Disc Brakes  
Clutch – Dry Type / Single Stage  
Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
Fuel Gauge  
Temperature Gauge

### FLUID CAPACITY

Fuel Tank 9.0 gal.  
Cooling System 6.3 qts.  
Crankcase 7.5 qts.  
Transmission and 6.2 gal.  
Hydraulics

### POWER TAKE OFF

Live-Continuous Running  
Speed - 540 @ 2425 Eng. rpm  
540 rpm Rear PTO – 1 Speed  
SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

ROPS w / Retractable Seat Belt  
PTO Shield  
Safety Start Switches  
Mechanical Wet Disc Brakes  
Parking Brakes  
SMV Sign  
Turn Signals / Hazard Lights

### OPERATOR STATION

Color coded controls  
Wide platform steps  
Operator Presence Control System  
Cup Holder

### TIRES AND WHEELS

Front 7.00 x 16 R1  
Rear 11.2 x 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3700SUHSTP	4WD TRACTOR with 2 Post Foldable ROPS w/ Retractable Seat Belt	2381	\$ 16,002.00

L3700SUHSTP		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$16,002.00
ALR9494**	R-TIRE 11.2-24 TITAN HI-PWR LUG ASSY	162	\$ 435.00	
ALR8893A	F-TIRE 25x8.5-14 R3 TF Steel Bias CA	38	\$ 207.00	\$15,878.00
ALR8804A ①	R-TIRE 13.6-16 R3 TF Steel Bias AA	127	\$ 428.00	
AMR8977A	F-TIRE 27x8.50-15 6 PLY BIAS TITAN PNF	53	\$ 251.00	\$16,656.00
ALR8809 ①	R-TIRE 15-19.5 R4 IN Steel Bias AA	201	\$ 773.00	

① Not compatible with L8066A Wheel Weights.

\*\* Standard tires.

# KUBOTA

## L4400F-1

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V-2203  
 4 Cyl. 134.1 cu. in.  
 + 43.0 Net Eng. HP  
 + 37.5 PTO HP  
 @ 2600 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Radial Air Flow Cooling  
 12V, RC:133 mm, CCA:582A  
 Charging Output 40 Amps  
 Electric Key Shutoff

### HYDRAULICS

Open Center — Gear Type  
 Dual Pumps  
 8.4 gpm Remote/3 Pt. Hitch  
 5.1 gpm for Power Steering  
 13.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 2870 lbs.  
 24" Behind 2310 lbs.

+ Manufacturer Estimate

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, Cast Iron  
 Tread Spacing, nonadjustable

### DRIVE TRAIN

Gear Shift Transmission  
 8 Forward Speeds  
 4 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch – Dry Type Single Stage  
 Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

### FLUID CAPACITY

Fuel Tank 11.1 gal.  
 Cooling System 6.9 qts.  
 Crankcase 8.0 qts.  
 Transmission and Hydraulics 42.4 qts.

### POWER TAKE OFF

Hydraulic Live Independent  
 540 rpm Rear PTO – 1 Speed  
 Speed - 540 @ 2475 Eng. rpm  
 SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

Foldable ROPS w / Retractable  
 Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 Turn Signals  
 SMV Sign  
 Hazard Lights

### OPERATOR STATION

Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control System  
 Cup Holder

### TIRES AND WHEELS

Front 7.5L - 15 F2  
 Rear 14.9 - 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4400F-1*	2WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt	2760	\$ 14,556.00

\* \* \*

L4400F-1		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8852A**	F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION	64	\$ 194.00	\$14,556.00
ALR6811A**	R-TIRE 14.9-24 R1BIAS SAT II	207	\$ 637.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$14,974.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	

\*\* Standard tires.

## L4400DT-1

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V-2203  
 4 Cyl. 134.1 cu. in.  
 + 43.0 Net Eng. HP  
 + 37.5 PTO HP  
 @ 2600 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Radial Air Flow Cooling  
 12V, RC:133 mm, CCA:582A  
 Charging Output 40 Amps  
 Electric Key Shutoff

### HYDRAULICS

Open Center — Gear Type  
 Dual Pumps  
 8.4 gpm Remote/3 Pt. Hitch  
 5.1 gpm for Power Steering  
 13.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 2870 lbs.  
 24" Behind 2310 lbs.

+ Manufacturer Estimate

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, Cast Iron  
 Tread Spacing, nonadjustable

### DRIVE TRAIN

Gear Shift Transmission  
 8 Forward Speeds  
 4 Reverse Speeds  
 Multiple Wet Disc Brakes  
 Clutch – Dry Type Single Stage  
 Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

### FLUID CAPACITY

Fuel Tank 11.1 gal.  
 Cooling System 6.9 qts.  
 Crankcase 8.0 qts.  
 Transmission and Hydraulics 42.4 qts.

### POWER TAKE OFF

Hydraulic Live Independent  
 540 rpm Rear PTO – 1 Speed  
 Speed - 540 @ 2475 Eng. rpm  
 SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

Foldable ROPS w / Retractable  
 Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 Turn Signals  
 SMV Sign  
 Hazard Lights

### OPERATOR STATION

Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control System  
 Cup Holder

### TIRES AND WHEELS

Front 8.3 - 16 R1  
 Rear 14.9 - 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4400DT-1*	4WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt	2760	\$ 20,050.00

\* \* \*

L4400DT-1		Price with Tire Option		
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$20,050.00
ALR6811A**	R-TIRE 14.9-24 R1BIAS SAT II	207	\$ 637.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$20,364.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$20,638.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$20,564.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	

\*\* Standard tires.



## L4400HST-1

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V-2203  
 4 Cyl. 134.1 cu. in. Tier III  
 + 43.0 Net Eng. HP  
 + 36.0 PTO HP  
 @ 2600 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Radial Air Flow Cooling  
 12V, RC:133 mm, CCA:582A  
 Charging Output 40 Amps  
 Electric Key Shutoff

### HYDRAULICS

Open Center — Gear Type  
 Dual Pumps  
 8.4 gpm Remote/3 Pt. Hitch  
 5.1 gpm for Power Steering  
 13.5 Total gpm  
 Cat I 3-point Hitch  
 At lift Point 2870 lbs.  
 24" Behind 2310 lbs.

+ Manufacturer Estimate

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, Cast Iron  
 Tread Spacing, nonadjustable

### DRIVE TRAIN

Feather Step HST  
 Hydraulic Pedal Assist  
 Cruise Control  
 Maximum Travel Speed 14.9 mph  
 Multiple Wet Disc Brakes  
 Clutch – Dry Type Single Stage  
 Differential Lock

### DASH INSTRUMENTS

Tachometer w/Hour Meter  
 Fuel Gauge  
 Temperature Gauge

### FLUID CAPACITY

Fuel Tank 11.1 gal.  
 Cooling System 6.9 qts.  
 Crankcase 8.0 qts.  
 Transmission and Hydraulics 47.5 qts.

### POWER TAKE OFF

Hydraulic Live Independent  
 540 rpm Rear PTO – 1 Speed  
 Speed - 540 @ 2475 Eng. rpm  
 SAE Std 1 3/8" Six Spline

### SAFETY EQUIPMENT

Foldable ROPS w / Retractable  
 Seat Belt  
 PTO Shield  
 Safety Start Switches  
 Mechanical Wet Disc Brakes  
 Parking Brakes  
 Turn Signals  
 SMV Sign  
 Hazard Lights

### OPERATOR STATION

Color Coded Controls  
 Wide Platform Steps  
 High Back Seat with Adjustable Suspension  
 Operator Presence Control System  
 Cup Holder

### TIRES AND WHEELS

Front 8.3 - 16 R1  
 Rear 14.9 - 24 R1

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4400HST-1*	4WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt	2840	\$ 21,890.00

\* \* \*

L4400HST-1		Price with Tire Option		
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$21,890.00
ALR6811A**	R-TIRE 14.9-24 R1BIAS SAT II	207	\$ 637.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$22,204.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$22,478.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$22,404.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	

\*\* Standard tires.

## Standard L Series Attachment Chart

Model	ROPS	Sunshade for ROPS	Front Suitcase Weights ②	Rear Wheel Weights ①	Double Element Air Cleaner	Spark Arrester	Ballast Box
L3200 L3800	Std (SFL-F380)	E1133 E1134	BL8060-1③ (Max. 5 pcs)	L8066A	TA040-93220	70000-01600	L8170
L4600	SFL-F460	E1133 E1134	BL8060-1③ (Max. 7 pcs)	L8066A	Std	70000-00280	L8170
L2800F (-1)* L2800DT (-1)* L2800HST (-1)*	Std (SFL-340) Opt. (SFL-F340)	E1133 E1134	BL8060-1③ (Max. 5 pcs)	L8066A	TA040-93220	70000-01600	L8170
L3400F (-1)* L3400DT (-1)* L3400HST (-1)*	Std (SFL-340) Opt. (SFL-F340)	E1133 E1134	BL8060-1③ (Max. 5 pcs)	L8066A	TA040-93220	70000-01600	L8170
L3700SU*	SFL-F340	E1133 E1134	BL8060-1③ (Max. 5 pcs)	L8066A	TA040-93220	70000-01600	L8170
L4400F-1 L4400DT-1 L4400HST-1	Std. (SFL-F440A)	E1134	BL8060-1④ (Max. 7 pcs)	L8066A	Std.	77700-00280	L8170
L4400F* L4400DT*	Std. (SLF-44) Opt. (SFL-F44)	E1133 E1134	BL8060-1④ (Max. 7 pcs)	L8066A	Std	N/A	L8170

① Only on 24" Rim.

② 4WD Models (DT and HST) require front weight bumper bracket (Standard on 2WD models). Not compatible with Front Grille Guard

③ Order from Parts (1) 32310-13810 Bumper Bracket, (4) 01173-51435 Bolts and (4) 04512-60140 Lock Washers.

④ Use MX8068 Front Weight Bracket with up to (7) BL8060-1 Front Suitcase Weight.

\* Subject to availability.

Model	Drawbar Clevis	Grille Guard⑤	Block Heater	3PT Stabilizer Kit	Extra Length Seat Belt	Draft Control
	Swinging Drawbar		Rear Work Light			Top-N-Tilt
L3200 L3800	L9496G N/A	MX8190	70000-00297 M9551	L8430	70002-06605	N/A
L4600	L9496G		L2267⑦			
L2800F (-1)* L2800DT (-1)* L2800HST (-1)*	L9496G N/A	L2251	70000-00297 M9551	L8430	70002-06605	N/A
L3400F (-1)* L3400DT (-1)* L3400HST (-1)*	L9496G N/A		L2251			
L3700SU	L9496G⑥ N/A	L2251	70000-00297 M9551	L8430	70002-06605	N/A
L4400F-1 L4400DT-1 L4400HST-1	L9496G		L2251			
L4400F* L4400DT*	L9496G L8416 L8416	L2251	70000-00297 M9551	STD	70002-06605	L8311A L8326 L8326A

⑤ For non-loader applications only, includes bracket to hold up to (4) BL8060-1 Front Suitcase Weights.

⑥ Optional L9491 Drawbar Assembly required.

\* Subject to availability.

## Standard L Series Dealer Installed Options

Tractor	Valve Options	Description	Valve Type	Stack-able	Required Parts	When Required	Notes
L3200, L3800, L2800, L3400, L3700SU	BL7303A	One rear remote valve, first position	Double-Acting	Y	L7314 Hose Kit	Required to install BL7303A <b>with</b> front loader	Must order BL7303A valve as the first rear remote
					L7315 Hose Kit	Required to install BL7303A <b>without</b> front loader	
					(1) 75541-68150 Tank Port Plug and (1) 75541-68160 O-Ring	All Installations	
	BL7373	One rear remote valve, second or third position	Double Acting w/ Detent, Not Self-Canceling	Y	BL7343 2nd Position Stacking Kit	When installing BL7373 as a 2nd rear remote (do not use when installing BL7353 3rd position stacking kit)	Order BL7373 as second or third rear remote
					BL7353 3rd Position Stacking Kit	When installing BL7373 as a 3rd rear remote (does not require BL7343 2nd position stacking kit)	
	BL7393	One rear remote valve, second or third position	Double Acting w/Float Detent	Y	BL7343 2nd Position Stacking Kit	When installing BL7393 as a 2nd rear remote (do not use when installing BL7353 3rd position stacking kit)	Order BL7393 as second or third rear remote
BL7353 3rd Position Stacking Kit					When installing BL7393 as a 3rd rear remote (does not require BL7343 2nd position stacking kit)		
L4400	L8407	One rear remote valve	Double-Acting	N	L8310 Hose Kit	Required to install L8407	All valve options require 70090-20823 male couplers for cylinder hoses as needed
					(1) 70090-20953	Required to install L8407 with backhoe	
	L8408	Two rear remote valves	Double-Acting	N	L8310 Hose Kit	Required to install L8408	
					(1) 70090-20940	Required to install L8408 with backhoe	
	L8409	Three rear remote valves	Double-Acting	N	L8310 Hose Kit	Required to install L8409	
					(1) 70090-20940 and (1) 70090-20953	Required to install L8409 with backhoe	
L4400-1	L8303	One remote valve, first, second or third position	Double Acting	Y	L8561 Base Kit and 1 <sup>st</sup> Lever	Required to install L8303 as 1 <sup>st</sup> Valve	Only 2 remote valves can be installed with BH90A/BH92 Backhoe
					L8562A 2 <sup>nd</sup> Lever	Required to install L8303 as 2 <sup>nd</sup> Valve	
					L8563A 3 <sup>rd</sup> Lever	Required to install L8303 as 3 <sup>rd</sup> Valve	
	L8304①	One remote valve, second position	Double Acting w/Float Detent	Y	L8562A 2 <sup>nd</sup> Lever	Required to install L8304 as 2 <sup>nd</sup> Valve	
L4600	L8303	One remote valve, first second or third position	Double Acting	Y	L8560 Base Kit and 1 <sup>st</sup> Lever	Required to install L8303 as 1 <sup>st</sup> Valve	Only 2 remote valves can be installed with BH92 Backhoe
					L8562 2 <sup>nd</sup> Lever	Required to install L8303 as 2 <sup>nd</sup> Valve	
	L8304①	One remote valve, second position	Double Acting w/Float Detent	Y	L8563A 3 <sup>rd</sup> Lever	Required to install L8303 as 3 <sup>rd</sup> Valve	
					L8562A 2 <sup>nd</sup> Lever	Required to install L8304 as 2 <sup>nd</sup> Valve	

① The L8304 can only be used in the second position.

## Standard L Series Dealer Installed Options

L3200 / L3800 / L2800 / L3400 / L3700SU / L4400 / L4600 Attachments

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>REAR REMOTE HYDRAULIC VALVES</b>			
BL7303	* Hydraulic Valve Kit (requires Hose Kit L7314/L7315) L2800, L3400, L3700SU	21	\$439.00
BL7303A	Hydraulic Valve Kit (requires Hose Kit L7314/L7315) L2800, L3400, L3700SU, L3200, L3800	21	\$501.00
L7314	L- Standard Series Hose Kit (required for BL7303 Hydraulic Valve Kit) L2800, L3400 (All Models with Loader), L3700SU, L3200, L3800	7	\$235.00
L7315	L- Standard Series Hose Kit (required for BL7303 Hydraulic Valve Kit) L2800, L3400 (All Models without Loader), L3700SU, L3200, L3800	9	\$272.00
<b>Additional valve types, dealer installed (select a valve section/s and the appropriate Stacking Kit to complete)</b>			
BL7343	2nd Position Stacking Kit to install 2nd valve section. Hardware and o-rings to install one (1) Additional valve section for BL7303 Requires BL7373 or BL7393 Valve Section.	2	\$50.00
BL7353	3rd Position Stacking Kit to install 3rd valve section. Hardware and o-rings to install two (2) additional valve sections to BL7303 or B7333 Requires BL7373 or BL7393 Valve Section(s).	2	\$50.00
BL7373	3-Position, DV-Detent Valve (Not Self-canceling) Closed Detent Valve Section The Valve Section features a single spool that should be used for double acting cylinders, both work ports are blocked in the neutral position with free flow oil through the valve in neutral. Important: The Detent position is not self-canceling and will not release when cylinder reaches end of stroke. Leaving this valve in detent position on a blocked circuit will cause system relief valve to remain open.	5	\$273.00
BL7393	4-Position, FD- Float Detent Section Both work ports are blocked in the neutral position. The Detent "float" position allows the hydraulic cylinder to float. Both work ports are blocked in the neutral position with free flow oil through the valve in neutral.	6	\$319.00

\* \* \*

# KUBOTA

## Standard L Series Dealer Installed Options

L3200 / L3800 / L2800 / L3400 / L3700SU / L4400 / L4600 Attachments (Cont.)

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>REAR REMOTE HYDRAULIC VALVES (cont.)</b>			
<b>L4400 MODELS</b>			
L8407	① Single Spool Remote Hyd. Valve Requires L8310.	18	\$868.00
L8408	① Double Spool Remote Hyd. Valve Requires L8310.	25	\$1,252.00
L8409	① Triple Spool Remote Hyd. Valve Requires L8310. NOTE: Remote Hydraulic Spool Valves are not stackable, i.e.: For Double Spool, only order L8408.	37	\$1,709.00
L8310	Hose Stay Kit	3	\$37.00

### L4400-1 / L4600 MODELS

L8303	Double Acting Valve Section	4	\$240.00
L8304	② Double Acting w/Float Detent Valve Section (2nd position only)	5	\$302.00
L8561	Base Kit & 1st Lever for L4400 Requires L8303 Valve to complete assembly.	16	\$512.00
L8562	Second Position Stacking Kit and 2nd Lever for L4400. Requires L8303 or L8304 Valve to complete assembly.	7	\$248.00
L8563	Third Position Stacking Kit and 3rd Lever for L4400. Requires L8303 Valve to complete assembly. Not compatible with BH4979 BH90A Mounting Kit	8	\$248.00
L8560	Base Kit & 1st Lever for L4600 Requires L8303 Valve to complete assembly.	16	\$512.00
L8562A	Second Position Stacking Kit and 2nd Lever for L4600. Requires L8303 or L8304 Valve to complete assembly.	7	\$248.00
L8563A	Third Position Stacking Kit and 3rd Lever for L4600. Requires L8303 Valve to complete assembly. Not compatible with BH4979 BH90A Mounting Kit	8	\$248.00

① Backhoe applications require relocating remote couplers due to backhoe seat interference. Order from Parts Dept: L8407 requires (1) 70090-20953, L8408 requires (1) 70090-20940, L8409 requires (1) 70090-20940 and (1) 70090-20953. These kits provide new couplers connected directly to the remote valves. If male couplers are required for cylinder hoses, order appropriate quantities of 70090-20823 male couplers.

② The L8304 can only be used in the second position.

# KUBOTA

## Standard L Series Dealer Installed Options

L3200 / L3800 / L2800 / L3400 / L3700SU / L4400 / L4600 Attachments (Cont.)

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>DRAWBAR OPTIONS</b>			
L9491	Drawbar Assembly (L3700SU)	25	\$128.00
L8479	Drawbar Assembly (L4400F-1 only)	25	\$140.00
L8416	Swinging Drawbar (L4400)	21	\$198.00
L9496G	Drawbar Clevis	8	\$67.00
<b>CRUISE CONTROL</b>			
L9485	Cruise Control Kit (L3700SU)	25	\$205.00
L8455	Cruise Control Kit (L3200HST and L3800HST)	25	\$205.00
<b>GRILLE GUARD (Non-Loader Applications)</b>			
L2251	② Front Grille Guard (L2800/3400/3700SU/4400) (Non-loader applications)	48	\$269.00
L2267	Front Grille Guard (L3200/3800/4600) (Non-loader applications)	61	\$319.00
<b>SEAT BELT KIT</b>			
	70002-06605 Extra Length Seat Belt Kit		(Order from Parts Department)
<b>FRONT SUITCASE WEIGHTS</b>			
BL8060-1	① Front Suitcase Weight Requires (1) BL8060B Bolt Kit per Weight	55	\$71.00
BL8060B	Bolt Kit (1 per Weight) Use with (5) weight bracket 32310-13810 and L2251 Grille Guard. Use with MX8068 (7) weight bracket.	1	\$2.00
<b>FRONT WEIGHT BRACKET KIT</b>			
32310-13810	1-5 Weights, L3200, L3800, L3400, L3700SU 4WD models (Std. on 2WD models) Requires (4) 01173-51435 Bolts, (4) 04512-60140 Washers		(Order from Parts Department)
MX8068	③ 1-7 Weights, L4400/L4600 4WD Models (Std. on L4400/L4600 2WD models) includes mounting hardware.	25	\$96.00
<b>REAR WHEEL WEIGHTS</b>			
L8066A	④ Rear Wheel Weight 64 lbs. each Set of 2 Weights, requires L8067A Bolt Kit Maximum of 3 Sets. (Not compatible with Turf Tires or R4 Ind. Tires.)	128	\$124.00
L8067A	Bolt Kit for L8066 Weight 1 Kit will hold up to (3) sets of weights	5	\$33.00

- ① Four wheel drive models (DT and HST) require front weight bumper bracket.
- ② Grille Guard includes bracket to hold up to (4) BL8060-1 Front Suitcase Weights.
- ③ MX8068 Front Weight Bracket is not compatible with L2251 Grille Guard
- ④ Not compatible with Turf tires or R4 tires.

## Standard L Series Dealer Installed Options

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>TOP-N-TILT-KIT</b>			
L8326A	①②⑤ Top-N-Tilt Kit (L4400-1, L4600)	44	\$871.00
<b>3PT STABILIZERS</b>			
L8430	③ 3 Pt. Hitch Stabilizer Kit (L2800/L3400/L3700SU/L3200/L3800)	15	\$175.00
<b>SUNSHADE FOR ROPS</b>			
E1133	Standard Sunshade	63	\$437.00
E1134	Deluxe Sunshade Requires E1136 Mounting Bracket Kit	63	\$387.00
E1136	Mounting Bracket Kit for E1134	30	\$191.00
E1138	Front Work Light Kit for E1134 (includes 2 lights)	10	\$125.00
<b>BLOCK HEATER</b>			
70000-00297	Block Heater		(Order from Parts Department)
<b>DUAL ELEMENT AIR CLEANER ③</b>			
TA040-93220	Inner Element (L2800/L3400/L3700SU/L3200/L3800) Only inner element is needed to create Dual Element Air Cleaner		(Order from Parts Department)
<b>DRAFT CONTROL</b>			
L8311A	Draft Control Kit L4400/L4400-1 models	25	\$462.00
L8311C	Draft Control Kit - L4600 Models	25	\$462.00
<b>SPARK ARRESTOR</b>			
70000-01600	Screen Type for L2800/L3400/L3700SU/L3200/L3800		(Order from Parts Department)
77700-00280	④ Screen Type for L4400-1		(Order from Parts Department)
L8368	Low Back Pressure Muffler (L4400-1)	25	\$228.00
<b>REAR WORK LIGHT</b>			
M9551	Rear Work Light (one light) (L2800 / L3400 / L3700SU / L4400 / L4600)	4	\$85.00
L8327	Rear Work Light Kit (L3200/L3800)		\$85.00
<b>BALLAST BOX</b>			
L8170	Ballast Box (1000 lbs cap. with dry sand) (L2800/L3400/L3700SU/L3200/L3800/L4400/L4600)	168	\$449.00

\* Subject to availability.

- ① L8326 Top-N-Tilt Kit: All L Series tractors will require the L8303 or L8304, L8561, and L8562 L8303 Double Acting Valve Section or L8304 Float Detent Valve Section L8561 Base Kit and First Lever: Requires L8303 or L8304 to complete assembly. L8562 Section Position Stacking Kit: Requires additional L8303 or L8304. L8563 Third Position Stacking Kit: Requires additional L8303 or L8304.
- ② Requires either L8408 or L8409 Remote Valves. (L8409 is required if Box Scraper has hydraulic scarifier.)
- ③ Standard items for L4400, L4400-1.
- ④ L8368 Low Back Pressure Muffler required for L4400-1.
- ⑤ Not compatible with BH90/BH92 and BL4690B.

**This page intentionally left blank.**



## Grand L - 40 Series

MODEL NAME	PTO H.P.	2 OR 4 WD	Trans. Type	Synchro Shuttle	Full ② Synchro	Trans. Speeds	PTO Type	Opt. Mid PTO③	Hyd. Power Steering	Creep Speed	Loader Valve
L3240 32.0 ①	26.5	2WD	F	S	S	8F X 8R	L Ind. Hyd.	C	S	OPT	S
	26.5	4WD	DT	S	S	8F X 8R	L Ind. Hyd.	C	S	OPT	S
	26.5	4WD	GST	S	S	12F X 8R	L Ind. Hyd.	C	S	OPT	S
	25.0	4WD	HST	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S
	25.0	4WD	HSTC	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S
L3540 35.0 ①	29.5	4WD	GST	S	S	12F X 8R	L Ind. Hyd.	C	S	OPT	S
	28.0	4WD	HST	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S
	28.0	4WD	HSTC	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S
L3940 38.5 ①	33.0	4WD	DT	S	S	8F X 8R	L Ind. Hyd.	C	S	OPT	S
	33.0	4WD	GST	S	S	12F X 8R	L Ind. Hyd.	C	S	OPT	S
	31.5	4WD	HST	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S
	31.5	4WD	HSTC	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S
L4240 42.0 ①	36.5	4WD	DT	S	S	8F X 8R	L Ind. Hyd.	C + I	S	OPT	S
	36.5	4WD	GST	S	S	12F X 8R	L Ind. Hyd.	C + I	S	OPT	S
	35.0	4WD	HST	N/A	N/A	Infinite	L Ind. Hyd.	C + I	S	N/A	S
	35.0	4WD	HSTC	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S
L4740 47.0 ①	41.5	4WD	GST	S	S	12F X 8R	L Ind. Hyd.	C + I	S	OPT	S
	40.0	4WD	HST	N/A	N/A	Infinite	L Ind. Hyd.	C + I	S	N/A	S
	40.0	4WD	HSTC	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S
L5040 50.0 ①	44.0	4WD	GST	S	S	12F X 8R	L Ind. Hyd.	C + I	S	OPT	S
L5240 52.0 ①	45.0	4WD	HST	N/A	N/A	Infinite	L. Ind. Hyd.	C + I	S	N/A	S
	45.0	4WD	HSTC	N/A	N/A	Infinite	L. Ind. Hyd.	C	S	N/A	S
L5740 57.0 ①	50.0	4WD	HST	N/A	N/A	Infinite	L. Ind. Hyd.	C + I	S	N/A	S
	50.0	4WD	HSTC	N/A	N/A	Infinite	L Ind. Hyd.	C	S	N/A	S

S = Standard Equipment

OPT = Field Installed Option

① Net Engine Horsepower

② Main Transmission (4 Speed)

③ C = Cassette style installation, C + I = Cassette plus requires internal gear installation.

## L3240F-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # D1703  
3 Cyl., 100.5 cu. in.  
+ 32.0 Net Eng. HP  
+ 26.5 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
Charging Output 40 Amps  
Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type, Dual Pumps  
4.9 gpm Power Steering  
8.3 gpm Remote/3 Pt. Hitch  
13.2 gpm Total Hyd. Flow  
Lift Capacity —  
At lift Point 3750 lbs.  
24" Behind 2650 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
Tubular Steel Beam, 2WD  
Adjustable (Telescoping) Tread Spacing

### DRIVE TRAIN

8 Forward / 8 Reverse  
Manual w/ Synchro Main and Shuttle  
Transmission  
Mech. Wet Disc Brakes  
Clutch — Dry Single Stage  
Differential Lock

### FLUID CAPACITY

Fuel Tank 11.6 gal  
Cooling System 6.3 qts  
Crankcase 6.0 qts  
Transmission and  
Hydraulics 11.1 gal

### POWER TAKE OFF

1 Speed Rear Live — HYD. IND.  
540 rpm @ 2550 Eng. rpm  
Electric over Hydraulic PTO Switch  
(-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switch

### STANDARD EQUIPMENT (Cont.)

Highback Adj. Reclining Seat  
w/Arm Rests  
Parking Brakes  
Electric Key Shut-off  
Tilt Steering  
Wide Anti-Slip Step  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Operator Presence Control System  
Telescoping Lower Links  
Halogen Head Lights  
4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO  
speeds, diagnostics system  
Warning Symbols

### TIRES AND WHEELS

Front 6.00-16 F2 AG  
Rear 12.4 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3240F-1	* L3240F-1 2WD TRACTOR with 2 Post Foldable ROPS (97.4" height)	2822	\$ 18,201.00
L3240F-2/-3	L3240F-2/F-3 2WD TRACTOR with 2 Post Foldable ROPS (94.1" height)	2822	\$ 18,201.00

\*\*\*

TIRES AND WHEELS (priced per piece) L3240F-1/-2/-3				Price with Tire Option	
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST	
ALR8852A**	F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION	64	\$ 194.00	\$18,201.00	
ALR8821B**	R-TIRE 12.4-24 FIRESTONE SAT II AG	154	\$ 533.00		
AMXR8837	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 311.00	\$19,019.00	
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00		
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$18,449.00	
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00		
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$19,367.00	
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00		

\*\* Standard tires.

## L3240DT-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # D1703  
3 Cyl., 100.5 cu. in.  
+ 32.0 Net Eng. HP  
+ 26.5 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
Charging Output 40 Amps  
Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type,  
Dual Pumps  
4.9 gpm Power Steering  
8.3 gpm Remote/3 Pt. Hitch  
13.2 gpm Total Hyd. Flow  
Lift Capacity —  
At lift Point 3750 lbs.  
24" Behind 2650 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

### DRIVE TRAIN

8 Forward / 8 Reverse  
Manual w/Synchro Main  
and Shuttle Transmission  
Mech. Wet Disc Brakes  
Clutch — Single Dry Plate  
Differential Lock

### FLUID CAPACITY

Fuel Tank 11.6 gal  
Cooling System 6.3 qts  
Crankcase 6.0 qts  
Transmission and 11.1 gal  
Hydraulics  
Front Axle 6.9 qts

### POWER TAKE OFF

Rear -1 Speed Live — HYD. IND.  
540 rpm @ 2550 Eng. rpm  
Electric over hydraulic PTO Switch  
(-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switch

### STANDARD EQUIPMENT (Cont.)

High Back Adj. Reclining Seat  
w/Arm Rests  
Parking Brakes  
Electric Key Shut-off  
Tilt Steering  
Wide Anti-Slip Step  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Operator Presence Control System  
Telescoping Lower Links  
Halogen Head Lights  
4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO  
speeds, diagnostics system  
Warning Symbols

### TIRES AND WHEELS

Front 7.2 - 16 R1 AG  
Rear 12.4 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3240DT-1	* L3240DT-1 4WD TRACTOR with 2 Post Foldable ROPS (97.4" height)	2919	\$ 19,948.00
L3240DT-2/-3	L3240DT-2/-3 4WD TRACTOR with 2 Post Foldable ROPS (94.1" height)	2919	\$ 19,948.00

\* \* \*

L3240DT-1		Price with Tire Option		
L3240DT-2		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
L3240DT-3				
ORDER CODE	DESCRIPTION			
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$19,948.00
ALR8821B**	R-TIRE 12.4-24 FIRESTONE SAT II AG	154	\$ 533.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$20,616.00
ALR8855	R-TIRE 420/70-24 R4 IN Steel Bias DA	235	\$ 777.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$20,648.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$20,060.00
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$20,978.00
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	

\*\* Standard tires.

## L3240GST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # D1703  
3 Cyl., 100.5 cu. in.  
+ 32.0 Net Eng, HP  
+ 26.5 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
Charging Output 40 Amps  
Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type Dual Pumps  
4.9 gpm Power Steering  
8.3 gpm Remote/3 Pt. Hitch  
13.2 gpm Total Hyd. Flow  
Cat I 3-point Hitch —  
At lift Point 3750 lbs.  
24" Behind 2650 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, 4WD  
Cast iron  
Tread Spacing, Nonadjustable

### DRIVE TRAIN

12 Forward / 8 Reverse  
Glideshift w / Synchro Shuttle  
Mech. Wet Disc Brakes  
Clutch — Single Dry Plate  
Differential Lock

### FLUID CAPACITY

Fuel Tank 11.6 gal  
Cooling System 6.3 qts  
Crankcase 6.0 qts  
Transmission and 11.1 gal  
Hydraulics  
Front Axle 6.9 qts

### POWER TAKE OFF

Rear -1 Speed Live Hyd. Independent  
540 rpm @ 2550 Eng. rpm  
Electric over Hydraulic PTO Switch  
(-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switch  
High Back Adj. Reclining Seat  
w/Arm Rests

### STANDARD EQUIPMENT (Cont.)

Parking Brakes  
Electric Key Shut-off  
Tilt Steering  
Wide Anti-Slip Step  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Operator Presence Control System  
Telescoping Lower Links  
Halogen Headlights  
4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO  
speeds, diagnostics system  
Warning Symbols

### TIRES AND WHEELS

Front 7.2 - 16 R1 AG  
Rear 12.4 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3240GST-1 *	L3240GST-1 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	2954	\$ 21,091.00
L3240GST-2/-3	L3240GST-2/-3 4WD TRACTOR with 2 Post Foldable ROPS (94.1" High)	2954	\$ 21,091.00

\* \* \*

L3240GST-1		Price with Tire Option		
L3240GST-2				
L3240GST-3				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$21,091.00
ALR8821B**	R-TIRE 12.4-24 FIRESTONE SAT II AG	154	\$ 533.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$21,759.00
ALR8855	R-TIRE 420/70-24 R4 IN Steel Bias DA	235	\$ 777.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$21,791.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$21,203.00
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$22,121.00
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	

\*\* Standard tires.

## L3240HST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # D1703  
3 Cyl., 100.5 cu. in.  
+ 32.0 Net Eng, HP  
+ 25.0 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
Charging Output 40 Amps  
Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type Dual  
Pumps  
4.9 gpm Power Steering  
8.3 gpm Remote/3 Pt. Hitch  
13.2 gpm Total Hyd. Flow  
Cat I 3-point Hitch —  
At lift Point 3750 lbs.  
24" Behind 2650 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, 4WD  
Cast iron  
Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
Stall Guard Plus (-3 only)  
3 Speed Low-Medium-High  
Mech. Wet Disc Brakes  
Clutch - Single Dry Plate  
Differential Lock  
Cruise Control

### FLUID CAPACITY

Fuel Tank 11.6 gal  
Cooling System 6.3 qts  
Crankcase 6.0 qts  
Transmission and  
Hydraulics 11.1 gal  
Front Axle 6.9 qts

### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
540 rpm @ 2550 Eng. rpm  
Electric over Hydraulic PTO Switch  
(-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switches

### STANDARD EQUIPMENT (Cont.)

High Back Adj. Reclining Seat  
w/Arm Rests  
Parking Brakes  
Electric Key Shut-off  
Wide Anti-Slip Step  
Tilt Steering  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Telescoping Lower Links  
Operator Presence Control System  
Halogen Headlights  
4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO  
speeds, diagnostics system  
Warning Symbols

### TIRES AND WHEELS

Front 7.2 - 16 R1 AG  
Rear 12.4 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3240HST-1	* L3240HST-1 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	3005	\$ 21,586.00
L3240HST-2/-3	L3240HST-2/-3 4WD TRACTOR with 2 Post Foldable ROPS (94.1" High)	3005	\$ 21,586.00

\*\*\*

L3240HST-1		L3240HST-2		L3240HST-3	
TIRES AND WHEELS (priced per piece)					
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	Price with Tire Option	
				SUGG. LIST	
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$21,586.00	
ALR8821B**	R-TIRE 12.4-24 FIRESTONE SAT II AG	154	\$ 533.00		
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$22,254.00	
ALR8855	R-TIRE 420/70-24 R4 IN Steel Bias DA	235	\$ 777.00		
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$22,286.00	
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00		
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$21,698.00	
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00		
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$22,616.00	
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00		

\*\* Standard tires.

## L3240HSTC-1/-3

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model # D1703  
 3 Cyl., 100.5 cu. in.  
 + 32.0 Net Eng, HP  
 + 25.0 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 60 Amps  
 Radial Air Flow Cooling

#### HYDRAULICS

Open Center — Gear Type Dual  
 Pumps  
 4.9 gpm Power Steering  
 8.3 gpm Remote/3 Pt. Hitch  
 13.2 gpm Total Hyd. Flow  
 Cat I 3-point Hitch —  
 At lift Point 3750 lbs.  
 24" Behind 2650 lbs.

#### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast iron  
 Tread Spacing, Nonadjustable

#### DRIVE TRAIN

HST Plus  
 Stall Guard Plus (-3 only)  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock  
 Cruise Control

#### FLUID CAPACITY

Fuel Tank 11.6 gal  
 Cooling System 6.3 qts  
 Crankcase 6.0 qts  
 Transmission and  
 Hydraulics 11.1 gal  
 Front Axle 6.9 qts

#### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

#### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

#### STANDARD EQUIPMENT

ROPS Certified Cab  
 w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switches  
 High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Electric Key Shut-off  
 Tilt Steering  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve  
 2 Front Work Lights  
 L/R Anti-slip Steps  
 Radio-wired  
 12V Outlet  
 L/R Door Struts  
 Heater and A/C  
 Front Wipe/Wash (2 Speed)  
 Horn  
 Cloth Headliner (-3 only)

#### TIRES AND WHEELS

Front 7.2 - 16 R1 AG  
 Rear 12.4 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3240HSTC-1/-3	L3240HSTC-1/-3 4WD CAB TRACTOR	2913	\$ 28,951.00

L3240HSTC-1		Price with Tire Option		
L3240HSTC-3		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ORDER CODE	DESCRIPTION			
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$28,951.00
ALR8821B**	R-TIRE 12.4-24 FIRESTONE SAT II AG	154	\$ 533.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$29,619.00
ALR8855	R-TIRE 420/70-24 R4 IN Steel Bias DA	235	\$ 777.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$29,651.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$29,063.00
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$29,981.00
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	

\*\* Standard tires.

## L3540GST-1/-2/-3

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model # D1803  
 3 Cyl., 111.4 cu. in.  
 + 35.0 Net Eng. HP  
 + 29.5 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 40 Amps  
 Radial Air Flow Cooling

#### HYDRAULICS

Open Center — Gear Type Dual  
 Pumps  
 4.9 gpm Power Steering  
 8.3 gpm Remote/3 Pt. Hitch  
 13.2 gpm Total Hyd. Flow  
 Cat 1 3-point Hitch —  
 At lift Point 3750 lbs.  
 24" Behind 2650 lbs.

#### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

#### DRIVE TRAIN

12 Forward / 8 Reverse  
 Glideshift w / Synchro Shuttle  
 Mech. Wet Disc Brakes  
 Clutch — Single Dry Stage  
 Differential Lock

#### FLUID CAPACITY

Fuel Tank 11.6 gal  
 Cooling System 7.9 qts  
 Crankcase 7.1 qts  
 Transmission and 11.1 gal  
 Hydraulics  
 Front Axle 6.9 qts

#### POWER TAKE OFF

Rear - 1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over hydraulic PTO Switch  
 (-3 only)

#### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switches  
 High Back Adj. Reclining Seat  
 w/Arm Rests

#### STANDARD EQUIPMENT (Cont.)

Parking Brakes  
 Electric Key Shut-off  
 Wide Anti-Slip Step  
 Tilt Steering  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve

#### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

#### TIRES AND WHEELS

Front 7.2 - 16 R1 AG  
 Rear 12.4 - 24 R1 AG

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3540GST-1	* L3540GST-1 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	2972	\$ 22,410.00
L3540GST-2/-3	L3540GST-2/-3 4WD TRACTOR with 2 Post Foldable ROPS (94.1" High)	2972	\$ 22,410.00

\*\*\*

L3540GST-1
L3540GST-2
L3540GST-3

TIRES AND WHEELS (priced per piece)				Price with Tire Option	
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST	
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00		
ALR8821B**	R-TIRE 12.4-24 FIRESTONE SAT II AG	154	\$ 533.00	\$22,410.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00		
ALR8855	R-TIRE 420/70-24 R4 IN Steel Bias DA	235	\$ 777.00	\$23,078.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00		
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	\$23,110.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00		
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	\$22,522.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00		
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	\$23,440.00	

\*\* Standard tires.

## L3540HST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # D1803  
3 Cyl., 111.4 cu. in.  
+ 35.0 Net Eng. HP  
+ 28.0 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
Charging Output 40 Amps  
Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type Dual Pumps  
4.9 gpm Power Steering  
8.3 gpm Remote/3 Pt. Hitch  
13.2 gpm Total Hyd. Flow  
Cat I 3-point Hitch —  
At lift Point 3750 lbs.  
24" Behind 2650 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
Stall Guard Plus (-3 only)  
3 Speed Low-Medium-High  
Mech. Wet Disc Brakes  
Clutch — Single Dry Plate  
Differential Lock  
Mech. Lever Cruise Control

### FLUID CAPACITY

Fuel Tank 11.6 gal  
Cooling System 7.9 qts  
Crankcase 7.1 qts  
Transmission and Hydraulics 11.1 gal  
Front Axle 6.9 qts

### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
540 rpm @ 2550 Eng. rpm  
Electric over Hydraulic PTO Switch  
(-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switches

### STANDARD EQUIPMENT (Cont.)

High Back Adj. Reclining Seat w/Arm Rests  
Parking Brakes  
Electric Key Shut-off  
Wide Anti-Slip Step  
Tilt Steering  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Telescoping Lower Links  
Operator Presence Control System  
Halogen Headlights  
4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO speeds, diagnostics system  
Warning Symbols

### TIRES AND WHEELS

Front 7.2 - 16 R1 AG  
Rear 12.4 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3540HST-1	* L3540HST-1 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	3034	\$ 22,904.00
L3540HST-2/-3	L3540HST-2/-3 4WD TRACTOR with 2 Post Foldable ROPS (94.1" High)	3034	\$ 22,904.00

\*\*\*

L3540HST-1		L3540HST-2		L3540HST-3	
TIRES AND WHEELS (priced per piece)					
				Price with Tire Option	
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST	
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$22,904.00	
ALR8821B**	R-TIRE 12.4-24 FIRESTONE SAT II AG	154	\$ 533.00		
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$23,572.00	
ALR8855	R-TIRE 420/70-24 R4 IN Steel Bias DA	235	\$ 777.00		
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$23,604.00	
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00		
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$23,016.00	
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00		
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$23,934.00	
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00		

\*\* Standard tires.



## L3540HSTC-1/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # D1803  
 3 Cyl., 111.4 cu. in.  
 + 35.0 Net Eng. HP  
 + 28.0 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 55 Amps  
 Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type  
 Dual Pumps  
 4.9 gpm Power Steering  
 8.3 gpm Remote/3 Pt. Hitch  
 13.2 gpm Total Hyd. Flow  
 Cat I 3-point Hitch —  
 At lift Point 3750 lbs.  
 24" Behind 2650 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

### DRIVE TRAIN

HST Plus  
 Stall Guard Plus (-3 only)  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch — Single Dry Plate  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 11.6 gal  
 Cooling System 7.9 qts  
 Crankcase 7.1 qts  
 Transmission and Hydraulics 11.1 gal  
 Front Axle 6.9 qts

### POWER TAKE OFF

1 Speed Rear Live-Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

### STANDARD EQUIPMENT

ROPS Certified Cab w/Retractable  
 Seat Belt  
 Swivel Seat (-3 only)  
 Flat Deck w/Hanging Pedals  
 Tilt Steering Wheel  
 High Back Adj. Reclining Cloth Seat  
 w/Arm Rests  
 Safety Start Switches  
 Electric Key Shut Off  
 Turn Signals / Hazard Flashers  
 2 Frt. Work Lights  
 L/R Anti-Slip Steps  
 Heater and A/C  
 Frt. Wiper w/Washer (2 speed)  
 Radio-wired  
 Parking Brakes  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 12V Outlet  
 L/R Door Struts  
 ISO Mounted Platform  
 Halogen Headlights  
 4 Position Loader Valve  
 Horn  
 Cloth Headliner (-3 only)

### TIRES AND WHEELS

Front 7.2 - 16 R1 AG  
 Rear 12.4 - 24 R1 AG

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3540HSTC-1/-3	4WD CAB TRACTOR	3512	\$ 30,270.00

\* \* \*

L3540HSTC-1		Price with Tire Option		
L3540HSTC-3				
TIRES AND WHEELS (priced per piece)		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ALR8866D**	F-TIRE 7.2-16 POWER TORQUE 8PR R1	56	\$ 262.00	\$30,270.00
ALR8821B**	R-TIRE 12.4-24 FIRESTONE SAT II AG	154	\$ 533.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$30,938.00
ALR8855	R-TIRE 420/70-24 R4 IN Steel Bias DA	235	\$ 777.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$30,970.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$30,382.00
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$31,300.00
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	

\*\* Standard tires.

## L3940DT-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2003  
 4 Cyl., 120.0 cu. in.  
 + 38.5 Net Eng. HP  
 + 33.0 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 40 Amps  
 Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type,  
 Dual Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Lift Capacity —  
 At lift Point 3860 lbs.  
 24" Behind 2760 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

8 Forward / 8 Reverse  
 Manual w/ Synchro Main and  
 Shuttle Transmission  
 Mech. Wet Disc Brakes  
 Clutch — Dry Single Stage  
 Differential Lock

### FLUID CAPACITY

Fuel Tank 13.2 gal  
 Cooling System 7.9 qts  
 Crankcase 8.7 qts  
 Transmission and 11.4 gal  
 Hydraulics  
 Front Axle 6.9 qts

### POWER TAKE OFF

1 Speed Rear Live - Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switch

### STANDARD EQUIPMENT (Cont.)

High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Tilt Steering Wheel  
 Electric Key Shut-off  
 Wide Anti-Slip Step  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

### TIRES AND WHEELS

Front 8.3-16 R1 AG  
 Rear 14.9-24 R1AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3940DT-1	* 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	3067	\$ 23,441.00
L3940DT-2/-3	4WD TRACTOR with 2 Post Foldable ROPS (94.5" High)	3067	\$ 23,441.00

\* \* \*

L3940DT-1		Price with Tire Option		
L3940DT-2		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
L3940DT-3				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$23,441.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$23,955.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$23,965.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$23,377.00
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$24,295.00
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	

\*\* Standard tires.

# KUBOTA

## L3940GST-1/-2/-3

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model # V2003  
4 Cyl., 122.0 cu. in.  
+ 38.5 Net Eng. HP  
+ 33.0 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
Charging Output 40 Amps  
Radial Air Flow Cooling

#### HYDRAULICS

Open Center — Gear Type, Dual Pumps  
4.9 gpm Power Steering  
9.8 gpm Remote/3 Pt. Hitch  
14.7 gpm Total Hyd. Flow  
Lift Capacity —  
At lift Point 3860 lbs.  
24" Behind 2760 lbs.

#### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

#### DRIVE TRAIN

12 Forward / 8 Reverse  
Glideshift w / Synchro Shuttle  
Mech. Wet Disc Brakes  
Clutch — Dry Single Stage  
Differential Lock

#### FLUID CAPACITY

Fuel Tank 13.2 gal  
Cooling System 7.9 qts  
Crankcase 8.7 qts  
Transmission and Hydraulics 11.4 gal  
Front Axle 6.9 qts

#### POWER TAKE OFF

1 Speed Rear Live - Hyd. Independent  
540 rpm @ 2550 Eng. rpm  
Electric over Hydraulic PTO Switch  
(-3 only)

#### SAFETY EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switch  
Large Adj. Reclining Seat w/Arm Rests  
Parking Brakes  
Tilt Steering Wheel  
Electric Key Shut-off  
Wide Anti-Slip Step  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Telescoping Lower Links  
Operator Presence Control System  
Halogen Headlights  
4 Position Loader Valve

#### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO speeds, diagnostics system  
Warning Symbols

#### TIRES AND WHEELS

Front 8.3-16 R1 AG  
Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3940GST-1	* 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	3104	\$ 24,584.00
L3940GST-2/-3	4WD TRACTOR with 2 Post Foldable ROPS (94.5" High)	3104	\$ 24,584.00

L3940GST-1		Price with Tire Option		
L3940GST-2		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
L3940GST-3				
ORDER CODE	DESCRIPTION			
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$24,584.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$25,098.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$25,108.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$24,520.00
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$25,438.00
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	

\*\* Standard tires.

## L3940HST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2003  
 4 Cyl., 122.0 cu. in.  
 + 38.5 Net Eng. HP  
 + 31.5 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 40 Amps  
 Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type,  
 Dual Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Lift Capacity —  
 At lift Point 3860 lbs.  
 24" Behind 2760 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
 Stall Guard Plus (-3 only)  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Dry Single Stage  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 13.2 gal  
 Cooling System 7.9 qts  
 Crankcase 8.7 qts  
 Transmission and  
 Hydraulics 11.4 gal  
 Front Axle 6.9 qts

### POWER TAKE OFF

1 Speed Rear Live - Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switch  
 High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Tilt Steering Wheel  
 Electric Key Shut-off  
 Wide Anti-Slip Step  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

### TIRES AND WHEELS

Front 8.3-16 R1 AG  
 Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3940HST-1	* 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	3157	\$ 25,078.00
L3940HST-2/-3	4WD TRACTOR with 2 Post Foldable ROPS (94.5" High)	3157	\$ 25,078.00

\* \* \*

L3940HST-1		Price with Tire Option		
L3940HST-2		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
L3940HST-3				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$25,078.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$25,592.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$25,602.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$25,014.00
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$25,932.00
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	

\*\* Standard tires.

## L3940HSTC-1/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2003  
 4 Cyl., 122.0 cu. in.  
 + 38.5 Net Eng. HP  
 + 31.5 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 55 Amps  
 Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type,  
 Dual Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Lift Capacity —  
 At lift Point 3860 lbs.  
 24" Behind 2760 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
 Stall Guard Plus (-3 only)  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Dry Single Stage  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 13.2 gal  
 Cooling System 7.9 qts  
 Crankcase 8.7 qts  
 Transmission and  
 Hydraulics 11.4 gal  
 Front Axle 6.9 qts

### POWER TAKE OFF

1 Speed Rear Live - Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

### STANDARD EQUIPMENT

ROPS Certified Cab  
 w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switch  
 High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Tilt Steering Wheel  
 Electric Key Shut-off  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve  
 2 Front Work Lights  
 L/R Anti-Slip Steps  
 Radio-Wires  
 12V Outlet  
 L/R Door Struts  
 Heater and A/C  
 Front Wash/White (2 Speed)  
 Horn  
 Cloth Headliner (-3 only)

### TIRES AND WHEELS

Front 8.3-16 R1 AG  
 Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3940HSTC-1/-3	4WD CAB TRACTOR	3620	\$ 32,444.00

L3940HSTC-1		Price with Tire Option		
L3940HSTC-3				
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$32,444.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$32,958.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR6813	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$32,968.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR8868	F-TIRE 27X8.5 R3 TF Steel Bias CA	44	\$ 215.00	\$32,380.00
LR6801	R-TIRE 355/80-D20 R3 TF Steel Bias	188	\$ 636.00	
ALR8898	F-TIRE 27-1050LLx15 R3 TF Steel Bias FF	70	\$ 384.00	\$33,298.00
ALR6804	R-TIRE 41-18LLx16.1 R3 TF Steel Bias FA	132	\$ 926.00	

\*\* Standard tires.

## L4240DT-1/-2/-3

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model # V2203  
 4 Cyl., 134.1 cu. in.  
 Internal Balancers  
 + 42.0 Net Eng. HP  
 + 36.5 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 40 Amps  
 Radial Air Flow Cooling

#### HYDRAULICS

Open Center — Gear Type Dual  
 Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I 3-point Hitch —  
 At lift Point 3860 lbs.  
 24" Behind 2760 lbs.

#### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

#### DRIVE TRAIN

8 Forward / 8 Reverse  
 Manual w/Synchro Main and  
 Shuttle Transmission  
 Mech. Wet Disc Brakes  
 Clutch — Single Dry Plate  
 Differential Lock

#### FLUID CAPACITY

Fuel Tank 13.2 gal  
 Cooling System 7.9 qts  
 Crankcase 8.7 qts  
 Transmission and  
 Hydraulics 11.4 gal  
 Front Axle 9.5 qts

#### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

#### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switch  
 High back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Tilt Steering Wheel  
 Electric Key Shut-off  
 Wide Anti-Slip Step  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve

#### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

#### TIRES AND WHEELS

Front 8.3 - 16 R1 AG  
 Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4240DT-1	* 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	3214	\$ 25,284.00
L4240DT-2/-3	4WD TRACTOR	3214	\$ 25,284.00

\* \* \*

L4240DT-1
L4240DT-2
L4240DT-3

TIRES AND WHEELS (priced per piece)		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$25,284.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$25,798.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$25,808.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$25,966.00
ALR6817	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00	

\*\* Standard tires.

# KUBOTA

## L4240GST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2203  
4 Cyl., 134.1 cu. in.  
Internal Balancers  
+ 42.0 Net Eng. HP  
+ 36.5 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
Charging Output 40 Amps  
Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type Dual  
Pumps  
4.9 gpm Power Steering  
9.8 gpm Remote/3 Pt. Hitch  
14.7 gpm Total Hyd. Flow  
Cat I 3-point Hitch —  
At lift Point 3860 lbs.  
24" Behind 2760 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

### DRIVE TRAIN

12 Forward / 8 Reverse  
Glideshift w / Synchro Shuttle  
Mech. Wet Disc Brakes  
Clutch - Single Dry Plate  
Differential Lock

### FLUID CAPACITY

Fuel Tank 13.2 gal  
Cooling System 7.9 qts  
Crankcase 8.7 qts  
Transmission and  
Hydraulics 11.4 gal  
Front Axle 9.5 qts

### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
540 rpm @ 2550 Eng. rpm  
Electric over Hydraulic PTO Switch  
(-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switch  
High Back Adj. Reclining Seat  
w/Arm Rests  
Parking Brakes  
Tilt Steering Wheel  
Electric Key Shut-off  
Wide Anti-Slip Step  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Telescoping Lower Links  
Operator Presence Control System  
Halogen Headlights  
4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO  
speeds, diagnostics system  
Warning Symbols

### TIRES AND WHEELS

Front 8.3 - 16 R1 AG  
Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4240GST-1	* 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	3170	\$ 26,428.00
L4240GST-2/-3	4WD TRACTOR with 2 Post Foldable ROPS (94.5" High)	3170	\$ 26,428.00

\* \* \*

L4240GST-1		L4240GST-2		L4240GST-3	
TIRES AND WHEELS (priced per piece)				Price with Tire Option	
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST	
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$26,428.00	
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00		
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$26,942.00	
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00		
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$26,952.00	
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00		
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$27,110.00	
ALR6817	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00		

\*\* Standard tires.

# KUBOTA

## L4240HST-1/-2/-3

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model # V2203  
4 Cyl., 134.1 cu. in.  
+ 42.0 Net Eng. HP  
+ 35.0 PTO HP  
@ 2700 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
Charging Output 40 Amps  
Radial Air Flow Cooling

#### HYDRAULICS

Open Center — Gear Type Dual  
Pumps  
4.9 gpm Power Steering  
9.8 gpm Remote/3 Pt. Hitch  
14.7 gpm Total Hyd. Flow  
Cat I 3-point Hitch —  
At lift Point 3860 lbs.  
24" Behind 2760 lbs.

#### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

#### DRIVE TRAIN

HST Plus  
3 Speed Low-Medium-High  
Mech. Wet Disc Brakes  
Clutch - Single Dry Plate  
Differential Lock  
Cruise Control

#### FLUID CAPACITY

Fuel Tank 13.2 gal  
Cooling System 7.9 qts  
Crankcase 8.7 qts  
Transmission and Hydraulics 11.4 gal  
Front Axle 9.5 qts

#### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
540 rpm @ 2550 Eng. rpm  
Electric over Hydraulic PTO Switch  
(-3 only)

#### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switch  
High Back Adj. Reclining Seat  
w/Arm Rests  
Parking Brakes  
Tilt Steering Wheel  
Electric Key Shut-off  
Wide Anti-Slip Step  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Telescoping Lower Links  
Operator Presence Control System  
Halogen Headlights  
4 Position Loader Valve

#### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO  
speeds, diagnostics system  
Warning Symbols

#### TIRES AND WHEELS

Front 8.3 - 16 R1 AG  
Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4240HST-1	* 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High)	3228	\$ 26,922.00
L4240HST-2/-3	4WD TRACTOR with 2 Post Foldable ROPS (94.5" High)	3228	\$ 26,922.00

\* \* \*

L4240HST-1		L4240HST-2		L4240HST-3	
TIRES AND WHEELS (priced per piece)			Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST	
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$26,922.00	
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00		
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$27,436.00	
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00		
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$27,446.00	
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00		
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$27,604.00	
ALR6817	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00		

\*\*Standard tires.

F.O.B. KTC designated shipping point.  
Complete revision March 1, 2012.



## L4240HSTC-1/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2203  
 4 Cyl., 134.1 cu. in.  
 Internal Balancers  
 + 42.0 Net Eng. HP  
 + 35.0 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 60 Amps  
 Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type  
 Dual Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I 3-point Hitch —  
 At lift Point 3860 lbs.  
 24" Behind 2760 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 13.2 gal  
 Cooling System 7.9 qts  
 Crankcase 8.7 qts  
 Transmission and  
 Hydraulics 11.4 gal  
 Front Axle 9.5 qts

### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

### STANDARD EQUIPMENT

ROPS Certified Cab  
 w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Flat Deck w/Hanging Pedals  
 Tilt Steering Wheel  
 High Back Adj. Reclining Cloth Seat  
 w/Arm Rests  
 Safety Start Switches  
 Electric Key Shut Off  
 Turn Signals / Hazard Flashers  
 2 Frt. Work Lights  
 L/R Anti-Slip Steps  
 ISO-Mounted Platform  
 Heater and A/C  
 Frt. Wiper w/Washer (2 speed)  
 Radio-wired  
 Parking Brakes  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 12V Outlet  
 L/R Door Struts  
 Halogen Headlights  
 4 Position Loader Valve  
 Horn  
 Cloth Headliner (-3 only)

### TIRES AND WHEELS

Front 8.3 - 16 R1 AG  
 Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4240HSTC-1/-3	4WD CAB TRACTOR	3743	\$ 34,288.00

L4240HSTC-1		Price with Tire Option		
L4240HSTC-3		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
<b>TIRES AND WHEELS (priced per piece)</b>				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$34,288.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$34,802.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$34,812.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$34,970.00
ALR6817	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00	

\*\* Standard tires.

## L4740GST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2403  
 4 Cyl., 148.5 cu. in.  
 Internal Balancers  
 + 47.0 Net Eng. HP  
 + 41.5 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 40 Amps  
 Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type Dual  
 Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I 3-point Hitch —  
 At lift Point 3860 lbs.  
 24" Behind 2760 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

Glide Shift w/ Synchro Shuttle  
 12 Forward / 8 Reverse  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock (Rear)

### FLUID CAPACITY

Fuel Tank 14.3 gal  
 Cooling System 8.7 gal  
 Crankcase 8.7 gal  
 Transmission and Hydraulics 11.4 gal  
 Front Axle 9.5 qts

### POWER TAKE OFF

Rear - 1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switch  
 High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Electric Key Shut-off  
 Tilt Steering  
 Wide Anti-Slip Step  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Operator Presence Control System  
 Telescoping Lower Links  
 Halogen Head Lights  
 4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

### TIRES AND WHEELS

Front 8.3 - 16 R1 AG  
 Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4740GST-1	* 4WD TRACTOR 2 Post Foldable ROPS (100.6" High)	3258	\$ 28,694.00
L4740GST-2/-3	4WD TRACTOR 2 Post Foldable ROPS (97.6" High)	3258	\$ 28,694.00

\* \* \*

L4740GST-1		Price with Tire Option		
L4740GST-2		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
L4740GST-3				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$28,694.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$29,208.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$29,218.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$29,376.00
ALR6817	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00	

\*\* Standard tires.

## L4740HST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2403  
 4 Cyl., 148.5 cu. in.  
 Internal Balancers  
 + 47.0 Net Eng. HP  
 + 40.0 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 Charging Output 40 Amps  
 Radial Air Flow Cooling

### HYDRAULICS

Open Center — Gear Type Dual  
 Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I 3-point Hitch —  
 At lift Point 3860 lbs.  
 24" Behind 2760 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 14.3 gal  
 Cooling System 8.7 qts  
 Crankcase 8.7 qts  
 Transmission and Hydraulics 11.4 gal  
 Front Axle 9.5 qts

### POWER TAKE OFF

Rear - 1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switch  
 High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Electric Key Shut-off  
 Tilt Steering  
 Wide Anti-Slip Step  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Operator Presence Control System  
 Telescoping Lower Links  
 Halogen Head Lights  
 4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system  
 Warning Symbols

### TIRES AND WHEELS

Front 8.3 - 16 R1 AG  
 Rear 14.9 - 24 R1 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4740HST-1	* 4WD TRACTOR with 2 Post Foldable ROPS (100.6" High)	3320	\$ 29,188.00
L4740HST-2/-3	4WD TRACTOR 2 Post Foldable ROPS (97.6" High)	3320	\$ 29,188.00

\* \* \*

L4740HST-1
L4740HST-2
L4740HST-3

TIRES AND WHEELS (priced per piece)		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$29,188.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$29,702.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$29,712.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$29,870.00
ALR6817	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00	

\*\* Standard tires

## L4740HSTC-1/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2403  
 4 Cyl. 148.5 cu. In.  
 + 47.0 Net Eng. HP  
 + 40.0 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V – 582 CCA Battery  
 Charging Output 60 Amps

### HYDRAULICS

Open Center — Gear Type, Dual Pump  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I 3-point Hitch  
 At lift Point 3860 lbs.  
 24" Behind 2760 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 14.3 gal  
 Cooling System 8.7 qts  
 Crankcase 8.7 qts  
 Transmission and Hydraulics 11.4 gal  
 Front Axle 9.5 qts

### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO speeds, diagnostics system  
 Warning Symbols

### STANDARD EQUIPMENT

ROPS Certified Cab w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Flat Deck w/Hanging Pedals  
 Tilt Steering Wheel  
 High Back Adj. Reclining Cloth Seat w/Arm Rests  
 Safety Start Switches  
 Electric Key Shut Off  
 Turn Signals / Hazard Flashers  
 2 Frt. Work Lights  
 L/R Anti-Slip Steps  
 Heater and A/C  
 Frt. Wiper w/Washer (2 speed)  
 Radio-wired  
 Parking Brakes  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 12V Outlet  
 L/R Door Struts  
 ISO Mounted Platform  
 Halogen Headlights  
 4 Position Loader Valve  
 Horn  
 Cloth Headliner (-3 only)

### TIRES AND WHEELS

Front 8.3 x 16 R1  
 Rear 14.9 x 24 R1

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L4740HSTC-1/-3	4WD CAB TRACTOR	3752	\$ 36,554.00

L4740HSTC-1		Price with Tire Option		
L4740HSTC-3				
TIRES AND WHEELS (priced per piece)		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ABR8753B**	F/R-TIRE 8.3-16 R1 AG Steel Bias BA	68	\$ 246.00	\$36,554.00
ALR6809B**	R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR PNF	233	\$ 637.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$37,068.00
ALR6807	R-TIRE 17.5L-24 R4 IN Steel Bias AA	259	\$ 788.00	
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$37,078.00
ALR6803	R-TIRE 44x18-20 R3 TF Steel Bias AA	229	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$37,236.00
ALR6817	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00	

\*\*Standard tires

## L5040GST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2403  
4 Cyl. 148.5 cu. in.  
Turbocharged  
+ 50 Net Eng. HP  
+ 44.0 PTO HP  
@ 2600 Eng. rpm  
Interim Tier IV Engine  
Indirect Injection (E-TVCS)  
12V – 582 CCA Battery  
Charging Output 40 Amps

### HYDRAULICS

Open Center — Gear Type, Dual  
Pumps  
4.9 gpm Power Steering  
9.8 gpm Remote/3 Pt. Hitch  
14.7 gpm Total Hyd. Flow  
Cat I or II 3-point Hitch  
At lift Point 3860 lbs.  
24" Behind 2980 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, 4WD  
Cast Iron  
Tread Spacing, Nonadjustable

### DRIVE TRAIN

12 Forward / 8 Reverse  
Glideshift w / Synchro Shuttle  
Mech. Wet Disc Brakes  
Clutch — Single Dry Plate  
Differential Lock

### FLUID CAPACITY

Fuel Tank 14.3 gal  
Cooling System 8.7 qts  
Crankcase 9.9 qts  
Transmission and  
Hydraulics 11.9 gal  
Front Axle 9.5 qts

### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
540 rpm @ 2550 Eng. rpm  
Electric over Hydraulic PTO Switch  
(-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
Swivel Seat (-3 only)  
Safety Start Switch  
High Back Adj. Reclining Seat  
w/Arm Rests  
Parking Brakes  
Electric Key Shut-off  
Tilt Steering  
Wide Anti-Slip Step  
ISO Mounted Platform  
Turn Signals / Hazard Flashers  
SMV Sign  
Operator Presence Control System  
Telescoping Lower Links  
Halogen Head Lights  
4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
Standard Tachometer  
Digital Read for Speed, MPH, PTO  
speeds, diagnostics system  
Warning Symbols

### TIRES AND WHEELS

Front 9.5 - 16 AG  
Rear 14.9 - 26 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L5040GST-1	* 4WD TRACTOR 2 Post Foldable ROPS (101.0" High)	3369	\$ 30,357.00
L5040GST-2/-3	4WD TRACTOR 2 Post Foldable ROPS (98.0" High)	3369	\$ 30,357.00

\*\*\*

L5040GST-1		L5040GST-2		L5040GST-3	
TIRES AND WHEELS (priced per piece)				Price with Tire Option	
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST	
AMXR8860A**	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$30,357.00	
AMXR8861**	R-TIRE 14.9-26 R1 6-PLY HI PWR LUG	246	\$ 825.00		
AMXR8860A	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$30,357.00	
AMXR8813A	R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC	245	\$ 825.00		
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$30,611.00	
AMXR8862	R-TIRE 17.5L-24 R4 6-PLY BIAS IND	280	\$ 883.00		
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$30,431.00	
ALR6802	R-TIRE 44x18-20 R3 TF Steel Bias AA	221	\$ 825.00		
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$30,589.00	
ALR6819	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00		

\*\* Standard tires.

## L5240HST-3/HSTC-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2403  
 4 Cyl. 148.5 cu. in.  
 Turbocharged  
 + 52.0 Net Eng. HP  
 + 45.0 PTO HP  
 @ 2600 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V – 582 CCA Battery  
 Charging Output 40 Amps

### HYDRAULICS

Open Center — Gear Type, Dual Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I or II 3-point Hitch  
 At lift Point 3860 lbs.  
 24" Behind 2980 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 14.3 gal  
 Cooling System 8.7 qts  
 Crankcase 9.9 qts  
 Transmission and 11.9 gal  
 Hydraulics  
 Front Axle 9.5 qts

### POWER TAKE OFF

Rear - 1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switches  
 High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Electric Key Shut-off  
 Wide Anti-Slip Step  
 Tilt Steering  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO  
 speeds, diagnostics system

### TIRES AND WHEELS

Front 9.5 - 16 AG  
 Rear 14.9 - 26 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L5240HST-1	* 4WD TRACTOR, GEAR DRIVE with 2 Post Foldable ROPS (101.0" High)	3426	\$ 31,274.00
L5240HST-2/-3	4WD TRACTOR, GEAR DRIVE with 2 Post Foldable ROPS (98.0" High)	3426	\$ 31,274.00

\*\*\*

L5240HST-1		Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
AMXR8860A**	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$31,274.00
AMXR8861**	R-TIRE 14.9-26 R1 6-PLY HI PWR LUG	246	\$ 825.00	
AMXR8860A	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$31,274.00
AMXR8813A	R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC	245	\$ 825.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$31,528.00
AMXR8862	R-TIRE 17.5L-24 R4 6-PLY BIAS IND	280	\$ 883.00	
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$31,348.00
ALR6802	R-TIRE 44x18-20 R3 TF Steel Bias AA	221	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$31,506.00
ALR6819	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00	

\*\* Standard tires.

## L5240HSTC-3

### \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model # V2403  
 4 Cyl. 148.5 cu. in.  
 Turbocharged  
 Internal Balancers  
 + 52.0 Net Eng. HP  
 + 45.0 PTO HP  
 @ 2600 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V – 582 CCA Battery  
 Charging Output 60 Amps

#### HYDRAULICS

Open Center -Gear Type, Dual Pumps  
 4.9 gpm Power Steering  
 9.8gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I or II 3-point Hitch  
 At lift Point 3860 lbs.  
 24" Behind 2980 lbs.

#### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

#### DRIVE TRAIN

HST Plus  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock  
 Cruise Control

#### FLUID CAPACITY

Fuel Tank 14.3 gal  
 Cooling System 8.7 qts  
 Crankcase 9.9 qts  
 Transmission and Hydraulics 11.9 gal  
 Front Axle 9.5 qts

#### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

#### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO speeds, diagnostics system

#### STANDARD EQUIPMENT

ROPS Certified Cab  
 w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switches  
 High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Electric Key Shut-off  
 Tilt Steering  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve  
 2 Front Work Lights  
 L/R Anti-slip Steps  
 Radio-wired  
 12V Outlet  
 L/R Door Struts  
 Heater and A/C  
 Front Wipe/Wash (2 Speed)  
 Horn  
 Cloth Headliner (-3 only)

#### TIRES AND WHEELS

Front 9.5 - 16 AG  
 Rear 14.9 - 26 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L5240HSTC-1/-3	4WD CAB TRACTOR	3911	\$ 38,639.00

L5240HSTC-1		Price with Tire Option		
L5240HSTC-3				
TIRES AND WHEELS (priced per piece)		APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
ORDER CODE	DESCRIPTION			
AMXR8860A**	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$38,639.00
AMXR8861**	R-TIRE 14.9-26 R1 6-PLY HI PWR LUG	246	\$ 825.00	
AMXR8860A	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$38,639.00
AMXR8813A	R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC	245	\$ 825.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$38,893.00
AMXR8862	R-TIRE 17.5L-24 R4 6-PLY BIAS IND	280	\$ 883.00	
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$38,713.00
ALR6802	R-TIRE 44x18-20 R3 TF Steel Bias AA	221	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$38,871.00
ALR6819	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00	

\*\* Standard tires.

## L5740HST-1/-2/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2403  
 4 Cyl. 148.5 cu. in.  
 Turbocharged  
 + 57.0 Net Eng. HP  
 + 50.0 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V – 582 CCA Battery  
 Charging Output 40 Amps

### HYDRAULICS

Open Center — Gear Type, Dual Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I or II 3-point Hitch  
 At lift Point 3860 lbs.  
 24" Behind 2980 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 14.3 gal  
 Cooling System 8.7 qts  
 Crankcase 9.9 qts  
 Transmission and Hydraulics 11.9 gal  
 Front Axle 9.5 qts

### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch (-3 only)

### STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switches  
 High Back Adj. Reclining Seat w/Arm Rests  
 Parking Brakes  
 Electric Key Shut-off  
 Wide Anti-Slip Step  
 Tilt Steering  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO speeds, diagnostics system

### TIRES AND WHEELS

Front 9.5 - 16 AG  
 Rear 14.9 - 26 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L5740HST-1	* 4WD TRACTOR with 2 Post High Profile Foldable ROPS (101.0" High)	3417	\$ 32,520.00
L5740HST-2/-3	4WD TRACTOR with 2 Post High Profile Foldable ROPS (98.0" High)	3417	\$ 32,520.00

\* \* \*

L5740HST-1		L5740HST-2		L5740HST-3	
TIRES AND WHEELS (priced per piece)			Price with Tire Option		
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST	
AMXR8860A**	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$32,520.00	
AMXR8861**	R-TIRE 14.9-26 R1 6-PLY HI PWR LUG	246	\$ 825.00		
AMXR8860A	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$32,520.00	
AMXR8813A	R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC	245	\$ 825.00		
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$32,774.00	
AMXR8862	R-TIRE 17.5L-24 R4 6-PLY BIAS IND	280	\$ 883.00		
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$32,594.00	
ALR6802	R-TIRE 44x18-20 R3 TF Steel Bias AA	221	\$ 825.00		
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$32,752.00	
ALR6819	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00		

\*\* Standard tires.



## L5740HSTC-1/-3

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

### DIESEL ENGINE

Model # V2403  
 4 Cyl. 148.5 cu. in.  
 Turbocharged  
 Internal Balancers  
 + 57.00 Net Eng. HP  
 + 50.0 PTO HP  
 @ 2700 Eng. rpm  
 Interim Tier IV Engine  
 Indirect Injection (E-TVCS)  
 12V – 582 CCA Battery  
 Charging Output 60 Amps

### HYDRAULICS

Open Center -Gear Type, Dual Pumps  
 4.9 gpm Power Steering  
 9.8 gpm Remote/3 Pt. Hitch  
 14.7 gpm Total Hyd. Flow  
 Cat I or II 3-point Hitch  
 At lift Point 3860 lbs.  
 24" Behind 2980 lbs.

### FRONT AXLE

Hydrostatic Power Steering  
 Bevel Gear, 4WD  
 Cast Iron  
 Tread Spacing, Nonadjustable

### DRIVE TRAIN

HST Plus  
 3 Speed Low-Medium-High  
 Mech. Wet Disc Brakes  
 Clutch - Single Dry Plate  
 Differential Lock  
 Cruise Control

### FLUID CAPACITY

Fuel Tank 14.3 gal  
 Cooling System 8.7 qts  
 Crankcase 9.9 qts  
 Transmission and Hydraulics 11.9 gal  
 Front Axle 9.5 qts

### POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent  
 540 rpm @ 2550 Eng. rpm  
 Electric over Hydraulic PTO Switch  
 (-3 only)

### IntelliPanel™

Lighted Communications Symbols  
 Standard Tachometer  
 Digital Read for Speed, MPH, PTO speeds, diagnostics system

### STANDARD EQUIPMENT

ROPS Certified Cab  
 w/Retractable Seat Belt  
 Swivel Seat (-3 only)  
 Safety Start Switches  
 High Back Adj. Reclining Seat  
 w/Arm Rests  
 Parking Brakes  
 Electric Key Shut-off  
 Tilt Steering  
 ISO Mounted Platform  
 Turn Signals / Hazard Flashers  
 SMV Sign  
 Telescoping Lower Links  
 Operator Presence Control System  
 Halogen Headlights  
 4 Position Loader Valve  
 2 Front Work Lights  
 L/R Anti-slip Steps  
 Radio-wired  
 12V Outlet  
 L/R Door Struts  
 Heater and A/C  
 Front Wipe/Wash (2 Speed)  
 Horn  
 Cloth Headliner (-3 only)

### TIRES AND WHEELS

Front 9.5 - 16 AG  
 Rear 14.9 - 26 AG

+ Manufacturer Estimate

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L5740HSTC-1/-3	4WD CAB TRACTOR	3911	\$ 39,886.00

L5740HSTC-1		Price with Tire Option		
L5740HSTC-3				
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	APPROX SHIP WT.	SUGG. LIST PRICE	SUGG. LIST
AMXR8860A**	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$39,886.00
AMXR8861**	R-TIRE 14.9-26 R1 6-PLY HI PWR LUG	246	\$ 825.00	
AMXR8860A	F-TIRE 9.5-16 R1 AG Steel Bias CA	76	\$ 283.00	\$39,886.00
AMXR8813A	R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC	245	\$ 825.00	
ALR8869A	F-TIRE 10-16.5 R4 IN Steel Bias AA	83	\$ 352.00	\$40,140.00
AMXR8862	R-TIRE 17.5L-24 R4 6-PLY BIAS IND	280	\$ 883.00	
ALR8895A	F-TIRE 29x12.5-15 R3 TF Steel Bias AA	73	\$ 320.00	\$39,960.00
ALR6802	R-TIRE 44x18-20 R3 TF Steel Bias AA	221	\$ 825.00	
ALR6818A	F-TIRE LSW305R343 R3 TF STL RADAL AA PNF	116	\$ 352.00	\$40,118.00
ALR6819	R-TIRE LSW610R470 R3 TF Steel Radial AA	227	\$ 872.00	

\*\* Standard tires

## Grand L - 40 Series Attachment Chart

	L3240 (-1) (-2)	L3540 (-1) (-2)	L3940 (-1) (-2)	L4240 (-1) (-2)	L4740 (-1) (-2)	L5040 (-1) (-2)	L5240 (-1) (-2)	L5740 (-1) (-2)
Foldable ROPS & Seat Belt <sup>Ⓞ</sup>	SFL-F354(A)	SFL-F354(A)	SFL-F424(A)	SFL-F424(A)	SFL-F474(A)	SFL-F574(A)	SFL-F574(A)	SFL-F574(A)
Sunshade for ROPS	E1133 Std. E1134 Deluxe	E1133 Std. E1134 Deluxe	E1133 Std. E1134 Deluxe	E1133 Std. E1134 Deluxe	E1133 Std. E1134 Deluxe	E1133 Std. E1134 Deluxe	E1133 Std. E1134 Deluxe	E1133 Std. E1134 Deluxe
Seat Belt - Extra Length	70002-06605	70002-06605	70002-06605	70002-06605	70002-06605	70002-06605	70002-06605	70002-06605
Rear Wheel Weight <sup>①</sup> (Max. 3/Wheel)	L8066A	L8066A	L8066A	L8066A	L8066A	LM8124	LM8124	LM8124
Front Weight Bracket <sup>⑤</sup>	MX8068	MX8068	MX8068	MX8068	MX8068	MX8068	MX8068	MX8068
Rear Work Light (ROPS)	L8329	L8329	L8329	L8329	L8329	L8329	L8329	L8329
Front Bumper Weight(s) Max. 7 <sup>Ⓣ</sup>	BL8060-1	BL8060-1	BL8060-1	BL8060-1	BL8060-1	BL8060-1	BL8060-1	BL8060-1
Rear Remote Hydraulics Sectional stackable valves Select double acting or Float Detent	See "Rear Remote Hydraulics" Section in corresponding Dealer Installed Options price pages.							
Draft Control (ROPS)	L8317	L8317	L8317	L8317	L8318	L8318	L8318	L8318
(Cab)	L8319	L8319	L8319	L8319	L8319	L8319	L8319	L8319
Swinging Drawbar	L8325	L8325	L8325	L8325	L8325	L8325	L8325	L8325
Drawbar Clevis	L9496G	L9496G	L9496G	L9496G	L9496G	L9496G	L9496G	L9496G
Front Grille Guard <sup>②</sup>	L2224	L2224	L2224	L2224	L2224	L2224	L2224	L2224
Creep Speed Kit <sup>③</sup>	L8324	L8324	L8324	L8324	L8324	L8324	N/A	N/A
3-pt Top-N-Tilt Kit <sup>④</sup>	L8326	L8326	L8326	L8326	L8326	L8326	L8326	L8326
Mid-PTO Kit <sup>⑥</sup>	L8338	L8338	L8338	L8338	L8338	L8338	L8338	L8338
Loader Valve Diverter Kit	L8349	L8349	L8349	L8349	L8349	L8349	L8349	L8349
Spark Arrester	77700-00280	77700-00280	77700-00280	77700-00280 <sup>⑦</sup>	77700-00280 <sup>⑦</sup>	L8366	L8366	L8366
Ballast Box	L8170	L8170	L8170	L8170	L8170	L8170	L8170	L8170
Block Heater	70000-00297	70000-00297	70000-00297	70000-00297	70000-00297	70000-00297	70000-00297	70000-00297

### CAB MODELS

L8333 Rear Work Light Kit (2 Lights)  
 L8334 Rear Wiper Kit, Washer connects to Front -Wiper's Washer.  
 L8330 Defogger Kit (Rear Window)  
 L8331 Defogger Kit (Corner Windows)

### RADIOS

E9259A AM / FM / Weather Band / Cassette <sup>Ⓢ</sup>  
 E9276A AM / FM / Weather Band / CD <sup>Ⓢ</sup>

- ① Not compatible with Turf Tires.
- ② Front Grille Guard for non-loader applications. If using BL8060-1 Front Bumper Weights in combination with L2224 Grille Guard and an L2180-1 Front Quick Hitch, then 70060-02225 Front Weight Bracket must be used. Order from Parts Department. Note: L2224 Loader Grille Guard is compatible with up to (4) BL8060-1 Front Suitcase Weights.
- ③ Not applicable to HST models.
- ④ Requires 2 or 3 Rear Hydraulic Remote depending on implement application. Please review Rear Remote Hydraulic section to select the correct remote configuration. Top-N-Tilt not compatible with BH75/BH90 sub-frames.
- ⑤ MX8068 Front Weight Bracket is not compatible with L2224 Grille Guard.
- ⑥ Requires Mid-PTO Gear installation on L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST.
- ⑦ Requires L8368 Low Back Pressure Muffler.
- ⑧ Grand L-30 Series requires L8332 Mounting Kit.
- ⑨ SFL-F354 ROPS will apply to Grand L40 and Grand L40-1 tractors.  
SFL-F354A ROPS will apply to Grand L40-2 tractors only.
- ⑩ Weights must be removed from bracket when Loader is installed.

## Grand L - 40 Series Dealer Installed Options

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>MID-PTO Kits</b>			
L8338	Mid-PTO Kit All Grand L-40 Series (ROPS Models L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, L5740HST require Internal Gear Kit L8316)	22	\$377.00
L8316	② Mid-PTO Internal Gear Kit For installation of L8338 Mid-PTO Kit L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, L5740HST models only (Standard on Cab tractors.)	25	\$248.00

### REAR REMOTE HYDRAULICS

#### ROPS MODELS:

<b>Must order Base Kit and one Valve Section to complete installation.</b>			
L8335	① Base Kit and 1st Lever Requires L8308 or L8309 Valve to complete Assembly	21	\$500.00
L8308	Double Acting Valve Section Requires: Base Kit and First Lever	4	\$240.00
L8309	FD Float Detent Valve Section Requires: Base Kit and First Lever	6	\$302.00
L8336	① Second Position Stacking Kit Includes Hardware and 2nd Lever Requires: Additional L8308 or L8309 Valve Section	7	\$248.00
L8337	① Third Position Stacking Kit Includes Hardware and 3rd Lever Requires: Additional L8308 or L8309 Valve Section (For Triple Remotes, Second Position Stacking Kit also required)	8	\$248.00

#### CAB MODELS:

<b>Must order Base Kit and one Valve Section to complete installation.</b>			
L8346A	Base Kit and 1st Lever Requires L8308 or L8309 Valve to complete Assembly	16	\$535.00
L8308	Double Acting Valve Section Requires: Base Kit and First Lever	4	\$240.00
L8309	FD Float Detent Valve Section Requires: Base Kit and First Lever	6	\$302.00
L8347	Second Position Stacking Kit Includes Hardware and 2nd Lever Requires: Additional L8308 or L8309 Valve Section	7	\$293.00
L8348	Third Position Stacking Kit Includes Hardware and 3rd Lever Requires: Additional L8308 or L8309 Valve Section (For Triple Remotes, Second Position Stacking Kit also required)	35	\$293.00

- ① When installing rear remote hydraulic valves in conjunction with BH76 Backhoes, additional kits are required. Please order additional kits through Parts Department. For L8335, order kit TD120-96750. For L8336, order kit TD120-96760. For
- ② Allow approximately 10 hours for installation time.

## Grand L - 40 Series Dealer Installed Options

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>HYDRAULIC DIVERTER KIT</b>			
L8349	② Hydraulic Diverter Kit enables standard Loader Valve to be used as (2) rear hydraulic remotes, one remote will be float detent and one will be standard double-acting GL40-1/-2 only.	20	\$562.00
L8369	② Hydraulic Diverter Kit enables standard Loader Valve to be used as (2) rear hydraulic remotes, one remote will be float detent and one will be standard double-acting, GL40-3 only.	20	\$562.00
<b>DRAFT CONTROL</b>			
L8317	Draft Control L3240, L3540, L3940, L4240 ROPS Model Tractors, GL40-1/-2 only	25	\$482.00
L8374	Draft Control L3240, L3540, L3940, L4240 ROPS Model Tractors, GL40-3 only)	25	\$482.00
L8318	Draft Control: L4740, L5040, L5240, L5740 ROPS Model Tractors, GL40-1/-2 only	25	\$482.00
L8375	Draft Control: L4740, L5040, L5240, L5740 ROPS Model Tractors, GL40-3 only	25	\$482.00
L8319	Draft Control: Cab Model Tractors, GL40-1/-2 only	25	\$524.00
L8376	Draft Control: Cab Model Tractors, GL40-3 only	25	\$524.00
<b>TNT (Top-N-Tilt Kit)</b>			
L8326	① Top (Cylinder) & Tilt (Cylinder) Kit	44	\$843.00
<b>DRAWBAR OPTIONS</b>			
L9496G	Drawbar Clevis	8	\$67.00
L8325	Swinging Drawbar	20	\$145.00
<b>CREEP SPEED KIT</b>			
L8324	Creep Speed Kit (All Grand L40 Series Models except HST)	24	\$602.00
<b>SUNSHADE FOR ROPS</b>			
E1133	Standard Sunshade	63	\$437.00
E1134	Deluxe Sunshade Requires E1136 Mounting Bracket Kit	63	\$387.00
E1136	Mounting Bracket Kit for E1134	30	\$191.00
E1138	Front Work Light Kit for E1134 (includes 2 lights)	10	\$125.00

① Requires 2 or 3 Rear Hydraulic Remote depending on implement application. Please review Rear Remote Hydraulic section to select the correct remote configuration.

② Not compatible with Front Loader or L8308/L8309 Hydraulic Valves.

## Grand L - 40 Series Dealer Installed Options

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT GRILLE GUARD</b>			
L2224	① Front Grille Guard (Non-Loader Applications)	45	\$269.00
70060-02225	Front Weight Bra (Order from the Parts Department) For use with L2224 Grille Guard, 1-4 Weights, Includes mounting hardware.		
<b>SEAT BELT KIT</b>			
70002-06605	Extra Length Seat Belt Kit		(Order from the Parts Department)
<b>BLOCK HEATER</b>			
70000-00297	Block Heater		(Order from the Parts Department)
<b>SPARK ARRESTER</b>			
L8366	Spark Arresting Muffler: L5040, L5240, L5740	10	\$462.00
77700-00280	Spark Arrester Kit, L3240, L3540, L3940, L4240, L4740		(Order from the Parts Department)
L8368	Low Back Pressure Muffler (L4240, L4740)	25	\$228.00
<b>WEIGHT KITS</b>			
<b>REAR WHEEL WEIGHTS</b>			
<b>L3240, L3540, L3940, L4240, L4740</b>			
L8066A	③ Rear Wheel Weights (64 lbs. each) One, two, or three weights per wheel. Mount to 24" wheels with 10.24" wheel weight bolt hole centers. Set of 2 weights, Requires L8067A Bolt Kit, max. 3 Sets	128	\$124.00
L8067A	Bolt Kit for L8066A (Max. 3 sets)	5	\$33.00
<b>L5040, L5240, L5740</b>			
LM8124	③ Rear Wheel Weights (103 lbs. each) Mount to 24" or 26" wheels with steel discs. Set of 2 weights, requires LM8125 Bolt Kit, max. 3 sets (not turf tire compatible)	105	\$279.00
LM8125	Bolt Kit for 1st set of LM8124 (one kit will accept one set of weights)	6	\$67.00
M8121	Bolt Kit for 2nd and 3rd set of LM8124 Weights	6	\$18.00

① Front Grille Guard for non-loader applications. If using BL8060-1 Front Bumper Weights in combination with L2224 Grille Guard and an L2180-1 Front Quick Hitch, then 70060-02225 Front Weight Bracket must be used. Order from Parts Department.

② For L4240 and L4740 tractors, L8368 Low Back Pressure Muffler must be ordered.

③ Not compatible with Turf Tires.

## Grand L - 40 Series Dealer Installed Options

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>WEIGHT KITS (Continued)</b>			
<b>FRONT WEIGHTS</b>			
MX8068	② Front Weight Bracket Kit (1-7 Weights) 4WD Models (Standard on 2WD models)	25	\$96.00
BL8060-1	Front Suitcase Weight (55 lbs. each) Requires 1 BL8060B Bolt Kit Per weight, Max. 7 weights	55	\$71.00
BL8060B	Bolt Kit (1 per weight required) Use with MX8068 Weight Bracket Use with L2224 Grille Guard	1	\$2.00

### REAR WORK LIGHT KIT (ROPS)

L8329	Rear Work Light Kit	5	\$89.00
-------	---------------------	---	---------

### BALLAST BOX

L8170	Ballast Box (1000 lb cap. with dry sand) (All Grand L-40 Series)	168	\$449.00
-------	---	-----	----------

### CAB MODEL OPTIONS

L8333	Rear Work light Kit (2 lights, Cab)	3	\$131.00
L8334	Rear Wiper Kit	4	\$143.00
L8330	Defogger Kit (Rear Window)	18	\$281.00
L8331	Defogger Kit (Corner Windows) (Requires: L8330)	18	\$307.00
E9299	A AM/FM Radio with MP3 Port and 7-Channel Weather Band.	4	\$310.00
E9276B	A AM/FM Radio CD/MP3 Player with 7-Channel Weather Band.	4	\$440.00

### REPLACEMENT CABS

L7042	① Replacement Cab for L3240HSTC, L3540HSTC		\$7,308.00
L7062	① Replacement Cab for L3240HSTC-3, L3540HSTC-3		\$7,308.00
L7043	① Replacement Cab for L3940HSTC, L4240HSTC		\$7,308.00
L7063	① Replacement Cab for L3940HSTC-3, L4240HSTC-3		\$7,308.00
L7044	① Replacement Cab for L4740HSTC		\$7,308.00
L7064	① Replacement Cab for L4740HSTC-3		\$7,308.00
L7045	① Replacement Cab for L5240HSTC, L5740HSTC		\$7,308.00
L7065	① Replacement Cab for L5240HSTC-3, L5740HSTC-3		\$7,308.00

A Radios have a 2-year warranty.

① Replacement Cab packages include Cab assembly, mounting hardware, installation manual, left and right hand external rear view mirrors, all standard exterior lights, air-conditioning controls and hoses. Cab packages DO NOT include steering wheel.

② MX8068 Front Weight Bracket is not compatible with L2234 Grille Guard.

## L Series Implement Charts

### STANDARD L IMPLEMENT CHART

TRACTOR	L3200F L2800F(-1)*	L3200DT L2800DT(-1)*	L3200HST L2800HST(-1)*	L3800F L3400F(-1)*	L3800DT L3400DT(-1)*	L3800HST L3400HST(-1)*	L3700SU	L4400F-1/ DT-1/HST/1	L4600F/DT /HST
Front Loader	LA463FL* LA463-1* LA524 LA524FL	LA463FL* LA463-1* LA524 LA524FL	LA463FL* LA463-1* LA524 LA524FL	LA463FL* LA463-1* LA524 LA524FL	LA463FL* LA463-1* LA524 LA524FL	LA463FL* LA463-1* LA524 LA524FL	LA463FL* LA463-1* LA524 LA524FL	LA703A LA764	L764
Backhoe	BH75(A)* BH76* BH77	BH75(A)* BH76* BH77	BH75(A)* BH76* BH77	BH75(A)* BH76* BH77	BH75(A)* BH76* BH77	BH75(A)* BH76* BH77	BH76* BH77	BH90A BH92	BH92
Rotary Tiller	FL1021C/RD	FL1021C/RD	FL1021C/RD	FL1021C/RD	FL1021C/RD	FL1021C/RD	FL1021C/RD	FL1021C/RD	FL1021C/RD
	FL1271C/RC	FL1271C/RC	FL1271C/RC	FL1271C/RC	FL1271C/RC	FL1271C/RC	FL1271C/RC	FL1271C/RC	FL1271C/RC
	FL1521C	FL1521C	FL1521C	FL1521C	FL1521C	FL1521C	FL1521C	FL1521C	FL1521C
Snowblower (Rear)	BL2664	BL2664	BL2664	BL2664	BL2664	BL2664	BL2664	BL2664	BL2664
	L2674	L2674	L2674	L2674	L2674	L2674	L2674	L2674	L2674

### GRAND L-40 IMPLEMENT CHART

MODEL	L3240 (-1/-2/-3)		L3540(-1/-2/-3)		L3940(-1/-2/-3)	L4240 (-1/-2/-3)	L4740 (-1/-2/-3)	L5040 (-1/-2/-3)	L5240 (-1/-2/-3)	L5740 (-1/-2/-3)
Front Loader	LA514	LA724	LA514	LA724	LA724	LA854	LA854	LA854	LA854	LA854
Sq. Back Bucket ①	L2246(66")	L2276(72")	L2246(66")	L2276(72")	L2276(72")	L2276(72")	L2276(72")	L2276(72")	L2276(72")	L2276(72")
	L2256(66")	L2235(72")	L2256(66")	L2235(72")	L2235(72")	L2235(72")	L2235(72")	L2235(72")	L2235(72")	L2235(72")
Heavy Duty Rnd Back Bucket①	L2266(66")	L2286(72")	L2266(66")	L2286(72")	L2286(72")	L2286(72")	L2286(72")	L2286(72")	L2286(72")	L2286(72")
	---	L2296(72")	---	L2296(72")	L2296(72")	L2296(72")	L2296(72")	L2296(72")	L2296(72")	L2296(72")
4 in 1 Bucket	N/A	L2244	N/A	L2244	L2244 / L2245	L2245	L2245	L2245	L2245	L2245
Lt Material Bucket①	L2236(72")	L2236(72")	L2236(72")	L2236(72")	L2236(72")	L2236(72")	L2236(72")	L2236(72")	L2236(72")	L2236(72")
Pallet Fork Frame Pallet Fork①	L2238/ K9048(36")	L2238/ K9048(36")	L2238/ K9048(36")	L2238/ K9048(36")	L2238/ K9048(36")	L2238/ K9058(42") K9048(36")	L2238/ K9058(42") K9048(36")	L2238/ K9058(42") K9048(36")	L2238/ K9058(42") K9048(36")	L2238/ K9058(42") K9048(36")
	L2237	L2237	L2237	L2237	L2237	L2237	L2237	L2237	L2237	L2237
3 <sup>rd</sup> Function Valve	L2221 (non-1/-1/-2 ROPS)	L2221 (non-1/-1/-2 ROPS)	L2221 (non-1/-1/-2 ROPS)	L2221 (non-1/-1/-2 ROPS)	L2225 (non-1/-1/-2 ROPS)	L2225 (non-1/-1/-2 ROPS)	L2225 (non-1/-1/-2 ROPS)	L2225 (non-1/-1/-2 ROPS) L2227 (non-1/-1 Cab) L2298 (-3 ROPS)	L2225 (non-1/-1/-2 ROPS)	L2225 (non-1/-1/-2 ROPS)
	L2222 (non-1/-1 Cab)	L2222 (non-1/-1 Cab)	L2222 (non-1/-1 Cab)	L2222 (non-1/-1 Cab)	L2227 (non-1/-1 Cab)	L2227 (non-1/-1 Cab)	L2227 (non-1/-1 Cab)		L2227 (non-1/-1 Cab)	L2227 (non-1/-1 Cab)
	L2288 (-3 ROPS)	L2288 (-3 ROPS)	L2288 (-3 ROPS)	L2288 (-3 ROPS)	L2298 (-3 ROPS)	L2298 (-3 ROPS)	L2298 (-3 ROPS)		L2298 (-3 ROPS)	L2298 (-3 ROPS)
	L2289 (-3 Cab)	L2289 (-3 Cab)	L2289 (-3 Cab)	L2289 (-3 Cab)	L2299 (-3 Cab)	L2299 (-3 Cab)	L2299 (-3 Cab)		L2299 (-3 Cab)	L2299 (-3 Cab)
Mid Mount Mower	RC72-38		RC72-38		RC72-38	---	---	---	---	---
Backhoe②③	BH75A*/BH77/BH90(A)*/BH76*/BH92		BH75A*/BH77/BH90(A)*/BH76*/BH92		BH90(A)* BH92	BH90(A)* BH92	BH90(A)* BH92	BH90(A)* BH92	BH90(A)* BH92	BH90(A)* BH92
Rotary Tiller	FL1521C		FL1521C		---	---	---	---	---	---
Snowblower (Front)③	L2194A (62")		L2194A (62")		L2194A (62")	L2195A (72")	L2195A (72")	L2195A (72")	L2195A (72")	L2195A (72")
Snowblower (Rear)	BL2664(64")		BL2664(64")		L2674(74")	L2674(74")	L2674(74")	L2674(74")	L2674(74")	L2674(74")
Front Blade ③	L2172A (72")		L2172A (72")		L2184 (84")	L2184 (84")	L2184 (84")	L2184 (84")	L2184 (84")	L2184 (84")
Front Rotary Sweeper ③	L2162(60") L2164(72")		L2162(60") L2164(72")		L2164(72")	L2164(72")	L2164(72")	L2164(72")	L2164(72")	L2164(72")

① Requires two lever style Quick Coupler L2216 (LA514) or L2226 (LA724/LA854).

② Backhoes are not compatible with Cab model tractors.

③ Requires L2180-1 Front Quick Hitch.

④ BH92 Compatible with all GL-40 ROPS Tractors and GL40-3 Cab.

■ 2-Lever Quick Attach

\* Subject to availability.

## L Series Loader Matching Charts

### STANDARD L SERIES

STANDARD L SERIES TRACTORS	LOADER and VALVE	BUCKET STRUCK / HEAPED CAPACITY		OPTIONAL ATTACHMENTS
L3200 L3800 L2800 (-1)* L3400 (-1)* L3700SU	<b>LA463FL*<sup>②</sup>③/LA524FL</b> Complete, includes Loader valve, bucket, mounting kit, grille guard, bucket, and hydraulic block	<b>LA463FL*</b> 60" width L1701 (Std) 8.1 cu. ft. / 9.9 cu. ft.	<b>LA524FL</b> 60" width L2242 (Std)	L2130 Bucket Rod Indicator Kit
	<b>LA463-1*<sup>②</sup>③/LA524</b> Includes loader valve, mounting kit, grille guard, hydraulic block, and 2 lever coupler	66" width L2256 8.1 cu. ft. / 9.9 cu. ft.		L2130 Bucket Rod Indicator Kit
L4400 (-1)	<b>LA703A</b> Can be used with optional L2228 skid steer style Quick Coupler, includes 4-Position Valve and Grille Guard	L2264 – 72" Sq Back Pin-on <sup>⑤</sup> 8.8 cu. ft. / 10.9 cu. ft. L2235A – 72" Sq Back Quick Attach 10.9 cu. ft. / 13.1 cu. ft. L2296 – 72" Round Back Quick Attach 10.9 cu. ft. / 13.1 cu. ft.		L2228 Quick Coupler <sup>④</sup> L2237 Bale Spear L2130 Bucket Rod Indicator Kit TL1748 Cutting Edge <sup>①</sup>
L4600	<b>LA764</b> Includes Loader Valve, Grille Guard, and Quick Coupler	L2236 – 72" Light Material 12.7 cu. ft. / 16.0 cu. ft.		

① TL1748 for L2296 Bucket only.

② To install the LA463-1 or LA463FL Loader on an L3200 or L3800, the old Grille Guard from the LA463 Loader has to be removed, and install the Grille Guard MX8190.

③ To install the LA524 and LA524FL Loader on an L2800 or L3800, install the Grille Guard MX8190

④ L2228 Quick Coupler standard on L4600.

⑤ L2264 Square Back Bucket not compatible with LA764 Loader.

\* Subject to availability.

### All Grand L-40 Series Loaders include Mounting Kit, Grille Guard, and Bucket Level Indicator

Tractor Models	Loader Model	Bucket Types (widths)	Optional attachments Skid-steer style	Compatible Mid-Mount Mower	3 <sup>RD</sup> FUNCTION VALVE
L3240 (-1/-2/-3) L3540 (-1/-2/-3)	LA514	<b>Direct Pin</b> 66" Square Back 66" Heavy Duty <sup>①</sup> <b>Quick-Attach</b> 66" Square Back 72" Light Material	L2216 Skid-steer style Quick-coupler Pallet Forks & Frame L2238 & K9048 (36") Bale Spear L2237	RC72-38 (72" Mid-Mount Mower) Requires: Mid-PTO Kit	Non-1 / -1 / -2 Models L2221 – ROPS L2222 – Cab -3 Models L2288 – ROPS L2289 -- Cab
L3240 (-1/-2/-3) L3540 (-1/-2/-3) L3940 (-1/-2/-3)	LA724	<b>Direct Pin</b> 72" Square Back 72" Heavy Duty <sup>①</sup> <b>Quick-Attach</b> 72" Square Back 72" Heavy Duty <sup>①</sup> 72" Light Material 72" 4-in-1 Bucket	L2226 Skid-steer style Quick-coupler Pallet Forks & Frame L2238 & K9048 (36") Bale Spear L2237	RC72-38 (72" Mid-Mount Mower) Requires: Mid-PTO Kit	For L3240(-1/-2) / L3540(-1/-2) L2221 – ROPS L2222 – Cab For L3240-3 / L3540-3 L2288 – ROPS L2289 -- Cab For L3940 (-1/-2) L2225 – ROPS L2227 – Cab For L3940-3 L2298 – ROPS L2299 -- Cab
L4240 (-1/-2/-3) L4740 (-1/-2/-3) L5040 (-1/-2/-3) L5240 (-1/-2/-3) L5740 (-1/-2/-3)	LA854	<b>Direct Pin</b> 72" Square Back 72" Heavy Duty <sup>①</sup> <b>Quick-Attach</b> 72" Square Back 72" Heavy Duty <sup>①</sup> 72" Light Material 72" 4-in-1 Bucket	L2226Skid-steer style Quick-coupler Pallet Forks & Frame L2238 & K9048 (36") or K9058 (42") Bale Spear L2237	N/A	Non-1 / -1 / -2 Models L2225 – ROPS L2227 – Cab -3 Models L2298 – ROPS L2299 -- Cab

① Heavy Duty Buckets are pre-drilled to accept optional bolt-on reversible cutting edges.



## Standard L-Series Front Loaders

ORDER CODE		DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>CURRENT L-SERIES FRONT LOADERS</b>				
LA524FL	12	HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve, Grille Guard and 60" Bucket.	710	\$4,142.00
LA524	2	HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve, Grille Guard Hydraulic Block and 2-Lever style coupler plate. Does not include bucket.	845	\$4,100.00
LA463FL	12*	HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve, Grille Guard and 60" Bucket.	710	\$4,142.00
LA463-1	2*	HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve, Grille Guard Hydraulic Block and 2-Lever style coupler plate. Does not include bucket.	845	\$4,100.00
LA703A		HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve and Grille Guard. Bucket must be ordered separately.	1000	\$4,271.00
LA764		HEAVY DUTY FRONT LOADER Includes Mounting Kit, 2-Lever type Quick Coupler, Valve and Grille Guard. Bucket must be ordered separately	970	\$4,845.00

**STANDARD L SERIES FRONT LOADER BUCKETS AND PALLET FORKS**  
QA = Quick Attach, PO = Pin On Type

L2256		66" Square Back QA LA463-1 / LA524	212	\$610.00
L2264		72" Square Back PO LA703 / LA703A	247	\$667.00
L2235A		72" Square Back QA LA703A / LA764	247	\$677.00
L2296		72" Round Back QA LA703A / LA764	400	\$1,050.00
L2236		72" Light Material QA LA703A / LA764	323	\$649.00
L2238		Pallet Fork Frame QA	165	\$677.00
K9048		36" Pallet Tines	176	\$407.00
K9058		42" Pallet Tines (Not compatible with LA764)	196	\$476.00
L2237		Bale Spear	165	\$642.00
TL1748		Bottom Cutting Edge for L2240/L2245/L2273/ L2296 72" Buckets	65	\$227.00
TL1756		Bolt on Cutting Edge for L2239/L2253/L2266 66" Buckets	65	\$210.00
L1701		60" Pin-on Bucket (Replacement for LA463)	212	\$474.00
L2242		60" Pin-on Bucket (Replacement for LA524)	200	\$500.00

L2228	3	2-Lever Quick Attach Coupler for LA703A Loader	116	\$443.00
L2216		2-Lever Quick Coupler (Replacement for LA524)	76	\$432.00
L2130		Bucket Rod Lever Indicator Kit for LA703(A), LA463FL, LA463-1, LA524FL, LA524, LA764	2	\$63.00

\* \*\*

- 1 FL = Full Loader, Cylinders and Hoses are pre-installed. FL packaged buckets are NOT returnable.
- 2 Requires subframe kit L4691 to be used with BL4690B Backhoe.
- 3 Cannot be used on LA703 Loader.

## L-Series Front Loaders

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>L SERIES GRILLE GUARD</b>			
L2251	Grille Guard (L2800/L3400/L3700SU/ L4400/L4400-1)	48	\$269.00
L2267	Foldable Grille Guard for L4600 (non-loader application)	61	\$319.00
MX8190	Grille Guard (L3200, L3800) for all loader and non-loader applications	50	\$269.00

### REPLACEMENT STANDARD L-SERIES LOADERS

LB552-1	LIGHT DUTY FRONT LOADER Includes Mounting Kit, Hydraulic Block, Valve and 60" Bucket (L4300F/DT)	835	\$3,601.00
LA682-1	FRONT LOADER Includes Mounting Kit and Grille Guard (L1766). Does not include Bucket or Joystick Control.	1000	\$3,491.00
LA852-2	FRONT LOADER Includes Mounting Kit and Grille Guard Does not include Bucket or Joystick Control	1275	\$3,353.00
LA450A*	FRONT LOADER Includes Mounting Kit. Does not include Bucket, Joystick Control Valve or Grille Guard.	870	\$2,796.00
LA650A*	FRONT LOADER Includes Mounting Kit. Does not include Bucket, Joystick Control Valve or Grille Guard.	1070	\$3,308.00
LA1150A*	FRONT LOADER Includes Mounting Kit and Hydraulic Valve. Bucket not included with Loader.	1500	\$4,877.00

### OPTIONAL WIDE LOADER PARKING STANDS

75548-475511 (2 Required per Loader) (Order from the Parts Department)

1 75548-47551 Wider Parking Stands are used for Loader applications in combination with the RC72-29 and RC72-36 Mid Mount Mower, or other applications where additional clearance is desired. Two Stands are required for proper application.

\* \* \*

# KUBOTA

## Standard L-Series Replacement Loader Attachments

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>MUST ORDER ONE (1) WITH LA450A AND LA650A LOADERS</b>			
L2074	* Standard Joystick Control Valve Valve exactly same as previous loader models. Attaches to and dismounts with the loader.	40	\$663.00
L2073	* Remote Hydraulic Kit replaces L2053 and L2043	40	\$1,041.00
L1738	ATTACHMENT LEVEL INDICATOR for LA852 only.	15	\$62.00

### CONTROL VALVES

#### MUST ORDER ONE (1) WITH LA682 LOADERS

L2205	* STANDARD JOYSTICK CONTROL VALVE with three (3) position bucket spool, incorporates automatic regenerative dump feature. Valve remains with the tractor. Standard in "FL" Package.	38	\$680.00
L2206	REMOTE JOYSTICK CONTROL VALVE (Cab Model) with four (4) position bucket spool. Valve is mounted to mainframe of loader and can be used for other than loader work. The single lever control mounts to right-hand fender and operates valve via push-pull cables. Four (4) position bucket spool, regenerative feature is detented so that third position is standard mode, necessary for front mount attachments. Valve remains with tractor. L2206 or L2207 required for L2054B Quick Hitch.	42	\$1,022.00
L2207-1	OPTIONAL JOYSTICK CONTROL VALVE with four (4) position bucket spool, regenerative feature is detented so that third position is standard mode, necessary for front mount attachments. Valve remains with the tractor. L2206 or L2207 required for L2054B Quick Hitch.	25	\$705.00

\*\*\*.

# KUBOTA

## Standard L-Series Replacement Loader Attachments

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>MUST ORDER ONE (1) WITH LA852-2 LOADERS</b>				
L2095-1	STANDARD JOYSTICK CONTROL VALVE Attaches to and dismounts with Loader, std. in "FL" Pkg. (3 Position Valve)		25	\$657.00
L2096-1	REMOTE JOYSTICK CONTROL VALVE (3) Position valve is mounted to main frame of loader. The single lever control mounts to right-hand fender and operates valve via push-pull cables. (Use for L4610HSTC Cab Model.)		25	\$952.00
<b>QUICK COUPLERS</b>				
BL1767	QUICK COUPLER for LA450S-1/-2, LA452S, LB400(A), LB402, LA480, LA481, LA482, LA680, LA681, LA682 and LB552 Loaders		65	\$279.00
L1716	QUICK COUPLER for LA852-1 Loader		42	\$352.00
<b>PALLET FORKS &amp; FRAMES FOR LB552, LA682, LA852, and LA1150(A) LOADERS</b>				
K9048	36" PALLET FORKS For LB400(A), LB402, LA450S-1/-2, LA452S, LA480, LA680, LA481, LA482, LA681, LA682, LA852, LB552 Two (2) pieces, One (1) set. Requires L2077A Frame, or LA852 Front Loader requires L2097 Frame.		176	\$407.00
K9058	42" PALLET FORKS For LA852 Front Loader. Two (2) pieces, One (1) set. Requires L2097 Frame.		196	\$476.00
L2077A	1 2 PALLET FORK FRAME For LB400(A), LB402, LA450S-1/-2, LA452S, LA480, LB552, LA680, LA481, LA482, LA681, and LA682 Front Loaders.		165	\$613.00
L2097	PALLET FORK FRAME (For LA852-1 Loader) Required for K9048 or K9058 Pallet Forks		165	\$687.00
M1048A	QUICK ATTACH PALLET FORK FRAME For LA950(A) and LA1150(A) Loaders Requires M1066 Quick-Coupler and K9058 Pallet Forks (42").		202	\$1,263.00

1 If used on any of the following Loaders; LB400, LA400, LA400S, LA450A, LA500, LA650 or LA650A; the loader will not be able to be removed because the removal arms have no place to mount to. The bucket will have to be installed in order to remove the loader.

2 L2077A is compatible with BL1767 Quick Coupler. The previous L2077 is not compatible with BL1767 Quick Coupler.

# KUBOTA

## Standard L-Series Replacement Loader Attachments

ORDER CODE		DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>QUICK-ATTACH COUPLER for LA950(A), LA1150(A), and LA703A Loaders</b>					
M1066		QUICK ATTACH COUPLER Required on LA950(A) and LA1150(A) Loaders to accept Quick-Coupler Implements.		46	\$197.00
M1067	1	QUICK ATTACH BRACKET KIT FOR BUCKETS Required on all approved Loader Buckets that are used with M1066 Quick-Coupler on LA950(A) and LA1150(A) Loaders. M1067 kit is not compatible with L1770(A) H.D. Bucket.		37	\$164.00

### BALE SPEAR

#### LA950(A), LA1150(A) Loaders with Quick Coupler

M1058A		BALE SPEAR For LA950(A) and LA1150(A) Includes Quick Coupler Bracket		195	\$647.00
L2237		BALE SPEAR For LA703A		165	\$642.00

### BUCKET TINE KITS

#### LA950(A), LA1150(A) Loader Buckets only

M1057		TINE KIT For LA950(A) and LA1150(A)		90	\$272.00
-------	--	--	--	----	----------

### BOLT-ON CUTTING EDGE

L1773		Bolt-On Cutting Edge OPTIONAL Edge for L1770 (A) Bucket (Applicable for BF1100 Ser. #10167 and up)		70	\$205.00
-------	--	--	--	----	----------

### L SERIES GRILLE GUARDS

(Recommended with Front Loaders and for use in non-loader applications.)

L1764	2	Grille Guard (GL's, L2900 - L4200)		51	\$258.00
L1766	345	Grille Guard (GL10's, L3010 - L4610)		51	\$264.00
L1794		Grille Guard (LA650A) (L4300, L2600, L3000)		48	\$278.00
L1704		Grille Guard (L4300 compatible with LB552)		48	\$269.00

1 Not compatible with L1770(A) heavy duty round back buckets.

2 Standard with "FL" Package.

3 Standard with LA481(FL), LA482(FL), LA681(FL), and LA682(FL) Loaders. Use for non-loader applications — requires Stay-Kit — L1765.

4 L1766 is different than the Grille Guard that is standard with LA852(FL) Loaders.

5 Requires Front Weight Bracket if tractor is not equipped with one. Order from Parts (1) 32420-44880 Bumper, (4) 01173-51435 Bolts, and (4) 04512-60140 Washers. See PIB-99-38.

## L-Series Loader Attachments

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>REPLACEMENT L SERIES GRILLE GUARD MOUNTING KIT/ NOT EQUIPPED WITH LOADERS</b>			
L1785	Grille Guard Mounting Kit For L2050 - L3250 and L2350 - L3650 Tractors	15	\$102.00
L1765	Grille Guard Stay Kit for L1766 Grille Guard For Grand L-Series Tractors (except L4610)	25	\$88.00

### REPLACEMENT L SERIES FRONT LOADER BUCKETS AND PALLET FORKS

L1746	60" Square Back Replacement	LB400A, LB402	212	\$417.00
L1740A	60" Square Back	LA450S, LA452S, LA480, LA481, LA482	212	\$474.00
L1780	66" Square Back	LA481, LA482	308	\$594.00
L1741A	60" H.D. Round Back	LA450A, LA452S, LA480, LA481, LA482	308	\$780.00
L1703	60" Square Back	LB552	212	\$474.00
L1742A	60" Square Back	LA650A, LA680, LA681, LA682, LB552	247	\$576.00
L1743A	60" H.D. Round Back	LA650A, LA680, LA681, LA682, LB552	308	\$951.00
L1790	66" Square Back	LA681, LA682	308	\$660.00
L1750	70" Light Material	LB400, LB402, LA450S, LA452S, LA480, LA481, LA482, LA680, LA681, LA682, LB552	212	\$646.00
L1769	72" Square Back	LA852 -- LA852-1	400	\$677.00
L1779	72" H.D. Round Back	LA852 -- LA852-1	400	\$1,106.00
L1774A	70" Square Back	LA950A	404	\$627.00
L1770A	70" H.D. Round Back	LA950A, LA1150A	583	\$1,122.00

## Grand L-40 Series Loaders

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	---------------------	-------------------------

### GRAND L-40 SERIES FRONT LOADERS

LA514	Loader for L3240 & L3540 Includes Grille Guard, Mounting Kit, and Bucket Level Indicator. Does not include Bucket.Loader valve is standard equipment on all Grand L40 Tractors.	970	\$3,261.00
-------	---	-----	------------

### Bucket and Attachment Options for LA514 Loader (Must order to one to complete.)

#### Direct Pin-on Buckets for LA514

L2246	66" Square Back Bucket 8.1 cu. ft. Struck, 9.9 cu. ft. Heaped	212	\$610.00
L2266	66" Heavy Duty Round Back 8.1 cu. ft. Struck, 9.9 cu. ft. Heaped (Pre-Drilled for Opt. TL1756 Edge)	308	\$903.00
TL1756	Bolt-on Reversible Cutting Edge (66") for L2266	65	\$210.00

## Grand L-40 Series Loaders

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>2-Lever Quick-Attach Options for LA514</b>			
L2216	Quick-coupler for LA514	79	\$432.00
L2256	66" Square Back Bucket 8.1 cu. ft. Struck, 9.9 cu. ft. Heaped	212	\$610.00
L2236	72" Light Material Bucket 12.7 cu. ft. Struck, 16.0 cu. ft. Heaped	323	\$649.00
L2238	Pallet Fork Frame	165	\$677.00
K9048	36" Pallet Forks for LA514	176	\$407.00
L2237	Bale Spear	165	\$642.00
<b>Third Function Valve for LA514</b>			
L2221	Third Function Valve (for L3240/-1/-2 and L3540/-1/-2 ROPS Models) for Hydraulic Loader Implements	25	\$779.00
L2222	Third Function Valve (for L3240/-1 and L3540/-1 Cab Models) for Hydraulic Loader Implements	25	\$779.00
L2288	Third Function Valve (for L3240-3 and L3540-3 ROPS models) for Hydraulic Loader Implements	25	\$899.00
L2289	Third Function Valve (for L3240-3 and L3540-3 Cab models) for Hydraulic Loader Implements	25	\$899.00
<b>LA724</b>	Loader for L3240, L3540, & L3940 Includes Mounting Kit, Grille Guard and Bucket Level Indicator. Does NOT include Bucket. Loader valve is standard equipment on all Grand L40 tractors.	970	\$3,913.00
<b>LA854</b>	Loader for L4240, L4740, L5040, L5240, L5740 Includes Mounting Kit, Grille Guard and Bucket Level Indicator. Does NOT include Bucket. Loader valve is standard equipment on all Grand L40 tractors.	970	\$4,125.00



## Grand L-40 Series Loaders

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>Bucket and Attachment Options for LA724 &amp; LA854 Loaders (Must order one to complete.)</b>			
<b>Direct Pin-on Buckets for LA724 and LA854</b>			
L2276	72" Square Back Bucket 10.9 cu. ft. Struck, 13.1 cu. ft. Heaped	325	\$667.00
L2286	72" Heavy Duty Round Back 10.9 cu. ft. Struck, 13.1 cu. ft. Heaped (Pre-Drilled for Opt. TL1748 Edge)	308	\$1,037.00
TL1748	Bolt-on Reversible Cutting Edge (72") for L2286	65	\$227.00
<b>2-Lever Style Quick-Attach Options for LA724 &amp; LA854 Loaders</b>			
L2226	Quick-coupler for LA724 & LA854	116	\$443.00
L2235	72" Square Back Bucket 10.9 cu. ft. Struck, 13.1 cu. ft. Heaped	247	\$677.00
L2296	72" Heavy Duty Round Back 10.9 cu. ft. Struck, 13.1 cu. ft. Heaped (Pre-Drilled for Opt. TL1748 Edge)	400	\$1,050.00
TL1748	Bolt-on Reversible Cutting Edge (72") for L2296 and L2245	65	\$227.00
TL2143	Bolt-on Reversible Cutting Edge (60") for L2244	45	\$211.00
L2236	72" Light Material Bucket 12.7 cu. ft. Struck, 16.0 cu. ft. Heaped	323	\$649.00
L2244	60" 4-in-1 Bucket (LA724 only) Requires Third Function Valve	450	\$1,985.00
L2245	① 72" 4-in-1 Bucket (LA724 and LA854) Requires Third Function Valve	640	\$2,098.00
L2238	Pallet Fork Frame	165	\$677.00
K9048	36" Pallet Forks for LA514, LA724 & L854	176	\$407.00
K9058	42" Pallet Forks for LA854	196	\$476.00
L2237	Bale Spear	165	\$642.00

① L2245 Bucket compatible on L3940 with LA724 loader and on all LA854 Loaders.

## Grand L-40 Series Loaders

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>Third Function Valve for LA724 &amp; LA854 Loaders</b>			
L2221	Third Function Valve (for L3240/-1/-2 and L3540/-1/-2 ROPS Models) for Hydraulic Loader Implements	25	\$779.00
L2222	Third Function Valve (for L3240/-1/-2 and L3540/-1/-2 Cab Models) for Hydraulic Loader Implements	25	\$779.00
L2225	Third Function Valve (for L3940/4240/4740/5040/5240/5740 -1/-2ROPS models) for Hydraulic Loader Implements	25	\$818.00
L2227	Third Function Valve (for L3940/4240/4740/5040/5240/5740 -1/-2 Cab models) for Hydraulic Loader Implements	25	\$818.00
L2288	Third Function Valve (for L3240-3 and L3540-3 ROPS Models) for Hydraulic Loader Implements	25	\$899.00
L2289	Third Function Valve (for L3240-3 and L3540-3 Cab Models) for Hydraulic Loader Implements	25	\$899.00
L2298	Third Function Valve (for L3940/4240/4740/5040/5240/5740 -3 ROPS models) for Hydraulic Loader Implements	25	\$899.00
L2299	Third Function Valve (for L3940/4240/4740/5040/5240/5740 -3 Cab models) for Hydraulic Loader Implements	25	\$899.00

**This page intentionally left blank.**

## L Series Backhoe Matching Chart

### BACKHOE APPLICATION CHART

BH76	TRACTOR MODELS	MOUNT KIT	SUB-FRAME KIT	BUCKETS	ROPS
STANDARD L	L2800, L3400, L3700SU	Included in Subframe	BH4976A	10" - BT1950A 12" - BT1951A 16" - BT1952A 24" - BT1953A	All ROPS are Acceptable
	L3200, L3800		BH4988		
GL40 ROPS (NON-1, -1, -2)	L3240, L3540 (Non-1, -1, -2)	Included in Subframe	BH4996A		
	L3240, L3540 (-3)	Included in Subframe	BH4986		

  

BH77	TRACTOR MODELS	MOUNT KIT	SUB-FRAME KIT	BUCKETS	ROPS
STANDARD L	L2800, L3400, L3700SU	N/A	BH4976A	10" - BT1950A 12" - BT1951A 16" - BT1952A 24" - BT1953A	All ROPS are Acceptable
STANDARD L	L3200, L3800	N/A	BH4988		
GL40 (Non-1, -1) (ROPS)	L3240, L3540	N/A	BH4996A		
GL40-3 (ROPS)	L3240, L3540	N/A	BH4986		

  

BH90	TRACTOR MODELS	MOUNT KIT	SUB-FRAME KIT	BUCKETS	ROPS
STANDARD L	L4400DT-1, L4400 HST-1	N/A	N/A	N/A	SFL-F440A
GL30 ROPS	L3130, L3430	BH4990	Included in BH90	12" - BT2901	SFL-F343
	L3830, L4330, L4630	BH4991		16" - BT2902	SFL-F463
	L5030	BH4991		18" - BT2903	SFL-F503
GL40 ROPS (NON-1, -1, -2, -3)	L3240, L3540	BH4997(A)	Included in BH90	24" - BT2904	SFL-F354(A)
	L3940, L4240	BH4998(A)	Included in BH90	30" - BT2905	SFL-F424(A)
	L4740	BH4998(A)	Included in BH90	36" - BT2906	SFL-F474(A)
	L5040, L5240, L5740	BH4998(A)	Included in BH90		SFL-F574(A)

  

BH90A	TRACTOR MODELS	MOUNT KIT	SUB-FRAME KIT	BUCKETS	ROPS
STANDARD L	L4400DT-1, L4400 HST-1	BH4979	Included in BH4979	12" - BT2901 16" - BT2902 18" - BT2903 24" - BT2904 30" - BT2905 36" - BT2906	SFL-F440A
GL30 ROPS	L3130, L3430	BH4990	BH4977		SFL-F343
	L3830, L4330, L4630	BH4991			SFL-F463
	L5030	BH4991			SFL-F503
GL40 ROPS (NON-1, -1, -2, -3)	L3240, L3540	BH4997(A)Ⓞ	BH4977	SFL-F354(A)	
	L3940, L4240	BH4998(A)Ⓞ		SFL-F424(A)	
	L4740	BH4998(A)Ⓞ		SFL-F474(A)	
	L5040, L5240, L5740	BH4998(A)Ⓞ		SFL-F574(A)	

  

BH92	TRACTOR MODELS	MOUNT KIT	SUB-FRAME KIT	BUCKETS	ROPS
STANDARD L	L4600	BH4946	N/A	PIN ON BUCKETS 12" - BT3001 16" - BT3002A 18" - BT3003A 24" - BT3004 30" - BT3005A 36" - BT3006	SFL-F460
	L4400F-1, L4400DT-1, L4400 HST-1	BH4979	Included		SFL-F440A
GL30 ROPS	L3130, L3430	BH4990	BH4977		SFL-F343
	L3830, L4330, L4630	BH4991			SFL-F463
	L5030	BH4991		SFL-F503	
GL30 CAB	L3130, L3430, L3830, L4330, L4630, L5030	N/A	N/A	N/A	
GL40 ROPS (NON-1, -1, -2)	L3240, L3540	BH4997(A)	BH4977	SFL-F354(A)	
	L3940, L4240	BH4998(A)		SFL-F424(A)	
	L4740			SFL-F474(A)	
	L5040, L5240, L5740			SFL-F574(A)	
GL40 ROPS (-3)	L3240, L3540	BH4941	BH4945	SFL-F354(A)	
	L3940, L4240	BH4943	BH4945	SFL-F424(A)	
	L4740	BH4943	BH4945	SFL-F474(A)	
	L5040, L5240, L5740	BH4943	BH4945	SFL-F574(A)	
GL40 CAB (NON-1, -1)	L3240, L3540, L3940, L4240, L4740, L5240, L5740	N/A	N/A	QUICK COUPLER BUCKETS 12" - BT4552 16" - BT4553 18" - BT4554 24" - BT4555 36" - BT4557	N/A
GL40-3 Cab	L3240, L3540, L3940, L4240, L4740, L5240, L5740	BH4942	BH4945		N/A
		BH4944			N/A

Ⓞ Kubota has developed hardware kit 7K505-95300 to make the BH4997/4998 Mounting Kits compatible with the BH90A/92 on GL40-3 tractors.

## L Series Backhoes

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
BH76* 12456	4-Pt. mounted quick-attach, easy-on easy-off, no tools design. Requires integral subframe kit/mounting kit. Backhoe seat is part of subframe for L2800/DT/HST(-1), L3400/DT/HST(1), L3700SU, L3200, L3800, L3240(-1/-2/-3), and L3540(-1/-2/-3) model tractors.	1400	\$6,709.00
BH77	7 4-Pt. mounted quick-attach, easy-on easy-off, no tools design. Requires integral subframe kit/mounting kit. Backhoe seat is part of subframe for L2800/DT/HST(-1), L3400/DT/HST(1), L3700SU, L3200F/DT/HST, L3800F/DT/HST, L3240(-1/-2/-3), and L3540(-1/-2/-3) model tractors.	1085	\$6,709.00
<b>BH75A/BH76/BH77 MOUNTING KITS</b>			
BH4976	Subframe required for BH75(A) with LA463.	200	\$485.00
BH4996	Subframe required for BH75A with LA514/LA724	292	\$796.00
BH4976A	Subframe required for BH76 / BH77 to mount on L2800/DT/HST(-1), L3400/DT/HST(-1) and L3700SU. Includes regular fixed seat.	200	\$739.00
BH4996A	Subframe required for BH76 / BH77 to mount on L3240(-1)(-2) and L3540(-1)(-2). Includes regular fixed seat.	292	\$1,050.00
BH4986	Subframe required for BH76 / BH77 to mount on L3240-3, L3540-3. Includes seat.	292	\$1,050.00
BH4988	Subframe required for BH76 / BH77 to mount on L3200, L3800. Includes seat.	200	\$739.00
<b>BH76/BH77 SEATS</b>			
BH7681	Seat kit for BH76 Backhoe when mounted with the following BH75A Subframes: BH4974, BH4975A, BH4976, and BH4996	50	\$254.00
<b>BH75A/BH76/BH77 BACKHOE BUCKETS &amp; THUMBS</b>			
BT1950A	10" Bucket — 3 Teeth	69	\$415.00
BT1951A	12" Bucket — 3 Teeth	69	\$491.00
BT1952A	16" Bucket — 4 Teeth	84	\$648.00
BT1953A	24" Bucket — 5 Teeth	118	\$847.00
BH1976	6 Position Mechanical Thumb for BH76/77	56	\$465.00
L9467	Rubber stabilizer flip pads (Set) for BH75(A), BH76, BH77 Two required per owner's manual	16	\$79.00

- 1 These Backhoes are not compatible with Top-N-Tilt Kits.
- 2 Not compatible with Grand L Cab Models.
- 3 Requires BH4996(A) Subframe for LA514 and LA724 Loaders (L3240, L3540).
- 4 Not compatible with Mid-mount Mower RC72-38.
- 5 Requires LA514 or LA724 Loaders on L3240 / L3540.
- 6 Requires BH4996A Subframe for LA514/724 Loader (L3240/-1/-2 and L3540/-1/-2).
- 7 Requires Loader.

\* \*\*

## L Series Backhoes

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
BH92 ②③⑤⑥⑦⑧	Easy-on, Easy-off, No Tools Design Performance matched, requires Mounting Kit and subframe kit, works with the tractor supplied hydraulics. (L4400-1, L4600, GL40 ROPS, GL40-3 Cab)	1800	\$7,508.00
BH90 ①②③④⑤⑥	* Easy-on, Easy-off, No Tools Design Performance matched, requires Mounting Kit and subframe kit, works with the tractor supplied hydraulics. (Grand L30/40 Series)	1800	\$7,679.00
BH90A ①②⑦	* Easy-on, Easy-off, No Tools Design Performance matched, requires Sub-frame/Mounting Kit, works with the tractor supplied hydraulics. (L4400DT-1/HST-1, GL30/40 Tractors)	1800	\$7,458.00
<b>Mounting and Subframe Kits BH90(A)</b>			
BH4990	⑤ Mounting Kit for 3130 and L3430 Tractors with BH90(A) Backhoe. Requires LA723 Loader.	50	\$293.00
BH4991	⑤ Mounting Kit for L3830, L4330, L4630, and L5030 Tractors with BH90(A) Backhoe. Requires LA723 or LA853 Loader.	67	\$293.00
BH4997A	⑤ Mounting Kit required for BH90(A) with LA514 / LA724 (L3240/L3540)	50	\$331.00
BH4998A	⑤ Mounting Kit required for BH90(A) with LA724 / LA854 (L3940/4240/4740/5040/5240/5740)	88	\$364.00
BH4977	⑤ Subframe required for BH90A only to mount on GL30 and GL40 ROPS tractors.	354	\$752.00
BH4979	Subframe and Mounting Kit required for BH90A to mount on L4400-1.	383	\$1,116.00
BH4946	Subframe and Mounting Kit required for BH92 to mount on L4600	383	\$1,116.00

\* Subject to availability.

① Not compatible with Grand L-30/40 Series Cab tractors.

② Not compatible with Top-N-Tilt Link Kits.

③ L3130 & L3430 require LA723 Loader. LA513 Loader is not compatible with BH90 Backhoe.

④ **Tractor Requirements:** Tractors with the Serial Numbers below (Serial Number list provided by model of tractor) will require a ROPS Frame Kit to update the tractor to be able to accept the backhoe subframe kit. The ROPS frame kit will be provided at **No Charge**. Please order the correct ROPS frame kit for the tractors specified.

**BH4992** -- L3130F (Serial #10005 and below)

L3130DT/GST/HST (Serial #30115 and below)

L3430DT/GST/HST (Serial #30017 and below)

**BH4993** -- L3830F (Serial #10002 and below)

L3830DT/GST/HST (Serial #30016 and below)

L4330DT/GST/HST (Serial #30035 and below)

L4630DT/GST/HST (Serial #30028 and below)

**BH4994** -- L5030GST/HST (Serial #30020 and below)

⑤ BH90 Mounting Kits do not interfere with 3 point hitch operation. 3-Point linkage must be removed for Backhoe operation. Not compatible with mid-mount mower RC72-38.

⑥ L3240/L3540 Requires LA514/LA724 Loader and BH4997A Mounting Kit and Subframe Kit.

L3940/L4240/L4740/L5040/L5240/L5740 Require LA724/LA854 Loader and BH4998A Mounting Kit and Subframe Kit.

⑦ Not compatible with L4400, must have L4400-1 with LA703(A) Loader.

⑧ Not compatible with GL30 Cab models, GL40, GL40-1 Cab tractors

## L Series Backhoes

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>BH92 Backhoe "PIN ON" Buckets</b>			
BT3001	12" Bucket	117	\$656.00
BT3002A	16" Bucket	140	\$729.00
BT3003A	18" Bucket	151	\$778.00
BT3004	24" Bucket	172	\$923.00
BT3005A	30" Bucket	205	\$1,044.00
BT3006	36" Bucket	226	\$1,191.00
<b>BH92 Backhoe "Quick Coupler &amp; Quick Coupler" Buckets</b>			
BT4550	BH92 Quick Coupler	19	\$647.00
BT4552	12" Bucket	69	\$781.00
BT4553	16" Bucket	69	\$824.00
BT4554	18" Bucket	151	\$867.00
BT4555	24" Bucket	140	\$1,024.00
BT4557	36" Bucket	140	\$1,304.00
<b>BH92 Thumb Options &amp; Flip Pads</b>			
BH4948	Hydraulic Valve Kit	55	\$862.00
BT4598	Hydraulic Thumb, requires BH4948 Valve kit	56	\$1,993.00
BH4949	6 Position Mechanical Thumb	56	\$875.00
L9467	Flip Pads, Street Shoes. Two Required per order.	16	\$79.00
<b>BH90A Backhoe Buckets</b>			
BT2901	12" Bucket	117	\$655.00
BT2902	16" Bucket	140	\$729.00
BT2903	18" Bucket	151	\$777.00
BT2904	24" Bucket	172	\$923.00
BT2905	30" Bucket	205	\$1,044.00
BT2906	36" Bucket	226	\$1,191.00
<b>Flip Pads</b>			
L9467	Rubber Flip Pad BH90(A)/BH92 (Two required per order.)	16	\$79.00

## L Series Backhoes

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>Mounting and Subframe Kits BH92</b>			
BH4990	Mounting kit for L3130/L3430 ROPS Models with BH92 backhoe. Requires LA723 loader.	50	\$293.00
BH4991	Mounting kit for L3830/L4330/L4630/L5030 ROPS Models with BH92 backhoe. Requires LA723/853 loader.	67	\$293.00
BH4941	Mounting kit for L3240/L3540 (-1/-2/-3) ROPS Models with BH92 backhoe. Requires LA724/LA514 loader.	50	\$331.00
BH4942	Mounting kit for L3240-3/L3540-3 Cab Models with BH92 backhoe. Requires LA724/LA514 loader.	50	\$531.00
BH4943	Mounting kit for L3940/L4240/L4740/L5040/L5240/L5740 (-1/-2/-3) ROPS Models with BH92 backhoe. Requires LA724/LA854 loader.	95	\$364.00
BH4944	Mounting kit for L3940/L4240/L4740/L5040/L5240/L5740 (-3) CAB Models with BH92 backhoe. Requires LA724/LA854 loader.	225	\$564.00
BH4945	Sub frame Kit for L3240/3540/L3940/L4240/ L4740/ L5040/L5240/L5740	383	\$752.00
BH4946	Subframe and Mounting Kit for L4600	383	\$1,116.00
BH4979	Sub frame Kit for L4400DT-1, L4400-1HST-1	383	\$1,116.00
<b>BH92 Backhoe "PIN ON" Buckets</b>			
BT3001	12" Bucket	117	\$656.00
BT3002A	16" Bucket	140	\$729.00
BT3003A	18" Bucket	151	\$778.00
BT3004	24" Bucket	172	\$923.00
BT3005A	30" Bucket	205	\$1,044.00
BT3006	36" Bucket	226	\$1,191.00
<b>BH92 Backhoe "Quick Coupler &amp; Quick Coupler" Buckets</b>			
BT4550	BH92 Quick Coupler	19	\$647.00
BT4552	12" Bucket	69	\$781.00
BT4553	16" Bucket	69	\$824.00
BT4554	18" Bucket	151	\$867.00
BT4555	24" Bucket	140	\$1,024.00
BT4557	36" Bucket	140	\$1,304.00
<b>BH92 Thumb Options &amp; Flip Pads</b>			
BH4948	Hydraulic Valve Kit	55	\$862.00
BT4598	Hydraulic Thumb Requires BH4948 Valve kit	56	\$1,993.00
BH4949	6 Position Mechanical Thumb	56	\$875.00
L9467	Flip Pads, Street Shoes. 2 Required per order.	16	\$79.00



## L Series Mowers

Tractor Models	Mower
<b>Current Models</b>	
L3240 L3540 L3940	<b>RC72-38</b> ® Requires Mid-PTO. Not compatible with ALR8869A Tires (Compatible with ALR8869A Tires on L3940)

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>MID-MOUNT MOWERS</b>			
Current Models			
RC72-38 ②③④⑤	72" CUTTING WIDTH Uses tractor mid-PTO, (mid-PTO required) RH discharge / 3-Blade Finishing Mower / 1.5" to 4.5" cutting height / 3 Anti-Scalp Rollers. Parallel linkage design for easy mounting.	476	\$3,592.00
Non-current Models			
RC72-29A	*①② 72" CUTTING WIDTH Uses tractor mid-PTO, RH discharge / 3-Blade Finishing Mower / 1.5" to 4.5" cutting height / 3 Anti-Scalp Rollers.	563	\$3,174.00
RC72-36A	*① 72" CUTTING WIDTH Uses tractor mid-PTO, RH discharge / 3-Blade Finishing Mower / 1.5" to 4.5" cutting height / 3 Anti-Scalp Rollers.	476	\$3,067.00
RC60-25	* 60" CUTTING WIDTH Requires L8384 or L8385 Mid PTO Kit. 60" cutting width / RH discharge / 3-Blade Finishing Mower / 1.5" to 4.0" cutting height range / 3 Anti-Scalp Rollers.	416	\$2,134.00
RC72-25	* 72" CUTTING WIDTH Requires L8384 or L8385 Mid PTO Kit. RH discharge / 3-Blade Finishing Mower / 1.5" to 4.5" cutting height / 3 Anti-Scalp Rollers.	603	\$3,164.00
Mounting Kit for L3940 Models			
L8367	RC72-38 Mid Mount Mower Mounting Kit	20	\$175.00

\* \*\*

① Installing this mower requires you to replace the return pipe on specific model tractors:

L3010HST: 70001-73332

L3410HST: 70002-70652

L3710HST: 70002-71468

L3710HSTC: 70002-71468

Please order part number TA250-56462. Please refer to SB00-10.

② Not compatible with R4 industrial tires. (Exception: Compatible with R4 tires only on L3940.)

③ Not compatible with Backhoes.

④ Requires L8367 Mounting Kit for L3940 Models.

⑤ Not compatible with L2180-1 Front Hitch Sub Frame.

## L Series Rotary Tiller Matching Chart

<b><i>CURRENT</i></b> <b>Model Tractors</b>	<b>Rotary Tiller Models</b>
L2800 L3400 L3700SU L3200 L3800	FL1021C or FL1021RC (40") FL1271C or FL1271RC (50") FL1521C (60")
L4400 L4600	FL1521C (60")
L3240 L3540 L3940 L4240 L4740 L6040 L5240 L5740	FL1521C (60")

## L Series Rotary Tillers

### L SERIES

NOTE: 3 POINT HITCH MOUNTED IMPLEMENTS REQUIRE FRONT COUNTER WEIGHT  
IN THE FORM OF FRONT MOUNTED IMPLEMENTS OR FRONT BUMPER WEIGHTS.

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** L SERIES ROTARY TILLERS ***			
FL1021C	40" CUTTING WIDTH Offset or Center Mounted/Skid Shoe Depth Control/ 17.3" dia. Rotor.	466	\$2,719.00
FL1021RC	40" CUTTING WIDTH Reverse Cutting Rotation/Offset or Center Mounting/ Skid Shoe Depth Control/17.3" diameter Rotor.	500	\$2,861.00
FL1271C	50" CUTTING WIDTH Offset or Center Mounted/Skid Shoe Depth Control/ 17.3" diameter Rotor.	493	\$3,005.00
FL1271RC	50" CUTTING WIDTH Reverse Cutting Rotation/Offset or Center Mounting/ Skid Shoe Depth Control/17.3" diameter Rotor.	493	\$3,025.00
FL1521C	60" CUTTING WIDTH Offset or Center Mounted/Friction Slip Clutch Skid Shoe Depth Control.	625	\$3,727.00

## L Series Front Blades

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT BLADES (GRAND L-10, L-30 AND L-40 SERIES)</b>			
L2172A	72" Front Blade Hydraulic Lift & Angle. Includes Skid Shoes and single Piece moldboard design. NOTE: Grand L-30 Series requires Quick-Hitch and Control Valve. Grand L-40 Series requires Quick-Hitch only.	485	\$2,186.00
L2184	84" Front Blade Hydraulic Lift & Angle. Includes Skid Shoes and single Piece moldboard design. NOTE: Grand L-30 Series requires Quick-Hitch and Control Valve. Grand L-40 Series requires Quick-Hitch only.	570	\$2,620.00

### Required for Grand L Series Front Blades

L2180-1	④⑤⑥ Quick-hitch for Grand L30 and L40 Series	535	\$1,682.00
L2213A	Joystick Control Valve - Grand L30 Series (4-position ROPS) With Loader installed	38	\$705.00
L2223A	Joystick Control Valve - Grand L30 Series (4-position CAB) without Loader Requires: L2187 Valve Mounting Kit	42	\$1,022.00
L2187	Valve Mounting Kit (without Loader) Grand L30 Series for L2223A Valve	17	\$80.00

### Requires Both Subframe and Joystick For L2172A

L2054B	①② Quick Hitch	335	\$1,257.00
L2206	Joystick/Hyd. Valve Kit (All Grand L (Ten) Series). Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab)	42	\$1,022.00
L2207-1	③ Joystick/Hyd. Valve Kit (All Grand L (Ten) Series). Two Spool Valve with Float. Compatible with Loader ((4) Position)	25	\$705.00
L2071	② BRACKET/BRACE SUPPORT KIT for Loader compatibility.	25	\$109.00
B2776	72" Rubber Cutting Edge for L2172A Blade	60	\$243.00

- ① The L2054B Quick Hitch is compatible with the LA482(FL) or LA682(FL) Loaders.
- ② L2071 Bracket/Brace Kit replaces single piece Front Loader bracket on LA481/LA681 to provide Loader compatibility.
- ③ Loader must also be installed.
- ④ Prior model, L2180, requires L2188 Upgrade Support Frame Kit.
- ⑤ L2180-1 Quick Hitch not compatible with RC72-38 Mid-mount Mower.
- ⑥ L2180-1 Quick Hitch not compatible with L2224 and L2233A Grille Guard unless lower cross member is removed.

**This page intentionally left blank.**

## L Series Snowblower Matching Chart

	Current Tractor Model	Order Code - Description	Mounting Kit Requirements	Chute Rotator	<u>OPTIONAL</u>
<b>FRONT SNOWBLOWERS</b>	L3240, L3540, L3940  L3130, L3430, L3830  Requires: Tractor Mid-PTO Installation	<b>L2194A</b> Ⓛ 62" Front Snowblower (Includes Blower and Chute Rotator)  Ⓛ Requires L8338 for Mid PTO installation in L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST	<b>L2180-1</b> Quick Hitch <b>L2182</b> Driveline Kit (L3240, L3540, L3130, L3430, L3830)  <b>L2186</b> Driveline Kit (L3940)  <b>Grand L30 Series Choice of One</b> <b>L2213(A)</b> Joystick Control Valve (4-Position ROPS) with Loader installed <b>L2223(A)</b> Joystick Control Valve (4-Position Fender Mounted/Cab)* *without Loader, Requires: L2187 Valve mounting Kit	Hydraulic Chute Rotator	<b>L2179</b> Electric Chute Deflector  <b>L2177</b> Side Extension Kit (adds 5" overall cut)  <b>BL2666</b> Hydraulic Chute Deflector Kit
	L4240 L4740 L5040 L5240 L5740  L4330 L4630 L5030  Requires: Tractor Mid-PTO Installation	<b>L2195A</b> Ⓛ 72" Front Snowblower (Includes Blower and Chute Rotator)  Ⓛ Requires L8338 for Mid PTO installation in L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST	<b>L2180-1</b> Quick Hitch <b>L2186</b> Driveline Kit (L4240, L4740, L5040, L5240, L5740, L4330, L4630, L5030)  <b>Grand L30 Series Choice of One</b> <b>L2213(A)</b> Joystick Control Valve (4-Position ROPS) with Loader installed <b>L2223(A)</b> Joystick Control Valve (4-Position Fender Mounted/Cab)* *without Loader, Requires: L2187 Valve mounting Kit	Hydraulic Chute Rotator	<b>L2179</b> Electric Chute Deflector  <b>L2177</b> Side Extension Kit (adds 5" overall cut)  <b>BL2666</b> Hydraulic Chute Deflector Kit
	L3130 L4330 L3430 L4630 L3830 L5030  Requires: Tractor Mid-PTO Installation	<b>Must order both</b> <b>L2174A</b> 62" <b>FRONT</b> Blower <b>L2175B</b> Front Mount Chute Kit  Or <b>Must order both</b> <b>L2185</b> 72" <b>FRONT</b> Blower <b>L2175B</b> Front Mount Chute Kit	<b>L2180-1</b> Quick-Hitch <b>L2182</b> Drive Line Kit (L3130, L3430, L3830) <b>L2183</b> Drive Line Kit (L4330, L4630, L5030)  <b>Choice of One</b> <b>L2213(A)</b> Joystick Control Valve (4-Position ROPS) with Loader installed <b>L2223(A)</b> Joystick Control Valve (4-Position Fender Mounted/Cab)* *without Loader, Requires: L2187 Valve mounting Kit	Hydraulic Chute Rotator	<b>L2179</b> Electric Chute Deflector  <b>L2177</b> Side Extension Kit (adds 5" overall cut)
<b>REAR SNOWBLOWERS</b>	<b>BL2664</b> :L2800, L3400, L3700SU L3200, L3800 L3130, L4400, L3430, L3830, L4330, L4630, L5030, L3240, L3540, L4600  <b>L2674</b> : L3940, L4240, L4740, L5040, L5240, L5740	<b>Must order both</b> <b>BL2664</b> 64" <b>REAR</b> Snowblower or <b>L2674</b> 74" <b>REAR</b> Snowblower  <u>and</u> BL2665 Manual Chute Rotator or B2784A Hydraulic Chute Rotator	No mounting kit required, units mount to 3-Pt. Hitch. Without Front Loader: (3) Front Weights recommended for BL2664 (4) Front Weights recommended for L2674	Manual Chute Rotator or Hydraulic Chute Rotator	<b>BL2666</b> Hyd. Chute Deflector with Electric Selector Valve <b>M2686</b> Hyd. Chute Deflector <b>B2516</b> Electric Chute Deflector <b>L2177</b> Side Extension Kit (Adds 5" to overall cut)

Ⓛ Requires L8338 for Mid PTO installation in L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST

**NOTE: Check all tractor and implement references for proper counter weight requirements.**

## L Series Snowblowers

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT SNOWBLOWERS FOR GRAND L-40 AND GRAND L-30 SERIES TRACTORS ①</b>			
<b>L3240, L3540, L3940, L3130, L3430, L3830 (Mid-PTO KIT Installation Required)</b>			
L2194A	62" Two-stage Commercial Snowblower Requires: L2180-1 Quick Hitch, Mid PTO Kit and Drive Line Kit	796	\$4,860.00
<b>L4240, L4740, L5040, L5240, L5740, L4330, L4630, L5030</b>			
L2195A	72" Two-stage Commercial Snowblower Requires: L2180-1 Quick Hitch, Mid PTO Kit and Drive Line Kit	835	\$5,272.00
<b>FRONT SNOWBLOWERS FOR GRAND L-30 SERIES TRACTORS ①</b>			
<b>L3130, L3430, L3830, L4330, L4630, L5030 (Mid-PTO KIT Installation Required)</b>			
L2174A*	62" Two-stage Commercial Snowblower Requires: L2175B Chute Kit. Also must order L2180-1 Quick-hitch Sub-frame, Drive Line Kit (see selection) And Valve kit for complete installation.	430	\$2,221.00
L2185*	72" Two-stage Commercial Snowblower. Requires: L2175B Chute Kit. Also must order L2180-1 Quick-hitch Sub-frame, Drive Line Kit (see selection) and Valve kit for complete installation.	430	\$2,564.00
L2175B*	Chute Kit. Required for L2174A or L2185. Hydraulic Chute rotation standard.	180	\$1,988.00
<b>Rear-Mount Snowblowers for L2800, L3400, L3700SU, L3200, L3800, L4400, L4400-1, L4600, Grand L-30, and Grand L-40 Series ① ②</b>			
BL2664	64" Two-stage Commercial Snowblower Mounts to Category I 3-point hitch Requires BL2665 Manual Rotator chute or B2784A hydraulic chute rotator.	681	\$2,677.00
L2674	74" Two-stage Commercial Snowblower Mounts to Category I 3-point hitch Requires BL2665 Manual Rotator chute or B2784A hydraulic chute rotator.	760	\$3,377.00
BL2665	Manual chute Rotator for BL2664 or L2674	11	\$161.00
B2784A	③ Hydraulic Chute Rotator for BL2664 or L2674	12	\$787.00
BL2666	Hydraulic Chute Deflector Kit (with electric selector valve) for B2789 and BL2664	21	\$902.00
M2686	Hydraulic Chute Deflector Kit (Requires second rear remote hydraulic outlet if B2784A Chute Rotation Kit is ordered	21	\$342.00

\* \* \*

- ① Track width may not be covered with all tire combinations.
- ② If mounting Snowblowers without a Loader, the use of front weights is recommended. (3) Weights are recommended for the BL2664, and (4) weights for the L2674.
- ③ Requires Rear Remote. BL2666 has electric selector valve, so only one rear remote is required if installing hydraulic deflector and chute rotator on the same Snowblower.

## L Series Snowblowers

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>Required and Optional Accessories</b>			
L2180-1	②③④ Quick-hitch for "ALL" GL30 and GL40 Series	535	\$1,682.00
L2213A	Joystick Control Valve (4-position ROPS) With Loader installed	38	\$705.00
L2223A	Joystick Control Valve (4-position CAB) without Loader Requires: L2187 Valve Mounting Kit	42	\$1,022.00
L2187	Valve Mounting Kit (without Loader) Requires: L2223 Joystick Control Valve	17	\$80.00
L2182	Drive Line Kit Required for L2194, L3240, L3540, L3130, L3430, L3830	32	\$618.00
L2186	Drive Line Kit Required for L2195 L3940, L4240, L4740, L5040, L5240, L5740, L4330, L4630, L5030	33	\$682.00
L2179	Electric Chute Deflector For L2174A, L2185, L2194 or L2195	16	\$773.00
L2177	Drift Cutter Kit (adds 5" overall cut)	27	\$108.00
L2188	* Upgrade Support Frame Kit for L2180 only (L2180-1 includes L2188)	5	\$101.00
BL2666	① Hydraulic Chute Deflector for BL2664 or L2674	21	\$902.00
B2516	Electric Chute Deflector for BL2664 or L2674	8	\$597.00

### SNOWBLOWERS FOR 10 SERIES TRACTORS

L2174A	SNOWBLOWER (Must order L2175B) 62", Two-Stage Commercial Front Snowblower. Requires L2054B Quick-Hitch Subframe, L2175A Chute Kit, L2076 or L2086, L2206, L2207 (only with LA482 or LA682 Loader) Joystick/Hyd Valve Kit and L2051A Mid-PTO Kit.	430	\$2,221.00
L2175B	Chute Kit, requires L2174A Snowblower. Hydraulic chute rotation standard.	180	\$1,988.00
L2179	Electric Chute Deflector	16	\$773.00
L2177	Drift Cutter Kit	27	\$108.00

\* \*\*

- ① Requires Rear Remote and BL2666 electric selector valve kit if only one rear remote is used when installing Hydraulic Deflector and Chute Rotator on the same Snowblower.
- ② Prior model L2180 requires L2188 Upgrade Support Frame Kit.
- ③ L2180-1 Quick Hitch not compatible with RC72-38 Mid-mount Mower.
- ④ L2180-1 Quick Hitch not compatible with L2224 and L2233A Grille Guard unless lower cross member is removed.



# KUBOTA

## L Series Snowblowers

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>SUBFRAME, CONTROL VALVE, AND MID-PTO KIT FOR L2174A (1 Each Required)</b>			
L2054B	Quick Hitch	335	\$1,257.00
L2206	Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), and L3710HST/HSTC. Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab)	42	\$1,022.00
L2207-1	Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), and L3710HST. Two Spool Valve with Float (requires LA482/LA682 Loader). Compatible with Loader. ((4) Position)	25	\$705.00
L2086	Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), L3710HST/HSTC. Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab)	56	\$907.00
L2051A	Mid-PTO Kit	25	\$485.00
L2071	Front Support Kit	25	\$109.00

## L Series Rotary Sweepers

### ROTARY SWEEPER MATCHING CHART

Tractor Model	Rotary Sweeper
<p>L3240 L3540 L3130 L3430</p> <p>(Mid PTO Installation Required)</p>	<p><b>L2162</b>① (60" Rotary Sweeper) (51.25" at full angle)</p> <p><b>Requires:</b> L2180-1 Quick Hitch L2182 Drive Line Kit</p> <p><b>Grand L 30 Models Only:</b> <b>CHOICE OF ONE:</b> <b>L2213A</b> Joystick Control Valve (4 Pos. ROPS) WITH Loader Installed <b>L2223A</b> Joystick Control Valve (4 Pos. Fender Mount /Cab*) *Without Loader, requires L2187 Valve Mounting Kit.</p>
<p>L3240, L3540, L3940, L4240, L4740, L5040, L5240, L5740</p> <p>L3430, L3830, L4330, L4630, L5030</p> <p>(Mid PTO Installation Required)</p>	<p><b>L2164</b>① (72" Rotary Sweeper) (62.5" at full angle)</p> <p><b>Requires:</b> L2180-1 Quick Hitch L2182 Drive Line Kit (L3240, L3540, L3430, L3830) L2186 Drive Line Kit (L3940, L4240k L4740, L5040, L5240, L5740, L4330, L4630, L5030)</p> <p><b>Grand L30 Models Only:</b> <b>CHOICE OF ONE:</b> <b>L2213A</b> Joystick Control Valve (4 Pos. ROPS) WITH Loader Installed <b>L2223A</b> Joystick Control Valve (4 Pos. Fender Mount /Cab*) *Without Loader requires L2187 Valve Mounting Kit.</p>

① Requires L8338 for Mid PTO installation in L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST.

## L Series Rotary Sweepers

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>ROTARY SWEEPERS (Mid-PTO KIT Installation Required)</b>			
L2162	60" Rotary Sweeper Power Angle Standard Requires Quick-Hitch, Driveline Kit Grand L30 also requires Control Valve	570	\$3,539.00
L2164	72" Rotary Sweeper Power Angle Standard Requires Quick-hitch, DriveLine Kit Grand L30 also requires Control Valve.	570	\$4,009.00
<b>Required for Grand L-40 Series Rotary Sweepers</b>			
L2180-1	①②③ Quick-hitch for "ALL" 40 Series	535	\$1,682.00
L2182	Drive Line Kit (Required for L3240, L3540)	32	\$618.00
L2186	Drive Line Kit (Required for L3940, L4240, L5040, L5240, L5740)	33	\$682.00
<b>Required for Grand L-30 Series Rotary Sweepers</b>			
L2180-1	①③ Quick-hitch for "ALL" 30 Series	535	\$1,682.00
L2213A	Joystick Control Valve (4-position ROPS) With Loader installed	38	\$705.00
L2223A	Joystick Control Valve (4-position CAB) without Loader Requires: L2187 Valve Mounting Kit	42	\$1,022.00
L2187	Valve Mounting Kit (without Loader) Requires: L2223(A) Joystick Control Valve	17	\$80.00
L2182	Drive Line Kit Required for L3130, L3430, L3830	32	\$618.00
L2186	Drive Line Kit Required for L4330, L4630, L5030 (Replaces L2183)	33	\$682.00
<b>Rotary Sweeper Options</b>			
L2168	Rubber Dust Deflector for L2162	31	\$153.00
L2169	Rubber Dust Deflector for L2164	36	\$180.00

① Prior model L2180 requires L2188 Upgrade Support Frame Kit.

② L2180-1 Quick Hitch not compatible with RC72-38 Mid-mount Mower.

③ L2180-1 Quick Hitch not compatible with L2224 and L2233A Grille Guard unless lower cross member is removed.

## L Series Rotary Sweepers

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>Required for Grand L-10 Series Rotary Sweepers</b>			
L2206	Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), and L3710HST/HSTC. Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab)	42	\$1,022.00
L2207-1	Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), and L3710HST. Two Spool Valve with Float (requires LA482/LA682 Loader). Compatible with Loader. ((4) Position)	25	\$705.00
L2086	Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), L3710HST/HSTC. Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab)	56	\$907.00
L2054B	Quick Hitch	335	\$1,257.00
L2051A	Mid-PTO Kit	25	\$485.00
Optional			
BL2178	Side Caster Wheels (Kit) for L2062C Sweeper	47	\$439.00
L2188	* Upgrade Support Frame Kit for L2180 only (L2180-1 includes L2188)	5	\$101.00

\* \* \*

## L Series Replacement Engines

L-SERIES REPLACEMENT ENGINES  
(All Engines are Fully Assembled and Run Tested)

ORDER CODE		DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>TIER I</b>				
D1102-AE		Replacement engine for L2050F/ DT, L2350F/DT	450	\$4,018.00
D1102ASC-1	*	Replacement engine for L235F(SC), L235DT(DC), L235DT(SC)	418	\$4,102.00
D1102ADC-1	*	Replacement engine for L235F (DC)	418	\$4,102.00
D1403-AE-2		Replacement engine for L2500DT, L2600DT	300	\$3,736.00
D1403-AE		Replacement engine for L2500F, L2600F	200	\$3,736.00
D1402DI-SC		Replacement engine for L2550F, L2550DT	484	\$4,808.00
D1402DIAEW		Replacement engine for L2550GST, L2650F (DC), L2650DT (DC), L2650DT-W, L2650GST	400	\$4,808.00
V1702DI-SC		Replacement engine for L2850F (SC), L2850F (DC), L2850DT (SC), L2850DT (DC), L2850GST	510	\$6,058.00
D1503-L-A		Replacement engine for L2900F/DT/GST	441	\$4,745.00
D1462DIAEW		Replacement engine for L2950F (DC), L2950DT (DC), L2950DT-W, L2950GST	400	\$5,096.00
D1503-ELA-1	*	Replacement engine for L3000F, L3000DT	441	\$4,519.00
D1503-L-AN		Replacement engine for L3010F/DT/GST/HST	441	\$4,745.00
D1503MAEG	*	Replacement engine for L3130GST	441	\$3,537.00
D1503MAEH	*	Replacement engine for L3130HST	441	\$3,537.00
D1703-A		Replacement engine for L3300F/DT/GST	441	\$4,745.00
D1703-AN	*	Replacement engine for L3410DT/GST/HST	441	\$3,131.00
D1703MAEG	*	Replacement engine for L3430GST	441	\$3,607.00
D1703MAEH	*	Replacement engine for L3430HST	441	\$3,607.00
V1903-A		Replacement engine for L3600DT/DTC/GST	512	\$4,342.00
V1902DIAEX		Replacement engine for L3650F (DC), L3650DT (DC), L3650DT-W, L3650GST	486	\$6,538.00
V1903-AN		Replacement engine for L3710DT/GST/HST/HSTC	512	\$4,342.00
V1903EAP	*	Replacement engine for L3710GST	520	\$3,437.00
V1903EAQ	*	Replacement engine for L3710HST	520	\$3,551.00
D1803MEG	*	Replacement engine for L3830GST	480	\$3,806.00
D1803MEH	*	Replacement engine for L3830HST	480	\$3,728.00
V2203-A		Replacement engine for L4200F/DT/FGST/GST	512	\$4,543.00
V2203-AN		Replacement engine for L4300, L4310DT, L4310F, L4310GST, L4310HST, L4310HSTC	512	\$4,543.00
V2203EAQP		Replacement engine for L4310GSTC	500	\$4,543.00
V2203MAEH	*	Replacement engine for L4330HST	512	\$3,988.00
V2203EHAP	*	Replacement engine for L4610GST	500	\$3,763.00
V2203-EHA		Replacement engine for L4610HST	500	\$4,543.00
V2203-EHAQ		Replacement engine for L4610HSTC	500	\$4,543.00
V2203MBEG	*	Replacement engine for L4630GST	512	\$3,988.00

\* \* \*

## L Series Replacement Engines

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b><u>TIER I (Continued)</u></b>			
V2203MBEH	* Replacement engine for L4630HST	512	\$3,988.00
F2503-DI	Replacement engine for L4850HDT-W	832	\$6,058.00
V2403MAEG	* Replacement engine for L5030GST	500	\$4,127.00
F2803-DI	Replacement engine for L5450HDT-W	650	\$6,346.00
<b><u>TIER II</u></b>			
D1403E2A	Replacement engine for L2500F and L2600F	200	\$3,837.00
D1403E2A2	Replacement engine for L2500DT and L2600DT	300	\$3,837.00
D1403M2A	Replacement engine for L2800F and L2800DT	300	\$4,139.00
D1503E2LA2	Replacement engine for L2900F/DT/GST	441	\$4,846.00
D1503E2LA1	Replacement engine for L3000F/DT	441	\$4,846.00
D1503E2LAP	Replacement engine for L3010F/DT	450	\$4,846.00
D1503E2LA	Replacement engine for L3010HST/GST	441	\$4,846.00
D1503MA2G	Replacement engine for L3130F/GST/DT	441	\$4,846.00
D1503MA2H	Replacement engine for L3130HST	441	\$4,846.00
D1703E2A	Replacement engine for L3300F/DT/GST	441	\$4,846.00
D1703MA2A	Replacement engine for L3400F/DT	451	\$5,048.00
D1703ME2H	Replacement engine for L3400HST	450	\$5,048.00
D1703E2AP	Replacement engine for L3410DT	450	\$4,846.00
D1703E2A2	Replacement engine for L3410GST/HST	441	\$4,846.00
D1703MA2G	Replacement engine for L3430DT/GST	441	\$5,048.00
D1703MA2H	Replacement engine for L3430HST/HSTC	441	\$5,048.00
V1903E2A	Replacement engine for L3600DT/DTC/GST and L3710HST/GST	512	\$4,443.00
V1903E2AP	Replacement engine for L3710DT	520	\$4,443.00
V1903E2AQ	Replacement engine for L3710HSTC	520	\$4,443.00
D1803M2G	Replacement engine for L3830F/GST/DT	480	\$5,048.00
D1803M2H	Replacement engine for L3830HST	480	\$5,048.00
V2203E2A2	Replacement engine for L4200F/DT/GST	512	\$4,644.00
V2203E2A1	Replacement engine for L4300F/DT	512	\$4,644.00
V2203E2AP	Replacement engine for L4310F/DT/GST	520	\$4,644.00
V2203E2AQP	Replacement engine for L4310GSTC	500	\$4,644.00
V2203E2A	Replacement engine for L4310HST	512	\$4,644.00
V2203E2AQ	Replacement engine for L4310HSTC	550	\$4,644.00
V2203MA2G	Replacement engine for L4330DT/GST	512	\$5,048.00
V2203MA2H	Replacement engine for L4330HST/HSTC	512	\$5,048.00
V2203E2HAP	Replacement engine for L4610GST	500	\$4,644.00
V2203E2HA	Replacement engine for L4610HST	500	\$4,644.00
V2203E2HAQ	Replacement engine for L4610HSTC	500	\$4,644.00
V2203MB2G	Replacement engine for L4630DT/GST/GSTC	512	\$5,048.00
V2203MB2H	Replacement engine for L4630HST	512	\$5,048.00

\* \* \*

## L Series Replacement Engines

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b><u>TIER II (Continued)</u></b>			
V2403MA2G	Replacement engine for L5030GST	500	\$5,250.00
V2403MA2H	Replacement engine for L5030HST/HSTC	500	\$5,250.00
V1903E2AP	Replacement engine for L3710DT	520	\$4,443.00
V20032GST	Replacement engine for L3940DT/GST	512	\$4,515.00
V20032HST	Replacement engine for L3940HST/HSTC	512	\$4,515.00
V2403T2GST	Replacement Engine for L5040GST	500	\$5,565.00
V2403T2HST	Replacement engine for L5240HST/HSTC	500	\$5,565.00
V2403T3HST2	Replacement Engine for L5740HST/HSTC	500	\$5,565.00
V24032HST	Replacement Engine for L4740HST/HSTC	500	\$5,250.00
D17032GST	Replacement Engine for L3240F/DT/GST	441	\$5,048.00
D17032HST	Replacement Engine for L3240HST/HSTC	441	\$5,048.00
D18032GST	Replacement Engine for L3540GST	480	\$5,048.00
D18032HST	Replacement Engine for L3540HST/HSTC	480	\$5,048.00
V22032GST	Replacement Engine for L4240DT/GST	512	\$5,048.00
V22032HST	Replacement engine for L4240HST/HSTC	512	\$5,048.00
V24032GST	Replacement engine for L4740GST	500	\$5,250.00
<b><u>TIER III</u></b>			
V-2203E3LB3	Replacement engine for L4400HST-1		TBA
<b><u>INTERIM TIER IV</u></b>			
D1503E3LB	Replacement engine for L2800F-1/DT-1/HST-1	387	\$4,991.00
D1703E3G	Replacement engine for L3240F/DT/GST/F-1/ DT-1/GST-1/F-2/DT-2/ GST-2/F-3/DT-3/GST-3	441	\$5,200.00
D1703E3H	Replacement engine for L3240HST/HSTC/ HST-1/HSTC-1/HST-2/ HST-3/HSTC-3	441	\$5,200.00
D1803E3G	Replacement engine for L3540GST/GST-1/ GST-2/GST-3	480	\$5,200.00
D1803E3H	Replacement engine for L3540HST/HSTC/ HST-1/HSTC-1/HST-2/ HST-3/HSTC-3	480	\$5,200.00
D1803E3LB2	Replacement engine for L3400F-1/DT-1/HST-1	396	\$5,200.00
V2003E3G	Replacement engine for L3940DT / GST/DT-1/ GST-1/DT-2/GST-2/ DT-3/GST-3	512	\$5,200.00
V2003E3H	Replacement engine for L3940HST/HSTC/HST-1/ HSTC-1/HST-2/HST-3/HSTC-3	512	\$5,200.00
V2203E3G	Replacement engine for L4240DT/GST/DT-1/GST-1/ DT-2/GST-2/DT-3/GST-3	512	\$5,200.00
V2203E3H	Replacement engine for L4240HST/HSTC/HST-1/ HSTC-1/HST-2/HST-3/HSTC-3	512	\$5,200.00
V2203E3LB2	Replacement engine for L4400DT-1/ HST-1	454	\$5,200.00
V2403E3G	Replacement engine for L4740GST/GST-1/GST-2/ GST-3	500	\$5,408.00
V2403E3H	Replacement engine for L4740HST/HSTC/HST-1/ HSTC-1/HST-2/HST-3/HSTC-3	500	\$5,408.00
V2203M3LB3	Replacement engine for L4600DT/HST	454	\$5,200.00

## L Series Replacement Engines

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b><u>INTERIM TIER IV (Cont.)</u></b>			
V2403TE3G	Replacement engine for L5040GST/GST-1/ GST-2/GST-3	500	\$5,732.00
V2403TE3H	Replacement engine for L5240HST/HSTC-1/ HST-2/HST-3	500	\$5,732.00
V2403TE3H2	Replacement engine for L5740HST/HSTC-1 HST-2/HST-3/HSTC-3	500	\$5,732.00



This page intentionally left blank.