

Project: My City Center, Abu Dhabi  
 Project No.: 15-7364-0000  
 Stage: Final Design

SL NO.	TYPE NO.	LOCATION	LUMINAIRE		LAMP		COLOUR TEMP(K)	REV.
			DESCRIPTION	MANUFACTURER	KEY	SPECIFICATION		
1	CL10	Internal Coves	Cove Lights	Ecosense	LED	20W/M LED	3000K	0
2	CL13	Internal Concourse Coves	Cove Lights with Asymmetric Distribution	Ecosense	LED	20W/M LED	3000K	0
3	D1	Mall corridor/STR	Downlights	Hoffmeister	LED	1X19W LED	3000K	0
4	D10	Food Court, General Mall Areas	Downlights	Lucent Lighting	LED	1X16W LED	3000K	0
5	D13	Mall circulation Corridors, Prayer Rooms	Downlights	iGuzzini	LED	11 W LED	3000K	0
6	D14	Prayer Room Ablution Areas	Downlights	John Cullen	LED	11 W LED	3000K	0
7	D16	Main Concourse	Downlights	Arkos Light	LED	14 W LED	3000K	0
8	D4	Restrooms	Downlights	iGuzzini	LED	1X10W LED	3000K	0
9	D6	Toilet	Downlights	ACDC Lighting	LED	1X3W LED	3000K	0
10	LED-03	Rest Rooms	Cove Lights	Ecosense	LED	7W/M LED	3000K	0
11	LC1	Car parks	Pole-top Area Flood Light	iGuzzini	LED	25 W LED	3000K	0
12	LC2	Car parks	Pole mounted cluster of 4 Lights	iGuzzini	LED	4X20 W LED	3000K	0
13	LL8	Façade Screens	Façade Linear LED	KKDC Lighting	LED	22W/M LED	3000K	0
14	LL9	Façade - Entrance Glass Portals	Façade Linear LED	Ecosense	LED	277W/M LED	3000K	0
15	LL14	Main Entrance Canopy Edges	Canopy Linear LED	Osram	LED	8W/M LED	3000K	0
16	LL15	EIFS Grooves on Façade	Façade Linear LED	ACDC Lighting	LED	10W/M LED	3000K	0
17	LL20	Food Court	Curved Linear LED	Lightnet Architectural Lighting	LED	23W/m LED	3000K	0
18	P10	Food Court	Corcular LED Pendant	Lightnet Architectural Lighting	LED	50W LED	3000K	0
19	P11	Food Court	Corcular LED Pendant	Lightnet Architectural Lighting	LED	65W LED	3000K	0
20	P12	Food Court	Circular LED Pendant	Lightnet Architectural Lighting	LED	86W LED	3000K	0
21	P13	Ground Floor Atrium	Bespoke Pendant	Lightcraft Lighting Solutions	LED	100 W (Max) LED	3000K	0
22	P14	Ground Floor Atrium	Bespoke Pendant	Lightcraft Lighting Solutions	LED	200 W (Max) LED	3000K	0
23	PR1	Façade canopies	Façade Projectors - Mounted on canopies	iGuzzini	LED	14 W LED	3000K	0
24	S20	Entrance Canopy	Surface Mounted Downlight for Canopy	B-Light	LED	9W LED	3000K	2
25	ST1	Ramp Walls	Recessed Wall Lights	Bega	LED	9W LED	3000K	2
26	UP20	Façade Walls	Recessed Wallwasher	Erco	LED	32W LED	3000K	0
27	UP21	Façade Walls near entrances	Recessed Inground Uplight	Hoffmeister	LED	14W LED	3000K	0
28	F1	BOH Room/Plant room	Surface Mounted Linear fitting	Thorn	LED	34W LED	3000K	0
29	F2	Management Offices - Pantries etc.	Recessed 60X60 LED	Thorn	LED	28 W LED	3000K	0
30	F3	Parking Bays	Surface Mounted Luminaire	Thorn Lighting	LED	37W LED	3000K	0
31	F4	Parking Bays	Surface Mounted Luminaire	Thorn Lighting	LED	53W LED	3000K	0
32	F5	Management Offices	Recessed 60X60 LED	Fagerhult	LED	28W LED	3000K	0
33	FL15	Management offices	Suspended Linear LED	Thorn Lighting	LED	23W LED	3000K	0

Project: My City Center, Abu Dhabi  
 Project No.: 15-7364-0000  
 Stage: Final Design

SL NO.	TYPE NO.	LOCATION	LUMINAIRE		LAMP		COLOUR TEMP(K)	REV.
			DESCRIPTION	MANUFACTURER	KEY	SPECIFICATION		
34	Em-1	Concourse	Emergency-recessed	COOPER	LED	14 W	3000K	0
35	Em-2	Corridor/Offices	Emergency-recessed	COOPER	LED	3 W	3000	0
36	Em-3	PLANT ROOMS	Emergency-Surfaced	COOPER	LED	1x8W	4948 K	0
37	EXIT-W	General Areas	Exit Lights - Wall	Inotec	LED	1x4W	3000K	0
38	EX	General Areas	Exit Lights - Recessed Ceiling	Inotec	LED	18x0.1W	3000K	0
39	EXIT	Normal Areas	Exit Lights - Surface Ceiling	Inotec	LED	1x4W	3000K	0
40	WL1	Stairs/lift shaft	Wall Mounted Lights	Thorn	LED	16 W LED	3000K	0
41	WL2	Parking Areas, External circulation areas	Wall Mounted Lights	iGuzzini	LED	23W LED	3000K	0
42	WL3	Parking Areas, External circulation areas	Wall Mounted Lights	CREE	LED	135W LED	3000K	0
43	Sheet1							


<b>LAMP KEY</b>	MH = Metal Halide INC = Incandescent CC = Cold Cathode TH = Tungsten Halogen H = Halogen LV = Low Voltage LED = Light Emitting Diode FL = Fluorescent PL = Compact Fluorescent
-----------------	--

Project	My City Center, Abu Dhabi	Type	CL10
Project No.	15-7364-0000	Stage:	

**Description**

Cove Lights

Location: Internal Covers


**Luminaire information:**

Manufacturer (Design based on)	Ecosense	Model	Trov L35-I-48-06-30-80-MULT-120
Alternative Manufacturer	Color Kinetics, Lumenpulse, Traxon	Protection Class	IP54
Colour	Grey	Controlgear	Remote Electronic 240V/50Hz
Housing	Extruded Aluminium	Dimming	-
Reflector	Individual LED reflectors, 120° beam	Luminaire Lumen Output	1676 lm/m
Diffuser	Polycarbonate Lens	Design Load (watts)	20W/m
Mounting	Surface mount, with adjustable brackets	Cut-Off Angle	
Accessories	Connectors, Cables, bracket (SCI-A-MNT-ADJ), all applicable installation accessories		

**Lamp information:**


Specification	20W/M LED	<b>Notes:</b>	
Lamp Key	LED	Continuous end-to-end Mounting for coves.	
Lumen output/Lamp	1700 lm/M	Contractor to verify exact lengths and required power supplies as per site conditions.	
Lamp Life (hours)	50,000		
Colour Temp	3000K	MacAdam 2 Single Bin	
Lamp Base			

Project	My City Center, Abu Dhabi	Type	CL13
Project No.	15-7364-0000	Stage:	

### Description

Cove Lights with Asymmetric Distribution

Location: Internal Concourse Coves



### Luminaire information:

Manufacturer (Design based on)	Ecosense	Model	Trov L50-I-12-06-30-80-MULT-ASYM
Alternative Manufacturer	Color Kinetics, Lumenpulse, Traxon	Protection Class	IP54
Colour	Grey	Controlgear	Remote Electronic 240V/50Hz
Housing	Extruded Aluminium	Dimming	-
Reflector	Individual LED reflectors, Asymmetric beam	Luminaire Lumen Output	1614 lm/m
Diffuser	Polycarbonate Lens	Design Load (watts)	20W/m
Mounting	Surface mount, with adjustable brackets	Cut-Off Angle	
Accessories	Connectors, Cables, bracket (SCI-A-MNT-ADJ), all applicable installation accessories		

### Lamp information: Notes:

Specification	20W/M LED	Continuous end-to-end Mounting for central
Lamp Key	LED	coves of concourse. Asymmetric.
Lumen output/Lamp	1614 lm/M	Contractor to verify exact lengths and required
Lamp Life (hours)	50,000	power supplies as per site conditions.
Colour Temp	3000K	MacAdam 2 Single Bin
Lamp Base		

Project	My City Center, Abu Dhabi	Type	D1
Project No.	15-7364-0000	Stage:	

**Description**

Downlights

Location: Mall corridor/STR



**Luminaire information:**

Manufacturer (Design based on)	Hoffmeister	Model	DL 170 102 484-1
Alternative Manufacturer	Erco, Bega, Zumtobel	Protection Class	IP20
Colour	White	Controlgear	Integral electronic
Housing	Thermoplastic, Aluminium Cooling elements	Dimming	-
Reflector	Aluminium, projected reflector edge with Shadow gap	Luminaire Lumen Output	1600 lm
Diffuser	-	Design Load (watts)	19W
Mounting	Recessed in Ceiling	Cut-Off Angle	
Accessories	Connectors, all applicable installation accessories		


Lamp information:		Notes:
Specification	1X19W LED	
Lamp Key	LED	
Lumen output/Lamp	2000 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type No.	D10
Project No.	15-7364-0000		

### Description

Downlights

Location: Food Court, General Mall Areas




Luminaire information:			
Manufacturer (Design based on)	Lucent Lighting	Model	090-XTM1980-TL-WH
Alternative Manufacturer	iGuzzini, Regianni, Delta Lighting	Protection Class	IP20
Colour	White	Controlgear	Integral electronic
Housing	Cast Aluminium	Dimming	Switched
Reflector	Matt white, 40 degrees	Luminaire Lumen Output	1460 lm
Diffuser	-	Design Load (watts)	16W
Mounting	Recessed in Ceiling	Cut-Off Angle	
Accessories	Connectors, all applicable installation accessories		
Lamp information:		Notes:	
Specification	1X16W LED		
Lamp Key	LED		
Lumen output/Lamp	2000 lm		
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			

Project	My City Center, Abu Dhabi	Type No.	D13
Project No.	15-7364-0000		

### Description

Downlights

Location: Mall circulation Corridors, Prayer Rooms



### Luminaire information:

Manufacturer (Design based on)	iGuzzini	Model	Laser P351
Alternative Manufacturer	Lucent, Delta Lighting, Erco	Protection Class	IP20
Colour	White	Controlgear	Remote electronic
Housing	Die Cast Aluminium	Dimming	Switched
Reflector	Fixed Optic Metallized Thermoplastic	Luminaire Lumen Output	870 lm
Diffuser	Anti Glare Screen, Glass Cover for LED module	Design Load (watts)	11W
Mounting	Recessed in Ceiling	Cut-Off Angle	
Accessories	Connectors, all applicable installation accessories		

### Lamp information: Notes:


Specification	11 W LED	
Lamp Key	LED	
Lumen output/Lamp	1000 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type No.	D14
Project No.	15-7364-0000		

### Description

Downlights

Location: Prayer Room Ablution Areas



### Luminaire information:

Manufacturer (Design based on)	John Cullen	Model	Aquabeam Medium
Alternative Manufacturer	Lucent, Delta Lighting, LumenAlpha	Protection Class	IP 54
Colour	White	Controlgear	Remote electronic 12V DC
Housing	Die Cast Aluminium Heat Sink	Dimming	Switched
Reflector	LED Lens reflector	Luminaire Lumen Output	900 lm
Diffuser	Softening Lens SL50	Design Load (watts)	10W
Mounting	Recessed in Ceiling	Cut-Off Angle	
Accessories	Connectors, Softening Lens SL50, all applicable installation accessories		

### Lamp information: Notes:

Specification	11 W LED	
Lamp Key	LED	
Lumen output/Lamp	900 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		



Project	My City Center, Abu Dhabi	Type	<b>D16</b>
Project No.	15-7364-0000	Stage:	


**Description**

Downlights

Location: Main Concourse



**DIMENSIONS**



**ACCESSORIES**

**Luminaire information:**

Manufacturer (Design based on)	Arkos Light	Model	LEX ECO 1 3000K W A0700101W
Alternative Manufacturer	Lucent Lighting, Delta Lighting, Lamp Lighting	Protection Class	IP 54
Colour	Matt White	Controlgear	Remote electronic 12V DC
Housing	Aluminium, Polycarbonate	Dimming	Switched
Reflector	LED Lens reflector	Luminaire Lumen Output	1500 lm
Diffuser	Glass lens	Design Load (watts)	14W
Mounting	Recessed in Ceiling	Cut-Off Angle	
Accessories	Connectors, all applicable installation accessories		

**Lamp information:**


Specification	14 W LED	<b>Notes:</b>
Lamp Key	LED	
Lumen output/Lamp	1500 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type	<b>D4</b>
Project No.	15-7364-0000	Stage:	

**Description**

Downlights

Location: Restrooms



**Luminaire information:**

Manufacturer (Design based on)	iGuzzini	Model	Deep Laser MA41
Alternative Manufacturer	Lucent, Delta Lighting, Erco	Protection Class	IP55
Colour	White	Controlgear	Remote electronic
Housing	Die Cast Aluminium	Dimming	Switched
Reflector	Fixed Optic Metallized Thermoplastic	Luminaire Lumen Output	750 lm
Diffuser	Anti Glare Screen, Glass Cover	Design Load (watts)	12W
Mounting	Recessed in Ceiling	Cut-Off Angle	
Accessories	Connectors, all applicable installation accessories		

**Lamp information:**


Specification	1X10W LED	<b>Notes:</b>
Lamp Key	LED	
Lumen output/Lamp	720 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type	D6
Project No.	15-7364-0000	Stage:	

### Description

Downlights

Location: Toilet




Luminare information:			
Manufacturer (Design based on)	ACDC Lighting	Model	Arena IP65
Alternative Manufacturer	Lucent, Delta Lighting, Erco	Protection Class	IP65
Colour	White	Controlgear	Remote electronic
Housing	Die Cast Aluminium	Dimming	Switched
Reflector	Anodized Aluminium	Luminaire Lumen Output	184 lm
Diffuser	Deep Regressed LED Lens	Design Load (watts)	3W
Mounting	Recessed in Ceiling	Cut-Off Angle	
Accessories	Connectors, all applicable installation accessories		
Lamp information:		Notes:	
Specification	1X3W LED		
Lamp Key	LED		
Lumen output/Lamp	184 lm		
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			

Project	My City Center, Abu Dhabi	Type	LED-03
Project No.	15-7364-0000	Stage:	

### Description

Cove Lights

Location: Rest Rooms




Luminaire information:			
Manufacturer (Design based on)	Ecosense	Model	Trov L35-I-48-04-30-80-MULT-120
Alternative Manufacturer	Color Kinetics, Lumenpulse, Traxon	Protection Class	IP54
Colour	Grey	Controlgear	Remote Electronic 240V/50Hz
Housing	Extruded Aluminium	Dimming	Reverse Phase (Trailing Edge)
Reflector	Individual LED reflectors, 120° beam	Luminaire Lumen Output	348 lm
Diffuser	Polycarbonate Lens	Design Load (watts)	7W/m
Mounting	Surface mount, with adjustable brackets	Cut-Off Angle	
Accessories	Connectors, Cables, bracket (SCI-A-MNT-ADJ), all applicable installation accessories		
Lamp information:		Notes:	
Specification	7W/M LED	Continuous end-to-end Mounting for coves.	
Lamp Key	LED	Contractor to verify exact lengths and required power supplies as per site conditions.	
Lumen output/Lamp	417 lm/M		
Lamp Life (hours)	50,000		
Colour Temp	3000K	MacAdam 2 Single Bin	
Lamp Base			

Project	My City Center, Abu Dhabi		Type No.	LC1
Project No.	15-7364-0000	Stage:		

### Description

Pole-top Area Flood Light

Location: Car parks




Luminaire information:			
Manufacturer (Design based on)	iGuzzini	Model	iTeka BU48+ Standard 4m Pole
Alternative Manufacturer	Thorn, Philips, Ligman	Protection Class	IP66
Colour	Grey	Controlgear	Integral Electronic
Housing	Corrosion resistant Aluminium	Dimming	None
Reflector	Individual LED Lens, asymmetrical Optics	Luminaire Lumen Output	1910 lm
Diffuser	Cleared Safety Glass	Design Load (watts)	25 W
Mounting	Pole Mounted		
Accessories	All applicable installation accessories		
Lamp information:		Notes:	
Specification	25 W LED	Standard Pole Mounted Fixture	
Lamp Key	LED	Mounting Height 4 M	
Lumen output/Lamp	1910 lm	Pole to be standard GI finish with access hatch.	
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			

Project	My City Center, Abu Dhabi		Type No.	LC2
Project No.	15-7364-0000	Stage:		

**Description**

Pole mounted cluster of 4 Lights

**Location:** Car parks



**Luminaire information:**

Manufacturer (Design based on)	iGuzzini	Model	Platea Pro P883
Alternative Manufacturer	Thorn, Philips, Ligman	Protection Class	IP66
Colour	Grey	Controlgear	Integral Electronic
Housing	Cast Aluminium Alloy	Dimming	None
Reflector	Individual LED Lens, Asymmetric 45° Optic	Luminaire Lumen Output	4X5400 lm
Diffuser	Cleared Safety Glass	Design Load (watts)	4X60 W
Mounting	Pole Mounted		
Accessories	All applicable installation accessories		

**Lamp information:**



Specification	4X20 W LED	<b>Notes:</b>
Lamp Key	LED	4X BV15 fixtures mounted on a single pole
Lumen output/Lamp	5200 lm	Orientation as per drawing EL-101
Lamp Life (hours)	50,000	Mounting Height 8 M
Colour Temp	3000K	Pole to be standard GI finish with access hatch.
Lamp Base		

Project	My City Center, Abu Dhabi	Type	LL8
Project No.	15-7364-0000	Stage:	

### Description

Façade Linear LED

Location: Façade Screens



### Luminaire information:

Manufacturer (Design based on)	KKDC Lighting	Model	SEN 050
Alternative Manufacturer	LED Linear, EcoSense, Lumenpulse	Protection Class	IP67
Colour	Steel Grey	Controlgear	Remote Electronic 240V/50Hz 350mA
Housing	Cast Aluminium	Dimming	
Reflector	Individual LED reflectors, 10°x45° Grazing optics	Luminaire Lumen Output	1420 lm/m
Diffuser	Polycarbonate Lens	Design Load (watts)	22W/m
Mounting	Surface mount, with brackets	Cut-Off Angle	
Accessories	Connectors, Cables, bracket (SCI-A-MNT-ADJ), all applicable installation accessories		

### Lamp information: Notes:


Specification	22W/M LED	
Lamp Key	LED	Continuous end-to-end Mounting for Façade
Lumen output/Lamp	1420 lm/M	Screen.
Lamp Life (hours)	50,000	Contractor to verify exact lengths and required power supplies as per site conditions.
Colour Temp	3000K	
Lamp Base		MacAdam 2 Single Bin

Project	My City Center, Abu Dhabi	Type	LL9
Project No.	15-7364-0000	Stage:	

### Description

Façade Linear LED

Location: Façade - Entrance Glass Portals



### Luminaire information:

Manufacturer (Design based on)	Ecosense	Model	Trov L50-E-12-08-30-80-MULT-25X25
Alternative Manufacturer	Color Kinetics, Lumenpulse, Traxon	Protection Class	IP66
Colour	Grey	Controlgear	Integral Electronic 240V/50Hz
Housing	Extruded Aluminium	Dimming	Reverse Phase (Trailing Edge)
Reflector	Individual LED reflectors, 25°X25° beam	Luminaire Lumen Output	2224 lm/m
Diffuser	Polycarbonate Lens	Design Load (watts)	27W/m
Mounting	Surface mount, with adjustable brackets	Cut-Off Angle	
Accessories	Connectors, Cables, bracket (SCI-A-MNT-ADJ), all applicable installation accessories		

### Lamp information: Notes:

Specification	277W/M LED	Continuous end-to-end Mounting for Façade	
Lamp Key	LED	Screen.	
Lumen output/Lamp	2224 lm/M	Contractor to verify exact lengths and required power supplies as per site conditions.	
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base		MacAdam 2 Single Bin	



Project	My City Center, Abu Dhabi	Type	LL14
Project No.	15-7364-0000	Stage:	


**Description**

Canopy Linear LED

**Location:** Main Entrance Canopy Edges



LINEARlight FLEX DIFFUSE TOP  
White




Luminaire information:			
Manufacturer (Design based on)	Osram	Model	Flex Diffuse 400 Top LFD400T - G1-827-06
Alternative Manufacturer	LED linear, Lined, MCI	Protection Class	IP67
Colour	White	Controlgear	Remote Electronic 24V DC
Housing	UV resistant Silicon	Dimming	None
Reflector	Individual LED reflectors, 25°X25° beam	Luminaire Lumen Output	490 lm/m
Diffuser	Diffused Silicon Coating	Design Load (watts)	8W/m
Mounting	Recessed in Canopy Edge	Cut-Off Angle	
Accessories	Connectors, Cables, all applicable installation accessories		
Lamp information:		Notes:	
Specification	8W/M LED	Continuous Mounting for Canopy	
Lamp Key	LED	Contractor to verify exact lengths, required	
Lumen output/Lamp	490 lm/M	power supplies and cut-at-site requirements	
Lamp Life (hours)	50,000	as per site conditions.	
Colour Temp	3000K		
Lamp Base		MacAdam 2 Single Bin	

Project	My City Center, Abu Dhabi		Type	LL15
Project No.	15-7364-0000	Stage:	Final Design	

### Description

Façade Linear LED

Location: EIFS Grooves on Façade



### Luminaire information:

Manufacturer (Design based on)	ACDC Lighting	Model	ACDC Vista
Alternative Manufacturer	KKDC, iGuzzini, Kemps	Protection Class	IP67
Colour	Aluminium Silver	Controlgear	Remote Electronic 24V DC
Housing	Aluminium Extrusion	Dimming	None
Reflector	Individual LED reflectors, 25°X25° beam	Luminaire Lumen Output	500 lm/m
Diffuser	UV resistan Opal Glass	Design Load (watts)	10W/m
Mounting	Recessed in Canopy Edge	Cut-Off Angle	
Accessories	Connectors, Cables, all applicable installation accessories		

### Lamp information: Notes:



Specification	10W/M LED	Mounting for EIFS Grooves in Façade	
Lamp Key	LED	Contractor to verify exact lengths, required	
Lumen output/Lamp	500 lm/M	power supplies requirements	
Lamp Life (hours)	50,000	as per site conditions.	
Colour Temp	3000K		
Lamp Base		MacAdam 2 Single Bin	

Project	My City Center, Abu Dhabi	Type	LL20
Project No.	15-7364-0000	Stage:	

**Description**

Curved Linear LED

**Location:** Food Court



**Luminaire information:**

Manufacturer (Design based on)	Lightnet Architectural Lighting	Model	Liquid Line A3
Alternative Manufacturer	Prolicht, XAL, Selux	Protection Class	IP20
Colour	Black	Controlgear	Integral Electronic 240V/50Hz
Housing	Extruded Aluminium	Dimming	None
Reflector	Individual LED reflectors	Luminaire Lumen Output	1770 lm/m
Diffuser	Microprismatic Screen	Design Load (watts)	23W/m
Mounting	Recessed	Cut-Off Angle	
Accessories	Connectors, Cables, bracket, all applicable installation accessories		

**Lamp information:**



Specification	23W/m LED	<b>Notes:</b>	Curved Linear Continuous Mount
Lamp Key	LED		Light Line LED
Lumen output/Lamp	5000 lm/m		
Lamp Life (hours)	50,000		
Colour Temp	3000K		MacAdam 2 Single Bin
Lamp Base			

Project	My City Center, Abu Dhabi	Type	P10
Project No.	15-7364-0000	Stage:	

### Description

Corcular LED Pendant

Location: Food Court



### Luminaire information:

Manufacturer (Design based on)	Lightnet Architectural Lighting	Model	Ringo Star-G1 Direct Opal
Alternative Manufacturer	Prolicht, XAL, Selux	Protection Class	IP20
Colour	Black	Controlgear	Integral Electronic 240V/50Hz
Housing	Extruded Aluminium	Dimming	None
Reflector	Individual LED reflectors	Luminaire Lumen Output	3600 lm
Diffuser	Opal Screen	Design Load (watts)	50W
Mounting	Pendant mount - Central Suspension	Cut-Off Angle	
Accessories	Cables, bracket, all applicable installation accessories		

### Lamp information: Notes:



Specification	50W LED	Circular LED Pendant
Lamp Key	LED	
Lumen output/Lamp	3600 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	MacAdam 2 Single Bin
Lamp Base		

Project	My City Center, Abu Dhabi	Type No.	P11
Project No.	15-7364-0000		

### Description

Corcular LED Pendant

Location: Food Court



### Luminaire information:

Manufacturer (Design based on)	Lightnet Architectural Lighting	Model	Ringo Star-G1 Direct Opal
Alternative Manufacturer	Prolicht, XAL, Selux	Protection Class	IP20
Colour	Black	Controlgear	Integral Electronic 240V/50Hz
Housing	Extruded Aluminium	Dimming	None
Reflector	Individual LED reflectors	Luminaire Lumen Output	4800 lm
Diffuser	Opal Screen	Design Load (watts)	65W
Mounting	Pendant mount - Central Suspension	Cut-Off Angle	
Accessories	Cables, bracket, all applicable installation accessories		



Lamp information:		Notes:	
Specification	65W LED	Circular LED Pendant	
Lamp Key	LED		
Lumen output/Lamp	4800 lm		
Lamp Life (hours)	50,000		
Colour Temp	3000K	MacAdam 2 Single Bin	
Lamp Base			

Project	My City Center, Abu Dhabi	Type	P12
Project No.	15-7364-0000	Stage:	

### Description

Circular LED Pendant

Location: Food Court



### Luminaire information:

Manufacturer (Design based on)	Lightnet Architectural Lighting	Model	Ringo Star-G1 Direct Opal
Alternative Manufacturer	Prolicht, XAL, Selux	Protection Class	IP20
Colour	Black	Controlgear	Integral Electronic 240V/50Hz
Housing	Extruded Aluminium	Dimming	None
Reflector	Individual LED reflectors	Luminaire Lumen Output	6400 lm
Diffuser	Opal Screen	Design Load (watts)	86W
Mounting	Pendant mount - Central Suspension	Cut-Off Angle	
Accessories	Cables, bracket, all applicable installation accessories		

### Lamp information: Notes:


Specification	86W LED	Circular LED Pendant
Lamp Key	LED	
Lumen output/Lamp	6400 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	MacAdam 2 Single Bin
Lamp Base		

Project	My City Center, Abu Dhabi	Type	P13
Project No.	15-7364-0000	Stage:	

**Description**

Bespoke Pendant

**Location:** Ground Floor Atrium



**Luminaire information:**

Manufacturer (Design based on)	Lightcraft Lighting Solutions	Model	
Alternative Manufacturer		Protection Class	
Colour		Controlgear	
Housing		Dimming	
Reflector	-	Luminaire Lumen Output	
Diffuser		Design Load (watts)	100W Max (LED) per pendant
Mounting	Pendant mount	Cut-Off Angle	
Accessories			

**Lamp information:** **Notes:**

Specification	100 W (Max) LED	
Lamp Key	LED	
Lumen output/Lamp		
Lamp Life (hours)		
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi		Type	<b>P14</b>
Project No.	15-7364-0000	Stage:	Final Design	

**Description**

Bespoke Pendant

**Location:** Ground Floor Atrium



**Luminaire information:**

Manufacturer (Design based on)	Lightcraft Lighting Solutions	Model	
Alternative Manufacturer		Protection Class	
Colour		Controlgear	
Housing		Dimming	
Reflector	-	Luminaire Lumen Output	
Diffuser		Design Load (watts)	200W Max (LED)
Mounting	Suspension mount	Cut-Off Angle	
Accessories			

**Lamp information:** **Notes:**

Specification	200 W (Max) LED	
Lamp Key	LED	
Lumen output/Lamp		
Lamp Life (hours)		
Colour Temp	3000K	
Lamp Base		




Project	My City Center, Abu Dhabi		Type	<b>PR1</b>
Project No.	15-7364-0000	Stage:	Final Design	

### Description

Façade Projectors - Mounted on canopies

Location: Façade canopies



Luminare information:			
Manufacturer (Design based on)	iGuzzini	Model	iPro BX05
Alternative Manufacturer	Erco, bega, Targetti	Protection Class	IP20
Colour	Grey	Controlgear	Integral electronic
Housing	Die Cast Aluminium	Dimming	Switched
Reflector	Anodized Aluminium	Luminaire Lumen Output	1350 lm
Diffuser	4mm Thick tempered glass	Design Load (watts)	14W
Mounting	Surface Mounted	Cut-Off Angle	
Accessories	Mounting base, all applicable installation accessories		
Lamp information:		Notes:	
Specification	14 W LED	To be aimed on site for optimal angle	
Lamp Key	LED		
Lumen output/Lamp	1350 lm		
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			

Project	My City Center, Abu Dhabi	Type No.	S20
Project No.	15-7364-0000		

**Description**

Surface Mounted Downlight for Canopy

**Location:** Entrance Canopy



**Luminaire information:**

Manufacturer (Design based on)	B-Light	Model	Okkio 55 CL
Alternative Manufacturer	iGuzzini, Simes, Bega	Protection Class	IP 65
Colour	Bronze	Controlgear	Remote Electronic
Housing	Aluminium	Dimming	None
Reflector	LED Lens reflector, 16°	Luminaire Lumen Output	500 lm
Diffuser	Anti Glare Lens	Design Load (watts)	6 W
Mounting	Surface Mounted on Canopy Nodes		
Accessories	All applicable installation accessories, Power supplies		

**Lamp information:** **Notes:**


Specification	9W LED	
Lamp Key	LED	
Lumen output/Lamp	500 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type No.	ST1
Project No.	15-7364-0000		

### Description

Recessed Wall Lights

Location: Ramp Walls



### Luminaire information:

Manufacturer (Design based on)	Bega	Model	Bega 2355 + A
Alternative Manufacturer	iGuzzini, Simes, Erco	Protection Class	IP 65
Colour	Steel Grey	Controlgear	Integral Electronic
Housing	Aluminium Alloy, Aluminum and Stainless Steel	Dimming	None
Reflector	-	Luminaire Lumen Output	100 lm
Diffuser	Aluminium Louvers for directed emission	Design Load (watts)	10 W
Mounting	Recessed in staircase walls		
Accessories	Installation Housing, All applicable installation accessories, Power supplies		

### Lamp information: Notes:



Specification	9W LED	
Lamp Key	LED	
Lumen output/Lamp	100 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi		Type	<b>UP20</b>
Project No.	15-7364-0000	Stage:	Final Design	

**Description**

Recessed Wallwasher

**Location:** Façade Walls



**Luminaire information:**

Manufacturer (Design based on)	Erco	Model	Tesis 33582.000
Alternative Manufacturer	Hoffmeister, Zumtobel, iGuzzini	Protection Class	IP68
Colour	Silver Grey	Controlgear	Integral Electronic
Housing	Toughened Plastic, Black, Stainless Steel Trim	Dimming	None
Reflector	LED Lens system, Wallwash optics	Luminaire Lumen Output	3360 lm
Diffuser	Toughened Glass	Design Load (watts)	32 W
Mounting	Recessed in ground		
Accessories	Power Supplies, connectors, all applicable installation accessories		

**Lamp information:**


Specification	32W LED	<b>Notes:</b>
Lamp Key	LED	
Lumen output/Lamp	3360 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi		
Project No.	15-7364-0000	Stage:	Final Design

Type No.	<b>UP21</b>
----------	-------------

**Description**

Recessed Inground Uplight

**Location:** Façade Walls near entrances

**Luminaire information:**

Manufacturer (Design based on)	Hoffmeister	Model	in.ground 100 round 071 334 03 902
Alternative Manufacturer	Erco, Bega, Meyer	Protection Class	IP68
Colour	Silver Grey	Controlgear	Integral Electronic
Housing	Polyamid, fibreglass reinforced	Dimming	None
Reflector	Individual LED reflectors, 25 °	Luminaire Lumen Output	980 lm
Diffuser	Toughened Glass	Design Load (watts)	14 W
Mounting	Recessed in ground		
Accessories	Power Supplies, connectors, all applicable installation accessories		

**Lamp information:**

Specification	14W LED
Lamp Key	LED
Lumen output/Lamp	1200 lm
Lamp Life (hours)	50,000
Colour Temp	3000K
Lamp Base	


**Notes:**


Project	My City Center, Abu Dhabi	Type	F1
Project No.	15-7364-0000	Stage:	

### Description

Surface Mounted Linear fitting

### Location: BOH Room/Plant room



LED CE EAC 850°C IK08 IP65

$T_a$  -20  
+25

### Luminaire information:

Manufacturer (Design based on)	Thorn	Model	96241869
Alternative Manufacturer	Trilux,Zumtobel,Philips	Protection Class	IP65
Colour	Powder coated dark grey	Controlgear	Integral Electronic
Housing	Poly carbonate	Dimming	None
Reflector	-	Luminaire Lumen Output	4300 lm
Diffuser	Polycarbonate (PC) with linear prisms	Design Load (watts)	34 W
Mounting	Ceiling surface mounted		
Accessories	All applicable installation accessories		

### Lamp information: Notes:


Specification	34W LED	
Lamp Key	LED	
Lumen output/Lamp	4300 lm	
Lamp Life (hours)		
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi		Type	F2
Project No.	15-7364-0000	Stage:	Final Design	

**Description**

Recessed 60X60 LED

**Location:** Management Offices - Pantries etc.




<b>Luminaire information:</b>			
Manufacturer (Design based on)	Thorn	Model	OMEGA LED 3250-830 HF Q597
Alternative Manufacturer	Trilux ,philips.Zumtobel	Protection Class	IP 44
Colour	white	Controlgear	Integral Electronic
Housing	deep drawn steel	Dimming	None
Reflector	opal acrylic	Luminaire Lumen Output	2604 lm
Diffuser	opal acrylic	Design Load (watts)	32 W
Mounting	Ceiling Recessed		
Accessories	All applicable installation accessories		
<b>Lamp information:</b>		<b>Notes:</b>	
Specification	28 W LED		
Lamp Key	LED		
Lumen output/Lamp	3465 lm		
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			

Project	My City Center, Abu Dhabi	Type	F3
Project No.	15-7364-0000	Stage:	

**Description**

Surface Mounted Luminaire

Location: Parking Bays



**Luminaire information:**

Manufacturer (Design based on)	Thorn Lighting	Model	ForceLED Pro 96628062
Alternative Manufacturer	Zumtobel, Philips, Sylvania	Protection Class	
Colour	Powder coated dark grey	Controlgear	Integral Electronic
Housing	Die Cast Aluminium	Dimming	None
Reflector	-	Luminaire Lumen Output	3800 lm
Diffuser	Corrosion resistant Polycarbonate	Design Load (watts)	37 W
Mounting	Ceiling surface mounted		
Accessories	All applicable installation accessories		

**Lamp information:**

Specification	37W LED	<b>Notes:</b>
Lamp Key	LED	
Lumen output/Lamp	4500 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		




Project	My City Center, Abu Dhabi	Type	F4
Project No.	15-7364-0000	Stage:	

### Description

Surface Mounted Luminaire

Location: Parking Bays



### Luminaire information:

Manufacturer (Design based on)	Thorn Lighting	Model	96628065 Force LED pro
Alternative Manufacturer	Zumtobel, Philips, Sylvania	Protection Class	IP65
Colour	Powder coated dark grey	Controlgear	Integral Electronic
Housing	Die Cast Aluminium	Dimming	None
Reflector	-	Luminaire Lumen Output	6400 lm
Diffuser	Polycarbonate (PC) with linear prisms	Design Load (watts)	53 W
Mounting	Ceiling surface mounted		
Accessories	All applicable installation accessories		

### Lamp information: Notes:


Specification	53W LED	
Lamp Key	LED	
Lumen output/Lamp	6400 lm	
Lamp Life (hours)	50,000	
Colour Temp	30000K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type No.	F5
Project No.	15-7364-0000		

**Description**

Recessed 60X60 LED

**Location:** Management Offices



**Luminaire information:**

Manufacturer (Design based on)	Fagerhult	Model	Indigo LED
Alternative Manufacturer	Zumtobel, Philips, Sylvania	Protection Class	IP20
Colour	White	Controlgear	Integral Electronic
Housing	White Enamelled Sheet Steel	Dimming	None
Reflector	-	Luminaire Lumen Output	2750 lm
Diffuser	Opal Acrylic	Design Load (watts)	28 W
Mounting	Ceiling surface mounted		
Accessories	All applicable installation accessories		

**Lamp information:** **Notes:**



Specification	28W LED	
Lamp Key	LED	
Lumen output/Lamp	2750 lm	
Lamp Life (hours)	50,000	
Colour Temp	30000K	
Lamp Base		

Project	My City Center, Abu Dhabi		Type	<b>FL15</b>
Project No.	15-7364-0000	Stage:	Final Design	

**Description**

Suspended Linear LED

**Location:** Management offices



**Luminaire information:**

Manufacturer (Design based on)	Thorn Lighting	Model	Equaline LED Recessed
Alternative Manufacturer	Zumtobel, Philips, Sylvania	Protection Class	IP20
Colour	Grey	Controlgear	Integral Electronic
Housing	Extruded Aluminium	Dimming	None
Reflector	-	Luminaire Lumen Output	1722 lm
Diffuser	Acrylic	Design Load (watts)	23 W
Mounting	Recessed		
Accessories	All applicable installation accessories with mains cable and suspension kits		

**Lamp information:**

Specification	23W LED	<b>Notes:</b>
Lamp Key	LED	
Lumen output/Lamp	1722 lm	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type	<b>Em-1</b>
Project No.	15-7364-0000	Stage:	

**Description**

Emergency-recessed

Location: Concourse



<b>Luminaire information:</b>			
Manufacturer (Design based on)	COOPER	Model	RXS2 LARGE
Alternative Manufacturer	Teknoware ,JSB	Protection Class	IP20
Colour	white	Controlgear	Electronic
Housing	die cast aluminium with polycarbonate cable clamp	Dimming	NA
Reflector	high grade satin anodised aluminium	Luminaire Lumen Output	1539lm
Diffuser	NA	Design Load (watts)	14
Mounting	Recessed		
Accessories	NA		
<b>Lamp information:</b>		<b>Notes:</b>	
Specification	14 W	With Softening lens 251 70 03 04	
Lamp Key	LED		
Lumen output/Lamp	1539 lm		
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			

Project	My City Center, Abu Dhabi		Type	<b>Em-2</b>
Project No.	15-7364-0000	Stage:	Final Design	

**Description**

Emergency-recessed

Location: Corridor/Offices



<b>Luminaire information:</b>			
Manufacturer (Design based on)	COOPER	Model	MP2HI230
Alternative Manufacturer	Teknoware,JSB	Protection Class	IP20
Colour	white	Controlgear	Electronic
Housing	Polycarbonite	Dimming	None
Reflector	None	Luminaire Lumen Output	298lm
Diffuser	None	Design Load (watts)	3 W
Mounting	Ceiling recessed		
Accessories	None		
<b>Lamp information:</b>		<b>Notes:</b>	
Specification	3 W		
Lamp Key	LED		
Lumen output/Lamp	298 lm		
Lamp Life (hours)	60,000		
Colour Temp	3000		
Lamp Base			

Project	My City Center, Abu Dhabi	Type	<b>Em-3</b>
Project No.	15-7364-0000	Stage:	

**Description**

Emergency-Surfaced

**Location:** PLANT ROOMS



**Luminaire information:**

Manufacturer (Design based on)	COOPER	Model	ALFALUX HIGH BAY LED
Alternative Manufacturer	Teknoware,JSB	Protection Class	IP65
Colour	White	Controlgear	Electronic
Housing	Polycarbonate White	Dimming	None
Reflector	None	Luminaire Lumen Output	600 lm
Diffuser	None	Design Load (watts)	8 W
Mounting	Surface Mounted		
Accessories	Power supply, all applicable installation accessories		

**Lamp information:** **Notes:**

Specification	1x8W	
Lamp Key	LED	
Lumen output/Lamp	600 lm	
Lamp Life (hours)	50,000	
Colour Temp	4948 K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type	<b>EXIT-W</b>
Project No.	15-7364-0000	Stage:	

**Description**

Exit Lights - Wall

**Location:** General Areas



<b>Luminaire information:</b>			
Manufacturer (Design based on)	Inotec	Model	SNP 2518 LED
Alternative Manufacturer	CEAG, Teknoware ,JSB	Protection Class	IP65
Colour	White	Controlgear	Electronic
Housing	Polycarbonate White	Dimming	None
Reflector	None	Luminaire Lumen Output	NA
Diffuser	None	Design Load (watts)	4.2
Mounting	Surface Mounted		
Accessories	Power supply, all applicable installation accessories		
<b>Lamp information:</b>		<b>Notes:</b>	
Specification	1x4W		
Lamp Key	LED		
Lumen output/Lamp	NA		
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			

Project	My City Center, Abu Dhabi		Type	EX
Project No.	15-7364-0000	Stage:	Final Design	

**Description**

Exit Lights - Recessed Ceiling

**Location:** General Areas



<b>Luminaire information:</b>			
Manufacturer (Design based on)	Inotec	Model	SNP 1018.2 E LED J/SV
Alternative Manufacturer	CEAG, Teknoware ,JSB	Protection Class	IP20
Colour	Grey	Controlgear	Electronic
Housing	Aluminum	Dimming	None
Reflector	None	Luminaire Lumen Output	NA
Diffuser	None	Design Load (watts)	2
Mounting	Recessed Mounted		
Accessories	Power supply, all applicable installation accessories		
<b>Lamp information:</b>		<b>Notes:</b>	
Specification	18x0.1W		
Lamp Key	LED		
Lumen output/Lamp	NA		
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			



Project	My City Center, Abu Dhabi	Type	<b>EXIT</b>
Project No.	15-7364-0000	Stage:	

**Description**

Exit Lights - Surface Ceiling

**Location:** Normal Areas



**Luminaire information:**

Manufacturer (Design based on)	Inotec	Model	SNP 2618 LED
Alternative Manufacturer	CEAG, Teknoware, JSB	Protection Class	IP65
Colour	White	Controlgear	Electronic
Housing	Polycarbonate White	Dimming	None
Reflector	NA	Luminaire Lumen Output	NA
Diffuser	NA	Design Load (watts)	4.2
Mounting	Recessed/Ceiling Mounted		
Accessories	Power supply, all applicable installation accessories		

**Lamp information:** **Notes:**


Specification	1x4W	
Lamp Key	LED	
Lumen output/Lamp	NA	
Lamp Life (hours)	50,000	
Colour Temp	3000K	
Lamp Base		

Project	My City Center, Abu Dhabi	Type	WL1
Project No.	15-7364-0000	Stage:	

### Description

Wall Mounted Lights

Location: Stairs/lift shaft



### Luminaire information:

Manufacturer (Design based on)	Thorn	Model	DA 1200 LED HF E3 OP RD WHI L840
Alternative Manufacturer	Thorlux, Sylvania, Concord	Protection Class	IP 65
Colour	Grey, white	Controlgear	Integral LED Driver
Housing	Die Cast Aluminium Base, white bezel	Dimming	None
Reflector	None	Luminaire Lumen Output	1600lm
Diffuser	Opal Polycarbonate	Design Load (watts)	20 W
Mounting	Wall Mounted		
Accessories	All applicable installation and mounting accessories		

### Lamp information: Notes:

Specification	16 W LED	Mounting height to be 2.8 m above FFL
Lamp Key	LED	
Lumen output/Lamp	1600lm	
Lamp Life (hours)	50000	
Colour Temp	3000K	
Lamp Base		



Project	My City Center, Abu Dhabi	Type No.	WL2
Project No.	15-7364-0000		

### Description

Wall Mounted Lights

Location: Parking Areas, External circulation areas

**Insert Picture**



Luminare information:			
Manufacturer (Design based on)	iGuzzini	Model	iTeka BV15
Alternative Manufacturer	Thorn, Philips, Ligman	Protection Class	IP66
Colour	Grey	Controlgear	Integral Electronic
Housing	Corrosion resistant Aluminium	Dimming	None
Reflector	Individual LED Lens, asymmetrical Optics	Luminaire Lumen Output	1800 lm
Diffuser	Cleared Safety Glass	Design Load (watts)	23 W
Mounting	Wall Mounted	Cut-Off Angle	
Accessories	All applicable installation accessories		
Lamp information:		Notes:	
Specification	23W LED	Mounting height to be 2.4 m above FFL	
Lamp Key	LED		
Lumen output/Lamp	1800 lm		
Lamp Life (hours)	50,000		
Colour Temp	3000K		
Lamp Base			