

Building connections that last™



Gruvlok® Mechanical Piping



BUILDING CONNECTIONS THAT LAST



For over 160 years, Anvil has worked diligently to build a strong, vibrant tradition of making connections — pipe to pipe and people to people.



We pride ourselves in providing the finest-quality pipe products and services with integrity and dedication to superior customer service at all levels.

We provide expertise and product solutions for a wide range of applications, from plumbing, mechanical, HVAC, industrial and fire protection to mining, oil and gas. Our comprehensive line of products includes: grooved pipe couplings, grooved and plain-end fittings, valves, cast and malleable iron fittings, forged steel fittings, steel pipe nipples and couplings, pipe hangers and supports, channel and strut fittings, mining and oil field fittings, along with much more.



As an additional benefit to our customers, Anvil offers a complete and comprehensive Design Services Analysis for mechanical equipment rooms, to help you determine the most effective and cost-efficient piping solutions.

At Anvil, we believe that responsive and accessible customer support is what makes the difference between simply delivering products — and delivering solutions.



Mechanical Piping Products

Durable. Flexible. Safe. Easy to install. Easy to maintain. That's Anvil's Gruvlok® product line. Gruvlok gives your building the toughest, simplest, and most adaptable piping system possible.

Through a combination of roll-grooving and two-bolt coupling design, this innovative product line joins piping and other components into a single rugged yet flexible system. This makes Gruvlok products ideal for a variety of applications — particularly in tight spaces such as subfloors, UFAD systems, crawlspaces, trenches, and tunnels.

Gruvlok products eliminate the need for traditional expansion joints, allowing your system to expand and contract with your needs. With a Gruvlok union at every joint, you have the freedom to make on-site tweaks without altering the overall design of your system.

Maintenance is as simple and flexible as installation. Every component in a Gruvlok system is easily replaceable and easily accessed, so that you can make repairs without resorting to a total shut-down.

3-D CAD Library



Anvil's Gruvlok product line is now available in 3-D CAD Models, as well as the standard 2-D drawings, at www.anvilintl.com. Anvil also offers downloadable Master Format 3 Part Specifications.



Building Green with Anvil

Anvil manufactures an extensive line of products composed of 90% recycled materials, visit www.anvilintl.com for current certificates related to recycled material. Anvil is a member of the United States Green Building Council.

Products include:

- Gruvlok® Couplings, Fittings, and Flanges
- Anvil® Cast and Malleable Threaded Fittings
- Anvil Cast Iron Flanged Fittings
- Anvil Pipe Hangers and Supports
- Merit® Tee-Lets and Drop Nipples
- Beck Welded Pipe Nipples

TABLE OF CONTENTS

INTRODUCTION

Gruvlok® Pictorial Parts Index.....	7-14
Agency Approvals.....	15
Gruvlok – The Engineered Coupling.....	16
The Gruvlok Piping Method.....	17
Gruvlok Couplings for Grooved-End Pipe.....	18
Coupling Data Chart Notes.....	19

COUPLINGS FOR GROOVED-END PIPE

Fig. 7401 Rigidlok® Coupling.....	20-21
Fig. 7401-2 Rigidlok® Coupling.....	22
Fig. 74 SlideLOK® Ready for Installation Coupling....	23-24
Fig. 7001 Flexible Coupling.....	25-26
Fig. 7001-2 Flexible Coupling.....	27
Fig. 7011 Standard Coupling.....	28-29
Fig. 7022 Weld Ring Gruv-Ring Coupling	30-33
Fig. 7000 Lightweight Flexible Coupling	34-35
Fig. 7400 Rigidlite® Coupling	36-37
Fig. 7003 Hingelok® Coupling.....	38-39
Fig. 7010 Reducing Coupling	40-41
Fig. 7788 Gruvlok Flange Adapter	42
Fig. 7012 Gruvlok Flange	43-45
Fig. 7013 Gruvlok Flange.....	46-48
Flanged Seal Rings.....	49
Fig. 7240 Expansion Joint	50-51

BRANCH OUTLETS

Fig. 7042 Outlet Coupling	52-53
Fig. 7045 Clamp-T, FPT Branch.....	54-56
Fig. 7046 Clamp-T, Grooved Branch.....	57-58
Fig. 7047, Fig. 7048 & Fig. 7049 Clamp-T, Cross... ..	59
Fig. 7043 Branch Outlet.....	60

FITTINGS FOR GROOVED-END PIPE

Technical Data	61
Fig. 7050 90° Elbow	62
Fig. 7051 45° Elbow	62
Fig. 7052 22 $\frac{1}{2}$ ° Elbow	62
Fig. 7053 11 $\frac{1}{4}$ ° Elbow	63
Fig. 7050LR 90° Long Radius Elbow	63
Fig. 7051LR 45° Long Radius Elbow	63
Fig. 7060 Tee	64
Fig. 7061 Reducing Tee Standard	64
Fig. 7063 Tee with Threaded Branch	65
Fig. 7064 Reducing Tee with Threaded Branch	65
Fig. 7076 Gr x Thd Concentric Reducer.....	66
Fig. 7073 & Fig. 7097 Eccentric Reducer	66
Fig. 7077, Fig. 7078 & Fig. 7079 Swaged Nipple.....	67

Fig. 7072 Gr x Gr Concentric Reducer.....67

Fig. 7069 45° Lateral.....68

Fig. 7070 45° Reducing Lateral

Fig. 7066 Tee Wye.....69

Fig. 7067 Reducing Tee Wye.....69

Fig. 7071 True Wye

Fig. 7087 Gr x FPT Female Thread Adapter

Fig. 7055 Gr x MPT 90° Adapter Elbow

Fig. 7056 Gr x MPT 45° Adapter Elbow

Fig. 7050RF Grooved x 150# Flanged (GxF)

Fig. 7072GF Gr x Flange Concentric Reducer.....71

Fig. 7084 Groove x Class 150 Flange Nipple

Fig. 7085 Groove x Class 300 Flange Nipple

Fig. 7074 Cap

Fig. 7075 Bull Plug

Fig. 7068 Cross

Fig. 7086 Gr x Hose Nipple

Fig. 7080 Gr x Gr Adapter Nipple

Fig. 7081 Gr x MPT Adapter Nipple

Fig. 7082 Gr x Bev Adapter Nipple

Fig. 7062 Bullhead Tee Specialty Tee (Gr x Gr x FPT)

Fig. 7065 Standpipe Tee (Gr x Gr x FPT)

Fig. 7050DR 90° Drain Elbow

Fig. 7450 90° Short Pattern Elbow.....75

Fig. 7460 Short Pattern Tee

FIG. 7050-3D LONG RADIUS ELBOWS

Fig. 7050-3D 90° Elbow.....76

Fig. 7057-3D 60° Elbow

Fig. 7051-3D 45° Elbow

Fig. 7058-3D 30° Elbow

Fig. 7052-3D 22 $\frac{1}{2}$ ° Elbow

Fig. 7053-3D 11 $\frac{1}{4}$ ° Elbow

FIG. 7050-5D LONG RADIUS ELBOWS

Fig. 7050-5D 90° Elbow.....77

Fig. 7057-5D 60° Elbow

Fig. 7051-5D 45° Elbow

Fig. 7058-5D 30° Elbow

Fig. 7052-5D 22 $\frac{1}{2}$ ° Elbow

Fig. 7053-5D 11 $\frac{1}{4}$ ° Elbow

FIG. 7050-6D LONG RADIUS ELBOWS

Fig. 7050-6D 90° Elbow.....78

Fig. 7057-6D 60° Elbow

Fig. 7051-6D 45° Elbow

Fig. 7058-6D 30° Elbow

Fig. 7052-6D 22 $\frac{1}{2}$ ° Elbow

Fig. 7053-6D 11 $\frac{1}{4}$ ° Elbow

VALVES & ACCESSORIES

Series 7700 Butterfly Valve.....79-83

Series 7600 Butterfly Valve.....84

Series 8000GR Butterfly Valve.....85-87

Fig. 70G Butterfly Valve

Model B333 Large Diameter Butterfly Valve
with Gear Operator.....90-91

Model B8101 Low Profile Butterfly Valve.....92

Model 8200L PVC Butterfly Valve.....93

Fig. 2000BV-FP Carbon Steel Ball Valve.....94

Fig. 2000BV-RP Carbon Steel Ball Valve

Series 161N LF Low Lead Brass Ball Valve.....96

Series 1615 LF Low Lead Brass Ball Valve.....96

Series 7500 Ball Valve.....97-98

Model BV835 Grooved End Ball Valve with
Lever Handle and Gear Operator

Fig. 90G Check Valve.....101-102

Fig. 400G Grooved-End Silent Check Valve

Series 7800 Check Valve

Fig. CV890 Dual Disc Check Valve

ABV-9900V Series – Straight DZR Brass
Automatic Balancing Valve.....109-111

MBV-9510 Series – Fixed Orifice Double
Regulating Valve.....112-115

MBV-9510AB Series – Fixed Orifice Double
Regulating Low Lead Valve.....116-119

CSV-9520AB Series – DZR Brass On/Off
Terminal Low Lead Balancing Valves.....120-124

Standard Coil Hook-up Kit Configurations

Fig. Anvil 92ST – DZR Brass Ball Valve
with Strainer

Fig. Anvil 92BPC – DZR Brass Ball Valve
with Bypass

Fig. Anvil 991BV – Ball Valve with Nut
for 9900V Series Valves

Fig. Anvil 92UN – DZR Brass Union Body with
Air Vent and Test Point

Fig. Anvil 92HS – Stainless Steel Braided Hose ..

Series GBV-A, GBV-F & GBV-G
Balancing Valves

Model CB800 Circuit Balancing Valves -
Grooved Ends

Model CB800 Circuit Balancing Valves -
Flanged Ends

Model FTV-S & FTV-A Tri-Service Valves ...

Fig. 7260 Tee Strainer

Model 758G Grooved-End "Wye" Strainer

Model 768G Grooved-End "Wye" Strainer

Fig. 7250 Suction Diffuser

Fig. S810 Suction Diffuser

Model GAV-15 Automatic Air Vent

TABLE OF CONTENTS

Model GAV-30 Automatic Air Vent 152

ANVILFLEX® FLEX CONNECTORS

Technical Data 153

Fig. AF-21-GG Grooved Ends Connector 153

Fig. AF-21-GF Gr x Class 150
Flanged Flex Connector 154Fig. AF-21-FF Class 150 Flanged x Class 150
Flanged Flex Connector 154Fig. AF-21-RFF Class 150 Flanged x Class 150
Flanged Reducing Flex Connector 155Fig. AF-21-RGF Gr x Class 150
Flanged Reducing Flex Connector 156

HIGH PRESSURE SYSTEMS

HIGH PRESSURE COUPLINGS

Fig. 7004 Coupling 158-159

Fig. 7004EG High Pressure Coupling 160-161

Fig. 770 Rigid Coupling 162-163

Fig. 7377 Double Groove Coupling 164

HIGH PRESSURE FITTINGS

Fig. 7050EG High Pressure 90° LR Elbow 165

Fig. 7051EG High Pressure 45° LR Elbow 165

Fig. 7060EG High Pressure Tee 166

Fig. 7662EG High Pressure Header Tee 166

Fig. 7068EG High Pressure Cross 166

GRUVLOK® CTS COPPER SYSTEM

CTS COPPER SYSTEM COUPLINGS

Technical Data 167, 177

Fig. 64 CTS SlideLOK Rigid Coupling 168-169

Fig. 6400 Rigid Coupling 170

Fig. 616 Reducing Coupling for Joining
Copper Tubing Systems 171-172Fig. 617 Transition Coupling for Joining
IPS to Copper Tubing Systems 173

CTS COPPER SYSTEM FITTINGS

Fig. 6050 90° Elbow 174

Fig. 6051 45° Elbow 174

Fig. 6060 Tee 174

Fig. 6074 End Caps 174

Fig. 6061 (Gr x Gr x Gr) Reducing Tee 175

Fig. 6064 (Gr x Gr x Cup) Reducing Tee 175

Fig. 6072 (Gr x Gr) Concentric Reducer 176

Fig. 6075 (Gr x Cup) Reducing Adapter 176

Fig. 6084 Flange Adapter 176

Fig. 610 90° CTS Elbow 178

Fig. 601 45° CTS Elbow 178

Fig. 619 CTS Tee 178

Fig. 660 CTS Cap 178

Fig. 621 (Gr x Gr x Gr) CTS Reducing Tee 179

Fig. 618 (Gr x Gr x Cup) CTS Reducing Tee 179

Fig. 650 (Gr x Gr) CTS Concentric Reducer 180

Fig. 652 (Gr x Cup) CTS Concentric Reducer 180

CTS COPPER SYSTEM VALVE

Series 6700 CTS Copper Butterfly Valve 181-182

DI-ELECTRIC PIPE NIPPLES

Fig. 7088 - Thread x Groove 183

Fig. 7089 - Groove x Groove 183

Fig. 7090 - Thread x Thread 183

Fig. 7091 - CTS Groove by IPS Groove 184

GRUVLOK PLAIN END FITTINGS

PLAIN-END COUPLINGS

Fig. 7005 Roughneck® Coupling 185

PLAIN-END FITTINGS

Technical Data 186

Fig. 7050P 90° Elbow 186

Fig. 7051P 45° Elbow 186

Fig. 7060P Tee 186

Fig. 7068P Cross 187

Fig. 7061P Reducing Tee 187

Fig. 7069P 45° Lateral 187

Fig. 7071P 90° True Wye 187

Fig. 7050LRP 90° LR Elbow 187

Fig. 7051LRP 45° LR Elbow 188

Fig. 7084P & Fig. 7085P (Plain-End x Class 150
or 300) Flange Nipple 188

Fig. 7075P Bull Plug 188

ADAPTER NIPPLES

Fig. 7080P Plain x Grooved 189

Fig. 7081P Plain x Thread 189

Fig. 7082P Plain x Bevel 189

Fig. 7077P Swaged Nipple 189

HDPE COUPLINGS

Fig. 7305 HDPE Coupling 190-191

Fig. 7307 HDPE Transition Coupling 192-193

Fig. 7312 HDPE Flange Adapter 194-195

SOCK-IT® PIPING METHOD FITTINGS

Technical Data 196

Fig. 7100 90° Elbow 196

Fig. 7101 90° Reducing Elbow 197

Fig. 7103 Straight Tee 197

Fig. 7107 Coupling 197

Fig. 7105 Reducing Outlet Tee 198

Fig. 7106 Reducing Tee 198

STAINLESS STEEL METHOD

STAINLESS STEEL COUPLINGS

Fig. 7400SS Rigidlite® Coupling 199

Fig. 472 Stainless Steel Rigid Coupling 200-201

Fig. 405 Stainless Steel Flexible Coupling 202-203

STAINLESS STEEL FITTINGS

Technical Data 204

Fig. A7050SS 90° Stainless Steel Elbow 205

Fig. A7051SS 45° Stainless Steel Elbow 205

Fig. A7060SS Stainless Steel Tee 205

Fig. A7061SS Stainless Steel Reducing Tee 206

Fig. A7074SS Stainless Steel Caps 207

Fig. A7084SS Stainless Steel Flange Adapter
(Groove x Class 150) 207Fig. A7072SS Stainless Steel Concentric
Reducer 208Fig. A7073SS Stainless Steel Eccentric
Reducer 209

STAINLESS STEEL VALVES

Model B480 Grooved End Stainless Steel
Butterfly Valve with Lever Handle 210-211Model BV435 Grooved End Stainless Steel
Ball Valve with Lever Handle 212

STAINLESS STEEL G-PRESS SYSTEM

Technical Data 213-216

Fig. 407 Straight Coupling (Press x Press) 217

Fig. 408 Slip Coupling (Press x Press) 217

Fig. 468 90° Elbow (Press x Press) 217

Fig. 467 90° Elbow (Male x Female) 218

Fig. 471 45° Elbow (Press x Press) 218

Fig. 470 45° Elbow (Male x Female) 218

Fig. 484 End Cap (Female Press) 219

Fig. 442 Equal Tees (Press x Press x Press) 219

Fig. 473 Reducing Tees (Press x Press x Press) 220

Fig. 478 Tee and Reducing Tee Adapters (Press x
Press x Female NPT) 221

Fig. 474 Reducer (Female Press x Male Press) 222

Fig. 476 Straight Connector (Female Press x
Male NPT) 222Fig. 479 Straight Connector (Female Press x
Female NPT) 223

Fig. 485 3-Piece Union (Press x Press) 223

Fig. 466 Van Stone Flange Adapter (Female
Press x ANSI 125/150 Flange) 224Fig. 477 Transition Nipple Grooved (Groove x
Male Press) 224

Fig. 475 Flange Adapters 225

Fig. 461 Weld Adapter (Male Weld x
Female Press) 225

Fig. 469 Ball Valve (Press x Press) 226

TABLE OF CONTENTS

ROLL GROOVERS

Model 1007 & 3007 Roll Groovers	227-228
Model 3006 Roll Groover	229-230

COUPLING INSTALLATION & ASSEMBLY

Specified Bolt Torque	232
Fig. 7401 Rigidlok® Coupling	233
Fig. 74 SlideLOK® Ready for Installation Coupling	234-235
Fig. 7001 Flexible Coupling	236
Fig. 7001-2 & Fig. 7401-2 Two-Piece Large Diameter Couplings	237
Fig. 7011 Standard Coupling	238
Fig. 7000 Lightweight Flexible Coupling	239
Fig. 7400 Rigidlite® Coupling	240
Fig. 64 CTS SlideLOK Rigid Coupling	241-242
Fig. 6400 Rigid Coupling	243
Fig. 616 Reducing Coupling for Joining Copper Tubing Systems	244
Fig. 617 Transition Coupling for Joining IPS to Copper Tubing Systems	245
Fig. 7003 Hingelok® Coupling	246
Fig. 7010 Reducing Coupling	247
Fig. 7012 Gruvlok Flange (2"-12")	248-249
Fig. 7012 Gruvlok Flange (14"-24")	250
Fig. 7042 Outlet Coupling	251
Fig. 7045 & Fig. 7046 Clamp-T® Branch Outlets	252
Fig. 7043 Branch Outlet	253
Fig. 7005 Roughneck® Coupling	254
Fig. 7004 High Pressure Coupling	255
Fig. 7004EG High Pressure Coupling	256
Fig. 7377 Double Groove Coupling	257
Fig. 7305 HDPE Coupling	258
Fig. 7307 HDPE Transition Coupling	259
Fig. 7312 HDPE Flange Adapter	260
Gruvlok Sock-It® Fitting	261
Stainless Steel G-Press System	262
Model FTV Tri-Service Valve	263-265
Model CB800 Circuit Balancing Valves	266
AnvilFlex® Flex Connectors	267

SPECIAL COATINGS

Anvil Special Coatings	268
------------------------------	-----

DESIGN SERVICES

Basic & Extended Services	269
Drawing Examples	270
Geometric Challenges & Gruvlok Training	271

TECHNICAL DATA

Table of Contents	272
Gruvlok® Lubricants	273
Specified Bolt Torque & Design Factors	274
Gruvlok Flow Control Components	275
Gruvlok Gasket Styles	276
Gasket Grade Index	277
Gruvlok Gasket Recommendations	277-279
Movement-Applications	280-281
Coupling Working Pressure Rating on Light Wall Roll Grooved Steel Pipe	282
Coupling Working Pressure Rating on Roll Grooved ISO Steel Pipe	283
Coupling & Flange Working Pressure Rating on 304 & 316 Stainless Steel Roll Grooved Pipe	284
Coupling & Flange Working Pressure Rating on Aluminum Pipe	285
Pipe Support	286-288
Coupling Flexibility	289-290
Drafting Symbols for Gruvlok Piping Systems	291
Pipe Preparation	292-293
Roll Groove Specifications	294
Cut Groove Specifications	295
Cut Groove End Guard® Specification	296
Roll Groove End Guard® Specification	296
Double Cut Groove Specification	297
Gruvlok CTS Copper System	
Roll Groove Specification	298
Master Format 3 Part Specification	299

PICTORIAL INDEX

Pipe Fitting Products	300-309
Pipe Hanger Products	310-316
Anvil-Strut™ Products	317-323

INDEX

Numeric Index	324-325
---------------------	---------

TERMS & CONDITIONS

Product Terms & Conditions	326
----------------------------------	-----

CROSS REFERENCE

Gruvlok Product Cross Reference	327
---------------------------------------	-----

GRUVLOK® PICTORIAL PARTS INDEX

COUPLINGS

Fig. 7401 Pages 20-21


Rigidlok® Coupling



Size Range: 1½" - 14"



Size Range: 16"




Size Range: 18" - 24"

Fig. 7401-2 Page 22


Rigidlok® Coupling

Size Range: 14" - 24"

**Fig. 74** Pages 23-24

SlideLOK® Ready for Installation Coupling


Size Range: 2" - 8"

**Fig. 7001** Pages 25-26


Flexible Coupling



Size Range: 1" - 14"



Size Range: 16" - 24"




Size Range: 28" - 30 I.D."

Fig. 7001-2 Page 27






Flexible Coupling

Size Range: 14" - 24"

**Fig. 7011** Pages 28-29

Standard Coupling


Size 30 O.D."

**Fig. 7022** Pages 30-33Weld Ring Gruv-Ring Coupling
Size Range: 30" - 60"**Fig. 7000** Pages 34-35Lightweight Flexible Coupling
Size Range: 1" - 8"**Fig. 7400** Pages 36-37300 PSI Rigidlite® Coupling
Size Range: 1" - 8"**Fig. 7003** Pages 38-39Hingelok® Coupling
Size Range: 1" - 4" and 5" - 8"**Fig. 7010** Pages 40-41Reducing Coupling
Size Range: 2" x 1½" thru 8"x 6"**Fig. 7788** Page 42Gruvlok Flange Adapter
Size Range: 2" - 12"**Fig. 7012** Pages 43-45




Gruvlok Flanges



Size Range: 2" - 12"



Size Range: 14" - 24"

Fig. 7013 Pages 46-48Gruvlok Flanges (#300 Flange)
Size Range: 2" - 12"**Flanged Seal Rings** Page 49Flange Adapter Inserts for use
with Fig. 7012/7013 Flanges
Size Range: 2" - 24"**Fig. 7240** Pages 50-51Expansion Joint
Size Range: 2" - 12"

BRANCH OUTLETS

Fig. 7042 Pages 52-53

Outlet Coupling
Size Range: 1½" - 6"




Fig. 7042F
Female IPS Outlet




Fig. 7042M
Male IPS Outlet





Fig. 7042G
Grooved Outlet

Fig. 7045 Pages 54-56

Clamp-T, FPT Branch
Size Range: 3" x 1¼" thru
8" x 4"



(U-Bolt)
Size Range: 2½" x ½" thru
4" x 1"



Branch Outlet
Size Range: 1¼" x ½" thru
2½" x 1"

Fig. 7046 Pages 57-58

Clamp-T, Grooved Branch
Size Range: 3" x 1¼" thru
8" x 4"



(U-Bolt)
Size Range: 2½" x 1¼" thru
2½" x 1½"



Fig. 7047, Fig. 7048 & Fig. 7049 Page 59

Clamp-T Cross
Size Range: 2" x ½" thru 8" x 4"



Fig. 7047
Thread x Thread



Fig. 7048
Groove x Groove



Fig. 7049
Groove x Thread

GROOVED FITTINGS

Fig. 7050 Page 62

90° Elbow
Size Range: 1" - 24"




Fig. 7051 Page 62

45° Elbow
Size Range: 1" - 24"



Fig. 7052 Page 62

22½° Elbow
Size Range: 1" - 24"



Fig. 7053 Page 63

11¼° Elbow
Size Range: 1" - 24"



Fig. 7050LR Page 63

90° Long Radius Elbow
Size Range: 1" - 24"



Fig. 7051LR Page 63

45° Long Radius Elbow
Size Range: 1" - 24"



Fig. 7060 Page 64

Tee
Size Range: 1" - 24"




Fig. 7061 Page 64

Reducing Tee Standard
Size Range: 1¼" x 1¼" x 1"
thru 24" x 24" x 20"




Fig. 7063 Page 65

Tee with Threaded Branch
Size Range: 1" - 12"




Fig. 7064 Page 65

Reducing Tee with
Threaded Branch
Size Range: 2" x 2" x ¾"
thru 24" x 24" x 12"




Fig. 7073 & Fig. 7097 Page 66

Eccentric Reducers
Size Range: 1¼" x 1" thru 24" x 20"




Fig. 7073
Groove x Groove




Fig. 7097
Groove x Thread

Fig. 7076 Page 66

Gr x Thd Concentric Reducer
Size Range: 1½" x 1" thru
6" x 4"



Fig. 7077, 7078 & 7079 Page 67

Swaged Nipples
Size Range: 2" x 1" thru 6" x 5"



Fig. 7077
Groove x Groove

Fig. 7078
Groove x Thread

Fig. 7079
Groove x Bevel

Fig. 7072 Page 67

Gr x Gr Concentric Reducer
Size Range: 1¼" x 1" thru
24" x 20"



Fig. 7070 Page 68

45° Reducing Lateral
Size Range: 3" x 3" x 2"
thru 24" x 24" x 20"




Fig. 7069 Page 68

45° Lateral
Size Range: 1" - 24"



Fig. 7071 Page 69

True Wye
Size Range: 1" - 24"




Fig. 7066 Page 69

Tee Wye
Size Range: 2" x 2" x 2"
thru 12" x 12" x 12"




Fig. 7067 Page 69

Reducing Tee Wye
Size Range: 4" x 3" x 3"
thru 8" x 6" x 8"




Fig. 7087 Page 70

Female Thread Adapter
Size Range: 1" - 4"



Fig. 7055 Page 70

90° Adapter Elbow
Size Range: 1" - 6"




Fig. 7056 Page 70

45° Adapter Elbow
Size Range: 1" - 6"




GROOVED FITTINGS

Fig. 7050RF Page 70


Reducing Base Support Elbow
Groove x 150# Flange (GxF)
Size Range: 5" x 4" thru 12" x 10"

**Fig. 7072GF** Page 71


Gr x Flange Concentric Reducer
Size Range: 3" x 2" thru 8" x 6"

**Fig. 7084** Page 71

Groove x Class 150 Flange Nipple
Size Range: 1" - 24"

**Fig. 7085** Page 71

Groove x Class 300 Flange Nipple
Size Range: 1" - 24"

**Fig. 7074** Page 72


Cap
Size Range: 1" - 24"

**Fig. 7075** Page 72

Bull Plug
Size Range: 2" - 6"

**Fig. 7068** Page 72

Cross
Size Range: 1" - 24"

**Fig. 7086** Page 73

Groove x Hose Nipple
Size Range: 1" - 12"

**Fig. 7065** Page 74

Standpipe Tee (Gr x Gr x FPT)
Size Range: 4" x 4" x 2½" thru 6" x 6" x 2½"

**Fig. 7062** Page 74

Bulthead Tee Specialty Tees
(Gr x Gr x FPT)
Size Range: 5" x 5" x 8" thru 6" x 6" x 8"

**Fig. 7050DR** Page 74

90° Drain Elbow
Size Range: 1¼" - 12"


**Fig. 7080,
Fig. 7081 &
Fig. 7082** Page 73




Nipples
Size Range: ¾" - 12"

Fig. 7080
Groove x GrooveFig. 7081
Groove x MPTFig. 7082
Groove x Bevel**Fig. 7450** Page 75




90° Short Pattern Elbow
Size Range: 2" - 8"

**Fig. 7050-3D** Page 76


Long Radius Elbows
Size Range: 2" - 24"

Fig. 7050-3D
90° ElbowFig. 7057-3D
60° ElbowFig. 7051-3D
45° ElbowFig. 7058-3D
30° ElbowFig. 7052-3D
22½° ElbowFig. 7053-3D
11¼° Elbow**Fig. 7050-5D** Page 77

Long Radius Elbows
Size Range: 2" - 24"

Fig. 7050-5D
90° ElbowFig. 7057-5D
60° ElbowFig. 7051-5D
45° ElbowFig. 7058-5D
30° ElbowFig. 7052-5D
22½° ElbowFig. 7053-5D
11¼° Elbow**Fig. 7050-6D** Page 78

Long Radius Elbows
Size Range: 2" - 24"

Fig. 7050-6D
90° ElbowFig. 7057-6D
60° ElbowFig. 7051-6D
45° ElbowFig. 7058-6D
30° ElbowFig. 7052-6D
22½° ElbowFig. 7053-6D
11¼° Elbow**Fig. 7460** Page 75

Short Pattern Tee
Size Range: 2" - 8"

**Fig. 7450** Page 75


90° Short Pattern Elbow
Size Range: 2" - 8"




VALVES & ACCESSORIES

Series 7700 Pages 79-83

Butterfly Valve
Size Range: 2" - 12"




AN-7722-3
Series 7700 Butterfly Valve
with Gear Operator




AN-7721-3
Series 7700 Butterfly Valve
with 10 Position Lever Lock

Series 7600 Page 84


Butterfly Valve
Size Range: 2" - 6"


Series 8000GR


Pages 85-87
Butterfly Valve
Size Range: 14" - 24"


Fig. 70G Pages 88-89


Butterfly Valve
Size Range: 2" - 6"


Model B333

Pages 90-91
Butterfly Valve
Size Range: 14" - 24"



Model B8101 Page 92

Low Profile Butterfly Valve
Size Range: 2" - 6"


Model B8200L


Page 93

PVC Butterfly Valve
Size Range: 2" - 8"


Fig. 2000BV-FP


Page 94

Full Port Ball Valve
Size Range: 1/4" - 2"



Fig. 2000BV-RP

Page 95

Reduced Port Ball Valve
Size Range: 1/4" - 2"



Series 161N LF & 1615 LF

Page 96
Low Lead Brass Ball Valve
161N LF – Size Range: 1/4" - 4"
1615 LF – Size Range: 1/2" - 3"




Series 7500

Page 97-98


Ball Valve
Size Range: 2" - 6"


Model BV835 Pages 99-100


Grooved End Ball Valve with Lever or Gear Operator
Size Range: 2" - 6"


Fig. 90G Page 101-102

Check Valve
Size Range: 2" - 4"



Fig. 400G Page 103

Grooved-End
Silent Check Valve
Size Range: 2" - 10"


Series 7800

Page 104-106

Check Valve for use in
Grooved-End Piping Systems
Size Range: 2" - 12"


Fig. CV890


Pages 107-108

Dual Disc Check Valve
Size Range: 14" - 24"


ABV-9900V Series

Pages 109-111

Straight DZR Brass
Automatic Balancing Valve
Solder (ABV-S-9909)
Threaded (ABV-T-9907)
Size Range: 1/2" - 2 1/2"


MBV-9510 Series

Pages 112-115

Fixed Orifice Double
Regulating Valve
Solder (MBV-S-9519)
Threaded (MBV-T-9517)
Size Range: 1/2" - 2"


MBV-9510AB Series


Pages 116-119

Fixed Orifice Double
Regulating Low Lead Valve
Solder (MBV-S-9519AB)
Threaded (MBV-T-9517AB)
Size Range: 1/2" - 2"


CSV-9520AB Series


Pages 120-124

DZR Brass On/Off Terminal
Low Lead Balancing Valve
Solder (CSV-S-9529AB)
Threaded (CSV-T-9527AB)
Size Range: 1/2" - 1"


Fig. Anvil 92ST


Pages 126-127

DZR Brass Ball Valve
with Strainer
Size Range: 1/2" - 2"


Fig. Anvil 92BPC


Pages 128-129

DZR Brass Ball Valve
with Bypass
Size Range: 1/2" - 2"


Fig. Anvil 99IBV


Pages 130-131

Ball Valve with Nut for
9900V Series Valves
Size Range: 1/2" - 2 1/2"


Fig. Anvil 92UN


Pages 132-133

DZR Brass Union Body
with Air Vent and Test Point
Size Range: 1/2" - 2"


Fig. Anvil 92HS


Page 134

Stainless Steel Braided Hose
Size Range: 1/2" - 2"




GBV-A & GBV-G

Pages 135-136

Balancing Valve
Ductile Iron, Grooved-End
Straight or Angle
Size Range: 2 1/2" - 12"


Model CB800 Pages 137-140


Circuit Balancing Valve, Grooved-End or Flanged End
Size Range: 2 1/2" - 12"




VALVES & ACCESSORIES

FTV-S Pages 141-142


Tri-Service Valve (Straight)
Size Range: 2½" - 12"

**FTV-A** Pages 141-142

Tri-Service Valve
(Angle Body)
Size Range: 2½" - 12"

**Fig. 7260** Pages 143-144


Gruvlok Tee Strainer
Size Range: 2" - 18"

**Model 758G** Page 145


Grooved-End
"Wye" Strainer
Size Range: 2" - 12"

**Model 768G** Page 146

Grooved-End
"Wye" Strainer
Size Range: 2" - 12"


**Fig. 7250** Pages 147-148

Suction Diffuser
Size Range: 2½" x 2½"
thru 16" x 14"

**Fig. S810**


Pages 149-150

Suction Diffuser
Size Range: 2" x 2" - 16" x 14"

**Model GAV-15**

Page 151

Automatic Air Vent
for Ultimate Performance
Size Range: ½" - 1"

**Model GAV-30**

Page 152

Automatic Air Vent
for Ultimate Performance
Size Range: ½" - ¾"



AnvilFlex® AF-21 Series Pages 153-156

Flex Connectors
Size Range: 2" - 12"



Fig. AF-21-GG
Grooved Ends



Fig. AF-21-GF
Grooved x Class 150 Flanged



Fig. AF-21-FF
Class 150 Flanged x
Class 150 Flanged




Fig. AF-21-RFF
Reducing Class 150 Flanged x
Class 150 Flanged




Fig. AF-21-RGF
Reducing Grooved x
Class 150 Flanged


HIGH PRESSURE SYSTEMS

Fig. 7004 Pages 158-159


Coupling
Size Range: 2" - 12"

**Fig. 7004EG** Pages 160-161


High Pressure Coupling with EG Gasket
Size Range: 2" - 12"

**Fig. 770** Pages 162-163


Rigid Coupling
Size Range: 2" - 12"

**Fig. 7377** Page 164

Double Groove Coupling
Size Range: 6" - 10"

**Fig. 7050 EG** Page 165


High Pressure 90° LR Elbow
Size Range: 2" - 12"

**Fig. 7051 EG** Page 165


High Pressure 45° LR Elbow
Size Range: 2" - 12"

**Fig. 7662 EG** Page 166


High Pressure Header Tee
Size: 2"

**Fig. 7060 EG** Page 166

High Pressure Tee
Size Range: 2" - 12"

**Fig. 7068 EG** Page 166

High Pressure Cross
Size Range: 2" - 12"



CTS COPPER SYSTEM

Fig. 64 Page 168-169

CTS SlideLOK® Ready for Installation Coupling
Size Range: 2" - 8"




Fig. 6400 Page 170

Rigid Coupling
Size Range: 2" - 8"




Fig. 6050 Page 174

90° Elbow
Size Range: 2" - 8"



Fig. 6051 Page 174

45° Elbow
Size Range: 2" - 8"



Fig. 6060 Page 174

Tee
Size Range: 2" - 8"




Fig. 6072 Page 176

Concentric Reducer (Gr x Gr)
Size Range: 2 1/2" x 2" - 8" x 6"



Fig. 6075 Page 176

Reducing Adapter (Gr x Cup)
Size Range: 2" x 1" - 4" x 2"




Fig. 6084 Page 176

Flange Adapter
Size Range: 2" - 6"




Fig. 619 Page 178

CTS Tee
Size Range: 2" - 8"




Fig. 621 Page 179

CTS Reducing Tee
(Gr x Gr x Gr)
Size Range: 2" - 8"




Fig. 618 Page 179

CTS Reducing Tee
(Gr x Gr x Cup)
Size Range: 2" - 8"




Fig. 650 Page 180

CTS Concentric Reducer
(Gr x Gr)
Size Range: 2" - 8"






Fig. 652 Page 180

CTS Concentric Reducer
(Gr x Cup)
Size Range: 2" - 8"



Series 6700 Pages 181-182

CTS Copper Butterfly Valve
Size Range: 2 1/2" - 6"



DI-ELECTRIC NIPPLES

Fig. 7088 Page 183

Di-Electric Pipe Connection
Thread x Groove
Size Range: 1" - 4"



Fig. 7089 Page 183

Di-Electric Pipe Connection
Groove x Groove
Size Range: 2" - 4"



Fig. 7090 Page 183

Di-Electric Pipe Connection
Thread x Thread
Size Range: 1/2" - 3"



Fig. 7091 Page 184

Gruvlok DI-LOK® Nipple
Di-Electric Pipe Connection
CTS Groove x IPS Groove
Size Range: 2" - 8"



HDPE COUPLINGS

Fig. 7305 Pages 190-191

HDPE Coupling
Size Range: 2" - 18"




Fig. 7307 Pages 192-193

HDPE Transition Coupling
Size Range: 2" - 12"





Fig. 7312 Pages 194-195

HDPE Flange Adapter
Size Range: 4" - 8"




PLAIN-END FITTINGS

Fig. 7005 Page 185


Roughneck® Coupling
Size Range: 2" - 16"

**Fig. 7050P, 7051P & 7060P** Page 186


Gruvlok Plain-End Fittings
Size Range: 2" - 8"

Fig. 7050P
90° ElbowFig. 7051P
45° ElbowFig. 7060P
Tee**Fig. 7061P** Page 187

Reducing Tee
Size Range: 3" x 3" x 2"
thru 12" x 12" x 10"

**Fig. 7050LRP**

90° LR Elbow
Size Range: 2" - 8"

**Fig. 7051LRP**


45° LR Elbow
Size Range: 2" - 8"

**Fig. 7071P** Page 187


90° True Wye
Size Range: 2" - 8"

**Fig. 7068P** Page 187

Cross
Size Range: 2" - 8"

**Fig. 7069P** Page 187


45° Lateral
Size Range: 2" - 8"

**Fig. 7075P** Page 188

Bull Plug
Size Range: 2" - 8"

**Fig. 7084P & 7085P**

Flange Nipples
Size Range: 2" - 8"

**Fig. 7077P** Page 189

Swaged Nipple
Size Range: 2 1/2" x 2" thru
8" x 6"

**Fig. 7080P, 7081P & 7082P** Page 189

Adapter Nipples
Size Range: 2" - 8"

Fig. 7080P
Plain x GrooveFig. 7081P
Plain x ThreadFig. 7082P
Plain x Bevel

SOCK-IT® METHOD

Fig. 7100 Page 196


90° Elbow
(Sock-It x Sock-It)
Size Range: 1" - 2"

**Fig. 7101** Page 197


90° Reducing Elbow
(Sock-It x NPT)
Size Range: 1" x 1 1/2" thru
1 1/2" x 1"

**Fig. 7103** Page 197


Straight Tee
(Sock-It x Sock-It x Sock-It)
Size Range: 1" - 2"

**Fig. 7105** Page 198


Reducing Outlet Tee
(Sock-It x Sock-It x NPT)
Size Range: 1" x 1" x 1 1/2"
thru 2 1/2" x 2 1/2" x 1"

**Fig. 7106** Page 198

Reducing Tee
(Sock-It x Sock-It x NPT)
Size Range: 1 1/4" x 1" x 1 1/2"
thru 2" x 1 1/2" x 1"

**Fig. 7107** Page 197


Coupling
(Sock-It x Sock-It)
Size Range: 1" - 2"




STAINLESS STEEL METHOD

Fig. 7400SS Page 199


Rigidlite® Coupling
Size Range: 1 1/4" - 8"

**Fig. 472** Pages 200-201


Stainless Steel Rigid Coupling
Size Range: 1 1/4" - 12"

**Fig. 405** Pages 202-203

Stainless Steel Flexible
Coupling
Size Range: 1" - 8"

**Fig. A7050SS**


90° Stainless Steel Elbow
Size Range: 1" - 12"

**Fig. A7051SS**


45° Stainless Steel Elbow
Size Range: 1" - 12"

**Fig. A7060SS**

Stainless Steel Tee
Size Range: 1" - 12"

**Fig. A7061SS**


Stainless Steel Reducing Tee
Size Range: 1 1/2" x 1 1/2" x 1"
thru 12" x 12" x 10"

**Fig. A7074SS**


Stainless Steel Cap
Size Range: 1" - 12"

**Fig. A7084SS** Page 207

Stainless Steel Flange Adapter
Size Range: 1" - 12"

**Fig. A7072SS** Page 208


Stainless Steel Concentric Reducer
Size Range: 1 1/2" x 1" thru 12" x 10"

**Fig. A7073SS** Page 209


Stainless Steel Eccentric Reducer
Size Range: 1 1/2" x 1" thru 12" x 10"

**Model B480** Pages 210-211

Grooved End Stainless Steel Butterfly Valve
Size Range: 2" - 6"

**Model BV435** Page 212

Grooved End Stainless Steel Ball Valve
Size Range: 1 1/2" - 4"



Fittings
Outlets
Fittings
Outlets

Valves &
Pressure Accessories

CTS Copper
System

Di-Electric
Nipples

HDPE
Couplings

Sock-It®
Fittings

Stainless Steel
Steel Method

Roll
Groovers

Installation
& Assembly

Special
Coatings

Design
Services

Technical
Data

Master Format
3 Part Specs.

Pictorial
Index



ANVIL
INTERNATIONAL

www.anvilintl.com

STAINLESS STEEL G-PRESS SYSTEM

Fig. 407 Page 217

Straight Coupling
(Press x Press)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 408 Page 217

Slip Coupling
(Press x Press)
Size Range: $\frac{1}{2}$ " - 2"



Fig. 468 Page 217

90° Elbow
(Press x Press)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 467 Page 218

90° Elbow
(Male x Female)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 471 Page 218

45° Elbow
(Press x Press)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 470 Page 218

45° Elbow
(Male x Female)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 484 Page 219

End Cap
(Female Press)
Size Range: $\frac{1}{2}$ " - 2"



Fig. 442 Page 219

Equal Tees
(Press x Press x Press)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 473 Page 220

Reducing Tees
(Press x Press x Press)
Size Range: $\frac{3}{4}$ " x $\frac{3}{4}$ " x $\frac{1}{2}$ "
thru 2" x 2" x 2"




Fig. 478 Page 221

Tee & Reducing Tee Adapters
(Press x Press x Female NPT)
Size Range: $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{1}{2}$ "
thru 2" x 2" x 2"




Fig. 474 Page 222

Reducer
(Female Press x Male Press)
Size Range: $\frac{3}{4}$ " x $\frac{1}{2}$ " thru
2" x $1\frac{1}{2}$ "




Fig. 476 Page 222

Straight Connector
(Female Press x Male NPT)
Size Range: $\frac{1}{2}$ " x $\frac{1}{2}$ " thru
2" x 2"




Fig. 479 Page 223

Straight Connector
(Female Press x Female NPT)
Size Range: $\frac{1}{2}$ " x $\frac{1}{2}$ " thru
2" x 2"




Fig. 485 Page 223

3-Piece Union
(Press x Press)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 466 Page 224

Van Stone Flange Adapter
(Female Press x Flange)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 477 Page 224

Transition Nipple Grooved
(Groove x Male Press)
Size Range: $\frac{1}{2}$ " - 2"



Fig. 475 Page 225

Flange Adapters
(Female Press x Flange)
Size Range: $\frac{1}{2}$ " - 2"




Fig. 461 Page 225

Weld Adapter
(Male Weld x Female Press)
Size Range: $\frac{1}{2}$ " - 2"





Fig. 469 Page 226

Ball Valve
(Press x Press)
Size Range: $\frac{1}{2}$ " - 2"



ROLL GROOVERS

Gruvlok roll grooving technology is protected by
U.S. Patents 5450738, 5570603, 5778715 and others pending.

Model 1007 Pages 227-228

Roll Groover
Groover Capability: 2" - 16"



Model 3007 Pages 227-228

Roll Groover
Groover Capability: 2" - 16"



Model 3006 Pages 229-230

Roll Groover
Groover Capability: 2" - 12"



PRODUCTS FOR GROOVED PIPING SYSTEM

The Gruvlok® System has been manufactured since the late 1960's. The Gruvlok product line has grown from standard couplings and fittings to today's extensive range of grooved product, plain-end product, butterfly valves, check valves, pump protection components, pipe preparation tools and various accessories.

Gruvlok is part of our overall commitment to provide today's piping industry with tomorrow's products.



Certified to
NSF/ANSI 61-G

For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

ISO 9001:2008

INDUSTRY & GOVERNMENT STANDARDS & APPROVALS

ANSI	American National Standards Institute
API	American Petroleum Institute: API Std. 5L, Sect. 7.5
ASHRAE	American Society of Heating, Refrigerating and Air Conditioning Engineers
ASME	American Society of Mechanical Engineers: Power Piping, B 31.1; Chemical Plant and Petroleum Refinery Piping, B 31.3; Refrigeration Piping, B 31.5; Building Services Piping, B 31.9; Slurry Pipelines, B 31.11
ASTM	American Society of Testing and Materials: F 1476, F 1387
AWWA	American Water Works Association: C 606
BV	Bureau Veritas
CDF	California State Fire Marshal
COE	Corps of Engineers: CEGS 15000
CSA	Canadian Standards Association: B 242
DNV	Det Norske Veritas Hong Kong Fire Services Board New Zealand Insurance Council New Zealand Building Act. (1991)

FAA	Federal Aviation Administration: HVAC, Plumbing, Fire Protection
FHA	Federal Housing Administration
FM	Factory Mutual Engineering Corp.
GSA	General Services Administration: 15000 Series
IAPMO	International Association of Plumbing & Mechanical Officials
LPC	Loss Prevention Council
MEA	Materials & Equipment Acceptance
MIL	Military Specifications: MIL-P-10388 Fittings; MIL-C-10387 Couplings; MIL-P-11087A(CE) Steel Pipe, Grooved MIL-I-45208 Inspection Procedure
NASA	National Aeronautics and Space Administration: 15000 Series
NAVFAC	Naval Facilities Engineering Command: NFGS 15000 Series
NFPA	National Fire Protection Association
NIH	National Institute of Health (Dept. of Health): 15000 Series
NSF	NSF International

NY-BSA	New York Board of Standards and Appeals
NYC	New York City
TVA	Tennessee Valley Authority: Fire protection, storm drains
UL	Underwriter's Laboratories, Inc.
ULC	Underwriter's Laboratories of Canada Bureau of Marine Inspection: Salt and fresh water, oil transfer
	Bureau of Public Roads; Div. of Bridges: Drain lines and bridge crossings
	Canadian Coast Guard
	U.S. Coast Guard – Approves each vessel individually
USGBC	United States Green Building Council
VA	Veterans Affairs : 15000 Series
VdS	Verband der Sachversicherer e.V.

Note: Please refer to product specific pages for exact listings and approvals related to a specific size for a specific product.

GRUVLOK® – THE ENGINEERED COUPLING

HOUSING (A) FLEXIBLE OR RIGID

The Gruvlok Coupling housing is designed to self-center around the pipe. The housing encircles and retains the gasket against the application of internal system pressure or vacuum.

The housing key sections fit into and engage the pipe-end grooves around the entire pipe circumference, thus restraining the pipe ends from separation due to the application of internal pressure.

Flexible Couplings provide designed-in clearances between the housing key sections and the pipe grooves to permit both angular and longitudinal movement of the pipe. Rigid couplings grip the pipe and lock the joint into position.


All housings are coated with paint for general service applications. The paint serves to provide protection against normal atmospheric corrosion. However, for couplings used in corrosive environments, hot-dip galvanizing, and stainless steel are available.

GASKET (B)



The unique single piece "C" style design of the gasket has been engineered to provide a pressure responsive, leak-tight seal in both pressure and vacuum applications without the aid of external forces. The "lips" of the gasket are molded so that upon installation onto the pipe ends they provide compression against the pipe surface to establish the leak-tight seal.

The gasket cavity functions as a "pressure reservoir". Pressure within the pipe system is applied to the internal surfaces of the gasket which increases the sealing force and enhances the leak-tight seal. In vacuum systems, non-pressure-responsive seals tend to "lift off" the pipe, producing leak paths. However, the Gruvlok gasket reacts to the negative pressure (higher outside atmospheric pressure) as to improve the sealing capability of the gasket.

Gasket Reaction to Pressure



Gasket Reaction to Vacuum



BOLTS AND NUTS (C)

Heat treated oval neck track head bolts serve to connect and secure the housing segments together. The oval neck design prevents turning of the bolt while tightening the hex nut with a single wrench. The bolt size and corresponding wrench (or socket) size for the hex nuts are shown in the chart below.

ANSI


Bolt Size	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{3}{4}$	$\frac{7}{8}$	1	$1\frac{1}{4}$
Wrench Size	$1\frac{1}{16}$	$\frac{7}{8}$	$1\frac{1}{16}$	$1\frac{1}{4}$	$1\frac{7}{16}$	$1\frac{5}{8}$	2

METRIC

Bolt Size	M10	M12	M16	M20	M22
Wrench Size	16	22	24	30	34

GROOVED PIPE ENDS (D)

The ends of the pipe must have a groove in them which may be either cut grooved or roll grooved. The grooved pipe ends engage the coupling keys, thus, providing a self-restraining, mechanical joint capable of resisting the separation of the pipe ends due to the application of system pressure. The groove diameters must be dimensionally accurate to obtain the maximum benefit of the Gruvlok Coupling.



THE GRUVLOK® PIPING METHOD

Gruvlok couplings and grooved-end fittings are widely used for joining pipe in a wide variety of piping systems. Gruvlok couplings for grooved-end pipe are designed to provide a self-centering joint which accommodates the application of pressure, vacuum and other external forces, while limiting the burdensome need for special supports, expansion joints, etc.

The Gruvlok piping method offers many mechanical design features which benefit the design engineer, the contractor, and the end user. Utilization of the functional characteristics of the Gruvlok coupling will aid in pipe system design and must be considered for proper installation, assembly and performance.

The design factors presented in the Gruvlok technical data section should always be referenced to when designing any grooved piping system to obtain the maximum benefit of the Gruvlok piping method.




GRUVLOK FEATURES

RIGIDITY OR FLEXIBILITY


Couplings are available where rigid connections are required. Rigid couplings are clearly marked with an "X" for identification.

Couplings with flexible design allow for pipe expansion and contractions with temperature changes. The need for an expansion joint is minimized or eliminated.




UNION AT EVERY JOINT

Gruvlok couplings can be disassembled easily permitting maintenance and servicing of the piping system. It will facilitate periodic rotation of pipe to distribute internal wear from slurries or other abrasive media.




MINIMIZES NOISE & VIBRATION

The resilient elastomeric gasket and pre-designed gap of the Gruvlok coupling help isolate and absorb noise and vibration, thus minimizing vibration transmission.




SELF RESTRAINED JOINT

The couplings engage the pipe around the entire circumference and restrain the pipe ends from separation due to pressure and other forces, up to the maximum coupling rated working pressure.




STRESS-FREE SYSTEM

Flexibility designed in the Gruvlok coupling absorbs and eliminates stress from settlement of buried pipe or those induced by seismic tremors.




ACCOMMODATES MISALIGNMENT AND JOINT DEFLECTION

The flexibility designed into the Gruvlok coupling will accommodate misalignments caused by imprecise location of pipe opening through walls and floors, will provide pitch for drainage piping systems and facilitate laying pipe on uneven terrain, thus permitting deflection in any direction.



GRUVLOK® COUPLINGS FOR GROOVED-END PIPE

Gruvlok couplings for grooved-end pipe are available in nominal pipe sizes 1" thru 60" and metric sizes. The variety of coupling designs provide a universal means for the connection of pipe, fittings and pipe system components. The wide assortment of Gruvlok couplings and gaskets permit selection of the most suitable combination for a specific application, thus providing the most versatile and economical pipe system installation.



MATERIAL SPECIFICATIONS

BOLTS:

SAE J429, Grade 5, Zinc Electroplated
ISO 898-1, Class 8.8, Zinc Electroplated followed by a Yellow Chromate Dip

HEAVY HEX NUTS:

ASTM A563, Grade A, Zinc Electroplated
ISO 898-2, Class 8.8, Zinc Electroplated followed by a Yellow Chromate Dip

STAINLESS STEEL BOLTS & NUTS:

Stainless steel bolts and nuts are available for the Fig. 7001, 7401, 7401-2, 7001-2, 7004, 7000 and 7400 couplings in standard 304SS, (316SS available as special order)

HOUSING:

Ductile Iron conforming to ASTM A 536, Grade 65-45-12

COATINGS:

Rust inhibiting paint Color: ORANGE (standard)
Hot Dipped Zinc Galvanized (optional)
Other Colors Available (IE: RAL3000 and RAL9000)
For other Coating requirements contact an Anvil Representative.

GASKETS: Materials

Properties as designated in accordance with ASTM D 2000

GRADE "EP" EPDM (Green/Red color code) NSF-61 Certified

-40°F to 250°F (Service Temperature Range)(-40°C to 121°C)
Recommended for water service, diluted acids, alkalies solutions, oil-free air and many other chemical services.
NOT FOR USE IN PETROLEUM APPLICATIONS.

GRADE "E" EPDM (Green color code) NSF-61 Certified

-40°F to 230°F (Service Temperature Range)(-40°C to 110°C)
Recommended for water service, diluted acids, alkalies solutions, oil-free air and many chemical services.
NOT FOR USE IN PETROLEUM APPLICATIONS.

GRADE "T" Nitrile (Orange color code)

-20°F to 180°F (Service Temperature Range)(-29°C to 82°C)
Recommended for petroleum applications. Air with oil vapors and vegetable and mineral oils.
NOT FOR USE IN HOT WATER OR HOT AIR

GRADE "O" Fluoro-Elastomer (Blue color code)

Size Range: 1" - 12" (C style only)
20°F to 300°F (Service Temperature Range)(-29°C to 149°C)
Recommended for high temperature resistance to oxidizing acids, petroleum oils, hydraulic fluids, halogenated hydrocarbons and lubricants

GRADE "L" Silicone (Red color code)

Size Range: 1" - 12" (C style only)
-40°F to 350°F (Service Temperature Range)(-40°C to 177°C)
Recommended for dry, hot air and some high temperature chemical services

GASKET TYPE:

Standard C Style
Flush Gap: 1" - 24"
End Guard: 1" - 12" (Fig. 7004 and 7377)
SlideLOK: 2" - 8"

LUBRICATION:

Standard Gruvlok
Gruvlok Xtreme™ (Do Not use with Grade "L")

WORKING PRESSURE, END LOAD, PIPE END SEPARATION & DEFLECTION FROM CENTER LINE:

Based on standard wall steel pipe with cut or roll grooves in accordance with Gruvlok specifications. Pressure ratings for light wall, stainless steel, aluminum, and ISO pipe available. See technical data section.

COUPLING DATA CHART NOTES

COUPLING DATA CHART NOTES														
Nominal Size	O.D.	Max. Work. Pressure	Max. End Load	Range of Pipe End Separation	Deflection from C		Coupling Dimensions			Coupling Bolts		Specified Torque		Approx. Wt. Ea.
					Per Coupling	of Pipe	X	Y	Z	Qty.	Size	Min.	Max.	
In./DN(mm)	In./mm	PSI/bar	Lbs./kN	In./mm	Degrees(°)-Minutes(')	In./ft-mm/m	In./mm	In./mm	In./mm		In./mm	Ft.-Lbs/N-m	Lbs./kg	
1	2	3	4	5	6		7			8		9	10	

- 1 Gruvlok Couplings are identified by either the nominal ANSI pipe size in inches or pipe O.D. in millimeters (see column 2).
- 2 Nominal Outside Diameter of Pipe.
- 3 Maximum line pressure, including surge, to which a joint can be subjected. Working pressure ratings are based on standard wall steel pipe with standard cut or roll grooves in accordance with Gruvlok specifications. For Performance Data on other than standard wall pipe, refer to Technical data section. **NOTE: For one time field test only, the maximum joint working pressure may be increased to 1.5 times the figure shown unless otherwise noted.**
- 4 Maximum end load from all interior and/or exterior forces to which the joint can be subjected are based on standard wall steel pipe with standard cut or roll grooves in accordance with Gruvlok specifications.
- 5 Range of pipe end separation for roll grooved pipe. Double values shown when using cut groove pipe; see page 274 for details.
- 6 Maximum allowable angular deflection values from centerline when using standard roll grooved pipe; Double values shown when using cut groove pipe; see page 274 for details.
- 7 "X", "Y", and "Z" are external dimensions for reference purposes only.
- 8 The quantity of bolts per coupling.
- 9 Nuts must be tightened alternating and evenly to the specified bolt torque. See individual product installation instructions for additional important information.
- 10 Approximate weight for a fully assembled coupling with gasket, bolts, and nuts.