

2015 RACE TIRE SPECIFICATIONS

Hoosier[®]

RACING TIRE



finish line
RACING PRODUCTS
Williams Lake, BC
1-800-734-3805

www.finishline.ca



Hoosier

NO WARRANTY POLICY

HOOSIER RACING TIRE CORP. offers racing tires for sale only upon the conditions and the terms contained in this disclaimer of liability and indemnity. Due to many varied and different conditions which Hoosier Racing Tires and Tubes are exposed and because of the manner in which racing is conducted, Hoosier Racing Tire Corp. makes absolutely **no warranty**, expressed or implied, as to the fitness for a general or particular purpose or of merchantability in connection with any offer of sale of Hoosier Racing Tires and tubes. **"HOOSIER RACING TIRES AND TUBES ARE SOLD AS IS."** Race tires are not tested or labeled to meet FMVSS 109, 119, 139 or ECE36 Safety Standards. Therefore it is dangerous and illegal to sell race tires for use on public highways. Any person selling Hoosier Racing Tires or Tubes for highway use agrees to indemnify and reimburse Hoosier Racing Tire Corp. for all loss, damage, or liability Hoosier Racing Tire Corp. may suffer because of such sales. Not applicable where prohibited by law. Not following these warnings can cause **SERIOUS PERSONAL INJURY OR DEATH**. For more information read tire labels, follow manufacturer's warnings as molded in tire sidewalls and visit hoosiertire.com.

FREEZE WARNING

Freeze Crack Advisory: This advisory addresses proper storage and use of Hoosier tires in cold conditions. Hoosier Tires, especially asphalt and hard compound tires, may experience Rubber Cracking if the tires are transported, crushed, flexed or stressed when frozen. The following guidelines are provided to avoid this problem.

1. Always store Hoosier Racing Tires indoors at temperatures above 32° F.
2. If tires have been subject to 32° F or less, allow them to warm to room temperature (about 70° F) for a minimum of 24 hrs before the tire is mounted, transported or flexed.
3. Always use spare tires not intended for future competition to store vehicles for prolonged periods of time or winter transport.
4. If below freezing temperatures are expected, please consider shipping tires once more favorable conditions exist.

Do not use tires that have evidence of Freeze Crack Damage.

WARNING

Service Life for Race Tires: Old tires can fail in use, causing loss of vehicle control and personal injury. Environmental conditions like temperature extremes, exposure to sunlight, electric arc, solvents, automotive fluids, and atmospheric pollutants accelerate the aging process. Hoosier Racing Tire strongly recommends that new (sticker) tires should be put in service within 2 years of date of purchase. Used (scuffed) tires have a shorter service life than new (sticker) tires. Poor storage and infrequent use accelerate the aging process.

DIRECTION OF ROTATION / MOUNTING INSTRUCTIONS

ROTATIONAL GUIDELINES FOR TIRES WITH DIRECTIONAL ARROWS

All Hoosier tires having directional arrows must be mounted so that the tire travels in the direction of the arrow. Hoosier tires having directional arrows will have them on both sidewalls. Directional arrows may not be on a tire that can have both left and/or right side application. All Hoosier tires not having directional arrows should be mounted as detailed below.

ROTATIONAL GUIDELINES FOR TIRES WITHOUT DIRECTIONAL ARROWS

Every Hoosier race tire has a four character serial code embossed into ONE sidewall of the tire. All Hoosier DOT tires will also have two additional codes as required by the Department of Transportation. (Example: J7AB 4AX8 3710)

CIRCLE TRACK RACING TIRES:

(Includes both dirt and asphalt tires)

Hoosier tires must be mounted with the **serial code** located toward the infield.

ROAD RACING TIRES:

(Includes catalog numbers beginning with 43, 44, 45, 46)

In most cases, Hoosier tires used in Road Race applications should be mounted with the **serial code** toward the center of the vehicle. Once a tire has been run in the proper orientation it is acceptable to remount the tire in the opposite direction to even out the wear.

DRAG RACING TIRES, INCLUDING DOT DRAG TIRES:

(Includes catalog numbers beginning with 17, 18)

Hoosier drag tires can be mounted to rotate in either direction. Hoosier drag tires can also be flipped or reversed to provide even wear.

WARNING TIRE MOUNTING IS DANGEROUS

Special Tire Mounting Instructions: Tire mounting should be done **only** by trained personnel using proper tools and procedures. Failure to follow safe mounting procedures could cause faulty positioning of the tire and cause the assembly to burst with explosive force sufficient to cause **SERIOUS PERSONAL INJURY OR DEATH**. Always inspect tire for kinked beads or other possible damage that may have occurred in shipping or storage. Clean rim and lubricate beads with rubber lubricant. Always lock rim on mounting machine or place in safety cage. Use a clip on chuck, an in-line valve with a pressure gauge or adjustable regulator and remote inflation/deflation device. Have enough air hose to stay out of the trajectory. Stand back.

WARNING VERIFY RIM SIZE

Verify Correct Wheel and Bead Flange: All tires are designed to be used on wheels that are manufactured to Tire and Rim Association (T&RA) specifications and tolerances. Some rims are non-standard or damaged and it is necessary to inspect the rim flange to assure proper fit. Consult your specific rim manufacturer to determine if your rim can be used in this application. Never attempt to install and inflate a tire of one bead diameter on a rim or wheel of a different bead diameter. Use of Hoosier Racing Tires on wheels with incorrect bead flanges or wheels that do not meet T&RA standards can cause the assembly to fail and burst with explosive force sufficient to cause **SERIOUS PERSONAL INJURY OR DEATH**. Use a certified wheel rim disk tape to confirm wheel rim flange size.

WARNING BEAD / RIM SEATING

When seating beads never exceed maximum bead seating pressure as molded in tire sidewall. Never exceed manufacturer's maximum inflation pressure. Always seat beads with wheel locked to mounting machine or placed in a safety cage. A damaged tire or wheel can fail during bead seating and burst with enough force sufficient to cause **SERIOUS PERSONAL INJURY OR DEATH**. Always use a clip on chuck, an in-line valve with a pressure gauge or adjustable regulator and remote inflation/deflation device. Have enough air hose to stay out of the trajectory. Stand back. If the beads will not seat at the manufacturer's maximum bead seating pressure, STOP, deflate tire, return the tire to the place of purchase.

WARNING NOT FOR HIGHWAY USE

NOT FOR HIGHWAY USE: All Hoosier Racing Tires including DOT labeled Hoosier Racing Tires are designed for racing purposes only on specified racing surfaces and are **not to be operated on public roadways**. DOT labeled Hoosier Racing Tires meet Department Of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and **SERIOUS PERSONAL INJURY OR DEATH**.

Exception – “PRO STREET” page 20.

WARNING MISUSE / MISAPPLICATION

Application/Misuse: All Hoosier Racing Tire products are designed for a specific purpose. Consult with Hoosier Racing Tire Corp. for specific fitment and application. Utilizing Hoosier Tires in any form outside of their intended use constitutes **misuse** of the product and can cause **SERIOUS PERSONAL INJURY OR DEATH**. Hoosier Racing Tire products are designed and manufactured for racing purposes only, within a closed course designed for organized competition. Not for recreational use. Hoosier Tires should never be used for Off Track Exhibition or for Land Speed Record Vehicles including Jet or Rocket Powered Cars.

WARNING DO NOT ALTER TIRES

Chemical Treatment of Tires: Hoosier Racing Tires strictly forbids any chemical alteration of the tire carcass and/or tread compound such as tire “soaking” or use of tread “softener.” Hoosier Racing Tire strictly forbids the physical defacement (removal, altering or covering), of tire sidewall markings in any manner. Failure to comply with this warning could result in premature or catastrophic tire failure and may result in **SERIOUS PERSONAL INJURY OR DEATH**.

TREAD PATTERNS

TIRE TREADS

TIRE TREADS

<p>DRAGSTER FRONT</p>  <p>A</p>	<p>DRAG FRONT</p>  <p>B</p>	<p>DRAG SLICK</p>  <p>C</p>	<p>QUICK TIME PRO</p>  <p>D</p>
<p>RACING D.O.T. RADIAL</p>  <p>E</p>	<p>PRO STREET</p>  <p>F</p>	<p>VINTAGE</p>  <p>G</p>	<p>STREET TREAD</p>  <p>H</p>
<p>ROAD RACING WET</p>  <p>I</p>	<p>D.O.T. RADIAL WET</p>  <p>J</p>	<p>WRS-2</p>  <p>K</p>	<p>SUPER CHAIN LINK</p>  <p>L</p>
<p>RIB DIRT</p>  <p>M</p>	<p>IMCA</p>  <p>N</p>	<p>CROSSBLOCK</p>  <p>O</p>	<p>LARGE CROSSBLOCK</p>  <p>P</p>
<p>SMALL CROSSBLOCK</p>  <p>Q</p>	<p>RIB ASPHALT</p>  <p>R</p>	<p>CHECKERBOARD</p>  <p>S</p>	<p>LARGE CHECKERBOARD</p>  <p>T</p>

TREAD PATTERNS

<p>ANGLE BLOCK</p>  <p>U</p>	<p>DIRT BOZZ STYLE</p>  <p>V</p>	<p>STAGGER BLOCK</p>  <p>W</p>	<p>MICRO FRONT</p>  <p>X</p>
<p>MIDGET FRONT</p>  <p>Y</p>	<p>TREADED KART CROSSBLOCK</p>  <p>Z</p>	<p>TREADED KART ANGLE BLOCK</p>  <p>aa</p>	<p>SLICK</p>  <p>bb</p>
<p>ATV FRONT - LS</p>  <p>cc</p>	<p>ATV KNOBBY</p>  <p>dd</p>	<p>ATV</p>  <p>ff</p>	<p>ATV FRONT - HP</p>  <p>gg</p>
<p>WIDE TRI-TRAC</p>  <p>hh</p>	<p>A-7/R-7</p>  <p>ii</p>		

TIRE TREADS

TIRE TREADS

Hoosier[®]

RACING TIRE

“TIRES DESIGNED FOR CHAMPIONS”[®]

TABLE OF CONTENTS

LEAD #	TIRE	PAGE #
	NO WARRANTY POLICY & WARNINGS	Inside Front Cover
	DIRECTION OF ROTATION/MOUNTING	
	INSTRUCTIONS	1
	Tread Patterns	2-3
39/40	ARCA	5
41	Little Car Asphalt/Mini-Cup.....	5
13	Midget Asphalt	5
08/10/37	Asphalt Short Track.....	5-6
08/09	Modified/Supers/Sprint/Silver Crown Asphalt.....	7
12	Oval Track D.O.T. Dirt.....	7
36	Late Model/E-Mod/Street Stock Dirt	7-9
14	Eastern Modified/358/Sportsman Dirt	9
31/38	Wing Sprint Dirt	9-10
31	Non-Wing Sprint Dirt/Silver Crown Short Track Dirt.....	10
31	Silver Crown Dirt/Mile Tracks	10
35	Midget Dirt/Mini Sprint.....	11
42	Modified Midget/Micro Sprint Dirt/Jr. Sprint.....	11
11	Dirt Oval Karting	11
11	Treaded Kart	12
15	Asphalt Oval Karting.....	12
15	Asphalt Quarter Midget.....	12
11	Dirt Quarter Midget	12
22	Sprint/Solo/Road Race Kart	12
	Super Kart.....	12
	Enduro Kart	13
16/42	ATV	13
17	Quick Time D.O.T.....	13
17	Quick Time Pro D.O.T.	14
18	Drag Racing	14-15
18	JR Dragster.....	15
28/32	Racing Tubes & Liner	15
17	D.O.T. Drag Radials.....	16
43	Road Racing Slicks - Bias	16
43	Road Racing Slicks - Radial.....	17
44	Road Racing Wets - Bias	17
44	Road Racing Wets - Radial.....	17
45	Sports Car D.O.T. - Bias	18
44/45/46	Vintage & Historic.....	18
46	Sports Car D.O.T. - Radial	19
46	Sports Car D.O.T. - Radial Wet	20
19	Pro Street D.O.T. - Radial.....	20
	Hoosier Racing Tire Distributors	Back Cover

SEE WARNINGS STARTING ON INSIDE COVER

Tire rule spec tires may not be listed in this catalog. Please contact local distributor for further information.

REV. 11/14
First Printing

ARCA

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
40310	11.0/88.015 Bias Dirt	L	11.0"	28.0"	88.0"	9.5"	9.5"	13.5"	D45L, D70R (Dirt Track)
39100	11.0/28.0R-15 Radial L	bb	10.7"	27.8"	87.3"	9.5"	9.5"	12.75"	27 (Short Track Radial -L)
39200	11.0/28.0R-15 Radial R	bb	10.7"	28.2"	88.6"	9.5"	9.5"	12.75"	44 (Short Track Radial -R)
*	12.0/28.0R-15 Radial L	bb	12.0"	27.8"	87.3"	9.5"	9.5"	13.2"	Speedway Left
*	12.0/28.0R-15 Radial L	bb	12.0"	28.0"	87.75"	9.5"	9.5"	13.2"	Talladega / Daytona Left
*	12.0/28.0R-15 Radial R	bb	12.0"	28.2"	88.6"	9.5"	9.5"	13.2"	Speedway Right

* DETERMINED BY HOOSIER RACING TIRE CORP. PRIOR TO THE EVENT

LITTLE CAR ASPHALT / MINI-CUP

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
41100	6.0/18.0-10	bb	6.0"	18.0"	56-57"	6-7"	7"	8.5"	LC0
41120	8.0/18.0-10	bb	8.0"	18.0"	56-57"	7-8"	8"	9.8"	LC3
41130	10.0/19.0-10	bb	10.0"	19.0"	60.0"	10"	10"	12.2"	LC5
MINI-CUP									
41149	15.0/ 7.0-8 SH	bb	6.25"	15.37"	48.25"		8.0"	7.5"	MC780
41150	15.0/ 7.0-8	bb	6.25"	15.75"	49.5"		8.0"	7.5"	MC780

SOFT _____ LC0 _____ LC3 _____ LC5 _____ MC780 _____ FIRM

MIDGET ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
13109	7.0/20.5-13	bb	7.0"	20.5"	65.0"	8"	8"	8.6"	MG4, MG5, MG6, 600
13110	7.0/20.5-13	bb	7.0"	20.5"	66.0"	8"	8"	8.6"	700, DX2, MG5, MG7, MG8
13115BG06	7.0/20.5-13 BG2006	bb	7.0"	20.5"	65.0"	8"	8"	8.6"	BG2006
13195	10.0/22.0-13	bb	9.0"	22.0"	69.0"	8"	8"	11.2"	500, MG5
13196	10.0/22.5-13	bb	10.0"	22.5"	69.0"	8"	8"	11.2"	MG5
13205	10.0/23.0-13	bb	10.0"	23.0"	70.0"	8"	8"	11.6"	MG5
13210	10.0/23.5-13	bb	10.0"	23.5"	73.0"	10"	10"	11.6"	760
13220	12.0/23.5-13	bb	12.0"	23.5"	74.0"	10-12"	10"	13.5"	MG7.3
13240	12.0/23.5-13	bb	12.0"	23.5"	74.0"	10-12"	10"	13.5"	MG7

SOFT _____ MG4 _____ MG5 _____ MG6 _____ MG7 _____ MG7.3 _____ MG8 _____ FIRM

ASPHALT SHORT TRACK

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
08600	27.0/10.0-15 SX	bb	10.0"	26.5"	83.0"	10"	10"	13.2"	1030, 1040
08625	27.0/10.0-15 MED	bb	10.0"	27.0"	85.5"	10"	10"	13.2"	1030
08650	27.0/10.0-15	bb	10.0"	27.5"	86.0"	10"	10"	13.2"	1040
10050	8.0/23.0-13	bb	8.0"	23.5"	73.8"	8"	8"	10.2"	F60, Sportsman, TUSA
10051	8.0/23.0-13 SH	bb	8.0"	23.0"	72.5"	8"	8"	10.2"	F60, Sportsman, TUSA
10060	22.5/ 7.0-13	H	7.0"	22.5"	70.7"	6"	6"	8.6"	SPORTMAN
10070	23.0/ 7.0-13	H	7.0"	23.0"	72.2"	6"	6"	8.6"	SPORTMAN, SUPER TD
10100	22.5/ 8.0-13	R	8.0"	22.5"	70.7"	8"	8"	9.8"	700
10110	23.0/ 8.0-13	R	8.0"	23.0"	72.2"	8"	8"	9.8"	700
10160	10.0/27.0-15 SH	bb	10.0"	27.0"	84.8"	10"	10"	13.2"	1070
10170	10.0/27.0-15	bb	10.0"	27.5"	86.0"	10"	10"	13.2"	1070
10175	27.0/10.0-15 SX	bb	10.0"	26.5"	83.0"	10"	10"	13.2"	2040
10179	27.0/10.0-15	bb	10.0"	27.5"	86.0"	10"	10"	13.2"	2040

OVAL TRACK ASPHALT

OVAL TRACK ASPHALT

ASPHALT SHORT TRACK CON'T.

OVAL TRACK ASPHALT

OVAL TRACK ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
10186	27.0/ 8.0-15 SX	bb	8.0"	26.8"	84.0"	8"	8"	11.5"	2040
10188	27.0/ 8.0-15 MED	bb	8.0"	27.3"	86.0"	8"	8"	11.4"	2040
10196	9.0/26.5-15	bb	9.0"	26.5"	84.0"	10"	10"	12.5"	400, 500
10198	9.0/27.0-15	bb	9.0"	27.0"	86.5"	10"	10"	12.75"	600, 700
10220	26.5/ 8.0-15	H	8.0"	26.5"	82.1"	8"	8"	10.2"	COMANCHE
10230	27.5/ 8.0-15	H	8.0"	27.5"	85.3"	8"	8"	10.7"	COMANCHE
10240	23.0/ 7.0-13 RIB	R	6.6"	22.75"	71.5"	7"	7"	9.3"	700, 800
10245	23.5/ 7.0-13 RIB	R	6.6"	23.2"	73.0"	7"	7"	9.1"	700, 800
10247	24.0/ 7.0-14	R	7.0"	24.15"	75.88"	7-8"	7"	9.19"	850
10257	24.0/ 7.0-15	R	7.0"	24.17"	75.94"	7-8"	7"	8.81"	850
10265	24.0/ 7.0-14 RIB	R	6.6"	24.1"	75.75"	7"	7"	9.2"	800
10267	24.0/ 7.0-16	R	7.0"	24.31"	76.38"	7-8"	7"	9.31"	850
10275	23.5/ 7.0-15 RIB	R	6.6"	23.15"	72.75"	7"	7"	9.2"	700, 800
10280	26.5/ 8.0-15 RIB	R	8.0"	26.5"	82.0"	8"	8"	10.75"	700, 800
10285	27.0/ 8.0-15 RIB	R	8.0"	27.0"	84.5"	8"	8"	11.25"	700, 800
10290	27.5/ 8.0-15 RIB	R	8.0"	27.5"	85.5"	8"	8"	11.25"	700, 800
10295	8.0/26.5-15	H	9.0"	26.5"	83.2"	8"	8"	11.0"	970
10300	8.0/26.5-15	H	9.0"	27.0"	84.0"	8"	8"	11.0"	970
10350	8.0/27.0-15	H	9.0"	27.5"	86.3"	8"	8"	11.0"	970
10400	23.0/ 7.0-13	H	7.0"	23.0"	72.2"	6"	6"	8.6"	790
10405	23.0/ 7.0-14	H	7.0"	23.0"	72.2"	6"	6"	8.6"	790
10408	24.0/ 7.0-14	H	7.0"	24.0"	75.0"	6"	6"	9.1"	790
10410	26.5/ 7.0-15	H	7.0"	26.4"	83.0"	6"	6"	9.1"	790
10411	26.5/ 7.0-15	H	7.0"	26.4"	83.0"	6-7"	6"	9.1"	850
10415	27.0/ 7.0-15	H	7.0"	27.0"	85.0"	6"	6"	9.2"	790
10416	27.0/ 7.0-15	H	7.0"	27.0"	85.0"	6-7"	6"	9.2"	850
10420	26.5/ 8.0-15	H	8.0"	26.5"	82.1"	8"	8"	10.2"	880, 890
10425	27.5/ 8.0-15	H	8.0"	27.5"	85.3"	8"	8"	10.7"	880, 890
10499	26.5/ 8.0-15	bb	8.0"	26.8"	84.0"	8"	8"	11.5"	950
10500	26.5/ 8.0-15	bb	8.0"	26.8"	84.0"	8"	8"	11.5"	980
10504	27.5/ 8.0-15	bb	8.0"	27.3"	86.0"	8"	8"	11.4"	960
10505	27.5/ 8.0-15	bb	8.0"	27.3"	86.0"	8"	8"	11.4"	980
10580	26.5/ 8.0-15 RIB	R	8.0"	26.5"	82.0"	8"	8"	10.75"	S650, S800
10583	27.0/ 8.0-15	R	8.0"	27.0"	84.5"	8"	8"	11.25"	S450
10588	27.5/ 8.0-15	R	8.0"	27.5"	85.5"	8"	8"	11.25"	S650
10600	26.5/10.0-15	bb	10.0"	26.8"	84.0"	10"	10"	13.2"	F25, F40
10610	27.0/10.0-15	bb	10.0"	27.1"	85.0"	10"	10"	13.2"	F40
10615	27.0/10.0-15	bb	10.0"	27.2"	85.5"	10"	10"	13.2"	F40
10620	27.5/10.0-15	bb	10.0"	27.3"	86.5"	10"	10"	13.2"	F48, F50
10700	27.0/10.0-15 SX	bb	10.0"	26.8"	84.0"	10"	10"	13.2"	3025, 3035
10710	27.0/10.0-15	bb	10.0"	27.2"	85.0"	10"	10"	13.2"	3035
10720	27.0/10.0-15	bb	10.0"	27.3"	86.5"	10"	10"	13.2"	3035, 3045
37130	8.0/27.0-15 L	bb	8.0"	26.8"	84.0"	8"	8"	11.5"	F53, F75
37139	8.0/27.0-15 MED	bb	8.0"	27.0"	85.0"	8"	8"	11.2"	F53, F75
37140	8.0/27.0-15	bb	8.0"	27.3"	86.0"	8"	8"	11.4"	F53, F75
37160	10.0/23.0-13 SH	bb	10.0"	22.4"	70.5"	10"	10"	12.5"	F15, F35
37170	10.0/23.0-13	bb	10.0"	23.0"	72.0"	10"	10"	12.5"	F15, F25, F35, F45
37181	10.0/27.0-15 SX	bb	10.0"	26.8"	84.0"	10"	10"	13.2"	F45
37190	10.0/27.0-15	bb	10.0"	27.3"	86.5"	10"	10"	13.2"	F45

SOFT

1030
F15

1040
3025
F25

400
3035
F35
950

TUSA
F60
SUPER TD

500
F45
F40
S450

3045
960
F53
2040
1058
F48

600

970
1070

700

800
F50
S800

880
980
F75
SPORTSMAN
S650

FIRM

COMANCHE
790
890
ST TD

850

MODIFIED / SUPERS / SPRINT ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
08400	25.5/13.0-15	bb	13.0"	25.5"	80.5"	14-15"	15"	16.4"	2020, M30
08410	26.0/13.0-15	bb	13.0"	26.0"	81.5"	14-15"	15"	16.4"	M20, M30, M45
08420	27.0/13.0-15	bb	13.0"	26.8"	84.0"	15"	15"	16.4"	M30, M45
08710	13.0/26.0-15	bb	13.0"	26.0"	81.5"	15"	15"	16.4"	1320
08720	13.0/27.0-15	bb	13.0"	26.8"	84.0"	15"	15"	16.4"	1330
09120	11.0/24.0-15	bb	11.0"	24.0"	76.0"	10"	10"	13.0"	M10, 2010
09121	11.0/24.0-15	bb	11.0"	24.0"	76.0"	12"	12"	13.0"	2030
09125	11.0/24.5-15	bb	11.0"	24.5"	77.5"	10"	10"	12.5"	2045, M60
09130	12.0/25.0-15	bb	12.0"	25.0"	78.0"	10-12"	12"	14.5"	2045
09142	13.0/25.0-15	bb	13.0"	25.0"	78.0"	13-14"	13"	15.0"	2045
09200	17.0/28.0-15	bb	17.0"	27.7"	86.5"	18"	18"	20.0"	2045
09206	17.0/28.0-15 (SC2)	bb	17.0"	27.7"	86.5"	18"	18"	20.0"	M40
09209	17.0/28.0-15 (SC1)	bb	17.0"	27.7"	86.5"	18"	18"	20.0"	M55

SOFT

FIRM

M10	M20	M30	M45	M50	M55
2010	2020 1320	2030 1330	2045 M40		

OVAL TRACK D.O.T. DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
12100	P195/65D-13	V	7.0"	23.3"	73.0"	6-7"	6"	8.5"	MED
12130	P205/60D-13	V	8.0"	22.6"	71.0"	7-8"	7"	9.1"	MED
12150	P215/60D-13	V	8.0"	23.3"	73.0"	7-8"	7"	9.3"	SOFT, MED
12160	P225/60D-13	V	8.0"	23.6"	74.5"	7-8"	7"	9.7"	MED
12170	P235/60D-13	V	8.0"	23.8"	75.0"	7-8"	7"	10.2"	MED
12322	P245/60D-15	V	8.0"	26.7"	84.0"	8-9"	8"	10.6"	MED
12330	P255/60D-15	V	8.0"	27.3"	86.0"	8-9"	8"	10.7"	MED
12340	P265/60D-15	V	8.0"	28.0"	88.0"	8-9"	8"	11.1"	MED
12352	P275/60D-15	V	10.0"	28.2"	88.5"	10-11"	10"	12.6"	MED
12360	P285/60D-15	V	10.0"	28.5"	90.0"	10-11"	10"	12.8"	SOFT, MED
12390	P305/60D-15	V	10.0"	29.0"	92.0"	10-11"	10"	13.6"	SOFT, MED

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

LATE MODEL / E-MOD / STREET STOCK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
SPEC									
36019	G60-15	N	8.5"	25.5"	81.0"	8"	8"	10.75"	IMCA
36020	G60-15	N	8.5"	26.0"	82.0"	8"	8"	10.75"	IMCA
36051	8.0/22.5-13	L	8.0"	22.6"	71.0"	7-8"	7"	9.1"	100, 400
36056	8.0/23.0-13	L	8.0"	23.3"	73.0"	7-8"	7"	9.3"	100, 400
36103	8.0/26.5-15	L	8.0"	26.5"	82.0"	8-9"	8"	10.5"	H 500, IMCA 500
36105	8.0/27.0-15	L	8.0"	27.0"	84.0"	8-9"	8"	10.5"	H 500, IMCA 500
36107	8.0/27.5-15	L	8.0"	27.4"	86.0"	8-9"	8"	11.0"	H 500
36108	10.0/27.0-15	L	10.0"	27.0"	84.0"	10-11"	10"	12.5"	500
36175	26.5/8.0-15 WISSOTA	L	8.0"	26.5"	83.0"	8-9"	8"	11.2"	35-W
36185	27.5/8.0-15 WISSOTA	L	8.0"	27.5"	86.0"	8-9"	8"	11.2"	35-W

LATE MODEL / E-MOD / STREET STOCK DIRT CON'T.

OVAL TRACK DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
SPEC CONT.									
36208	26.5/8.0-15	L	8.0"	26.5"	83.2"	8-9"	8"	11.0"	D40
36212	27.5/8.0-15	L	8.0"	27.5"	86.3"	8-9"	8"	11.2"	A40S, H40
36213	27.5/8.0-15	L	8.0"	27.5"	86.3"	8-9"	8"	11.2"	D40
36215	26.5/8.0-15	L	8.0"	26.5"	83.2"	8-9"	8"	11.0"	RC4, A40S
36216	27.5/8.0-15	L	8.0"	27.5"	86.3"	8-9"	8"	11.2"	RC4
36226	27.5/11.0-15	L	11.0"	27.0"	86.0"	10-12"	12"	13.0"	IMCA
36239	28.0/11.0-15	L	11.0"	28.0"	88.0"	10-12"	12"	13.0"	IMCA
36240	28.0/10.5-15	L	10.5"	28.0"	88.0"	10-12"	10"	13.0"	RC4
36310	29.0/10.5-15	L	10.5"	29.0"	91.0"	10-12"	10"	13.5"	RC4, RC6
36316	29.0/11.0-15	L	11.0"	29.0"	91.0"	10-12"	12"	13.5"	IMCA
36608	88.0/11.0-15	W	11.0"	27.8"	87.5"	12-14"	14"	15.5"	FT200
36610	88.0/11.0-15	W	11.0"	28.0"	87.5"	12-14"	14"	15.5"	D21, D28, D35
36612	88.0/11.0-15	K	11.0"	28.0"	87.5"	12-14"	14"	15.25"	WRS-2
36617	UMP LM8811	P	11.0"	28.0"	87.5"	12-14"	14"	14.25"	M10, M20, M40
36618	90.0/11.0-15	W	11.0"	28.2"	88.5"	12-14"	14"	15.75"	FT200
36620	90.0/11.0-15	W	11.0"	28.5"	88.5"	12-14"	14"	15.5"	D21, D28, D35, D45, D55, HTW55
36622	90.0/11.0-15	K	11.0"	28.5"	88.5"	12-14"	14"	15.25"	WRS-2
36627	UMP LM9011	P	11.0"	28.1"	88.5"	12-14"	14"	14.25"	M10, M20, M30S, M40
36628	92.0/11.0-15	W	11.0"	29.3"	92.0"	12-14"	14"	15.5"	FT200, FT400
36630	92.0/11.0-15	W	11.0"	29.0"	92.0"	12-14"	14"	15.5"	D21, D28, D35, D45, D55, HTW55
36632	92.0/11.0-15	K	11.0"	29.0"	92.0"	12-14"	14"	15.5"	WRS-2
36637	UMP LM9211	P	11.0"	29.0"	92.0"	12-14"	14"	14.5"	M10, M20, M30S, M40
36800	23.0/7.0-13	L	7.0"	23.3"	73.0"	7-8"	7"	9.0"	HTWD
36805	205/60-13	V	8.0"	22.6"	71.0"	7-8"	7"	9.1"	HTWD, STARS Soft, STARS Medium
36810	215/60-13	V	8.0"	23.3"	73.0"	7-8"	7"	9.3"	HTWD, STARS Soft, STARS Medium
36815	235/60-13	V	8.0"	23.8"	75.0"	7-8"	7"	10.2"	HTWD
36935	205/60-13	V	8.0"	22.6"	71.0"	7-8"	7"	9.1"	TUSA Soft
36940	215/60-13	V	8.0"	23.3"	73.0"	7-8"	7"	9.3"	TUSA Soft, TUSA Medium
36945	235/60-13	V	8.0"	23.8"	75.0"	7-8"	7"	10.2"	TUSA Soft, TUSA Medium
36975	195/70-14	L	5.5"	24.2"	76.0"	5-6"	6"	6.2"	Stocker
36980	195/70-15	L	5.5"	24.5"	77.0"	5-6"	6"	6.3"	Stocker
PREMIUM SPEC									
36606	28.5/11.0-15	U	11.0"	28.5"	90.5"	12-14"	14"	14.25"	USA21, USA55
36615	88.0/11.0-15	P	11.0"	27.8"	87.0"	12-14"	14"	14.25"	HTS 1350
36616	88.0/11.0-15	P	11.0"	27.8"	87.0"	12-14"	14"	14.25"	USA21, USA55
36625	90.0/11.0-15	P	11.0"	28.1"	88.5"	12-14"	14"	14.25"	1200, 1300, 1325, HTS1350, HTS1600, DRS1350, DRS1600
36626	90.0/11.0-15	P	11.0"	28.1"	88.5"	12-14"	14"	14.25"	USA21, USA55
36635	92.0/11.0-15	P	11.0"	29.0"	92.0"	12-14"	14"	14.25"	1110, 1300, 1350, SUPR1350, HTS1350, HTS1600, DRS1350, DRS1600
36636	92.0/11.0-15	P	11.0"	29.0"	92.0"	12-14"	14"	14.25"	USA21, USA55
36638	92.0/11.0-15	P	11.0"	29.0"	92.0"	12-14"	14"	14.25"	D70
36670	92.0/11.0-15	P	11.0"	29.0"	92.0"	12-14"	14"	14.25"	O1, O2, O3, O4, O5, O6
OPEN COMPETITION									
36021	G60-15	N	8.5"	25.5"	81.0"	8"	8"	10.75"	
36022	G60-15	N	8.5"	26.0"	82.0"	8"	8"	10.75"	
36104	8.0/26.5-15	L	8.0"	26.5"	82.0"	8-9"	8"	10.5"	500
36106	8.0/27.0-15	L	8.0"	27.0"	84.0"	8-9"	8"	10.5"	500
36109	8.0/27.5-15	L	8.0"	27.4"	86.0"	8-9"	8"	11.0"	500
36143	26.0/8.0-15	L	8.0"	26.0"	82.0"	8-9"	8"	11.0"	Soft
36149	26.5/8.0-15	L	8.0"	26.5"	84.0"	8-9"	8"	11.2"	Soft, Medium 100, Medium
36156	27.5/8.0-15 NRM	L	8.0"	27.5"	86.5"	8-9"	8"	11.3"	Soft, Medium 100, Medium 200, Medium, Hard
36420	28.5/11.0-15	M	11.0"	28.5"	88.5"	12-14"	14"	15.5"	South 1600
36421	28.5/11.0-15	M	11.0"	28.5"	88.5"	12-14"	14"	15.5"	1200, 1300, 1325, 1350, 1425, 1450, 1600, D70, SUPR1350
36422	28.5/11.0-15	P	11.0"	28.5"	88.5"	12-14"	14"	15.5"	1110, 1320, 1640
36423	11.0/28.5-15	M	11.0"	28.5"	88.5"	12-14"	14"	15.5"	1425, 1600
36431	29.0/11.0-15	M	11.0"	29.0"	92.0"	12-14"	14"	15.5"	1600

LATE MODEL / E-MOD / STREET STOCK DIRT CON'T.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
OPEN COMPETITION CON'T.									
36432	11.0/29.0-15	M	11.0"	29.0"	92.0"	12-14"	14"	15.5"	1600
36441	29.0/11.0-15 NRM	M	11.0"	29.4"	92.4"	12-14"	14"	15.25"	1200, 1300, 1325, 1350, 1400, 1425, 1450,
36442	11.0/29.0-15 NRM	M	11.0"	29.4"	92.4"	12-14"	14"	15.25"	1425, 1600
36444	29.0/11.0-15 NRM	M	11.0"	29.4"	92.4"	12-14"	14"	15.25"	South 1600
36451	29.0/11.0W-15 NRM	M	11.0"	29.4"	92.6"	12-14"	14"	15.85"	1200, 1300, 1325, 1350
36452	11.0/29.0W-15 NRM	M	11.0"	29.4"	92.6"	12-14"	14"	15.85"	D70
36747	11.0/88.0-15 C4000	P	11.0"	28.0"	88.5"	12-14"	14"	16.25"	1200, 1300, 1325, 1350

SOFT		D40 FT200 STARS Soft TUSA Soft		D21 1350 USA21	D28 TUSA Med	D35	A40S M30S HTWD	FT400 D45	USA55	WRS-2 D55	H40 IMCA	FIRM
1110	1200	1300	1325	HTS1350	1400	1425	1450	RC4	HTS1600 DRS1600	1600	Hard	D70
M10	SOFT	MEDIUM 100	DRS1350	MEDIUM 200			500 MEDIUM			HTW 55		STOCKER IMCA 500
		M20 100	SUPR1350				STARS Medium			M40	South 1600	RC6
		1320								400	35-W	
		01	02	03		04	05			1640		
										06		

EASTERN MODIFIED / 358 / SPORTSMAN DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
SPEC									
14131	11.0/82.0-15SH	L	10.5"	25.5"	80.5"	10-12"	10"	12.0"	D300, D400
14133	11.0/82.0-15	L	10.5"	26.0"	82.0"	10-12"	10"	12.0"	D300, D400
14135	11.0/87.0-15	L	11.0"	27.2"	85.5"	10-12"	12"	14.2"	M45
14143	11.0/90.0-15SH	L	11.0"	28.0"	88.5"	10-12"	12"	14.2"	M45, D50
14145	11.0/90.0-15	L	11.0"	29.0"	90.5"	10-13"	12"	14.5"	M45, D60
14151	13.0/82.0-15	L	13.0"	26.3"	82.0"	12-14"	12"	14.0"	D300, D400, D500
14177	13.0/87.0-15	L	13.0"	27.5"	86.0"	12-14"	14"	16.2"	D300, D400
14189	13.0/89.0-15	L	13.0"	28.0"	88.0"	12-14"	14"	16.2"	D300, D400
14190	13.0/89.0-15	L	13.0"	28.0"	88.0"	12-14"	14"	16.2"	D200
14224	13.0/92.0-15	L	13.0"	29.0"	91.5"	12-14"	14"	16.5"	D300, D400, D500
14226	13.0/92.0-15Tall	L	13.0"	29.5"	92.5"	12-14"	14"	16.5"	D200
14229	13.0/92.0-15Tall	L	13.0"	29.5"	92.5"	12-14"	14"	16.5"	D300, D400
14435	13.0/82.0-13	L	13.0"	26.3"	82.0"	12-14"	13"	14.0"	H70
14555	28.0x13.0-15	L	13.0"	28.0"	88.0"	13-14"	14"	16.2"	H60
14625	29.0x13.0-15	L	13.0"	29.5"	92.5"	14"	14"	16.5"	H70

SOFT	Soft		Hard				Extra		FIRM
D200	D300	M45	D400	D60	H60	D500	H70		

WING SPRINT DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
31131	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D10, D12
31132	85.0/ 8.0-15	L	8.0"	27.0"	85.0"	8"	8"	10.5"	D15, D20
31149	88.0/15.0-15	T	15.0"	28.0"	88.0"	14-15"	15"	18.6"	RD12
31159	90.0/15.0-15	T	15.0"	28.5"	90.0"	14-15"	15"	18.0"	D10, RD12
31167	92.0/15.0-15	T	15.0"	28.9"	91.5"	14-15"	15"	18.5"	RD12
31169	92.0/15.0-15	T	15.0"	29.0"	92.0"	14-15"	15"	18.5"	D10, RD12, D12

OVAL TRACK DIRT

OVAL TRACK DIRT

WING SPRINT DIRT CON'T.

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
31189	94.0/15.0-15	T	15.0"	30.0"	94.0"	14-15"	15"	18.3"	RD12, D12
31191	94.0/15.0-15	T	15.0"	29.7"	93.5"	14-15"	15"	18.3"	RD12, D12
31208	96.0/15.0-15	T	15.0"	30.5"	96.0"	14-15"	15"	18.7"	D12
31209	96.0/15.0-15	T	15.0"	30.5"	96.0"	14-15"	15"	18.7"	RD12
31303	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	RD12, D12, RD15, D15, RD20, D25
38133	90.0/14.0-15	T	15.0"	28.5"	90.0"	14-15"	14"	18.0"	MED
38137	15.0/90.0-15	T	15.0"	28.5"	90.0"	14-15"	15"	18.0"	H12
38143	92.0/14.0-15	T	15.0"	29.0"	92.0"	14-15"	14"	18.0"	MED
38146	92.0/14.0-15	T	15.0"	29.0"	92.0"	14-15"	14"	18.0"	RC1
38147	15.0/92.0-15	T	15.0"	29.0"	92.0"	14-15"	15"	18.5"	H12, H15
38153	94.0/14.0-15	T	15.0"	30.0"	94.0"	14-15"	14"	18.0"	MED
38156	94.0/14.0-15	T	15.0"	30.0"	94.0"	14-15"	14"	18.0"	RC1
38157	15.0/94.0-15 SH	T	15.0"	29.7"	93.5"	14-15"	15"	18.3"	H12
38159	15.0/94.0-15	T	15.0"	30.0"	94.0"	14-15"	15"	18.3"	H12, H15
38162	96.0/14.0-15	T	15.0"	30.5"	96.0"	14-15"	14"	18.5"	RC1, MED
38167	15.0/96.0-15	T	15.0"	30.5"	96.0"	14-15"	15"	18.7"	H12, H15
38214	104.0/16.0-15	T	16.0"	33.1"	104.0"	16-18"	17"	19.8"	RaceSaver
38221	105.0/16.0-15	T	16.0"	33.2"	105.0"	16-18"	17"	20.3"	H15, H20
38222	105.0/16.0-15	T	16.0"	33.1"	104.0"	16-18"	17"	20.3"	MED
38230	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	HTC, NRA, HTW
38231	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	Hard
38250	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	SC25

SOFT _____ D10 _____ RD12 _____ D12 _____ RD15 _____ D15 _____ HTW _____ MED (38222) _____ FIRM
 _____ NRA _____ D20 _____ SC25 _____
 _____ D25 _____ HARD _____
 _____ DT3 _____
 _____ RaceSaver _____
 _____ H12 _____ H15 _____ H20 _____
 _____ MED _____

NON-WING SPRINT / SILVER CROWN SHORT TRACK DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
31131	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D10, D12
31132	85.0/ 8.0-15	L	8.0"	27.0"	85.0"	8"	8"	10.5"	D15, D20
31183	92.0/14.0-15	T	15.0"	29.0"	92.0"	14"	14"	18.0"	D10
31203	94.0/14.0-15	T	15.0"	30.0"	94.0"	14"	14"	18.0"	D10
31225	96.0/14.0-15	T	15.0"	30.5"	96.0"	14"	14"	18.5"	RD12
31227	96.0/14.0 W-15	T	16.0"	30.5"	97.0"	15"	15"	19.0"	RD12
31237	98.0/14.0-15	T	15.0"	31.5"	98.0"	14"	14"	18.5"	RD12, D12
31239	98.0/14.0 W-15	T	16.0"	31.5"	99.0"	15"	15"	19.0"	RD12, D12
31249	100.0/13.0-15	S	13.2"	31.8"	100.0"	14"	14"	17.2"	D12
31303	105.0/18.0-15	C-2055 T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	RD12, D12, RD15, D15, RD20, D25
31253	103.0/14.0-15	T	14.5"	32.1"	102.0"	14"	14"	18.5"	RD12
38215	104.0/17.0-15	S	17.0"	33.0"	103.5"	16-18"	18"	21.0"	DT3
38222	105.0/16.0-15	T	16.0"	33.1"	104.0"	16-18"	17"	20.3"	MED
38232	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	HT2

SOFT _____ D10 _____ RD12 _____ D12 _____ D15 _____ D20 _____ RD20 _____ D25, DT3 _____ FIRM
 _____ HT2 _____
 _____ MED (38222) _____

SILVER CROWN DIRT / MILE TRACKS

A ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
31132	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D20, F75
31256	103.0/14.0-15	T	14.5"	32.1"	103.0"	14"	14"	18.5"	D50, F55
31303	105.0/18.0-15	C2055 T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	F85A, F95

SOFT _____ D20 _____ D50 _____ F55 _____ F75 _____ F85A _____ F95 _____ FIRM

MIDGET DIRT / MINI SPRINT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
35050	68.0/ 6.0-13	X	6.0"	21.0"	67.0"	6-7"	7"	7.8"	D12
35112	68.0/ 7.0-13	Y	7.0"	21.6"	68.0"	7-8"	7"	8.5"	D12, D15
35120	68.0/ 8.0-13	W	8.0"	22.1"	69-70"	8"	8"	9.5"	RD12, RD20
35140	74.0/10.0-13	Q	10.0"	23.7"	73-74"	8-10"	8"	11.7"	D10, D12, *FOCUS
35155	76.0/10.0-13	Q	10.0"	24.2"	75-76"	8"	8"	12.0"	D10, RD12, D12, *FOCUS
35161	77.0/10.0-13	Q	10.0"	24.5"	77.0"	8-10"	8"	12.0"	RD12, D12
35165	78.0/10.0-13	Q	10.0"	24.8"	78.0"	8"	8"	12.0"	D10, RD12, D12, *FOCUS, D20
35172	80.0/10.0-13	Q	10.0"	25.5"	79-80"	8"	8"	12.0"	D12, FOCUS
35234	82.0/12.0-13	T	12.0"	26.1"	82.0"	10-12"	10"	14.1"	RD12, SP2, SP3, SP4
35240	84.0/12.0-13	T	12.0"	26.7"	84.0"	10-12"	10"	14.1"	D10, RD12, RD15, D12, D15, RD20

SOFT _____ FIRM

D10 RD12 D12 RD15 D15 D20 RD20 SP4

*FOCUS SP2 FOCUS SP3

OVAL TRACK DIRT

MODIFIED MIDGET / MICRO SPRINT DIRT / JR. SPRINT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
42050	57.0/ 6.0-10	X	5.8"	18.0"	57.0"	5-6"	5"	6.8"	D10, D12, D15, D20
42100	57.0/ 6.5-10	L	7.0"	18.0"	57.0"	7"	7"	8.7"	D10, D12, D15, D20
42124	59.0/ 8.0-10	P	8.5"	18.5"	58.5"	8"	8"	9.5"	D10, RD12, RD15, RD20
42130	60.0/ 7.0-10	L	7.5"	19.0"	60.0"	7"	7"	9.0"	D12, D15, D20
42164	61.0/ 8.0-10	P	8.2"	19.0"	60.5"	8"	8"	10.1"	RD12, RD15
42168	61.0/10.0-10	P	10.2"	19.0"	60.5"	10"	10"	11.8"	RD12, RD15
42170	62.0/ 8.0-10	P	8.2"	19.7"	62.0"	8"	8"	10.1"	RD12, RD15
42172	62.0/10.0-10	P	10.0"	19.7"	62.0"	10"	10"	11.9"	D10, RD12, RD15
42173	63.0/ 8.0-10	P	8.2"	19.0"	63.0"	8"	8"	10.1"	RD12, RD15
42183	63.0/10.0-10	P	10.0"	20.0"	63.0"	10"	10"	12.0"	D10, RD12, RD15, RD20, D25
42185	64.0/ 8.0-10	P	8.2"	20.2"	64.0"	8"	8"	10.6"	RD12, RD15
42195	64.0/10.0-10	P	10.0"	20.2"	64.0"	10"	10"	12.5"	D10, RD12, RD15
42225	65.0/10.0-10	O	10.0"	20.5"	65.0"	10"	10"	11.5"	D10, RD12, D12, RD15, RD20
42237	69.0/10.0-10	O	11.0"	22.0"	69.0"	10-12"	10"	12.5"	D10, RD12, D12, RD15, D25, D28
42239	69.0/10.0 W-10	O	12.5"	22.0"	69-70"	10-12"	11"	14.7"	D10, RD12, D12, RD15, RD20, D20, D25, KS1, ASCS2
42400	15.0/ 6.0-8	aa	6.0"	15.0"	49.0"	6"	6"	7.4"	D12, RD20
42450	15.0/ 7.0-8	Q	7.0"	15.0"	49.0"	6"	6"	7.5"	RD20
42500	15.0/ 8.0-8	Q	8.0"	15.0"	49.5"	7"	7"	8.5"	RD20
42550	16.0/ 8.5-8	Q	8.5"	16.0"	53.5"	9"	9"	10.5"	RD20

SOFT _____ FIRM

D10 RD12 D12 RD15 D15 RD20 D20 D25

ASCS2 KS1 D28

OVAL TRACK DIRT

DIRT OVAL KARTING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
SOFT, WET, TACKY TRACK CONDITIONS									
11325	10.5 x 5.0-6	bb	4.75"	10.5"	32.75"	6.5"	6.5"	6.63"	D10A, D20A, D30A
11600	11.0 x 6.0-6	bb	6.0"	11.0"	33.0"	8.25-8.5"	8.5"	8.5"	D10A, D20A, D30A
11800	11.0 x 8.0-6	bb	7.5"	11.0"	34.0"	10"	10"	10.13"	D10A, D20A, D30A
INTERMEDIATE/TRANSITIONING TRACK CONDITIONS									
15305	10.5 x 5.0-6	bb	4.75"	10.5"	32.75"	6.5"	6.5"	6.63"	A40
15600	11.0 x 6.0-6	bb	6.0"	11.0"	33.0"	8.25-8.5"	8.5"	8.5"	A40
15800	11.0 x 8.0-6	bb	7.5"	11.0"	34.0"	10"	10"	10.13"	A40
HARD TRACK CONDITIONS									
15500	10.5 x 5.0-6	bb	4.75"	10.5"	32.5"	6.5"	6.5"	6.63"	50
15600	11.0 x 6.0-6	bb	6.0"	11.0"	33.0"	8.25-8.5"	8.5"	8.5"	50
15900	11.0 x 9.0-6	bb	9"	11.0"	34.0"	10"	10"	10.5"	50

TREADED KART

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
11900	11.0 x 5.5-6	aa	5.5"	11.0"	34.5"	6-6.5"	6.0"	6.375"	D10A, D20A, D30A
11920	11.0 x 6.5-6	aa	6.5"	11.0"	35.5"	6-5.8"	6.5"	7.125"	D10A, D20A, D30A
11940	12.0 x 8.0-6	Z	8.0"	12.0"	37.5"	9-10"	10.0"	9.75"	D10A, D20A, D30A
11960	12.0 x 9.0-6	Z	9.0"	12.0"	38.5"	9-10"	10.0"	10.25"	D10A, D20A, D30A, D50, D55

ASPHALT OVAL KARTING & 4-CYCLE SPRINT KARTING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
15305	10.5 x 5.0-6	bb	4.5"	10.5"	33.125"	6-6.5"	6"	6.25"	A40
15656	11.0 x 6.5-6	bb	6.25"	11.0"	34.75"	8-9"	8.5"	8.625"	A40
15745	11.0 x 7.1-6	bb	7.25"	11.0"	34"	9"	9"	8.875"	A40
15800	11.0 x 8.0-6	bb	7.875"	11.0"	34"	10"	10"	9.75"	A40

ASPHALT QUARTER MIDGET

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
15031	31.0/4.5-5	bb	4.5"	10.0"	31"	5-6"	5.5"	5.5"	A35
15032	32.0/4.5-5	bb	4.5"	10.25"	32"	5-6"	5.5"	5.5"	A35
15033	32.0/4.5-5 SH	bb	4.5"	10.25"	31.5"	5-6"	5.5"	5.5"	A35
USAC	.25 MIDGET	POSITION							
15325	33.0/5.0-6 NY1	RF	4.5"	10.5"	33.125"	6-6.5"	6"	6.25"	A35
15650	34.5/6.5-6 NY1	RR	6.0"	11.0"	34.5"	8-8.5"	8.5"	8.25"	A35

DIRT QUARTER MIDGET

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
11031	31.0/4.5-5	bb	4.5"	10.00"	31"	5-6"	5.5"	5.5"	D10, D20A, RD40
11032	32.0/4.5-5	bb	4.5"	10.25"	32"	5-6"	5.5"	5.5"	D10, D20A, RD40
11033	32.0/4.5-5 SH	bb	4.5"	10.25"	31.5"	5-6"	5.5"	5.5"	D20A
11325	10.5 x 5.0-6	bb	4.5"	10.5"	33.125"	6.0"	6.0"	6.25"	D20A, RD40
11650	11.5 x 6.5-6	bb	6.25"	11.5"	34.5"	8-8.5"	8.5"	8.25"	D20A, RD40
USAC	.25 MIDGET	POSITION							
11175	33.0/5.0-6	RF	4.5"	10.50"	33.125"	6-6.5"	6"	6.25"	D10, D30
11225	34.5/6.5-6	RR	6.25"	11.00"	34.5"	8-8.5"	8.5"	8.25"	D10, D30

SPRINT / SOLO / ROAD RACE KART

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
22150	4.5/10.0-5	bb	4.25"	10.0"	32"	5.0-5.5"	5.0"	5.5"	R60A, R60
22250	6.0/11.0-5	bb	5.5"	11.0"	34"	7.0-7.25"	7.0"	7.25"	R60A, R60
22370	7.1/11.0-5	bb	6.75"	11.0"	34.25"	8.0-8.25"	8.25"	8.625"	R60A, R60

SUPER KART

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
22500	5.0/10.5-6 CIK	bb	4.5"	10.5"	33.125"	6.0"	6.0"	6.25"	R60A
22800	8.0/11.0-6 CIK	bb	7.0"	11.0"	34.75"	8-9"	9.0"	9.25"	R60A

ENDURO KART SPECS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
22150	4.5/10.0-5	bb	4.25"	10.0"	32"	5"	5"	5.5"	R60A, R60
22250	6.0/11.0-5	bb	5.5"	11.0"	34"	7-7.25"	7"	7.25"	R60A, R60
22450	4.5/10.5-6	bb	4.25"	10.5"	33.0"	5"	5"	5.5"	R60
22500	5.0/10.5-6	bb	4.5"	10.5"	33.125"	6-6.5"	6"	6.25"	R60A, R60
22550	5.5/11.0-6	bb	4.75"	11.0"	34.25"	5-6"	5.5"	6.75"	R60
22800	8.0/11.0-6	bb	7.0"	11.0"	35"	8-9"	8"	8.375"	R60A

ATV

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS	APPLICATION
11940	12.0 X 8.0-6	Z	8.0"	12.0"	38.0"	9-10"	10"	9.75"	D10A, D20A, D30A	Youth ATV Rear
11960	12.0 X 9.0-6	Z	9.0"	12.0"	39.0"	9-10"	10"	10.25"	D10A, D20A, D30A	Youth ATV Rear
16110	18.0 X 11.0-10	hh	10.0"	18.0"	57.0"	10"	10"	11.0"	T10, T20	MX-Rear
16130	18.5 X 6.0-10	ff	6.0"	18.5"	59.0"	5"	5"	7.5"	T10	MX-Front
16250	18.0 X 5.5-10	X	5.5"	18.0"	57-58"	5"	5"	6.6"	D10, D12, RD20	Flat Track & TT
16275	18.5 X 8.0-10	P	8.5"	18.5"	59.0"	8"	8"	9.5"	RD12, D12, RD15, RD20	Flat Track & TT
16285	18.5 X 9.0-10	P	9.0"	18.5"	60-61"	8-10"	8"	10"	RD12, D12, RD15, RD20, RD30	Flat Track & TT
16325	18.5 X 10.0-10	P	10"	18.5"	59.0"	10"	10"	10.9"	D10, RD12, D12, RD15	Flat Track & TT
16600	20.5 X 6.0-10	cc	5.0"	20.5"	63.25"	5"	5"	6.5"	MX150	MX-Front
16700	18.0 X 10.0-8	dd	8.5"	18.0"	56.5"	8"	8"	9.625"	MX150	MX-Rear
16800	18.0 X 10.0-8 C2000	dd	8.5"	18.0"	56.3"	8"	8"	9.625"	MX150	MX-Rear
42400	15.0 X 6.0-8	aa	6.0"	15.0"	49.0"	6"	6"	7.4"	D12, RD20	Flat Track & TT
42450	15.0 X 7.0-8	Q	7.0"	15.0"	49.0"	6"	6"	7.5"	RD20	Flat Track & TT
42500	15.0 X 8.0-8	Q	8.0"	15.0"	49.0"	7"	7"	8.5"	RD20	Flat Track & TT
42550	16.0 X 8.5-8	Q	8.5"	16.0"	53.5"	9"	9"	10.5"	RD20	Flat Track & TT



WARNING: Not For recreational use. Hoosier ATV Tires are designed and manufactured for racing purpose only, within a closed course designed for organized competition. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

QUICK TIME D.O.T.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
17010	P175/70D-15	L	5.6"	24.5"	77.0"	5-6"	5"	7.0"	Quick Time Frt.
17030	P275/55D-14	L	8.5"	25.8"	81.0"	6-8"	8"	11.0"	Quick Time
17050	P245/60D-15	L	8.0"	26.2"	82.3"	6-8"	8"	11.3"	Quick Time
17100	P275/50D-15	L	10.0"	25.8"	81.0"	8-10"	8"	11.0"	Quick Time
17110	P275/60D-15	L	9.0"	27.3"	85.8"	8-10"	8"	11.3"	Quick Time
17120	P295/50D-15	L	10.0"	27.3"	85.8"	8-10"	8"	12.3"	Quick Time
17125	P295/60D-15	L	10.0"	29.6"	93.0"	8-10"	8"	12.0"	Quick Time
17130	P325/50D-15	L	10.5"	28.1"	88.3"	8-10"	8"	12.5"	Quick Time
17140	31 x 16.50-15 LT	L	14.0"	30.7"	96.5"	12-14"	14"	18.0"	Quick Time
17150	31 x 18.50-15 LT	L	15.0"	31.1"	97.5"	14-15"	14"	17.8"	Quick Time
17210	33 x 22.50-15 LT	L	17.0"	33.0"	103.5"	15-16"	15"	20.5"	Quick Time

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

KART/ATV

QUICK TIME

QUICK TIME PRO D.O.T.

QUICK TIME

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
17411	26 X 9.50-14 LT	D	8.0"	26.1"	82.0"	6-8"	8"	10.0"	Quick Time Pro
17415	26 X 9.50-15 LT	D	8.0"	26.1"	82.0"	6-8"	8"	10.0"	Quick Time Pro
17421	26 X 11.50-15 LT	D	10.0"	26.1"	83.0"	8-10"	8"	10.8"	Quick Time Pro
17431	26 X 9.50-16 LT	D	8.0"	26.1"	82.0"	6-8"	8"	9.3"	Quick Time Pro
17500	27 X 10.50-15 LT	D	9.0"	27.1"	85.0"	8-10"	8"	10.5"	Quick Time Pro
17510	27 X 11.50-15 LT	D	10.0"	27.1"	85.0"	8-10"	8"	11.3"	Quick Time Pro
17601	28 X 11.50-15 LT	D	10.0"	27.9"	87.5"	8-10"	8"	12.3"	Quick Time Pro
17603	28 X 11.50-16 LT	D	10.0"	27.9"	87.5"	8-10"	10"	11.8"	Quick Time Pro
17606	28 X 13.50-15 LT	D	11.0"	27.8"	87.3"	10-12"	10"	12.8"	Quick Time Pro
17611	28 X 14.50-15 LT	D	12.0"	27.7"	87.0"	10-12"	10"	13.3"	Quick Time Pro
17651	28 X 14.50-16 LT	D	11.6"	27.9"	87.5"	10-12"	10"	12.8"	Quick Time Pro
17700	29 X 11.50-15 LT	D	10.0"	29.0"	91.0"	8-10"	8"	12.8"	Quick Time Pro
17705	29 X 13.50-15 LT	D	11.0"	29.0"	91.0"	10-12"	10"	13.3"	Quick Time Pro
17710	29 X 14.50-15 LT	D	12.0"	29.2"	91.8"	10-12"	10"	13.8"	Quick Time Pro
17790	31 X 13.50-15 LT	D	11.0"	30.6"	96.0"	10-12"	10"	14.3"	Quick Time Pro
17800	31 X 16.50-15 LT	D	13.1"	30.9"	97.0"	12-14"	12"	15.8"	Quick Time Pro
17810	31 X 18.50-15 LT	D	15.0"	30.9"	97.0"	14-15"	14"	17.8"	Quick Time Pro
17900	33 X 18.50-15 LT	D	15.0"	33.0"	103.5"	14-15"	14"	18.5"	Quick Time Pro
17910	33 X 22.50-15 LT	D	17.0"	33.4"	105.0"	15-16"	15"	19.3"	Quick Time Pro

SOFT Quick Time Quick Time FIRM

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

DRAG RACING

DRAG RACING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
Drag Front									
18085	23.0/ 5.0-15	B	4.8"	23.0"	72.0"	3.5-4"	3.5"	5.5"	Drag Front
18095	24.0/ 5.0-15	B	4.8"	23.8"	75.0"	3.5-4"	3.5"	5.8"	Drag Front
18102	25.0/ 5.0-15	B	4.8"	24.8"	77.9"	3.5-4"	3.5"	6.3"	Drag Front
18105	26.0/ 4.5-15	B	4.3"	25.8"	81.0"	3.5-4"	3.5"	6.0"	Drag Front
18106	27.0/ 4.5-15	B	4.5"	27.0"	85.0"	3.5-4"	4"	6.8"	Drag Front
18107	28.0/ 4.5-15	B	4.5"	27.7"	87.0"	3.5-4"	4"	7.5"	Drag Front
18108	22.0/ 2.5-17	A	1.5"	22.0"	69.0"	2.5"	2.5"	2.7"	Dragster Front
18109	27.5/ 4.5-17	B	4.8"	27.6"	86.5"	3.5-4.5"	4.5"	7.5"	Drag Front
Drive Tires - Slicks									
18060	24.5/ 8.0-13	C	7.8"	24.3"	76.0"	6-8"	7"	9.0"	D06
18110	26.0/ 8.0-15	C	8.0"	26.1"	82.0"	7-8"	8"	9.7"	D06
18115	26.0/ 8.5-15*	C	9.0"	26.1"	82.0"	7-8"	8"	10.3"	C11
18120	26.0/ 9.0-15	C	9.0"	26.1"	82.0"	7-8"	8"	10.5"	D06
18131	26.0/10.0-15	C	10.0"	26.2"	82.0"	8-10"	9"	11.0"	D06
18140	28.0/ 9.0-15	C	9.0"	28.0"	88.0"	8-10"	8"	11.1"	D06
18150	28.0/10.0-15	C	10.0"	28.0"	88.0"	8-10"	8"	11.3"	D06
18153	28.0/10.0-16	C	10.0"	28.0"	88.0"	8-10"	10"	12.0"	C07
18155	28.0/10.5-15*	C	10.2"	28.0"	88.0"	8-10"	8"	11.3"	C07
18157	28.0/10.0-17	C	9.5"	28.0"	88.0"	8-10"	8"	10.3"	D06
18160	29.0/ 9.0-15	C	9.0"	29.1"	91.5"	8-10"	8"	11.3"	D06, D07
18170	29.0/10.0-15	C	10.0"	29.1"	91.5"	8-10"	8"	12.8"	D06
18175	29.0/10.5-15 W*	C	11.0"	29.3"	92.0"	8-10"	10"	13.0"	D06
18180	29.0/11.0-15	C	11.0"	29.3"	92.0"	8-10"	10"	13.2"	D06
18190	29.0/12.0-15	C	12.0"	29.3"	92.0"	10-12"	10"	13.7"	D06
18192	29.5/10.5-15	C	11.1"	30.6"	96.0"	10-12"	10"	13.2"	D06
18195	29.5/11.5-15 W*	C	13.5"	30.6"	96.0"	12-14"	12"	15.0"	D06
18200	30.0/ 9.0-15	C	9.0"	30.0"	94.0"	8-10"	8"	11.5"	D05, D07
18205	30.0/10.5-15	C	10.5"	30.0"	94.0"	8-10"	10"	13.3"	D05
18209	30.0/9.0R-15 Radial***	C	9.0"	29.5"	92.5"	8-10"	8"	11.0"	C06

DRAG RACING CONT.

DRAG RACING

DRAG RACING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
18210	30.0/9.0R-15 Radial	C	9.0"	29.5"	92.5"	8-10"	8"	11.0"	C07
18211	9.0/30.0R-15 Radial	C	9.0"	29.9"	94.0"	8-10"	8"	11.0"	C07
18212	9.0/30.0R-15 Radial***	C	9.0"	29.9"	94.0"	8-10"	8"	11.0"	C06
18214	30.0/10.5R-15 Radial***	C	10.5"	29.5"	92.5"	9-10"	10"	12.5"	C06
18215	30.0/10.5R-15 Radial	C	10.5"	29.5"	92.5"	9-10"	10"	12.5"	C07
18216	10.5/30.0R-15 Radial***	C	10.5"	29.9"	94.0"	9-10"	10"	12.5"	C06
18221	31.0/10.5-15*	C	11.0"	30.8"	97.0"	10-12"	12"	14.5"	C07
18225	31.0/12.0-15*	C	12.0"	30.8"	97.0"	10-12"	12"	16.0"	C11
18235	31.5/12.5-15 W*	C	13.5"	31.7"	99.5"	12-14"	14"	17.0"	D05
18237	13.5/31.5-15 L***	C	13.5"	31.7"	99.5"	12-14"	14"	17.2"	C07
18239	31.5/13.5R-15 Radial	C	13.5"	31.8"	99.7"	14-15"	14"	16.3"	C06
18240	31.0/14.0-15	C	14.0"	31.2"	98.0"	12-14"	12"	16.5"	D05
18242	32.0/12.0-15	C	12.2"	32.0"	101.0"	10-12"	12"	16.0"	D05
18243	32.0/13.0-15	C	13.2"	32.0"	101.0"	12-13"	12"	16.5"	D05
18245	32.0/13.5-15 W*	C	14.0"	32.3"	102.0"	12-14"	14"	17.5"	D05
18247	32.0/13.5R-15 Radial	C	13.5"	32.2"	101.5"	14-15"	14"	16.8"	C06
18250	32.0/14.0-15	C	14.0"	32.3"	102.0"	12-14"	14"	17.5"	D05
18255	14.0/32.0-15 L***	C	14.0"	32.3"	102.0"	12-14"	14"	17.5"	C07
18260	32.0/14.5-15 W*	C	15.0"	32.6"	102.5"	14-15"	14"	18.0"	D05
18265	14.5/32.0-15 L***	C	15.0"	32.3"	102.0"	14-15"	14"	18.0"	C07
18267	32.0/14.5R-15 Radial	C	15.0"	32.2"	101.2"	14-16"	14"	17.8"	C06
18300	32.5/16.5-15*	C	16.7"	32.3"	101.5"	15-16"	15"	19.5"	C07
18332	33.0/10.5-15 Outlaw	C	10.8"	33.0"	104.0"	10-12"	12"	15.5"	C11
18350	33.0/12.0-15	C	12.2"	33.0"	102.0"	10-12"	10"	15.3"	C09
18367	14.5/33.0-15 L***	C	14.5"	33.0"	104.0"	14-16"	14"	17.8"	C07
18370	33.0/15.0-15*	C	15.0"	33.0"	104.0"	14-15"	14"	18.3"	D05
18400	33.0/16.0-15*	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	D05, D06, C07
18450	33.0/16.5-15 S**	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	D06, C07
18500	33.0/17.0-16*	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	C07
18600	33.5/16.0-15*	C	17.0"	33.6"	106.0"	15-16"	15"	19.5"	C07
18640	33.5/16.5-16 S**	C	17.0"	33.6"	106.0"	15-16"	16"	19.5"	C07
18650	33.5/17.0-16*	C	17.0"	33.6"	106.0"	15-16"	16"	19.5"	C07
18700	33.5/17.0-16	C	17.0"	33.6"	106.0"	15-16"	16"	20.3"	C06
18770	15.0/34.5-16	C	15.0"	35.0"	110.0"	15-16"	16"	19.5"	C1500
18780	17.0/34.5-16	C	17.0"	35.0"	110.0"	15-16"	16"	20.0"	C2055
18790	34.5/17.0-16	C	17.0"	35.0"	110.0"	15-16"	16"	21.0"	C2055
18900	36.0/17.0-16	C	17.0"	36.2"	114.0"	15-16"	16"	21.3"	C2055
18910	17.0/36.0-16	C	17.0"	36.2"	114.0"	15-16"	16"	20.5"	C2055

SOFT	JR3	C06 C07	C11	Drag Front	FIRM
	D05	D06	D07	N/TF C09	

* STIFF SIDEWALL
 ** SOFT SIDEWALL
 *** LIGHTWEIGHT

JR DRAGSTER

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
18030	18.0/ 8.0-8	C	7.7"	17.7"	56.0"	7-8"	8"	9.9"	JR3
18040	18.0/ 10.0-8	C	9.5"	17.7"	56.0"	8-10"	8"	10.6"	JR3

RACING TUBES & LINER

ITEM NUMBER	TUBE SIZE	COMPOUNDS
288088-15	80/ 88-15 TUBE	WILL FIT 80" TO 88" CIRC. 6" TO 11" TREAD WIDTH
2886100-15	86/100-15 TUBE	WILL FIT 86" TO 100" CIRC. 11" TO 13" TREAD WIDTH
2894106-15	94/106-15 TUBE	WILL FIT 94" TO 106" CIRC. 15" TO 19" TREAD WIDTH
32400	75/16.0-16 LINER	FOR USE WITH ITEM NUMBERS 18780, 18790, 18900, 18910

D.O.T. DRAG RADIALS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
17310	P225/50R15	E	8.5"	23.8"	74.8"	7-9"	7"	9.5"	
17313	P295/55R15	E	10.3"	27.8"	87.3"	8-10"	9.5"	12.5"	
17314DR2	P235/60R15	ii	8.6"	26.2"	82.3"	7-9"	7"	10.0"	DR2
17315	P275/50R15	E	9.5"	25.7"	80.8"	8-10"	8.5"	10.3"	
17316DR2	P295/65R15	ii	10.0"	29.6"	92.6"	8-10"	8.5"	12.0"	DR2
17317	P275/60R15	E	10.0"	27.7"	87.0"	8-10"	8"	11.5"	
17318	P325/50R15	E	11.75"	27.7"	87.0"	9-11"	10"	13.5"	
17319DR2	P315/60R15	ii	TBD"	TBD"	TBD"	9-11"	TBD"	TBD"	DR2
17320	P225/50R16	E	8.8"	24.8"	78.0"	7-9"	7"	9.5"	
17325	P255/50R16	E	9.5"	26.1"	82.0"	8-10"	8"	10.5"	
17326	P295/50R16	E	10.5"	27.7"	87.0"	8-10"	9"	12.0"	
17327	P225/45R17	E	8.5"	24.8"	78.0"	7-8.5"	8"	9.5"	
17328	P245/45R17	E	9.4"	25.7"	80.8"	7.5-9"	8"	9.8"	
17330	P275/40R17	E	9.8"	25.6"	80.5"	9-11"	10"	11.3"	
17332	P315/35R17	E	11.5"	25.8"	81.0"	9-11"	11"	12.8"	
17335	P335/35R17	E	12.0"	25.7"	80.8"	11-13"	12"	13.8"	
17340	P245/40R18	E	8.8"	26.0"	81.5"	7-9"	9"	10.2"	
17342	P315/30R18	E	11.0"	25.8"	81.0"	11-12"	11"	12.5"	
17343DR2	P325/45R18	ii	11.2"	30.2"	94.7"	10-12"	11"	13.1"	DR2
17345	P335/30R18	E	12.2"	26.0"	81.5"	12-13"	12"	13.0"	
17375	P275/60R15	ii	TBD"	TBD"	TBD"	8-10"	TBD"	TBD"	DR2

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

ROAD RACING SLICKS – BIAS

ITEM NUMBER	TIRE SIZE	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
43101	18.0 x 6.0-10	C2000 F500	6.2"	18.1"	57.0"	6"	6"	8.1"	R25B
43105	18.0 x 7.5-10	F500	7.5"	18.3"	57.5"	7-8"	8"	9.5"	R25B, R35A
43110	19.5 x 6.5-10	F500	6.5"	19.4"	61.0"	6"	6"	8.2"	R25B
43120	19.5 x 7.5-10	F500	7.5"	19.5"	61.2"	7-8"	8"	9.5"	R25B
43127	20.5 x 6.0-13	A2500 FF	6.0"	20.9"	65.7"	5.5"	5.5"	7.0"	R25B
43130	20.0 x 6.0-13	CF	6.0"	20.7"	65.0"	5.5-6.5"	5.5"	7.0"	R60A
43163	20.5 x 7.0-13	F1600	6.75"	20.8"	66.2"	6-8"	6"	8.0"	F1600
43163	20.5 x 7.0-13	A2500 FB, FC, FM, SR	6.75"	20.8"	66.2"	6-8"	6"	8.0"	R25B, R35A, R45B
43168	20.0 x 7.5-13	A2500 SR	8.0"	20.6"	65.0"	6-9"	8"	9.4"	R25B, R35A
43171	20.0 x 8.0-13	C3000 FP, HP, GT3, GTL	8.0"	20.0"	63.0"	5-6"	6"	9.2"	R35A, R45B
43186	20.0 x 9.0-13	A2500 FA, SR	9.75"	20.6"	64.7"	8-10"	10"	11.0"	R25B, R35A
43191	20.0 x 9.5-13	C3000 EP, FP, GT3, GTL	9.4"	20.0"	63.0"	7"	7"	10.5"	R35A, R45B
43271	21.5 x 8.0-13	SCCA-F, SR	8.2"	21.4"	66.8"	8"	8"	9.5"	FE SCCA
43288	22.0 x 8.0-13	A2500 FA, FB, FC, FM, SR	8.1"	22.1"	69.2"	8-10"	8"	9.5"	R25B, R35A
43292	22.0 x 9.0-13	A2500 FA, FB, FC, FM, SR	8.8"	22.0"	69.5"	8-10"	8"	10.0"	R25B, R35A, R45B
43303	22.0 x 10.0-13	SCCA-F, SR	9.8"	22.3"	70.0"	10"	10"	11.0"	FE SCCA
43307	22.5 x 7.2-13	CF	7.25"	22.6"	71.0"	5.5"	5.5"	9.8"	R60A
43309	22.5 x 7.2-13	F1600	7.25"	22.6"	71.0"	5.5"	5.5"	9.8"	F1600
43309	22.5 x 7.2-13	A2500 FF	7.25"	22.6"	71.0"	5.5"	5.5"	9.8"	R25B, R35A, R45B
43311	22.5 x 9.0-13	A2500 FM, SR	9.0"	22.6"	71.0"	8-10"	10"	10.1"	R35A, R45B
43314	22.5 x 10.0-13	A2500 SR	9.8"	22.6"	71.0"	8-10"	10"	11.0"	R25B, R35A
43319	23.0 x 12.0-13	A3000 FA, SR	12.0"	23.6"	74.1"	12-15"	15"	15.9"	R25B, R35A
43336	21.0 x 5.0-15	C3000 FV	5.0"	21.2"	66.5"	4"	4"	5.5"	R55A
43352	22.5 x 5.5-15	C3000 FV	5.5"	21.9"	69.0"	4"	4"	6.5"	R55A
43374	23.0 x 8.5-15	C3000 EP, FP, GT3, GTL	8.2"	22.8"	71.5"	6-7"	7"	9.4"	R45B
43384	23.0 x 9.5-15	C3000 EP, FP, GT3, GTL	9.2"	22.8"	71.5"	6-7"	7"	9.4"	R35A, R45B
43481	23.5 x 11.5-16	C4000 GT2	11.0"	23.8"	75.0"	10-12"	12"	12.5"	R35A, R45B
43499	25.0 x 13.0-16	C5000 GT1, GT2	13.0"	25.3"	79.5"	12"	12"	13.5"	R35A, R45B
43537	27.0 x 14.0-16	C5000 GT1	13.8"	26.7"	84.0"	12-13"	12"	14.5"	R35A, R45B

ALL TREAD PATTERNS bb

SOFT ————— R25B ————— R35A ————— F1600 ————— R45B ————— F5A ————— R55A ————— R60A ————— FIRM

ROAD RACING SLICKS – RADIAL

ITEM NUMBER	TIRE SIZE	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUNDS
43541	20.5 x 7.0R13	F2000	7.2"	20.8"	66.0"	6"	6"	7.8"	
43544	22.5 x 8.0R13	F2000	8.3"	22.4"	70.5"	8"	8"	9.5"	
43547	200/580R15	RADICAL	8.0"	22.9"	71.9"	6.5-8"	8"	8.8"	R35A
43548	190/530R13	PROD., GT	7.3"	20.8"	65.3"	6-7"	6"	7.8"	S80
43549	215/530R13	PROD., GT	8.3"	20.8"	65.4"	6-7"	7"	8.8"	S75, S80
43558	215/580R15	PROD., GT	8.6"	22.9"	71.8"	7-9"	7"	9.7"	S80, S100
43568	245/580R15	PROD., GT	9.4"	22.9"	71.8"	7-10"	7"	10.0"	S80, S100
43571	23.0 x 9.5R15	FA	9.4"	22.9"	72.0"	10"	10"	10.7"	R25B, FA
43585	23.5 x 13.0R15	FA	13.0"	23.5"	73.8"	14"	14"	14.5"	R25B
43586	24.5 x 13.75R15	FA	13.75"	24.5"	77.0"	14"	14"	14.5"	R25B, FA
43590	27.5 x 11.5R15	HSCF	11.5"	27.4"	86.0"	10"	9.5"	12.8"	
43595	27.5 x 11.5R15	HSCR	11.5"	27.4"	86.0"	10"	9.5"	12.8"	
43656	23.5 x 11.0R16	GT2	10.6"	23.6"	74.0"	10"	10"	11.0"	R75A
43661	23.5 x 12.0R16	GT2	12.0"	23.5"	73.8"	12"	12"	13.0"	R75A
43662	265/605R16	RADICAL	9.7"	23.9"	75.1"	9-10"	10"	10.9"	R35A
43672	25.5 x 12.5R16	C2000 GT1	12.4"	25.8"	81.0"	12"	12"	13.3"	R75A
43677	25.5 x 14.0R16	C2000 GT1	13.6"	25.7"	80.9"	12"	12"	14.1"	R75A
43692	28.0 x 14.0R16	C2000 GT1	13.9"	28.2"	88.5"	13"	13"	15.1"	R75A
43725	235/620R17		8.8"	24.3"	76.5"	8-9.5"	9"	9.6"	S100
43740	265/630R17		10.1"	24.8"	77.9"	9-10"	10"	10.7"	S100
43821	240/640R18		9.1"	25.6"	80.4"	8-9.5"	9"	9.8"	S80, S100
43830	255/645R18		9.8"	25.5"	80.0"	10"	10"	10.9"	S80
43836	265/645R18		10.1"	25.5"	80.0"	9-10"	10"	10.9"	S80, S100
43851	280/680R18		10.0"	26.9"	84.6"	9-11"	10"	11.3"	S100
43856	285/645R18		10.9"	25.5"	80.0"	10-12"	11"	11.7"	S80, S100
43864	305/645R18		11.8"	25.6"	80.6"	11-13"	12"	12.7"	S80, S100
43866	305/680R18		12.0"	26.7"	84.0"	13"	13"	13.5"	S100
43871	320/650R18		12.0"	25.8"	80.8"	11-13"	12"	13"	S100
43891	345/710R18		12.5"	28.2"	88.4"	10-12"	12"	13.6"	S100
43896	355/650R18		13.8"	25.7"	80.8"	12-14"	13"	14.2"	S100
43915	235/645R19		8.5"	25.5"	80.1"	8-9.5"	9"	9.5"	R100
43945	295/680R19		9.8"	26.9"	84.5"	10-12"	11"	11.7"	R100

ALL TREAD PATTERNS bb

SOFT — R25B — FA — R35A — R75 — R45B — S80 — S100 — FIRM

ROAD RACING WETS – BIAS

ITEM NUMBER	TIRE SIZE	TREAD PATTERNS	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH
44115	18.0 x 6.0-10	Y	F500	6.2"	17.8"	56.0"	6-8"	8"	7.8"
44125	19.5 x 6.5-10	I	F500	6.2"	19.7"	62.0"	6-8"	8"	8.2"
44150	20.0 x 7.5-13	I	CSR, FA	7.4"	20.6"	64.6"	7-8"	7"	8.3"
44185	21.0 x 6.5-13	I	FF, FM, FC, S2000, DSR	6.7"	21.2"	66.5"	6-8"	6"	7.2"
44195	21.5 x 7.5-13	I	SCCA-F, SR	7.5"	21.4"	66.8"	8.0"	8"	8.8"
44217	22.0 x 9.0-13	I	SCCA-F, SR, FC, FA, FM, S2000, DSR, CSR	8.5"	22.9"	71.8"	8.5-10"	8"	10.0"
44220	22.5 x 7.5-13	I	FF	7.5"	22.8"	71.5"	5.5-6.0"	5.5"	9.8"
44266	22.5 x 5.0-15	I	FV	5.0"	22.0"	69.2"	4"	4"	6.5"
44275	22.5 x 9.0-15	I	FA	8.8"	22.4"	70.5"	10"	10"	10.1"
44280	23.5 x 11.5-15	I	FA	11.5"	23.7"	74.5"	14"	14"	14.8"
44307	27.0 x 10.0-15	L	HSC/GTA	10.0"	27.0"	84.0"	10-11"	10"	12.5"

ROAD RACING WETS – RADIAL

ITEM NUMBER	TIRE SIZE	TREAD PATTERNS	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH
44441	20.5 x 7.0R-13		F2000	7.2"	20.8"	65.3"	6"	6"	7.8"
44444	22.5 x 8.0R-13		F2000	8.3"	22.4"	70.5"	8"	8"	9.8"
44670	25.5 x 12.0R-16WET	J	GT1, GT2	12.2"	25.7"	80.9"	12"	12"	13.2"
44690	28.0 x 12.5R-16WET	J	GT1	13.6"	27.3"	85.7"	12"	12"	14.2"

TREAD PATTERN IS HAND GROOVED.

ROAD RACING SLICKS

ROAD RACING SLICKS

SPORTS CAR D.O.T. - BIAS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	STREET T.D. S	WET
45100	P185/60D-13	H	6.2"	20.6"	64.7"	5-7"	5"	7.0"	X	
45110	P205/60D-13	H	6.2"	22.4"	70.5"	5.5-7"	5.5"	7.5"	X	
45111DS	P205/60D-13*	L	6.8"	21.9"	68.8"	5.5-7.5"	5.5"	7.8"		X
45115	P225/45D-13	H	7.8"	20.8"	65.5"	6.5-8.5"	7.5"	9.0"	X	
45120	P205/60D-14	H	7.2"	23.0"	72.3"	6-8"	5.5"	8.3"	X	
45140	P225/50D-14	H	7.8"	23.0"	72.5"	7-9"	6"	8.8"	X	
45150	P205/50D-15	H	6.7"	23.0"	72.5"	5.5-7"	6"	7.6"	X	
45160	P225/45D-15	H	7.6"	23.0"	72.5"	6.5-8.5"	7.5"	8.5"	X	
45170	P225/50D-15	H	7.0"	24.0"	75.5"	6.5-8.5"	6"	8.5"	X	
45180	P225/60D-15	H	8.0"	25.8"	81.0"	7-9"	6"	9.2"	X	
45165	P245/45D-15	H	8.5"	24.0"	75.5"	7.5-9.5"	8"	10.0"	X	
45190	P245/60D-15	H	8.0"	26.4"	83.0"	7-9.5"	7"	10.0"	X	
45200	P275/60D-15	H	9.5"	27.6"	86.5"	8.5-10"	7.5"	11.0"	X	

*DS RECOMMENDED FOR WET APPLICATION ONLY.

VINTAGE & HISTORIC

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	MODEL
44391	165/70-10	H	5.2"	18.8"	59.0"	5-6"	5.5"	7.3"	HOOSIER T.D. S
45105	A70-13	H	6.2"	22.4"	70.3"	5-7"	5"	7.5"	STREET T.D. S
44286	25.5 X 8.5-15	H	8.7"	25.4"	79.7"	8-10"	8"	10.3"	HOOSIER T.D. S
44296	25.5 X 10.0-15	H	10.0"	25.8"	81.0"	8-11"	8"	11.2"	HOOSIER T.D. S
44306	26.5 X 9.5-15	H	9.5"	26.6"	83.5"	8-10"	8"	11.0"	HOOSIER T.D. S
44316	27.5 X 11.0-15	H	11.0"	27.7"	87.0"	10-13"	10"	13.2"	HOOSIER T.D. S
44336	24.0 X 8.5-16	H	8.2"	24.1"	75.4"	8-10"	8"	10.5"	HOOSIER T.D. S
44346	25.5 X 10.0-16	H	10.0"	25.6"	80.5"	9-11"	9"	11.3"	HOOSIER T.D. S
44400	5.00-15	L	5.2"	24.7"	77.6"	4-6"	4"	7.0"	VINTAGE T.D.
44405	120/590-15	L	4.8"	22.6"	70.9"	4.5"	4.5"	6.1"	VINTAGE T.D.
44408	135/620-15	L	5.6"	24.1"	75.6"	4.5"	4.5"	6.9"	VINTAGE T.D.
44410	5.50-15	L	6.5"	24.7"	77.6"	4.5-7"	4.5"	7.7"	VINTAGE T.D.
46010	P185/65R15	G	6.4"	24.2"	76.0"	5.0-6.5"	5"	7.0"	SPEEDSTER
46015	P205/60R15	G	7.3"	24.2"	76.0"	5.5-7.5"	6.5"	8.25"	SPEEDSTER

S = Stiff Sidewall

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

SPORTS CAR D.O.T. - RADIAL

SPORTS CAR D.O.T.

SPORTS CAR D.O.T.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	A-7 AUTO CROSS	R-7 ROAD RACE
46301	P185/60ZR13	ii	6.9"	21.7"	68.2"	6.0-7.0"	6.0"	7.8"		X
46306	P205/60ZR13	ii	8.0"	22.8"	71.7"	5.5-7.5"	6.0"	8.8"		X
46308	P225/45ZR13	ii	8.5"	20.9"	65.8"	7.0-8.5"	7.5"	9.3"	X	X
46311	P225/50ZR13	ii	8.5"	21.9"	69.0"	6.0-8.0"	7.0"	9.4"		X
46321	P255/40ZR13	ii	9.5"	20.9"	65.6"	8.5-10.0"	9.0"	10.5"	X	
46406	P205/55ZR14	ii	8.1"	22.8"	71.6"	5.5-7.5"	7.0"	9.1"		X
46410	P205/60ZR14	ii	7.8"	23.6"	74.2"	7.0-8.0"	6.0"	8.2"		X
46416	P225/50ZR14	ii	8.5"	22.9"	72.0"	6.0-8.0"	7.0"	9.4"	X	X
46502	P205/50ZR15	ii	8.0"	22.8"	71.8"	5.5-7.5"	6.5"	8.5"	X	X
46501	P205/50ZR15 SM7	E	8.0"	22.8"	71.7"	5.5-7.5"	6.5"	8.7"		X
46511	P225/45ZR15	ii	8.5"	22.8"	71.8"	7.0-8.5"	7.5"	9.3"	X	X
46516	P225/50ZR15	ii	8.8"	23.8"	74.8"	6.0-8.0"	7.0"	9.7"		X
46522	P245/40ZR15	ii	9.0"	23.0"	72.0"	8.0-9.5"	8.5"	10.0"	X	X
46526	P245/50ZR15	ii	9.4"	24.4"	76.2"	7.0-8.5"	7.5"	10.3"		X
46536	P275/35ZR15	ii	10.1"	23.0"	72.2"	9.0-11.0"	9.5"	10.8"	X	X
46540	P275/50ZR15	ii	10.0"	25.5"	80.0"	7.5-9.5"	8.0"	10.8"		X
46601	P205/45ZR16	ii	8.0"	23.0"	72.1"	7.0-8.5"	7.0"	8.5"	X	X
46611	P225/50ZR16	ii	8.8"	24.7"	77.6"	6.0-8.0"	7.0"	9.4"	X	X
46616	P245/45ZR16	ii	9.5"	24.4"	76.5"	7.5-9.0"	8.0"	10.3"	X	X
46630	P275/45ZR16	ii	10.3"	25.6"	80.5"	8.5-10.0"	9.0"	11.2"	X	X
46706	P225/40ZR17	ii	9.0"	23.8"	74.8"	8.0-9.5"	8.0"	9.6"	X	X
46711	P225/45ZR17	ii	9.0"	24.7"	77.8"	7.0-8.5"	7.5"	9.7"	X	X
46716	P245/40ZR17	ii	9.7"	24.3"	76.0"	8.0-9.5"	8.5"	10.3"	X	X
46729	P275/35ZR17	ii	10.3"	24.7"	77.7"	9.0-11.0"	9.5"	11.0"	X	X
46730	P275/40ZR17	ii	10.3"	25.5"	80.1"	9.0-11.0"	9.5"	11.0"	X	X
46733	P295/35ZR17	ii	10.8"	25.3"	79.5"	9.5-11.0"	10.0"	11.6"	X	X
46735	P315/35ZR17	ii	11.4"	25.6"	80.4"	11.0-12.0"	11.0"	12.6"	X	X
46740	P335/35ZR17	ii	12.9"	25.6"	80.5"	11.0-13.0"	12.0"	13.6"	X	X
46811	P225/40ZR18	ii	8.8"	24.7"	77.6"	7.5-9.0"	8.0"	9.6"		X
46821	P245/35ZR18	ii	9.4"	24.4"	76.7"	8.0-9.5"	8.5"	9.9"	X	X
46826	P245/40ZR18	ii	9.0"	25.4"	79.8"	8.0-9.5"	8.5"	10.3"	X	X
46832	P255/35ZR18	ii	10.3"	24.8"	77.8"	8.5-10.0"	9.0"	10.8"	X	X
46836	P275/35ZR18	ii	10.3"	25.5"	80.2"	9.0-11.0"	9.5"	10.7"	X	X
46840	P285/30ZR18	ii	10.9"	24.9"	78.1"	10.0-11.0"	10.0"	11.5"	X	X
46843	P295/30ZR18	ii	10.8"	25.3"	79.5"	9.5-11.0"	10.0"	11.6"	X	X
46846	P315/30ZR18	ii	11.8"	25.6"	80.5"	11.0-12.0"	11.0"	12.5"	X	X
46850	P335/30ZR18	ii	12.8"	25.6"	80.5"	12.0-13.0"	12.0"	13.5"	X	X
46855	P345/35ZR18	ii	13.2"	26.8"	84.2"	11.0-13.0"	12.0"	13.9"	X	X
46916	P235/35ZR19	ii	9.2"	25.6"	80.5"	8.0-9.5"	9.0"	10.2"	X	X
46925	P265/35ZR19	ii	9.6"	26.2"	82.25"	9.0-10.0"	9.0"	10.4"	X	X
46935	P295/30ZR19	ii	10.4"	26.1"	82.1"	10.0-12.0"	10.0"	11.5"	X	X
46937	P315/30ZR19	ii	12.0"	26.1"	82.2"	11.0-12.0"	11.0"	12.5"	X	X
46945	P325/30ZR19	ii	12.2"	26.8"	84.1"	12.0-13.0"	13.0"	13.6"	X	X
46950	P345/30ZR19	ii	13.0"	26.8"	84.3"	12.0-13.0"	13.0"	14.1"	X	X

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE.** It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

SPORTS CAR D.O.T. RADIAL WET

ITEM NUMBER	TIRE SIZE	SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH
46100	P185/60R13	86H	J	6.8"	21.7"	68.1"	5-6"	6.0"	7.7"
46105	P205/60R13	86H	J	7.1"	23.5"	73.8"	6-7.5"	6.0"	8.5"
46115	P205/55R14	85H	J	7.1"	23.5"	73.8"	6.5-7.5"	6.5"	8.7"
46125	P205/50R15	84H	J	7.1"	23.5"	73.8"	6.5-7.5"	6.5"	8.2"
46127	P225/45R15	81H	J	8.9"	22.9"	72.0"	7-8.5"	8.0"	9.4"
46130	P225/55R15	92H	J	8.8"	24.8"	77.9"	7-8"	7.0"	9.4"
46135	P205/45R16	77H	J	7.1"	23.5"	73.8"	7-7.5"	7.0"	8.4"
46140	P225/50R16	91H	J	8.8"	24.8"	77.9"	7-9"	7.0"	9.6"
46145	P245/45R16	88H	J	9.0"	24.8"	77.9"	7-9"	8.0"	10.0"
46150	P255/50R16	99H	J	9.3"	26.3"	82.5"	8-9"	8.0"	10.7"
46160	P315/40R16	99H	J	12.0"	25.6"	80.6"	11-12"	12.0"	13.4"
46165	P355/40R16	130H	J	13.1"	27.0"	84.6"	12-13"	12.0"	14.9"
46170	P225/45R17	84H	J	8.8"	24.8"	77.9"	8-9"	7.5"	9.5"
46175	P245/40R17	86H	J	9.0"	24.8"	77.9"	7-9"	8.0"	10.0"
46177	P245/45R17	89H	J	9.0"	25.5"	80.1"	7-9"	8.0"	10.0"
46185	P275/40R17	93H	J	10.0"	25.2"	79.2"	9-11"	9.5"	11.3"
46190	P315/35R17	93H	J	11.8"	25.6"	80.4"	11-12"	11.0"	12.7"
46200	P225/40R18	83H	J	8.8"	24.8"	77.9"	7-9"	8.0"	9.9"
46205	P245/35R18	80H	J	9.0"	24.8"	77.9"	7-9"	8.0"	10.0"
46207	P245/40R18	88H	J	8.75"	25.5"	80.25"	8-9.5"	9.0"	9.75"
46215	P275/35R18	87H	J	10.0"	25.2"	79.2"	10-11"	9.5"	11.3"
46220	P305/30R18	89H	J	11.8"	25.6"	80.4"	11-12"	11.0"	12.7"
46230	P325/35R18	130H	J	12.0"	27.0"	84.6"	11-12"	12.0"	13.3"
46240	P235/35R19	89H	J	8.1"	25.5"	80.3"	8-9.5"	9.0"	9.3"
46250	P295/30R19	89H	J	10.0"	26.2"	82.2"	9-11"	11.0"	12.0"
46260	P325/30R19	130H	J	12.0"	27.0"	85.0"	11-12"	12.0"	13.2"

WARNING: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

NOTE: H Speed Rating = 130 mph/210 km/h.

PRO STREET D.O.T. RADIAL

ITEM NUMBER	TIRE SIZE	SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	MAX. LOAD	RATED INF. PSI	MODEL
Fronts												
19030	24 x 7.50R-15 LT	71H	F	5.3"	23.8"	73.3"	5-6.5"	6"	7.5"	760	35	Pro Street
19040	25 x 7.50R-15 LT	75H	F	5.3"	24.9"	76.9"	5-6.5"	6"	7.5"	855	35	Pro Street
19050	26 x 7.50R-15 LT	79H	F	5.3"	25.9"	80.5"	5-6.5"	6"	7.5"	965	35	Pro Street
19055	26 x 7.50R-17 LT	74H	F	5.3"	25.9"	80.5"	5-6.5"	6"	7.5"	825	35	Pro Street
19075	27 x 10.50R-15 LT	88H	F	8.3"	26.5"	82.8"	7-9.0"	8.5"	10.5"	1235	35	Pro Street
19100	28 x 9.50R-15 LT	90H	F	8.0"	27.0"	85.0"	7.5-9.0"	8.0"	9.75"	1325	35	Pro Street
19150	29 x 12.50R-15 LT	97H	F	10.0"	29.0"	90.8"	8.5-11"	10"	13.0"	1610	35	Pro Street
19200	29 x 15.50R-15 LT	99H	F	12.1"	29.0"	91.5"	11-13"	12"	15.2"	1710	35	Pro Street
19250	29 x 18.50R-15 LT	101H	F	14.6"	29.0"	91.3"	13-16"	14"	17.8"	1820	35	Pro Street
19275	31 x 12.50R-15LT	103H	F	10.3"	31.0"	96.5"	8.5-11"	10"	13.4"	1930	35	Pro Street
19300	31 x 16.50R-15 LT	106H	F	12.8"	31.0"	96.3"	12-14"	12"	16.0"	2095	35	Pro Street
19315	31 x 16.50R-16 LT	104H	F	12.8"	31.0"	96.8"	12-14"	12"	16.0"	1985	35	Pro Street
19350	31 x 18.50R-15 LT	108H	F	14.5"	31.0"	96.3"	13-16"	14"	18.0"	2205	35	Pro Street
19410	33 x 21.50R-15 LT	115H	F	16.8"	32.0"	100.8"	15-19"	17"	21.3"	2680	35	Pro Street

WARNING: "Pro Street Tires are designed for highway use and are not suitable for racing purposes."

NOTE: H Speed Rating = 130 mph / 210 km/h

the
tradition
lives on

Bob Newton
(1927 - 2012)



Scotty Merrill • Joyce Newton • Marge Skaggs

Hoosier®

RACING TIRE

65465 U.S. 31 ♦ Lakeville, IN 46536
(574) 784-3152 ♦ Fax: (574) 784-2385
www.hoosiertire.com

In honor of Hoosier Tire Co-founder, Bob Newton, and the values established over 50 years ago, the current leadership team is proud to lead the next generation of race enthusiasts into the future!

We're happy to present our high performance racing tires and our apparel and accessories catalog in hopes that these quality products will help you show winning Hoosier spirit everywhere you go!

On behalf of the Hoosier Racing family, thanks for your support and enthusiasm.



Visit Your Local Hoosier Tire Distributor
To See the NEW 2015 High Performance
Racing Tires and Apparel Line Up!

“TIRES DESIGNED FOR CHAMPIONS”®

Hoosier[®]

RACING TIRE

CORPORATE

65465 U.S. 31 ♦ Lakeville, IN 46536
 (574) 784-3152 ♦ Fax: (574) 784-2385
www.hoosiertire.com

OUR DISTRIBUTORS

Hoosier[®]

TIRE EAST
 56-H Loomis Street ♦ Manchester, CT 06042
 Phone: (860) 646-9646 ♦ Fax: (860) 646-2054
 E-mail: rob@hoosiertireeast.com

Hoosier[®]

TIRE SOUTH
 Asphalt
 P.O. Box 537 ♦ Welcome, NC 27374
 Phone: (336) 731-6100 ♦ Fax: (336) 731-6086
 E-mail: hoosierasp@lexcominc.net

Hoosier[®]

TIRE MIDWEST
 Springfield
 3886 E. State Route 54 ♦ Springfield, IL 62707
 Phone: (217) 522-1955 ♦ Fax: (217) 670-0746
 E-mail: jessica@racetires.com ♦ www.racetires.com

Hoosier[®]

TIRE MID-ATLANTIC
 Baltimore
 2931 Industrial Park Drive ♦ Finksburg, MD 21048
 Phone: (410) 833-2061 ♦ Fax: (410) 833-5921
 E-mail: sales@hoosiermidatlantic.com ♦ www.hoosiermidatlantic.com

Hoosier[®]

TIRE SOUTHWEST
 103 Gross Road, Bldg. A ♦ Mesquite, TX 75149
 Phone: (972) 289-RACE (7223) ♦ Fax: (972) 289-8055
 E-mail: tom@smileysracing.com ♦ tclonch@smileysracing.com
www.smileysracing.com

Hoosier[®]

TIRE SOUTH
 Road & Drag ♦ P.O. Box 6080 ♦ Maryville, TN 37802
 Phone: (865) 984-3232 ♦ Fax: (865) 681-0775
 E-mail: road&drag@hoosiertiresouth.com

Hoosier[®]

TIRE SOUTH
 Dirt Oval
 P.O. Box 1437 ♦ Clinton, TN 37717
 Phone: (865) 457-9888 ♦ Fax: (865) 457-8033
 E-mail: hoosiertireavid@bellsouth.net

Hoosier[®]

TIRE MIDWEST
 Indianapolis
 4155 North 1000 E., Suite A, Wally Parks Dr. ♦ Brownsburg, IN 46112
 Phone: (317) 858-1234 ♦ Fax: (317) 858-1307
 E-mail: hoosiertiregirl@gmail.com ♦ www.racetires.com

Hoosier[®]

TIRE MID-ATLANTIC
 Pittsburgh
 110 South Pike Road, #207 ♦ Sarver, PA 16055
 Phone: (724) 360-8000 ♦ Fax: (724) 360-8044
 E-mail: sales@hoosiermidatlantic.com ♦ www.hoosiermidatlantic.com

Hoosier[®]

TIRE CANADA-NY
 1733 Maryland Avenue
 Niagara Falls, New York 14305
 Phone: (716) 285-7502 ♦ Fax: (800) 285-1454
 E-mail: usasales@bicknellracingproducts.com
www.bicknellracingproducts.com

Hoosier[®]

TIRE GREAT PLAINS
 3801 W. Pawnee, Suite 200 ♦ Wichita, KS 67213
 Phone: (316) 945-4000 ♦ Fax: (316) 945-4003
 E-mail: sales@hoosiertiregp.com ♦ www.hoosiertiregp.com

Hoosier[®]

TIRE GREAT PLAINS
 12252 N. 153rd Circle ♦ Bennington, NE 68007
 Phone: (402) 281-9700 ♦ Fax: (402) 933-7516
 E-mail: sales@hoosiertiregp.com ♦ www.hoosiertiregp.com

Hoosier[®]

TIRE WEST
 2608 E. California ♦ Fresno, CA 93721
 Phone: (559) 485-4612 ♦ Fax: (559) 485-4632
 E-mail: racing@hoosiertirewest.com ♦ www.hoosiertirewest.com

Hoosier[®]

TIRE MIDWEST
 Plymouth
 1801 Jim Neu Drive ♦ Plymouth, IN 46563
 Phone: (574) 936-8344 ♦ Fax: (574) 936-1673
 E-mail: hoosiertireply@aimg.com ♦ www.racetires.com

Hoosier[®]

TIRE OHIO VALLEY
 1933 Staunton Turnpike ♦ Parkersburg, WV 26104
 Phone: (304) 428-5000 ♦ Fax: (304) 485-8038
 1-800-430-7223 ♦ E-mail: todd@poske.com ♦ www.poske.com

Hoosier[®]

TIRE NORTH
 21601 John Deere Lane ♦ Rogers, MN 55374
 Phone: (763) 428-8780 ♦ Fax: (800) 555-8577
 E-mail: htrance@aol.com ♦ bfollmer1@aol.com
www.hoosiertirenorth.com

YOUR INTERNATIONAL HOOSIER DISTRIBUTORS

Hoosier[®]

TIRE AUSTRALIA
 17 Blind Road ♦ Nelson N.Z.
 Phone: (61) 296 791990
 E-mail: mdimport@bigpond.net.au ♦ www.hoosier.com.au

Hoosier[®]

TIRE CANADA
 52 Humber Street
 Albany, Auckland 0632 ♦ New Zealand
 Phone: (09) 415 1388 ♦ Fax: (09) 415 0788
 E-mail: 8@cardwells.co.nz ♦ www.cardwells.co.nz

Hoosier[®]

TIRE EUROPE
 781
 5267
www.geeandgeeracing.com
 (England, Scotland, France, Germany, Netherlands, Belgium, Germany & France)
 Phone: +44 (0) 1293 863579 ♦ Fax: +44 (0) 1293 863574
 E-mail: info@hoosiertyre.co.uk ♦ www.hoosiertyre.co.uk



www.finishline.ca

finish line

RACING PRODUCTS
 Williams Lake, BC
 1-800-734-3805

"TIRES DESIGNED FOR CHAMPIONS"®

In addition to the locations above, Hoosier Racing Tire Corp. has distributor locations in Brazil, China/Hong Kong, the Caribbean, Germany, Italy, Israel Japan, Mexico, Russia, South Africa, Sweden, Taiwan and Thailand. Contact information for these locations can be found on www.hoosiertire.com. To learn more about purchasing Hoosier tires in areas not listed, you can e-mail us at internationalsales@hoosiertire.com.