

# OPTIMA • STANTRON PIONEER ENCLOSURES

The Pioneer enclosure is the cornerstone of our enclosure line, offering flexibility, versatility and strength to meet the requirements of any Broadcast application. Pioneer enclosures are offered in Pre-Configured, Configure-Your-Own and Seismic models, with more than 25 different sizes creating hundreds of configuration possibilities. Plus a multitude of accessories are available, including shelving, cable management, cooling, power solutions and more.



Heavy-Duty Manufacturing



Three-Point Lock Rod



14-Gauge Steel Frame



Dual, Split-Door Option



One-Piece Door Option



## PRE-CONFIGURED



### PRE-CONFIGURED

#### The easy-to-order cabinet solution

Several unique Pre-Configured series to choose from  
Initial and Add-on modules available:

#### AVB Kits

Two Heights (40U and 45U)

Three Depths (25", 30" and 36" external)

One Width (22.16" external)

Available with Tapped Mounting Rails, or optional Square Holed Mounting Rails for Cage-Nut applications are available

Can be bayed together for a completely integrated system solution

## CONFIGURE-YOUR-OWN



### CONFIGURE-YOUR-OWN

#### The versatile config-your own cabinet solution

Nine Heights (12U, 25U, 30U, 35U, 40U, 42U, 45U, 48U and 50U)

Four Depths (25", 30", 36" and 42" external)

Three Widths (22", 24" and 27" external)

19" EIA, 23" TIA or 24" EIA rack-mounting configurations

Wide variety of accessories available

Can be bayed together for a completely integrated system solution

UBC Seismic Compliant

## SEISMIC



### SEISMIC

#### The strength you need

Five Heights (35U, 40U, 42U, 45U and 48U)

Four Depths (25", 30", 36" and 42" external)

3 Widths (22", 24" and 27" external)

19" EIA, 23" TIA or 24" EIA rack-mounting configurations

Wide variety of accessories available

Can be bayed together for a completely integrated system solution

NEBS Zone GR-63-CORE compliant

## ACCESSORIES



Shelving



Riser Bases



Cable Management



Rack-Mount Power Options



Filler Panels



Top Fan Panels

## AVB Pre-Configured Initial Assemblies

	Order code	Overall Depth*	Overall Width**	Overall Height	Rack Units	VPO	HPO
Series 1 AVB Initial Kits	PVK122MT7025	25.63"	22.16"	78.75"	40U	70.25"	19"
	PVK122MT7030	30.88"					
	PVK122MT7036	36.12"	22.16"	87.50"	45U	78.75"	19"
	PVK122MT7825	25.63"					
	PVK122MT7830	30.88"					
PVK122MT7836	36.12"						
Series 2 AVB Initial Kits	PVK222MT7025	25.63"	22.16"	78.75"	40U	70.25"	19"
	PVK222MT7030	30.88"					
	PVK222MT7036	36.12"	22.16"	87.50"	45U	78.75"	19"
	PVK222MT7825	25.63"					
	PVK222MT7830	30.88"					
PVK222MT7836	36.12"						
Series 3 AVB Initial Kits	PVK322MT7025	25.63"	22.16"	78.75"	40U	70.25"	19"
	PVK322MT7030	30.88"					
	PVK322MT7036	36.12"	22.16"	87.50"	45U	78.75"	19"
	PVK322MT7825	25.63"					
	PVK322MT7830	30.88"					
PVK322MT7836	36.12"						
Series 4 AVB Initial Kits	PVK422MT7025	25.63"	22.16"	78.75"	40U	70.25"	19"
	PVK422MT7030	30.88"					
	PVK422MT7036	36.12"	22.16"	87.50"	45U	78.75"	19"
	PVK422MT7825	25.63"					
	PVK422MT7830	30.88"					
PVK422MT7836	36.12"						

## AVB Pre-Configured Add-on Assemblies (Add-on Assemblies do not include side panels)

	Order code	Overall Depth	Overall Width	Overall Height	Rack Units	VPO	HPO
Series 1 AVB Add-on Kits	PVA122MT7025	25.63"	22.16"	78.75"	40U	70.25"	19"
	PVA122MT7030	30.88"					
	PVA122MT7036	36.12"	22.16"	87.50"	45U	78.75"	19"
	PVA122MT7825	25.63"					
	PVA122MT7830	30.88"					
PVA122MT7836	36.12"						
Series 2 AVB Add-on Kits	PVA222MT7025	25.63"	22.16"	78.75"	40U	70.25"	19"
	PVA222MT7030	30.88"					
	PVA222MT7036	36.12"	22.16"	87.50"	45U	78.75"	19"
	PVA222MT7825	25.63"					
	PVA222MT7830	30.88"					
PVA222MT7836	36.12"						

### Contents of kits

AVB Series 1	Enclosure frame, base with (4) levelers, solid rear door, blank – non-locking handle, solid side panel set and two pair (4) 10-32 tapped mounting rails
AVB Series 2	Enclosure frame, base with (4) levelers, vented rear door, blank – non-locking handle, vented side panel set and two pair (4) 10-32 tapped mounting rails
AVB Series 3	Enclosure frame, base with (4) levelers, vented rear door, blank – non-locking handle, solid side panel set and two pair (4) 10-32 tapped mounting rails
AVB Series 4	Enclosure frame, base with (4) levelers, solid rear door, blank – non-locking handle, vented side panel set and two pair (4) 10-32 tapped mounting rails

\* Overall depth of cabinet without doors – add 1.39" for a single door with handle.

\*\* Overall width of cabinet without side panels – add 1.20" for a set of side panels.

Note: All frames are available in the standard color offering: M – Black, F – Computer Gray, P – Light Gray and E – Royal Blue

## SIX EASY STEPS TO A CONFIGURED PIONEER CABINET

Pioneer cabinets are offered in a wide variety of sizes and accessory options that give you the flexibility to configure your own enclosure to suit your specific application needs. Use this simple 6-step process to configure your own Pioneer enclosure. **Be sure to record the part number at each step.**

### STEP 1: SELECT YOUR FRAME

Choose the appropriate height, depth and width frame along with the type of mounting rails you would like.

### STEP 2: CHOOSE DOOR & HANDLE/LOCK STYLE

Choose the quantity, style, and hinged preference door (front and rear) that best suits your application. If not specified, each door will be left hinged. **Be sure to order your handles. Handles/locks must be ordered as a separate line item—they are not included in door part number.** See page 19 for a listing of the available lock & handle options.

### STEP 3: CHOOSE SIDE PANELS

Choose the side panels that best protect your equipment and provide the ventilation your installation requires. Side panels are sold as pairs.

### STEP 4: CHOOSE TOP PANELS

Select top panels that best fit your ventilation and cable management needs.

### STEP 5: ADD ACCESSORIES

Finish your cabinet by adding the specific functionality to suit your application; select from equipment shelves, Power Options, lighting options, cable management, grounding bars and more.

### STEP 6: CHOOSE COLOR

Pioneer cabinets are available in 4 color choices. Add the code letter for the color you want to each part number. Color choices and code letters are: Black – M, Computer Gray – F, Light Gray – P or Royal Blue – E.



### Top Panels

Top panels are offered in several different configurations based on your installation requirements. Three panel kits are available in full depth panels and in solid or perforated configurations.

### Optional Fan Panels

Fan panels are available to provide extra ventilation to your cabinet. Fans are internally mounted at the top of the enclosure. Fan panels can either be the full depth or can also be ordered with 2 cable management panels included.

### Mounting Rails

Rails are available with either 10-32 tapped mounting holes or clip-nut configurations.

### 14-Gauge Steel Construction

With a weight capacity of 2,000 lbs., Pioneer's heavy-duty frame uses the Interweld™ design with cross braces interlocked and welded into the corner post.

### Front and/or Rear Doors

Doors are available in solid, vented, perforated, perforated edge Plexiglas® and solid edge Plexiglas configurations. Can be either left- or right-hand swinging. Solid, vented and perforated doors are also available in split design. Don't forget to specify the handle type you require; non-locking, key-lock or combination lock. Three-point latching kits are also available for most doors.

### Rack-Mount or Vertical Power Strips

Add the power management accessories that your installation needs. Our Power Options line offers many different types of power, from rack-mount to vertical, from 15-amp to 20-amp and from low- to high-density.

### Equipment Shelf (Optional)

A variety of shelves are available to suit your needs; short-depth, light-duty shelves; full-depth fixed; or roll-out shelves.

### Side Panels

Several styles of side panels are available to fit your installation and ventilation requirements, from solid, vented or fully perforated. Side panels sold in pairs and include a lock on each panel for added security.

### Raised Pontoon Sub-Base

Three-inch pontoon sub-base raises valuable equipment off the floor and can accommodate casters. Base includes levelers for on-site cabinet leveling. Bases can be inverted and used with anchor kits for floor mounting applications.

\*Plexiglas® is a trademark of the Atoglas Company

## Pioneer Enclosure Configure-Your-Own

### STEP 1 – SELECT YOUR FRAME

Use the part numbering guides on this page to determine the catalog part numbers for the components of your Pioneer Cabinet. The tables in the Part Code Reference section will give you the relevant internal and external width, height and depth dimensions associated with each Pioneer frame and component.

#### Part Number Code References

WIDTH Needed for STEPS 1 & 2		
Part # Code	External Frame Width	Rack Mount Width
22	22.16"	19"
24	24.00"	19"
27	27.16"	19", 23", 24"

RACK MOUNT WIDTH Needed for STEP 4	
Part # Code	Compatible with 22 & 24 Width Code Frames
19	Compatible with 22 & 24 Width Code Frames
24	Compatible with 27 Width Code Frames

HEIGHT Needed for STEPS 1,2 & 3			
Part # Code	U Height	VPO (Vertical Panel Opening)	External Frame Height
21	12U	21.00"	29.75"
44	25U	43.75"	52.50"
53	30U	52.50"	61.25"
61	35U	61.25"	70.00"
70	40U	70.00"	78.75"
74	42U	73.50"	82.25"
78	45U	78.75"	87.50"
84	48U	84.00"	92.75"
88	50U	87.50"	96.25"

DEPTH Needed for STEPS 1,3 & 4		
Part # Code	Usable Depth	External Frame Depth
25	24.38"	25.63"
30	29.63"	30.88"
36	34.87"	36.12"
42	40.12"	41.37"

### STEP 1 – Select Your Frame

Pioneer	Width Code	Rail Shape	Rail Mount Hole Type	Height Code	Depth Code	Color
<b>P</b>	<b>22</b>	<b>M</b>	<b>T</b>	<b>88</b>	<b>36</b>	<b>M</b>

P = Standard  
 PZ = Seismic  
 M = M style  
 C = C style  
 R = R style  
 L = L style  
 T = 10-32 Tapped  
 S = Square (.375)  
 21  
 25  
 30  
 36  
 42  
 44  
 53  
 61\*  
 70\*  
 74\*  
 78\*  
 84\*  
 88  
 M = Black  
 F = Computer Gray  
 P = Light Gray  
 E = Royal Blue  
 \* = Seismic Heights

### STEP 2 – Choose Door

Pioneer Door	Door Type	Width Code	Height Code	Hinge	Color
<b>PD</b>	<b>S</b>	<b>22</b>	<b>21</b>	<b>L</b>	<b>M</b>

S = Solid  
 LS = Plexiglas Solid Perimeter  
 LP = Plexiglas Perforated Perimeter  
 P = Perforated  
 V = Vented  
 22  
 24  
 27  
 21  
 44  
 53  
 61  
 70  
 74  
 78  
 84  
 88  
 L = Left  
 R = Right  
 S = Split  
 M = Black  
 F = Computer Gray  
 P = Light Gray  
 E = Royal Blue

Each door adds 1.39" to External Frame Depth

### STEP 3 – Choose Side Panels

Pioneer Side Panel	Side Type	Height Code	Depth Code	Color
<b>PS</b>	<b>S</b>	<b>21</b>	<b>30</b>	<b>M</b>

S = Solid  
 V = Vented  
 P = Perforated  
 21  
 44  
 53  
 61  
 70  
 74  
 78  
 84  
 88  
 M = Black  
 F = Computer Gray  
 P = Light Gray  
 E = Royal Blue

Each Side Panel adds .60" to External Frame Width

### STEP 4 – Choose Top Panels

Top Panel Type	Style	Rack Mount Width	Depth Code	Color
<b>PT</b>	<b>4F</b>	<b>19</b>	<b>25</b>	<b>M</b>

TFP = Full Depth, Single Piece  
 PT = 3-Piece Kit\*  
 S = Solid  
 P = Perforated  
 4F = 4 Fan  
 19  
 24  
 25  
 30  
 36  
 42  
 M = Black  
 F = Computer Gray  
 P = Light Gray  
 E = Royal Blue

\*Three-piece kits consist of one front cable access panel, one rear cable access panel and either a solid, perforated or four-fan center panel.

Configure-Your-Own				
Usable Height 12U 21.00" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
Order Code	Order Code	Order Code	Order Code	Order Code
<b>Rack Frame (each)</b>				
12U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P22MT2125	P22MT2130	P22MT2136	P22MT2142
Usable Height	21.00" (12U)	21.00" (12U)	21.00" (12U)	21.00" (12U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	29.75"	29.75"	29.75"	29.75"
<b>Doors (each) *Specify L or R (Left/Right hand)<sup>2,3</sup></b>				
Solid	PDS2221*	PDS2221*	PDS2221*	PDS2221*
Plexiglas Solid Perimeter	PDLS2221*	PDLS2221*	PDLS2221*	PDLS2221*
Plexiglas Perforated Perimeter	PDLP2221*	PDLP2221*	PDLP2221*	PDLP2221*
Perforated	PDP2221*	PDP2221*	PDP2221*	PDP2221*
Vented	PDV2221*	PDV2221*	PDV2221*	PDV2221*
<b>Side Panel (pair)</b>				
Solid	PSS2125	PSS2130	PSS2136	PSS2142
Vented	PSV2125	PSV2130	PSV2136	PSV2142
Perforated	PSP2125	PSP2130	PSP2136	PSP2142
<b>Top Panel (each)</b>				
Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

### STEP 5 – ORDER DOOR HANDLE & OTHER ACCESSORIES, OPTIONS START ON PAGE 26

Notes: 1. M Style 10-32 tapped rails ship standard with every Pioneer cabinet unless otherwise specified. Also available in other rail shapes and with square holes.

\*2. Specify LEFT or RIGHT hand door by adding L or R to door part #.

3. Be sure to order handles—must be ordered as a separate line item.

\*4. For SPLIT door, add "S" to end of part number, but before color (Example: PDS2244SM).

DO NOT specify L or R swing designation for split doors, which are sold in pairs.

Configure-Your-Own				
Usable Height 25U 43.75" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
Order Code	Order Code	Order Code	Order Code	Order Code
<b>Rack Frame (each)</b>				
25U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P25MT4425	P25MT4430	P25MT4436	P25MT4442
Usable Height	43.75" (25U)	43.75" (25U)	43.75" (25U)	43.75" (25U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	52.50"	52.50"	52.50"	52.50"
<b>Doors (each) *Specify L or R (Left/Right hand)<sup>2,3</sup></b>				
Solid	PDS2244*	PDS2244*	PDS2244*	PDS2244*
Plexiglas Solid Perimeter	PDLS2244*	PDLS2244*	PDLS2244*	PDLS2244*
Plexiglas Perforated Perimeter	PDLP2244*	PDLP2244*	PDLP2244*	PDLP2244*
Perforated	PDP2244*	PDP2244*	PDP2244*	PDP2244*
Vented	PDV2244*	PDV2244*	PDV2244*	PDV2244*
<b>Side Panel (pair)</b>				
Solid	PSS4425	PSS4430	PSS4436	PSS4442
Vented	PSV4425	PSV4430	PSV4436	PSV4442
Perforated	PSP4425	PSP4430	PSP4436	PSP4442
<b>Top Panel (each)</b>				
Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

22 Represents 22" width frames/doors, also available in 24" & 27" widths - see page 5 to determine exact part numbers for other widths

19 Represents 19" width top panels, also available in 24" width - see page 5 to determine exact part numbers for other width


- tan indicates parts not available in Split Door versions



Pioneer frame



Standard Solid Door - PDS



Configure-Your-Own				
Usable Height 30U 52.50" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
	Order Code	Order Code	Order Code	Order Code
<b>Rack Frame (each)</b>				
Step 1 30U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P22MT5325	P22MT5330	P22MT5336	P22MT5342
Usable Height	52.50" (30U)	52.50" (30U)	52.50" (30U)	52.50" (30U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	61.25	61.25	61.25	61.25
<b>Doors (each) *Specify L or R (Left/Right hand)<sup>2,3</sup></b>				
Step 2 Solid	PDS2253*	PDS2253*	PDS2253*	PDS2253*
Plexiglas Solid Perimeter	PDLS2253*	PDLS2253*	PDLS2253*	PDLS2253*
Plexiglas Perforated Perimeter	PDLP2253*	PDLP2253*	PDLP2253*	PDLP2253*
Perforated	PDP2253*	PDP2253*	PDP2253*	PDP2253*
Vented	PDV2253*	PDV2253*	PDV2253*	PDV2253*
<b>Side Panel (pair)</b>				
Step 3 Solid	PSS5325	PSS5330	PSS5336	PSS5342
Vented	PSV5325	PSV5330	PSV5336	PSV5342
Perforated	PSP5325	PSP5330	PSP5336	PSP5342
<b>Top Panel (each)</b>				
Step 4 Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

Configure-Your-Own				
Usable Height 35U 61.25" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
	Order Code	Order Code	Order Code	Order Code
<b>Rack Frame (each)</b>				
Step 1 35U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P22MT6125	P22MT6130	P22MT6136	P22MT6136
Usable Height	61.25" (35U)	61.25" (35U)	61.25" (35U)	61.25" (35U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	70.00"	70.00"	70.00"	70.00"
<b>Doors (each) *Specify L or R (Left/Right hand)<sup>2,3</sup></b>				
Step 2 Solid	PDS2261*	PDS2261*	PDS2261*	PDS2261*
Plexiglas Solid Perimeter	PDLS2261*	PDLS2261*	PDLS2261*	PDLS2261*
Plexiglas Perforated Perimeter	PDLP2261*	PDLP2261*	PDLP2261*	PDLP2261*
Perforated	PDP2261*	PDP2261*	PDP2261*	PDP2261*
Vented	PDV2261*	PDV2261*	PDV2261*	PDV2261*
<b>Side Panel (pair)</b>				
Step 3 Solid	PSS6125	PSS6130	PSS6136	PSS6142
Vented	PSV6125	PSV6130	PSV6136	PSV6142
Perforated	PSP6125	PSP6130	PSP6136	PSP6142
<b>Top Panel (each)</b>				
Step 4 Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

Configure-Your-Own				
Usable Height 40U 70.00" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
	Order Code	Order Code	Order Code	Order Code
<b>Rack Frame (each)</b>				
Step 1 40U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P22MT7025	P22MT7030	P22MT7036	P22MT7042
Usable Height	70.00" (40U)	70.00" (40U)	70.00" (40U)	70.00" (40U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	78.75"	78.75"	78.75"	78.75"
<b>Doors (each) *Specify L or R (Left/Right hand)<sup>2,3</sup></b>				
Step 2 Solid	PDS2270*	PDS2270*	PDS2270*	PDS2270*
Plexiglas Solid Perimeter	PDLS2270*	PDLS2270*	PDLS2270*	PDLS2270*
Plexiglas Perforated Perimeter	PDLP2270*	PDLP2270*	PDLP2270*	PDLP2270*
Perforated	PDP2270*	PDP2270*	PDP2270*	PDP2270*
Vented	PDV2270*	PDV2270*	PDV2270*	PDV2270*
<b>Side Panel (pair)</b>				
Step 3 Solid	PSS7025	PSS7030	PSS7036	PSS7042
Vented	PSV7025	PSV7030	PSV7036	PSV7042
Perforated	PSP7025	PSP7030	PSP7036	PSP7042
<b>Top Panel (each)</b>				
Step 4 Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

Configure-Your-Own				
Usable Height 42U 73.50" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
	Order Code	Order Code	Order Code	Order Code
<b>Rack Frame (each)</b>				
Step 1 42U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P22MT7425	P22MT7430	P22MT7436	P22MT7442
Usable Height	73.50" (42U)	73.50" (42U)	73.50" (42U)	73.50" (42U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	82.25	82.25	82.25	82.25
<b>Doors (each) *Specify L or R (Left/Right hand)<sup>2,3</sup></b>				
Step 2 Solid	PDS2274*	PDS2274*	PDS2274*	PDS2274*
Plexiglas Solid Perimeter	PDLS2274*	PDLS2274*	PDLS2274*	PDLS2274*
Plexiglas Perforated Perimeter	PDLP2274*	PDLP2274*	PDLP2274*	PDLP2274*
Perforated	PDP2274*	PDP2274*	PDP2274*	PDP2274*
Vented	PDV2274*	PDV2274*	PDV2274*	PDV2274*
<b>Side Panel (pair)</b>				
Step 3 Solid	PSS7425	PSS7430	PSS7436	PSS7442
Vented	PSV7425	PSV7430	PSV7436	PSV7442
Perforated	PSP7425	PSP7430	PSP7436	PSP7442
<b>Top Panel (each)</b>				
Step 4 Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

**STEP 5 – ORDER DOOR HANDLE & OTHER ACCESSORIES, OPTIONS START ON PAGE 26**

- Notes: 1. M Style 10-32 tapped rails ship standard with every Pioneer cabinet unless otherwise specified. Also available in other rail shapes and with square holes.  
 \*2. Specify LEFT or RIGHT hand door by adding L or R to door part#.  
 3. Be sure to order handles—must be ordered as a separate line item.  
 \*4. For SPLIT door, add "S" to end of part number, but before color (Example: PDS2244SM).  
 DO NOT specify L or R swing designation for split doors, which are sold in pairs.

- 22** Represents 22" width frames/doors, also available in 24" & 27" widths - see page 5 to determine exact part numbers for other widths  
**19** Represents 19" width top panels, also available in 24" width - see page 5 to determine exact part numbers for other width  
 - tan indicates parts not available in Split Door versions


**STEP 5 – ORDER DOOR HANDLE & OTHER ACCESSORIES, OPTIONS START ON PAGE 26**

- Notes: 1. M Style 10-32 tapped rails ship standard with every Pioneer cabinet unless otherwise specified. Also available in other rail shapes and with square holes.  
 \*2. Specify LEFT or RIGHT hand door by adding L or R to door part#.  
 3. Be sure to order handles—must be ordered as a separate line item.  
 \*4. For SPLIT door, add "S" to end of part number, but before color (Example: PDS2244SM).  
 DO NOT specify L or R swing designation for split doors, which are sold in pairs.

- 22** Represents 22" width frames/doors, also available in 24" & 27" widths - see page 5 to determine exact part numbers for other widths  
**19** Represents 19" width top panels, also available in 24" width - see page 5 to determine exact part numbers for other width  
 - tan indicates parts not available in Split Door versions



Plexiglas Solid Door - PDLS



Perforated Door - PDP



Vented Door - PDV



Solid Side Panel - PDS



Vented Side Panel - PDV



Perforated Side Panel - PDP



3 Piece Top Fan Panel Kit - TFPS



Full Depth Single Piece Top Fan Panel- TFP4F

Configure-Your-Own				
Usable Height 45U 78.75" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
Order Code	Order Code	Order Code	Order Code	Order Code
<b>Step 1</b>				
Rack Frame (each)				
45U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P22MT7825	P22MT7830	P22MT7836	P22MT7842
Usable Height	78.75" (45U)	78.75" (45U)	78.75" (45U)	78.75" (45U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	87.50"	87.50"	87.50"	87.50"
<b>Step 2</b>				
Doors (each) *Specify L or R (Left/Right hand) <sup>2,3</sup>				
Solid	PDS2278* <sup>tan</sup>	PDS2278* <sup>tan</sup>	PDS2278* <sup>tan</sup>	PDS2278* <sup>tan</sup>
Plexiglas Solid Perimeter	PDLS2278*	PDLS2278*	PDLS2278*	PDLS2278*
Plexiglas Perforated Perimeter	PDLP2278*	PDLP2278*	PDLP2278*	PDLP2278*
Perforated	PDP2278* <sup>tan</sup>	PDP2278* <sup>tan</sup>	PDP2278* <sup>tan</sup>	PDP2278* <sup>tan</sup>
Vented	PDV2278* <sup>tan</sup>	PDV2278* <sup>tan</sup>	PDV2278* <sup>tan</sup>	PDV2278* <sup>tan</sup>
<b>Step 3</b>				
Side Panel (pair)				
Solid	PSS7825	PSS7830	PSS7836	PSS7842
Vented	PSV7825	PSV7830	PSV7836	PSV7842
Perforated	PSP7825	PSP7830	PSP7836	PSP7842
<b>Step 4</b>				
Top Panel (each)				
Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

### STEP 5 – ORDER DOOR HANDLE & OTHER ACCESSORIES, OPTIONS START ON PAGE 26

Notes: 1. M Style 10-32 tapped rails ship standard with every Pioneer cabinet unless otherwise specified. Also available in other rail shapes and with square holes (see page 14).

- \*2. Specify LEFT or RIGHT hand door by adding L or R to door part#.
- 3. Be sure to order handles—must be ordered as a separate line item.

\*4. For SPLIT door, add "S" to end of part number, but before color (Example: PDS2221SM). DO NOT specify L or R swing designation for split doors, which are sold in pairs.

<sup>tan</sup> Represents 22" width frames/doors, also available in 24" & 27" widths - see page 5 to determine exact part numbers for other widths

<sup>19</sup> Represents 19" width top panels, also available in 24" width - see page 5 to determine exact part numbers for other width

tan - tan indicates parts not available in Split Door versions

### STEP 6 – CHOOSE COLOR

Be sure to indicate color choice. Add the color code to each part number:

- M = Black**
- F = Computer Gray**
- P = Light Gray**
- E = Royal Blue**

Configure-Your-Own				
Usable Height 48U 84.00" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
Order Code	Order Code	Order Code	Order Code	Order Code
<b>Step 1</b>				
Rack Frame (each)				
48U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P22MT8425	P22MT8430	P22MT8436	P22MT8442
Usable Height	84.00" (48U)	84.00" (48U)	84.00" (48U)	84.00" (48U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	92.75"	92.75"	92.75"	92.75"
<b>Step 2</b>				
Doors (each) *Specify L or R (Left/Right hand) <sup>2,3</sup>				
Solid	PDS2284* <sup>tan</sup>	PDS2284* <sup>tan</sup>	PDS2284* <sup>tan</sup>	PDS2284* <sup>tan</sup>
Plexiglas Solid Perimeter	PDLS2284*	PDLS2284*	PDLS2284*	PDLS2284*
Plexiglas Perforated Perimeter	PDLP2284*	PDLP2284*	PDLP2284*	PDLP2284*
Perforated	PDP2284* <sup>tan</sup>	PDP2284* <sup>tan</sup>	PDP2284* <sup>tan</sup>	PDP2284* <sup>tan</sup>
Vented	PDV2284* <sup>tan</sup>	PDV2284* <sup>tan</sup>	PDV2284* <sup>tan</sup>	PDV2284* <sup>tan</sup>
<b>Step 3</b>				
Side Panel (pair)				
Solid	PSS8425	PSS8430	PSS8436	PSS8442
Vented	PSV8425	PSV8430	PSV8436	PSV8442
Perforated	PSP8425	PSP8430	PSP8436	PSP8442
<b>Step 4</b>				
Top Panel (each)				
Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

Configure-Your-Own				
Usable Height 50U 87.75" VPO	19" Rack Mount			
	25" Depth	30" Depth	36" Depth	42" Depth
Order Code	Order Code	Order Code	Order Code	Order Code
<b>Step 1</b>				
Rack Frame (each)				
50U Pioneer with Leveler Base, M Style, 10-32 Tapped Rails <sup>1</sup>	P22MT8825	P22MT8830	P22MT8836	P22MT8842
Usable Height	87.75" (50U)	87.75" (50U)	87.75" (50U)	87.75" (50U)
External Frame Depth	25.63"	30.88"	36.12"	41.37"
External Frame Width	22.16"	22.16"	22.16"	22.16"
External Frame Height	96.25"	96.25"	96.25"	96.25"
<b>Step 2</b>				
Doors (each) *Specify L or R (Left/Right hand) <sup>2,3</sup>				
Solid	PDS2288* <sup>tan</sup>	PDS2288* <sup>tan</sup>	PDS2288* <sup>tan</sup>	PDS2288* <sup>tan</sup>
Plexiglas Solid Perimeter	PDLS2288*	PDLS2288*	PDLS2288*	PDLS2288*
Plexiglas Perforated Perimeter	PDLP2288*	PDLP2288*	PDLP2288*	PDLP2288*
Perforated	PDP2288* <sup>tan</sup>	PDP2288* <sup>tan</sup>	PDP2288* <sup>tan</sup>	PDP2288* <sup>tan</sup>
Vented	PDV2288* <sup>tan</sup>	PDV2288* <sup>tan</sup>	PDV2288* <sup>tan</sup>	PDV2288* <sup>tan</sup>
<b>Step 3</b>				
Side Panel (pair)				
Solid	PSS8825	PSS8830	PSS8836	PSS8842
Vented	PSV8825	PSV8830	PSV8836	PSV8842
Perforated	PSP8825	PSP8830	PSP8836	PSP8842
<b>Step 4</b>				
Top Panel (each)				
Solid	TFPS1925	TFPS1930	TFPS1936	TFPS1942
Perforated	TFPP1925	TFPP1930	TFPP1936	TFPP1942
Single Fan Panel w/4 Fans	TFP4F1925	TFP4F1930	TFP4F1936	TFP4F1942
4 Fan Panel Kit w/cable management panels	PT4F1925	PT4F1930	PT4F1936	PT4F1942

Optima•Stantron offers many accessories for complete customization of our racks and enclosures to be customized to suit your specific application requirements. Consider the following:

- Door Handles and Locks
- Door Options Including Double-Panel, Access to Front and Back, Plexiglas See-Through, Etc.
- Three-Point Latching and Locking Kits
- Casters
- Cable Management
- Shelving, Trays and Drawers
- Filler Panels and Wedges
- Work Surfaces
- Thermal Management
- Reducer Brackets
- Power Options and Lighting
- Plus Many Other Accessories.

Note: Be sure to order handles for your doors. Handles must be ordered as a separate line item.


### Pioneer Handle/Locking Options

Order Code	Description
PHB000	Handle with non-locking insert, removable core
PHL100*	Handle with lock, removable core, 2 keys #100
PHP000	Swing handle with padlock hasp and 3-point cam
PHC300	Deluxe combination swing handle with 3 barrel combination and 3-point cam
PHC400	Economy combination swing handle with 4 barrel combination and 3-point cam

25 different key options are available—call your dealer or 800-821-0019 for more information

### Pioneer 3-Point Latching Kits

Order Code	Description
3PTR0D38KT	Kit, 3-point Lock Rod 22U
3PTR0D44KT	Kit, 3-point Lock Rod 25U
3PTR0D49KT	Kit, 3-point Lock Rod 28U
3PTR0D53KT	Kit, 3-point Lock Rod 30U
3PTR0D61KT	Kit, 3-point Lock Rod 35U
3PTR0D70KT	Kit, 3-point Lock Rod 40U
3PTR0D74KT	Kit, 3-point Lock Rod 42U
3PTR0D78KT	Kit, 3-point Lock Rod 45U
3PTR0D84KT	Kit, 3-point Lock Rod 48U
3PTR0D88KT	Kit, 3-point Lock Rod 50U
3PTR0D91KT	Kit, 3-point Lock Rod 52U



Handle With Lock- PHL100



PHL100



PHP000



PHC300



PHC400



Rack Mount Reducer Brackets - AB



Bottom Panels With Cable Entry - PBP

### Pioneer Rack Mount Reducer Brackets

Order Code	Description
AB01	Reducer bracket, 24" HPO to 19" HPO, tapped 10-32 holes, 1.75", 1U, - set of 2, black
AB02	Reducer bracket, 24" HPO to 19" HPO, tapped 10-32 holes, 3.50", 2U, - set of 2, black
AB03	Reducer bracket, 24" HPO to 19" HPO, tapped 10-32 holes, 5.25", 3U, - set of 2, black
AB04	Reducer bracket, 24" HPO to 19" HPO, tapped 10-32 holes, 7.00", 4U, - set of 2, black
AB05	Reducer bracket, 24" HPO to 19" HPO, tapped 10-32 holes, 8.75", 5U, - set of 2, black
AB2301	Reducer bracket, 23" HPO to 19" HPO, tapped 10-32 holes, 1.75", 1U, - set of 2, black
AB2302	Reducer bracket, 23" HPO to 19" HPO, tapped 10-32 holes, 3.50", 2U, - set of 2, black
AB2303	Reducer bracket, 23" HPO to 19" HPO, tapped 10-32 holes, 5.25", 3U, - set of 2, black
AB2304	Reducer bracket, 23" HPO to 19" HPO, tapped 10-32 holes, 7.00", 4U, - set of 2, black
AB2305	Reducer bracket, 23" HPO to 19" HPO, tapped 10-32 holes, 8.75", 5U, - set of 2, black

### Pioneer Caster & Floor Mounting Kits

Order code	Description
ANCHORKT	Vertical enclosure floor anchoring kit - set of 4 brackets, black
ANTIPKT	Vertical enclosure, anti-tip plate
CST1KT	Caster kit - 4 casters, T3CST1 swivel casters with brackets, supports 1080lbs., black
CST8KT	Caster kit - 4 casters, T3CST8 swivel casters with brackets, supports 1600lbs., black



Castors - CST



Anchor Kit -

### Pioneer Bottom Panels

Order Code	Panel Width	Style of Panel	Cabinet Depth
PBP1925	19"	Perforated	25"
PBP1930	19"	Perforated	30"
PBP1936	19"	Perforated	36"
PBS1925	19"	Solid	25"
PBS1930	19"	Solid	30"
PBS1936	19"	Solid	36"

Note: Bottom panel part numbers published here are for 19" rack mount widths only. These are available in 23" and 24" rack mount widths also.