

GE Healthcare

Optima* XR240amx

Mobile Digital Radiographic System



System Application

Optima XR240amx is a self-contained; battery operated mobile radiographic imaging system designed to generate diagnostic radiographic images (medical x-rays) that may increase the ability to detect disease or injury early enough for a medical problem to be managed, treated, or cured.

The Optima XR240amx system is indicated for use on adult and pediatric patients for general-purpose diagnostic radiographic examinations and procedures. Its mobility enables general-purpose radiographic procedures throughout the clinical environment, or as needed within the emergency, intensive care, premature birth ward, cardiac and operating departments, for patients that may not be able to be moved or in cases where it is unsafe or impractical to move them to a traditional RAD room. The incorporation of digital flat panel detectors provides increased functionality to enable images of patients of all sizes.

Key Features

- FlashPad* HD detectors can support up to 150 Kg (330 lbs.) of distributed load for bariatric applications
- Portable detectors can be seamlessly shared across compatible systems within the healthcare facility by all users
- Can be used with GE Healthcare Giraffe* OmniBed Carestation incubator and radiant warmer
- Designed for use with films or CR Cassettes
- Automatic charging algorithms allow the system to be re-charged at any charge level, even during exposures enabling 24/7 availability
- 30kW (nominal) generator
- 802.11 wireless connectivity from detector to system
- Detector battery charges automatically while the detector is in the bin when the system is on, or in standby mode
- "Stand-by" mode eliminates boot up cycles and allows start of imaging exam within 20 seconds from "stand-by" mode
- Optimized Graphical User Interface – Technique, image acquisition and display tools in a single integrated user interface
- Commonly used tools available in all image processing screens
- Dose Reports can be downloaded from the system
- DAP meter included
- Compatible with multiple cleaning agents (Refer to Operator Manual for details)

Productivity

- Less than 4.5 hours to go from 20% to 100% for system battery charge
- System can be driven within 4 seconds of activation
- Pre-programmed techniques per anatomy, view, and patient size
- Image text annotations are supported with configurable font size for display and print
- Copy existing exams allows image reprocessing capability without additional exposures
- Reprocessing of images allow multiple "looks" selection with configurable display parameters during an exam or post exam closure
- Optional Auto Protocol Assist – matches procedure codes from Worklist to select anatomy technique
- Worklist entries remain visible on the user interface as part of the scheduled procedure step browser
- Automated and customizable image transfer to PACS and printers
- Worklist auto-refresh (configurable)
- Optional Repeat/Reject Analysis tool allows classification and analysis of repeated/rejected exposures on the system
- Bin stores and charges detector(s) with grid(s) attached or detached
- Built in storage for cleaning wipes, gloves, and lead apron

Wireless Digital Detector

- Single panel (non-tiled) amorphous silicon detector with a directly deposited cesium iodide scintillator
- Pixel pitch 100 microns
- FlashPad HD 2530 image area: 298 mm x 248 mm (11.7 in x 9.8 in)
- FlashPad HD 3543 image area: 350 mm x 426 mm (13.8 in x 16.6 in)
- FlashPad HD 2530 pixel matrix: 2508 x 3004 pixels
FlashPad HD 3543 pixel matrix: 3524 x 4288 pixels
- Typical DQE @ 0lp/mm: 75%
- FlashPad HD 2530 (10"x12") weighs 1.9 kg (4.2 lbs.)
FlashPad HD 3543 (14"x17") weighs 3.2 kg (7.1 lbs.)

- Includes QAP (Quality Assurance Procedure)
- Available with 6:1 and 8:1 removable grids
- Tether (Included)
- Removable, rechargeable battery and battery charger available
- 802.11n 5GHz link between the system and detector
- Supports automatic channel switching to improve image transfer and avoid wireless interference with hospital network



Networking

- Worklist can be retrieved from HIS/RIS systems
- Images can be automatically transmitted through the DICOM interface to printers, archival devices (PACS), servers or review workstations
- RJ45 10/100 Base T Ethernet port and optional 802.11 wireless connection
- IHE and DICOM 3.0 compliant services:
 - DICOM DX Image generated
 - Support image transfer in DX or CR (multiple destinations)
 - DICOM storage – Service Class User (SCU)
 - DICOM storage commitment - SCU
 - DICOM modality Worklist for HIS/RIS, SCU (with programmable auto refresh)
 - DICOM gray scale print – manual and auto
 - Multi-format printing
 - DICOM CD-R media exchange (DX only)
 - Verification of connectivity for SCU and SCP services
 - DICOM Modality Performed Procedure Step (MPPS) feedback to the HIS/RIS (SPS PPS) (configurable)
 - VOI LUT burn on send (configurable)

Detector Environmental Conditions	
Temperature	10°C to 35°C Operating
Humidity	20% to 80% RH. noncondensing



Please refer to DICOM conformance statement for complete definition of supported DICOM services.

Automated Image Display, Processing, and Annotation Functions

- Images can be previewed in 3 seconds
- Total processing time of less than 15 seconds
- Integrated 15 in (38.1 cm) touch-screen user interface
- Monitor matrix size 1024 x 768 pixels
- Patient orientation feature to match detector position image display and DICOM header
- Multiple sets of predefined and customizable image processing parameters for each anatomy, view, and patient size combination: Image processing looks
- Multi-resolution processing for image enhancement
- Advanced Noise Reduction (ANR) that reduces image noise while preserving detail
- EMI reduction algorithm to reduce potential artifacts generated from environmental electromagnetic interference
- Tissue Equalization (TE) algorithm that provides dynamic range control to enhance contrast in areas with varying densities
- Smart Windowing algorithm for automatic adjustment of brightness/contrast
- Intelligent Collimation Edge Detection (ICED) algorithm that locates collimation edges present in an X-ray image based solely on image information for automatic shuttering
- Digital L/R markers and image annotation
- Image rotation, zoom, manual shuttering, invert, and gray scale adjustment available
- Storage for more than 5000 uncompressed images
- Images can be exported to CD/DVD media for storage
- USB ports for external drive, barcode reader, and service keyboard

Drive

- Battery operated
- Self-propelled single handle drive control variable speed automatically adjusts to the operator's pace. Nominal speeds of 5 km/h (3.1 mph) forward on flat surfaces
- Speed is reduced in reverse or when the tube is not parked
- Capable of climbing an incline of 7°

Generator

- 300 mA max
- kVp and mAs controls

	Ratings	Steps
kVp	50 - 125	±1 kVp increments
mAs	0.2 - 630	1 Renard (25% up - 20% down)

- Super-resonant inverter with varying frequency
- Less than 2% low frequency ripple
- Frequency: greater than 100 kHz

X-ray Source

- Nominal tube voltage (Radiographic) 40 ~ 150 kV
- Nominal focal spot size (IEC 60336):
 - Large focus: 1.2 mm
 - Small focus: 0.6 mm
- Anode rotation speed (minimal): 3200 per min
- Permanent filtration: 0.9 mm Al/75 kV
- Maximum X-ray tube current:
 - Large focus: 500 mA
 - Small focus: 200 mA
- Maximum continuous heat dissipation without air-circulator: 170 W (238 HU/s)
- Maximum anode heat units 140 kHU
- Exposure time: 4.0 msec – 6.0 sec

Tube Positioning

- The column may be rotated up to ± 270° from the park position
- Tube angle display and SID measuring tool
- Focal spot range from 62.48 cm (24.6 in) to 200 cm (78.7 in)

Collimator

- A pair of independent collimator blades controls the field of view
- 160 lux light field lamp
- 43 cm x 43 cm (17 in x 17 in) coverage at a 100 cm (40 in) SID
- The collimator rotates ±180 degrees with detents at -180, -90, 0, +90, and +180 degrees

Power

- Capable of 100-240 V nominal, 50/60 Hz operation
- System battery status display
- Battery operated system can perform up to 50 exams (100 X-ray exposures over approximately 6 hours) without being plugged into a power outlet

System Weight

- Weight is 445 kg (980 lbs.) max

Environmental and Safety Features

- Drive Inhibit keypad access
- Password protected to access patient information and to allow exposures
- Automatic safety brake requiring operator to hold drive controls that allows system movement
- Integrated front bumper activates brakes to stop the unit preventing forward drive until the bumper is released
- Bin storage for accessories such as bags or standard sized film/CR cassettes
- Smooth surfaces for cleanability

Compliance to Standards

Optima XR240amx Mobile Radiographic Imaging System is designed to meet applicable performance standards for diagnostic X-ray equipment enunciated by the U.S. Department of Health and Human Services pursuant to the Radiation Control for Health and Safety Act in addition, the system complies with AAMI, IEC and CSA requirements.

Warranty

The published company warranty in effect on date of shipment shall apply. Right reserved to make changes



GE Healthcare provides transformational medical technologies and services to meet the demand for increased access, enhanced quality and more affordable healthcare around the world. GE (NYSE: GE) works on things that matter - great people and technologies taking on tough challenges.

From medical imaging, software and IT, patient monitoring and diagnostics to drug discovery, biopharmaceutical manufacturing technologies and performance improvement solutions, GE Healthcare helps medical professionals deliver great healthcare to their patients.

GE Healthcare
3000 N. Grandview
Blvd. Waukesha, WI
53188 USA

Imagination at work

Product may not be available in all countries and regions.
Contact a GE Healthcare Representative for more information.
Please visit www.gehealthcare.com/promotional-locations.

Data subject to change.

©2016 General Electric Company

* GE, the GE Monogram, Imagination at work, Healthymagination, Optima, FlashPad, and Giraffe are trademarks of General Electric Company.

Reproduction in any form is forbidden without prior written permission from GE. Nothing in this material should be used to diagnose or treat any disease or condition. Readers must consult a healthcare professional. DOC1913974

DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information.