



Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

Golden West Product Specification & Data Sheets

Interactive Table of Contents:

Click on any individual description to jump to that data sheet.

Golden West Antifreeze/Coolants

- [Global Antifreeze and Summer Coolant](#)
- [Global Antifreeze and Summer Coolant 50/50 Blend](#)
- [Antifreeze and Summer Coolant](#)
- [Antifreeze and Summer Coolant 50/50 Blend](#)

Automatic Transmission Fluid

- [Dexron VI Automatic Transmission Fluid](#)
- [DIII/M Automatic Transmission Fluid](#)
- [Multi-Vehicle Automatic Transmission Fluid](#)
- [Synthetic Trans-Fluid 50](#)
- [Type "F" ATF](#)
- [Automatic Transmission Fluid Type "A"](#)

Engine Oils

- [Semi-Syn Premium GF-4 Motor Oils](#)
- [10W40 Motor Oil](#)
- [15W40 Heavy Duty Diesel Engine Oil - CJ-4](#)
- [15W40 Heavy Duty Diesel Engine Oil - CJ-4 PFO](#)
- [High Mileage Premium 10W30 Motor Oils GF-4](#)
- [Series 3 and Heavy Duty Motor Oils](#)
- [Non-Detergent Motor Oil SAE 30W & SAE 40W](#)

Gear Oils

- [Full Synthetic Gear Oils](#)
- [Gear Oil 80W 90LS](#)
- [EP Gear Oil 90W & 140W](#)
- [Gear Oil 90 & 140](#)
- [Gear Oil 85W 140](#)
- [Fleet Gear Oil 90W](#)

Grease

- [Hi-Temp Red Grease](#)
- [Multi-Purpose Lithium Grease #2](#)

Hydraulic Oils

- [Premium Universal Tractor Fluid](#)
- [DynaTrac 303](#)
- [Anti-Wear Hydraulic Fluid](#)
- [Hydraulic AW 10WT](#)
- [R&O Hydraulic Oil 32, 46, 100 & 150](#)
- [R&O Hydraulic Oil](#)
- [Hydraulic Oil PMO](#)
- [Fleet Tractor Hydraulic Fluid](#)
- [Fleet Hydraulic Oil with R&O](#)

Power Steering/Brake Fluids

- [Heavy Duty DOT3 Brake Fluid](#)
- [Power Steering Fluid](#)

Solvent

- [Safety Solvent](#)

Specialty Oils

- [Rock Drill Oil 150, 100 & 46](#)
- [C2/C3 Torque Fluid](#)
- [Chain Oil](#)
- [Cotton Spray Oil](#)
- [Premium Drip Oil](#)
- [Regular Non-Detergent Oil](#)
- [Turbine Oil](#)
- [Twin Disc Fluid](#)

Various

- [Brake Parts Cleaner — Non-Chlorinated](#)
- [Brake Parts Cleaner — Chlorinated](#)
- [Throttle Body / Choke & Carburetor Cleaner](#)
- [Heavy Duty Glass Cleaner](#)
- [Windshield Washer Fluid](#)
- [Bar & Chain Oil](#)

[Back to Home](#)

Data Sheet: Global Antifreeze and Summer Coolant



Available:



BULK



55/1



6/1 Gal.s

This product is also comparable with the following industry specifications as a concentrate or pre-diluted antifreeze/coolant: TMC RP 329 Type A/302A-1 • SAE J1034, J1038 • GM 1825M/1899M/6277M • Cummins 90T8-4, 3666132 • Detroit Diesel 7SE298 • Caterpillar EC-1, ELC • John Deere H-5, 8650-5 • Freightliner 48-22880 • Ford ESE-M97B44-A, ESE-M97B44-B • Chrysler MS 7170 • Case JIC-501, MS1710 • Waukesha 4-19470 • Mack 014GS17004

Physical Properties	
Antifreeze Glycols	mass % 95.0 min.
Corrosion Inhibitors	mass % 2.1
Water	mass % 2.9
Flash Point	250°F
Weight Per Gallon@60°F	19.30-9.40lbs.
Silicon	<1 ppm
Freeze Protection is at 70%	
Percentage Antifreeze	50
Freezing Point	-34°F/-36°C
Boiling Point	226°F/107°C
Boiling Point shown using conventional 15 psi radiator cap.	

Product Application:

Golden West Global Antifreeze and Summer Coolant possesses a proprietary combination of complex carboxylic acid derivatives along with nitrite to protect all six standard metal alloys, (iron, copper, brass, solder, aluminum, and steel) found in radiator systems. Its hybrid organic acid technology (HOAT) additive package is formulated with a stabilization with both conventional inorganic salts and OAT-type antifreezes.

Golden West Global Antifreeze and Coolant contains no phosphates, nitrates, borates, or silicates. In addition, the product will not cause turbidity, precipitation, or inhibitor effectiveness reduction when mixed with carboxylate-based coolants such as Dex-Cool or Texaco Extended life nor with conventional coolants such as Prestone, Zerex, and Peak. In automobiles, this antifreeze should provide service life in excess of 5 years or 150,000 miles. It is ideal for initial fills, coolant change-outs or top-off.

Golden West Global Antifreeze and Summer Coolant meets ASTM D-3306 (Automotive Pre-diluted Coolant), ASTM D-4985 (Heavy Duty Pre-diluted Coolant), and ASTM D-6210 (Fully Formulated Pre-charged).

Test Number & Description	Specifications	Typicals	ASTM Method
Chloride	25ppm, max	<25	D-3306
Nitrate	2400ppm, min.	2890	D-5827
Special Gravity	1.115-1.125	1.120	D-1122
Freezing Point, 50% V/V	-34°F/-36°C, max	-34°F/-36°C	D1177
Boiling Point, undiluted	325°F/162°C, min	330°F/164°C	D-1120
Boiling Point, 50% V/V	226°F/107°C, min	226°F/107°C	D-1120
Effect on Engine Finish	No Effect	No Effect	-
Ash content, mass %	5 max.	2.5-2.7	D1119
pH, 50% V/V	8.5-10	9.0-10.0	D-1287
Reserve Alkalinity	N/A	2.0-5.0	D-1121
Water mass %	5 max.	<5	D-1123
Color	Distinctive	Varies with dye	
Effect on Nonmetals	No Adverse Effect	No Adverse Effect	
Cavitation-erosion rating	8 min.	>8	D2809
Corrosion of Aluminum	<1 mg/cm ² /wk	<0.1 mg/cm ² /wk	D-4340

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Global Antifreeze and Summer Coolant 50/50 Blend*



Available:



BULK



55/1



6/1 Gal.s

Product Application:

Golden West Global Antifreeze and Summer Coolant possesses a proprietary combination of complex carboxylic acid derivatives along with nitrite to protect all six standard metal alloys, (iron, copper, brass, solder, aluminum, and steel) found in radiator systems. Its hybrid organic acid technology (HOAT) additive package is formulated with a stabilization with both conventional inorganic salts and OAT-type antifreezes.

Golden West Global Antifreeze and Coolant contains no phosphates, nitrates, borates, or silicates. In addition, the product will not cause turbidity, precipitation, or inhibitor effectiveness reduction when mixed with carboxylate-based coolants such as Dex-Cool or Texaco Extended life nor with conventional coolants such as Prestone, Zerex, and Peak. In automobiles, this antifreeze should provide service life in excess of 5 years or 150,000 miles. It is ideal for initial fills, coolant change-outs or top-off.

Golden West Global Antifreeze and Summer Coolant meets ASTM D-3306 (Automotive Pre-diluted Coolant), ASTM D-4985 (Heavy Duty Pre-diluted Coolant), and ASTM D-6210 (Fully Formulated Pre-charged).

* Please note that values below are not diluted. Our 50/50 blend reduces this protection by approximately one-half.

This product is also comparable with the following industry specifications as a concentrate or pre-diluted antifreeze/coolant: TMC RP 329 Type A/302A-1 • SAE J1034, J1038 • GM 1825M/1899M/6277M • Cummins 90T8-4, 3666132 • Detroit Diesel 7SE298 • Caterpillar EC-1, ELC • John Deere H-5, 8650-5 • Freightliner 48-22880 • Ford ESE-M97B44-A, ESE-M97B44-B • Chrysler MS 7170 • Case JIC-501, MS1710 • Waukesha 4-19470 • Mack 014GS17004

Physical Properties	
Antifreeze Glycols	mass % 95.0 min.
Corrosion Inhibitors	mass % 2.1
Water	mass % 2.9
Flash Point	250°F
Weight Per Gallon@60°F	19.30-9.40lbs.
Silicon	<1 ppm
Freeze Protection is at 70%	
Percentage Antifreeze	50
Freezing Point	-34°F/-36°C
Boiling Point	226°F/107°C
Boiling Point shown using conventional 15 psi radiator cap.	

Test Number & Description	Specifications	Typicals	ASTM Method
Chloride	25ppm, max	<25	D-3306
Nitrate	2400ppm, min.	2890	D-5827
Special Gravity	1.115-1.125	1.120	D-1122
Freezing Point, 50% V/V	-34°F/-36°C, max	-34°F/-36°C	D1177
Boiling Point, undiluted	325°F/162°C, min	330°F/164°C	D-1120
Boiling Point, 50% V/V	226°F/107°C, min	226°F/107°C	D-1120
Effect on Engine Finish	No Effect	No Effect	-
Ash content, mass %	5 max.	2.5-2.7	D1119
pH, 50% V/V	8.5-10	9.0-10.0	D-1287
Reserve Alkalinity	N/A	2.0-5.0	D-1121
Water mass %	5 max.	<5	D-1123
Color	Distinctive	Varies with dye	
Effect on Nonmetals	No Adverse Effect	No Adverse Effect	
Cavitation-erosion rating	8 min.	>8	D2809
Corrosion of Aluminum	<1 mg/cm ² /wk	<0.1 mg/cm ² /wk	D-4340

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

PRODUCT SPECIFICATIONS

[Back to Home](#)

Data Sheet: Antifreeze and Summer Coolant

Product Application:



Available:



BULK



55/1



6/1 Gal.s

Golden West Antifreeze and Summer Coolant is compatible with other major brands and satisfies the requirements for "low silicate" type coolants, and, as such, is suitable for use where the following specifications are required:

GM1825M (Automotive Performance Standard for GM6043M); GM1899M (Automotive Performance Standard for GM6038M); Ford ESE-M97B44-A; Chrysler MS 7170; CSMA; SAE Standard J1034 and J1941; ASTM D3306, D4340, D4985; Maintenance Council of American Trucking Association (ATA), RP302; Cummins 90T8-4 (for low silicate equipment) and 85T8-2; General Services Administration A-A-870A; International Harvester B1; Mack Truck 014-GS-17004; J.I. Case JIC-501; Caterpillar

Golden West Antifreeze and Summer Coolant is a premium, ethylene glycol antifreeze/coolant for use in year round service in both aluminum and conventional metal engine cooling systems of automobiles, trucks, marine and stationary equipment. Formulated with a unique "low silicate" type rust and corrosion inhibitor system which effectively alleviates the problems of "gel" formation seen in many coolant systems using conventional coolants of the "high silicate" type and prevents loss of radiator heat transfer capacity.

Test Number & Description	Test Result	ASTM D-4985 accepted value
D-1122, Specific Gravity	1.129	1.110 - 1.145
D-1177, Freeze Point	-35.9°F	-34°F max. or lower
D-1120, Boiling Point @100%	325°F	325°F min.
D-1120, Boiling Point @50%	226°F	226°F min.
D-1182, Auto Finish Effect	No Effect	No Effect
D-1119, Ash Content	1.10%	5% max.
D-1287, pH 1+1 V/V	11.0	7.5 - 11.0
D-5827, Chloride	23	25 ppm max.
D-1123, Water P% (as rec'd)	2.7%	5% max.
D-1121, Reserve Alkalinity	11.3	n/a
D-1881, Foaming Tendencies	Break: 1.7 sec/Vol. 50ml	Break: 5 sec/Vol. 150ml
Color	Bright Green	Bright Green
Test Description	Amount Found	ASTM D-4985 accepted value
Silicone	250 ppm	250 ppm max.

These values are representative of current production. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS





Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Antifreeze and Summer Coolant 50/50 Blend*

Product Application:



Golden West Antifreeze and Summer Coolant is a premium, ethylene glycol antifreeze/coolant for use in year round service in both aluminum and conventional metal engine cooling systems of automobiles, trucks, marine and stationary equipment. Formulated with a unique "low silicate" type rust and corrosion inhibitor system which effectively alleviates the problems of "gel" formation seen in many coolant systems using conventional coolants of the "high silicate" type and prevents loss of radiator heat transfer capacity.

* Please note that values below are not diluted. Our 50/50 blend reduces this protection by approximately one-half.

Available:



BULK



55/1



6/1 Gal.s

Golden West Antifreeze and Summer Coolant is compatible with other major brands and satisfies the requirements for "low silicate" type coolants, and, as such, is suitable for use where the following specifications are required:

GM1825M (Automotive Performance Standard for GM6043M); GM1899M (Automotive Performance Standard for GM6038M); Ford ESE-M97B44-A; Chrysler MS 7170; CSMA; SAE Standard J1034 and J1941; ASTM D3306, D4340, D4985; Maintenance Council of American Trucking Association (ATA), RP302; Cummins 90T8-4 (for low silicate equipment) and 85T8-2; General Services Administration A-A-870A; International Harvester B1; Mack Truck 014-GS-17004; J.I. Case JIC-501; Caterpillar

Test Number & Description	Test Result	ASTM D-4985 accepted value
D-1122, Specific Gravity	1.129	1.110 - 1.145
D-1177, Freeze Point	-35.9°F	-34°F max. or lower
D-1120, Boiling Point @100%	325°F	325°F min.
D-1120, Boiling Point @50%	226°F	226°F min.
D-1182, Auto Finish Effect	No Effect	No Effect
D-1119, Ash Content	1.10%	5% max.
D-1287, pH 1+1 V/V	11.0	7.5 - 11.0
D-5827, Chloride	23	25 ppm max.
D-1123, Water P% (as rec'd)	2.7%	5% max.
D-1121, Reserve Alkalinity	11.3	n/a
D-1881, Foaming Tendencies	Break: 1.7 sec/Vol. 50ml	Break: 5 sec/Vol. 150ml
Color	Bright Green	Bright Green
Test Description	Amount Found	ASTM D-4985 accepted value
Silicone	250 ppm	250 ppm max.

These values are representative of current production. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Dexron VI Automatic Transmission Fluid



DEXRON-VI ATF is a synthetic blend formulation designed for high performance that meets the strict requirements of GM's DEXRON-VI specification. DEXRON-VI ATF provides warranty protection for 2006 and newer GM vehicles, plus improved performance in older GM vehicles, wherever DEXRON is specified.

Product Benefits:

The advantages of DEXRON-VI ATF compared to Dexron/Mercon:

- Improved anti-wear protection which contributes to extended transmission life
- Excellent resistance against sludge and deposit formation
- Reduced-friction properties providing smooth gear shifting during low temperature use — helps prevent transmission vibration
- Improved oxidation and thermal stability
- Excellent low temperature performance

Vehicle Applications:

DEXRON-VI ATF provides warranty protection for 2006 and newer GM vehicles, plus improved performance in older GM vehicles, wherever DEXRON is specified.

Available:



Typical Properties	
Viscosity cSt@40°C	29.5
Viscosity cSt@100°C	5.83
Viscosity cSt@-40°C	11,500
Viscosity Index	145
Flash Point, °C (°F)	220 (428)
Gravity, API	35.76
Color	Red

Dexron and Dexron-VI are registered trademarks of GM.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: **DIII/M Automatic Transmission Fluid**



Available:



BULK



55/1



5/1



12/1 Quarts

Benefits

- Excellent low temp. fluidity for good cold-start shifting
- Resistance to foaming
- Oxidation and thermal stability for long life
- Protection against rust, corrosion and wear
- Multiple approvals for lower inventory requirements
- Compatible with all transmission seal material

DIII/M Automatic Transmission Fluid (ATF) is recommended as a replacement fluid for former Dexron III/Mercon H specification. This product is also recommended for Detroit Diesel Allison C-3, C-4 application, Caterpillar TO-2, Ford late model C-4 and C-5 transmissions, and Ford ESP-M2C138-CJ and Ford ESP-M2C166-H.

Typical Analysis:

@40° C, cSt	37.0
@100° C, cSt	7.2
@100° C, SUS	164
@210° C, cSt	49.7
Viscosity Index	161
Pour Point COC, °F	-50
Flash Point COC, °F	378
Dexron III G, Dexron III Approved for H Spec.	Yes
Mercon	Yes
Mercon V	No
Allison C-4	Yes
ZF TE-ML	No
Voith	No
Cat TO-2	Yes

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Multi-Vehicle Automatic Transmission Fluid



Product Application:

Multi-Vehicle ATF is a special blend of high quality synthetic and mineral base stocks with an advanced additive system for automatic and power shift transmissions. It is fully qualified as a Dexron III (H), Mercon, Mercon V and Allison C-4 fluid. It is recommended for all Chrysler automatic transmissions and can function as a Caterpillar TO-2 lubricant.

Multi-Vehicle ATF provides protection that meets or exceeds the highest quality standards in the industry. It protects against shudder, eliminates the need to stock ATF supplements and ensures a high-performance smooth driving experience. Carefully balanced friction modifiers allow friction retention for long life performance and maintains the smooth lock-ups required by a variety of vehicles. Enhanced oxidation, thermal stability and corrosion resistance helps maintain year-round protection of the transmission components.

Multi-Vehicle ATF can be used in passenger car manual transmissions, trucks and buses, off-highway construction/mining equipment, agricultural equipment, mobile hydraulic systems, industrial machinery, and power steering systems where Dexron, Dexron II, Dexron IIE, Dexron III (H), Mercon or Mercon V type fluids are specified.

Available:



- Anti-shudder protection
- Oxidation and thermal stability
- Anti-Wear performance
- Excellent cold temperature flow
- Protects from corrosive acids
- Compatible with seal materials to prevent leaks
- Year-round performance

Technical Specifications	MIN	MAX
Appearance	Red	Match
Phosphorus	160	260
Flash Pt. (PMCC), °C	145	190
SP. Gr.@15.6°C	Typical	0.86
Viscosity@100°C, cSt	6.6	8
VI	150	179
Brookfield Visc@-40°C, cP	Typical	13,000 cps

Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Synthetic Trans-Fluid 50

Product Application:

Golden West Synthetic Trans-Fluid 50 was developed specifically for long life use in heavy duty manual transmissions which specify a premium quality non-E.P. oil. Golden West Synthetic Trans-Fluid 50 matches the requirements set by Eaton and Rockwell for 250,000 mile extended drain intervals. Meets TO-4 application.

Available: Bulk, 55/1, 120#, 5/1, 6/1



Available:



BULK



55/1



120lb. Keg



5/1



6/1 Gal.s

Typical Test Data	
API Gravity	32.46
Specific Gravity 60/60°F	0.863
Viscosity@40°C	135
Viscosity@100°C	18.04
Color, ASTM	3.5
Water and Sediment	Pass
Appearance	Amber
lb./Gal	7.19
Flash Point	435°F
Pour Point	0

These values are representative of current production. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Type "F" ATF

Automatic Transmission Fluid



This product is a red-dyed automatic transmission fluid meeting all of the requirements of Ford Specification M2C33-F, and is qualified and approved by Ford Motor Company.

Ford ATF is designed specifically for use in all automatic transmissions of cars and trucks manufactured by Ford Motor Company, except 1977 and later C-6 transmissions and certain other recent transmissions for which Ford ESP M2C138-CJ or Mercon-DEXRON® Type fluid is recommended.

Typical Analysis:	
Appearance	Red, Dyed
Vis @ 40° C, cSt	39.1
Vis @ 100° C, cSt	7.44
Viscosity Index	160
Pour Point,	-40
Flash Point COC, F	340
SAE Grade	10W20 Approximately

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. They may vary within modest ranges.

Available:



Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Automatic Transmission Fluid Type "A"



Available:



BULK



55/1



5/1



12/1 Quarts

Description:

This product is formulated with a non-detergent pale oil and red dye to provide a low-priced ATF to use as a make-up ATF in older model vehicle automatic transmissions.

Product Application:

To be used as add-on ATF in older model automobile transmissions. Not recommended for total fill on newer automobile transmissions.

Typical Inspections	
Viscosity cSt at 100°F	200-220
Gravity at 60°F	19.0
COC Flash °F	245
Pour Point °F	+15
Sulphur %	.05
ASTM Color (Red)	2.0

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Premium GF-4 Motor Oils



NOW Synthetic Blend!

Product Application: SM and GF-4

Golden West 10W30 Passenger Car Motor Oils (PCMO) are superior quality, high detergent automotive engine oils specifically formulated to meet the stringent requirements of today's engines. High viscosity index Group II base oils are combined with a carefully selected additive package to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits.

API Classifications

SM	SL	SJ	SH	Complies with ILSAC GF-4 requirements
----	----	----	----	---------------------------------------

Meets or Exceeds Requirements of

MIL-1-46152E	Ford WSS-M2C153-H	Ford WSS-M2C930-A	GM-6048M	GM-6049M
--------------	-------------------	-------------------	----------	----------

Typical Analysis: GF-4	5W20	5W30	10W30
@40° C, cSt	47.36	68.5	76.3
@100° C, cSt	8.05	10.5	11.2
Viscosity index	142	150	136
API Gravity	0.8634	0.6767	0.6811
Flash, COC, °F	428	420	405
Pour Pt, °F	-35	-30	-30
TBN	7.0	7.0	7.0
Zinc, Wt. %	0.0845	0.0845	0.0845
Phosphorous, Wt. %	0.0768	0.0768	0.0768
API Performance	SM	SM	SM

Available:



BULK



55/1



5/1



12/1 Quarts

Benefits

- Resists breakdown under high temperatures
- Helps protect emissions systems
- Minimizes rust and corrosion
- Good temperature pour point
- Universal product for consolidation of products

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: 10W40 Motor Oil

Product Application:

Golden West 10W40 Motor Oil is a premium quality engine oil recommended for gasoline engines requiring a "SL" specification lubricant. This product is a blend of highly refined paraffinic base stock and the most recent additive package to give the engine maximum protection in severe duty operation.



Typical Analysis	
Vis cSt @ 100°C	14.1
Vis cSt @ 40°C	100.5
Viscosity index	134
Pour point °F	-30
Flash Point °F	420
Sulfated ash % wt.	<1.0

Available:



12/1 Quarts

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

PRODUCT SPECIFICATIONS

[Back to Home](#)

Data Sheet: 15W40 Heavy Duty Diesel Engine Oil

Product Application: CJ-4



Available:



Golden West Heavy Duty Diesel Engine Oil is recommended for all major automotive diesel operations.

API Classifications

CJ-4	CI-4 Plus	CH-4	Cf-2	SL	SJ
------	-----------	------	------	----	----

Meets Requirements:

Meets Requirements:	
Golden West Heavy Duty 15W40 CJ-4	✓
API CJ-4, CI-4 Plus, CH-4, CG-4, CF-4, CF/SM, SL, SJ, SH	✓
Caterpillar ECF-1, ECF-3	✓
Cummins CES 20081, 20077, 20076	✓
Mack EO-0 Premium Plus 07, Mack EO-N Premium Plus 03, EO-N Premium Plus, EO-M Plus, EO-M	✓
Mercedes Benz 228.3	✓
MAN 3275	✓
DHD-1, ACEA E7 and E5	✓
Volvo VDS-4, VDS-3	✓
DDC Power Guard 93 K218	✓
Allison C-4	✓
Global DHD-1	✓
JASO DH-2	✓
Renault RLD-3	✓
Product Data	Typical
@ 40°C, cST	118.2
@ 100°C, cST	15.4
Viscosity Index	130
Sulfazed Ash, wt%	1.0
Pour Point °F	-36
TBN-E	10
Flash Point °F	460
API Performance	CJ-4

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929


Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

PRODUCT SPECIFICATIONS

[Back to Home](#)

Data Sheet: 15W40 Heavy Duty Diesel Engine Oil

Product Application: CI-4 SL



Available:



6/1 Gal.s 12/1 Quarts

Golden West Heavy Duty Diesel Engine Oil is recommended for all major automotive diesel and gasoline engine operations.

API Classifications

CI-4	CH-4	Cf-2	SL	SJ
------	------	------	----	----

Meets Requirements				Volvo
MIL-L-2104 F	Mack EO-k2	EO-L	EO-M	EO-M+
Cat. 1P	Cat. 1K	Cat. 1N	Cat. TO-2	Ford M2C133-A
Ford M2C153-E	Cummins CES20078	CES20072	CES20074	
CES20075	CES20078	Mercedes Benz	Navistar	ACEA
Duetz	Fiat-Allis	International	Isuzu	J.I. Case
John Deere	Komatsu	Kubota	Mitsubishi	Scania

Typical Analysis:

Vis @40° C, cSt	119
Vis @100° C, cSt	15.8
Vis @100° C, SUS	505
Vis @210° C, SUS	74
Viscosity Index	140
Sulfated Ash % wt.	1.2
Pour Point °F	-33
TBN-E	9.4
Flash Point Deg F	435
API Performance	CI-4, SL

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: High Mileage Premium 10W30 Motor Oils GF-4

Product Application: SM and GF-4



Golden West High Mileage Premium Motor Oil is formulated with a unique combination of special conditioning additives designed for vehicles over 75,000 miles. Golden West High Mileage Oil helps restore engine performance and extend engine life, provides enhanced protection for worn engine parts, helps prevent engine leaks and oil burn off, and helps condition seals in older engines. Excellent anti-aging detergent properties help keep engine parts clean and helps protect engines from overheating.

API Classifications

SM	SL	SJ	SH	Complies with ILSAC GF-4 requirements
----	----	----	----	---------------------------------------

Meets or Exceeds Requirements of

MIL-1-46152E	Ford WSS-M2C153-H	Ford WSS-M2C930-A	GM-6048M	GM-6049M
--------------	-------------------	-------------------	----------	----------

Typical Analysis: GF-4

Typical Analysis: GF-4	10W30
@40° C, cSt	76.3
@100° C, cSt	11.2
Viscosity index	136
API Gravity	0.6811
Flash, COC, °F	405
Pour Pt, °F	-30
TBN	7.0
Zinc, Wt. %	0.0845
Phosphorous, Wt. %	0.0768
API Performance	SM

Available:



Benefits

- For vehicles over 75,000 miles
- Resists breakdown under high temperatures
- Helps protect emissions systems
- Minimizes rust and corrosion
- Good temperature pour point
- Universal product for consolidation of products

Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS





Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Series 3 and Heavy Duty Motor Oils

Product Application:

Golden West Series 3 Heavy Duty Engine Oils are blended from the finest base stocks with the latest additive package to provide a high-performance engine oil for diesel and gasoline engines. API application varies by grade. These engine oils are premium quality for all-season use.



Available:



BULK



55/1



5/1



12/1 Quarts
(HD30 only)

Typical Analysis:

	Heavy Duty Series 3 - 10WT	Heavy Duty Series 3 - 30WT	Heavy Duty Series 3 - 40WT
Viscosity cSt@40°C	33.3	114	116
Viscosity cSt@100°C	5.7	11.8	14.9
Viscosity SUS@100°F		560	780
Viscosity SUS@210°F		65	65
Viscosity Index	110	92	92
Sulfated ASH %WT	<1.0	<1.0	<1.0
Pour Point	-3.0	-5	0
TBN-E (min)	7.0	7.5	7.5
Flash of	480	466	450
API	CD	CD	CD
	CF	CF-2	CF-2
	SJ	SJ	SJ

These values are representative of current production. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Non-Detergent Motor Oil SAE 30W & SAE 40W

Product Application:

A non-detergent pale oil packaged to provide a low-cost add-on product for 1950 and older automobile engines requiring "SA" specification oil. Also can be used in lawn mower engines.



Typical Analysis:

	30WT	40WT
Viscosity SUS@100°F	1200	2400
Gravity @60°F	17.0	15.0
COC Flash °F	325	325
Pour Point °F	+25	+25
Sulphur %	.05	.05
ASTM	4.0	4.0

These values are representative of current production. They may vary within modest ranges.

Available:



Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Full Synthetic Gear Oils

Product Application:

Golden West Full Synthetic Gear Oil is 100% synthetic, multi-grade, heavy duty gear lubricant designed to meet the service demands of the commercial fleet's manual transmissions, axles and drive units, plus the added advantage of improved fuel economy, extended drain capabilities and all season use even at sub zero temperatures. Golden West Gear Oils are fortified with additives to prevent rust and corrosion, and meets limited slip specifications.

Suitable for use where an API GL-5 and MT-1 are recommended. Also suitable for use where the following specifications are recommended: Eaton PS-163, PS-037, PS-109; General Electric D50E9C; Harnishfeger (P&H) 474; Mack Truck GO-J Plus; GO-J; Meritor Automotive, Inc. (formerly Rockwell International) O-76-E (petrol), O-76-N (syn); MIL-PRF-2105E; Navistar TMS 6816; U.S. Steel Specifications 224; AGMA Standard 250.03.



Available:



BULK



55/1



120lb. Keg



5/1



12/1 Quarts

Note: 80w140 Grade
Not Available in Quarts.

Typical Analysis:

Grade	75W-90	80W-140	75W-140
ISO	150	220	
AGMA	4-EP	5-EP	
Gravity, API	25.3	23.3	31.3
Viscosity cSt@40°C	128	262	176.4
Viscosity cSt@100°C	17.5	31.06	24.8
Viscosity Index	151	159	173
Color	1.5	2.0	2.0
Flash Point °F Minimum	400	400	396
Pour Point °F Minimum	-40	-20	-51

The values shown here are representative of current production and may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Gear Oil 80W 90LS

Product Application:

Golden West Gear Oil 80W 90LS is a multi-purpose, heavy duty, extreme pressure gear lubricant recommended for enclosed gear cases. Gear Oil 80W 90LS can be applied in full refill or top-off of Limited Slip Differentials. Please note that there could be instances when axle chatter may be present, and if this occurs, it is recommended to add at least 4oz. of after-market slip additive.



Typical Analysis:

Viscosity Index	95
Gravity °API	26.8
SUS@100°F	705
SUS@210°F	76
cSt@40°C	137
cSt@100°C	14.0
Color	7.0
Pour °F	-15
Flash °F	375
AGMA GL-5	

Available:



BULK



55/1



120lb. Keg



5/1



6/1 Gal.s



12/1 Quarts

These values are representative of current production.

Note: 6/1 gallon package, not limited slip
12/1qrt Package, not limited slip.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: EP Gear Oil 90W & 140W

Product Application:

EP Gear Oils are recommended for many types of manual transmissions, differentials and final drives, including worm-type gear. Meets many requirements for EP Gear Oils, including API, GL-2, GL-3, GL-4, GL-5. This product is blended from quality gear socks. The additive type is Sulfur-Phosphorus. Can be used for extreme pressure, Hypoid, or multi-purpose type gear oils.

This product is formulated for limited slip differentials.



Available:



Typical Analysis:			
		SAE90	SAE140
Gravity	°API	22.4	22.8
Flash Point	COC, °F	425	580
Pour Point, °F	°F	-5	+15
Viscosity	cSt@40°C	212	955
	cSt@100°C	15.0	40.6
	cSt@40°C	1140	2675
Viscosity Index	cSt@210°C	80	138
		58	65

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. They may vary within modest ranges.

Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Gear Oil 90 & 140

Product Application:

This lubricant is designed for the type of service characteristic of automotive spiral-bevel and worm-gear axles and some manually operated transmissions operating under mild conditions. Available is SAE 90 and SAE 140. These are pure mineral oils.

Gear oil utilizes high quality, refined base oils. Friction modifiers and extreme pressure agents are not employed in GL-1 oils.

Gear Oil is recommended for use in conventional transmissions, differentials, final drives and miscellaneous applications in hydraulic systems, gear cases, etc. of mobile equipment where GL-1 and /pr straight mineral oil is specified by the manufacturer.



Available:



Typical Analysis:		
SAE Grade	Gear 90	Gear 140
Gravity, °API (1)	18.0	21.0
Flash Point, °F	390	580
Viscosity, cSt@100°C	17.3 - 18.6	40.1
Viscosity, SUS@210°F	90-95	138
Viscosity Index, Min.	58	69
Pour Point °F	5	+15
Foam Test (3)	Pass	Pass

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Gear Oil 85W 140

Product Application:

Golden West gear oils are formulated from the finest base oils and premium additive packages. They carry extreme pressure properties, resist wear, and have excellent oxidation stability. This gear oil is in compliance with all manufactures specifications, and recommended for severe service.

API Service: GL-5



Available:



BULK



55/1



120lb. Keg



5/1



6/1 Gal.s



12/1 Quarts

Typical Analysis:	
SAE Grade	85W 140
API Gravity	24.0
Flash COC °F	425
Pour Point °F	+5
Viscosity cSt@40°C	385
Viscosity cSt@100°F	2172
Viscosity SUS@210°F	133.3
Sulfur %	2.0
Phosphorus	0.10
Viscosity Index	96

The values shown here are representative of current production and may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Fleet Gear Oil 90W

Product Application:

This lubricant is designed for the type of service characteristic of automotive spiral-bevel and worm-gear axles and some manually operated transmissions operating under mild conditions. These are pure mineral oils.

Fleet Gear Oil utilizes medium quality, refined base oils. Friction modifiers and extreme pressure agents are not employed in GL-1 oils.

Fleet Gear Oil is recommended for use in conventional transmissions, differentials, final drives and miscellaneous applications in hydraulic systems, gear cases, etc., of mobile equipment where GL-1 and/or straight mineral oil is specified by the manufacturer.



Available:



Typical Analysis:	
SAE Grade	Gear 90
Gravity, °API (1)	18.0
Flash Point, °F	390
Viscosity cSt@100°C	17.3 - 18.6
Viscosity SUS@210°F	65
Viscosity Index, Min.	44
Pour Point °F	+15
Foam Test (3)	Pass

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Hi-Temp Red Grease

Product Application:

Golden West Hi-Temp Red Grease is a NLGI 2 grade premium quality extreme pressure lithium complex multi-purpose grease. This product has outstanding high temperature characteristics. Dropping point of this product exceeds 500°F.

Recommended for fleets and heavy-duty applications, including wheel bearings (disc and drum brakes). - NLGI Service classification-GC-LB.



Available:



400 lb. Drum



120lb. Keg



5/1



14oz. Tube

Characteristics of Base Oil	
Viscosity cSt@100°C	15.74
Viscosity cSt@40°C	214.0
Viscosity Index	67
Pour Point, °F (°C)	+5 (-15) Max
Flash Point, °F	425 (218) Min
Timken	45

Typical Analysis	
NLGI Consistency Number	2
Thickener	Lithium Complex
Texture	Smooth, Adhesive
Color Observed	Red
Worked 60 Penetration, D-217	265-295
Dropping Point, D-2265°F (°C)	500 (260)
Wheel Bearing Leakage, D-4290, g Loss	1.4
Water Washout, D-1264, % loss	4.1@175°F
Rust Prevention, D-1743, rating	Pass
Copper Corrosion, D-4048, rating	Pass
Oxidation Stability, D-942, psi drop	10 max@100 hrs
Oil Separation, D-1742, % loss	1.2
Four-Ball War, D-2266, mm	0.54
Four-Ball EP Weld Point, D-2596, kgf	315
Four-Ball Load Wear Index, D-2596, kgf	50
High Temp Life, D-3527, hrs	100
Low Temp Torque, D-4693, N-m	13.0
Fretting Wear, D-4170, mg	7.8
Elastomer Compatibility, D-4289:	
CR Volume Change @ 100°C, %	24
CR Hardness Change @100°C, pts	-9
NRB-L Volume Change @ 150°C, pts	27
NRB-L Hardness Change @ 150°C, pts	-10
Approximate Temperature Range, °F (°C)	-10 to 325 (-23 to 163)

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS





Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Multi-Purpose Lithium Grease #2



Available:



55/1



120lb. Keg



5/1



14oz. Tube

Product Application:

Golden West Multi-Purpose Lithium Grease is an amber colored, NLGI 2 grade lithium stearate based grease with rust and oxidation inhibitors. It has good stability, water resistance and softening resistance at high operating temperatures.

Golden West Multi-Purpose Lithium Grease is recommended for general automotive chassis lubrication points, ball joints and universal joints, as well as general farm and light industrial lubrication applications. It is compatible with other lithium grease, but is not recommended for disc type wheel bearings.

Typical Characteristics:	
NLGI Consistency Number	2
Thickener	Lithium Stearate
Texture	Smooth
Color, Observed	Amber
Worked 60 Penetration, D-217	265-295
Dropping Point, D-566 °F (°C)	340 (171)
Characteristics of Base Oil	
Viscosity @ cSt@40°C	152
Viscosity @ cSt@100°C	11.8
Viscosity @ cSt@210°F (SUS)	12.2 (67.0)
Viscosity @ cSt@100°F (SUS)	175 (8130)
Viscosity Index	50
Timken (approximate)	30

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Premium Universal Tractor Fluid

Product Application:



Golden West Premium Universal Tractor Fluid is a high quality specifically compounded lubricant containing anti-foam, anti-rust and oxidation inhibitors blended with other additives necessary for a wide range of applications. Their product handles temperature extremes in an excellent manner. Users will appreciate the multipurpose application for transmissions, final drives and hydraulic systems of tractors.

Advantages:

- Protection from seal and pump deterioration
- Reduces brake chatter
- Meets latest manufacturers specifications including J-20C

Available:



Tractor Hydraulic is suitable for use where the following specifications are recommended:

John Deere: Quatrol, J20A, J20C, J21A, Hy-gard J14B/C, Type 303

International Harvester: Hy Tran, B-6, B-7

Massey Ferguson: M-1110, M-1127B, M-1129A, M01135 (European), M-1141 (Permatran III)

Allis Chalmers: Power Fluid 821 XL

White Farm Equipment: Q1705, Q1722, Q1766B (UHTF Type 55), Q1802, Q1826

J.I. Case/David Brown: TFD (JIC - 143/146),

Hi-Vis (JIC-185), JIC-144/145, MS-1204, MS-1205 (TFD II)/-1206 (powergard PTF)/-1207 (HyTran Plus) MS-1210 (TCH) and B-6

Ford New Holland: M2C86-A/B/C (European), M2C134-A/B/C/D, M2C41-B, M2C43, M2C53-A/B, M2C92-A

Detroit Diesel Allison Division: C-2, C-3, C-4 Fluid

Caterpillar: TO-2

Oliver: Type 55

Sauer-Sunstrand: HMS-103

Deutz: HTF

Versatile: HY-Gear (23M, 24M)

Stieger: HTF (SEMS 17001)

Vickers: I-2986-S

Kubota Universal Transdraulic Fluid: UTD

Typical Analysis:

	Range
API Gravity @60°F	28-30
Viscosity Index	75-125
Pour Point, °F	-20 to -30
Flash Point, °F	300-400
Viscosity cSt@40°C	40-65
Viscosity cSt@100°C	7.5-9.5
Viscosity cSt@100°F	200-300

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702

Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219

Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605

Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415

Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380

Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041

Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504

Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: DynaTrac 303 Multi-Service Tractor Hydraulic Fluid



Available:



DynaTrac 303 Hydraulic Fluid is an economical tractor hydraulic fluid blended to meet the requirements of manufacturers make-up service applications. This product has an EP additive package to give good wear and oxidation protection, along with foam reduction. This multiservice application permits the user to utilize one product for farm and construction equipment that requires an economical fluid where leaks are a problem. For broader and severe service applications we recommend Golden West Premium Universal Tractor Fluid.

Typical Analysis:

	Range
API Gravity @60°F	28-30
Viscosity Index	75-125
Pour Point, °F	-20 to -30
Flash Point, °F	300-400
Viscosity cSt@40°C	40-65
Viscosity cSt@100°C	7.5-9.5
Viscosity cSt@100°F	200-300

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

PRODUCT SPECIFICATIONS

[Back to Home](#)

Data Sheet: **Anti Wear Hydraulic Oil ISO Grades 32, 46 & 68**



Available:



Product Application:

Golden West Premium Anti Wear Hydraulic oils are blended of High VI solvent neutral base stocks. These stocks provide excellent temperature extremes protection. Additive packages contain, anti-wear, anti-foam, rust inhibitors and anti-oxidation agents. Additionally this Lubrizol additive package contains seals well ingredients to keep seals tight.

Typical Inspections			
ISO Grade	32	46	68
Viscosity cSt at 40°C	30.1	42	58
Viscosity cSt at 100°F	5.2	5.0	7.0
Viscosity SUS at 100°F	160	216	325
Viscosity SUS at 210°F	44	43	48
Viscosity Index	103	95	95
Pour Point °F	-35	-30	-25
Flash Point °F	401	410	422
Color	2.0	2.5	2.5
Carbon Residue W+%	.01	.01	.01

Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Hydraulic AW 10WT

Product Application:

10WT Hydraulic Oil is a high quality multi-purpose oil that can be used in all hydraulic applications that call for a light oil application, except for pumps such as LUCAS, with silver alloy bearings. It is an excellent choice for applications requiring premium, rust and oxidation-inhibited circulating oils, even though the anti-wear properties may not be required.



Available:



Typical Inspections	
Viscosity cSt at 40°C	30.1
Viscosity cSt at 100°C	5.17
Viscosity cStat 108°F	155
Viscosity SSU at 210°F	43.6
Viscosity Index	101
Gravity API at 60°F	31.7
Color	L 1.5
Pour Point	-9°C
	15°F
Flash Point	207°C
	405°F

Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: R&O Hydraulic Oil 32, 46, 100 & 150

Product Application:

R&O Hydraulic Oil is a high-grade utility hydraulic oil used in hydraulically activated equipment. Other uses include machine tools, hydraulic jacks, hoist etc. Additionally Golden West R&O can be used a drip oil or common machine oil.

Characteristics:

R&O Hydraulic Oil is blended with premium pale blend stocks and compounded with rust and oxidation inhibitors and foamleration suppressant.



Available:



Typical Inspections				
ISO Grade	32	46	100	150
Viscosity at 100°F (SUS)	16.5	227	525	780
Gravity API 60°F	31.5	30.0	28.4	28.9
Color ASTM	1.5	1.5	1.5	2
Sulphur Wt. %	.07	.06	.06	.06
Flash Point	325°F	330°F	332°F	340°F
Pour Point	+10°F	+12°F	+14°F	+15°F

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: R&O Hydraulic Oil

Product Application:

R&O Hydraulic Oil is a high-grade utility hydraulic oil used in hydraulically activated equipment. Other uses include machine tools, hydraulic jacks, hoist etc. Additionally Golden West R&O can be used as a drip oil or common machine oil.

Characteristics:

R&O Hydraulic Oil is blended with premium pale blend stocks and compounded with rust and oxidation inhibitors and foam-aeration suppressant.



Available:



Typical Inspections	
ISO Grade	32
Viscosity at 100°F (SUS)	16.5
Gravity API 60°F	31.5
Color ASTM	1.5
Sulphur Wt. %	.07
Flash Point	325°F
Pour Point	+10°F

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Hydraulic Oil PMO

Product Application:

This Hydraulic Oil is a pure mineral oil with no additive package.

Applications: Generally recommended where temperature extremes are not present. This low VI, low priced product can be used in floor jacks, hydraulic lifts, and certain heavy leak applications.



Typical Inspections	
Viscosity at 100°F	200
Gravity API 60°F	19
Flash Point °F	345
Pour Point	+10°F
Sulphur %	.05

Available:



Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Fleet Tractor Hydraulic Fluid

Product Application:

Fleet Tractor Hydraulic Fluid is blended as an economical make-up fluid. Recommended for use in an older tractor's hydraulic system.



Typical Inspections	
Gravity API at 60°F	20.2
Viscosity cSt at 100°C	7.7
Viscosity Index	62
Flash Point	350°F
Pour Point	+10°F

Available:



Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Fleet Hydraulic Oil with R&O

Product Application:

Fleet Hydraulic Oil is a medium grade utility hydraulic oil used in hydraulically activated equipment. Other uses include machine tools, hydraulic jacks, hoists etc. Additionally Fleet R&O can be used as a drip oil or common machine oil.

Characteristics:

Fleet Hydraulic Oil is blended with Low VI pale blend stocks and compounded with rust and oxidation inhibitors and foam/aeration suppressant.



Available:



Typical Inspection	
ISO Grade	32-46
Viscosity at 100°F (SUS)	165
Gravity API 60°F	22
Color ASTM	1.5
Sulphur Wt. %	.07
Flash Point	325°F
Pour Point	+20°F

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS





Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Heavy Duty Dot 3 Brake Fluid

Product Application:

Golden West Heavy Duty Brake Fluid is a fully approved DOT 3 type motor vehicle brake fluid suitable for use in all vehicles where DOT 3 fluids are recommended. Suitable for use on both disc and drum brake systems and fully compatible with all DOT 3 fluids.

Meets or exceeds the requirements of DOT 3 Motor Vehicle Standard No. 116 and SAE J1704 and ISO 4925.



Available:



6/1 Gal.s



12/1 Quarts



12/1 12oz

Property	Specification	Typical Data
Dry Boiling Point, Min.	401°F	440°F
Wet Boiling Point, Min.	284°F	288°F-292°F
pH	7.0-11.5	10.5
Viscosity cSt@-40°C	MAX 1500	1400-1450
Specific Gravity	1.01-1.04	1.02
Pounds Per Gallon	8.6-8.6	8.7
Color	Light Amber	Light Amber
Appearance	Clear	Clear
Corrosion, FMVSS 116	Pass	Pass
Rubber Swell, FMVSS 116	Pass	Pass
Evaporation/Weight Loss	MAX 60%	40-55%

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Power Steering Fluid

Product Application:

Golden West Power Steering Fluid is blended with high quality base oils and a balanced additive package to maintain efficiency and performance in power steering systems. It helps prevent leakage, squealing, corrosion, oxidation and wear.

Golden West Power Steering Fluid will not clog or foam and can be used year round.



Available:



12/1 Quarts



12/1 12oz

Typical Test Data	Specification	Typical Data
Viscosity, ASTM D2161		
SUS@100°F	210.00	200-215
SUS@210°F	44.00	44.00
Viscosity, ASTM D445		
cSt@40°C	40.20	38.2-41.2
cSt@100°C	5.30	5.30
Gravity, 60°F		
API, ASTM D287	23.200	23.200
Specific, ASTM D1250	.9147	.9147
Pounds Per Gallon	7.6170	7.6170
Color, ASTM D1500	0.5000	MAX 1.50
Pour Point, °F ASTM D97	-20.00	MAX -10.0
Flash Point, COC, °F ASTM D92	355.00	MIN 340.00
Aniline Point, °F ASTM D611	166.00	160-175.00
Sulfur, wt% ASTM D4294	.0500	.0500

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Safety Solvent



Product Application:

Golden West Safety Solvent is recommended for general cleaning of Petroleum based contaminated surfaces. This product has a high flash point of 142°F. Other uses include part washer fluid.

Typical Analysis	
Gravity API	45.4
Sulpher	.004
Flash Point	142°F
Pour Point	-30°F
Specific Gravity	1.0
Boiling Point	240°F

Available:



BULK



400 lb. Drum



5/1

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Rock Drill Oil 150, 100 & 46

Product Application:

Golden West Rock Drill Oil is recommended for pneumatic tools used under moderate atmosphere and operation conditions. Rock Drill Oil has EP capability, rust and oxidation control, and meets emission control standards.



Available:



	150	100	46
API Gravity	27.2	29.0	26.2
Viscosity SUS at 100°F	690	556	216
Viscosity SUS at 210°F	68	60	43
Viscosity Index	90	90	88
Pour Point °F	+15	-15	-20
Flash Point °F	400	380	360
Color		Caramel	Caramel

The values shown here are representative of current production. Some are controlled by Manufacturing Specifications while others are not. All of them may vary within modest ranges.

Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: C2/C3 Torque Fluid

Product Application:

C-3 fluid is a specialty product meeting the performance requirements of the Detroit Diesel Allison Division of General Motor, Spec C-3. It has been developed for their automatic transmissions (except AT-MT-HT-V series which require Dexron III Transmissions Fluid), power shift transmissions and industrial torque converters.



Available:



55/1

5/1

Typical Inspection		
API Gravity	API at 60°F	29.6
Viscosity	cSt at 40°C	40.5
	cSt at 100°C	6.62
	SSU at 100°F	208
	SSU at 210°F	48.4
Viscosity Index		116
Pour Point °F	C°	-29
Flash Point °F	C°	224
	F°	435
Sulfated Ash		0.9
Quality Level		C-3

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Chain Oil

Product Application:

A multi-purpose lubricant commonly used on exposed metal surfaces, wire ropes and chains. Widely used on drilling rigs for general purpose lubricant. This is a premium pure mineral oil.



Typical Inspection	SAE 20W	
Viscosity	SUS 100°F	1200
API Gravity		15°
Color, ASTM		3.0
Flash Point	COC °F	325
Pour Point	°F	+15

Available:



Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Cotton Spray Oil



This paraffinic and naphthenic base product is blended with pine oil and oil of citronella to provide a quality spray oil. Cotton Spray Oil is used to reduce static electricity and prevent rust when coming in contact with metal, and suppresses dust. Cotton Spray Oil does not leave stain on cotton.

Typical Analysis:

API Gravity at 60°F	23
Color ASTM D	L2
Flash °F	250
Pour Point	-10°F
Pounds Per Gallon	7.6
Viscosity SSU at 100°F	290

The values shown here are representatives of current production. Some are controlled by Manufacturing Specifications while others are not. All of them may vary within modest ranges.

Available:



Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Premium Drip Oil

Product Application:

Golden West Premium Drip Oil is blended with a highly refined solvent neutral paraffinic base stock. This product has a high viscosity index that adapts well to temperature extremes. This product is recommended for drip systems that encounter very low temperature situations as well as those that range well above the 100°F range.



Typical Analysis:	
Viscosity cSt 40°C	21.8
Viscosity cSt 100°C	4.2
Viscosity Index	97
Gravity, API 60°F	33.7
Flash COC°F	410
Color	1

These values are representative of current production. They may vary within modest ranges.

Available:



Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS





Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Regular Non-Detergent Oil

Product Application:

Golden West Regular Oil is a Napthenic base oil that does not contain any additive package. This Non-Detergent product is recommended for use where a pure mineral oil is required.



Typical Analysis:

SAE	10WT	20WT	30WT	40WT	50WT
Viscosity@40°C	22	54	86	118	140
Viscosity Index	70	74	78	77	77
Flash °F	315	320	325	325	400
Pour Point °F	10	15	20	25	25

Available:



Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Turbine Oil



Product Application:

Generally recommended where temperature extremes are not present. This low VI, low priced product can be used in floor jacks, hydraulic lifts, and certain heavy leak applications and certain low-speed turbine applications.

Typical Inspections	
Viscosity cSt at 100°C	200
Gravity API at 60°F	19
Flash Point °F	245
Pour Point °F	+10°F
Sulphur %	.05

Available:



Allied Sales Company
5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio
3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene
2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock
3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi
710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo
5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen
10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Twin Disc Fluid

Product Application:

Golden West Twin Disc Fluid is used in Torque Converters made only by Twin Disc Co.



Typical Analysis:		
Gravity		
Viscosity	SSU at 100°F	36.0
Color		Red
Pour Point	°F	-90
Flash Point	°F	200
Neutral No.		.03
Rust Test		Pass
Oxidation		Pass
Zinc	App. 1000 PPM (AW)	

Available:



The values shown here are representative of current production. Some are controlled by Manufacturing Specifications while others are not. All of them may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Brake Parts Cleaner – Non-Chlorinated



Available:



Aerosol Cans

NON-CHLORINATED

Flammable

Product Application:

This highly concentrated solvent blend provides maximum performance in a brake parts cleaner without the use of ozone depleting chlorinated solvents. Powerful blasting spray easily removes brake fluid, grease, oily dirt and contaminants from linings, pads and drums, cylinders and springs without disassembling the unit.

Health Hazard Data: Vapors from this product may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from point of product use. Adequate ventilation must be provided during use. Waste oil contaminated with this product poses a flammability hazard.

Contains petroleum distillates. Harmful or fatal if swallowed. If swallowed, do not induce vomiting. Call a physician immediately. Vapor harmful. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapors. Extremely flammable. Do not use near fire, flame, or while smoking. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures in excess of 120°F. KEEP OUT OF REACH OF CHILDREN.

Spill Or Leakage Procedures: Aerosol cans when vented to atmospheric pressure through normal use pose no disposal hazard. Do not flush to sewer. Absorb with suitable media.

Product Specifications	
Wt./20oz. Can	14 oz.
USDA Category	P1
Classification	Aerosol Solvent Based Cleaner/Degreaser
General Appearance	Clear Liquid
Color	Colorless
Odor	Aliphatic, Alcohol
pH:	N/A
Vapor Pressure at 70°F	80-100 psig
Spray Pattern	Blasting Stream
Flammability	Extremely Flammable per CPSC Flame Projection Test
NFPA Code 30B	Level 3

These values are representative of current production. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Brake Parts Cleaner – Chlorinated

Product Application:

This powerful solvent blend easily removes brake fluid, grease, oil and dirt from brake parts. Useful on brake linings, disc pads, drums, cylinders and springs. Nonflammable spray eliminates the danger of fire. Powerful blasting spray dries quickly and free of residue. No need to disassemble brake units. This product is ozone friendly.



Available:



Aerosol Cans

CHLORINATED

Non-Flammable

Health Hazard Data: Vapor harmful. Contains Perchloroethylene. Use with adequate ventilation to keep exposure levels below the 25 parts per million O.S.H.A. permissible exposure limit (PEL) during an eight hour period (time weighted average). Consult the product material safety data sheet for additional information regarding exposure concerns. Avoid inhalation of the spray mist or vapors. If overcome by fumes, remove victim to fresh air. Resuscitate if necessary. Get medical attention. Avoid contact with eyes and skin. In case of eye contact, flush immediately with water and continue for 15 minutes. If discomfort persists, see a physician. Contains under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120° F. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **KEEP OUT OF REACH OF CHILDREN.**

Spill Or Leakage Procedures: Aerosol cans when vented to atmospheric pressure through normal use pose no disposal hazard. Do not flush to sewer. Absorb with suitable media.

Product Specifications	
Wt./20oz. Can	14 oz.
USDA Category	P1
Classification	Aerosol Solvent Based Cleaner/Degreaser
General Appearance	Clear Liquid
Color	Colorless
Odor	Aliphatic, Alcohol
pH:	N/A
Vapor Pressure at 70°F	80-100 psig
Spray Pattern	Blasting Stream
Flammability	Extremely Flammable per CPSC Flame Projection Test
NFPA Code 30B	Level 3

These values are representative of current production. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Throttle Body/ Choke & Carburetor Cleaner



Available:



Product Application:

This powerful combination of concentrated solvents is specially formulated to remove dirt, gum and varnish deposits that tend to build up on the moving and sealing surfaces of engine carburetors, heat valves and automatic chokes, throttle bodies, PCV valves and linkages. Our product helps to free sticky valves, stuck heat risers and throttle linkages. No alcohol, lead or silicone. Will not harm oxygen sensors, catalytic converters or fuel injectors. Periodic use on cars, trucks, airplanes, boats, lawnmowers, etc., will keep engines clean, fuel efficient and trouble free. This cleaner can even be used on running engines. This product is formulated for high performance without the use of ozone depleting chlorinated solvents.

Health Hazard Data: Contains Toluene, Acetone, Aliphatic Petroleum Distillates, and Methanol. Extremely flammable. Do not use near heat, sparks, open flame or any other ignition source. Harmful or fatal if swallowed. If swallowed, do not induce vomiting. Call a physician immediately. Vapor harmful. Avoid prolonged breathing of vapors or contact with eyes or skin. Use with adequate ventilation. If overcome by fumes, remove victim to fresh air. Resuscitate if necessary. Get medical attention. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or temperatures exceeding 120°F. **WARNING:** This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm. **KEEP OUT OF REACH OF CHILDREN.**

Spill Or Leakage Procedures: Absorb with suitable medium. Incinerate or landfill according to local, state and federal regulations. Prevent from entering drains or sewers. Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

Product Specifications	
Wt./20oz. Can	15.5 oz.
Equivalent to	17.75 oz.
Classification	Aerosol Carburetor Cleaner
General Appearance	Clear
General Appearance	Clear
Color	Colorless
Odor	Aromatic Solvent
pH:	N/A
Vapor Pressure at 70°F	85-100
Spray Pattern	Blasting Stream
Flammability	Extremely Flammable per CPSC Flame Projection Test
NFPA Code 30B	Level 3

These values are representative of current production. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



[Back to Home](#)

Data Sheet: Heavy Duty Glass Cleaner



Available:



Product Application:

This versatile, extra strength product is the ONE product for even the toughest glass cleaning applications. Windows, glass, windshields, mirrors, displays, counters and more are easily cleaned of dirt, grease, oil, smudges, finger prints, lipstick, and other stubborn deposits. The nonammoniated formula even removes paint overspray, nicotine film and insects when used on vehicles and is even safe on window/windshield tinting film. The advanced chemistry provides professional quality cleaning without streaking, smearing, hazing or leaving behind any residue or film. The special formulation is pleasantly fragrant and has a stable foam consistency that breaks quickly and easily when wiped. There is no "pushing around excess foam" yet the optimum economic yield is achieved. Use this product in Commercial and Institutional Cleaning, Automotive/Fleet/Marine/Aircraft/RV Maintenance and Detailing, Glass and Glass Product Manufacturing, Window/Windshield Tinting and Installation/Repair, and other applications where "Professional" performance and quality are required. It is safe to use on most other hard surfaces and materials.

Product Specifications	
Wt./20oz. can	19 oz.
USDA Category	C1
Classification	Aerosol Glass Cleaner
General Appearance	White Foamy Spray
Color	White
Odor	Lemon
pH	10
Vapor Pressure at 70°F	60 psig
Spray Pattern	Wide Oval
Flammability	Not Flammable per CPSC Flame Projection Test
NFPA Code 30B	Level 1

These values are representative of current production. They may vary within modest ranges.

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Windshield Washer Fluid



Available:



6/1 Gal.s

Product Application:

Golden West Windshield Washer Fluid is specially formulated to clear windshields of dirt, bug stains, ice and frost. Contains detergency and antifreeze components for maximum performance and protection. Golden West Windshield Washer Fluid keeps windshields clean and improves visibility. It does not harm paint, rubber or plastic, and is ideal for use in winter or summer providing freeze protection to 0°F.



Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS



Golden West

Superior Since 1929

Golden West offers high-quality products that meet or exceed manufacturer's specifications at the most economical prices.

P R O D U C T S P E C I F I C A T I O N S

[Back to Home](#)

Data Sheet: Bar & Chain Oil

Product Application:



Golden West Bar & Chain oil is 100% virgin mineral oil incorporated with improved additives especially designed for to day's high speed chain saws in all weather conditions. This product acts as a solid film lubricant giving boundary lubrication under apparently dry lubricant conditions and a rust inhibitor to protect bar and chain during storage. It has extreme pressure additives with shock absorbing properties that reduce friction and increase chain life up to 65%.

Golden West Bar & Chain Oil demonstrates a special penetrating ability to give instant chain lubrication after start-up, plus a high-tac/no-sling additives to keep lubricant on the chain. This product is manufactured for industrial, commercial and residential chain saws. It meets the needs of the forest products industry under the most adverse operation conditions.

Product Specifications		
	Summer	Winter
Viscosity, SUS @100°F	630	300
Flash Point @ °F	425	410
Pour Point @ °F	-10	-20
Color	4	4

These values are representative of current production. They may vary within modest ranges.

Available:



6/1 Gal.s

Allied Sales Company

5005 E. 7th Street, Austin • TX 78702
Ph: (512) 385-2167 • Fax: (512) 385-0259

Golden West San Antonio

3010 Aniol Street • San Antonio, TX 78219
Ph: (800) 638-6628 • Fax: (210) 222-1034

United Oil & Grease Company Abilene

2702 Industrial Blvd • Abilene, TX 79605
Ph: (325) 695-0150 • Fax: (325) 695-7539

United Oil & Grease Company Lubbock

3100 Clovis Rd. • Lubbock, TX 79415
Ph: (806) 763-1818 • Fax: (806) 763-5447

Golden West Corpus Christi

710B Industrial Blvd. • Robstown, TX 78380
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West Laredo

5400 Santa Maria Ave. • Laredo, TX 78041
Ph: (800) 638-6628 • Fax: (210) 222-1034

Golden West McAllen

10721 North 10th St. • McAllen, TX 78504
Ph: (800) 638-6628 • Fax: (210) 222-1034



GOLDEN WEST: A COMPLETE LINE OF LUBRICANT PRODUCTS

