



Contractor's Organization Name:	Roberts Supply, Inc.
Contractor's FEIN:	59-1320461
Manufacturing / Brand Name:	Exmark Mfg. Co.
Contracted Group No(s):	4, 5, 8, 18
Revision Date:	11/1/2014

Notes:

- Commodity Type Key: B = Base Equipment; O = OEM Option, Accessory, & Implement
- The Authorized Price List is not complete unless used in conjunction with the full requirements, specifications, terms, and conditions of the Contract. Please see the State Term Contract website.

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
Please click on a blue product number to see full specifications and related parts and accessories								
Sub Group 6: Mower: Walk-behind Lawn, Commercial Type; Deck less than 44"								
4	6	B	ECX180CKA21000	Commercial 21 X-Series Self Prop Zone Start with Kawasaki FJ180V KAI 180cc	1,099.00	11/1/2014	20.00%	879.20
4	6	B	ECX160CHN21000	Commercial 21 X-Series Self Prop Zone Start with Honda GXV 160cc	1,299.00	11/1/2014	20.00%	1,039.20
4	6	B	ECX180CKA210BC	Commercial 21 X-Series Self Prop Blade Brake Control-Kawasaki FJ180V KAI 180cc	1,299.00	11/1/2014	20.00%	1,039.20
4	6	B	ECS180GKA21000	Commercial 21 S-Series Self Propelled Zone Start with Kawasaki FJ180V 180cc	999.00	11/1/2014	20.00%	799.20
4	6	B	ECS180CKA30000	Commercial 30 Self Propelled Blade Brake Control - Kawasaki FJ180V KAI 180cc	1,899.00	11/1/2014	20.00%	1,519.20
4	6	B	MGS481GKA322PO	Metro Gear FS481V Kawasaki with 32" Series 2 Deck - Pistol Grip	3,199.00	11/1/2014	20.00%	2,559.20
4	6	B	MGS481CKA36200	Metro Gear FS481V Kawasaki with 36" Series 2 Deck - ECS Handles	3,599.00	11/1/2014	20.00%	2,879.20
4	6	B	VHS481GKA36200	Viking Hydro FS481V Kawasaki with 36" Series 2 Deck	5,299.00	11/1/2014	20.00%	4,239.20
4	6	B	TTS481CKA36300	Turf Tracer S-Series FS481V Kawasaki with 36" Ultra Cut Series 3 Deck	6,099.00	11/1/2014	20.00%	4,879.20
Sub Group 7: Mower: Walk-behind Lawn, Commercial Type; Deck greater than or equal to 44"								
4	7	B	MGS481CKA48300	Metro Gear FS481V Kawasaki with 48" Series 3 Deck - ECS Handles	3,799.00	11/1/2014	20.00%	3,039.20
4	7	B	VHS481GKA48300	Viking Hydro FS481V Kawasaki with 48" Series 3 Deck	5,599.00	11/1/2014	20.00%	4,479.20
4	7	B	TTS481GKA48300	Turf Tracer S-Series FS481V Kawasaki with 48" UltraCut Series 3 Deck	6,599.00	11/1/2014	20.00%	5,279.20
4	7	B	TTS680PKC483EO	Turf Tracer S-Series PCV680 Kohler EFI Estart with 48" UltraCut 3 Deck-Propane	9,699.00	11/1/2014	20.00%	7,759.20
4	7	B	TTS541GKA52300	Turf Tracer S-Series FS541V Kawasaki with 52" UltraCut 3 Deck	6,999.00	11/1/2014	20.00%	5,599.20
4	7	B	TTS600GKA523EO	Turf Tracer S-Series FS600V Electric Start with 52" UltraCut 3 Deck	7,299.00	11/1/2014	20.00%	5,839.20
4	7	B	TTX650EKC52400	Turf Tracer X-Series ECV650 EFI Kohler with 52" UltraCut 4 Deck	8,599.00	11/1/2014	20.00%	6,879.20
4	7	B	TTX691GKA52400	Turf Tracer X-Series FX691V Kawasaki with 52" UltraCut 4 Deck	8,499.00	11/1/2014	20.00%	6,799.20
4	7	B	TTX680PKC52400	Turf Tracer X-Series PCV680 Kohler EFI with UltraCut 52" Series 4 Deck- Propane	10,799.00	11/1/2014	20.00%	8,639.20
4	7	B	TTX650EKC60400	Turf Tracer X-Series ECV650 EFI Kohler with 60" UltraCut 4 Deck	8,799.00	11/1/2014	20.00%	7,039.20
4	7	B	TTX691CKA60400	Turf Tracer X-Series FX691V Kawasaki with 60" UltraCut 4 Deck	8,699.00	11/1/2014	20.00%	6,959.20
4	7	B	TTX650EKC604N0	Turf Tracer X-Series ECV650 EFI Kohler with 60" UltraCut 4 Deck, Mlch Kit & Standon	9,299.00	11/1/2014	20.00%	7,439.20
4	7	B	TTX680PKC60400	Turf Tracer X-Series PCV680 Kohler EFI with UltraCut 60" Series 4 Deck- Propane	10,999.00	11/1/2014	20.00%	8,799.20

MODEL # ECX180CKA21000

Commercial 21 X-Series Self propelled Zone Start with Kawasaki FJ180V KAI (180cc)

MSRP 1,099.00
Discount 20.00%
Net Price 879.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	109-9328	9.5" Diameter Tire Kit	105.29	11/1/2014	20.00%	84.23
4	6	O	109-9331	Wheel Weight Kit	84.33	11/1/2014	20.00%	67.46

Decks

Bag Capacity 2.5 bushels (20 gallons).
Blade Tip Speed Approximately 18,500 fpm.
Blades 1 Blade at 20.5" Length
Cutting Heights 1.0" (2.5 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 5" deep, 1/4"-thick die-cast aluminum.
Deck Style Fixed Deck
Deck Style Description Fixed deck, Rear-discharge bagger and mulch plug standard.
Width / Cutting Deck 21"

Dimensions

Curb Weight 114 lbs.

Equipment

Drive Tires 9" x 2.5", semi-pneumatic.
Height 38 in. (96.5 cm)
Length 62 in. (157.5 cm)
Mower Size Compact
Safety Package Zone start
Width 22 in. (55.9 cm)

Power Components

Air Filter Dual element air cleaner
Carb Compliant Yes
Drive Belt-Drive
Drive Description Self-propelled; rear-wheel gear-driven.
Engine Brand Kawasaki®
Engine Displacement 179cc
Engine Model FJ180V KAI
Engine Series FJ KAI
Engine Speed 3,300 rpm
Engine Type Carbureted
Fuel Capacity 1 gallon (3.8-L).
Fuel Indicator None
Speed 0.0 mph to 4.2 mph (6.6 kmph) forward.
Fuel Type Gas Carbureted



MODEL # ECX160CHN21000

Commercial 21 X-Series Self Prop Zone Start with Honda GXV 160cc

MSRP 1,299.00
Discount 20.00%
Net Price 1,039.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	109-9328	9.5" Diameter Tire Kit	105.29	11/1/2014	20.00%	84.23
4	6	O	109-9331	Wheel Weight Kit	84.33	11/1/2014	20.00%	67.46

Decks

Bag Capacity 2.5 bushels (20 gallons).
Blade Tip Speed Approximately 18,500 fpm.
Blades 1 Blade at 20.5" Length
Cutting Heights 1.0" (2.5 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 5" deep, 1/4"-thick die-cast aluminum.
Deck Style Fixed Deck
Deck Style Description Fixed deck, Rear -discharge bagger and mulch plug standard.
Width / Cutting Deck 21"

Dimensions

Curb Weight 112 lbs.

Equipment

Drive Tires 9" x 2.5", semi-pneumatic.
Height 38 in. (96.5 cm)
Length 62 in. (157.5 cm)
Mower Size Compact
Safety Package Zone start
Width 22 in. (55.9 cm)

Power Components

Air Filter Dual element air cleaner
Carb Compliant Yes
Drive Belt-Drive
Drive Description Self-propelled; rear-wheel gear-driven.
Engine Brand Honda
Engine Displacement 163cc
Engine Model GXV 160
Engine Series GXV
Engine Speed 3,300 rpm
Engine Type Carbureted
Fuel Capacity 1 gallon (3.8-L).
Fuel Indicator None
Speed 0.0 mph to 4.2 mph (6.6 kmph) forward.
Fuel Type Gas Carbureted



MODEL # ECX180CKA210BC

Commercial 21 X-Series Self Prop Blade Brake Control-Kawasaki FJ180V KAI 180cc

MSRP	1,299.00
Discount	20.00%
Net Price	1,039.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	109-9328	9.5" Diameter Tire Kit	105.29	11/1/2014	20.00%	84.23
4	6	O	109-9331	Wheel Weight Kit	84.33	11/1/2014	20.00%	67.46

Decks

Bag Capacity	2.5 bushels (20 gallons).
Blade Tip Speed	Approximately 18,500 fpm.
Blades	1 Blade at 20.5" Length
Cutting Heights	1.0" (2.5 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction	5" deep, 1/4"-thick die-cast aluminum.
Deck Style	Fixed Deck
Deck Style Description	Fixed deck, Rear-discharge bagger and mulch plug standard.
Width / Cutting Deck	21"

Dimensions

Curb Weight	115 lbs.
-------------	----------

Equipment

Drive Tires	9" x 2.5", semi-pneumatic.
Height	38 in. (96.5 cm)
Length	62 in. (157.5 cm)
Mower Size	Compact
Safety Package	Blade Brake Clutch (BBC).
Width	22 in. (55.9 cm)

Power Components

Air Filter	Dual element air cleaner
Carb Compliant	Yes
Drive	Belt-Drive
Drive Description	Self-propelled; rear-wheel gear-driven.
Engine Brand	Kawasaki®
Engine Displacement	179cc
Engine Model	FJ180V KAI
Engine Series	FJ KAI
Engine Speed	3,300 rpm
Engine Type	Carbureted
Fuel Capacity	1 gallon (3.8-L).
Fuel Indicator	None
Speed	0.0 mph to 4.2 mph (6.6 kmph) forward.
Fuel Type	Gas Carbureted



MODEL # ECS180GKA21000

Commercial 21 S-Series Self Propelled Zone Start with Kawasaki FJ180V 180cc

MSRP 999.00
Discount 20.00%
Net Price 799.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	109-9333	1 Gallon Tank Kit	95.20	11/1/2014	20.00%	76.16
4	6	O	109-9329	Deck Wear Kit	36.12	11/1/2014	20.00%	28.90
4	6	O	116-0522	Engine Guard	7.82	11/1/2014	20.00%	6.26
4	6	O	109-9328	9.5" Diameter Tire Kit	105.29	11/1/2014	20.00%	84.23
4	6	O	116-0251	Mulch Plug	14.99	11/1/2014	20.00%	11.99
4	6	O	109-9331	Wheel Weight Kit	84.33	11/1/2014	20.00%	67.46

Decks

Bag Capacity 2.5 bushels (20 gallons).
Blade Tip Speed Approximately 18,500 fpm.
Blades 1 Blade at 20.5" Length
Cutting Heights 1.0" (2.5 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 5" deep, 1/4"-thick die-cast aluminum.
Deck Style Fixed Deck
Deck Style Description Fixed deck, Rear -discharge bagger standard with option to mulch.
Width / Cutting Deck 21"

Dimensions

Curb Weight 112 lbs.

Equipment

Drive Tires 9" x 2.5", semi-pneumatic.
Height 38 in. (96.5 cm)
Length 62 in. (157.5 cm)
Mower Size Compact
Safety Package Zone start
Width 22 in. (55.9 cm)

Power Components

Engine Model FJ180V
Air Filter Dual element air cleaner
Carb Compliant No
Drive Belt-Drive
Drive Description Self-propelled; rear-wheel gear-driven.
Engine Brand Kawasaki®
Engine Displacement 179cc
Engine Series FJ
Engine Speed 3,300 rpm
Engine Type Carbureted
Fuel Capacity 2 quart integral fuel tank
Fuel Indicator None
Speed 0.0 mph to 4.2 mph (6.6 kmph) forward.
Fuel Type Gas Carbureted



MODEL # ECS180CKA30000

Commercial 30 Self Propelled Blade Brake Control - Kawasaki FJ180V KAI 180cc

MSRP	1,899.00
Discount	20.00%
Net Price	1,519.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	116-8841	High-Performance Mulch Kit	119.00	11/1/2014	20.00%	95.20

Decks

Bag Capacity	2.5 bushels (20 gallons)
Blade Tip Speed	Approximately 18,500 fpm.
Blades	2 Blades at 15.4" Length
Cutting Heights	1.5"(3.8 cm) to 5.0" (12.7 cm) in 0.5" (1.3 cm) increments.
Deck Construction	4.6" Deep Stamped Steel with welded reinforcement
Deck Style	Fixed Deck
Deck Style Description	Fixed deck, Rear-discharge bagger with option to mulch or side discharge.
Width / Cutting Deck	30"

Dimensions

Curb Weight	170 lbs.
-------------	----------

Equipment

Drive Tires	10 x 3.0, semi-pneumatic
Mower Size	Full
Safety Package	Blade Brake Clutch (BBC).
Width	31.9 in. (81cm)
Height	38.3 in. (97.2 cm)
Length	66 in. (167.6 cm)

Power Components

Air Filter	Dual element air cleaner
Carb Compliant	Yes
Drive	Belt-Drive
Drive Description	Self-propelled, rear-wheel gear-driven.
Engine Brand	Kawasaki®
Engine Displacement	179cc
Engine Model	FJ180V KAI
Engine Series	FJ KAI
Engine Speed	3,500 rpm
Engine Type	Carbureted
Fuel Capacity	1 gallon (3.8-L)
Fuel Indicator	None
Speed	0.0 mph to 4.2 (6.6 kmph) mph forward.
Fuel Type	Gas Carbureted



MODEL # MGS481GKA322P0

Metro Gear FS481V Kawasaki with 32" Series 2 Deck - Pistol Grip

MSRP 3,199.00
Discount 20.00%
Net Price 2,559.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	6	O	103-2444	ECS Conversion Kit for Metro	644.00	11/1/2014	20.00%	515.20
4	6	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	6	O	MK322	Mulching Kit for 32" Unit	230.00	11/1/2014	20.00%	184.00
4	6	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20

Decks

Width / Cutting Deck	32"
Blade Spindles	No maintenance, sealed and non-greasable spindles; 5.40"-diameter cutter housing and 1.0" diameter spindle tube.
Blade Tip Speed	Approximately 18,500 fpm.
Blades	2 Blades at 16.25" Length
Cutting Heights	1.0" (2.5 cm) to 4.25" (10.8 cm) in 0.25" (0.64 cm) increments.
Deck Construction	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle.
Deck Style	Fixed Deck
Deck Style Description	Fixed UltraCut Series 2, side discharge standard, with molded discharge chute and option to bag or mulch.

Dimensions

Curb Weight	421 lbs.
-------------	----------

Equipment

Casters	.38" thick caster yoke arms
Cup Holder	No
Drive Tires	13 x 5.0-6, 4-ply Turf Saver
Drive Wheel Release	Gearbox in neutral allows unit movement w/ no power.
Electrical	No battery, recoil start.
Front Caster Tires	9 x 3.5-4, smooth-tread, semi-pneumatic.
Height	43.0 in. (109.2 cm)
Length	73.0 in. (185.4 cm)
Mower Size	Full
Parking Brake	Standard; brake bands.
Safety Package	Operator Presence Controls (OPC).
Steering Control	Gear drive with Pistol grip, forward/reverse assist.
Width	43.3 in. (110.0 cm)



Power Components

Fuel Type	Gas Carbureted
Air Filter	Standard Engine Manufacturer's air filter
Carb Compliant	No
Deck Lift	Manual cutter housing and front caster spacer position adjustment.
Drive	Belt-Drive
Drive Description	Direct drive from transmission to single-belt wheel drives
Engine Brand	Kawasaki®
Engine Displacement	603cc
Engine Model	FS481V
Engine Series	V-Twin
Engine Speed	3,600 rpm
Engine Type	Carbureted
Fuel Capacity	5-gallon (18.9-L) fuel tank.
PTO Engagement	Lever-actuated blade engagement with blade brake.
Speed	2.0 mph (3.2 kmph) to 6.2 mph (10 kmph) forward, reverse assist.

MODEL # MGS481CKA36200

Metro Gear FS481V Kawasaki with 36" Series 2 Deck - ECS Handles

MSRP **3,599.00**
 Discount **20.00%**
 Net Price **2,879.20**



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	6	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	6	O	MK362	Mulching Kit for 36" Unit	230.00	11/1/2014	20.00%	184.00
4	6	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20

Decks

Width / Cutting Deck 36"
Blade Spindles No maintenance, sealed and non-greasable spindles; 5.40"-diameter cutter housing and 1.0" diameter spindle tube.
Blade Tip Speed Approximately 18,500 fpm.
Blades 2 Blades at 18.00" Length
Cutting Heights 1.0" (2.5 cm) to 4.25" (10.8 cm) in 0.25" (0.64 cm) increments.
Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.
Deck Style Fixed Deck
Deck Style Description Fixed UltraCut Series 2, side discharge standard, with molded discharge chute and option to bag or mulch.

Dimensions

Curb Weight 456 lbs.

Equipment

Casters .38" thick caster yoke arms
Cup Holder No
Drive Tires 13 x 6.5-6, 4-ply Turf Master®
Drive Wheel Release Gearbox in neutral allows unit movement w/ no power.
Electrical No battery, recoil start.
Front Caster Tires 9 x 3.5-4, smooth-tread, semi-pneumatic.
Height 43.0 in. (109.2 cm)
Length 78.0 in. (198.1 cm)
Mower Size Full
Parking Brake Standard; brake bands.
Safety Package Operator Presence Controls (OPC).
Steering Control Gear drive with Enhanced Control System (ECS), forward/reverse assist.
Width 47.0 in. (119.4 cm)



Power Components

Fuel Type Gas Carbureted
Air Filter Standard Engine Manufacturer's air filter
Carb Compliant Yes
Deck Lift Manual cutter housing and front caster spacer position adjustment.
Drive Belt-Drive
Drive Description Direct drive from transmission to double-belt wheel drives
Engine Brand Kawasaki®
Engine Displacement 603cc
Engine Model FS481V
Engine Series V-Twin
Engine Speed 3,600 rpm
Engine Type Carbureted
Fuel Capacity 5-gallon (18.9-L) fuel tank.
PTO Engagement Lever-actuated blade engagement with blade brake.
Speed 2.0 mph (3.2 kmph) to 6.2 mph (10 kmph) forward, reverse assist.

MODEL # VHS481GKA36200

Viking Hydro FS481V Kawasaki with 36" Series 2 Deck

MSRP 5,299.00
Discount 20.00%
Net Price 4,239.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	6	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	6	O	116-7223	StandOn Sulky	499.00	11/1/2014	20.00%	399.20
4	6	O	103-2637	Sulky Counterweight Kit	169.00	11/1/2014	20.00%	135.20
4	6	O	MK362	Mulching Kit for 36" Unit	230.00	11/1/2014	20.00%	184.00

Decks

Width / Cutting Deck	36"
Blade Spindles	No maintenance, sealed and non-greasable spindles; 5.40"-diameter cutter housing and 1.0" diameter spindle tube.
Blade Tip Speed	Approximately 18,500 fpm.
Blades	2 Blades at 18.00" Length
Cutting Heights	1.0" (2.5 cm) to 4.25" (10.8 cm) in 0.25" (0.54 cm) increments.
Deck Construction	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.
Deck Style	Fixed Deck
Deck Style Description	Fixed Ultracut Series 2, side discharge standard, with molded discharge chute and option to bag or mulch.

Dimensions

Curb Weight 481 lbs.

Equipment

Casters	.38" thick caster yoke arms
Cup Holder	No
Drive Tires	16 x 6.5-8, 4-ply Turf Master®
Drive Wheel Release	Allows unit movement without engine running.
Electrical	No battery, recoil start.
Front Caster Tires	9 x 3.5-4, smooth-tread, semi-pneumatic.
Height	43.2 in. (109.7 cm)
Length	78.0 in. (198.1 cm)
Mower Size	Full
Parking Brake	Lever-actuated mechanical compression.
Safety Package	Operator Presence Controls (OPC).
Steering Control	Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width	47.0 in. (119.4 cm)



Power Components

Fuel Type	Gas Carbureted
Air Filter	Standard Engine Manufacturer's air filter
Carb Compliant	No
Deck Lift	Manual lift with hairpin from hole to hole for position adjustment.
Drive	Hydro-Drive
Drive Description	Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Displacement	603cc
Engine Model	FS481V
Engine Series	V-Twin
Engine Speed	3,600 rpm
Engine Type	Carbureted
Fuel Capacity	5-gallon (18.9-L) fuel tank.
Fuel Indicator	None
PTO Engagement	Mechanical blade engagement with blade brake.
Speed	Infinitely variable speed selection from 0– 6.2 mph (10 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.

MODEL # TTS481CKA36300

Turf Tracer S-Series FS481V Kawasaki with 36" Ultra Cut Series 3 Deck

MSRP 6,099.00
 Discount 20.00%
 Net Price 4,879.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	6	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	6	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	6	O	116-7223	StandOn Sulky	499.00	11/1/2014	20.00%	399.20
4	6	O	103-2637	Sulky Counterweight Kit	169.00	11/1/2014	20.00%	135.20
4	6	O	MK363Q	Mulching Kit for 36" Unit	230.00	11/1/2014	20.00%	184.00
4	6	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20

Decks

Blade Spindles No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing
Blade Tip Speed Approximately 18,500 fpm.
Blades 2 Blades at 18.00" Length
Cutting Heights 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.
Deck Style Floating Deck
Deck Style Description Full-floating UltraCut Series 3, side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck 36"

Dimensions

Curb Weight 573 lbs.

Equipment

Casters .38" thick caster yoke arms
Cup Holder No
Drive Tires 16 x 6.5-8, 4-ply Turf Master®
Drive Wheel Release Allows unit movement without engine running.
Electrical No battery, recoil start w/ 5 amp clutch coil
Front Caster Tires 9 x 3.5-4, smooth-tread, semi-pneumatic.
Height 42.0 in. (106.7 cm)
Length 77.7 in. (197.4 cm)
Mower Size Full
Parking Brake Lever-actuated mechanical compression.
Safety Package Operator Presence Controls (OPC).
Steering Control Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width 47.5 in. (120.7 cm)



Power Components

Air Filter Standard Engine Manufacturer's air filter
Carb Compliant Yes
Deck Lift Manual lift with hairpin from hole to hole for position adjustment.
Drive Hydro-Drive
Drive Description Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Displacement 603cc
Engine Model FS481V
Engine Series V-Twin
Engine Speed 3,600 rpm
Engine Type Carbureted
Fuel Capacity 5-gallon (18.9-L) fuel tank.
Fuel Indicator None
PTO Engagement Electromagnetic 105 ft-lbs clutch.
Speed Infinitely variable speed selection from 0– 6.2 mph (10 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.
Fuel Type Gas Carbureted

MODEL # MGS481CKA48300

Metro Gear FS481V Kawasaki with 48" Series 3 Deck - ECS Handles

MSRP 3,799.00
Discount 20.00%
Net Price 3,039.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	MK483Q	Mulching Kit for 48" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20

Decks

Width / Cutting Deck	48"
Blade Spindles	No maintenance, sealed and non-greasable spindles; 5.40"-diameter cutter housing and 1.0" diameter spindle tube.
Blade Tip Speed	Approximately 18,500 fpm.
Blades	3 Blades at 16.25" Length
Cutting Heights	1.0" (2.5 cm) to 4.25" (10.8 cm) in 0.25" (0.64 cm) increments.
Deck Construction	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.
Deck Style	Fixed Deck
Deck Style Description	Fixed UltraCut Series 3, side discharge standard, with molded discharge chute and option to bag or mulch.

Dimensions

Curb Weight	506 lbs.
-------------	----------

Equipment

Casters	.38" thick caster yoke arms
Cup Holder	No
Drive Tires	13 x 6.5-6, 4-ply Turf Master®
Drive Wheel Release	Gearbox in neutral allows unit movement w/o power.
Electrical	No battery, recoil start.
Front Caster Tires	9 x 3.5-4, smooth-tread, semi-pneumatic.
Height	43.0 in. (109.2 cm)
Length	78.0 in. (198.1 cm)
Mower Size	Full
Parking Brake	Standard; brake bands.
Safety Package	Operator Presence Controls (OPC).
Steering Control	Gear drive with Enhanced Control System (ECS), forward/reverse assist.
Width	57.9 in. (147.1 cm)



Power Components

Fuel Type	Gas Carbureted
Air Filter	Standard Engine Manufacturer's air filter
Carb Compliant	Yes
Deck Lift	Manual cutter housing and front caster spacer position adjustment.
Drive	Belt-Drive
Drive Description	Direct drive from transmission to double-belt wheel drives
Engine Brand	Kawasaki®
Engine Displacement	603cc
Engine Model	FS481V
Engine Series	V-Twin
Engine Speed	3,600 rpm
Engine Type	Carbureted
Fuel Capacity	5-gallon (18.9-L) fuel tank.
Fuel Indicator	None
PTO Engagement	Lever-actuated blade engagement with blade brake.
Speed	2.0 mph (3.2 kmph) to 6.2 mph (10 kmph) forward, reverse assist.

MODEL # VHS481GKA48300

Viking Hydro FS481V Kawasaki with 48" Series 3 Deck

MSRP 5,599.00
Discount 20.00%
Net Price 4,479.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sulky	499.00	11/1/2014	20.00%	399.20
4	7	O	103-2637	Sulky Counterweight Kit	169.00	11/1/2014	20.00%	135.20
4	7	O	MK483Q	Mulching Kit for 48" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20

Decks

Width / Cutting Deck	48"
Blade Spindles	No maintenance, sealed and non-greasable spindles; 5.40"-diameter cutter housing and 1.0" diameter spindle tube.
Blade Tip Speed	Approximately 18,500 fpm.
Blades	3 Blades at 16.25" Length
Cutting Heights	1.0" (2.5 cm) to 4.25" (10.8 cm) in 0.25" (0.54 cm) increments.
Deck Construction	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.
Deck Style	Fixed Deck
Deck Style Description	Fixed UltraCut Series 3, side discharge standard, with molded discharge chute and option to bag or mulch.

Dimensions

Curb Weight 531 lbs.

Equipment

Casters	.38" thick caster yoke arms
Cup Holder	No
Drive Tires	16 x 6.5-8, 4-ply Turf Master®
Drive Wheel Release	Allows unit movement without engine running.
Electrical	No battery, recoil start.
Front Caster Tires	9 x 3.5-4, smooth-tread, semi-pneumatic.
Height	43.2 in. (109.7 cm)
Length	78.0 in. (198.1 cm)
Mower Size	Full
Parking Brake	Lever-actuated mechanical compression.
Safety Package	Operator Presence Controls (OPC).
Steering Control	Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width	57.9 in. (147.1 cm)



Power Components

Fuel Type	Gas Carbureted
Air Filter	Standard Engine Manufacturer's air filter
Carb Compliant	No
Deck Lift	Manual lift with hairpin from hole to hole for position adjustment.
Drive	Hydro-Drive
Drive Description	Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Displacement	603cc
Engine Model	FS481V
Engine Series	V-Twin
Engine Speed	3,600 rpm
Engine Type	Carbureted
Fuel Capacity	5-gallon (18.9-L) fuel tank.
Fuel Indicator	None
PTO Engagement	Mechanical blade engagement with blade brake.
Speed	Infinitely variable speed selection from 0– 6.2 mph (10 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.

MODEL # TTS481GKA48300

Turf Tracer S-Series FS481V Kawasaki with 48" UltraCut Series 3 Deck

MSRP 6,599.00
Discount 20.00%
Net Price 5,279.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sully	499.00	11/1/2014	20.00%	399.20
4	7	O	103-2637	Sully Counterweight Kit	169.00	11/1/2014	20.00%	135.20
4	7	O	MK483Q	Mulching Kit for 48" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRHPW48	Turf Striping Kit 48" and 52" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.

Blade Tip Speed Approximately 18,500 fpm.

Blades 3 Blades at 16.25" Length

Cutting Heights 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.

Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.

Deck Style Floating Deck

Deck Style Description Full-floating UltraCut Series 3, side discharge standard, with molded discharge chute and option to bag or mulch.

Width / Cutting Deck 48"

Dimensions

Curb Weight 586 lbs.

Equipment

Casters .38" thick caster yoke arms

Cup Holder No

Drive Tires 16 x 7.5-8, 4-ply Turf Master®

Drive Wheel Release Allows unit movement without engine running.

Electrical No battery, recoil start w/ 5 amp clutch coil

Front Caster Tires 9 x 3.5-4, smooth-tread, semi-pneumatic.

Height 42.0 in. (106.7 cm)

Length 73.7 in. (187.2 cm)

Mower Size Full

Parking Brake Lever-actuated mechanical compression.

Safety Package Operator Presence Controls (OPC).

Steering Control Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.

Width 59.5in. (151.1 cm)



Power Components

Air Filter Standard Engine Manufacturer's air filter

Carb Compliant No

Deck Lift Manual lift with hairpin from hole to hole for position adjustment.

Drive Hydro-Drive

Drive Description Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.

Engine Brand Kawasaki®

Engine Displacement 603cc

Engine Model FS481V

Engine Series V-Twin

Engine Speed 3,600 rpm

Engine Type Carbureted

Fuel Capacity 5-gallon (18.9-L) fuel tank.

Fuel Indicator None

PTO Engagement Electromagnetic 105 ft-lbs clutch.

Speed Infinitely variable speed selection from 0– 6.2 mph (10 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.

MODEL # TTS680PKC483E0

Turf Tracer S-Series PCV680 Kohler EFI Estart with 48" UltraCut 3 Deck-Propane

MSRP 9,699.00
 Discount 20.00%
 Net Price 7,759.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sully	499.00	11/1/2014	20.00%	399.20
4	7	O	103-2637	Sully Counterweight Kit	169.00	11/1/2014	20.00%	135.20
4	7	O	MK483Q	Mulching Kit for 48" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRHPW48	Turf Striping Kit 48" and 52" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed Approximately 18,500 fpm.
Blades 3 Blades at 16.25" Length
Cutting Heights 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.
Deck Style Floating Deck
Deck Style Description Full-floating UltraCut Series 3, side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck 48"

Dimensions

Curb Weight 741 lbs.

Equipment

Casters .38" thick caster yoke arms
Cup Holder No
Drive Tires 16 x 7.5-8, 4-ply Turf Master®
Drive Wheel Release Allows unit movement without engine running.
Electrical 12-volt battery with 15-amp alternator.
Front Caster Tires 9 x 3.5-4, smooth-tread, semi-pneumatic.
Height 42.0 in. (106.7 cm)
Length 73.7 in. (187.2 cm)
Mower Size Full
Parking Brake Lever-actuated mechanical compression.
Safety Package Operator Presence Controls (OPC).
Steering Control Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width 59.5in. (151.1 cm)



Power Components

Air Filter Standard Engine Manufacturer's air filter
Carb Compliant Yes
Deck Lift Manual lift with hairpin from hole to hole for position adjustment.
Drive Hydro-Drive
Drive Description Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Displacement 674cc
Engine Model Kohler® PCV680
Engine Series Command™ EFI
Engine Speed 3,600 rpm
Engine Type EFI Propane
Fuel Capacity 7.9-Gallon Propane Tank
Fuel Indicator Yes - Float Gauge
PTO Engagement Electromagnetic 125 ft-lbs clutch.
Speed Infinitely variable speed selection from 0– 6.2 mph (10 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.
Fuel Type Propane EFI

MODEL # TTS541GKA52300

Turf Tracer S-Series FS541V Kawasaki with 52" UltraCut 3 Deck

MSRP 6,999.00
Discount 20.00%
Net Price 5,599.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sulky	499.00	11/1/2014	20.00%	399.20
4	7	O	103-2637	Sulky Counterweight Kit	169.00	11/1/2014	20.00%	135.20
4	7	O	MK523Q	Mulching Kit for 52" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRHPW48	Turf Striping Kit 48" and 52" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed Approximately 18,500 fpm.
Blades 3 Blades at 18.00" Length
Cutting Heights 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.
Deck Style Floating Deck
Deck Style Description Full-floating UltraCut Series 3, side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck 52"

Dimensions

Curb Weight 670 lbs.

Equipment

Casters .38" thick caster yoke arms
Cup Holder No
Drive Tires 16 x 7.5-8, 4-ply Turf Master®
Drive Wheel Release Allows unit movement without engine running.
Electrical No battery, recoil start w/ 5 amp clutch coil
Front Caster Tires 9 x 3.5-4, smooth-tread, semi-pneumatic.
Height 42.0 in. (106.7 cm)
Length 75.9 in. (192.8 cm)
Mower Size Full
Parking Brake Lever-actuated mechanical compression.
Safety Package Operator Presence Controls (OPC).
Steering Control Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width 64.3 in. (163.3 cm)



Power Components

Air Filter Standard Engine Manufacturer's air filter
Carb Compliant No
Deck Lift Manual lift with hairpin from hole to hole for position adjustment.
Drive Hydro-Drive
Drive Description Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Displacement 603cc
Engine Model Kawasaki® FS541V
Engine Series V-Twin
Engine Speed 3,600 rpm
Engine Type Carbureted
Fuel Capacity 5-gallon (18.9-L) fuel tank.
Fuel Indicator None
PTO Engagement Electromagnetic 105 ft-lbs clutch.
Speed Infinitely variable speed selection from 0– 6.2 mph (10 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.
Fuel Type Gas Carbureted

MODEL # TTS600GKA523E0

Turf Tracer S-Series FS600V Electric Start with 52" UltraCut 3 Deck

MSRP 7,299.00
 Discount 20.00%
 Net Price 5,839.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sulky	499.00	11/1/2014	20.00%	399.20
4	7	O	103-2637	Sulky Counterweight Kit	169.00	11/1/2014	20.00%	135.20
4	7	O	MK523Q	Mulching Kit for 52" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRHPW48	Turf Striping Kit 48" and 52" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed Approximately 18,500 fpm.
Blades 3 Blades at 18.00" Length
Cutting Heights 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations.
Deck Style Floating Deck
Deck Style Description Full-floating UltraCut Series 3, side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck 52"

Dimensions

Curb Weight 690 lbs.

Equipment

Casters .38" thick caster yoke arms
Cup Holder No
Drive Tires 16 x 7.5-8, 4-ply Turf Master®
Drive Wheel Release Allows unit movement without engine running.
Electrical 12-volt battery with 15-amp alternator.
Front Caster Tires 9 x 3.5-4, smooth-tread, semi-pneumatic.
Height 42.0 in. (106.7 cm)
Length 75.9 in. (192.8 cm)
Mower Size Full
Parking Brake Lever-actuated mechanical compression.
Safety Package Operator Presence Controls (OPC).
Steering Control Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width 64.3 in. (163.3 cm)



Power Components

Air Filter Standard Engine Manufacturer's air filter
Carb Compliant No
Deck Lift Manual lift with hairpin from hole to hole for position adjustment.
Drive Hydro-Drive
Drive Description Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Brand Kawasaki®
Engine Displacement 603cc
Engine Model FS600V
Engine Series V-Twin
Engine Speed 3,600 rpm
Engine Type Carbureted
Fuel Capacity 5-gallon (18.9-L) fuel tank.
Fuel Indicator None
PTO Engagement Electromagnetic 105 ft-lbs clutch.
Speed Infinitely variable speed selection from 0– 6.2 mph (10 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.
Fuel Type Gas Carbureted

MODEL # TTX650EKC52400

Turf Tracer X-Series ECV650 EFI Kohler with 52" UltraCut 4 Deck

MSRP **8,599.00**
 Discount **20.00%**
 Net Price **6,879.20**



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sulky	499.00	11/1/2014	20.00%	399.20
4	7	O	MK526	Mulching Kit for 52" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRFMD	Turf Striping Kit 52" and 60" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed Approximately 18,500 fpm.
Blades 3 Blades at 18" Length
Cutting Heights 1.5" (3.8 cm.) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 10-gauge welded spindle mounting locations.
Deck Style Floating Deck
Deck Style Description Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck 52"

Dimensions

Curb Weight 720 lbs.

Equipment

Casters .38" thick caster yoke arms
Cup Holder No
Drive Tires 18 x 8.5-8, 4-ply Turf Master®
Drive Wheel Release Allows unit movement without engine running.
Electrical 12-volt battery with 20-amp alternator.
Front Caster Tires 11 x 4.0-5, smooth tread, semi-pneumatic.
Height 45.0 in.
Length 84.8 in.
Mower Size Full
Parking Brake Lever-actuated mechanical compression.
Safety Package Operator Presence Controls (OPC).
Steering Control Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width 64.8 in.



Power Components

Air Filter Heavy-duty canister air filtration system
Deck Lift Manual lift with hairpin from hole to hole for position adjustment.
Drive Hydro-Drive
Drive Description Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Brand Kohler®
Engine Model ECV650
Engine Type Electronic Fuel Injected
Fuel Capacity 5-gallon (18.9-L) fuel tank.
PTO Engagement Electromagnetic 200 ft-lbs clutch.
Speed Infinitely variable speed selection from 0– 6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.
Fuel Type Gas EFI

MODEL # TTX691GKA52400

Turf Tracer X-Series FX691V Kawasaki with 52" UltraCut 4 Deck

MSRP **8,499.00**
 Discount **20.00%**
 Net Price **6,799.20**



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sully	499.00	11/1/2014	20.00%	399.20
4	7	O	MK526	Mulching Kit for 52" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRFMD	Turf Striping Kit 52" and 60" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles	No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed	Approximately 18,500 fpm.
Blades	3 Blades at 18" Length
Cutting Heights	1.5" (3.8 cm.) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 10-gauge welded spindle mounting locations.
Deck Style	Floating Deck
Deck Style Description	Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck	52"

Dimensions

Curb Weight	720 lbs.
--------------------	----------

Equipment

Casters	.38" thick caster yoke arms
Cup Holder	No
Drive Tires	18 x 8.5-8, 4-ply Turf Master®
Drive Wheel Release	Allows unit movement without engine running.
Electrical	12-volt battery with 20-amp alternator.
Front Caster Tires	11 x 4.0-5, smooth tread, semi-pneumatic.
Height	45.0 in. (114.3 cm)
Length	84.8 in. (215.4 cm)
Mower Size	Full
Parking Brake	Lever-actuated mechanical compression.
Safety Package	Operator Presence Controls (OPC).
Steering Control	Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width	64.0 in. (162.6 cm)



Power Components

Air Filter	Heavy-duty canister air filtration system
Carb Compliant	No
Deck Lift	Manual lift with hairpin from hole to hole for position adjustment.
Drive	Hydro-Drive
Drive Description	Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Brand	Kawasaki®
Engine Displacement	726cc
Engine Model	FX691V
Engine Series	V-Twin
Engine Speed	3,600 rpm
Engine Type	Carbureted
Fuel Capacity	5-gallon (18.9-L) fuel tank.
Fuel Indicator	None
PTO Engagement	Electromagnetic 200 ft-lbs clutch.
Speed	Infinitely variable speed selection from 0– 6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.
Fuel Type	Gas Carbureted

MODEL # TTX680PKC52400

Turf Tracer X-Series PCV680 Kohler EFI with UltraCut 52" Series 4 Deck- Propane

MSRP 10,799.00
 Discount 20.00%
 Net Price 8,639.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sully	499.00	11/1/2014	20.00%	399.20
4	7	O	MK526	Mulching Kit for 52" Unit	300.00	11/1/2014	20.00%	240.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRFMD	Turf Striping Kit 52" and 60" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed Approximately 18,500 fpm.
Blades 3 Blades at 18" Length
Cutting Heights 1.5" (3.8 cm.) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 10-gauge welded spindle mounting locations.
Deck Style Floating Deck
Deck Style Description Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck 52"

Dimensions

Curb Weight 740 lbs.

Equipment

Casters .38" thick caster yoke arms
Cup Holder No
Drive Tires 18 x 8.5-8, 4-ply Turf Master®
Drive Wheel Release Allows unit movement without engine running.
Electrical 12-volt battery with 20-amp alternator.
Front Caster Tires 11 x 4.0-5, smooth tread, semi-pneumatic.
Height 45.0 in. (114.3 cm)
Length 84.8 in. (215.4 cm)
Mower Size Full
Parking Brake Lever-actuated mechanical compression.
Safety Package Operator Presence Controls (OPC).
Steering Control Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width 64.0 in. (162.6 cm)



Power Components

Air Filter Heavy-duty canister air filtration system
Carb Compliant Yes
Deck Lift Manual lift with hairpin from hole to hole for position adjustment.
Drive Hydro-Drive
Drive Description Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Brand Kohler®
Engine Displacement 674cc
Engine Model PCV680
Engine Series Command™ EFI Propane
Engine Speed 3,600 rpm
Engine Type EFI Propane
Fuel Capacity 7.9 -Gallon Propane Tank
Fuel Indicator None
PTO Engagement Electromagnetic 200 ft-lbs clutch.
Speed Infinitely variable speed selection from 0– 6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.
Fuel Type Propane EFI

MODEL # TTX650EKC60400

Turf Tracer X-Series ECV650 EFI Kohler with 60" UltraCut 4 Deck

MSRP **8,799.00**
 Discount **20.00%**
 Net Price **7,039.20**



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sully	499.00	11/1/2014	20.00%	399.20
4	7	O	MK606	Mulching Kit for 60" Unit	330.00	11/1/2014	20.00%	264.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRFMD	Turf Striping Kit 52" and 60" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed Approximately 18,500 fpm.
Blades 3 Blades at 20.5" Length
Cutting Heights 1.5" (3.8 cm.) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 10-gauge welded spindle mounting locations.
Deck Style Floating Deck
Deck Style Description Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck 60"

Dimensions

Curb Weight 760 lbs.

Equipment

Casters .38" thick caster yoke arms
Cup Holder No
Drive Tires 18 x 8.5-8, 4-ply Turf Master®
Drive Wheel Release Allows unit movement without engine running.
Electrical 12-volt battery with 20-amp alternator.
Front Caster Tires 11 x 4.0-5, smooth tread, semi-pneumatic.
Height 45.0 in.
Length 84.8 in.
Mower Size Full
Parking Brake Lever-actuated mechanical compression.
Safety Package Operator Presence Controls (OPC).
Steering Control Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width 73.0 in.



Power Components

Air Filter Heavy-duty canister air filtration system
Deck Lift Manual lift with hairpin from hole to hole for position adjustment.
Drive Hydro-Drive
Drive Description Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Brand Kohler®
Engine Model ECV650
Engine Type Electronic Fuel Injected
Fuel Capacity 5-gallon (18.9-L) fuel tank.
PTO Engagement Electromagnetic 200 ft-lbs clutch.
Speed Infinitely variable speed selection from 0– 6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.
Fuel Type Gas EFI

MODEL # TTX691CKA60400

Turf Tracer X-Series FX691V Kawasaki with 60" UltraCut 4 Deck

MSRP 8,699.00
Discount 20.00%
Net Price 6,959.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sully	499.00	11/1/2014	20.00%	399.20
4	7	O	MK606	Mulching Kit for 60" Unit	330.00	11/1/2014	20.00%	264.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRFMD	Turf Striping Kit 52" and 60" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles	No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed	Approximately 18,500 fpm.
Blades	3 Blades at 20.5" Length
Cutting Heights	1.5" (3.8 cm.) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 10-gauge welded spindle mounting locations.
Deck Style	Floating Deck
Deck Style Description	Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck	60"

Dimensions

Curb Weight	760 lbs.
-------------	----------

Equipment

Casters	.38" thick caster yoke arms
Cup Holder	No
Drive Tires	18 x 8.5-8, 4-ply Turf Master®
Drive Wheel Release	Allows unit movement without engine running.
Electrical	12-volt battery with 20-amp alternator.
Front Caster Tires	11 x 4.0-5, smooth tread, semi-pneumatic.
Height	45.0 in. (114.3 cm)
Length	84.8 in. (215.4 cm)
Mower Size	Full
Parking Brake	Lever-actuated mechanical compression.
Safety Package	Operator Presence Controls (OPC).
Steering Control	Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width	72.0 in. (182.96 cm)



Power Components

Air Filter	Heavy-duty canister air filtration system
Carb Compliant	No
Deck Lift	Manual lift with hairpin from hole to hole for position adjustment.
Drive	Hydro-Drive
Drive Description	Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Brand	Kawasaki®
Engine Displacement	726cc
Engine Model	FX691V
Engine Series	V-Twin
Engine Speed	3,600 rpm
Engine Type	Carbureted
Fuel Capacity	5-gallon (18.9-L) fuel tank.
Fuel Indicator	None
PTO Engagement	Electromagnetic 200 ft-lbs clutch.
Speed	Infinitely variable speed selection from 0– 6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.
Fuel Type	Gas Carbureted

MODEL # TTX650EKC604N0

Turf Tracer X-Series ECV650 EFI Kohler with 60" UltraCut 4 Deck, Mulch Kit & Standon

MSRP 9,299.00
Discount 20.00%
Net Price 7,439.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRFMD	Turf Striping Kit 52" and 60" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles	No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed	Approximately 18,500 fpm.
Blades	3 Blades at 20.5" Length
Cutting Heights	1.5" (3.8 cm.) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 10-gauge welded spindle mounting locations.
Deck Style	Floating Deck
Deck Style Description	Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck	60"

Dimensions

Curb Weight 840 lbs.

Equipment

Casters	.38" thick caster yoke arms
Cup Holder	No
Drive Tires	18 x 8.5-8, 4-ply Turf Master®
Drive Wheel Release	Allows unit movement without engine running.
Electrical	12-volt battery with 20-amp alternator.
Front Caster Tires	11 x 4.0-5, smooth tread, semi-pneumatic.
Height	45.0 in. (114.3 cm)
Length	104.8 in. (266.2 cm)
Mower Size	Full
Parking Brake	Lever-actuated mechanical compression.
Safety Package	Operator Presence Controls (OPC).
Steering Control	Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width	72.0 in. (182.96 cm)



Power Components

Air Filter	Heavy-duty canister air filtration system
Carb Compliant	No
Deck Lift	Manual lift with hairpin from hole to hole for position adjustment.
Drive	Hydro-Drive
Drive Description	Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Brand	Kohler®
Engine Displacement	694cc
Engine Model	ECV650
Engine Series	Command™ EFI
Engine Speed	3,600 rpm
Engine Type	Electronic Fuel Injected
Fuel Capacity	5-gallon (18.9-L) fuel tank.
Fuel Indicator	None
PTO Engagement	Electromagnetic 200 ft-lbs clutch.
Speed	Infinitely variable speed selection from 0– 6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.
Fuel Type	Gas EFI

MODEL # TTX680PKC60400

Turf Tracer X-Series PCV680 Kohler EFI with UltraCut 60" Series 4 Deck- Propane

MSRP 10,999.00
Discount 20.00%
Net Price 8,799.20



Parts & Accessories Available

[Return to Top Page](#)

Group No.	Sub Group No.	Commodity Type	Product Number	Product Description	MSRP	MSRP List Date	MSRP Disc %	Contracted Net Price
4	7	O	GC3602	3-Bushel Bagger	389.00	11/1/2014	20.00%	311.20
4	7	O	116-1379	Equipment Cover - Large	199.00	11/1/2014	20.00%	159.20
4	7	O	116-7223	StandOn Sulky	499.00	11/1/2014	20.00%	399.20
4	7	O	MK606	Mulching Kit for 60" Unit	330.00	11/1/2014	20.00%	264.00
4	7	O	116-8430	Operator Controlled Discharge	349.00	11/1/2014	20.00%	279.20
4	7	O	STRFMD	Turf Striping Kit 52" and 60" Unit	449.00	11/1/2014	20.00%	359.20

Decks

Blade Spindles	No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft.
Blade Tip Speed	Approximately 18,500 fpm.
Blades	3 Blades at 20.5" Length
Cutting Heights	1.5" (3.8 cm.) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.
Deck Construction	10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 10-gauge welded spindle mounting locations.
Deck Style	Floating Deck
Deck Style Description	Full-floating UltraCut Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.
Width / Cutting Deck	60"

Dimensions

Curb Weight	780 lbs.
-------------	----------

Equipment

Casters	.38" thick caster yoke arms
Cup Holder	No
Drive Tires	18 x 8.5-8, 4-ply Turf Master®
Drive Wheel Release	Allows unit movement without engine running.
Electrical	12-volt battery with 20-amp alternator.
Front Caster Tires	11 x 4.0-5, smooth tread, semi-pneumatic.
Height	45.0 in. (114.3 cm)
Length	84.8 in. (215.4 cm)
Mower Size	Full
Parking Brake	Lever-actuated mechanical compression.
Safety Package	Operator Presence Controls (OPC).
Steering Control	Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.
Width	72.0 in. (182.96 cm)



Power Components

Air Filter	Heavy-duty canister air filtration system
Carb Compliant	Yes
Deck Lift	Manual lift with hairpin from hole to hole for position adjustment.
Drive	Hydro-Drive
Drive Description	Twin Hydro-Gear variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" tapered shafts.
Engine Brand	Kohler®
Engine Displacement	674cc
Engine Model	PCV680
Engine Series	Command™ EFI Propane
Engine Speed	3,600 rpm
Engine Type	EFI Propane
Fuel Capacity	7.9 -Gallon Propane Tank
Fuel Indicator	None
PTO Engagement	Electromagnetic 200 ft-lbs clutch.
Speed	Infinitely variable speed selection from 0– 6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.
Fuel Type	Propane EFI