



Quality Products Since 1932 • DRYLOK® • ZAR® • UGL®

Product Training

DRYLOK®

WATERPROOFER



Certified to
NSF/ANSI 61



DRYLOK® POWDERED MASONRY WATERPROOFER (MIX WITH WATER)

- Prevents water penetration interior/exterior; above/below grade
- Superior efflorescence resistance
- Hold back 10 psi of hydrostatic pressure, < than a wall of water 22 feet high
- ARCOM's Master Spec 071613; NSF Approved for drinking water
- Apply to wet surfaces



ORIGINAL DRYLOK® LATEX BASE MASONRY WATERPROOFER

- Rated #1 by a Leading Independent Consumer Ratings Publication
- Passes ASTM D-7088 Resistance to Hydrostatic Pressure / ASTM D-6904 Resistance to 98 mph Wind Driven Rain
- **Fully Transferable 10-Year Warranty**



DRYLOK® EXTREME MASONRY WATERPROOFER

- Smooth, bright white finish. Latex Based formula with Flexible Encapsulated Polymers and a non-hazardous biocide to resist mildew growth on the paint film.
- Passes ASTM D-7088 Resistance to Hydrostatic Pressure and ASTM D-6904 Resistance to 98 mph Wind Driven Rain.
- **Fully Transferable 15-year warranty**



DRYLOK® FLOOR & WALL MASONRY WATERPROOFER

- Use on basement floors, retaining and foundation walls (interior/exterior masonry) and decorative surfaces.
- Stops hydrostatic pressure and resists 98 mph wind driven rain.

PRODUCT COMPARISON CHART



DRYLOK[®]
MASONRY WATERPROOFER



DRYLOK[®] penetrates and bonds to porous masonry surfaces, creating a waterproof barrier on interior, exterior, above and below grade walls.

	NEW PACKAGING	NEW PACKAGING	NEW PACKAGING	NEW PACKAGING
PRODUCTS				
WARRANTY	None			
REASONS TO BUY	<ul style="list-style-type: none"> • Powder mixes with Water to Mimic the Original Surface Texture • NSF[®] Certified for use with Potable Water, Concrete Holding Tanks, Concrete Cisterns, Pools, etc. • Soap and Water Cleanup 	<ul style="list-style-type: none"> • SANDY Texture • Great for Fish Ponds, Fountains, Utility Areas • Low-Odor Formula • Soap and Water Cleanup 	<ul style="list-style-type: none"> • SMOOTH Texture • Withstands Cat 4 Hurricane Winds • Great for Pools • Green Wise[®] Certified • Low-Odor Formula • Mildew-Resistant on Dry Paint Film • Soap and Water Cleanup 	<ul style="list-style-type: none"> • HIGH GLOSS • Approved for Use on Interior Floors, Exterior Decorative Stone, Walls, Stairway • Soap and Water Cleanup
TINTS*	None	9	9	None
GUARANTEED TO STOP WATER!				
AVAILABLE SIZES	35lb. Container	Quart, Gallon, 2 Gallon, 5 Gallon	Quart, Gallon, 5 Gallon	Gallon, 5 Gallon
COVERAGE (per gallon)	140-210 Sq. Ft.	75-100 Sq. Ft.	75-100 Sq. Ft.	90-100 Sq. Ft.
CLEANUP	Soap and Water	Soap and Water	Soap and Water	Soap and Water
READY-MIXED COLORS	None			

* See UGL's DRYLOK[®] Masonry Waterproofer Brochure for Tint Color Selections

Find Home Improvement Tips at www.ugl.com



PATCHING



DRYLOK® FAST PLUG®

- Fast setting hydraulic cement – sets in 3-5 minutes
- Stop the flow of water – even under pressure – through holes and cracks in masonry
- Ideal for sealing floor and wall joints and settlement cracks in masonry walls



DRYLOK® LIQUID ETCH® / DRYLOK® ETCH

- Use to clean and etch concrete, stone, tile, and brick
- Remove efflorescence (salt-like deposits) and excess mortar
- Etch smooth concrete and galvanized surfaces prior to painting
- Safer than Muriatic Acid



DRYLOK® MASONRY CRACK FILLER

- Seal and waterproof cracks in concrete walks, walls, steps and floors
- Replaces cracked mortar joints-dries to color of concrete.
- Will not bleed, can paint over immediately



DRYLOK® POURABLE MASONRY CRACK FILLER

- Seal and waterproof cracks in concrete walks, walls, steps and floors
- Replaces cracked mortar joints – dries to color of concrete
- Will not bleed, can paint over immediately
- Apply without the use of a caulk gun
- Adjust tip opening for any size job

PENETRATING SEALERS



PENETRATING SEALERS



DRYLOK® SILOXANE 7

- Has no sheen and is virtually invisible on stucco, brick, and concrete.
- Durable, one-coat water repellent specially formulated for exterior above-grade vertical surfaces
- Resists 98 mph wind driven rain and complies with all current VOC requirements
- Will not damage asphalt shingles



DRYLOK® NATURAL LOOK CURING MEMBRANE & PENETRATING SEALER

- Provides VOC compliant protection with a natural appearance
- Penetrates deep to seal and protect masonry against acids, household cleaners, gasoline, oil, and salt
- Ideal masonry primer that hardens concrete with one coat protection
- Minimizes concrete dusting, cracking and pock marking



DRYLOK® PROTECTOR CLEAR LOW SHEEN PENETRATING SEALER

- Seal bare masonry surface against dusting, staining, and surface cracking
- Provide clear weatherproof protection against deterioration caused by de-icing salt, gasoline, oil, weathering and efflorescence (white, powdery, salt-like deposits visible on masonry)
- SaltLok Technology provides superior resistance to unsightly efflorescence staining often visible on brick, block and poured concrete surfaces



DRYLOK® WETLOOK CLEAR HIGH GLOSS PENETRATING SEALER

- A clear, non-yellowing, water-based acrylic coating for interior and exterior masonry surfaces
- Unique SaltLok Technology provides superior hardness, durability, and protects against efflorescence
- Excellent chemical resistance to de-icing salts, gasoline, oil and weathering- 25% solids



DRYLOK Product Line	Where Used	Attributes	Application
Latex Base DRYLOK® Masonry Waterproofer	Interior/Exterior – Above/Below grade < 100 g/L, vertical surfaces	Eliminated water seepage, reduces radon gas penetration, sandy texture, off white, resists 98 mph rain	Brush, roll
DRYLOK® Extreme Masonry Waterproofer	Interior/Exterior – Above/Below grade < 100 g/L, vertical surfaces	Eliminated water seepage, mildew resistant on dry paint film, reduces radon gas penetration, smooth finish, bright white, resists 98 mph rain	Brush, roll, spray
DRYLOK® Floor & Wall Masonry Waterproofer	Interior/Exterior – Above grade < 100 g/L, vertical or horizontal surfaces	Clear for decorative substrates, eliminated water seepage, moisture vapor barrier for floors, gloss finish, resists 98 mph rain	Brush, roll, spray
Oil Base DRYLOK® Masonry Waterproofer	Interior/Exterior – Above/Below grade <400 g/L, vertical surfaces	Can be applied to a slightly damp surface, Eliminates water seepage, reduces radon gas penetration, resists 98 mph rain	Brush, roll
DRYLOK® Powdered Masonry Waterproofer	Interior/Exterior – Above/Below Grade, horizontal/vertical surfaces	0 VOCs, very effective against efflorescence, NSF approved for drinking water	Brush, roll
DRYLOK® Siloxane 7	Exterior stucco, brick and concrete <200 g/L, horizontal/vertical surfaces	Clear, allows water vapor to escape, resists 98 mph rain	Brush, roll, spray
DRYLOK® Natural Look Sealer	Interior/Exterior, horizontal / vertical surfaces < 250 g/L	Clear, UV resistant, ideal primer	Brush, roll, spray, squeegee
DRYLOK® WetLook High Gloss Sealer	Interior/Exterior, horizontal / vertical surfaces	Clear, high gloss, UV resistant, Contains SaltLok®, resists de-icing salts	Brush, pad applicator, garden sprayer, squeegee
DRYLOK® Concrete Protector with SaltLok® Technology	Interior/Exterior, horizontal/vertical surfaces, latex, <100 g/L	Clear, semi-gloss, UV resistant, Contains SaltLok®, prevents excessive dusting, surface cracking and pock marking	Brush, pad applicator, garden sprayer, squeegee

DRYLOK® Latex Concrete Floor Paint



- Formulated to protect and decorate masonry floors indoors/outdoors
- Outperforms ordinary floor paint. Endures scuffing, moisture, washings on basement and garage floors, patios and stairs
- No Primer Needed
- Can be used on new or previously painted surfaces
- Resists hot tire pick-up
- Complies with all current VOC requirements

Application

- ▶ Stir thoroughly. The first coat should be brushed well into the surface. Brush or roller may apply the second coat. For best result, apply two coats. Paint only when air and surface temperature are 50°F or higher.
- ▶ For garage floors, allow to dry 5 days before subjecting to automobile use



5 Ready-Mixed Colors – Dark & Light Tint Bases for custom colors



DRYLOK® E1 Latex 1-Part Epoxy Concrete Floor Paint



- A revolutionary low VOC 50 g/L VOC, 1-part epoxy floor paint
- Utilizes advanced epoxy technology for excellent durability
- Resistant to hot tire marks and pickup, chemicals, oil, grease and gasoline stains
- Formulated using Advanced Epoxy Technology for a durable finish
- Easy to maintain, UV-resistant semi-gloss finish
- Available in ready mix colors Gray, Platinum, and Tint Base

Ready-Mixed Colors



Tints

