



contents



	Corporation Histroy	03		Testing Center	21
	Organizational Structure	04	-0	Warehouse	- 22
-	Sales Network	05		Logestic Center	23
	Production Base	- 06	-	OEM Product	- 24
	Production Categories	07	-	Testing Equipments	25-26
	Sales Ratio	- 08	-	Technology	- 27
	Growth	09	-0	Research and Develop	28
	Company Status	10		Dry Gas Seal	29
	Certification	11-12		FFKM and Spring Energized Seal	30
	Test Report	13	-0	Bearing Isolator	- 31
	Sample Room	14		Coating Technology	32
	Office	15		Supplier	33
	Production Line	16		Customer	34-35
	Production Line	17-18		Footprint	- 36
	Workshop	19-20		Exhibition	37-38

High Efficient, Clean and Green

History



- 1999 Pass IS09001:2000 Certificate
- 2002 Establish Shanghai Trisun Parts Manufacture Co., Ltd.
- 2003 Set up Guangzhou Sales Branch
- 2004 Pass TS14001:2004 Environment System Certificate
- 2005 Establish Shanghai Songjiang Plant and equip with the global famous Company
- 2006 Develop and manufacture the metal bellows and cartridge seals
- 2008 Pass TS16949:2009 Certificate










•	2009	Develop the h	igh technol	ogy product —	dry gas seals
---	------	---------------	-------------	---------------	---------------

- 2010 Manufacture high-quality PPS impeller, and relocate Sales Headquarters to Lujiazui Financial Center
- 2011 The production ability of Wenzhou plant exceeded 1 million sets per month and Shanghai plant moved to the new building
- 2013 Pass FDA and WRAS Certificates, Establish North American Sales
 & Logistics Center
- Pass API Certificate for cartridge seals, and set up Shanghai R&D and Logistics Center
- 2016 Wenzhou new production building is completed
- 2017 Build E-commerce sales platform
- 2019 Develop coating seal ring and shaft

Structure




Network





North America Sales branch





Shanghai Sales Headquarters







Wenzhou Sales branch

Production Base









Shanghai Trisun Production Base: 10000 m² and 36 employees


Wenzhou Trisun Production Base: 30000 m² and 160 employee




Products





















Sales Ratio




- Single-Spring Mechanical seals(35%)
- Metal Bellow seal 、Cartridge Seal & vessel tank、Dry Gas Seal (20%)
- Auto Cooling Pump Seal (17%)
- A/C Compressor Seal & Valve (8%)
- Impeller and Nozzel(5%)
- Test machine, Lapping machine and other parts (15%)



Growth





however we confidence will recovery in 2022.

Company Status



TRISUNJA

温州市天成密封件制造有影

Trisun Seal Manufacture & Lie

Turnove

• Annual Turnover: \$23,600,000

Company Scale

Total 236 employees

20 R&D personnel

15 Quality Checkers

4 Process Engineers

15 Salesmen

5 Purchasers

162 Workers

5 Financial Staff

10 administration Staff

Our Capacity

Mechanical seals: 10,000,000 pcs/Year

Impellers: 2,000,000 Pcs/Year

Control Valves: 300,000 Pcs/Year

Metal Bellows : 24,000 pcs/Year

Cartridge Seals: 6,000 pcs/Year

Thermosiphon Vessels: 5,000 pcs/Year

Certification









ISO9001

IS16949

ISO14001

Certification









FDA

API

WRAS

Test Report



Products TÜVRheinland® Test Report No.: 0244219513a 001 Shanghai Trisun Parts Manufacture Co.,Ltd Room 3005-06, Sino-Life Tower, No.707 Zhangyang Rd Pudong Dist.Shanghai. China. Buyer's name: Manufacturer's name: Resin Impregnated Carbon Graphite Identification / Model No(s): 2020-02-28 to 2020-03-06 **Testing Period:** Test specification: Test conclusion: Selected test(s) by client: Specific Release of Metals Other Information Sample Photo Selected test condition by client. For and on behalf of TÜV Rheinland (Shanghai) Co., Ltd. 0 Sven Posselt 2020-03-09 Sven Posselt / Technical Head Name / Position Test result is drawn according to the kind and extent of tests performed. This test report relates to the a.m. test sample. Without permission of the test center this test report is not pe extracts. This test report does not entitle to carry any safety mark on this or similar products. TÜV Rheinland (Shanghai) Co., Ltd. Shanghai TÜV Rheinland Building, No. 177, Lane 777, West Guangzho Shanghai 200072, P.R. China Tel.: +86 21 6108 1188 Fax: +86 21 6108 1099 Mail: info@shg.chn.tuv.com Web: www.tuv.com

报告编号: TS19040490	^{日期: 2019-44-16} 第1 页 共 11 页 检测报告			
委托方	過州市天成密封件制造有限公司			
地址	浙江省温州市陇海区三溪工业区康宏西路 29 号			
样品名称	石墨材料			
型号	15" And the state of the state of			
材质/颜色	Carbon/black			
其他信息	Part No.: Sealing ring series; Item/LotNo.: MK			
样品接收日期	2019-04-10			
測试周期	2019-04-10~ 2019-04-16			
測试要求	根据欧盟法规(EC) No 1907/2006 (即 REACH 法规) 所列明的 197 项高关注度物质(SVHC) 清单 (质量百分浓度不得超过 0.1%)、检测样品中 SVHC 含量。			
测试方法	CIRS-TC-SVHC001, CIRS-TC-SVHC002, CIRS-TC-SVHC003, CIRS-TC-SVHC004, CIRS-TC-SVHC005, CIRS-TC-SVHC006			
测试结果	委托方产品中检出的当前 REACH 法规第 57 条规定的 197 项高关注物质质量百分浓度少于 0.1%(重量比)。			
編制: <mark>採夏分</mark>	事核: 左言峰			



TUV EU1935

REACH Certification

ROSH Certification

Sample Room







Office







Production Line







Production Line












Production Line







Workshop







Workshop







Testing Center









Warehouse







Logestic Center







OEM Product









Automatic Retainer Healing



Automatic Leakage Testing

Auto cooling pump seal, dish-washing seal, sanitary pump seal

Trisun assemble 7 million mechancial seals annually, We always aims to OEM market . In order to match the strict requirments of Food Manufacturing and Sanitary Industry, Our mateiral also have FDA, NSF, WARS and TUV1935 certification. Trisun OEM standard seal will have 100% air static testing before shipment.

Testing Equipments















Testing Equipments















Technology




Our R & D team members :
 PhD supervisor:1 person , PhD: 3 persons, Senior engineer:2 persons,
 5 years working experience engineer(fluid industry, polymer materials): 6 persons


Research & Development


- Impeller hydraulic model design of centrifugal pump, mixed-flow pump, axial flow pump and other special pump.
- Performance optimization of all types of turbine and pump
- Flow field numerical simulation and performance prediction of fluid machinery

Project Performance

- (National "South-to-North water diversion" project)
- Chemical axial pump's numerical analyze and optimization
- (National Natural Science Foundation)
- Chemical axial pump's numerical simulation and performance and prediction (One domestic famous pump factorys project)
- The Research & develop of the centrifugal pump with inlet guide vane.
- Centrifugal pump's cavitation performance prediction.








Research and Develop



3D Printing applied in the tooling design and new products development

 We use 3D printing technology in industrial product design and development process (such as pump housing, thermostat, pulley, impeller, etc.). Designers can use this method to quickly convert the computer graphics to physical model in order to improve the accuracy of design and shorten the product development cycle.



Nozzel Prototype by 3D printing

Final Products by Tooling

Dry Gas Seal



State-of-the-art Technology

• Through computer numerical simulation, we obtain accurate parameters of mechanical and thermodynamic properties to design outstanding, stable and reliable dry gas seals.

Advanced Processing Techniques

• The high-performance laser equipment can process all kinds of dynamic pressure grooves on the surfaces of the different material rings


Abundant Product Models

• The product range covers pump seals, compressor seals and agitator seals. Besides our standard product models, we can also provide special design according to customers requirements.

The First-class R&D Team

• R&D team is composed of Masters and PHD. Meanwhile, we have close cooperation with famous universities and institutions.





FFKM and Spring Energized Seal







Dupont-Kalrez and FFKM

Spring energized seal

Bearing Isolator

TRISUN'3

Bearing Isolator, also named Bearing Protector, It consists of a rotor and a stator, which are unitized by an O-ring. The two components interact to keep the pollutants

out of the bearing housing and prevent the leakage of the lubricants.





Features of Bearing Isolator

- Non-contact , No wear to the shaft
- Zero energy consumption
- Block moisture enter the bearing housing when equipment
- Shaft speed up to 60m/s
- More than 40,000 hours lifetime

- Split design available
- emperature range: -35 °C~204°C

Coating Technology



Trisun developed the coating technology for pump shaft and mechaincal seal rings . There are Aluminimu base , Chromium Trioxide (Cr_2O_3) base and Diamond base coatings The coating thickness from 0.2mm to 1 mm .







Coating technology will efficiently improve pump life. These insulation coating-material will down the pump temperature when pump under the dry run or high-speed operation .Pump will also enhance the wear and corrosion resitant by coating technology.

Supplier



Carbon



Germany-SGL



UK-MORGAN

The miracles of science

American DUPONT

QUPOND



Germany Schunk



American Dow



American METCAR



Japan Zeonex

Rubber



Japan DAIKIN



Uniroyal Chemical Inc

SIC



SAINT- GOBAIN

PTFE W



Italy-MTU

Spring



Japan GMB

Other







Japan Polyplastics



Automotive



河南西峡汽车水 泵股份有限公司



一汽富奥汽车 零部件有限公司



上海乾通汽车 附件有限公司



洛拖集团(中国一 拖集团有限公司)



韩国 KIA(起亚) OEM配套



伊朗标致 OEM 配套



南非大众



河北宏业机械股份



美国三电



中国上海三电



广州动源压缩机



汉钟精机股份







意大利富士豪





Chemical Industry















Pump



GMB



KUBOTA Corporation



EBARA



Flowserve Corportation












Footprint





80% products are exported to more than 60 countries all over the world!


Exhibition











Exhibition









Italy-EIMA show



Turkey - ISK-SODEX



Add: No 3005-07 ,Sino-Life Tower,No 707 Zhangyang

Rd, Pudong Shanghai China 20020

Tel: 0086-21-58355541 58353145 50102677

Fax:0086-21-5858353141

http//www.trisunltd.com

