

Project: _____

Part#: _____

Type: _____

2/4' LED Vapor Tight Fixture



The EnVision LED Vapor Tight fixtures features a new slim and modern design is perfect for any environment. The vapor tight is available in tri-color 3000k/4000k/5000k, making it easy to stock for the distributors and convenient to the contractor in case an end user decides to change the color temperature on site. Motion sensor and emergency backups are optional.

Applications:

- Warehouse, Barn, Auto shop lighting
- Basement, Barn, Garage Lighting
- Gas Station, Car Wash, Auto Shop Lighting
- Industrial Kitchen, Airport Lighting

Product Information:

- Environmentally friendly injection molding
- Driving includes dimming control for 0-10V
- 50,000-hour LED lifespan based on IES LM-80 results
- IP67 Waterproof
- Metal Anti-Rust Clips

L E D - V P T -	Feet/Watt	T R I -	Accessories	Warranty
1	2	3	4	5

1	Product	2	Feet/Watt	3	Color	4	Accessories	5	Warranty
LED-VPT	Vapor Tight Fixture	2FT-20W 4FT-40W	2 FT / 20W / 2,600lm 4 FT / 40W / 5,200lm	TRI	Variable 30K/40K/50K	(Blank) MS BMS EMB	None Motion Sensor (Internal) Bi-Level Motion Sensor (Internal) Emergency Backup (90 Mins. Internal 15W)	(Blank) 10YR	5 Year (incl.) 10 Year

Specs and model numbers are subject to change with or without notice

REFERENCE TABLES



Available in Tri-Color: 30/40/50K

Trim Model	Description
LED-VPT-2FT-20W-TRI	2 FT LED Vapor Tight Fixture
LED-VPT-4FT-40W-TRI	4 FT LED Vapor Tight Fixture

Fixture Model	Voltage	Watts	Lumens	Dimmable	Color	CRI
LED-VPT-2FT-20W-TRI	120/277V	20w	2,600	0-10V	30/40/50k	>80
LED-VPT-4FT-40W-TRI	120/277V	40w	5,200	0-10V	30/40/50k	>80

Listings

ETL Listing :

Suitable for wet locations

DLC Listed

This product is on the Design Lights Consortium(DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities

IESNA LM-79 &IESNA LM-80 Testing:

This product has been tested by an independent laboratory in accordance with IESNA LM-79 and 80 and have received the Department of Energy Lighting Facts label.

LED Characteristics

Lifespan :

50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

LEDs :

Long-life, high-efficiency SMD2835, patent free.

Color Stability:

Comply with DLC's requirements.

Color Uniformity:

CCT(Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.388-2015

Mounting :

Surface mount & Suspended mount.

IP Rating:

IP67 rated

Finish :

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contain no VOC or toxic heavy metals


Green Technology:

Mercury and UV free RoHS compliant components Polyester powder coat finish formulated without the use of VOC or toxic heavy metals


FEATURES

Knock-outs on both ends, connectable
with waterproof connectors


2' LED Vapor Tight Fixture Dimensions



4' LED Vapor Tight Fixture Dimensions




INSTALLATION DIMENSIONS




	X1(Single Tube)	X2(Double Tube)	Y
2FT	—	40±2mm	300±50mm
4FT	—	40±2mm	818±50mm
5FT	—	40±2mm	1018±50mm


2' LED VAPOR TIGHT FIXTURE PHOTOMETRICS



Height	Average Lux (lx)	Light range (dia.)
1M	540.6	266.87cm
2M	135.1	533.75cm
3M	60.06	800.62cm
4M	33.79	1067.5cm
5M	21.62	1334.37cm



4' LED VAPOR TIGHT FIXTURE PHOTOMETRICS



Height	Average Lux (lx)	Light range (dia.)
1M	557.0	261.51cm
2M	139.2	523.02cm
3M	61.89	784.53cm
4M	34.81	1046.03cm
5M	22.28	1307.54cm

