



Restek Refined

Restek's PLOT Column Family —

# The Benchmark for Performance!

- Innovative bonding process minimizes particle release.
- More consistent flow means stable retention times.
- Outstanding peak symmetry improves impurity analysis.

Visit us at [www.restek.com/petro](http://www.restek.com/petro)



**RESTEK**

Pure Chromatography

[www.restek.com](http://www.restek.com)

# Next Generation of Porous Layer Open Tubular (PLOT) Columns

- Stabilized particle layers improve robustness and reproducibility of retention and flow.
- Compatible with valve switching and Deans switching systems.
- Highly efficient, reproducible analyses; ideal for permanent gases, solvents, and hydrocarbons.
- Innovative manufacturing procedure reduces particle generation and improves performance of PLOT columns.
- Wound on a 7"-diameter, 11-pin cage unless otherwise noted.

Porous layer open tubular (PLOT) columns are very beneficial for solving application problems, especially for the analysis of volatile compounds. PLOT columns have a unique selectivity, allowing for the separation of volatile compounds at ambient temperature. Due to the adsorption mechanism of the stationary phases used in PLOT columns, permanent gases and light hydrocarbons can be resolved at ambient temperature; columns can then be programmed to higher temperatures to elute higher boiling compounds.

## Traditional PLOT Columns Offer Poor Stability

The traditional PLOT column is built with a 5–50  $\mu\text{m}$  layer of particles adhered to the tubing walls. Because this layer of particles generally lacks stability, PLOT columns must be used very carefully, as particle release is common and can cause unpredictable changes in retention time and flow behavior. Traditional PLOT columns also must generally be used in conjunction with particle traps to prevent the contamination of valves, injectors, and GC detectors. Detectors contaminated with particles typically generate electronic noise, which shows up chromatographically as a spike in the baseline. In extreme cases, detector flow can be obstructed by particle buildup. Particles can also affect valves by becoming lodged in the valve and causing leaks or restricting flow. Figure 1 shows an example of blockage caused by particle accumulation inside a Press-Tight connector.

## Restek PLOT Columns Offer Improved Stability to Minimize Particle Release

Restek has developed technology and procedures to manufacture PLOT columns with concentric stabilized adsorption layers. These next-generation PLOT columns show a constant flow behavior (permeability) and have significantly improved mechanical stability, resulting in easier operation, better chromatography, and reduced particle release. Greater particle stability means more reproducible retention times, virtually no spiking, and longer column lifetimes. This innovative Restek stabilization chemistry is currently applied to all fused silica and metal PLOT columns featured here.

## Consistent Flow Restriction Factor (F) Guarantees Reproducible Flow

Thick layers of particles are difficult to deposit in a homogeneous layer, and in traditionally manufactured PLOT columns, this results in variable coating thicknesses. The positions where the layer is thicker act as restrictions and affect flow (Figure 2). Depending on the number and intensity of these restrictions, traditional PLOT columns often show greater variation in flow restriction than wall coated open tubular (WCOT) columns. In practice, conventional PLOT columns with the same dimensions can differ in flow by a factor of 4 to 6 when operated at the same nominal pressure. For applications where flow is important, such as with Deans switching, the nonreproducible flow behavior of most commercially available PLOT columns is a problem.

## PLOT Columns Available In:

### Fused Silica

#### Rt Column Phases:


Rt-Alumina BOND/MAPD  
Rt-Alumina BOND/ $\text{Na}_2\text{SO}_4$   
Rt-Alumina BOND/KCl  
Rt-Alumina BOND/CFC  
Rt-MSieve 5A  
Rt-Q-BOND  
Rt-QS-BOND  
Rt-S-BOND  
Rt-U-BOND

### Metal


#### MXT Column Phases:

MXT-Alumina BOND/MAPD  
MXT-Alumina BOND/ $\text{Na}_2\text{SO}_4$   
MXT-MSieve 5A  
MXT-Q-BOND  
MXT-S-BOND

**Figure 1:** Particles released from traditional PLOT columns can cause blockages.




**Figure 2:** Inconsistent coating thicknesses result in restrictions that cause significant variation in flow.




In order to measure flow restriction reproducibility, Restek introduced a new factor: the flow restriction factor (F). This factor is based on the retention time of an unretained marker compound, as measured on both coated and uncoated tubing using the same backpressure setting (Equation 1). For quality control purposes, methane is used as the marker when evaluating porous polymer columns, and helium is used for testing molecular sieve 5A columns.

Flow restriction factor determination can be used to assess both the degree of column restriction and the reproducibility of the column coating process. Figure 3 shows typical results for PLOT columns manufactured using a conventional process. Because of the difference in flow restriction, individual columns have very different flow characteristics. In contrast, Figure 4 shows results for columns made using our Rt-QS-BOND (bonded porous polymer) PLOT column process. Clearly, our manufacturing process results in greater consistency in both column coating thickness and flow restriction, which results in more stable retention times and better performance in Deans and related flow switching techniques. Flow restriction factors are specified on the certificate of analysis (CofA) included with every Restek PLOT column, and the values are listed on the report.

**Figure 3:** Traditional PLOT columns show significant flow variability, indicating inconsistent column coating thicknesses.



**Figure 4:** PLOT columns from Restek offer consistent flow restriction, giving more reproducible results column to column.



**Equation 1:** Flow restriction factor (F) is used to demonstrate coating consistency.

$$F = \frac{\text{tr}_1 \text{ of unretained component (uncoated tubing)}}{\text{tr}_2 \text{ of unretained component (coated column)}}$$

tr = retention time

Note: F values will always be <1 as the coated column always has more restriction than the uncoated column.

Restek's PLOT columns are exceptionally robust, featuring concentric stabilized coating layers. They allow for more consistent gas flows and are recommended for applications sensitive to variation in retention time or flow. These PLOT columns are a significant advance in technology and are ideal for efficient, reproducible analyses of permanent gases, solvents, and hydrocarbons.

## PLOT Column Phase Cross-Reference: Similar Selectivity

Restek Rt and MXT Columns	Porous Layer	Supelco	Alltech	Agilent (J&W, Varian, Chrompack)	Quadrex
Alumina BOND/Na <sub>2</sub> SO <sub>4</sub>	Aluminum oxide	Alumina-Sulfate	AT-Alumina	GS-Alumina, CP-Al <sub>2</sub> O <sub>3</sub> /NA <sub>2</sub> SO <sub>4</sub>	_____
Alumina BOND/KCl	Aluminum oxide	Alumina-Chloride	_____	GS-Alumina KCl, HP PLOT Al <sub>2</sub> O <sub>3</sub> , CP-Al <sub>2</sub> O <sub>3</sub> /KCl	_____
Alumina BOND/CFC	Aluminum oxide	_____	_____	<b>unique product</b>	_____
Alumina BOND/MAPD	Aluminum oxide	_____	_____	Select Al <sub>2</sub> O <sub>3</sub> MAPD	_____
M sieve 5A	Molecular sieve 5A	Molsieve 5A	AT-Molesieve	HP PLOT Molesieve, CP-Molesieve 5A	PLT-5A
Q-BOND	100% Divinylbenzene	Supel-Q-PLOT	AT-Q	HP PLOT Q, CP-PoraPlot Q, PoraBond Q	_____
QS-BOND	Intermediate polarity porous polymer	_____	_____	GS-Q	_____
S-BOND	DVB vinylpyridine polymer	_____	_____	CP-PoraPlot S	_____
U-BOND	DVB ethylene glycol-dimethylacrylate polymer	_____	_____	HP PLOT U, CP-PoraPlot U, CP-PoraBond U	_____

## i tech tip

Traces of water in the carrier gas and samples will affect the retention and the selectivity of alumina. If exposed to water, the retention times will shorten. The column can be regenerated by conditioning for 15–30 minutes at 200 °C under normal carrier gas flow. Periodic conditioning ensures excellent run-to-run retention time reproducibility.

Unless noted, the maximum programmable temperature for an Rt-Alumina BOND column is 200 °C. Temperatures higher than the stated maximum temperature can cause irreversible changes to the porous layer adsorption properties.

## Rt-Alumina BOND Columns

Restek Rt-Alumina BOND columns are highly selective for C1–C5 hydrocarbons and separate all saturated and unsaturated hydrocarbon isomers above ambient temperatures. The reactivity of the aluminum oxide stationary phase is minimized, by deactivation with inorganic salts like KCl or Na<sub>2</sub>SO<sub>4</sub>, to improve column response for polar unsaturates, such as dienes, and the column's sensitivity (or response) ensures linear and quantitative chromatographic analysis for these compounds. Strong bonding minimizes particle generation and release, which allows valve switching with minimal risk to the injection or detection systems. And because they are stable up to at least 200 °C, Rt-Alumina BOND columns can be regenerated to restore full efficiency and selectivity by conditioning at their maximum temperature if water is adsorbed. High capacity and loadability give you exceptionally symmetrical peaks, making these columns ideal for volatile hydrocarbon separations at percent levels, as well as impurity analyses at ppm concentrations. Restek Rt-Alumina BOND PLOT columns are manufactured on fused silica tubing; select phases are also available on metal MXT tubing.

To ensure reproducible retention times and predictable flow behavior column to column, each Rt-Alumina BOND column is extensively tested. A hydrocarbon test mix confirms proper phase retention and selectivity. To calculate *k* (retention or capacity factor), which is a measure of phase retention, 1,3-butadiene is used, while selectivity is measured using retention indices for propadiene and methyl acetylene. The resolution of *trans*-2-butene and 1-butene is also verified and, to measure efficiency, plates per meter are checked using 1,3-butadiene.

### Rt-Alumina BOND/Na<sub>2</sub>SO<sub>4</sub> Columns (fused silica PLOT)

Na<sub>2</sub>SO<sub>4</sub> deactivation

- Acetylene and propadiene elute after butanes.
- Best separation for butene isomers (impurities in butene streams).
- Methyl acetylene elutes after 1,3-butadiene.
- Cyclopropane (impurity in propylene) elutes well before propylene.
- Stable to 200 °C.
- Also available on metal MXT tubing! (See page 12.)


## similar phases

GS-Alumina, CP-Al<sub>2</sub>O<sub>3</sub>/Na<sub>2</sub>SO<sub>4</sub>, Alumina-Sulfate, AT-Alumina

ID	df	temp. limits	30-Meter cat.#	50-Meter cat.#
0.25 mm	4 μm	to 200 °C	19775	—
0.32 mm	5 μm	to 200 °C	19757	19758
0.53 mm	10 μm	to 200 °C	19755	19756

## did you know?

Restek draws our own fused silica tubing and applies our own proprietary stationary phases. By fully managing our production streams, we are able to ensure unparalleled reliability and stability.



## Rt-Alumina BOND/KCl Columns (fused silica PLOT)

KCl deactivation


- Restek's lowest polarity alumina column.
- Low moisture sensitivity reduces the need for frequent regeneration.
- Acetylene elutes before *n*-butane.
- Methyl acetylene (impurity in 1,3-butadiene) elutes before 1,3-butadiene.
- Stable to 200 °C.

## similar phases

GS-Alumina KCl, HP-PLOT  
Al<sub>2</sub>O<sub>3</sub>/KCl, CP-Al<sub>2</sub>O<sub>3</sub>/KCl,  
Alumina-Chloride

ID	df	temp. limits	30-Meter cat.#	50-Meter cat.#
0.25 mm	4 µm	to 200 °C	19776	—
0.32 mm	5 µm	to 200 °C	19761	19762
0.53 mm	10 µm	to 200 °C	19759	19760

### Ethylene and C1-C5 Hydrocarbons by ASTM D6159-97 on Rt-Alumina BOND/KCl, Rtx-1




**Column** Rt-Alumina BOND/KCl \*, 50 m, 0.53 mm ID, 10 µm (cat.# 19760)  
**Sample** Ethylene gas plus C1 through C5 hydrocarbons  
**Injection**  
 Inj. Vol.: 1 µL split  
 Liner: 2 mm splitless (cat.# 20712)  
 Inj. Temp.: 200 °C  
 Split Vent  
 Flow Rate: 60 mL/min  
**Oven**  
 Oven Temp.: 35 °C (hold 2 min) to 190 °C at 4 °C/min (hold 15 min)

**Carrier Gas** He, constant pressure (8.0 psi, 55.2 kPa)  
 Linear Velocity: 25.4 cm/sec @ 35 °C  
**Detector** FID @ 200 °C  
**Make-up Gas**  
 Type: N<sub>2</sub>  
 Data Rate: 20 Hz  
**Instrument** HP5890 GC  
**Notes**  
 \* Rt-Alumina BOND/KCl, 50 m, 0.53 mm ID, 10.0 µm (cat.# 19760) in series with an Rtx-1, 30 m, 0.53 mm ID, 5.0 µm (cat.# 10179) connected using a universal Press-Tight connector (cat.# 20401)  
 (conditions as per ASTM D6159-97)

## did you know?

All Restek PLOT columns come standard on a 7"-diameter, 11-pin cage. Metal MXT columns are also available coiled to 3.5" diameter by adding the suffix -273 to the part number (See page 12). If you need more information, please call your local Restek representative.



For more chromatograms, search our extensive library at  
[www.restek.com/chromatograms](http://www.restek.com/chromatograms)

### Rt-Alumina BOND/CFC Columns (fused silica PLOT)

- Improved inertness for chlorofluorocarbon (CFC) compounds.
- Highly selective alumina-based column, separates most CFCs.
- High retention and capacity for CFCs.
- Stable to 200 °C.

Restek  
exclusive!

#### **i** tech tip

Especially when valve switching or backflushing is used, Restek recommends using particle traps to help prevent detector spikes and valve rotor scratches.


Visit [www.restek.com/plot](http://www.restek.com/plot) for specialized PLOT column particle traps.

The Alumina BOND/CFC adsorbent is ideal for retaining volatile halogenated compounds, especially CFCs (chlorinated fluorocarbons) like Freon products. It offers high selectivity, allowing a wide range of CFC isomers to be resolved at above ambient temperatures. The Rt-Alumina BOND/CFC column is thoroughly deactivated to reduce the reactivity of alumina. Even though there is still some residual reactivity for some mono- or di-substituted CFCs, the majority of these compounds can be accurately quantified from mainstream processes or in impurity analyses.

ID	df	temp. limits	30-Meter cat.#
0.53 mm	10 µm	to 200 °C	19763

### Impurity Analysis of 1,1,1,2-Tetrafluoroethane (CFC-134a) on Rt-Alumina BOND/CFC


Rt-Alumina BOND/CFC columns provide the best selectivity for impurity analysis of CFCs.



**Column** Rt-Alumina BOND/CFC, 30 m, 0.53 mm ID (cat.# 19763)  
**Sample** 1,1,1,2-Tetrafluoroethane  
**Conc.:** Neat  
**Injection**  
**Inj. Vol.:** 500 µL split  
**Oven**  
**Oven Temp.:** 80 °C (hold 6 min) to 140 °C at 10 °C/min (hold 2 min)  
**Carrier Gas** He  
**Detector** FID  
**Notes** Gas sampling, purity analysis

Note that tailing peaks are common in CFC analyses due to overloading normally employed for this type of work.

GC\_GN1155



For more chromatograms, search our extensive library at  
[www.restek.com/chromatograms](http://www.restek.com/chromatograms)

## Rt-Alumina BOND/MAPD Columns (fused silica PLOT)

- Optimized deactivation produces maximum response when analyzing trace levels of acetylene, methyl acetylene, and propadiene.
- Stable response factors make this column ideal for process-type applications where recalibration must be minimized.
- High loadability reduces peak tailing and improves separations.
- Extended temperature range up to 250 °C for fast elution of high molecular weight (HMW) hydrocarbons and accelerated column regeneration following exposure to water.
- Stable to 250 °C.
- Also available on metal MXT tubing! (See page 12.)

Restek's R&D chemists have optimized the deactivation technology applied to our Rt-Alumina BOND/MAPD column for improved analysis of trace concentrations of polar hydrocarbons like acetylene, methyl acetylene, and propadiene in hydrocarbon streams containing higher levels of C1-C5 hydrocarbons. Our alumina PLOT deactivation produces an incredibly inert column that offers superior reproducibility and stable response factors to maximize the number of analyses before recalibration is required. Its high sample capacity reduces peak tailing, thereby improving the separation of target compounds. In addition, a 250 °C maximum operating temperature lets you more quickly elute hydrocarbons up to dodecane and reduces regeneration time when the column is exposed to water from samples or carrier gases.

ID	df	temp. limits	30-Meter cat.#	50-Meter cat.#
0.25 mm	4 µm	to 200/250 °C	19781	—
0.32 mm	5 µm	to 250 °C	19779	19780
0.53 mm	10 µm	to 250 °C	19777	19778

## did you know?


All Restek PLOT columns come standard on a 7"-diameter, 11-pin cage. Metal MXT columns are also available coiled to 3.5" diameter by adding the suffix -273 to the part number. If you need more information, please call your local Restek representative.

## similar phases

Select Al<sub>2</sub>O<sub>3</sub> MAPD

### 1,3-Butadiene on Rt-Alumina BOND/MAPD (Purity Analysis)

- Peaks**
1. Isobutane
  2. *n*-Butane
  3. Propadiene
  4. *trans*-2-Butene
  5. 1-Butene
  6. Isobutene
  7. *cis*-2-Butene
  8. Isopentane
  9. *n*-Pentane
  10. 1,2-Butadiene
  11. 1,3-Butadiene
  12. Methyl acetylene



Rt-Alumina BOND/MAPD PLOT columns are made specifically for the analysis of petrochemicals and downstream products such as ethylene, propylene, butylenes, and butadiene.

**Column** Rt-Alumina BOND/MAPD, 50 m, 0.53 mm ID, 10.0 µm (cat.# 19778)  
**Sample Injection** Crude 1,3-butadiene  
**Inj. Vol.:** 10 µL split  
**Liner:** 2.0 mm ID straight inlet liner (cat.# 20712)  
**Inj. Temp.:** 200 °C  
**Split Vent**  
**Flow Rate:** 100 mL/min  
**Oven**  
**Oven Temp.:** 70 °C (hold 5 min) to 200 °C at 10 °C/min (hold 0 min)

**Carrier Gas** He, constant pressure (20 psi, 137.9 kPa)  
**Detector** FID @ 250 °C  
**Make-up Gas**  
**Flow Rate:** 30 mL/min  
**Make-up Gas**  
**Type:** N<sub>2</sub>  
**Data Rate:** 20 Hz  
**Instrument** HP5890 GC



## also available! Metal MXT PLOT Columns

See page 12 for more information.

## did you know?

Rt-Msieve 5A PLOT columns are designed for efficient separation of Ar/O<sub>2</sub> and other permanent gases, including CH<sub>4</sub>, C<sub>2</sub>H<sub>6</sub>, and CO.

## similar phases

HP PLOT Molesieve, CP-Molsieve 5A, Molsieve 5A, AT-Molsieve, PLT-5A

### **i** tech tip

Because molecular sieve materials are very hydrophilic, they will adsorb water from the sample or carrier gas. Water contamination can have a detrimental effect on peak symmetry and can reduce the resolution of all compounds. If water contamination occurs, reactivate your Rt-Msieve 5A PLOT column by conditioning at 300 °C with dry carrier gas flow for 3 hours.



## also available! Metal MXT PLOT Columns

See page 12 for more information.

# Molecular Sieve 5A PLOT Columns


Restek's molecular sieve 5A PLOT columns are designed for efficient separation of argon/oxygen and other permanent gases, including carbon monoxide. Special coating and deactivation procedures ensure chromatographic efficiency and the integrity of the porous layer coating. Molecular sieves have very high retention, allowing separations of permanent gases at temperatures above ambient. Our deactivation technology also allows carbon monoxide to elute as a sharp peak. Additionally, our unique immobilization process guarantees that the uniform particles remain adhered to the tubing—even after continuous valve cycling.

### Rt-Msieve 5A Columns (fused silica PLOT)

- Improve accuracy with sharp, symmetrical peaks for argon, oxygen, and carbon monoxide.
- Easily separate permanent gases at temperatures above ambient.
- Restek PLOT technology reduces particle release, improving flow reproducibility and reducing downtime for maintenance.
- Stable to 300 °C.
- Also available on metal MXT tubing! (See page 12.)

ID	df	temp. limits	15-Meter cat.#	30-Meter cat.#
0.25 mm	20 µm	to 300 °C	19773	—
0.32 mm	30 µm	to 300 °C	19720	19722
0.53 mm	50 µm	to 300 °C	19721	19723

### Separation of Argon/Oxygen and Other Permanent Gases on Rt-Msieve 5A



Peaks	Conc. (µg/mL)
1. Hydrogen	40
2. Argon	30
3. Oxygen	50
4. Nitrogen	50
5. Methane	40
6. Carbon monoxide	50

GC\_PC00898

**Column** Rt-Msieve 5A, 30 m, 0.53 mm ID, 50 µm (cat.# 19723)  
**Sample** Permanent gases  
**Injection** Sample valve  
**Sample Loop Vol.:** 5 µL  
**Valve Name:** 6-port Valco valve  
**Inj. Temp.:** 200 °C  
**Valve Temp.:** Ambient  
**Oven**  
**Oven Temp.:** 27 °C (hold 5 min) to 100 °C at 10 °C/min (hold 5 min)  
**Carrier Gas** He, constant flow  
**Flow Rate:** 5.0 mL/min  
**Detector** Valco helium ionization detector @ 150 °C



# Porous Polymer Columns

Porous polymers are unique, highly retentive stationary phases with a wide application range that are able to elute both polar and nonpolar compounds. They are very hydrophobic, so water has no impact on retention times and even elutes as a good chromatographic peak. The Q-BOND is our most nonpolar and widely used porous polymer column; functional groups can be added to increase polarity (i.e., QS-, S-, and U-BOND). The process used to manufacture porous polymer PLOT columns causes the particles to adhere strongly to the walls of the tubing, so there is virtually no particle generation. You get reproducible performance from column to column, including selectivity and flow.

## Rt-Q-BOND Columns (fused silica PLOT)

100% divinylbenzene



- Nonpolar PLOT column incorporating 100% divinylbenzene.
- Excellent for analysis of C1 to C3 hydrocarbons as well as isomers and alkanes up to C10.
- High retention for CO<sub>2</sub> simplifies gas analysis; CO<sub>2</sub> and methane separated from O<sub>2</sub>/N<sub>2</sub>/CO. (Note: O<sub>2</sub>/N<sub>2</sub>/CO not separated at ambient temperature.)
- Use for analysis of oxygenated compounds and solvents.
- Maximum temperature of 300 °C.
- Also available on metal MXT tubing! (See page 12.)

ID	df	temp. limits	15-Meter cat.#	30-Meter cat.#
0.25 mm	8 µm	to 280/300 °C	19764	19765
0.32 mm	10 µm	to 280/300 °C	19743	19744
0.53 mm	20 µm	to 280/300 °C	19741	19742

Our porous polymer PLOT columns are not moisture sensitive, making them ideal for applications where moisture is of major concern.

## similar phases

HP PLOT Q, CP-PoraPLOT Q, CP-PoraBOND Q, Supel-Q-PLOT, AT-Q



## similar phases

GS-Q


### Rt-QS-BOND Columns (fused silica PLOT)

porous divinylbenzene homopolymer

- Intermediate polarity porous polymer PLOT column incorporating low 4-vinylpyridine.
- Separates ethane, ethylene, and acetylene to baseline.
- Stable to 250 °C.

ID	df	temp. limits	15-Meter cat.#	30-Meter cat.#
0.25 mm	8 μm	to 250 °C	19767	19768
0.32 mm	10 μm	to 250 °C	19739	19740
0.53 mm	20 μm	to 250 °C	19737	19738

#### Refinery Gas Mixture on Rt-QS-BOND



**Column** Rt-QS-BOND, 30 m, 0.53 mm ID, 20 μm (cat.# 19738)  
Refinery gas standard

**Sample Injection**  
Inj. Vol.: 20 μL split  
Liner: 2 mm (cat.# 20712)  
Inj. Temp.: 200 °C  
Split Vent  
Flow Rate: 35 mL/min

**Oven**  
Oven Temp.: 40 °C (hold 2 min) to 225 °C at 15 °C/min (hold 5 min)

**Carrier Gas**  
He, constant pressure (11.5 psi, 79.3 kPa)  
Linear Velocity: 68 cm/sec @ 40 °C

**Detector**  
Make-up Gas  
Type: He  
Data Rate: 20 Hz  
Sensitivity Mode: He/Hz

**Instrument** HP5890 GC

### Rt-S-BOND Columns (fused silica PLOT)

porous divinylbenzene homopolymer


- Midpolarity porous polymer PLOT column, incorporating high 4-vinylpyridine.
- Use for the analysis of nonpolar and polar compounds.
- Stable to 250 °C.
- Also available on metal MXT tubing! (See page 12.)

## similar phases

CP-PoraPLOT S

ID	df	temp. limits	15-Meter cat.#	30-Meter cat.#
0.25 mm	8 μm	to 250 °C	19769	19770
0.32 mm	10 μm	to 250 °C	—	19748
0.53 mm	20 μm	to 250 °C	19745	19746

#### Solvent Mixture on Rt-S-BOND



**Column** Rt-S-BOND, 30 m, 0.53 mm ID, 20 μm (cat.# 19746)  
Solvent mixture

**Sample Injection**  
Inj. Vol.: 1.0 μL split  
Liner: Taper (4 mm) (cat.# 20798)  
Inj. Temp.: 200 °C  
Split Vent Flow Rate: 100 mL/min

**Oven**  
Oven Temp.: 120 °C to 220 °C at 5 °C/min (hold 5.0 min)

**Carrier Gas**  
Hz, constant pressure (4.2 psi, 29.0 kPa)  
Linear Velocity: 40 cm/sec @ 120 °C

**Detector** FID @ 220 °C

**Rt-U-BOND Columns** (fused silica PLOT)  
divinylbenzene ethylene glycol/dimethylacrylate

- Restek's highest polarity porous polymer column.
- Polar PLOT column, incorporating divinylbenzene ethylene glycol/dimethylacrylate.
- Highly inert for the analysis of polar and nonpolar compounds.
- Common applications include: trace H<sub>2</sub>S, COS, and mercaptans in hydrocarbon streams.
- Stable to 190 °C.


ID	df	temp. limits	15-Meter		30-Meter	
			cat.#	cat.#	cat.#	cat.#
0.25 mm	8 µm	to 190 °C	19771	19772		
0.32 mm	10 µm	to 190 °C	19751	19752		
0.53 mm	20 µm	to 190 °C	19749	19750		

also available!  
**Metal MXT PLOT  
Columns**

See page 12 for more  
information.

**similar phases**

HP-PLOT U, CP-PoraPLOT U,  
CP-PoraBOND U





## Metal MXT PLOT Columns

Advantages of metal MXT PLOT columns include:

- Can be made in small coil diameters—perfect for tight spaces.
- Rugged material withstands rough handling and shock.
- Designed for robust performance in process GCs and field instruments.
- Available in 3.5"-coil diameter or 7"-diameter, 11-pin cage.

Restek chemists have developed technology that allows many of our popular PLOT columns to be made on Siltek-treated stainless steel. These columns have the same characteristics and performance as fused silica PLOT columns, but offer additional benefits for process GCs and field applications as they are virtually unbreakable and can be coiled into very small diameters.

ID	df	temp. limits	3.5" coil 15-Meter cat.#	7" diameter 11-pin cage 15-Meter cat.#	3.5" coil 30-Meter cat.#	7" diameter 11-pin cage 30-Meter cat.#
<b>MXT-Msieve 5A</b>						
0.25 mm	20 µm	to 300 °C	79717-273	79717	—	—
0.53 mm	50 µm	to 300 °C	—	—	79723-273	79723
<b>MXT-Alumina BOND/Na<sub>2</sub>SO<sub>4</sub></b>						
0.53 mm	10 µm	to 200 °C	—	—	79714-273	79714
<b>MXT-Alumina BOND/MAPD</b>						
0.53 mm	10 µm	to 250 °C	—	—	79728-273	79728
<b>MXT-Q-BOND</b>						
0.25 mm	8 µm	to 300 °C	79718-273	79718	—	—
0.53 mm	20 µm	to 280/300 °C	—	—	79716-273	79716
<b>MXT-S-BOND</b>						
0.53 mm	20 µm	to 250 °C	—	—	79712-273	79712

## MXT Low Dead Volume Connector Kits for Metal Columns

- Connect a guard column/transfer line to an MXT stainless steel column.
- Low thermal mass tracks rapid oven temperature programming.
- Stainless steel ferrules and nuts.
- Available in "Y" and union configurations.
- Siltek treatment ensures ultimate inertness.



Each kit contains the MXT union, two 1/32-inch ferrules and nuts.

Description	qty.	cat.#
For 0.28 mm ID MXT Columns	kit	20397
For 0.18/0.25/0.32 mm ID MXT Columns	kit	20536
For 0.53 mm ID MXT Columns	kit	20394

Visit us at [www.restek.com/petro](http://www.restek.com/petro)

**RESTEK**  
Pure Chromatography

Questions? Contact us or your local Restek representative ([www.restek.com/contact-us](http://www.restek.com/contact-us)).

Restek patents and trademarks are the property of Restek Corporation. (See [www.restek.com/Patents-Trademarks](http://www.restek.com/Patents-Trademarks) for full list.) Other trademarks in Restek literature or on its website are the property of their respective owners. Restek registered trademarks are registered in the U.S. and may also be registered in other countries. To unsubscribe from future Restek communications or to update your preferences, visit [www.restek.com/subscribe](http://www.restek.com/subscribe). To update your status with an authorized Restek distributor or instrument channel partner, please contact them directly.

© 2019 Restek Corporation. All rights reserved. Printed in the U.S.A.

[www.restek.com](http://www.restek.com)



Lit. Cat.# PCSS1163G-UNV