

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**Commercial product name: **WACKER® PRIMER G 790****1.2 Relevant identified uses of the substance or mixture and uses advised against**

Use of substance / preparation:

Industrial.  
primer .**1.3 Details of the supplier of the safety data sheet**

Manufacturer/distributor:	Wacker Chemie AG
Street/POB-No.:	Hanns-Seidel-Platz 4
State/postal code/city:	D 81737 München
Telephone:	+49 89 6279-0
Telefax:	+49 89 6279-1770

Information about the Safety Data Sheet:	Telephone	+49 8677 83-4888
	Telefax	+49 8677 886-9722
	eMail	WLCP-MSDS@wacker.com

**1.4 Emergency telephone number**Emergency Information: **+44 1273 289451****SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No. 1272/2008:

Hazard class	Hazard category	Route of exposure	H-Code
Long-term (chronic) aquatic hazard	Category 2		H411
Aspiration hazard	Category 1		H304
Specific target organ toxicity - single exposure	Category 3		H336
Reproductive toxicity	Category 2		H361d
Serious eye damage/eye irritation	Category 1		H318
Skin corrosion/irritation	Category 2		H315
Flammable liquids	Category 2		H225

**2.2 Label elements**

Labelling according to Regulation (EC) No. 1272/2008:

Pictogram(s):



Signal Word: Danger

H-Code	Hazard Statements
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

P-Code	Precautionary Statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection.
P273	Avoid release to the environment.
P243	Take action to prevent static discharges.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/ doctor.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/ doctor if you feel unwell.
P391	Collect spillage.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P370 + P378	In case of fire: Use extinguishing powder, alcohol-resistant foam or carbon dioxide to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to waste disposal.

Hazard ingredients (labelling):

C7 - C9 Isoalkanes

Titanium tetrabutanolate

Toluene

The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 6,7 %.

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients**
**3.1 Substances**

not applicable

**3.2 Mixtures**
**3.2.1 Chemical characteristics**

silane and siloxane with functional groups + auxiliary + solvent

**3.2.2 Hazardous ingredients**

Type	CAS No.	EC-No. REACH no.	Substance	Content %	Classification according to Regulation (EC) No. 1272/2008*	Comment
INHA	90622-56-3	292-458-5 01-2119471305-42	C7 - C9 Isoalkanes	>75	Asp. Tox. 1; H304 STOT SE 3; H336 Flam. Liq. 2; H225 Skin Irrit. 2; H315 Aquatic Chronic 2; H411	[1]
INHA	5593-70-4	227-006-8 01-2119967423-33	Titanium tetrabutanolate	<10	STOT SE 3; H336 STOT SE 3; H335 Eye Dam. 1; H318 Flam. Liq. 3; H226 Skin Irrit. 2; H315	[1]

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

INHA	108-88-3	203-625-9 01-2119471310-51	Toluene	>3 – <5	Repr. 2; H361d STOT RE 2; H373 STOT SE 3; H336 Skin Irrit. 2; H315 Asp. Tox. 1; H304 Flam. Liq. 2; H225	[1], [2]
INHA	78-10-4	201-083-8 01-2119496195-28	Tetraethyl silicate	<2	Flam. Liq. 3; H226 Acute Tox. 4 by inhalation; H332 Eye Irrit. 2; H319 STOT SE 3; H335	[1], [2]

Type: INHA: ingredient, VERU: impurity

[1] = Hazardous or environmentally harmful substance; [2] = substance with a Community workplace exposure limit; [3] = PBT substance; [4] = vPvB substance

\*Classification codes are explained in section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above  $\geq 0.1\%$ .**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

**After contact with the eyes:**

Rinse immediately with plenty of water for 10-15 minutes and seek medical advice.

**After contact with the skin:**

Wash with plenty of water or soap and water; immediately remove all contaminated clothing. Seek medical advice and clearly identify substance.

**After inhalation:**

Move to fresh air, keep the victim laying down and restful. If breathing has stopped, give artificial respiration. Seek medical advice and clearly identify substance. Administer oxygen in case of breathing difficulties. If unconscious place in stable sideways position.

**After swallowing:**

Seek medical advice and clearly identify substance. Do not induce vomiting. Danger of aspiration.

**4.2 Most important symptoms and effects, both acute and delayed**

Any relevant information can be found in other parts of this section.

**4.3 Indication of any immediate medical attention and special treatment needed**

Further toxicology information in section 11 must be observed.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media:**

water mist , extinguishing powder , alcohol-resistant foam , carbon dioxide .

**Extinguishing media which must not be used for safety reasons:**

water jet .

**5.2 Special hazards arising from the substance or mixture**

Heavy soot formation during combustion.

**5.3 Advice for firefighters****Special protective equipment for fire fighting:**

Use respiratory protection independent of recirculated air.

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Keep unprotected persons away. Wear personal protection equipment (see section 8). Avoid inhaling mists and vapours. Avoid contact with eyes and skin.

**6.2 Environmental precautions**

Prevent material from entering sewers or surface waters. Inform authorities if substance leaks into surface waters, sewerage or ground. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers.

**6.3 Methods and material for containment and cleaning up**

Take up mechanically and dispose of according to local/state/federal regulations. Absorb with a liquid binding material such as diatomaceous earth and dispose of according to local/state/federal regulations. Contain larger amounts and pump up into suitable containers.

**Further information:**

Eliminate all sources of ignition.

**6.4 Reference to other sections**

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Precautions for safe handling:**

Ensure adequate ventilation. Must be syphoned off in situ. Keep away from incompatible substances in accordance with section 10.

**Precautions against fire and explosion:**

Cool endangered containers with water. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging.

**7.2 Conditions for safe storage, including any incompatibilities****Conditions for storage rooms and vessels:**

Make sure there is no possibility of entering the ground.

**Advice for storage of incompatible materials:**

none known

**Further information for storage:**

Protect against moisture. Keep container tightly closed and store in a cool, well ventilated place.

**7.3 Specific end use(s)**

No data available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Maximum airborne concentrations at the workplace:**

CAS No.	Substance	Type	mg/m <sup>3</sup>	ppm	Dust fract.	Fibre/m <sup>3</sup>
108-88-3	Toluene	TLV_GB	191,0	50,0		
108-88-3	Toluene	EU	192,0	50,0		
78-10-4	Tetraethyl silicate	TLV_GB	87,0	10,0		
78-10-4	Tetraethyl silicate	EU	44,0	5,0		
71-36-3	1-Butanol	TLV_GB				
64-17-5	Ethanol	TLV_GB	1920,0	1000,0		

Toluene (CAS No. 108-88-3): STEL (EU) is 384 mg/m<sup>3</sup> (=100 ppm), can be absorbed through the skin.

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

**Derived No-Effect Level (DNEL):****Tetraethyl silicate**

Area of use:	Value:
Worker; dermal; systemic (acute)	12,1 mg/kg/day
Worker; dermal; systemic (long term)	12,1 mg/kg/day
Worker; by inhalation; systemic (acute)	85 mg/m <sup>3</sup>
Worker; by inhalation; local (acute)	85 mg/m <sup>3</sup>
Worker; by inhalation; systemic (long term)	85 mg/m <sup>3</sup>
Worker; by inhalation; local (long term)	85 mg/m <sup>3</sup>
Consumer; dermal; systemic (acute)	8,4 mg/kg/day
Consumer; dermal; systemic (long term)	8,4 mg/kg/day
Consumer; by inhalation; systemic (acute)	25 mg/m <sup>3</sup>
Consumer; by inhalation; local (acute)	25 mg/m <sup>3</sup>
Consumer; by inhalation; systemic (long term)	25 mg/m <sup>3</sup>
Consumer; by inhalation; local (long term)	25 mg/m <sup>3</sup>

**Predicted No Effect Concentration (PNEC):****Tetraethyl silicate**

Area of use:	Value:
freshwater	0,192 mg/l The value has been derived for the following hydrolysis product: ethanol
marine water	0,0192 mg/l The value has been derived for the following hydrolysis product: ethanol
Sediment (freshwater)	0,18 mg/kg wet weight The value has been derived for the following hydrolysis product: ethanol
Sediment (marine water)	0,018 mg/kg wet weight The value has been derived for the following hydrolysis product: ethanol
Soil	0,05 mg/kg wet weight The value has been derived for the following hydrolysis product: ethanol
sewage treatment plant	4000 mg/l The value has been derived for the following hydrolysis product: ethanol
Intermittent release	10 mg/l The value has been derived for the following hydrolysis product: ethanol

**8.2 Exposure controls****8.2.1 Exposure in the work place limited and controlled****General protection and hygiene measures:**

Do not eat, drink or smoke when handling. Do not breathe vapours. Avoid contact with eyes and skin.

**Personal protection equipment:****Respiratory protection**

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Gas filter type ABEK (certain inorganic, organic and acidic gases and vapors; ammonia/amines), according to acknowledged standards such as EN 14387

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136.

Recommended Filter type: Combined filter type ABEK-P2 (certain inorganic, organic and acidic gases and vapors; ammonia/amines; particles), according to acknowledged standards such as EN 14387

For long or intense exposure, use respiratory protective equipment. Suitable respiratory equipment: Positive pressure self contained breathing apparatus, according to acknowledged standards such as EN 137.

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

Observe the equipment manufacturer's information and wear time limits for respirators.

**Eye protection**

protective goggles .

**Hand protection**

Protective gloves are required at all times when handling the material, according to recognized standards such as EN374.

Recommended glove types: Protective gloves made of fluorinated rubber  
thickness of the material: > 0,7 mm  
Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of 5-layer laminate of PE and EVOH (4H)  
thickness of the material: > 0,062 mm  
Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

**Skin protection**

protective clothing

**8.2.2 Exposure to the environment limited and controlled**

Prevent material from entering surface waters, drains or sewers and soil.

**8.3 Further information for system design and engineering measures**

Observe information in section 7.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Property:	Value:	Method:
<b>Appearance</b>		
Physical state .....	liquid	
Colour.....	yellowish	
<b>Odour</b>		
Odour .....	faint	
<b>Odour limit</b>		
Odour limit.....	no data available	
<b>pH-Value</b>		
pH-Value .....	not applicable	
<b>Melting point/freezing point</b>		
Melting point / melting range .....	not applicable	
<b>Initial boiling point and boiling range</b>		
Boiling point / boiling range .....	116 - 142 °C at 1013 hPa	(not specified)
<b>Flash point</b>		
Flash point.....	3 °C	(ISO 13736)
<b>Evaporation rate</b>		
Evaporation rate .....	no data available	
<b>Upper/lower flammability or explosive limits</b>		
Lower explosion limit (LEL) .....	0,9 Vol-%	
Upper explosion limit (UEL).....	7,0 Vol-%	
<b>Vapour pressure</b>		
Vapour pressure.....	50 hPa / 25 °C	(EU-GL.A.4)
<b>Solubility(ies)</b>		
Water solubility / miscibility.....	virtually insoluble	
<b>Vapour density</b>		
Relative gas/vapour density .....	No data known.	

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

**Relative Density**Relative Density .....: 0,76 (23 °C; 1013 hPa) (DIN 51757)  
(Water / 4 °C = 1,00)Density .....: 0,76 g/cm<sup>3</sup> (23 °C; 1013 hPa) (DIN 51757)**Partition coefficient: n-octanol/water**

Partition coefficient: n-octanol/water.....: No data known.

**Auto-ignition temperature**

Ignition temperature .....: 370 °C (EN 14522)

**Decomposition temperature**

Thermal decomposition .....: not applicable

**Viscosity**

Viscosity (dynamic) .....: 0,76 mPa.s at 23 °C (not specified)

Viscosity (kinematic).....: 1 mm<sup>2</sup>/s (DIN 51562-1)**Molecular mass**

Molecular mass .....: not applicable

**9.2 Other information**

Explosion limits for released ethanol: 3.5 - 15%(V).

**SECTION 10: Stability and reactivity****10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

**10.4 Conditions to avoid**

Moisture.

**10.5 Incompatible materials**

Reacts with: acids , water and alkalis . The reaction takes place with the formation of alcohols.

**10.6 Hazardous decomposition products**

If stored and handled properly: none known. Butanol and ethanol under the effect of humidity.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****11.1.1 General information**

Data derived for the product as a whole are of higher priority than data for single ingredients.

**11.1.2 Acute toxicity****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Acute toxicity estimate (ATE):**ATE<sub>mix</sub> (Oral): > 5000 mg/kg**Data on substances:****Toluene:**

Route of exposure	Result/Effect	Species/Test system	Source
Oral	LD50: 5580 mg/kg	Rat	ECHA
dermal	LD50: 12400 mg/kg	Rabbit	ECHA
by inhalation (vapour)	LC50: 28,1 mg/l; 4 h	Rat	ECHA

**11.1.3 Skin corrosion/irritation****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

**Data on substances:****Toluene:**

Result/Effect	Species/Test system	Source
irritating	Rabbit	ECHA OECD 404

**11.1.4 Serious eye damage / eye irritation****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Data on substances:****Toluene:**

Result/Effect	Species/Test system	Source
No eye irritation	Rabbit	ECHA OECD 405

**11.1.5 Respiratory or skin sensitization****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Data on substances:****Toluene:**

Route of exposure	Result/Effect	Species/Test system	Source
dermal	Does not cause skin sensitisation.	Guinea pig; Maximisation Test	ECHA OECD 406

**11.1.6 Germ cell mutagenicity****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Data on substances:****Toluene:**

Result/Effect	Species/Test system	Source
negative	mutation assay (in vitro) mouse lymphoma cells	ECHA OECD 476
negative	mutation assay (in vitro) bacterial cells	ECHA OECD 471
negative	chromosome aberration assay (in vivo) Rat Intraperitoneal; bone marrow cells	ECHA

**11.1.7 Carcinogenicity****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**11.1.8 Reproductive toxicity****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Data on substances****Toluene:**

The substance can possibly impair the unborn child in humans.



**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

**11.1.9 Specific target organ toxicity (single exposure)****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Data on substances:****Toluene:**

Route of exposure	Result/Effect	Source
by inhalation	Target organs: Central nervous system Vapours may be narcotising.	ECHA

**11.1.10 Specific target organ toxicity (repeated exposure)****Assessment:**

For this endpoint no toxicological test data is available for the whole product.

**Data on substances:****Toluene:**

Target organs in animal experiments: Central nervous system.

**11.1.11 Aspiration hazard****Assessment:**

In case an aspiration hazard is based on ingredients, this can be seen from the classification and labeling of the whole product.

**Data on substances:****Toluene:**

Product can pose an aspiration hazard.

**11.1.12 Further toxicological information**

According to literature aliphatic hydrocarbons are slightly irritating to the skin and mucuous membranes and have a skin drying and narcotic effect. If the lungs are directly affected (e.g. by aspiration), inflammation of the lungs may occur. According to documentation n-butanol (71-36-3) is irritating to mucous membranes, slightly irritating to skin, degreases skin, has narcotic effects. Hydrolysis product / impurity: Ethanol (64-17-5) is readily absorbed at all exposure routes. Ethanol may cause irritation of eyes and mucosa, trigger dysfunction of the central nervous system and cause nausea as well as dizziness. Chronic exposure to high amounts of ethanol may cause damage to liver and central nervous system.

**SECTION 12: Ecological information****12.1 Toxicity****Assessment:**

No data known.

**Data on substances:**

Data derived for the product as a whole are of higher priority than data for single ingredients.

**Toluene:**

Result/Effect	Species/Test system	Source
LC50: 5,5 mg/l (measured)	dynamic Coho salmon ( <i>Oncorhynchus kisutch</i> ) (96 h)	ECHA
EC50: 3,78 mg/l (measured)	semistatic Daphnia (48 h)	ECHA
EC50 (photosynthesis): 134 mg/l (nominal)	algae (3 h)	ECHA

**12.2 Persistence and degradability****Assessment:**

No data known.

**Data on substances:**

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

**Toluene:**

Readily biodegradable.

**12.3 Bioaccumulative potential****Assessment:**

Bioaccumulation is not expected to occur.

**12.4 Mobility in soil****Assessment:**

No data known.

**12.5 Results of PBT and vPvB assessment**

No data available.

**12.6 Other adverse effects**

none known

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****13.1.1 Material**

## Recommendation:

Dispose of according to regulations by incineration in a special waste incinerator. Observe local/state/federal regulations.

**13.1.2 Uncleaned packaging**

## Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Uncleaned packaging should be treated with the same precautions as the material.

**13.1.3 Waste Disposal Legislation Ref.No.(EC)**

It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

**SECTION 14: Transport information****14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group****Road ADR:**

Valuation .....: Dangerous Goods  
14.1 UN no. ....: 1993  
14.2 Proper Shipping Name .....: Entzündbarer flüssiger Stoff, n.a.g. (enthält C7-C9 Isoalkane, Titanatetrabutanolat)  
14.2 Proper Shipping Name (national) ....: Flammable liquid, n.o.s (contains C7-C9 Isoalkanes, Titanium tetrabutanolate)  
14.3 Class .....: 3  
14.4 Packaging Group .....: II

**Railway RID:**

Valuation .....: Dangerous Goods  
14.1 UN no. ....: 1993  
14.2 Proper Shipping Name .....: Entzündbarer flüssiger Stoff, n.a.g. (enthält C7-C9 Isoalkane, Titanatetrabutanolat)  
14.2 Proper Shipping Name (national) ....: Flammable liquid, n.o.s (contains C7-C9 Isoalkanes, Titanium tetrabutanolate)  
14.3 Class .....: 3  
14.4 Packaging Group .....: II

**Transport by sea IMDG-Code:**

Valuation .....: Dangerous Goods  
14.1 UN no. ....: 1993  
14.2 Proper Shipping Name .....: Flammable liquid, n.o.s. (contains C7-C9 Isoalkanes, Titanium tetrabutanolate)  
14.3 Class .....: 3  
14.4 Packaging Group .....: II

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

**Air transport ICAO-TI/IATA-DGR:**

Valuation .....: Dangerous Goods  
 14.1 UN no. ....: 1993  
 14.2 Proper Shipping Name .....: Flammable liquid, n.o.s. (contains C7-C9 Isoalkanes, Titanium tetrabutanolate)  
 14.3 Class .....: 3  
 14.4 Packaging Group .....: II

**14.5 Environmental hazards**

Hazardous to the environment: yes  
 Marine Pollutant (IMDG): yes

**14.6 Special precautions for user**

Relevant information in other sections has to be considered.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**

Bulk transport in tankers is not intended.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

**Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances (Seveso III):**

Listed in Directive	Ser. number in list	Qualifying Quantity 1	Qualifying Quantity 2
FLAMMABLE LIQUIDS	P5c	5.000 t	50.000 t
ENVIRONMENTAL HAZARDS	E2	200 t	500 t

**Relevant regulations:**

SI 2002/1689: CHIP Regulations 2002

SI 2002/2677: COSHH Regulations 2002

SI 1999/3242: Management of Health &amp; Safety at Work Regulations 1999

Health &amp; Safety at Work Act 1974

SI 1993/1643: Environmental Protection Act 1993 &amp; Subsidiary Regulations.

Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.

**Other specifications, restrictions and prohibitions:**

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals: Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII): This product contains toluene in an amount of over 0.1 wt.%. Annex XVII, entry 48, of regulation 1907/2006, in its current version, must be taken into account.

**15.2 Chemical safety assessment**

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

**15.3 Details of international registration status**

Relevant information about individual substance inventories, where available, is given below.

Japan.....: **ENCS** (Handbook of Existing and New Chemical Substances):  
This product is listed in, or complies with, the substance inventory.

New Zealand .....: **NZIoC** (New Zealand Inventory of Chemicals):  
This product is listed in, or complies with, the substance inventory. (For a correct interpretation of the New Zealand status, additional information like GHS classification or Group Standard is required.)

Australia .....: **AICS** (Australian Inventory of Chemical Substances):  
This product is listed in, or complies with, the substance inventory.

China .....: **IECSC** (Inventory of Existing Chemical Substances in China):  
This product is listed in, or complies with, the substance inventory.

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

Canada.....	: <b>DSL</b> (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines .....	: <b>PICCS</b> (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA) .....	: <b>TSCA</b> (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan .....	: <b>TCSI</b> (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA) .....	: <b>REACH</b> (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea).....	: <b>AREC</b> (Act on Registration and Evaluation of Chemicals; "K-REACH"): Please approach your regular WACKER contact for more detailed information.

**SECTION 16: Other information****16.1 Material**

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on [www.wacker.com](http://www.wacker.com). WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

**16.2 Further information:**

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

**Safety Data Sheet (1907/2006/EC)**

Material: 60003263

WACKER® PRIMER G 790

Version: 9.13 (GB)

Date of print: 26.08.2020

Date of last alteration: 24.08.2020

## Explanation of the GHS classification code:

- Asp. Tox. 1; H304 .....: Aspiration hazard Category 1; May be fatal if swallowed and enters airways.  
 STOT SE 3; H336 .....: Specific target organ toxicity - single exposure Category 3; May cause drowsiness or dizziness.  
 Flam. Liq. 2; H225 .....: Flammable liquids Category 2; Highly flammable liquid and vapour.  
 Skin Irrit. 2; H315 .....: Skin corrosion/irritation Category 2; Causes skin irritation.  
 Aquatic Chronic 2; H411 .....: Long-term (chronic) aquatic hazard Category 2; Toxic to aquatic life with long lasting effects.  
 .....:  
 STOT SE 3; H336 .....: Specific target organ toxicity - single exposure Category 3; May cause drowsiness or dizziness.  
 STOT SE 3; H335 .....: Specific target organ toxicity - single exposure Category 3; May cause respiratory irritation.  
 Eye Dam. 1; H318 .....: Serious eye damage/eye irritation Category 1; Causes serious eye damage.  
 Flam. Liq. 3; H226 .....: Flammable liquids Category 3; Flammable liquid and vapour.  
 Skin Irrit. 2; H315 .....: Skin corrosion/irritation Category 2; Causes skin irritation.  
 Repr. 2; H361d .....: Reproductive toxicity Category 2; Suspected of damaging the unborn child.  
 STOT RE 2; H373 .....: Specific target organ toxicity - repeated exposure Category 2; May cause damage to organs through prolonged or repeated exposure.  
 STOT SE 3; H336 .....: Specific target organ toxicity - single exposure Category 3; May cause drowsiness or dizziness.  
 Skin Irrit. 2; H315 .....: Skin corrosion/irritation Category 2; Causes skin irritation.  
 Asp. Tox. 1; H304 .....: Aspiration hazard Category 1; May be fatal if swallowed and enters airways.  
 Flam. Liq. 2; H225 .....: Flammable liquids Category 2; Highly flammable liquid and vapour.  
 Flam. Liq. 3; H226 .....: Flammable liquids Category 3; Flammable liquid and vapour.  
 Acute Tox. 4; H332 .....: Acute toxicity Category 4; Harmful if inhaled.  
 Eye Irrit. 2; H319 .....: Serious eye damage/eye irritation Category 2; Causes serious eye irritation.  
 STOT SE 3; H335 .....: Specific target organ toxicity - single exposure Category 3; May cause respiratory irritation.

Classification	Rationale:
Long-term (chronic) aquatic hazard, Category 2	Calculation method
Aspiration hazard, Category 1	Calculation method
Specific target organ toxicity - single exposure, Category 3	Calculation method
Reproductive toxicity, Category 2	Calculation method
Serious eye damage/eye irritation, Category 1	Calculation method
Skin corrosion/irritation, Category 2	Calculation method
Flammable liquids, Category 2	On basis of test data.

**- End of Safety Data Sheet -**