Safety Data Sheet





According to Regulation(EC) No. 1907/2006/EC

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| Product / Trade name: | I-IMAGE-1L-T6 |
|--------------------------------|-----------------------------|
| Synonyms: | Pigment Black ink - Type T6 |
| Proper shipping name: | None |
| Other means of identification: | None |
| Contains: | Ethane-1,2-diol |

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

For Screen Engraving/Film Masking

For Professional/Industrial use only

1.2.2. Uses advised against

Advice against other uses

1.3. Details of the supplier of the safety data sheet

Supplier name: The M&R Companies

Address: 440 Medinah Road, Roselle, IL.

Telephone: 800-736-6431

1.4. Emergency telephone number

Chemtrec:+1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

| Classification | Category | Exposure route |
|----------------|----------|----------------|
| Skin Sens. | 1 | - |
| STOT Rep. Exp. | 2 | Oral |
| Acute Tox. | 4 | - |
| | | |

Other adverse physico-chemical, human health and environmental effects

None

M1000004 Version:2.1

2.2. Label elements

Labeling according to Regulation (EC) No 1272/2008 (CLP)

Hazard pictogram:



Signal word:

Hazard statements:

Warning H302: Harmful if swallowed H317: May cause an allergic skin reaction

H373: May cause damage to organs through prolonged or repeated exposure

May produce an allergic reaction

Precautionary statements:

Prevention: P260: Do no breathe mist/vapors

P280: Wear protective gloves/ protective clothing/ protective eye and face protection

Response:

P302+P350: IF ON SKIN: Wash with plenty of soap and water P333+P313: If skin irritation or rash occurs: Get medical advice /attention

P305+P351+P338 IF IN EYES: Rinse immediately with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice / attention.

Other hazards

No reliable data available.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Mixtures

| Name | CAS No. | EC No. | Index No. | REACH No. | % wt/wt | Classification according to (EC) No1272/2008 (CLP) |
|-----------------|----------|-----------|--------------|-----------------------|---------|--|
| Ethylene Glycol | 107-21-1 | 203-473-3 | 603-027-21-1 | 01-2119456816-28-0128 | <20 | Acute Tox4; H302 STOT Rep. Exp. 2 H373 |

Note: Undisclosed components are not classified or water.

SECTION 4: First aid measures

4.1. Description of first aid measures

General Advise: Remove contaminated clothing.

If Inhaled: Keep patient calm, remove to fresh air, seek medical attention.

M1000004 Version:2.1

I-IMAGE-1L-T6

On Skin contact: Wash thoroughly with soap and water P302+ P352: Wash with plenty of soap and water

On contact with eyes: Remove contact lenses, if present and easy to do. Wash affected eyes for at least 15 minutes under running water with eyelids held open. If eye irritation persists: Get medical advice / attention.

On ingestion: immediately rinse mouth and then drink 200-300 ml of water, seek medical attention P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

4.2. Most important symptoms and effects, both acute and delayed

Inhaled:

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Ingestion:

Ingestion is thought to produce harmful effects (as classified under EC Directives), the material causes damage to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident.

Skin Contact:

Since material may cause sensitization to skin, good hygiene practice requires that exposure be kept to a minim um and that suitable gloves be used in an occupational setting.

Eve:

The material is thought to cause serious eye irritation.

Chronic:

May cause damage to organs through prolonged or repeated exposure: Affected organs: kidney; Route of exposure: Oral

4.3. Indication of any immediate medical attention and special treatment needed

P314: Get medical attention if you feel unwell

SECTION 5: Firefighting measures

5.1. Extinguishing media

There is no restriction on the type of extinguisher which may be used. Use extinguishing media suitable for surrounding area.

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Alert Fire Brigade and tell them location and nature of hazard.

Wear breathing apparatus plus protective gloves.

Prevent, by any means available, spillage from entering drains or water courses.

Use water delivered as a fine spray to control fire and cool adjacent area.

DO NOT approach containers suspected to be hot.

Cool fire exposed containers with water spray from a protected location.

If safe to do so, remove containers from path of fire.

Further information: Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

P281: Use personal protective equipment as required.

6.1.1. For non-emergency personnel

Avoid breathing mist/vapors/spray. Wear protective gloves/ protective clothing/ protective eye and face protection. Wash hands/ area of contact thoroughly after handling. Do not eat, drink, or smoke when using this product. Obtain special instructions before use. Use personal protective equipment as required.

6.1.2. For emergency responders

M1000004 Version:2.1

Wear suitable protective equipments.

Environmental precautions

Take precautions to prevent entry into waterways, sewers, or surface drainage systems. Dispose according to local or international regulations.

Methods and material for containment and cleaning up

P264: Wash hands/ area of contact thoroughly after handling.

Methods for cleaning up or taking up:

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product. Correctly dispose of recovered product immediately

Reference to other sections

Personal Protective Equipment advice is contained in Section 8 and section 13 of the MSDS

SECTION 7: Handling and storage

Precautions for safe handling

Avoid ingestion, inhalation, skin and eye contact. Minimize dust generation and accumulation. Handle in accordance with good industrial hygiene practice and any legal requirements.

P270: Do not eat, drink, or smoke when using this product.

P273: Avoid release to the environment.

Handling: Protection against fire and explosion, Electrical devices must meet the specified temperature class.

Conditions for safe storage, including any incompatibilities

Note: For the best performance of the inks for application it is advisable to store and transport between 10 deg C to 35 deg C

Suitable container: PP/ HDPE/LDPE plastic can or drums. Check all containers are clearly labeled and free from leaks. Keep container tightly closed in the ventilated place. Store in a cool and dry place. Keep away from heat and direct sunlight.

Storage incompatibility: Avoid reaction with incompatible substances. Avoid reaction with oxidizing agents.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

| 8.1. Control parameters Substance Ethylene Glycol | Form Particulate | TWA 10 mg/m³ | STEL | Reference Ls (United Kingdom |
|---|---------------------|------------------------|--------------------|--------------------------------------|
| Ethylene Glycol | Faiticulate | TO HIG/III | E1140/2003 WEI | (UK), 8/2007). Absorbed through skin |
| | Vapour Vapour | 52 mg/m³ 20ppm | 104 mg/m³ 40ppm | Same Same/ ACGIH/ OSHA |
| thylene Glycol Derived effect levels | | | | |

Eth

Long term exposure 35 mg/m³ Workers DNEL skin irritation/corrosion DNFI 106 mg/kg bw/day Workers repeated dose toxicity General Population **DNEL** 7 mg/m³ skin irritation/corrosion 53 mg/kg bw/day **DNEL** General Population repeated dose toxicity

Predicted effect concentrations

| PNEC aqua (freshwater) | 10 mg/L | Assessment Factor |
|-----------------------------------|-----------------------|-----------------------|
| PNEC aqua (marine water) | 1 mg/L | Assessment Factor |
| PNEC aqua (intermittent releases) | 10 mg/L | Assessment Factor |
| PNEC STP | 199.5 mg/L | Assessment Factor |
| PNEC sediment (freshwater) | 37 mg/kg sediment dw | partition coefficient |
| PNEC sediment (marine water) | 3.7 mg/kg sediment dw | partition coefficient |
| PNEC soil | 1.53 mg/kg soil dw | partition coefficient |

M1000004 Version:2.1

8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. W ell-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

General Personal Protection: Safety goggles or face shield, chemical resistant gloves, protective clothing and apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state: | Liquid |
|---|-------------------|
| Colour: | Black |
| Odour: | Very Mild |
| Odour threshold | No data available |
| pH: | 7~9 |
| Melting point / Freezing point: | Not applicable |
| Boiling point: | >100°C |
| Flash point: | >100°C |
| Evapotation rate: | Not established |
| Flammability (solid, gas): | Non flammable |
| Upper/lower flammability: | No data available |
| Explosive limits: | No data available |
| Vapour pressure: | No data available |
| Vapour density | No data available |
| Density g/cm3: | 1.12 |
| Water Solubility(ies): | Soluble |
| Partition coefficient: n-octanol/water: | No data available |
| Auto-ignition temperature: | Not applicable |
| Viscosity: | 3-12cPs |
| Explosive properties: | Not explosive |
| Oxidising properties: | Not oxidising |
| | <u> </u> |

9.2. Other information

No additional data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal storage conditions. May react with strong oxidizing agents and incompatible materials.

10.2. Chemical stability

Product is considered stable during storage and transportation under normal condition.

10.3. Possibility of hazardous reactions

Stable under normal conditions. Hazardous reactions may occur if contact with incompatible material.

10.4. Conditions to avoid

Heat and direct sunlight, high temperature, ignition sources (sparks, flames, static), incompatible materials.

M1000004 Version:2.1

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Thermal decomposition products: may emit toxic fumes. Oxides of carbon, sulphur, nitrogen, zinc and phosphorus.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

(a) Acute Oral Toxicity

Data not available for the mixture.

Component wise data

1. Ethylene glycol

LD50= 7712 mg/kg bw 7d Rat

Clinical signs

Depression, narcosis.

Gross pathology

Animals that died: kidney damage

(b) Acute Dermal Toxicity

No Data available for the mixture.

Component wise data

Ethylene glycol

LD50 > 3500 mg/kg bw Mouse

(c) Acute Inhalation Toxicity

No Data available for the mixture.

Component wise data

Ethylene glycol

LC50 > 2.5 mg/L air 6h Rat

(d) Irritant/Corrrosive

No Data available for the mixture.

Component wise data

Ethylene glycol

Not irritating

(e) Sensitising

No Data available for the mixture.

Component wise data

Ethylene glycol

Not sensitising

(f) Genetic toxicity

No Data available for the mixture.

Component wise data

Ethylene glycol

In Vitro- Negative

In Vivo- Negative

M1000004 Version:2.1

I-IMAGE-1L-T6

(g) Carcigenocity

No Data available for the mixture.

Component wise data

Ethylene glycol

The results of this study suggest that ingestion of EG at a dosage of 1000 mg/kg diet may have accelerated the appearance of lymphosarcomas in female mice. However, the incidence was equivocal. There was no evidence of an increase in any other tumor type.

(h) STOT- Repeated exposures

No data available for mixtures

Component wise data

Ethylene glycol

Oral- Increased mortality appeared in male animals receiving 1 and 4% in the diet but the mortality data for females were difficult to interpret. Calcification of the kidneys and oxalate-containing calculi were observed in males on the 0.5, 1 and 4% diets. Females receiving diets containing 1 and 4% showed calcification but oxalate-containing calculi were detectable only in the females on the 4% diet. One female rat in the group receiving 0.1% ethylene glycol developed a large magnesium phosphate stone which contained no demonstrable amount of oxalate. There was an increased water consumption and appearance of protein in the urine of males receiving the 1 and 4% diets and females on the 4% diet.

Dermal- No testicular damage that was definitely induced by the test substance was detected in any of the male dogs investigated.

LD50 dermal (dog): > 4000 mg/kg bw

(i) Reproductive Toxicity

No Data available for the mixture.

Component wise data

Ethylene glycol

Exposure to ethylene glycol resulted in a small but significant decrease in the number of litters per breeding pair, in the number of live pups per pair and in the live pup weight. A significant number of pups in the 1.0% dose group were born with distinct facial deformities. In the retained litters at this dose, the facial deformities were more obvious with age. These malformed animals also exhibited fused ribs and shortened nasal, parietal, and/or frontal bones of the skull. When pups from the high dose group were raised to adulthood (with continued exposure to ethylene glycol) and mated, they exhibited decreased mating and fertility indices relative to controls handled in the same manner, but there were no effects on litter size, pup weight or sex ratio. The authors deemed ethylene glycol a "weak reproductive toxicant, but a potential teratogen.

(j) Aspiration hazard: not tested

No Data available for the mixture.

Component wise data

Ethylene glycol

No data available

Other information: None

SECTION 12: Ecological information

12.1. Toxicity

No data available for the mixture.

Component wise data

Ethylene glycol

Short term fish

LC50 = 72860 mg/ 96 h

Pimephales promelas

Long term fish

Safety Data Sheet

I-IMAGE-1L-T6

M1000004 According to Regulation(EC) No. 1907/2006/EC Version:2.1

NOEC = 32000 mg/L 7 d Pimephales promelas

Toxicity to aquatic algae and cyanobacteria

other: TGK= > 10000 mg/L Scenedesmus quadricauda

Persistence and degradability

Abiotic Degradation: No data available for mixture

Physical- and photo-chemical elimination: No data available for mixture

Biodegradation: no data available.

Component wise data

Ethylene glycol

Readily biodegradable

Bioaccumulative potential

Bioconcentration factor (BCF): No data available for mixture

Component wise data

. Ethylene glycol

No data available

Mobility in soil

Distribution to environmental compartments: No data available for mixture

Adsorption/ Desorption: No data available for mixture

Component wise data

Ethylene glycol

log Koc= 0

Results of PBT and vPvB assessment 12.5.

No data available for this mixture

Component wise data

Ethylene glycol

This substance is not PBT / vPvB

Other adverse effects

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product disposal: refer to specific national regulation. Do not discharge into sewer or waterways. Contaminated packaging: contaminated, empty containers must be disposed of as chemical waste.

Where possible, arrange for product to be recycled. Dispose of via an authorized person/licensed waste disposal contractor in accordance with local regulations.

European waste catalogue (EWC) Hazardous waste Yes.

Waste code Waste designation.

08 03 03 Waste from water-based ink 15 01 02 Plastic packaging (packaging)

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging Material:

13/07/2015 EN (English) 8/11

Safety Data Sheet

I-IMAGE-1L-T6

M1000004 Version:2.1

Disposal: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container. Packed in HDPE bottles.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

SECTION 14: Transport information

Note: For the best performance of the inks for application it is advisable to store and transport between 10 deg C to 35 deg C.

Land transport (ADR / RID / GGVSE)

According to Regulation(EC) No. 1907/2006/EC

| | , | | | |
|---------------------------------|---------------------|-----------------------------------|--------------------------------|-------------------|
| 14.1 UN number | Not applicable | 14.4 Packing group | Not applicable | |
| 14.2 UN proper shipping name | Not dangerous goods | 14.5 Environmental hazard | No relevant data | |
| 14.3 Transport hazard class(es) | Not applicable | 14.6 Special precautions for user | Hazard identification (Kemler) | Not applicable |

Air transport (ICAO-IATA / DGR)

| 14.1 UN number | Not applicable | 14.4 Packing group | Not applicable |
|---------------------------------|----------------|-----------------------------------|-------------------|
| 14.2 UN proper shipping name | Not applicable | 14.5 Environmental hazard | No relevant data |
| 14.3 Transport hazard class(es) | Not applicable | 14.6 Special precautions for user | No data available |

Inland waterways transport (ADNR / River Rhine)

| 14.1 UN number | None | |
|-----------------------------------|----------------|------|
| 14.2 UN proper shipping nam e | None | |
| 14.3 Transport hazard class(es) | None | |
| 14.4 Packing group | None | |
| 14.5 Environment al hazards | None | |
| 14.6 Special precautions for user | Classification | None |
| · | code | None |
| | Equipment | None |
| | Fire cones | None |

Sea Transport (IMDG code-GGVSee)

| 14.1 UN number | None | 14.4 Packing group | None | |
|---------------------------------|------|------------------------------|-----------------|-------|
| 14.2 UN proper shipping name | None | 14.5 Environmental hazard | None | |
| Hame | | 14.6 Special precautions for | EMS Number | None |
| 14.3 Transport hazard class(es) | None | user | LIVIO INUITIDEI | NOTIC |

14.7. Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Not applicable

I-IMAGE-1L-T6 M1000004 Version:2.1

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer not regulated Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

Not regulated

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

Not regulated

Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC Regulation (EC) No 689/2008 concerning the export and import of dangerous chemicals

Not regulated

Substances of very high concern (SVHC)

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of ≥ 0.1 % (w/w).

Directive 2000/39/EC - indicative occupational exposure limit values

Ethylene glycol

15.2. Chemical safety assessment

CSA has been performed on Ethylene Glycol

SECTION 16: Other information

16.1 Key literature references and sources for data

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Category | Method of classifications |
|----------|---------------------------|
| 1 | Bridging Principle |
| 2 | Bridging Principle |
| 4 | Bridging Principle |
| | |
| | 1 2 |

LEGEND

ACGIH = American Conference of Governmental Industrial Hygienists

DNEL= Derived No-Effect Level

EC= European Commission

LC= Lethal Concentration

OSHA = Occupational Safety and Health Administration (U.S.A.)

PBT= Persistant bioaccumalative toxic

PNEC= Predicted No Effect Concentration

REACH= Registration, Evaluation, Authorisation and Restriction of Chemicals

STEL = Short Term Exposure Limit

STOT= SPECIFIC TARGET ORGAN SYSTEMIC

TWA = Time-weighted Average

UN= United Nation

vPVB = very persistant very Bioaccumalative

WEL= Workplace Exposure Limits

SOURCE

- REACH registered chemicals, http://echa.europa.eu/chem_data_en.asp
- CLP details, http://echa.europa.eu/clp-2015
- Toxnet, http://toxnet.nlm.nih.gov

13/07/2015 EN (English) 10/11

M1000004 Version:2.1

16.2 List of relevant hazard statements and risk phrases

Hazard statements: H302: Harmful if swallowed

H317: May cause an allergic skin reaction

H373: May cause damage to organs through prolonged or repeated exposure

May produce an allergic reaction

Precautionary statements:

P201: Obtain special instructions before use.

P260: Do not breathe mist/vapors

P264: Wash hands/ area of contact thoroughly after handling. P270: Do not eat, drink, or smoke when using this product.

P273: Avoid release to the environment.

P280: Wear protective gloves/ protective clothing/ protective eye and face protection

P281: Use personal protective equipment as required

P302+P350: IF ON SKIN: Wash with plenty of soap and water
P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse immediately with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice / attention.

P302+ P352: Wash with plenty of soap and water

P333+P313: If skin irritation or rash occurs: Get medical advice /attention

P314: Get medical attention if you feel unwell.

P405: Store locked up.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

16.3 Other

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EUCEN Standards:

EN 16 Personal eye – protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro - organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices.

16.4 HMIS RATINGS.

Health **Flammability** Reactivity : 0 **Personal Protection** : B

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.