

acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name Bug Off
OPA Ref# BUG0FF

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses cleaner/degreaser

### 1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States

Telephone: 1.800.875.6320, 1.303.289.6320 Telefax e-mail: info@bbblending.com

Website: bbblending.com

Competent person responsible for the SDS

Robert Blahnik

e-mail (competent person) bblahnik@bbblending.com

1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500

24 hour emergency telephone number.

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Annex	<ul> <li>Hazard class and category</li> </ul>	-	Hazard s	tatement code(s)	
B.16	corrosive to metals		Cat. 1	(Met. Corr. 1)	H290
A.2 skin corrosion/irritation			Cat. 2	(Skin Irrit. 2)	H315
A.3	serious eye damage/eye irritation		Cat. 1	(Eye Dam. 1)	H318

### Remarks

For full text of H-phrases: see SECTION 16.

### Hazards not otherwise classified

Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).

### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word danger



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

### **Pictograms**

GHS05



### **Hazard statements**

H290 May be corrosive to metals.
H315 Causes skin irritation.
H318 Causes serious eye damage.

# **Precautionary statements**

### Precautionary statements - prevention

Keep only in original container.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

# **Precautionary statements - response**

IF ON SKIN: Wash with plenty of water.

IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Take off contaminated clothing.

Absorb spillage to prevent material damage.

### Hazardous ingredients for labelling

Alcohols, C9-11 ethoxylated, sodium hydroxide

### 2.3 Other hazards

There is no additional information.

# **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

not relevant (mixture)

### 3.2 Mixtures

# Description of the mixture

Name of substance	Identifier	Wt%	Hazard class and cat- egory	Hazard statement	Pictograms
Alcohols, C9-11 ethoxylated	CAS No 68439-46-3	1 - < 5	A.3 Eye Dam. 1	H318	L. C.
sodium hydroxide	CAS No 1310-73-2	1 - < 5	B.16 Met. Corr. 1 A.2 Skin Corr. 1A A.3 Eye Dam. 1	H290 H314 H318	K N



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

Name of substance	Identifier	Wt%	Hazard	class and cat- egory	Hazard statement	Pictograms
ethylene glycol monobutyl ether	CAS No 111-76-2	1 - < 5	B.6 A.10 A.1D A.1I A.2 A.3	Flam. Liq. 4 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2A	H227 H302 H312 H332 H315 H319	<u>•</u>

For full text of abbreviations: see SECTION 16.

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

#### **General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

### Following inhalation

In case of respiratory tract irritation, consult a physician. Provide fresh air.

### Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

### Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

### **Following ingestion**

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

### Suitable extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO2)

### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Corrosive to metals.



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

### **Hazardous combustion products**

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

# **SECTION** 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

### For non-emergency personnel

Remove persons to safety.

### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

### 6.3 Methods and material for containment and cleaning up

#### Advices on how to contain a spill

Covering of drains.

### Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

### Appropriate containment techniques

Use of adsorbent materials.

### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

#### Recommendations

### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

### Handling of incompatible substances or mixtures

Do not mix with acids.

### Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

#### • Corrosive conditions

Store in corrosive resistant container with a resistant inner liner.

### Incompatible substances or mixtures

Observe compatible storage of chemicals.

#### Control of the effects

### Protect against external exposure, such as

frost

#### Consideration of other advice

#### Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

### **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

#### National limit values

### Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Source
US	2-butoxyethanol	111-76-2	PEL	50	240			29 CFR OSHA

#### Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified.

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average.



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

#### Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

### 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### **Individual protection measures (personal protective equipment)**

# Eye/face protection

Wear eye/face protection.

### Skin protection

### · hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### **Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state liquid
Color different

Odor characteristic

# Other physical and chemical parameters

pH (value) 13 at 25 °C (base)

Melting point/freezing point not determined

Initial boiling point and boiling range 100 °C

Flash point >100 °C at 1,013 hPa (closed cup)

Evaporation rate not determined
Flammability (solid, gas) not relevant (fluid)
Explosive limits not determined

Vapor pressure 31.69 hPa at 25 °C



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

Density not determined

Relative density Information on this property is not available.

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

n-octanol/water (log KOW)

This information is not available.

Auto-ignition temperature 230 °C

Viscosity not determined

Explosive properties none
Oxidizing properties none

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". corrosive to metals

### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

# Physical stresses which might result in a hazardous situation and have to be avoided

strong shocks

### 10.5 Incompatible materials

There is no additional information.

### Release of flammable materials with

light metals (due to the release of hydrogen in an acid/alkaline medium)

### Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

### **Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

# Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

### Acute toxicity

Shall not be classified as acutely toxic.

### Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
ethylene glycol monobutyl ether	111-76-2	oral	1,746
ethylene glycol monobutyl ether	111-76-2	dermal	1,100
ethylene glycol monobutyl ether	111-76-2	inhalation: vapor	11

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

### Carcinogenicity

• National Toxicology Program (United States):

none of the ingredients are listed

### Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

#### **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

# **SECTION 12: Ecological information**

# 12.1 Toxicity

# Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

# Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Alcohols, C9-11 ethoxylated	68439-46-3	LC50	7 <sup>mg</sup> / <sub>l</sub>	fish	96 hours
Alcohols, C9-11 ethoxylated	68439-46-3	EC50	2.5 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 hours
sodium hydroxide	1310-73-2	EC50	40.4 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 hours
ethylene glycol monobutyl ether	111-76-2	LC50	1,474 <sup>mg</sup> / <sub>l</sub>	fish	96 hours
ethylene glycol monobutyl ether	111-76-2	EC50	1,550 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 hours
ethylene glycol monobutyl ether	111-76-2	ErC50	1,840 <sup>mg</sup> / <sub>l</sub>	algae	72 hours

# Aquatic toxicity (chronic)

### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethylene glycol monobutyl ether	111-76-2	EC50	297 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	21 d

# 12.2 Process of degradability

Data are not available.

# Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
ethylene glycol monobutyl ether	111-76-2	carbon dioxide generation	18.3 %	3 d

# 12.3 Bioaccumulative potential

Data are not available.



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Alcohols, C9-11 ethoxylated	68439-46-3		3.75	
ethylene glycol monobutyl ether	111-76-2		0.81	

# 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

Data are not available.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

### Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

1760

### 13.3 Remarks

UN number

14.1

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

# **SECTION 14: Transport information**

14.2	UN proper shipping name	CORROSIVE LIQUID, N.O.S.
	Hazardous constituents	sodium hydroxide
14.3	Transport hazard class(es)	
	Class	8 (corrosive substances)
14.4	Packing group	III (substance presenting low danger)
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the danger- ous goods regulations)

# B&B BLENDING

# **Safety Data Sheet**

acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

# • Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number 1760

Proper shipping name Corrosive liquid, n.o.s.

Class 8
Packing group III
Danger label(s) 8



Special provisions (SP) IB3, T7, TP1, TP28

ERG No 154

### • International Maritime Dangerous Goods Code (IMDG)

UN number 1760

Proper shipping name CORROSIVE LIQUID, N.O.S.

Class 8
Subsidiary risk(s) Packing group III
Danger label(s) 8



Special provisions (SP) 223, 274

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L

EmS F-A, S-B

Stowage category B

Clear of living quarters

III

### • International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1760

Proper shipping name Corrosive liquid, n.o.s.

Class 8

Packing group



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

8

Danger label(s)

Special provisions (SP) A3

Excepted quantities (EQ) E1

Limited quantities (LQ) 1 L

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Industry or sector specific available guidance(s)

• NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

Category	Rating	Description
Chronic	/	None.
Health	3	Major injury likely unless prompt action is taken and medical treatment is given.
Flammability	1	Materials that must be preheated before ignition can occur.
Physical hazard	0	Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.
Personal protective equipment	-	

### • NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States) - National Fire Protection Association (United States)

Category	Degree of hazard	Description		
Flammability	1	Materials that must be preheated before ignition can occur.		
Health	3	Materials that, under emergency conditions, can cause serious or permanent injury.		
Instability	0	Materials that are normally stable, even under fire conditions.		
Special hazard				



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

# Relevant European Union (EU) safety, health and environmental provisions

# Classification according to GHS (1272/2008/EC, CLP)

Corrosive to metals

Cat. 1 (Met. Corr. 1)

Skin corrosion/irritation

Cat. 2 (Skin Irrit. 2)

Serious eye damage/eye irritation

Cat. 1 (Eye Dam. 1)

Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).

# **SECTION 16: Other information**

# 16.2 Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	acute toxicity
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	BioConcentration Factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant)
Met. Corr.	corrosive to metals



acc. to OSHA, Appendix D to § 1910.1200

# **Bug Off**

Version number: GHS 1.0 Date of compilation: 2015-03-30

Abbr.	Descriptions of used abbreviations
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)
NPCA-HMIS®	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts per million
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
vPvB	very Persistent and very Bioaccumulative

### 16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200
- 49 CFR § 172.101 Hazardous Materials Table (DOT)

### 16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### 16.5

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H227	combustible liquid
H290	may be corrosive to metals
H302	harmful if swallowed
H312	harmful in contact with skin
H314	causes severe skin burns and eye damage
H315	causes skin irritation
H318	causes serious eye damage
H319	causes serious eye irritation
H332	harmful if inhaled

### 16.7 Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.