

# SAFETY DATA SHEET

## SikaTop® Armatec®-110 EpoCem® (A)



Version 1.0

SDS Number: 000000022459

Revision Date: 08.11.2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaTop® Armatec®-110 EpoCem® (A)  
Product code : 000000022459  
Type of product : liquid

#### Recommended use of the chemical and restrictions on use

Product use : Concrete protection

#### Manufacturer or supplier's details


Company : SIKA (SINGAPORE) PTE LTD.  
66A Sungei Kadut Street 1  
Singapore 729368  
Telephone : +65 63680883  
Telefax : +65 6779 6200  
E-mail address : -  
Emergency telephone number : +65 63680883

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 2  
Skin sensitisation : Category 1  
Long-term (chronic) aquatic hazard : Category 2

#### GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.

# SAFETY DATA SHEET

## SikaTop® Armatec®-110 EpoCem® (A)



Version 1.0

SDS Number: 000000022459

Revision Date: 08.11.2018

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	25068-38-6	$\geq$ 30 - < 50
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700)	9003-36-5	$\geq$ 10 - < 20
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	$\geq$ 1 - < 10

### 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

# SAFETY DATA SHEET

## SikaTop® Armatec®-110 EpoCem® (A)



Version 1.0

SDS Number: 000000022459

Revision Date: 08.11.2018

- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitising effects  
Allergic reactions  
Excessive lachrymation  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.
- Notes to physician : Treat symptomatically.

---

### 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### 7. HANDLING AND STORAGE

# SAFETY DATA SHEET

## SikaTop® Armatec®-110 EpoCem® (A)



Version 1.0

SDS Number: 000000022459

Revision Date: 08.11.2018

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with local regulations.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

## SikaTop® Armatec®-110 EpoCem® (A)



Version 1.0

SDS Number: 000000022459

Revision Date: 08.11.2018

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: white
Odour	: very faint
Odour Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 23 hPa (17 mmHg)
Relative vapour density	: No data available
Density	: 1 g/cm <sup>3</sup> (20 °C (68 °F) ( ))
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 7 mm <sup>2</sup> /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

# SAFETY DATA SHEET

## SikaTop® Armatec®-110 EpoCem® (A)



Version 1.0

SDS Number: 000000022459

Revision Date: 08.11.2018

---

### 10. STABILITY AND REACTIVITY

- Reactivity : No dangerous reaction known under conditions of normal use.
- Chemical stability : The product is chemically stable.
- Possibility of hazardous reactions : Stable under recommended storage conditions.
- Conditions to avoid : No data available
- Incompatible materials : No data available
- No decomposition if stored and applied as directed.

---

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

# SAFETY DATA SHEET

## SikaTop® Armatec®-110 EpoCem® (A)



Version 1.0

SDS Number: 000000022459

Revision Date: 08.11.2018

---

### 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
Exposure time: 48 h

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

##### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

### 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

### 14. TRANSPORT INFORMATION

#### International Regulations

##### **UNRTDG**

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(epoxy resin)  
Class : 9

# SAFETY DATA SHEET

## SikaTop® Armatec®-110 EpoCem® (A)



Version 1.0

SDS Number: 000000022459

Revision Date: 08.11.2018

Packing group : III  
Labels : 9

### IATA-DGR

UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : Miscellaneous Dangerous Goods  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

### IMDG-Code

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

### Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and : Not applicable  
Environmental Protection and Management (Hazardous Substances) Regulations

---

## 16. OTHER INFORMATION

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.