



The First in Synthetics®

U.S. WHOLESALE PRICE LIST

CONFIDENTIAL

EFFECTIVE JULY 1, 2011



CONTENTS

ORDERING INFORMATION	2	EA® OIL FILTERS	20
MOTOR OILS	3	EA® MOTORCYCLE FILTERS	21
FORMULA 4-STROKE® OILS	6	BY-PASS FILTRATION UNITS	22
ADVANCED SYNTHETIC MOTORCYCLE OILS ...	6	BY-PASS REPLACEMENT PARTS	23
SUSPENSION FLUIDS	7	OIL ANALYSIS	23
DIESEL OILS	8	FUEL ADDITIVES	24
GEAR LUBES	9	CLEANERS & PROTECTANTS	25
TRANSMISSION FLUIDS	11	COOLANT	26
TWO-CYCLE OILS	13	HYDRAULIC FLUIDS	26
GREASES	14	MISCELLANEOUS PRODUCTS	27
HYDRAULIC OILS	16	AFTERMARKET PARTNERS INFORMATION	28
COMPRESSOR OILS	17	ADDITIONAL ORDERING INFORMATION	29
EA® AIR FILTERS	18		

– PRICES AND AVAILABILITY SUBJECT TO CHANGE WITHOUT NOTICE –

Errors will be corrected where discovered and AMSOIL reserves the right to revoke any offer or price inadvertently published due to error or omission.

Ordering Information

Ordering Instructions

Place orders for AMSOIL products by calling the orders-only 800-number (800-777-7094), by fax (715-392-5225) or online (www.amsoil.com).

Phone: (800) 777-7094

Open Monday - Friday, 7 a.m. to 5 p.m. Central Time

When calling in your order, tell the AMSOIL Telephone Ordering Operator whether you will pick up your order or have it shipped to you.

Fax: (715) 392-5225

Faxes accepted 24 hours a day, 7 days a week

Online Store: www.amsoil.com

Login to your appropriate Account Zone by entering your account number and password. If you have not set up a password, click on the "First Time Logging In" link, enter your account number and email address and click "Submit." A link will be emailed to you that allows you to set a password. Once inside your Account Zone, you can choose to use the Orders link, which takes you to the EZ Online Order Forms, or you can click the Online Store link to browse through AMSOIL products.

Choosing Your AMSOIL Products

AMSOIL Online Application Guides and MyAMSOILGarage™

The AMSOIL Online Product Application Guides are the fastest way to determine which AMSOIL lubricants, filters and accessories apply to your automotive, heavy-duty or powersports equipment. Just click the link to the appropriate application guide on the right-hand side of the AMSOIL home page and enter the information for your application in the fields provided. You can also use the MyAMSOILGarage™ feature to store vehicle information for future purchases, set email reminders and more. Visit www.amsoil.com for details.

AMSOIL Technical Services

The AMSOIL Technical Services Department is available to assist in the selection and application of AMSOIL products. To assist the processing of your inquiry, please have your specific application information ready to relay to the Technical Services staff, and be prepared to answer questions regarding your application needs. Call AMSOIL Technical Services at (715) 399-TECH and follow the prompts.

Alaska Freight Surcharge

For purchases made from the AMSOIL Distribution Center in Alaska, add 7.5% to the total cost for extra freight expenses from the contiguous U.S. to Alaska. Alaskan orders for Superior-only items are charged actual freight.

Hawaii Ordering Information

Hawaiian orders are shipped from the Portland, Ore. or Superior, Wis. Distribution Centers using the best possible method and are charged actual freight. Most orders are shipped using United States Postal Service (USPS) Priority Flat Rate Boxes. The USPS will not accept AMSOIL fuel additives, aerosol containers or any product marked with "†" in this price list. Contact the Portland, Ore. Distribution Center at (503) 620-5213 to arrange surface transportation for large orders and orders with restricted items.

AMSOIL Product Lookup By Code

Code	Page	Code	Page
ABC	14	EAPF	19
ACB	25	EAPF	20
ACD	9	FGO	10
ACF	24	FGR	10
ADA	11	FLSH	26
ADF	24	FOG	25
AEL	5	GLA	15
AFF	6	GLB	15
AFL	5	GLC	15
AGL	10	GLCSC	15
AGM	11	GPOR1	15
AHR	5	GPOR2	14
AIT	13	GPTR1	15
AME	9	GPTR2	15
AMH	25	GRG	14
AMO	4	GSF	16
AMP	25	GVC	16
AMW	26	GWR	16
ANGS	7	GXC	16
ANGV	8	HDD	8
ANT	26	HPI	13
AOB	25	MCF	7
APF	26	MCS	7
API	24	MCT	6
AQS	24	MCV	7
ARO	4	MTF	12
ART	12	MTG	12
ASE	6	OAI	23
ASL	3	OED	8
ASM	3	OEF	4
ASO	6	OEM	4
AST	24	OET	4
ATD	12	PCH	17
ATF	11	PCI	17
ATH	16	PCJ	17
ATL	11	PCK	17
ATM	3	PCL	17
ATO	14	PCO	9
ATP	14	PSF	27
AWF	16	RD20	5
AWG	17	RD30	5
AWH	17	RD50	5
AWI	17	RDCB	26
AWJ	17	SDF88	21
AZO	3	SEI	17
BF3	26	SMF	21
BF4	26	SRN	10
BHO	17	SRT	10
BMK	22	STL	7
BRK	5	STM	7
CTG	13	SVG	9
CTJ	13	SVO	9
CTL	13	SVT	9
DEO	8	TCC	14
DFC	24	TDR	13
DME	8	WCF	6
DRC	25	WCT	6
EAA	18	XLF	3
EAAR	19	XLM	3
EAAU	19	XLO	4
EABP	23	XLT	3
EAO	20	ZRF	4
EAOM	21	ZRT	4

ORDERING INFORMATION

Worldwide Performance Specifications:

- API SN (Resource Conserving), SM...
- ILSAC GF-5, 4. . .
- ACEA A5/B5, A1/B1
- GM dexos1 (0W/5W-30 only)



Signature Series 100% Synthetic Motor Oil

The top tier of AMSOIL synthetic motor oil. Delivers extraordinary lubrication in all types of automotive gasoline engines. Combines industry-premier synthetic technology with AMSOIL premium additives and exceeds the higher performance demands of modern engines. Withstands the stress of higher horsepower, higher heat and complicated emissions control systems. Signature Series Synthetic Motor Oil is engineered to outperform competitive conventional and synthetic motor oils and deliver long-lasting performance and protection throughout drain intervals of up to 25,000 miles/one year.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 0W-20 100% Synthetic Motor Oil						
ASMQT	-FA	1 Quart	2.1	8.15	--	10.55
ASMQT	-CA	12 Quarts	25.2	92.85	7.74	125.35
ASM1G	-FA	1 Gallon	7.9	31.90	--	41.40
ASM1G	-CA	4 Gallons	31.6	121.40	30.35	163.90
ASM30	-FA	30-Gallon Drum*	241.0	843.00	--	1,053.75
ASM55	-FA	55-Gallon Drum*	432.0	1,496.00	--	1,840.10
SAE 0W-30 100% Synthetic Motor Oil						
AZQQT	-FA	1 Quart	2.1	8.15	--	10.55
AZQQT	-CA	12 Quarts	25.2	92.85	7.74	125.35
AZO1G	-FA	1 Gallon	7.9	31.90	--	41.40
AZO1G	-CA	4 Gallons	31.6	121.40	30.35	163.90
AZO30	-FA	30-Gallon Drum*	243.0	843.00	--	1,053.75
AZO55	-FA	55-Gallon Drum*	435.8	1,496.00	--	1,840.10
AZO27	-FA	275-Gallon Tote*	2,091.0	7,452.50	--	9,166.60
SAE 5W-30 100% Synthetic Motor Oil						
ASLQT	-FA	1 Quart	2.0	7.85	--	10.15
ASLQT	-CA	12 Quarts	24.0	89.25	7.44	120.50
ASL1G	-FA	1 Gallon	7.6	30.65	--	39.80
ASL1G	-CA	4 Gallons	30.4	116.60	29.15	157.45
ASL30	-FA	30-Gallon Drum*	245.3	807.00	--	1,008.75
ASL55	-FA	55-Gallon Drum*	440.0	1,430.00	--	1,758.90
ASL27	-FA	275-Gallon Tote*	2,125.0	7,122.50	--	8,760.70
SAE 10W-30 100% Synthetic Motor Oil						
ATMQT	-FA	1 Quart	2.1	7.85	--	10.15
ATMQT	-CA	12 Quarts	25.2	89.25	7.44	120.50
ATM1G	-FA	1 Gallon	7.9	30.65	--	39.80
ATM1G	-CA	4 Gallons	31.6	116.60	29.15	157.45
ATM30	-FA	30-Gallon Drum*	242.3	807.00	--	1,008.75
ATM55	-FA	55-Gallon Drum*	434.5	1,430.00	--	1,758.90
ATM27	-FA	275-Gallon Tote*	2,102.0	7,122.50	--	8,760.70

XL Synthetic Motor Oil

AMSOIL Extended Life Synthetic Motor Oil delivers exceptional protection for up to 10,000-mile/6-month oil change intervals, or longer when recommended in owners' manuals or indicated by oil life monitoring systems. It provides peace of mind for owners of modern vehicles where drain intervals exceed conventional oil recommendations of 3,000 miles.

Worldwide Performance Specifications:

- API SN, SM . . .
- ILSAC GF-5, 4 . . .
- ACEA A1/B1
- GM dexos1 (5W-30 only)



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 5W-20 XL Synthetic Motor Oil						
XLMQT	-FA	1 Quart	2.0	5.85	--	7.65
XLMQT	-CA	12 Quarts	24.0	66.75	5.56	90.15
XLM1G	-FA	1 Gallon	7.8	22.75	--	29.65
XLM1G	-CA	4 Gallons	31.2	86.60	21.65	116.95
XLM30	-FA	30-Gallon Drum*	241.1	582.00	--	727.50
XLM55	-FA	55-Gallon Drum*	432.6	1,017.50	--	1,251.55
XLM27	-FA	275-Gallon Tote*	2,062.0	5,060.00	--	6,223.80
SAE 5W-30 XL Synthetic Motor Oil						
XLFQT	-FA	1 Quart	2.0	5.85	--	7.65
XLFQT	-CA	12 Quarts	24.0	66.75	5.56	90.15
XLF1G	-FA	1 Gallon	7.8	22.75	--	29.65
XLF1G	-CA	4 Gallons	31.2	86.60	21.65	116.95
XLF30	-FA	30-Gallon Drum*	241.0	582.00	--	727.50
XLF55	-FA	55-Gallon Drum*	432.1	1,017.50	--	1,251.55
XLF27	-FA	275-Gallon Tote*	2,080.0	5,060.00	--	6,223.80
SAE 10W-30 XL Synthetic Motor Oil						
XLTQT	-FA	1 Quart	2.1	5.85	--	7.65
XLTQT	-CA	12 Quarts	25.2	66.75	5.56	90.15
XLT1G	-FA	1 Gallon	7.8	22.75	--	29.65
XLT1G	-CA	4 Gallons	31.2	86.60	21.65	116.95
XLT30	-FA	30-Gallon Drum*	241.1	582.00	--	727.50
XLT55	-FA	55-Gallon Drum*	432.4	1,017.50	--	1,251.55
XLT27	-FA	275-Gallon Tote*	2,088.0	5,060.00	--	6,223.80

SIGNATURE SERIES 100% SYNTHETIC MOTOR OIL

XL MOTOR OIL



SAE 10W-40 XL Synthetic Motor Oil

XLOQT	-FA	1 Quart	2.0	5.85	--	7.65
XLOQT	-CA	12 Quarts	24.0	66.75	5.56	90.15
XLO30	-FA	30-Gallon Drum*	239.0	582.00	--	727.50
XLO55	-FA	55-Gallon Drum*	429.0	1,017.50	--	1,251.55
XLO27	-FA	275-Gallon Tote*	2,073.0	5,060.00	--	6,223.80

OE Synthetic Motor Oil

Offers the protection and performance benefits of a high-quality synthetic, including better wear control, improved high- and low-temperature performance and increased fuel economy. Friendly toward modern emissions control systems. Resists sludge and carbon deposits. Recommended for the entire length of original equipment manufacturer (OEM) drain intervals.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 5W-20 OE Synthetic Motor Oil						
OEMQT	-FA	1 Quart	2.0	4.70	--	6.10
OEMQT	-CA	12 Quarts	24.0	53.28	4.44	71.95
OEM30	-FA	30-Gallon Drum*	240.0	493.80	--	617.25
OEM55	-FA	55-Gallon Drum*	430.0	855.80	--	1,052.65
OEM27	-FA	275-Gallon Tote*	2,073.0	4,251.50	--	5,229.35

SAE 5W-30 OE Synthetic Motor Oil

OEFTQ	-FA	1 Quart	2.0	4.70	--	6.10
OEFTQ	-CA	12 Quarts	24.0	53.28	4.44	71.95
OE30	-FA	30-Gallon Drum*	240.0	493.80	--	617.25
OE55	-FA	55-Gallon Drum*	430.0	855.80	--	1,052.65
OE27	-FA	275-Gallon Tote*	2,074.0	4,251.50	--	5,229.35

SAE 10W-30 OE Synthetic Motor Oil

OETQT	-FA	1 Quart	2.0	4.70	--	6.10
OETQT	-CA	12 Quarts	24.0	53.28	4.44	71.95
OET30	-FA	30-Gallon Drum*	241.0	493.80	--	617.25
OET55	-FA	55-Gallon Drum*	432.0	855.80	--	1,052.65
OET27	-FA	275-Gallon Tote*	2,083.0	4,251.50	--	5,229.35

Premium Protection Synthetic Motor Oil

Formulated for use in gasoline engines and on- and off-road diesel applications not equipped with diesel particulate filters (DPFs). Offers multi-functionality and excellent wear protection. Ideal for applications where the extra protection of a high-zinc formula is desired. Excellent for flat-tappet, high-performance, heavy-duty and high-mileage applications.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
-----------	-----------------	----------	---------------	---------------------	---------------	------------------------

SAE 10W-40 Premium Protection Synthetic Motor Oil

AMQQT	-FA	1 Quart	2.1	7.75	--	10.10
AMQQT	-CA	12 Quarts	25.2	88.50	7.38	119.50
AMQ1G	-FA	1 Gallon	8.0	30.35	--	39.45
AMQ1G	-CA	4 Gallons	32.0	115.60	28.90	156.10
AMQTP	-FA	(1) 2.5-Gal. Bottle	19.5	74.85	--	95.80
AMQTP	-CA	(2) 2.5-Gal. Bottles	39.0	142.50	71.25	189.55
AMQ30	-FA	30-Gallon Drum*	241.9	799.50	--	999.40
AMQ55	-FA	55-Gallon Drum*	433.8	1,416.25	--	1,742.00

SAE 20W-50 Premium Protection Synthetic Motor Oil

AROQT	-FA	1 Quart	2.1	7.85	--	10.20
AROQT	-CA	12 Quarts	25.2	89.55	7.46	120.90
ARO1G	-FA	1 Gallon	8.1	30.75	--	39.90
ARO1G	-CA	4 Gallons	32.4	117.00	29.25	157.95
ARO16	-FA	16-Gallon Keg*	132.9	456.80	--	584.75
ARO30	-FA	30-Gallon Drum*	245.3	810.00	--	1,012.50
ARO55	-FA	55-Gallon Drum*	440.0	1,435.50	--	1,765.70
ARO27	-FA	275-Gallon Tote*	2,115.0	7,150.00	--	8,794.50

Z-ROD™ Synthetic Motor Oil

High-zinc, high-phosphorus formulation engineered specifically for classic cars and performance vehicles. Provides extra protection for flat-tappet cams, lifters, rockers and other areas susceptible to wear. Unique blend of rust and corrosion inhibitors ensure maximum protection during long-term storage.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
-----------	-----------------	----------	---------------	---------------------	---------------	------------------------

SAE 10W-30 Z-ROD Synthetic Motor Oil

ZRTQT	-FA	1 Quart	2.1	7.55	--	9.80
ZRTQT	-CA	12 Quarts	25.2	85.95	7.16	116.05

SAE 20W-50 Z-ROD Synthetic Motor Oil

ZRFQT	-FA	1 Quart	2.1	7.85	--	10.20
ZRFQT	-CA	12 Quarts	25.2	89.55	7.46	120.90

OE MOTOR OIL



PREMIUM PROTECTION MOTOR OIL

- Worldwide Performance Specifications:**
- API SL/CF, CI-4+
 - JASO MA
 - ISO-L-EMA
 - Motorcycle Compatible



Z-ROD™ MOTOR OIL

- Worldwide Performance Specifications:**
- API SL/CF





Dominator® Synthetic Racing Oil

Provides superior performance and maximum protection in high-performance and racing applications. Formulated to withstand the elevated RPM, high temperatures and shock-loading common to racing applications. Delivers superior performance and maximum protection in extreme conditions. Shear-stable formulation engineered to provide maximum horsepower without sacrificing engine protection. Provides straight-grade protection in a multi-grade formulation.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
RD20QT	-FA	1 Quart	2.0	9.10	--	11.80
RD20QT	-CA	12 Quarts	24.0	103.65	8.64	139.95
RD2055	-FA	55-Gallon Drum*	431.0	1,694.00	--	2,083.65

Dominator SAE 10W-30 Synthetic Racing Oil

RD30QT	-FA	1 Quart	2.0	9.15	--	11.85
RD30QT	-CA	12 Quarts	24.0	104.25	8.69	140.75
RD3055	-FA	55-Gallon Drum*	433.0	1,705.00	--	2,097.15

Dominator SAE 15W-50 Synthetic Racing Oil

RD50QT	-FA	1 Quart	2.1	9.60	--	12.45
RD50QT	-CA	12 Quarts	25.2	109.65	9.14	148.05
RD501G	-FA	1 Gallon	8.0	37.75	--	48.95
RD501G	-CA	4 Gallons	32.0	143.80	35.95	194.15
RD5055	-FA	55-Gallon Drum*	435.0	1,804.00	--	2,218.95

Super Heavy Weight SAE 60 Synthetic Racing Oil

High-viscosity oil designed for high-horsepower racing engines, typically supercharged and alcohol-burning or nitro-fueled and requiring a high-viscosity oil to resist the thinning effects of fuel dilution. Also ideal for motor-cycles where SAE 60 motor oil is required.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
AHRQT	-FA	1 Quart	2.1	9.45	--	12.25
AHRQT	-CA	12 Quarts	25.2	107.85	8.99	145.60
AHRTP	-FA	(1) 2.5-Gal. Bottle	19.9	91.75	--	117.25
AHRTP	-CA	(2) 2.5-Gal. Bottles	39.8	174.75	87.38	232.45
AHR55	-FA	55-Gallon Drum*	442.0	1,771.00	--	2,178.35

Break-In Oil

SAE 30 viscosity grade oil formulated without friction modifiers to allow for quick and efficient piston ring seating in new and rebuilt high-performance and racing engines. Contains anti-wear additives to protect cam lobes, lifters and rockers during the critical break-in period when wear rates are highest, while increased film strength protects rod and main bearings from damage.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
BRKQT	-FA	1 Quart	2.1	5.50	--	7.15
BRKQT	-CA	12 Quarts	25.2	62.55	5.21	84.45

European Car Formula 5W-40 Synthetic Motor Oil

Specially formulated for the lubrication needs of European gasoline and diesel cars and light trucks. Blended with a broad 5W-40 viscosity rating. Allows for the maximum extended drain intervals recommended while providing superior protection and performance. Recommended for Volkswagen 505.01 applications including Passat, Beetle, Jetta, Touareg, Phaeton, GTI, Golf and Audi A3, A4, A6, A8, S4/RS4, TT and Q7.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
AELQT	-FA	1 Quart	2.1	7.85	--	10.15
AELQT	-CA	12 Quarts	25.2	89.25	7.44	120.50
AEL5L	-FA	(1) Five-Liter Bottle	11.1	40.45	--	52.25
AEL5L	-CA	(2) Five-Liter Bottles	22.2	77.00	38.50	103.95
AEL30	-FA	30-Gallon Drum*	244.0	807.00	--	1,008.75
AEL55	-FA	55-Gallon Drum*	438.0	1,430.00	--	1,758.90

European Car Formula 5W-30 Synthetic Motor Oil

Provides exceptional performance and protection in high-performance European gasoline and direct injection diesel engines. Low SAPS (sulfated ash, phosphorus and sulfur) formula is compatible with modern exhaust treatment devices, including diesel particulate filters (DPFs), for optimum life. Low-viscosity formulation maximizes fuel economy. Resists shear and deposit formation. Delivers excellent turbocharger protection. Recommended for the longest drain interval recommended by original equipment manufacturer.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
AELQT	-FA	1 Quart	2.1	8.50	--	11.00
AELQT	-CA	12 Quarts	25.2	96.75	8.06	130.65
AEL5L	-FA	(1) Five-Liter Bottle	11.1	43.90	--	56.75
AEL5L	-CA	(2) Five-Liter Bottles	22.2	83.60	41.80	112.90
AEL30	-FA	30-Gallon Drum*	244.0	882.00	--	1,102.50
AEL55	-FA	55-Gallon Drum*	438.0	1,567.50	--	1,928.05

DOMINATOR® RACING OIL

SAE 60 RACING OIL

BREAK-IN OIL

EUROPEAN MOTOR OILS

- Performance Specifications:**
- API SL/CF
 - JASO MA
 - ISO-L-EMA



- Worldwide Performance Specifications:**
- API SM/CF
 - ACEA C3, A3/B3-04, A3/B4-04
 - MB 229.31, 229.51
 - BMW LL-04
 - Porsche A40
 - Volvo
 - Saab
 - VW 502.00, 505.00, 505.01
 - MS-10725



- Worldwide Performance Specifications:**
- VW 504.00/507.00
 - ACEA A3/B3, A3/B4
 - MB 229.51
 - BMW LL-04
 - Porsche C30



FORMULA 4-STROKE® OILS

- Performance Specifications:**
- API SL/CF, SJ, SH, SG
 - JASO MA/MA2
 - ISO-L-EMA2



Formula 4-Stroke® Power Sports Oil

Specially formulated for four-stroke recreational motors, ATVs and snowmobiles. Reduces wear. Wet-clutch compatible. Contains no friction modifiers. Broad viscosity range makes it excellent for use in both hot and cold weather conditions.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 0W-40 Formula 4-Stroke Synthetic Power Sports Motor Oil						
AFFQ1	-FA	1 Quart	2.0	8.50	--	11.00
AFFQ1	-CA	12 Quarts	24.0	96.75	8.06	130.65
AFF30	-FA	30-Gallon Drum*	240.0	882.00	--	1,102.50
AFF55	-FA	55-Gallon Drum*	430.4	1,567.50	--	1,928.05

- Performance Specifications:**
- API SL
 - JASO MA/MA2
 - NMMA - FC-W (10W-30 Certification #FB-30011B) (10W-40 Certification #FB-30012K)



Formula 4-Stroke® Marine Synthetic Motor Oils

Formulated specifically for use in four-stroke gasoline-fueled engines used in marine applications. Offer exceptional wear protection, viscosity stability, low volatility and excellent rust protection. NMMA FC-W approved and "Warranty Certified." Recommended for use in four-stroke outboard motors including Honda, Yamaha, Mercury, Suzuki, Johnson-Evinrude (BRP), Nissan and Tohatsu. Excellent for use in marine inboard engines including Mercury (MerCruiser), OMC, Volvo-Penta, Crusader, Marine Power, GM, Ford and Chrysler. Recommended for use with personal watercraft (PWC) including Sea-Doo (BRP), Honda, Yamaha and Polaris. Wet-clutch compatible.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
10W-30 Formula 4-Stroke Marine Synthetic Oil						
WCTQ1	-FA	1 Quart	2.0	7.80	--	10.10
WCTQ1	-CA	12 Quarts	24.0	88.65	7.39	119.70
WCT55	-FA	55-Gallon Drum*	432.5	1,419.00	--	1,745.40
10W-40 Formula 4-Stroke Marine Synthetic Oil						
WCFQ1	-FA	1 Quart	2.0	8.35	--	10.85
WCFQ1	-CA	12 Quarts	24.0	95.25	7.94	128.60
WCF55	-FA	55-Gallon Drum*	433.3	1,540.00	--	1,894.20

- Performance Specifications:**
- API SL, SJ, SH, SG. . . (Gasoline)
 - API CG-4, CF, CD (Diesel)
 - JASO MA/MA2
 - ISO-L-EMA2 (Motorcycle wet-clutch)



Formula 4-Stroke® Synthetic Small Engine Oil

A commercial-grade formulation designed for hot-temperature, severe-service operation of small engines where routine maintenance is often difficult or infrequent. Recommended for use wherever SAE 10W-30 or SAE 30 oil is specified in gasoline or diesel engines, transmissions, hydraulics and chaincases requiring the listed specifications. Applications include maintenance equipment, tractors, lawn and garden equipment, generators, compactors, pumps, light towers, welders, log splitters, power washers, cement mixers and trowels, skid-steers, excavators and compressors.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Formula 4-Stroke 10W-30/SAE 30 Synthetic Small Engine Oil						
ASEQ1	-FA	1 Quart	2.0	6.40	--	8.30
ASEQ1	-CA	12 Quarts	24.0	72.75	6.06	98.25
ASE30	-FA	30-Gallon Drum*	237.0	642.00	--	802.50
ASE55	-FA	55-Gallon Drum*	425.0	1,127.50	--	1,386.85

- Performance Specifications:**
- API SG, SL/CF
 - JASO MA/MA2
 - ISO-L-EMA2 (Motorcycle wet-clutch)



Formula 4-Stroke® Synthetic Scooter Oil

Formulated specifically to meet the special needs of today's high-tech air- and water-cooled four-stroke motorized scooters. Offers excellent wear protection and friction reduction for longer equipment life and cooler operating temperatures. Exceptional shear stability ensures consistent viscosity protection and provides additional protection for transmissions and gear boxes. Friction-modifier-free formulation ensures wet-clutch compatibility and smooth clutch operation. A special anti-corrosion additive package provides long-term protection during periods of inactivity and storage.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Formula 4-Stroke 10W-40 Synthetic Scooter Oil						
ASOQ1	-FA	1 Quart	2.0	6.40	--	8.30
ASOQ1	-CA	12 Quarts	24.0	72.60	6.05	98.05

- Performance Specifications:**
- API SG, SL/CF, CG-4
 - JASO MA/MA2
 - ISO-L-EMA2
 - SAE 80
 - API GL-1



10W-30 Advanced Synthetic Motorcycle Oil

A premium oil designed for those who demand the absolute best lubrication for their motorcycles. Extensive research created an oil that is specially formulated to excel in all areas unique to motorcycles, including high engine RPM, wet-clutch lubrication, extreme-pressure regions of gears and rust common to short drives and storage. Multi-functional and fulfills the requirements of both domestic and foreign motorcycles. Outperforms other conventional and synthetic motorcycle oils. No friction modifiers. Wet-clutch compatible.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
10W-30 Advanced Synthetic Motorcycle Oil						
MCTQ1	-FA	1 Quart	2.0	8.65	--	11.20
MCTQ1	-CA	12 Quarts	24.0	98.55	8.21	133.05
MCT30	-FA	30-Gallon Drum*	242.0	900.00	--	1,125.00
MCT55	-FA	55-Gallon Drum*	433.0	1,600.50	--	1,968.65

SYNTHETIC MOTORCYCLE OIL

*Not stocked in all distribution centers. Call for availability.

†Product cannot be shipped air freight or parcel post.

- Performance Specifications:**
- API SG, SL/CF, CG-4
 - JASO MA/MA2
 - ISO-L-EMA2
 - SAE 80W-90
 - API GL-1



10W-40 Advanced Synthetic Motorcycle Oil

For those who demand the best. Advanced multi-functional formula. Fulfills the requirements of both domestic and foreign motorcycles. Recommended for high-performance liquid- or air-cooled four-stroke engines and transmissions and both four- and two-stroke motorcycles. Wet-clutch compatible. Outstanding gear protection. Anti-rust fortified. Recommended for Honda, Kawasaki, Yamaha, Suzuki, BMW, Husqvarna and Victory motorcycles. Not recommended where an API GL-4 or GL-5 gear oil is required.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
10W-40 Advanced Synthetic Motorcycle Oil						
MCFQT	-FA	1 Quart	2.1	8.90	--	11.55
MCFQT	-CA	12 Quarts	25.2	101.70	8.48	137.30
MCF1G	-FA	1 Gallon	8.0	35.00	--	45.40
MCF1G	-CA	4 Gallons	32.0	133.20	33.30	179.85
MCF30	-FA	30-Gallon Drum*	242.1	931.50	--	1,164.40
MCF55	-FA	55-Gallon Drum*	434.2	1,658.25	--	2,039.65

- Performance Specifications:**
- API SG, SL/CF, CG-4
 - JASO MA/MA2
 - ISO-L-EMA2
 - SAE 90
 - API GL-1



20W-50 Advanced Synthetic Motorcycle Oil

For those who demand the best. Multi-functional and fulfills the requirements of both domestic and foreign motorcycles. Excellent performance in air-cooled motorcycle engines due to high heat resistance, anti-wear additives and oxidation resistance. Recommended for engines, transmissions and the primary chaincase. Absolutely shear stable and will not thin out from mechanical activity. Contains special anti-rust agents for superior rust protection, and contains no friction modifiers for excellent wet-clutch performance. Recommended for use in Harley-Davidson, Buell, KTM, Ducati, Aprilia, BMW and Triumph motorcycles. Not recommended where an API GL-4 or GL-5 gear oil is required.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
20W-50 Advanced Synthetic Motorcycle Oil						
MCVQT	-FA	1 Quart	2.1	9.20	--	11.90
MCVQT	-CA	12 Quarts	25.2	104.70	8.73	141.35
MCV1G	-FA	1 Gallon	8.0	36.05	--	46.75
MCV1G	-CA	4 Gallons	32.0	137.20	34.30	185.25
MCV30	-FA	30-Gallon Drum*	242.9	961.50	--	1,201.90
MCV55	-FA	55-Gallon Drum*	435.7	1,713.25	--	2,107.30

- Performance Specifications:**
- API SG, SL/CF
 - JASO MA/MA2
 - ISO-L-EMA2
 - SAE 140
 - API GL-1



SAE 60 Advanced Synthetic Motorcycle Oil

Designed specifically for big-bore, air-cooled motorcycle engines, including Harley-Davidson Panhead, Show-elhead and Knucklehead. Shear-stable formula helps stop viscosity loss. Excellent performance due to high heat resistance, anti-wear additives and oxidation resistance. Contains special anti-rust agents for superior rust protection, and contains no friction modifiers for excellent wet-clutch performance. Recommended for all foreign and domestic motorcycle engines and transmissions requiring an SAE 60 lubricant. Not recommended for primary chaincases.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 60 Advanced Synthetic Motorcycle Oil						
MCSQT	-FA	1 Quart	2.0	9.40	--	12.20
MCSQT	-CA	12 Quarts	24.0	107.25	8.94	144.80

Shock Therapy® Suspension Fluid

Controls friction, heat, wear, foaming and scuffing in suspension components. High viscosity index and shear-stability control shock fade and inconsistent dampening in temperature extremes.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Shock Therapy Suspension Fluid #5 Light						
STLQT	-FA	1 Quart	1.9	9.10	--	11.80
STLQT	-CA	12 Quarts	22.8	103.95	8.66	140.35
STL05	-FA	5-Gallon Pail	37.7	168.25	--	223.80
Shock Therapy Suspension Fluid #10 Medium						
STMQT	-FA	1 Quart	2.1	8.95	--	11.60
STMQT	-CA	12 Quarts	25.2	102.00	8.50	137.70
STM05	-FA	5-Gallon Pail	38.1	165.00	--	219.45

- Performance Specifications:**
- API CF
 - SAE (20W) 40
 - Low Ash



Synthetic Stationary Natural Gas Engine Oil

Delivers continuous protection in stationary four-stroke and select two-stroke natural gas engines requiring a low ash (<0.5%) oil. Shear-stable formula qualifies as a multi-grade and can be used over broader ambient temperature ranges. Premium synthetic base oils provide optimum lubrication while naturally resisting nitration. Reduces valve recession and wear.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Stationary Natural Gas Engine Oil						
ANGS05	-FA	5-Gallon Pail	39.2	142.25	--	189.20
ANGS55	-FA	55-Gallon Drum*	435.7	1,413.50	--	1,738.65
ANGS27	-FA	275-Gallon Tote*	2,074.0	7,040.00	--	8,659.20

SYNTHETIC MOTORCYCLE OIL

SUSPENSION FLUID

NATURAL GAS ENGINE OILS

Performance Specifications:

- Meets Cummins CES 20074
- API CF
- SAE 15W-40
- Low Ash

Synthetic Vehicular Natural Gas Engine Oil

Delivers superior protection and performance in vehicular natural gas engines calling for a 15W-40 low-ash engine oil. Provides enhanced valve train protection, whether roller or slider followers are used. Formulated with high levels of zinc and phosphorus to provide outstanding wear protection. Recommended for mobile applications fueled by compressed natural gas (CNG), liquefied natural gas (LNG) or liquefied petroleum gas (LPG).

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
ANGV05	-FA	5-Gallon Pail	39.2	126.00	--	167.60
ANGV55	-FA	55-Gallon Drum*	435.7	1,234.75	--	1,518.75
ANGV27	-FA	275-Gallon Tote*	2,074.0	6,146.25	--	7,559.90

Premium API CJ-4 Synthetic Diesel Oil

The premium choice for model-year 2007 and newer heavy-duty and pickup truck diesel engines requiring API CJ-4 emission-quality oil standards. Offers extended drain intervals of up to 3X OEM recommendation. Delivers extraordinary lubrication and maximum fuel efficiency in diesel engines found in commercial, fleet and personal vehicles. Contains low sulfated ash, phosphorus and sulfur additives to meet modern specifications for emission-quality diesel oil. Compatible with all exhaust treatment devices, including diesel particulate filters (DPFs).

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
DEOQT	-FA	1 Quart	2.1	7.80	--	10.10
DEOQT	-CA	12 Quarts	25.2	88.65	7.39	119.70
DEO1G	-FA	1 Gallon	8.0	30.40	--	39.50
DEO1G	-CA	4 Gallons	32.0	115.80	28.95	156.35
DEOTP	-FA	(1) 2.5-Gal. Bottle	19.5	74.95	--	95.95
DEOTP	-CA	(2) 2.5-Gal. Bottles	39.0	142.75	71.38	189.90
DEO30	-FA	30-Gallon Drum*	243.0	801.00	--	1,001.25
DEO55	-FA	55-Gallon Drum*	437.1	1,419.00	--	1,745.40
DEO27	-FA	275-Gallon Tote*	2,089.0	7,067.50	--	8,693.05

Premium API CJ-4 15W-40 Synthetic Diesel Oil

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
DMEQT	-FA	1 Quart	2.1	7.60	--	9.90
DMEQT	-CA	12 Quarts	25.2	86.85	7.24	117.25
DME1G	-FA	1 Gallon	8.0	29.80	--	38.70
DME1G	-CA	4 Gallons	32.0	113.40	28.35	153.10
DMETP	-FA	(1) 2.5-Gal. Bottle	19.5	73.40	--	93.95
DMETP	-CA	(2) 2.5-Gal. Bottles	39.0	139.75	69.88	185.90
DME30	-FA	30-Gallon Drum*	242.0	783.00	--	978.75
DME55	-FA	55-Gallon Drum*	437.1	1,386.00	--	1,704.80
DME27	-FA	275-Gallon Tote*	2,089.0	6,902.50	--	8,490.10

OE 15W-40 Synthetic Diesel Oil

Provides excellent protection and performance in both on- and off-road diesel engines for the original equipment manufacturer's recommended drain interval. Meets API CJ-4 specifications and is suitable for both modern and older diesel applications. Exceeds the higher performance demands of modern engines and withstands the stress of heat, soot and acids to help prevent deposits, wear and corrosion.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
OEDQT	-FA	1 Quart	2.1	5.25	--	6.80
OEDQT	-CA	12 Quarts	25.2	59.55	4.96	80.40
OED1G	-FA	1 Gallon	8.0	20.45	--	26.70
OED1G	-CA	4 Gallons	32.0	77.80	19.45	105.05
OEDTP	-FA	(1) 2.5 Gallon Bottle	19.5	50.05	--	64.35
OEDTP	-CA	(2) 2.5 Gallon Bottles	39.0	95.25	47.63	126.70
OED30	-FA	30-Gallon Drum*	242.0	556.50	--	695.65
OED55	-FA	55-Gallon Drum*	437.1	970.75	--	1,194.05
OED27	-FA	275-Gallon Tote*	2,089.0	4,826.25	--	5,936.30

Series 3000 5W-30 Synthetic Heavy Duty Diesel Oil

Long service-life oil. Engineered for on- and off-road diesel applications not equipped with diesel particulate filters (DPFs). Also engineered for all gasoline engines recommending API SL specifications, including turbo-charged vehicles. Provides superior wear protection and fuel efficiency compared to conventional oils. Premium synthetic base oils and additives with 12 TBN chemistry resist oil breakdown from heat, blow-by chemicals, acids and oxygen. Improves cold-temperature starting.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
HDDQT	-FA	1 Quart	2.1	8.60	--	11.15
HDDQT	-CA	12 Quarts	25.2	97.95	8.16	132.25
HDD1G	-FA	1 Gallon	8.0	33.70	--	43.70
HDD1G	-CA	4 Gallons	32.0	128.20	32.05	173.10
HDDTP	-FA	(1) 2.5-Gal. Bottle	19.6	83.10	--	106.25
HDDTP	-CA	(2) 2.5-Gal. Bottles	39.2	158.25	79.13	210.50
HDD30	-FA	30-Gallon Drum*	244.6	894.00	--	1,117.50
HDD55	-FA	55-Gallon Drum*	438.8	1,589.50	--	1,955.10
HDD27	-FA	275-Gallon Tote*	2,118.9	7,920.00	--	9,741.60

*Not stocked in all distribution centers. Call for availability. †Product cannot be shipped air freight or parcel post.

PREMIUM DIESEL OIL

Worldwide Performance Specifications:

- API CJ-4/CI-4+/CF
- API SM, SL, SJ . . .
- ACEA E7, E9
- MACK EO-O Premium Plus
- DDC Power Guard 93K218
- Caterpillar ECF-3, ECF-2
- Cummins 20081
- Volvo VDS-4
- MB 228.31
- MTU Type I & II
- MAN 3275
- JASO DH-2
- Global DHD-1
- Renault RLD-3



OE SYNTHETIC DIESEL OIL

Worldwide Performance Specifications:

- API CJ-4, CI-4+, SM...
- ACEA E9
- DDC 93K218
- Cummins CES 20081
- MB 228.31
- CAT ECF-3, ECF-2, ECF-1a
- Mack EO-O Plus
- Volvo VDS-4
- MAN 3575
- Renault RLD-3
- MTU Type 2.1



SERIES 3000 DIESEL OIL

Worldwide Performance Specifications:

- API CI-4+/CF/CF-2, SL
- Global DHD-1
- ACEA A3/B3, E2, E3, E5, E7
- JASO DH-1
- Mack EO-N+ '03
- Detroit Diesel 93K214
- Caterpillar ECF-1-a, ECF-2
- Cummins 20078, 20077, 20076
- Volvo VDS-3, VDS-2
- Daimler-Benz 228.1, 228.3, 229.1
- MTU Type 2
- MAN 3275



Worldwide Performance Specifications:

- API CI-4/CF/CF-2, SL
- Global DHD-1
- ACEA A3/B3, E2, E3, E5, E7
- JASO DH-1
- Mack EO-N+ '03
- Detroit Diesel 93K214
- Caterpillar ECF-1-a, ECF-2
- Cummins 20078, 20077, 20076
- Volvo VDS-3, VDS-2
- Daimler-Benz 228.1, 228.3, 229.1
- MTU Type 2
- MAN 3275



15W-40 Synthetic Heavy Duty Diesel Oils

Engineered for on- and off-road diesel applications not equipped with diesel particulate filters (DPFs). High 12 TBN controls acids from combustion blow-by and EGR. High levels of detergency and dispersancy additives control soot thickening, oxidation and wear. Resist bore polishing, deposit formation and ring sticking. Provide clean engine performance. Extended drain capabilities reduce downtime and motor oil expenses.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 15W-40 Synthetic Heavy Duty Diesel and Marine Motor Oil						
AMEQT	-FA	1 Quart	2.1	7.10	--	9.25
AMEQT	-CA	12 Quarts	25.2	81.00	6.75	109.35
AME1G	-FA	1 Gallon	8.0	27.75	--	36.05
AME1G	-CA	4 Gallons	32.0	105.60	26.40	142.60
AMETP	-FA	(1) 2.5-Gal. Bottle	19.6	68.25	--	87.45
AMETP	-CA	(2) 2.5-Gal. Bottles	39.2	130.00	65.00	172.90
AME30	-FA	30-Gallon Drum*	242.8	724.50	--	905.65
AME55	-FA	55-Gallon Drum*	436.0	1,278.75	--	1,572.90
AME27	-FA	275-Gallon Tote*	2,102.2	6,366.25	--	7,830.50

SAE 15W-40 Synthetic Blend Heavy Duty Diesel Oil

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
PCOQT	-FA	1 Quart	2.1	6.40	--	8.35
PCOQT	-CA	12 Quarts	25.2	73.05	6.09	98.65
PCO1G	-FA	1 Gallon	8.0	24.95	--	32.50
PCO1G	-CA	4 Gallons	32.0	95.00	23.75	128.25
PCOTP	-FA	(1) 2.5-Gal. Bottle	19.8	61.30	--	78.65
PCOTP	-CA	(2) 2.5-Gal. Bottles	39.6	116.75	58.38	155.30
PCO30	-FA	30-Gallon Drum*	245.0	645.00	--	806.25
PCO55	-FA	55-Gallon Drum*	439.4	1,133.00	--	1,393.60
PCO27	-FA	275-Gallon Tote*	2,122.2	5,637.50	--	6,934.15

SAE 10W-30/SAE 30 Synthetic Heavy Duty Diesel Oil

Exceeds both 10W-30 multi-grade and SAE 30 straight-grade viscosity requirements. Engineered for on- and off-road diesel applications not equipped with diesel particulate filters (DPFs). Also recommended for gasoline engines requiring API SL or previous specifications. Excellent for heavy equipment and personal vehicles.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 10W-30/SAE 30 Synthetic Heavy Duty Diesel Oil						
ACD1G	-FA	1 Gallon	8.1	27.75	--	36.05
ACD1G	-CA	4 Gallons	32.4	105.60	26.40	142.60
ACD30	-FA	30-Gallon Drum*	244.7	724.50	--	905.65
ACD55	-FA	55-Gallon Drum*	438.9	1,278.75	--	1,572.90
ACD27	-FA	275-Gallon Tote*	2,120.0	6,366.25	--	7,830.50

Severe Gear® Synthetic EP Lubricant

Specifically engineered for high-demand applications, including trailer towing, heavy hauling, 4x4 off-road driving, commercial use and racing. Superior lube film strength combined with extra additives protects gears and bearings from scoring and wear. Resists high heat and possesses excellent cold-flow properties. Outperforms conventional gear oils. Recommended for all types of vehicles including turbo-diesel pickups, SUVs, autos, trucks, heavy equipment and motor homes. Compatible with most limited-slip differentials.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
-----------	-----------------	----------	---------------	---------------------	---------------	------------------------

Severe Gear SAE 75W-90 Synthetic Gear Lube

SVGQT	-FA	1 Quart	2.0	11.55	--	14.90
SVGQT	-CA	12 Quarts	24.0	131.55	10.96	177.60
SVG05	-FA	5-Gallon Pail	38.8	214.25	--	285.00
SVG16	-FA	16-Gallon Keg*	131.0	677.60	--	867.35
SVG30	-FA	30-Gallon Drum*	241.0	1,230.00	--	1,537.50
SVG55	-FA	55-Gallon Drum*	432.0	2,200.00	--	2,706.00

Severe Gear SAE 75W-110 Synthetic Gear Lube

SVTQT	-FA	1 Quart	2.1	11.95	--	15.45
SVTQT	-CA	12 Quarts	25.2	136.35	11.36	184.10
SVT05	-FA	5-Gallon Pail	40.0	222.25	--	295.60
SVT16	-FA	16-Gallon Keg*	132.0	703.20	--	900.10
SVT30	-FA	30-Gallon Drum*	244.0	1,278.00	--	1,597.50
SVT55	-FA	55-Gallon Drum*	437.0	2,288.00	--	2,814.25

Severe Gear SAE 75W-140 Synthetic Gear Lube

SVOQT	-FA	1 Quart	2.1	13.05	--	16.85
SVOQT	-CA	12 Quarts	25.2	148.65	12.39	200.70
SVO05	-FA	5-Gallon Pail	39.2	242.75	--	322.90
SVO16	-FA	16-Gallon Keg*	132.0	768.80	--	984.10
SVO30	-FA	30-Gallon Drum*	244.0	1,401.00	--	1,751.25
SVO55	-FA	55-Gallon Drum*	437.0	2,513.50	--	3,091.65
SVO27	-FA	275-Gallon Tote*	2,131.0	12,540.00	--	15,424.20

Worldwide Performance Specifications:

- API CI-4/CF/CF-2, SL
- Global DHD-1 • ACEA A3/B3, E2, E3, E5, E7 • JASO DH-1 • Mack EO-N+ '03 • Detroit Diesel 93K214
- Caterpillar ECF-1-a, ECF-2 • Cummins 20078, 20077, 20076 • Volvo VDS-3, VDS-2 • Daimler-Benz 228.1, 228.3, 229.1 • MTU Type 2 • MAN 3275



Performance Specifications:

- API GL-5/MT-1
- MIL-PRF-2105E
- Mack GO-J
- Dana SHAES 234 (Eaton PS-037)



HEAVY DUTY DIESEL OILS

SEVERE GEAR® SYNTHETIC GEAR LUBE

SEVERE GEAR® SYNTHETIC GEAR LUBE

Performance Specifications:
• API GL-5



Severe Gear® Heavy Viscosity Synthetic Gear Lube

Engineered specifically for the demands of severe racing conditions. Recommended for off-road truck racing, rock racing, rock crawling, tractor pulling, funny car racing and dragster racing applications that require heavier-viscosity gear lubricants. Formulated with shear-stable, heavy synthetic base oils for high film strength and extra heavy treatments of additives. Provides improved flow over conventional oils, reducing viscous drag and power loss. Engineered for high-horsepower, high-torque conditions where centrifugal gear lube sling-off is encountered. Tenacious formulation clings to gears and bearings for maximum protection during shock loading, high G-forces and where pinion gears are installed at steep angles.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Severe Gear SAE 190 Synthetic Gear Lube						
SRNQT	-EA	1 Quart	2.1	12.30	--	15.90
SRNQT	-CA	12 Quarts	25.2	140.40	11.70	189.55
SRN05	-EA	5-Gallon Pail	40.0	229.00	--	304.60
SRN16	-EA	16-Gallon Keg*	134.1	724.80	--	927.75
SRN30	-EA	30-Gallon Drum*	247.4	1,318.50	--	1,648.15
SRN55	-EA	55-Gallon Drum*	443.9	2,362.25	--	2,905.60
SRN27	-EA	275-Gallon Tote*	2,144.5	11,783.75	--	14,494.05

Severe Gear SAE 250 Synthetic Gear Lube

SRTQT	-EA	1 Quart	2.1	12.30	--	15.90
SRTQT	-CA	12 Quarts	25.2	140.40	11.70	189.55
SRT05	-EA	5-Gallon Pail	40.0	229.00	--	304.60
SRT16	-EA	16-Gallon Keg*	134.5	724.80	--	927.75
SRT30	-EA	30-Gallon Drum*	248.2	1,318.50	--	1,648.15
SRT55	-EA	55-Gallon Drum*	445.4	2,362.25	--	2,905.60
SRT27	-EA	275-Gallon Tote*	2,151.9	11,783.75	--	14,494.05

Long Life Synthetic Gear Lube

Specifically engineered for extended drain intervals up to 500,000 miles as set by equipment manufacturers for over-the-road trucks and heavy equipment. Provides long life in passenger cars and trucks. Protects against wear and improves equipment life. Excellent all-season performance. Outperforms conventional gear oils. Compatible with most limited-slip differentials.

Performance Specifications:
• API GL-5/MT-1
• MIL-PRF-2105E
• Mack GO-J+
• Dana SHAES 256 (Eaton PS-163)



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 75W-90 Long Life Synthetic Gear Lube						
EGRQT	-EA	1 Quart	2.1	9.50	--	12.35
EGRQT	-CA	12 Quarts	25.2	108.45	9.04	146.45
EGR1G	-EA	1 Gallon	8.1	37.45	--	48.55
EGR1G	-CA	4 Gallons	32.4	142.60	35.65	192.55
EGR05	-EA	5-Gallon Pail	39.7	175.75	--	233.75
EGR16	-EA	16-Gallon Keg*	133.4	554.40	--	709.65
EGR30	-EA	30-Gallon Drum*	246.0	999.00	--	1,248.75
EGR55	-EA	55-Gallon Drum*	442.0	1,776.50	--	2,185.10
EGR27	-EA	275-Gallon Tote*	2,133.0	8,855.00	--	10,891.65

SAE 80W-140 Long Life Synthetic Gear Lube

EGO05	-EA	5-Gallon Pail	40.0	175.75	--	233.75
EGO16	-EA	16-Gallon Keg*	135.0	554.40	--	709.65
EGO30	-EA	30-Gallon Drum*	249.0	999.00	--	1,248.75
EGO55	-EA	55-Gallon Drum*	446.0	1,776.50	--	2,185.10
EGO27	-EA	275-Gallon Tote*	2,154.0	8,855.00	--	10,891.65

Synthetic 80W-90 Gear Lube

High-quality replacement for applications specifying SAE 80W-90 conventional gear lube. Synthetic construction provides improved cold-flow properties, high viscosity index and heat resistance. Contains an over-treat of high-quality additives, exceeding the minimum standards. Provides excellent wear protection and long equipment life.

Performance Specifications:
• API GL-5/MT-1
• MIL-PRF-2105E
• Mack GO-J
• Dana SHAES 234 (Eaton PS-037)



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 80W-90 Synthetic Gear Lube						
AGLQT	-EA	1 Quart	2.1	8.05	--	10.40
AGLQT	-CA	12 Quarts	25.2	91.50	7.63	123.55
AGL1G	-EA	1 Gallon	8.1	31.50	--	40.90
AGL1G	-CA	4 Gallons	32.4	120.00	30.00	162.00
AGL05	-EA	5-Gallon Pail	39.8	147.50	--	196.20
AGL16	-EA	16-Gallon Keg*	133.9	464.00	--	593.95
AGL30	-EA	30-Gallon Drum*	247.0	829.50	--	1,036.90
AGL55	-EA	55-Gallon Drum*	443.2	1,465.75	--	1,802.90
AGL27	-EA	275-Gallon Tote*	2,141.2	7,301.25	--	8,980.55

LONG LIFE GEAR LUBE

Performance Specifications:
 • API GL-4, GL-5
 • SAE 75W/80W-90



Universal Synthetic Marine Gear Lube

Provides true marine gear performance. Contains a stable extreme-pressure additive package that provides superior protection from shock loading. Resists foam and retains extreme-pressure qualities, even when subjected to 10 percent water contamination. For use in outboard lower units, stern drives, V-drives, bow and tunnel thrusters and marine transmissions requiring an SAE 75W-90 or 80W-90 lube meeting either GL-4 or GL-5 performance standards. Excellent for use in ATV applications.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 75W/80W-90 Universal Synthetic Marine Gear Lube						
AGMTB	-FA	(1) 10-oz. Tube	1.2	5.30	--	7.10
AGMTB	-CA	(6) 10-oz. Tubes	7.2	30.22	5.04	41.75
AGMQT	-FA	1 Quart	2.1	8.65	--	11.25
AGMQT	-CA	12 Quarts	25.2	98.85	8.24	133.45
AGM05	-FA	5-Gallon Pail	39.4	159.75	--	212.50
AGM16	-FA	16-Gallon Keg*	132.5	503.20	--	644.10
AGM30	-FA	30-Gallon Drum*	245.0	903.00	--	1,128.75
AGM55	-FA	55-Gallon Drum*	438.5	1,600.50	--	1,968.65

Slip Lock® Differential Additive

Formulated with advanced friction modifiers. Designed to eliminate gear-housing chatter in cars, trucks and SUVs equipped with limited-slip, positraction and locking differentials. Formulated for use with both synthetic and petroleum gear lubricants and safely replaces manufacturer-recommended friction modifiers.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Slip Lock Differential Additive						
ADATB	-FA	(1) 4-oz. Tube	0.3	6.10	--	8.10
ADATB	-CA	(12) 4-oz. Tubes	3.6	69.36	5.78	95.75



Synthetic Multi-Vehicle Automatic Transmission Fluid

Recommended for most automatic transmissions. Helps eliminate confusion and misapplications, and lowers inventory requirements. Delivers maximum protection and is excellent in demanding environments such as towing, hauling or commercial use. Lasts longer than conventional oil for extended drain intervals. Saves time and costly maintenance expenses. Superior hot- and cold-weather performance. Improves efficiency and typically reduces operating temperatures by as much as 50°F. Excellent for power steering units that use ATF.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Multi-Vehicle Automatic Transmission Fluid						
ATFQT	-FA	1 Quart	2.0	8.90	--	11.50
ATFQT	-CA	12 Quarts	24.0	101.25	8.44	136.70
ATF1G	-FA	1 Gallon	7.9	34.85	--	45.20
ATF1G	-CA	4 Gallons	31.6	132.60	33.15	179.05
ATFTP	-FA	(1) 2.5-Gal. Bottle	19.3	86.00	--	109.90
ATFTP	-CA	(2) 2.5-Gal. Bottles	38.6	163.75	81.88	217.80
ATF16	-FA	16-Gallon Keg*	129.5	519.20	--	664.60
ATF30	-FA	30-Gallon Drum*	238.9	927.00	--	1,158.75
ATF55	-FA	55-Gallon Drum*	428.3	1,650.00	--	2,029.50
ATF27	-FA	275-Gallon Tote*	2,066.4	8,222.50	--	10,113.70

Synthetic Fuel Efficient Automatic Transmission Fluid

Fuel-efficient formulation engineered to exceed the requirements of GM, Ford and Toyota where low-viscosity oil is required. Exceptional hot- and cold-temperature performance with a -63°F pour point. High film strength and a select anti-wear/extreme-pressure additive package for outstanding wear protection. Delivers outstanding clutch-holding capacity, torque-transfer ability and anti-shudder properties.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Fuel Efficient Automatic Transmission Fluid						
ATLQT	-FA	1 Quart	2.0	8.90	--	11.50
ATLQT	-CA	12 Quarts	24.0	101.25	8.44	136.70
ATLTP	-FA	(1) 2.5-Gal. Bottle	19.5	86.00	--	109.90
ATLTP	-CA	(2) 2.5-Gal. Bottles	39.0	163.75	81.88	217.80
ATL30	-FA	30-Gallon Drum*	237.0	927.00	--	1,158.75
ATL55	-FA	55-Gallon Drum*	424.0	1,650.00	--	2,029.50

Performance Specifications:
 • GM DEXRON® III-H
 • Ford MERCON® & MERCON V
 • Chrysler ATF-4®
 • Toyota Type T-III & T-IV
 • Honda Z-1 (not CVT)
 • Diamond SP II & III (Mitsubishi/Hyundai/Kia)
 • Mazda ATF-III, ATF-MV
 • Subaru ATF, ATF-HP
 • Nissan Matic D, J & K
 • Idemitsu K-17
 • BMW LA2634, LT 71141
 • Audi G-052-025-A2 & G-052-162-A1
 • Volvo 97340
 • MB 236.1, 236.2, 236.5, 236.6, 236.7, 236.9 & 236.10
 • JWS 3309
 • NAG 1
 • ETL-7045E, ETL-8072B & N402
 • Voith 55.6335.XX (G607, G1363)
 • ZF TE-ML 03D, 04D, 09, 14A, 14B, 14C, 16L, 17C
 • Allison C-4, TES 389
 • Mopar AS68RC



Performance Specifications:
 • GM DEXRON® VI
 • Ford MERCON® LV & SP
 • Toyota WS

MARINE GEAR LUBE

SLIP LOCK®

TRANSMISSION FLUID

- Recommended for use in or as a replacement for the following:**
- New Venture NV T350, NV1500, NV2550, NV3500, NV3550 & NV5600
 - Tremec T4, T5, T18, T56 T176, TK0500, TK0600, TR3550 (GM Vehicles) & TR3450
 - Honda Genuine MTF
 - GM Part #12345349, #12345577, #12377916 & #1052931
 - Chrysler Part #4874464 & #4874465
 - GM Specs #9985648, #9986105 & #9985535
 - Chrysler Specs MS-9224 & MS-9417
 - MTF-94 & Texaco MTX Fluids

Synthetic Manual Synchronesh Transmission Fluid

Specifically designed for manual transmissions and transaxles with synchronizers. Formulated with advanced additive technology to provide proper friction characteristics for smooth shifting without grinding or bump-shifting while providing maximum gear and bearing protection. Outperforms motor oils commonly used for manual transmissions. Protects at extreme temperatures from -40°F to 300°F. Possesses outstanding anti-wear and anti-foam properties and is non-corrosive to yellow metals.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Manual Synchronesh Transmission Fluid						
MTFQT	-EA	1 Quart	2.1	9.80	--	12.70
MTFQT	-CA	12 Quarts	25.2	111.75	9.31	150.90
MTF05	-EA	5-Gallon Pail	39.2	181.25	--	241.10
MTF55	-EA	55-Gallon Drum*	436.0	1,842.50	--	2,266.30

Synthetic Manual Transmission and Transaxle Gear Lube

Designed to meet the requirements of certain manual transmissions and transaxles. Provides improved internal component protection. Formulated with extreme-pressure additives and advanced synchronesh qualities that provide smooth shifts while protecting bearings, gears and seals. Non-corrosive to yellow metals.

- Recommended for use in or as a replacement for the following:**
- API GL-4/MT-1, ZF TE-ML 02B, 16A, 17A, 19A and MAN 341 MI.
 - Synchronized manual transmissions and transaxles that require 75W-85, 75W-90 or 80W-90 API GL-4 Gear Lube
 - NV 4500 Transmissions
 - GM Part #12346190
 - Chrysler Part #4874459
 - Chrysler Spec MS-9070
 - Certain Acura, Hyundai, Infiniti, Kia, Land Rover, Lexus, Mazda, Mitsubishi-Fuso and Zetor models requiring GL-4
 - Tremec TR3550 (Chrysler) and T56 (Dodge SRT-10 truck & Viper)
 - Gear Vendors Gear Splitters



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 75W-90 Synthetic Manual Transmission and Transaxle Gear Lube						
MTGQT	-EA	1 Quart	2.0	11.45	--	14.80
MTGQT	-CA	12 Quarts	24.0	130.35	10.86	176.00
MTG05	-EA	5-Gallon Pail	38.9	212.25	--	282.30
MTG55	-EA	55-Gallon Drum*	434.0	2,183.50	--	2,685.75

Super Shift® Synthetic Racing Transmission Fluid

Delivers outstanding performance in high-performance, high-horsepower vehicles. Formulated without friction modifiers or viscosity improvers for positive clutch pack engagement and stable viscosity. Formulated to prevent slippage and lower heat compared to conventional transmission fluids. Superb high-temperature resistance controls oxidation and varnish. Resists wear, lasts longer and improves transmission life. Recommended for racing and street performance automatic transmissions.

- Performance Specifications:**
- Allison C-4
 - Ford Type F



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SAE 10W Super Shift Synthetic Racing Transmission Fluid						
ARTQT	-EA	1 Quart	2.0	8.95	--	11.60
ARTQT	-CA	12 Quarts	24.0	101.85	8.49	137.50
ART55	-EA	55-Gallon Drum*	429.4	1,661.00	--	2,043.05

Torque-Drive® Synthetic Automatic Transmission Fluid

Engineered specifically for the Allison® TES-295 transmission fluid specification. Replaces Allison/Castrol® Transynd® fluid. Excellent protection in temperature extremes. Ensures consistent, smooth clutch engagement over the life of the fluid and controls clutch glazing and elongated shift times. Recommended for extended drain intervals set by Allison.

- Recommended for use in applications specifying:**
- Allison TES-295 or C-4
 - DEXRON III
 - MERCON
 - ZF TE-ML 14C
 - VOITH G1363
 - Caterpillar TO-2



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Torque-Drive Synthetic Automatic Transmission Fluid						
ATD1G	-EA	1 Gallon	7.8	37.35	--	48.40
ATD1G	-CA	4 Gallons	31.2	142.20	35.55	192.00
ATDTP	-EA	(1) 2.5-Gal. Bottle	19.1	92.30	--	117.90
ATDTP	-CA	(2) 2.5-Gal. Bottles	38.2	175.75	87.88	233.75
ATD16	-EA	16-Gallon Keg*	129.0	557.60	--	713.75
ATD30	-EA	30-Gallon Drum*	238.0	999.00	--	1,248.75
ATD55	-EA	55-Gallon Drum*	426.0	1,782.00	--	2,191.90
ATD27	-EA	275-Gallon Tote*	2,054.0	8,882.50	--	10,925.50

TRANSMISSION FLUID

- Recommended for use in applications specifying:**
SAE 10W
- CAT T0-4
 - Allison C-4
 - Komatsu 07.868.1
 - API GL-1
- SAE 30
- CAT T0-4
 - Allison C-4
 - Komatsu 07.868.1
 - API GL-1
- SAE 50
- CAT T0-4
 - CD-50
 - Komatsu 07.868.1
 - API GL-1

Synthetic Powershift Transmission Fluid

Specifically formulated for heavy-duty powershift transmissions. Provides outstanding friction performance for enhanced clutch engagement. Formulated to prevent slippage and glazing. Shear stable and anti-wear fortified. Protects gears and bearings. Resists high-temperature oxidation, varnish and sludge formation. Superb cold-flow properties. Extended-drain-interval capable. Recommended for heavy-duty service found in commercial and earth-moving applications as well as lighter-duty transmissions requiring the listed specifications. SAE 30 & 50 are also excellent for manual transmissions.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Powershift Transmission Fluid SAE 10W						
CTG05	-FA	5-Gallon Pail	38.6	150.25	--	199.85
CTG55	-FA	55-Gallon Drum*	429.4	1,501.50	--	1,846.85
CTG27	-FA	275-Gallon Tote*	2,071.9	7,480.00	--	9,200.40
Synthetic Powershift Transmission Fluid SAE 30						
CTJ05	-FA	5-Gallon Pail	39.2	151.25	--	201.20
CTJ55	-FA	55-Gallon Drum*	436.0	1,512.50	--	1,860.40
Synthetic Powershift Transmission Fluid SAE 50						
CTL05	-FA	5-Gallon Pail	39.8	160.25	--	213.15
CTL55	-FA	55-Gallon Drum*	442.7	1,611.50	--	1,982.15
CTL27	-FA	275-Gallon Tote*	2,138.7	8,030.00	--	9,876.90

Synthetic Two-Cycle Oils

Engineered for maximum performance in specific applications, yet recommended for use in multiple applications. Contain application-specific additives designed to prevent carbon build-up, ring sticking, plug fouling and varnish formation. Provide excellent lubricity to help prevent wear and piston scuffing.

hp Injector®

Excellent for all outboard motors with a performance emphasis on modern direct-fuel-injected (DFI) technology. Also recommended for personal watercraft, jet boats, motorcycles, snowmobiles and ATVs. Injector use or 50:1 pre-mix.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
hp Injector Synthetic 2-Cycle Oil						
HPIQT	-FA	1 Quart	2.0	6.85	--	8.90
HPIQT	-CA	12 Quarts	24.0	78.15	6.51	105.55
HPI1G	-FA	1 Gallon	7.9	26.75	--	34.80
HPI1G	-CA	4 Gallons	31.6	101.80	25.45	137.45
HPI16	-FA	16-Gallon Keg*	131.0	396.00	--	506.90
HPI30	-FA	30-Gallon Drum*	241.0	696.00	--	870.00
HPI55	-FA	55-Gallon Drum*	432.0	1,226.50	--	1,508.60
HPI27	-FA	275-Gallon Tote*	2,087.0	6,105.00	--	7,509.15

DOMINATOR®

Premier two-cycle racing oil with a performance emphasis toward high-horsepower and modified racing or trail motors. Examples include snowmobiles, motorcycles, ATVs, personal watercraft, go-carts or outboard racing motors that are periodically inspected. Contains higher-viscosity base oils for best overall protection. Contains additives designed for higher operating temperatures. Injector use or 50:1 pre-mix.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
DOMINATOR Synthetic 2-Cycle Racing Oil						
TDRQT	-FA	1 Quart	2.1	7.80	--	10.15
TDRQT	-CA	12 Quarts	25.2	89.10	7.43	120.30
TDR1G	-FA	1 Gallon	8.2	30.60	--	39.70
TDR1G	-CA	4 Gallons	32.8	116.40	29.10	157.15
TDR16	-FA	16-Gallon Keg*	135.0	454.40	--	581.65
TDR30	-FA	30-Gallon Drum*	249.0	805.50	--	1,006.90
TDR55	-FA	55-Gallon Drum*	447.0	1,427.25	--	1,755.55

INTERCEPTOR®

A high-performance two-cycle oil with a performance emphasis on exhaust power valves. Excellent for all types of snowmobiles, motorcycles, personal watercraft, ATVs and jet boats. Contains high levels of detergent additives to prevent valve sticking. High-quality replacement for manufacturer-branded oils. Injector use or 50:1 pre-mix.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
INTERCEPTOR Synthetic 2-Cycle Oil						
AITQT	-FA	1 Quart	2.1	7.80	--	10.15
AITQT	-CA	12 Quarts	25.2	89.10	7.43	120.30
AIT1G	-FA	1 Gallon	8.2	30.60	--	39.70
AIT1G	-CA	4 Gallons	32.8	116.40	29.10	157.15
AIT16	-FA	16-Gallon Keg*	136.0	454.40	--	581.65
AIT30	-FA	30-Gallon Drum*	251.0	805.50	--	1,006.90
AIT55	-FA	55-Gallon Drum*	451.0	1,427.25	--	1,755.55
AIT27	-FA	275-Gallon Tote*	2,176.0	7,108.75	--	8,743.80

- Performance Specifications:**
- TC-W3
 - API TC
- (Injection or 50:1 pre-mix)



- Performance Specifications:**
- API TC
 - JASO FC



- Performance Specifications:**
- API TC
 - JASO FC



TRANSMISSION FLUID

TWO-CYCLE OILS

TWO-CYCLE OILS

- Performance Specifications:**
- ISO-L-EGD
 - JASO FD, FC
 - API TC



Saber® Synthetic 100:1 Pre-Mix 2-Cycle Oils

Designed for pre-mix applications as lean as 100:1 ratios. Richer mix ratios may be used where desired. Saber oils are designed to improve throttle response, reduce or eliminate smoke, minimize deposit formation and reduce emissions. Saber Professional has a performance emphasis on hand-held power equipment such as chainsaws and lawn/utility equipment. Saber Outboard has a performance emphasis on the cooler operations of water-cooled motors.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Saber Professional Synthetic 100:1 Pre-Mix 2-Cycle Oil						
ATPPK	-FA	(1) 1.5-oz. Pack	0.1	1.00	--	1.45
ATPPK	-CA	(48) 1.5-oz. Packs	5.1	43.58	0.91	65.45
ATPBA	-FA	(1) 3.5-oz. Bottle	0.4	1.75	--	2.40
ATPBA	-CA	(12) 3.5-oz. Bottles	4.8	19.49	1.62	27.30
ATPBC	-FA	(1) 8-oz. Bottle	0.7	3.20	--	4.30
ATPBC	-CA	(12) 8-oz. Bottles	8.4	36.23	3.02	50.00
ATPQT	-FA	1 Quart	2.1	8.30	--	10.75
ATPQT	-CA	12 Quarts	25.2	94.65	7.89	127.80
ATP30	-FA	30-Gallon Drum*	250.0	861.00	--	1,076.25
ATP55	-FA	55-Gallon Drum*	449.0	1,529.00	--	1,880.70

CHAINCASE OIL

- Performance Specifications:**
- TC-W3 (pre-mix)
 - API TC



Saber Outboard Synthetic 100:1 Pre-Mix 2-Cycle Oil

ATOBC	-FA	(1) 8-oz. Bottle	0.7	3.35	--	4.45
ATOBC	-CA	(12) 8-oz. Bottles	8.4	37.73	3.14	52.10
ATOQT	-FA	1 Quart	2.2	8.85	--	11.45
ATOQT	-CA	12 Quarts	26.4	100.65	8.39	135.90
ATO30	-FA	30-Gallon Drum*	252.0	921.00	--	1,151.25
ATO55	-FA	55-Gallon Drum*	453.0	1,639.00	--	2,016.00

Series 2000 Synthetic Chaincase Oil

Provides superior protection and performance for enclosed chains. Ideal for snowmobiles, ATVs and general equipment. Extreme-pressure additives provide extra wear protection. Extends chain life, repels water and inhibits rust, oxidation and foam. Superior low-temperature performance and protection.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Series 2000 Synthetic Chaincase Oil						
TCCBE	-FA	(1) 12-oz. Bottle	0.8	4.95	--	6.80
TCCBE	-CA	(6) 12-oz. Bottles	4.8	28.13	4.69	39.95
TCC05	-FA	5-Gallon Pail	32.4	141.25	--	187.90

BAR & CHAIN OIL



Semi-Synthetic Bar and Chain Oil

Tacky formula clings to metal surfaces better than other oils. Delivers excellent lubrication and protection. Anti-wear additives extend the life of bar and chain applications. Ideal for chainsaws.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Semi-Synthetic Bar and Chain Oil						
ABCQT	-FA	1 Quart	2.1	4.30	--	5.60
ABCQT	-CA	12 Quarts	25.2	48.60	4.05	65.65
ABC1G	-FA	1 Gallon	8.1	16.50	--	21.60
ABC1G	-CA	4 Gallons	32.4	62.80	15.70	84.80
ABC05	-FA	5-Gallon Pail	39.2	76.00	--	101.10
ABC55	-FA	55-Gallon Drum*	436.2	679.25	--	835.50

GREASE

- Performance Specifications:**
- NLGI #2
 - GC/LB



Series 2000 Synthetic Racing Grease

Exceptional protection for hard-driven, high-performance vehicles. Dramatically reduces friction and wear for improved performance. Excels at both high- and low-temperature performance. Outperforms other conventional and synthetic greases.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Series 2000 Synthetic Racing Grease						
GRGCR	-FA	(1) 14-oz. Cartridge	1.0	9.14	--	12.75
GRGCR	-CA	(10) 14-oz. Cartridges	10.0	88.81	8.88	122.60
GRGCR	-PK	(40) 14-oz. Cartridges	40.0	346.50	8.66	467.80
GRG35	-FA	35-lb. Lug*	40.0	309.26	--	402.05
GRG99	-FA	120-lb. Keg*	132.0	942.00	--	1,205.80

Synthetic Polymeric Off-Road Grease

Extreme-pressure, moly-fortified. Provides outstanding protection for steering knuckles, spring shackles, heavy equipment pivot joints and other components operating in high-load, low-speed conditions. NLGI #1 is preferred for cold temperatures. Offers excellent water washout resistance. Synthetic polymeric technology delivers tenacious cling ability and maximum pound-out resistance over extended service intervals.

- Performance Specifications:**
- NLGI #2, #1
 - 5% Moly



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Polymeric Off-Road Grease NLGI #2						
GPOR2CR	-FA	(1) 15-oz. Cartridge	1.0	6.94	--	9.65
GPOR2CR	-CA	(10) 15-oz. Cartridges	10.0	68.44	6.84	92.40
GPOR2CR	-PK	(40) 15-oz. Cartridges	40.0	270.00	6.75	364.50
GPOR235	-FA	35-lb. Lug*	40.0	234.50	--	304.85
GPOR299	-FA	120-lb. Keg*	132.0	780.00	--	998.40
GPOR240	-FA	400-lb. Drum*	415.0	2,520.00	--	3,099.60

*Not stocked in all distribution centers. Call for availability.

†Product cannot be shipped air freight or parcel post.



Synthetic Polymeric Off-Road Grease NLGI #1

GPOR1CR	-FA	(1) 15-oz. Cartridge	1.0	6.66	--	9.30
GPOR1CR	-CA	(10) 15-oz. Cartridges	10.0	65.63	6.56	88.60
GPOR1CR	-PK	(40) 15-oz. Cartridges	40.0	258.75	6.47	349.35
GPOR135	-FA	35-lb. Lug*	40.0	224.00	--	291.20
GPOR199	-FA	120-lb. Keg*	132.0	744.00	--	952.35
GPOR140	-FA	400-lb. Drum*	415.0	2,400.00	--	2,952.00

Performance Specifications:
• NLGI #2, #1



Synthetic Polymeric Truck, Chassis and Equipment Grease

Delivers excellent wear protection and performance in the severe-service, extreme-pressure environments faced by medium- and heavy-duty over-the-road trucks and equipment. Clings tenaciously to metal surfaces and delivers maximum impact/pound-out resistance, staying in place to seal out water and contaminants and provide a protective barrier between metal components. Extended service life reduces the need for frequent re-application (or requires less grease at each servicing), reducing maintenance costs and increasing equipment life.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Polymeric Truck, Chassis and Equipment Grease NLGI #2						
GPTR2CR	-FA	(1) 14-oz. Cartridge	1.0	5.86	--	8.15
GPTR2CR	-CA	(10) 14-oz. Cartridges	10.0	57.75	5.78	78.00
GPTR2CR	-PK	(40) 14-oz. Cartridges	40.0	227.50	5.69	307.15
GPTR235	-FA	35-lb. Lug*	40.0	210.00	--	273.00
GPTR299	-FA	120-lb. Keg*	132.0	696.00	--	890.90
GPTR240	-FA	400-lb. Drum*	415.0	2,240.00	--	2,755.20



Synthetic Polymeric Truck, Chassis and Equipment Grease NLGI #1

GPTR1CR	-FA	(1) 14-oz. Cartridge	1.0	5.69	--	7.95
GPTR1CR	-CA	(10) 14-oz. Cartridges	10.0	56.00	5.60	75.60
GPTR1CR	-PK	(40) 14-oz. Cartridges	40.0	220.50	5.51	297.70
GPTR135	-FA	35-lb. Lug*	40.0	203.00	--	263.90
GPTR199	-FA	120-lb. Keg*	132.0	672.00	--	860.20
GPTR140	-FA	400-lb. Drum*	415.0	2,160.00	--	2,656.80



Synthetic Multi-Purpose Grease

Reduces friction and wear in high-speed, high-temperature components such as automotive wheel bearings and electric motors. Helps keep components running clean and trouble-free for outstanding performance and long life. NLGI #0 and NLGI #1 greases have better mobility and are preferred for cold temperatures and automatic pump systems. NLGI #0 is not recommended for automotive wheel bearings. NLGI #2 is the primary wheel bearing recommendation.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Multi-Purpose Grease NLGI #2						
GLCTB	-FA	(1) 8-oz. Tube	0.7	4.59	--	6.40
GLCTB	-CA	(12) 8-oz. Tubes	8.4	54.52	4.54	75.25
GLCCR	-FA	(1) 14-oz. Cartridge	1.0	5.41	--	7.55
GLCCR	-CA	(10) 14-oz. Cartridges	10.0	51.50	5.15	71.10
GLCCR	-PK	(40) 14-oz. Cartridges	40.0	197.26	4.93	266.35
GLC35	-FA	35-lb. Lug*	40.0	167.51	--	217.80
GLC99	-FA	120-lb. Keg*	132.0	532.32	--	681.40
GLC40	-FA	400-lb. Drum*	415.0	1,714.40	--	2,108.75

Performance Specifications:
• NLGI #2
• GC/LB



Synthetic Multi-Purpose Grease NLGI #1

GLBCR	-FA	(1) 14-oz. Cartridge	1.0	5.41	--	7.55
GLBCR	-CA	(10) 14-oz. Cartridges	10.0	51.50	5.15	71.10
GLBCR	-PK	(40) 14-oz. Cartridges	40.0	197.26	4.93	266.35
GLB35	-FA	35-lb. Lug*	40.0	167.51	--	217.80
GLB99	-FA	120-lb. Keg*	132.0	532.32	--	681.40
GLB40	-FA	400-lb. Drum*	415.0	1,714.40	--	2,108.75

Performance Specifications:
• NLGI #1
• GC/LB



Synthetic Multi-Purpose Grease NLGI #0

GLA35	-FA	35-lb. Lug*	40.0	167.51	--	217.80
GLA99	-FA	120-lb. Keg*	132.0	532.32	--	681.40
GLA40	-FA	400-lb. Drum*	415.0	1,714.40	--	2,108.75

Performance Specifications:
• NLGI #0



Synthetic Multi-Purpose Spray Grease

The same great AMSOIL Synthetic Multi-Purpose Grease in a convenient spray formulation. Ideal for greasing hard-to-reach equipment such as hinges, springs and other common applications.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Multi-Purpose Spray Grease						
GLCSC	-FA	(1) 10.5-oz. Spray Can†	1.0	5.96	--	8.30
GLCSC	-CA	(12) 10.5-oz. Spray Cans†	12.0	69.19	5.77	95.50

Performance Specifications:
• NLGI #2

GREASE

GREASE

- Performance Specifications:**
- NLGI #2
 - GC/LB



Synthetic Water Resistant Grease

Resists water washout and degradation. Maximum protection for boat trailer wheel bearings and other components frequently exposed to water. Stays in place, lubricates and protects against rust.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Water Resistant Grease						
GWRCR	-FA	(1) 14-oz. Cartridge	1.0	5.82	--	8.10
GWRCR	-CA	(10) 14-oz. Cartridges	10.0	55.56	5.56	76.70
GWRCR	-PK	(40) 14-oz. Cartridges	40.0	213.50	5.34	288.25
GWR35	-FA	35-lb. Lug*	40.0	183.75	--	238.90
GWR99	-FA	120-lb. Keg*	132.0	582.00	--	745.00

- Performance Specifications:**
- NLGI #2



Synthetic High Viscosity Lithium Complex Grease

Lithium-complex-thickened grease blended with premium ISO 320 base oils. Fully compounded with additives providing EP protection, oxidation resistance and rust and corrosion protection. Excellent for use in heavy-duty industrial and off-road applications where equipment is working under adverse conditions such as exposure to environmental elements, slow, heavily loaded applications and shock-loading conditions.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic High Viscosity Lithium Complex Grease						
GVCCR	-CA	(10) 14-oz. Cartridges	10.0	55.56	5.56	76.70
GVCCR	-PK	(40) 14-oz. Cartridges	40.0	213.50	5.34	288.25
GVC35	-FA	35-lb. Lug*	40.0	183.75	--	238.90
GVC99	-FA	120-lb. Keg*	132.0	582.00	--	745.00
GVC40	-FA	400-lb. Drum*	415.0	1,860.00	--	2,287.80

- Performance Specifications:**
- NLGI #00

Semi-Fluid 00 Synthetic EP Grease

Formulated with high-viscosity ISO 460 base oils and a sophisticated additive package to provide exceptional protection against wear. Ideal for leaky gear boxes in industrial and fleet applications, centralized lubrication systems and for use in applications that are difficult to service. Primarily used in grease-filled cases where conventional semi-fluid greases do not provide adequate lubricant life or protection. Replaces Mobil SHC 007.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Semi-Fluid 00 Synthetic EP Grease						
GSE35	-FA	35-lb. Lug*	40.0	289.80	--	376.75
GSE99	-FA	120-lb. Keg*	132.0	945.60	--	1,210.40
GSE40	-FA	400-lb. Drum*	415.0	3,072.00	--	3,778.60

- Performance Specifications:**
- USDA H-1
 - NLGI #2
 - High-Temperature EP



X-Treme Synthetic Food Grade Grease

An ultra-premium lubricant designed for high levels of protection in food and pharmaceutical industry equipment. Former USDA H-1 rated for incidental contact with food. Controls seal leakage.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
X-Treme Synthetic Food Grade Grease						
GXCCR	-FA	(1) 14-oz. Cartridge	1.0	7.09	--	9.90
GXCCR	-CA	(10) 14-oz. Cartridges	10.0	68.25	6.83	94.20
GXCCR	-PK	(40) 14-oz. Cartridges	40.0	264.25	6.61	356.75
GXC35	-FA	35-lb. Lug*	40.0	234.50	--	304.85
GXC99	-FA	120-lb. Keg*	132.0	756.00	--	967.70
GXC40	-FA	400-lb. Drum*	415.0	2,440.00	--	3,001.20

Synthetic Tractor Hydraulic/Transmission Oil

Formulated for combinations of transmission, hydraulic systems, final drives, power take-off systems and wet brakes. Engineered specifically to meet the tough applications of heavy-duty farm and industrial equipment as well as commercial and residential lawn tractors. Exceeds the demanding all-weather specifications of both Case New Holland 3526 & 3525 (formerly Ford New Holland FNHA-2-C-200 & 2-C-201) and John Deere J20C & J20D, as well as most other tractor hydraulic transmissions. Eliminates the need for seasonal oil changes. Ideal for lawn tractor hydrostatic transmissions.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Tractor Hydraulic/Transmission Oil						
ATHQT	-FA	1 Quart	2.1	7.60	--	9.85
ATHQT	-CA	12 Quarts	25.2	86.40	7.20	116.65
ATH05	-FA	5-Gallon Pail	39.0	139.00	--	184.90
ATH30	-FA	30-Gallon Drum*	242.1	778.50	--	973.15
ATH55	-FA	55-Gallon Drum*	434.2	1,377.75	--	1,694.65
ATH27	-FA	275-Gallon Tote*	2,095.8	6,861.25	--	8,439.35

Synthetic Anti-Wear Hydraulic Oil

Protects hard-working hydraulic systems from the stress of high-pressure, high-load and heavy-duty operations. Engineered to remain fluid in cold temperatures for immediate cold-weather flow. Special anti-wear additives and rust inhibitors provide optimum protection to expensive equipment.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Anti-Wear Hydraulic Oil - ISO 15						
AWF05	-FA	5-Gallon Pail	37.7	163.50	--	217.50
AWF55	-FA	55-Gallon Drum*	419.9	1,647.25	--	2,026.15
AWF27	-FA	275-Gallon Tote*	2,024.6	8,208.75	--	10,096.80

- Recommended For:**
- Denison HF-0, HF-1, HF-2
 - Vickers M-2950-S & I-286-S
 - Cincinnati Milacron P-68, P-69, P-70
 - MEHF
 - Many Others

HYDRAULIC OILS



Synthetic Anti-Wear Hydraulic Oil - ISO 22

AWG05	-FA	5-Gallon Pail	38.0	152.00	--	202.20
AWG55	-FA	55-Gallon Drum*	422.8	1,520.75	--	1,870.55

Synthetic Anti-Wear Hydraulic Oil - ISO 32

AWH05	-FA	5-Gallon Pail	38.9	137.25	--	182.55
AWH30	-FA	30-Gallon Drum*	241.3	768.00	--	960.00
AWH55	-FA	55-Gallon Drum*	432.7	1,358.50	--	1,671.00
AWH27	-FA	275-Gallon Tote*	2,088.4	6,765.00	--	8,320.95

Synthetic Anti-Wear Hydraulic Oil - ISO 46

AWI05	-FA	5-Gallon Pail	38.9	142.25	--	189.20
AWI55	-FA	55-Gallon Drum*	432.9	1,413.50	--	1,738.65
AWI27	-FA	275-Gallon Tote*	2,089.5	7,040.00	--	8,659.20

Synthetic Anti-Wear Hydraulic Oil - ISO 68

AWJ05	-FA	5-Gallon Pail	39.1	145.75	--	193.85
AWJ55	-FA	55-Gallon Drum*	434.8	1,452.00	--	1,786.00
AWJ27	-FA	275-Gallon Tote*	2,098.9	7,232.50	--	8,896.00

Synthetic Biodegradable Hydraulic Oil

A premium lubricant designed to biodegrade to its natural state when subjected to sunlight, water and microbial activity. Very low toxicity level because it is formulated with ashless additives that do not contain heavy metals. Recommended for gear, vane and piston stationary and mobile hydraulic systems. Multi-viscosity, SAE 5W-20 oil recommended for use in place of either ISO 32 or ISO 46 hydraulic oils.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Biodegradable Hydraulic Oil ISO 46						
BH005	-FA	5-Gallon Pail	43.0	186.75	--	248.40
BH055	-FA	55-Gallon Drum*	468.0	1,903.00	--	2,340.70
BH027	-FA	275-Gallon Tote*	2,264.0	9,487.50	--	11,669.65

Synthetic Compressor Oil

The correct manufacturer-recommended viscosity grade of AMSOIL PC Series Compressor Oil is recommended for use in rotary screw, rotary vane, reciprocating and other compressor applications. Compatible with PAO-, ester- and petroleum-based compressor oils. Not compatible with glycol- or silicone-based compressor oils. Consult AMSOIL INC. for further information.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
Synthetic Compressor Oil - ISO 32, SAE 10W						
PCH05	-FA	5-Gallon Pail	38.4	151.75	--	201.85
PCH55	-FA	55-Gallon Drum*	427.2	1,512.50	--	1,860.40
PCH27	-FA	275-Gallon Tote*	2,060.9	7,535.00	--	9,268.05
Synthetic Compressor Oil - ISO 46, SAE 20						
PCIQT	-FA	1 Quart	2.0	8.35	--	10.85
PCIQT	-CA	12 Quarts	24.0	95.25	7.94	128.60
PCI05	-FA	5-Gallon Pail	38.4	153.75	--	204.50
PCI30	-FA	30-Gallon Drum*	238.3	867.00	--	1,083.75
PCI55	-FA	55-Gallon Drum*	427.3	1,534.50	--	1,887.45
PCI27	-FA	275-Gallon Tote*	2,061.5	7,645.00	--	9,403.35

Synthetic Compressor Oil - ISO 68, SAE 30

PCJ05	-FA	5-Gallon Pail	39.0	157.25	--	209.15
PCJ55	-FA	55-Gallon Drum*	429.4	1,573.00	--	1,934.80
PCJ27	-FA	275-Gallon Tote*	2,072.2	7,837.50	--	9,640.15

Synthetic Compressor Oil - ISO 100, SAE 40

PCKQT	-FA	1 Quart	2.1	8.85	--	11.45
PCKQT	-CA	12 Quarts	25.2	100.65	8.39	135.90
PCK05	-FA	5-Gallon Pail	38.8	162.75	--	216.50
PCK30	-FA	30-Gallon Drum*	240.8	921.00	--	1,151.25
PCK55	-FA	55-Gallon Drum*	431.8	1,633.50	--	2,009.25
PCK27	-FA	275-Gallon Tote*	2,084.0	8,140.00	--	10,012.20

Synthetic Compressor Oil - ISO 150, SAE 50

PCL05	-FA	5-Gallon Pail	39.0	169.25	--	225.15
PCL55	-FA	55-Gallon Drum*	434.2	1,705.00	--	2,097.15

SIROCCO® Synthetic Compressor Oil

SIROCCO is recommended as a direct replacement for PAG compressor oils such as Sullair Sullube 32 and Ingersoll-Rand SSR Ultra Coolant. Not recommended for use with silicone base fluids. Consult AMSOIL for further information.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
SIROCCO Synthetic Compressor Oil - ISO 32/46 SAE 5W-20						
SEI05	-FA	5-Gallon Pail	42.0	210.75	--	280.30
SEI55	-FA	55-Gallon Drum*	466.0	2,161.50	--	2,658.65
SEI27	-FA	275-Gallon Tote*	2,257.0	10,780.00	--	13,259.40

Performance Specifications:

- Vickers M-2950-S & I-286-S
- 95% Biodegradable (CEC L-33-T-93)
- ISO 46

Performance Specifications:

- Vickers I-286-S, M-2950-S
- Denison HF-0, HF-1, HF-2



Performance Specifications:


- ISO 32/46
- Denison HF-0, HF-1, HF-2

HYDRAULIC OILS

COMPRESSOR OILS

Ea® Air Filters

AMSOIL has brought nanofiber technology to the auto/light-truck market. Hold 15 times more dust than wet gauze-type filters. Remove 5 times more dust than traditional cellulose filters and 50 times more dust than wet gauze. Provide outstanding filtration and have an unmatched 4-year/100,000-mile guarantee. Available individually or in cases of six.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
AAA04	-EA	(1) Filter	0.9	26.00	34.15
AAA04	-CA	(6) Filters	5.4	145.20	190.80
AAA08	-EA	(1) Filter	1.0	29.00	38.10
AAA08	-CA	(6) Filters	6.0	162.00	213.00
AAA22	-EA	(1) Filter	0.9	22.50	29.55
AAA22	-CA	(6) Filters	5.4	125.70	165.30
AAA23	-EA	(1) Filter	1.1	22.50	29.55
AAA23	-CA	(6) Filters	6.6	125.70	165.30
AAA24	-EA	(1) Filter	0.9	26.00	34.15
AAA24	-CA	(6) Filters	5.4	145.20	190.80
AAA25	-EA	(1) Filter	2.1	29.00	38.10
AAA25	-CA	(6) Filters	12.6	162.00	213.00
AAA29	-EA	(1) Filter	1.0	29.00	38.10
AAA29	-CA	(6) Filters	6.0	162.00	213.00
AAA32	-EA	(1) Filter	1.1	22.50	29.55
AAA32	-CA	(6) Filters	6.6	125.70	165.30
AAA47	-EA	(1) Filter	0.6	22.50	29.55
AAA47	-CA	(6) Filters	3.6	125.70	165.30
AAA49	-EA	(1) Filter	0.8	26.00	34.15
AAA49	-CA	(6) Filters	4.8	145.20	190.80
AAA51	-EA	(1) Filter	1.9	29.00	38.10
AAA51	-CA	(6) Filters	11.4	162.00	213.00
AAA52	-EA	(1) Filter	1.9	29.00	38.10
AAA52	-CA	(6) Filters	11.4	162.00	213.00
AAA74	-EA	(1) Filter	0.8	26.00	34.15
AAA74	-CA	(6) Filters	4.8	145.20	190.80
AAA81	-EA	(1) Filter	0.7	22.50	29.55
AAA81	-CA	(6) Filters	4.2	125.70	165.30
AAA82	-EA	(1) Filter	0.7	22.50	29.55
AAA82	-CA	(6) Filters	4.2	125.70	165.30
AAA83	-EA	(1) Filter	1.3	36.15	47.45
AAA83	-CA	(6) Filters	7.8	201.90	265.20
AAA86	-EA	(1) Filter	0.6	22.50	29.55
AAA86	-CA	(6) Filters	3.6	125.70	165.30
AAA87	-EA	(1) Filter	0.6	22.50	29.55
AAA87	-CA	(6) Filters	3.6	125.70	165.30
AAA88	-EA	(1) Filter	0.7	26.00	34.15
AAA88	-CA	(6) Filters	4.2	145.20	190.80
AAA101	-EA	(1) Filter	0.9	26.00	34.15
AAA101	-CA	(6) Filters	5.4	145.20	190.80
AAA103	-EA	(1) Filter	2.5	45.00	59.10
AAA103	-CA	(6) Filters	15.0	251.10	330.00
AAA104	-EA	(1) Filter	1.2	36.15	47.45
AAA104	-CA	(6) Filters	7.2	201.90	265.20
AAA106	-EA	(1) Filter	1.9	36.15	47.45
AAA106	-CA	(6) Filters	11.4	201.90	265.20
AAA111	-EA	(1) Filter	2.3	45.00	59.10
AAA111	-CA	(6) Filters	13.8	251.10	330.00
AAA112	-EA	(1) Filter	2.8	45.00	59.10
AAA112	-CA	(6) Filters	16.8	251.10	330.00
AAA118	-EA	(1) Filter	1.3	29.00	38.10
AAA118	-CA	(6) Filters	7.8	162.00	213.00
AAA121	-EA	(1) Filter	1.8	36.15	47.45
AAA121	-CA	(6) Filters	10.8	201.90	265.20
AAA122	-EA	(1) Filter	1.1	29.00	38.10
AAA122	-CA	(6) Filters	6.6	162.00	213.00
AAA123	-EA	(1) Filter	1.7	36.15	47.45
AAA123	-CA	(6) Filters	10.2	201.90	265.20
AAA124	-EA	(1) Filter	0.8	29.00	38.10
AAA124	-CA	(6) Filters	4.8	162.00	213.00
AAA127	-EA	(1) Filter	0.8	26.00	34.15
AAA127	-CA	(6) Filters	4.8	145.20	190.80
AAA128	-EA	(1) Filter	1.1	29.00	38.10
AAA128	-CA	(6) Filters	6.6	162.00	213.00
AAA129	-EA	(1) Filter	1.1	26.00	34.15
AAA129	-CA	(6) Filters	6.6	145.20	190.80
AAA170	-EA	(1) Filter	1.0	26.00	34.15
AAA170	-CA	(6) Filters	6.0	145.20	190.80
AAA176	-EA	(1) Filter	1.5	36.15	47.45
AAA176	-CA	(6) Filters	9.0	201.90	265.20
AAA191	-EA	(1) Filter	1.1	29.00	38.10
AAA191	-CA	(6) Filters	6.6	162.00	213.00
AAA200	-EA	(1) Filter	1.0	29.00	38.10
AAA200	-CA	(6) Filters	6.0	162.00	213.00
AAA201	-EA	(1) Filter	0.8	29.00	38.10
AAA201	-CA	(6) Filters	4.8	162.00	213.00
AAA202	-EA	(1) Filter	0.8	22.50	29.55
AAA202	-CA	(6) Filters	4.8	125.70	165.30

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
AAA203	-EA	(1) Filter	1.9	36.15	47.45
AAA203	-CA	(6) Filters	11.4	201.90	265.20
AAA204	-EA	(1) Filter	1.5	36.15	47.45
AAA204	-CA	(6) Filters	9.0	201.90	265.20
AAA205	-EA	(1) Filter	1.2	26.00	34.15
AAA205	-CA	(6) Filters	7.2	145.20	190.80
AAA206	-EA	(1) Filter	0.9	26.00	34.15
AAA206	-CA	(6) Filters	5.4	145.20	190.80
AAA207	-EA	(1) Filter	1.0	26.00	34.15
AAA207	-CA	(6) Filters	6.0	145.20	190.80
AAA208	-EA	(1) Filter	1.0	26.00	34.15
AAA208	-CA	(6) Filters	6.0	145.20	190.80
AAA209	-EA	(1) Filter	1.0	36.15	47.45
AAA209	-CA	(6) Filters	6.0	201.90	265.20
AAA210	-EA	(1) Filter	0.9	29.00	38.10
AAA210	-CA	(6) Filters	5.4	162.00	213.00
AAA211	-EA	(1) Filter	1.3	36.15	47.45
AAA211	-CA	(6) Filters	7.8	201.90	265.20
AAA212	-EA	(1) Filter	1.0	29.00	38.10
AAA212	-CA	(6) Filters	6.0	162.00	213.00
AAA214	-EA	(1) Filter	0.8	29.00	38.10
AAA214	-CA	(6) Filters	4.8	162.00	213.00
AAA215	-EA	(1) Filter	2.5	36.15	47.45
AAA215	-CA	(6) Filters	15.0	201.90	265.20
AAA216	-EA	(1) Filter	1.6	36.15	47.45
AAA216	-CA	(6) Filters	9.6	201.90	265.20
AAA217	-EA	(1) Filter	0.8	36.15	47.45
AAA217	-CA	(6) Filters	4.8	201.90	265.20
AAA218	-EA	(1) Filter	0.5	36.15	47.45
AAA218	-CA	(6) Filters	3.0	201.90	265.20
AAA219	-EA	(1) Filter	0.5	29.00	38.10
AAA219	-CA	(6) Filters	3.0	162.00	213.00
AAA220	-EA	(1) Filter	0.5	29.00	38.10
AAA220	-CA	(6) Filters	3.0	162.00	213.00
AAA221	-EA	(1) Filter	1.0	29.00	38.10
AAA221	-CA	(6) Filters	6.0	162.00	213.00
AAA222	-EA	(1) Filter	1.0	36.15	47.45
AAA222	-CA	(6) Filters	6.0	201.90	265.20
AAA223	-EA	(1) Filter	0.3	36.15	47.45
AAA223	-CA	(6) Filters	1.8	201.90	265.20
AAA224	-EA	(1) Filter	0.4	29.00	38.10
AAA224	-CA	(6) Filters	2.4	162.00	213.00
AAA225	-EA	(1) Filter	0.5	29.00	38.10
AAA225	-CA	(6) Filters	3.0	162.00	213.00
AAA226	-EA	(1) Filter	0.9	36.15	47.45
AAA226	-CA	(6) Filters	5.4	201.90	265.20
AAA227	-EA	(1) Filter	0.2	36.15	47.45
AAA227	-CA	(6) Filters	1.2	201.90	265.20
AAA228	-EA	(1) Filter	0.8	26.00	34.15
AAA228	-CA	(6) Filters	4.8	145.20	190.80
AAA229	-EA	(1) Filter	0.8	22.50	29.55
AAA229	-CA	(6) Filters	4.8	125.70	165.30
AAA232	-EA	(1) Filter	1.0	22.50	29.55
AAA232	-CA	(6) Filters	6.0	125.70	165.30
AAA233	-EA	(1) Filter	0.2	22.50	29.55
AAA233	-CA	(6) Filters	1.2	125.70	165.30
AAA234	-EA	(1) Filter	1.0	22.50	29.55
AAA234	-CA	(6) Filters	6.0	125.70	165.30
AAA237	-EA	(1) Filter	0.2	26.00	34.15
AAA237	-CA	(6) Filters	1.2	145.20	190.80
AAA238	-EA	(1) Filter	1.0	26.00	34.15
AAA238	-CA	(6) Filters	6.0	145.20	190.80
AAA239	-EA	(1) Filter	0.9	22.50	29.55
AAA239	-CA	(6) Filters	5.4	125.70	165.30
AAA240	-EA	(1) Filter	4.5	26.00	34.15
AAA240	-CA	(6) Filters	27.0	145.20	190.80
AAA289	-EA	(1) Filter	0.9	29.00	38.10
AAA289	-CA	(6) Filters	5.4	162.00	213.00
AAA419	-EA	(1) Filter	0.9	29.00	38.10
AAA419	-CA	(6) Filters	5.4	162.00	213.00
AAA484	-EA	(1) Filter	1.0	29.00	38.10
AAA484	-CA	(6) Filters	6.0	162.00	213.00
AAA524	-EA	(1) Filter	0.7	26.00	34.15
AAA524	-CA	(6) Filters	4.2	145.20	190.80
AAA728	-EA	(1) Filter	1.7	36.15	47.45
AAA728	-CA	(6) Filters	10.2	201.90	265.20

EA® AIR FILTERS



Ea® Universal Air Induction Filters

Designed to replace stock oil-wetted gauze or foam conical filters that were supplied with custom induction systems produced by K&N, Injen, S&B, Green, AIRAID, AFE, TrueFlow and more. Offer better efficiency, excellent airflow and are cleanable.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
EAAU3050	-FA	(1) EaAU Filter	1.5	36.75	49.05
EAAU3051	-FA	(1) EaAU Filter	1.4	36.75	49.05
EAAU3090	-FA	(1) EaAU Filter	1.5	51.75	69.05
EAAU3555	-FA	(1) EaAU Filter	1.3	45.75	61.05
EAAU3560	-FA	(1) EaAU Filter	1.6	38.50	51.35
EAAU3570	-FA	(1) EaAU Filter	1.3	42.00	56.05
EAAU3590	-FA	(1) EaAU Filter	1.6	51.75	69.05
EAAU4070	-FA	(1) EaAU Filter	1.4	45.75	61.05
EAAU4075	-FA	(1) EaAU Filter	2.0	46.50	62.05
EAAU4090	-FA	(1) EaAU Filter	1.6	47.25	63.05
EAAU4091	-FA	(1) EaAU Filter	3.6	69.50	92.70
EAAU4095	-FA	(1) EaAU Filter	2.2	49.50	66.05
EAAU4178	-FA	(1) EaAU Filter	2.5	51.75	69.05
EAAU4510	-FA	(1) EaAU Filter	2.8	57.00	76.05
EAAU4560	-FA	(1) EaAU Filter	1.5	38.50	51.35
EAAU6065	-FA	(1) EaAU Filter	1.8	45.00	60.05
EAAU6075	-FA	(1) EaAU Filter	1.8	49.50	66.05
EAAU6080	-FA	(1) EaAU Filter	1.7	51.00	68.05
EAAU6081	-FA	(1) EaAU Filter	1.7	49.50	66.05

Ea® Racing Air Filters

Specially designed for racing and street rod enthusiasts who desire Ea protection in carbureted applications. Custom assemblies designed for use with carbureted engines that use a 14" round element air cleaner housing. Cleanable and reusable. Kits feature the common 14" diameter carburetor plate, filter and high-airflow lid. Kits are available with 2", 3", 4", 5" or 6"-high filters. Replacement filters, airflow lids and carburetor plates are also available for purchase separately.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
Ea Racing Air Filters (Contain Filter, Base & Lid)					
EAAAR31	-FA	(1) Replacement Filter	4.7	51.00	68.05
EAAAR2102	-FA	(1) Kit - 14" Dia. 2 3/4" Ht.	4.7	97.00	129.35
EAAAR2103	-FA	(1) Kit - 14" Dia. 3 5/8" Ht.	5.0	97.00	129.35
EAAAR2104	-FA	(1) Kit - 14" Dia. 4 11/16" Ht.	5.3	97.00	129.35
EAAAR2105	-FA	(1) Kit - 14" Dia. 5 11/16" Ht.	5.6	102.00	136.05
EAAAR2106	-FA	(1) Kit - 14" Dia. 6 7/8" Ht.	5.9	102.00	136.05
EAAAR2140	-FA	(1) Replacement Base	1.0	38.50	51.35
EAAAR2141	-FA	(1) Replacement Lid	1.7	52.00	69.35
EAAAR2142	-FA	(1) Replacement Filter 2" Ht.	2.0	38.50	51.35
EAAAR2143	-FA	(1) Replacement Filter 3" Ht.	2.3	38.50	51.35
EAAAR2144	-FA	(1) Replacement Filter 4" Ht.	2.6	38.50	51.35
EAAAR2145	-FA	(1) Replacement Filter 5" Ht.	2.9	40.50	54.05
EAAAR2146	-FA	(1) Replacement Filter 6" Ht.	3.2	40.50	54.05

AMSOIL/Injen Power-Flow Gasoline and Diesel Air Intake Systems

Increase the amount of oxygen available to the engine and reduce air turbulence, resulting in increased power. Improve combustion of fuel by capturing cooler air from outside the engine compartment. AMSOIL designed, developed and manufactured special Ea® Intake Air Filters for both gasoline and diesel systems. AMSOIL/Injen Ea Intake Air Filters provide increased horsepower and torque, improved acceleration and fuel economy and maximum air flow. The high quality of AMSOIL Ea Filter media offers long filter life because filters can be cleaned and reused. For application and pricing information, consult your Account Zone at www.amsoil.com.



Ea® Pre-Filters

Help prevent large particles from sticking to EaAR and EaAU Filters and blocking the flow of air in racing applications. Polyester mesh bags fit over the top of existing air filters and feature an industrial-grade elastic band at the opening to ensure the pre-filter does not slide off. Prevent particles down to 0.005" from getting to the air filter without significantly reducing airflow. Particles larger than 0.005" generally fall off the pre-filter.



Stock No.	Unit of Measure	Fits	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
EAPF01	-FA	EaAR2102	0.2	13.95	18.60
EAPF02	-FA	EaAR2102‡	0.2	19.95	26.55
EAPF03	-FA	EaAR2103	0.2	13.95	18.60
EAPF04	-FA	EaAR2103‡	0.2	19.95	26.55
EAPF05	-FA	EaAR2104	0.2	13.95	18.60
EAPF06	-FA	EaAR2104‡	0.2	19.95	26.55
EAPF07	-FA	EaAR2105	0.2	13.95	18.60
EAPF08	-FA	EaAR2105‡	0.2	19.95	26.55
EAPF09	-FA	EaAR2106	0.2	19.95	26.55
EAPF10	-FA	EaAR2106‡	0.2	19.95	26.55
EAPF11	-FA	EaAU3560/4560	0.2	15.95	21.25

‡Fits Filter Unit with Top

EA® AIR FILTERS

Stock No.	Unit of Measure	Fits	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
Ea Pre-Filters for EaAU Filters					
EAPF12	-EA	EaAU4095	0.2	18.95	25.25
EAPF13	-EA	EaAU4091	0.2	20.95	27.90
EAPF14	-EA	EaAU4178	0.2	18.95	25.25
EAPF15	-EA	EaAU6080/6081	0.2	15.95	21.25
EAPF16	-EA	EaAU6075	0.2	15.95	21.25
EAPF17	-EA	EaAU6065	0.2	15.95	21.25
EAPF18	-EA	EaAU4075	0.2	15.95	21.25
EAPF19	-EA	EaAU4070	0.2	15.95	21.25
EAPF20	-EA	EaAU4510	0.2	18.95	25.25
EAPF21	-EA	EaAU3090/3590/4090	0.2	15.95	21.25
EAPF22	-EA	EaAU3555	0.2	13.95	18.60
EAPF24	-EA	EaAU3050	0.2	15.95	21.25
EAPF25	-EA	EaAU3051	0.2	15.95	21.25
EAPF26	-EA	EaAU3570	0.2	13.95	18.60
EAPF27	-EA	POD	0.2	9.95	13.30

Ea® Oil Filters

AMSOIL Ea Oil Filters are the highest efficiency filters available to the auto/light truck market. Featuring advanced full synthetic nanofiber technology, Ea Oil Filters provide greater efficiency, capacity and durability than cellulose filters, extending engine and filter life and reducing engine wear. When used in conjunction with AMSOIL Synthetic Motor Oil, AMSOIL Ea Oil Filters are guaranteed for extended service life:

- Ea Filters designated with product code Ea15K are recommended for 15,000 miles/one year, whichever comes first, in normal or severe service.
- Ea Filters designated with product code EaO are recommended for 25,000 miles/one year, whichever comes first, in normal service or 15,000 miles/one year, whichever comes first, in severe service.

Consult the AMSOIL Online Application Guide or MyAMSOILGarage™ at www.amsoil.com to determine the appropriate filter for each application. When AMSOIL Ea Oil Filters are used with a motor oil other than AMSOIL motor oil the filter should be changed according to the vehicle manufacturer recommendation.



EA® OIL FILTERS

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.	Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
EA15K09	-EA	(1) Filter	0.6	10.85	14.35	EAQ35	-EA	(1) Filter	0.9	13.90	18.30
EA15K09	-CA	(12) Filters	7.2	121.09	159.20	EAQ35	-CA	(12) Filters	10.8	155.40	204.60
EA15K10	-EA	(1) Filter	0.6	11.40	15.00	EAQ37	-EA	(1) Filter	0.7	14.05	18.45
EA15K10	-CA	(12) Filters	7.2	127.36	167.45	EAQ37	-CA	(12) Filters	8.4	157.20	207.00
EAQ11	-EA	(1) Filter	0.9	13.15	17.30	EAQ38	-EA	(1) Filter	0.7	14.35	18.85
EAQ11	-CA	(12) Filters	10.8	147.00	193.20	EAQ38	-CA	(12) Filters	8.4	160.20	210.60
EA15K12	-EA	(1) Filter	0.6	11.35	14.95	EAQ40	-EA	(1) Filter	1.0	13.90	18.30
EA15K12	-CA	(12) Filters	7.2	127.26	167.60	EAQ40	-CA	(12) Filters	12.0	155.40	204.60
EA15K13	-EA	(1) Filter	0.6	12.05	15.90	EAQ41	-EA	(1) Filter	1.0	13.90	18.30
EA15K13	-CA	(12) Filters	7.2	134.72	177.10	EAQ41	-CA	(12) Filters	12.0	155.40	204.60
EAQ15	-EA	(1) Filter	1.0	14.25	18.75	EAQ42	-EA	(1) Filter	1.0	13.75	18.10
EAQ15	-CA	(12) Filters	12.0	159.60	210.00	EAQ42	-CA	(12) Filters	12.0	153.60	202.20
EA15K20	-EA	(1) Filter	0.7	10.65	14.05	EAQ43	-EA	(1) Filter	1.0	13.90	18.30
EA15K20	-CA	(12) Filters	8.4	118.86	156.25	EAQ43	-CA	(12) Filters	12.0	155.40	204.60
EAQ21	-EA	(1) Filter	0.9	13.90	18.30	EAQ45	-EA	(1) Filter	1.1	14.35	18.85
EAQ21	-CA	(12) Filters	10.8	155.40	204.60	EAQ45	-CA	(12) Filters	13.2	160.20	210.60
EAQ22	-EA	(1) Filter	1.1	18.95	24.90	EA15K46	-EA	(1) Filter	0.7	13.90	18.30
EAQ22	-CA	(12) Filters	13.2	211.80	278.40	EA15K46	-CA	(12) Filters	8.4	155.40	204.60
EAQ23	-EA	(1) Filter	0.8	12.65	16.65	EAQ48	-EA	(1) Filter	0.9	13.90	18.30
EAQ23	-CA	(12) Filters	9.6	141.60	186.00	EAQ48	-CA	(12) Filters	10.8	155.40	204.60
EAQ24	-EA	(1) Filter	0.6	14.40	18.95	EA15K50	-EA	(1) Filter	0.7	12.95	17.05
EAQ24	-CA	(12) Filters	7.2	160.80	211.20	EA15K50	-CA	(12) Filters	8.4	144.84	190.55
EAQ25	-EA	(1) Filter	1.0	13.15	17.30	EA15K51	-EA	(1) Filter	0.7	11.35	14.95
EAQ25	-CA	(12) Filters	12.0	147.00	193.20	EA15K51	-CA	(12) Filters	8.4	126.67	166.50
EAQ26	-EA	(1) Filter	1.3	17.65	23.20	EAQ52	-EA	(1) Filter	1.0	14.35	18.85
EAQ26	-CA	(12) Filters	15.6	197.40	259.20	EAQ52	-CA	(12) Filters	12.0	160.20	210.60
EAQ27	-EA	(1) Filter	1.1	13.95	18.35	EAQ58	-EA	(1) Filter	0.7	13.15	17.30
EAQ27	-CA	(12) Filters	13.2	156.00	205.20	EAQ58	-CA	(12) Filters	8.4	147.00	193.20
EA15K29	-EA	(1) Filter	0.7	12.15	16.00	EAQ59	-EA	(1) Filter	0.8	13.90	18.30
EA15K29	-CA	(12) Filters	8.4	136.02	178.70	EAQ59	-CA	(12) Filters	9.6	155.40	204.60
EAQ31	-EA	(1) Filter	1.0	13.90	18.30	EAQ64	-EA	(1) Filter	0.6	12.65	16.65
EAQ31	-CA	(12) Filters	12.0	155.40	204.60	EAQ64	-CA	(12) Filters	7.2	141.60	186.00
EA15K32	-EA	(1) Filter	0.8	10.40	13.70	EAQ80	-EA	(1) Filter	2.0	18.85	24.80
EA15K32	-CA	(12) Filters	9.6	116.46	153.20	EAQ80	-CA	(12) Filters	24.0	210.60	276.60
EA15K33	-EA	(1) Filter	0.7	11.95	15.75	EAQ96	-EA	(1) Filter	1.3	13.65	17.95
EA15K33	-CA	(12) Filters	8.4	133.96	176.40	EAQ96	-CA	(12) Filters	15.6	152.40	200.40
EAQ34	-EA	(1) Filter	0.8	13.15	17.30	EAQ99	-EA	(1) Filter	2.2	21.45	28.20
EAQ34	-CA	(12) Filters	9.6	147.00	193.20	EAQ99	-CA	(12) Filters	26.4	239.40	314.40



Super Duty Oil Filter

For Ford 6.0/6.4L Power Stroke Diesel pickups. Features cellulose media designed for OEM-recommended change intervals. Compatible with BMK11 and BMK21 by-pass systems. Replaces Donaldson P550528 and WIX 57312.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
SDF88	-FA	(1) Oil Filter	0.5	17.95	23.60
SDF88	-CA	(12) Oil Filters	6.0	200.40	263.40

Ea® Motorcycle Air Filters

Made from ultra-premium synthetic nanofiber media. Hold 15 times more dust than wet gauze-type filters. Remove 5 times more dust than traditional cellulose filters and 50 times more dust than wet gauze.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
EAAM22	-FA	(1) Motorcycle Air Filter	1.0	14.50	38.70
EAAM23	-FA	(1) Motorcycle Air Filter	1.0	14.00	37.35
EAAM24	-FA	(1) Motorcycle Air Filter	0.4	18.40	49.00
EAAM25	-FA	(1) Motorcycle Air Filter	1.5	25.50	67.95
EAAM26	-FA	(1) Motorcycle Air Filter	1.4	31.60	84.30
EAAM27	-FA	(1) Motorcycle Air Filter	0.8	27.90	74.35
EAAM33096	-FA	(1) Motorcycle Air Filter	1.1	22.65	60.35
EAAM33104	-FA	(1) Motorcycle Air Filter	2.0	27.35	72.95
EAAM33196	-FA	(1) Motorcycle Air Filter	1.1	23.50	62.70
EAAM43701	-FA	(1) Motorcycle Air Filter	1.3	18.75	50.00
EAAM46199	-FA	(1) Motorcycle Air Filter	1.4	28.50	76.00
EAAM46299	-FA	(1) Motorcycle Air Filter	1.4	27.85	74.30



Ea® Motorcycle Oil Filters

Made from ultra-premium synthetic nanofiber media. Most efficient filters available for the motorcycle market. Many filters available in black or chrome.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
EAOM102	-FA	(1) Motorcycle Oil Filter	0.6	12.55	16.20
EAOM103	-FA	(1) Motorcycle Oil Filter	0.6	13.30	17.20
EAOM103C	-FA	(1) Motorcycle Oil Filter	0.6	16.60	21.40
EAOM109	-FA	(1) Motorcycle Oil Filter	0.6	13.60	17.55
EAOM109C	-FA	(1) Motorcycle Oil Filter	0.6	17.95	23.10
EAOM122	-FA	(1) Motorcycle Oil Filter	0.8	13.10	16.90
EAOM122C	-FA	(1) Motorcycle Oil Filter	0.8	17.15	22.10
EAOM132	-FA	(1) Motorcycle Oil Filter	0.7	11.05	14.25
EAOM132C	-FA	(1) Motorcycle Oil Filter	0.7	14.20	18.35
EAOM133	-FA	(1) Motorcycle Oil Filter	1.0	13.10	16.90
EAOM133C	-FA	(1) Motorcycle Oil Filter	1.0	17.20	22.15
EAOM134	-FA	(1) Motorcycle Oil Filter	0.8	11.20	14.45
EAOM134C	-FA	(1) Motorcycle Oil Filter	0.9	14.10	18.20
EAOM135	-FA	(1) Motorcycle Oil Filter	0.8	10.90	14.05
EAOM135C	-FA	(1) Motorcycle Oil Filter	0.9	15.20	19.65
EAOM136C	-FA	(1) Motorcycle Oil Filter	1.0	13.60	17.55
EAOM137C	-FA	(1) Motorcycle Oil Filter	1.0	17.30	22.30
EAOM138C	-FA	(1) Motorcycle Oil Filter	0.9	13.70	17.65



Note: "C" designates that the filter is chrome.

Super Duty Motorcycle Oil Filters

Full-flow filters designed specifically for extended drain intervals and severe service for motorcycle and ATV applications. Provide superior efficiency and greater capacity than other popular filters.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
SMF104	-FA	(1) Motorcycle Oil Filter	0.3	5.15	6.80
SMF113	-FA	(1) Motorcycle Oil Filter	0.2	7.85	10.05
SMF120	-FA	(1) Motorcycle Oil Filter	0.3	7.85	10.05
SMF121	-FA	(1) Motorcycle Oil Filter	0.3	7.85	10.05
SMF127	-FA	(1) Motorcycle Oil Filter	0.2	7.85	10.05
SMF131	-FA	(1) Motorcycle Oil Filter	0.2	6.35	8.25

PowerCore Air Filters

AMSOIL offers premium PowerCore Air Filters for Ford 6.0L and 7.3L Power Stroke Diesel, H2 Hummer 6.0L Vortec applications and select John Deere and Freightliner applications.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
P603577	-FA	(1) Air Filter	4.4	57.65	76.90
P610875	-FA	(1) Air Filter	2.4	45.55	60.75



SDF88

EA® MOTORCYCLE FILTERS

AMSOIL PowerCore Air Filter for H2 Hummer 6.0L Vortec Applications

PCFH2	-FA	(1) Air Filter	2.7	52.50	69.95
-------	-----	----------------	-----	-------	-------

7.3L Power Stroke Air Induction System

PCIS73	-FA	(1) Air Induction System	14.0	225.00	300.00
PCF73	-FA	(1) Replacement Air Filter	2.8	90.70	120.95

PowerCore Filter for Freightliner M2

P607955	-FA	(1) Primary Air Filter	4.4	69.25	92.35
---------	-----	------------------------	-----	-------	-------

PowerCore Filter for John Deere 6020 Series

P606121	-FA	(1) Primary (AL150288) Air Filter	1.0	34.40	45.90
P606119	-FA	(1) Secondary 4 Cylinder (AL119839) Air Filter	2.8	65.85	87.80
P606120	-FA	(1) Secondary 6 Cylinder (AL150285) Air Filter	3.8	73.90	98.55

Fuel Filter for Ford 6.0L Power Stroke Diesel Applications

FFK60	-FA	(2) Fuel Filters (Primary & Secondary)	2.0	45.00	60.00
-------	-----	--	-----	-------	-------

By-Pass Oil Filter Units

Remove particles less than one micron or larger, virtually eliminating engine wear. Filter all of the oil in a typical five-quart system in less than 10 minutes. Designed for use with AMSOIL Ea® Filters. By-pass replacement parts available online at www.amsoil.com.

Marine By-Pass Filter Mounting Kit

Easily accessible remote mounting capability for a full-flow spin-on oil filter and a spin-on by-pass oil filter. Specifically designed for marine applications with Alumiplated-coated materials to resist corrosion. Hoses are U.S. Coast Guard approved.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
BMK18	-FA	(1) Marine By-Pass Kit	10.2	410.00	472.00

Single Remote By-Pass Filter Mounting Kit

Without filter element - 1 by-pass filter required. For use with EaBP90, EaBP100 or EaBP110 By-Pass Filters.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
BMK21	-FA	(1) Single Remote By-Pass Kit	3.1	146.20	191.00

DUAL GARD® Mounting Kit

Links two AMSOIL By-Pass Filters together for engines with sump capacities greater than 20 quarts. Includes flow restrictor without hardware, hoses or by-pass filter elements - 2 by-pass filters required. For use with EaBP90, EaBP100 or EaBP110 By-Pass Filters.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
BMK22	-FA	(1) DUAL GARD By-Pass Kit	4.7	115.75	151.00

Dual Remote Oil Filtration Mounting Kit

Versatile system combines full-flow and by-pass filtration on a single, easy-to-install mount. Without filter elements - 1 by-pass and 1 full-flow required. For use with EaBP90, EaBP100 or EaBP110 By-Pass Filters. Must purchase spin-on adapter separately by matching full-flow filter thread. Consult next page for spin-on adapter kits and prices.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
BMK23	-FA	(1) Dual Remote Filtration Kit	8.6	208.50	271.65

Dual Remote System for Dodge Cummins Diesels

Includes an EaO26 Full-Flow Filter, EaBP100 By-Pass Filter and appropriate spin-on adapter for Dodge Cummins applications.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
BMK25	-FA	(1) Dodge Diesel By-Pass Kit	14.0	281.00	367.15

Dual Remote System for Ford 7.3L Power Stroke Diesels

Includes an EaO26 Full-Flow Filter, EaBP100 By-Pass Filter and appropriate spin-on adapter for Ford 7.3L Power Stroke applications.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
BMK26	-FA	(1) Ford Diesel By-Pass Kit	15.0	296.25	386.05

Dual Remote System for GM 6.6L Duramax Diesels

Includes an EaO26 Full-Flow Filter, EaBP100 By-Pass Filter and appropriate spin-on adapter for GM 6.6L Duramax applications.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
BMK27	-FA	(1) Duramax Diesel By-Pass Kit	14.0	283.75	370.45

Heavy-Duty By-Pass System

High-quality cast aluminum and steel filter spud have been thoroughly tested in on-road and severe off-road service. Powdercoated paint provides maximum resistance to degrading effects of road salt, debris and engine compartment chemicals. Maximum filtration performance for virtually all heavy-duty diesel applications, including Class 6, 7 and 8 heavy-duty trucks, off-road equipment, buses, generators, marine engines, logging and agricultural equipment. EaBP Filter sold separately.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
BMK30	-FA	(1) Heavy-Duty By-Pass Kit	7.0	107.40	140.00

BY-PASS FILTRATION UNITS





By-Pass Oil Filter Spin-On Filter Elements and Parts

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
EABP90	-EA	(1) 6" Filter	2.3	29.30	38.20
EABP100	-EA	(1) 8" Filter	2.7	31.75	41.40
EABP110	-EA	(1) 10" Filter	3.5	36.70	47.80
EABP120	-EA	(1) Heavy-Duty Filter for BMK30	4.7	41.95	54.60
BP250	-EA	Hose by the Foot	0.0	4.30	5.40

BMK18 Marine By-Pass Oil Filter Spin-On Adapter Parts

Part No.	Unit of Measure	Description	Cost
BK194	-EA	Filter Mount Assembly, BMK18	69.60
BP225	-EA	Mounting Bracket (Top)	7.25
BP226	-EA	Mounting Bracket (Bottom)	7.25
BP228	-EA	Allen Head Plug	8.60
BP229	-EA	Hose Fitting	31.25
BP230	-EA	1/2" I.D. Hose - Sold per Foot	78.40
BP231	-EA	90-Degree Fitting	34.00
BP232	-EA	O-Ring Fitting Adapter	12.65
BP239	-EA	BMK18 Installation Instructions	1.20
BP246	-EA	O-Ring for Adapter Nut	0.70
BP304	-EA	3/4" - 16 Thread Adapter Retaining Nut	24.00
BP305	-EA	13/16" - 16 Thread Adapter Retaining Nut	24.00
BP306	-EA	18mm x 1.5 Thread Adapter Retaining Nut	24.00
BP307	-EA	20mm x 1.5 Thread Adapter Retaining Nut	24.00

BMK21 Single Remote Oil Filter Aluminum Billet Parts

AMSOIL offers by-pass components to ease the installation of the BMK21 By-Pass Filtration System in three popular diesel engines: the Ford 6.0L Power Stroke, the Dodge 5.9L Cummins and the GM 6.6L Duramax.

Part No.	Unit of Measure	Description	Cost
BK1101	-EA	Aluminum Billet Oil Filter Cap	98.00
BK1102	-EA	Aluminum Billet Oil Fill Cap	51.50
BP242	-EA	90-Degree JIC Elbow	3.50

For installation of BMK21 on 2004 & later Dodge 5.9L Cummins pickups

BK1301	-EA	Aluminum Billet Oil Fill Cap (2007 & Older)	51.50
BK1302	-EA	Aluminum Billet Oil Fill Cap (2008 & Newer)	51.50
BP242	-EA	90-Degree JIC Elbow	3.50

For installation of BMK21 on GMC Duramax pickups

BK1201	-EA	Aluminum Oil Filter Sandwich Adapter w/O-Ring	51.50
BK1202	-EA	Aluminum Billet Oil Fill Cap	51.50
BP242	-EA	90-Degree JIC Elbow	3.50

BMK23 Dual Remote Adapter Parts

Purchase spin-on adapter separately by matching full-flow filter thread

Part No.	Unit of Measure	Description	Cost
BK295	-EA	Adapter 3/4" - 16	44.95
BK296	-EA	Adapter 13/16" - 16	44.95
BK297	-EA	Adapter 18mm - 1.5mm	44.95
BK298	-EA	Adapter 20mm - 1.5mm	44.95
BK299	-EA	Adapter 22mm - 1.5mm	44.95
BK300	-EA	Adapter 1" - 16	39.60
BK301	-EA	Adapter 1.5" - 16	55.20
BK302	-EA	Adapter 13/16" - 16	42.35

More by-pass parts available online @ www.amsoil.com

BY-PASS REPLACEMENT PARTS

Oil Analyzers

Oil Analysis Options

AMSOIL offers oil analysis service options from OIL ANALYZERS INC.® By analyzing used engine oil, a qualified lab can detect mechanical problems your equipment may have developed. For more information, visit www.oaitesting.com.

AMSOIL Oil Analysis Options

Stock No.	Unit of Measure	Kit Description	Package Quantity	Wholesale Cost, ea.	Min. Sugg. Retail, ea.
KIT01	-EA	Oil Sample Kit (Postage Paid)	1.0	24.99	31.25
KIT01	-CA	Oil Sample Kit (Postage Paid)	50.0	1,199.50	1,562.50
KIT01	-PK	Oil Sample Kit (Postage Paid)	100.0	2,399.00	3,125.00
KIT02	-EA	Oil Sample Kit (UPS Paid)	1.0	25.75	32.20
KIT06	-EA	Oil Sample Kit (Non-Postage Paid)	1.0	17.95	22.45
KIT06	-CA	Oil Sample Kit (Non-Postage Paid)	50.0	847.50	1,122.50
KIT06	-PK	Oil Sample Kit (Non-Postage Paid)	100.0	1,695.00	2,245.00
KIT09	-EA	Coolant Sample Kit	1.0	31.60	39.50
KIT10	-EA	Fuel Contamination Kit (UPS Paid)	1.0	65.59	82.00
KIT11	-EA	Fuel Performance Kit (UPS Paid)	1.0	91.25	114.10
KIT12	-EA	Winter Fuel Package (UPS Paid)	1.0	168.20	210.25
KIT13	-EA	Winter Fuel Package Plus (UPS Paid)	1.0	258.58	323.25

Oil Analysis Sample Collection Pump

Order a sample pump when ordering your sample kit. Makes drawing samples quick and easy. Comes with complete instructions and 10' of hose.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G1206	-EA	(1) OAI Pump	0.0	25.00	--	27.80
G1571	-EA	25' of Sampling Hose	0.0	7.95	--	8.85



OIL ANALYSIS



Quickshot®

Formulated to thoroughly clean varnish, gums and insoluble debris in two- and four-stroke gasoline-powered small engines and powersports equipment fuel systems, restoring peak performance. Effectively addresses performance issues related to ethanol, water and dirty pump gas. Stabilizes fuel between uses and during short-term storage periods.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
AQSCN	-FA	(1) 8.5-oz. Bottle†	0.6	6.65	--	8.80
AQSCN	-CA	(6) 8.5-oz. Bottles†	3.6	37.80	6.30	52.20
AQSQT	-FA	1 Quart†	2.0	21.10	--	27.25
AQSQT	-CA	12 Quarts†	24.0	240.90	20.08	325.25



P.i.® Performance Improver Gasoline Additive

Improves fuel mileage an average of 2.3% and up to 5.7%. Reduces emissions such as hydrocarbons (HC) up to 15%, carbon monoxide (CO) up to 26% and nitrous oxides (NOx) up to 17%. Restores power and performance. Reduces the need for costly higher-octane fuel. Reduces noise from carbon rap and pre-ignition. Offers better vehicle drivability and smoother operation.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
APICN	-FA	(1) 12-oz. Bottle†	0.9	8.75	--	11.55
APICN	-CA	(12) 12-oz. Bottles†	10.8	99.45	8.29	137.25



Gasoline Stabilizer

Reduces the oxidation process that occurs when fuel is stored for extended periods to help prevent the formation of varnish and sludge, which can clog injectors, stick floats and cause poor engine performance. Ideal for stored seasonal equipment such as snowmobiles, lawnmowers, motorcycles and boats.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
ASTCN	-FA	(1) 16-oz. Bottle†	1.1	8.40	--	11.15
ASTCN	-CA	(6) 16-oz. Bottles†	6.6	48.00	8.00	66.25



Diesel Concentrate

A total system cleaner and lubricity improver for all types of diesel engines. Improves the performance, fuel efficiency and longevity of diesel engines while reducing deposits, black smoke and emissions. Improves fuel economy by cleaning dirty injectors and restores horsepower. Designed for use in heavy-duty diesel engines.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
ADFCN	-FA	(1) 16-oz. Bottle†	1.2	5.80	--	7.70
ADFCN	-CA	(12) 16-oz. Bottles†	14.4	66.08	5.51	91.20
ADF05	-FA	5-Gallon Pail*†	40.2	158.25	--	210.50
ADF55	-FA	55-Gallon Drum*†	447.0	1,556.50	--	1,914.50



Cold Flow Improver

Use with Diesel Concentrate to improve cold-weather performance in applications below 40°F. Lowers the cold filter-plugging point by as much as 34°F and decreases the need for #1 diesel fuel that is diluted with kerosene. Contains jet-fuel-type deicer to help prevent ice formation in fuels that are contaminated with water.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
ACFCN	-FA	(1) 16-oz. Bottle†	1.2	5.50	--	7.30
ACFCN	-CA	(12) 16-oz. Bottles†	14.4	62.55	5.21	86.35
ACF05	-FA	5-Gallon Pail*†	40.0	149.50	--	198.85
ACE55	-FA	55-Gallon Drum*†	443.0	1,474.00	--	1,813.05



Diesel Concentrate Plus Cold Flow Improver

Combination of Diesel Concentrate and Cold Flow Improver in one convenient bottle. Improves the performance, fuel efficiency and longevity of diesel engines while reducing deposits, black smoke and emissions. Lowers the cold filter-plugging point by as much as 34°F and reduces the need for #1 diesel fuel that is diluted with kerosene.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
DFCCN	-FA	(1) 16-oz. Bottle†	1.2	7.10	--	9.45
DFCCN	-CA	(12) 16-oz. Bottles†	14.4	80.93	6.74	111.70
DFC05	-FA	5-Gallon Pail*†	40.0	206.50	--	274.65
DFC55	-FA	55-Gallon Drum*†	445.0	2,101.00	--	2,584.25



Diesel Recovery

Emergency diesel fuel treatment that dissolves the wax crystals that form when diesel fuel has surpassed its cloud point. Liquefies gelled diesel fuel and thaws frozen fuel filters. One bottle treats 30 gallons.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
DRCCN	-FA	(1) 30-oz. Bottle†	2.0	9.75	--	12.60
DRCCN	-CA	(12) 30-oz. Bottles†	24.0	111.00	9.25	149.85

Cetane Boost

Improves combustion efficiency to increase power in diesel engines. Raises cetane up to seven points. Also improves low-temperature starting, fuel ignition quality and reliability. For use in any diesel-fueled engine.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
ACBCN	-FA	(1) 16-oz. Bottle†	1.3	6.45	--	8.55
ACBCN	-CA	(12) 16-oz. Bottles†	15.6	73.20	6.10	101.05
ACB05	-FA	5-Gallon Pail*†	43.3	180.00	--	239.40
ACB55	-FA	55-Gallon Drum*†	481.3	1,817.75	--	2,235.85

Series 2000 Octane Boost

Maximizes power and improves performance in all two-cycle and four-cycle gasoline engines. Increases octane number up to seven points. Reduces engine knock, improves ignition and engine response, helps fuel burn cleaner and inhibits corrosion. Recommended for off-road and racing use.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
AOBBE	-FA	(1) 12-oz. Bottle†	0.8	7.45	--	9.65
AOBBE	-CA	(6) 12-oz. Bottles†	4.8	42.30	7.05	57.15

Engine Fogging Oil

Highly effective rust preventative designed to protect internal engine components during storage or long periods of inactivity. Ideal for outboard motors, lawn and garden equipment, motorcycles, snowmobiles, ATVs, motor homes and generators or any equipment with a two- or four-stroke engine.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
FOGSC	-FA	(1) 12-oz. Spray Can†	0.8	5.20	--	6.80
FOGSC	-CA	(6) 12-oz. Spray Cans†	4.8	29.70	4.95	40.10

MP Metal Protector

Displaces water and protects metal surfaces from rust and corrosion. Provides a light film that prevents metal-to-metal contact. Excellent for use on guns, hinges, squeaky mechanical objects, electrical systems and more. Penetrates existing rust buildup. Also dries wet electrical systems.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
AMPSC	-FA	(1) 8.75-oz. SP Can†	0.8	4.30	--	5.65
AMPSC	-CA	(12) 8.75-oz. SP Cans†	9.6	49.00	4.08	66.15
AMP55	-FA	55-Gallon Drum*†	407.3	1,395.00	--	1,563.00

MP Heavy Duty Metal Protector

Heavy-duty spray lubricant fortified with special rust and corrosion inhibitors. Penetrates and adheres to metal surfaces, leaving a long-lasting protective coating. Apply MPHD to any metal surface that requires a heavy-duty lubricant or is exposed to the damaging effects of salt, moisture or chemical corrosion. Works as an undercoat, leaving a wax-like film. Recommended for motorcycle chains. Won't sling off. Dry to the touch. Does not attract dust.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
AMHSC	-FA	(1) 16-oz. Spray Can†	1.4	6.05	--	7.90
AMHSC	-CA	(12) 16-oz. Spray Cans†	16.8	68.90	5.74	93.05

Silicone Spray

Perfect for lubricating non-metal surfaces that contact metal such as nylon, cardboard, fiberglass, wood or plastic. Special non-staining formula. USDA H-1 rated for incidental contact with food. Excellent for waterproofing leather boots, shoes, jackets, suede, etc.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
ALSSC	-FA	(1) 10-oz. Spray Can†	0.9	5.40	--	7.05
ALSSC	-CA	(6) 10-oz. Spray Cans†	5.4	30.80	5.13	41.60

FUEL ADDITIVES

CLEANERS & PROTECTANTS

CLEANERS & PROTECTANTS



Power Foam®

Improves starting and performance. Cleans dirty intake systems and spark plugs; frees sticky valves; removes gum, varnish and carbon deposits. Recommended for carburetors and fuel injectors.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
APFSC	-FA	(1) 18-oz. Spray Can†	1.5	5.80	--	7.55
APFSC	-CA	(12) 18-oz. Spray Cans†	18.0	66.20	5.52	89.40

Engine and Transmission Flush

Helps restore operating efficiency, increase fuel economy and reduce emissions in gasoline and diesel engines and automatic transmissions. Its potent detergent-based formula dissolves and disperses sludge, varnish and deposits, promoting lower operating temperatures and reduced oil consumption. More environmentally friendly than solvent-based products, providing safer cleaning action and easy disposal with waste oil.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
FLSHCN	-FA	(1) 16-oz. Bottle	1.2	6.85	--	9.10
FLSHCN	-CA	(12) 16-oz. Bottles	14.4	77.85	6.49	107.45
FLSHQ5	-FA	5-Gallon Pail*	40.0	199.75	--	265.70
FLSH55	-FA	55-Gallon Drum*	442.0	2,035.00	--	2,503.05

Miracle Wash®

Unique dry car wash and polish delivers outstanding performance and quick, easy and economical spray application. No water required. Simply the fastest way to clean your vehicle.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
AMWSC	-FA	(1) 13-oz. Spray Can†	1.0	7.25	--	9.40
AMWSC	-CA	(6) 13-oz. Spray Cans†	6.0	41.20	6.87	55.65
AMWQT	-FA	1 Quart	2.3	13.00	--	17.40
AMWQT	-CA	4 Quarts	9.2	49.40	12.35	69.20

Propylene Glycol Antifreeze and Engine Coolant

Super-long-life fluid - 750,000 miles/7 years of service in over-the-road trucks and 250,000 miles/7 years of service in auto/light-truck applications. Compatible with all major brands of antifreeze. Essentially nontoxic and biodegradable. Provides superior performance in all climates. Contains special corrosion inhibitors and anti-foam agents.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
ANT1G	-FA	1 Gallon	9.8	30.25	--	39.45
ANT1G	-CA	4 Gallons	39.2	115.20	28.80	156.10
ANT55	-FA	55-Gallon Drum*	536.0	1,504.25	--	1,657.70

Dominator® Coolant Boost

Formulated with proprietary tiered-surfactant technology and a robust mixture of corrosion inhibitors. Helps reduce engine temperatures, increase horsepower, promote faster engine warm-up times and reduce radiator and engine corrosion in racing and passenger vehicles. Indicates the need for a coolant change by changing color when used in straight water applications.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
RDCBCN	-FA	(1) 16-oz. Bottle	1.1	8.35	--	11.10
RDCBCN	-CA	(6) 16-oz. Bottles	6.6	47.70	7.95	65.85

High Performance Brake Fluid

Superior high-temperature performance in auto/light-truck, high-performance, racing and powersports applications. Formulated with the best zinc-based anti-corrosion additives and pH stabilizers. Designed for high-temperature stability, yet flows easily in low temperatures. High boiling temperatures ensure maximum life and reliable braking power, even in extreme conditions.

Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
BE3SN	-FA	(1) 12-oz. Bottle	1.0	5.50	--	7.20
BE3SN	-CA	(12) 12-oz. Bottles	12.0	62.80	5.23	84.80
Series 600 DOT 4 Racing Brake Fluid						
BE4SN	-FA	(1) 12-oz. Bottle	1.0	10.50	--	13.60
BE4SN	-CA	(12) 12-oz. Bottles	12.0	119.80	9.98	161.75

COOLANT



HYDRAULIC FLUIDS



Universal Power Steering Fluid

Provides excellent wear protection. Delivers better lubricity and reduced friction, resulting in cooler operating temperatures, longer component life and quieter operation. Low pour point ensures immediate lubrication at startup and in cold temperatures, yet resists thermal breakdown and maintains maximum protection in high temperatures. 100,000-mile service life. Meets or exceeds motor vehicle specifications for use in GM, Chrysler, Honda, Ford, Volkswagen, Mercedes, Saab, Subaru and Audi applications.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
PSECN	-FA	(1) 16-oz. Bottle	1.1	5.30	--	7.05
PSECN	-CA	(12) 16-oz. Bottles	13.2	60.38	5.03	83.35
PSE05	-FA	5-Gallon Pail	38.0	141.25	--	187.90
PSE55	-FA	55-Gallon Drum*	423.0	1,383.25	--	1,701.40

Fluid Extraction Pump

Aids in the removal of old fluids when servicing vehicles. High-quality pump can be used to remove old power steering fluid when converting a vehicle to AMSOIL Synthetic Power Steering Fluid. It can also be used to remove other fluids such as engine oil, drivetrain lubricants and engine coolant.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2576	-FA	(1) Extraction Pump	2.0	15.00	--	16.75

Filter Wrenches

Large Filter Wrench

Adjustable filter wrench has two clamping legs driven by a gear mechanism for maximum range and gripping ability. For auto/light-truck applications. Range: 3 1/8" to 3 7/8".



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2197	-FA	(1) Large Filter Wrench	1.3	11.50	--	12.80

Small Filter Wrench

Adjustable filter wrench has two clamping legs driven by a gear mechanism for maximum range and gripping ability. For auto and motorcycle applications in hard-to-reach locations. Range: 2 1/2" to 3 1/8".



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2198	-FA	(1) Small Filter Wrench	0.8	9.95	--	11.10

Strap Filter Wrench

Wide band tightens while you turn. Offers the widest range of any wrench. For all filters. Range: up to 6".



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2199	-FA	(1) Strap Wrench	0.5	3.90	--	4.35

Filter Cap Wrench

Designed for Harley-Davidson and BMW motorcycle oil filter applications and can be used to install and remove the following AMSOIL Ea® Motorcycle Oil Filters: EaOM122/122C, EaOM132/132C, EaOM133/133C, EaOM134/134C, EaOM135/135C and EaOM136C.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2309	-FA	(1) Filter Cap Wrench	0.5	1.90	--	2.15

Motorcycle Filter Wrench

Designed for 2000-2008 Harley-Davidson Twin Cam applications and can be used to install and remove AMSOIL Ea® Motorcycle Oil Filters EAOM134/134C and EAOM135/135C.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2685	-FA	(1) Motorcycle Filter Wrench	0.5	10.00	--	11.15

Motorcycle Filter Wrench

Can be used to install and remove AMSOIL Ea® Motorcycle Oil Filters EAOM103/103C and EAOM109/109C.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2686	-FA	(1) Motorcycle Filter Wrench	0.5	1.90	--	2.15

Mechanic's Lube Kit

Contains the most critical tools for complete lube service on most makes and models. Includes tools for foreign and domestic servicing. Each kit contains: (13) cap-type wrenches, (2) hex-cap socket wrenches, (2) swivel-type filter wrenches, (1) strap wrench, (1) small spider wrench, (1) adjustable pliers-type wrench, (6) drain plug wrenches, (2) metric square plug wrenches, (3) metric hex drain plug wrenches, (1) 12-point x 16mm drain plug wrench, (1) low-profile T45 Torx oil filter tool.



Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2200	-FA	(1) Mechanic's Lube Kit	20.0	150.00	--	167.00

HYDRAULIC FLUIDS

MISCELLANEOUS PRODUCTS



EaBP110 Cutaway Demo						
Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2204	-FA	(1) EaBP-110 Cutaway Demo	3.5	35.00	--	38.90



Ea® Oil Filter Cutaway Demo						
Ideal for demonstrating the superior quality and construction of AMSOIL Ea Oil Filters.						
Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2196	-FA	(1) EaO Filter Cutaway	1.0	35.00	--	38.90

Oil Fill Hand Pump						
Specially designed to fit AMSOIL quart, gallon and twin pack bottles. Guarantees efficient, quick dispensing of AMSOIL gear oils, transmission fluids and any oil that may need to be pumped. Great for fluid fills in differentials, transmissions, transaxles, boat lower units and boat stern drives.						
Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2039	-FA	(1) Hand Pump	0.7	9.95	--	11.10



Plexiglas By-Pass Display Mount						
Perfect for trade shows and other sales events.						
Stock No.	Unit of Measure	Pkg/Size	Wt. Lbs., ea.	Wholesale Cost, ea.	Cost Per Unit	Min. Sugg. Retail, ea.
G2410	-FA	(1) Plexiglass Mount Stand	6.0	62.00	--	69.00

MOTHERS®
Polishes•Waxes•Cleaners



Mothers® Car Care Appearance Products

Regular washing and waxing can easily make the difference between a long-lasting, luminous glow, or a dull finish. Proper vehicle maintenance involves cleaning paint and keeping it clean, which is a much smarter choice long-term than trying to repair distressed, damaged paint. Mothers offers a unique and wide product line that includes everything needed to clean, polish and care for vehicles. For application and pricing information, visit www.amsoil.com.



TRICO® Wiper Blades

AMSOIL offers four lines of wiper blades from TRICO: Exact Fit, NeoForm, Winter and Heavy Duty. TRICO is committed to providing the broadest line of wiper products at the highest level of quality for automotive original equipment manufacturers and the aftermarket. Drivers around the world depend on TRICO wiper blades. Their innovative design, quality production and superior performance make TRICO a perfect complement to AMSOIL and AMSOIL products. For application and pricing information, visit www.amsoil.com.



NGK® Spark Plugs and Plug Wires

NGK is the world leader in spark plugs and plug wires for both original equipment manufacturers and the aftermarket. AMSOIL offers NGK spark plugs and plug wires for auto/light-truck, powersports, auto racing and small engine applications. For application and pricing information, visit www.amsoil.com.

AMSOIL TOLL-FREE ORDERING LINE 1-800-777-7094
Sales Tax Information

AMSOIL INC. is registered to collect sales tax in each state, province and most local jurisdictions where applicable. AMSOIL is responsible for collecting and remitting sales tax to the appropriate taxing jurisdiction for all AMSOIL Dealers and accounts.

Tax Rate Determination

Sales tax rates are set in the following manner:

1. If you pick up your order at an AMSOIL Distribution center, you will be charged the applicable sales tax at that point of sale. This is the prevailing tax rate at that Distribution Center.

2. If you have the order shipped, sales tax will be charged at the rate applicable to the ship-to address, with the exception of orders being shipped within one of the following states: Illinois, Ohio, Pennsylvania, Texas and Virginia.

Exemption Certificates

If you prefer to pay state sales tax directly to your state revenue department rather than have it collected by AMSOIL at the time of purchase, contact your state for registration information.

AMSOIL INC. requires proper documentation on file at AMSOIL Corporate Headquarters for those with an exempt status. Refer to the Uniform Sales Tax Certificate (G495) for more information. Complete the Uniform Sales Tax Certificate if you are registered with your state to collect sales tax. Several states have state-specific requirements. These include: Florida, Indiana, Louisiana, Massachusetts, New York, Virginia, West Virginia and Wyoming. Refer to the Uniform Sales Tax Certificate for specific state-by-state requirements.

It is important that you are aware that under the terms of state registrations, you will be exempt only in those states in which you have a valid registration. It is the responsibility of AMSOIL INC. to collect sales tax on all sales unless the products are exempt or the ultimate purchaser provides a valid exemption certificate.

If you pick up products at an AMSOIL Distribution Center in a state where you are not registered to collect sales tax you will need to complete a Uniform Sales Tax Certificate and return it to AMSOIL INC. so the appropriate records can be updated. This will allow you to pick up products at any location with a tax exempt status because you are taking them into another state for resale.

Tax Rate Differences

If you have been charged an incorrect tax rate on your order, contact AMSOIL at:

AMSOIL INC .
Att: Sales Tax Dept.
925 Tower Ave.
Superior, WI 54880
(715) 392-7101

Please allow time for processing this rate change. Tax rate changes will be verified via a written notice from AMSOIL INC.

To recover or remit sales tax differences when you resell product in a different rate area, take the following steps:

1. Obtain a Sales Tax Refund Claim Form (G20) from AMSOIL INC., which is available in your Account Zone at www.amsoil.com or can be emailed or faxed upon request. Remit the completed and signed form along with the sales receipt copies of the different rate transactions.
2. Alternatively, you can deduct unrecovered portions of sales tax on your Federal Income Tax return on Schedule C.

order online @ www.amsoil.com

Sales Tax Table as of February 1, 2010

This table provides you with the state sales tax rate and a combined average rate by state. This will allow you to estimate the sales tax due on your order. Please note that the rate is an average combined rate and there may be other local rates you will need to take into consideration. Local taxing jurisdictions can include county, city, district, township, parish, borough, municipality, etc. At the time you place your order the correct sales tax will calculate based on the destination of your product or pick-up location. Sales tax is calculated at the point of sale, which is the location where the goods are received by the purchaser – the end destination. Sales tax rates will be broken out on your invoice into state and local taxing jurisdictions.

State	State Rate	Combined Average Rate*
Alabama	4.00%	8.15%
Alaska	--	1.45%
Arizona	5.60%	7.15%
Arkansas	6.00%	8.20%
California	6.25%	8.00%
Colorado	2.90%	6.40%
Connecticut	6.00%	6.00%
Delaware	--	--
District of Columbia	5.75%	5.75%
Florida	6.00%	6.70%
Georgia	4.00%	6.95%
Hawaii	4.00%	4.40%
Idaho	6.00%	6.05%
Illinois	6.25%	8.40%
Indiana	7.00%	7.00%
Iowa	6.00%	6.75%
Kansas	5.30%	6.90%
Kentucky	6.00%	6.00%
Louisiana	4.00%	8.70%
Maine	5.00%	5.00%
Maryland	6.00%	6.00%
Massachusetts	5.00%	5.00%
Michigan	6.00%	6.00%
Minnesota	6.50%	6.85%
Mississippi	7.00%	7.00%
Missouri	4.225%	7.05%
Montana	--	--
Nebraska	5.50%	6.00%
Nevada	6.50%	7.50%
New Hampshire	--	--
New Jersey	7.00%	6.95%
New Mexico	5.00%	6.40%
New York	4.00%	8.25%
North Carolina	4.50%	6.80%
North Dakota	5.00%	5.75%
Ohio	5.50%	6.80%
Oklahoma	4.50%	8.10%
Oregon	--	--
Pennsylvania	6.00%	6.25%
Puerto Rico	5.50%	5.5%
Rhode Island	7.00%	7.0%
South Carolina	6.00%	6.90%
South Dakota	4.00%	5.50%
Tennessee	7.00%	9.40%
Texas	6.25%	8.00%
Utah	4.70%	6.70%
Vermont	6.00%	6.05%
Virginia	4.00%	5.00%
Washington	6.50%	8.50%
West Virginia	6.00%	6.00%
Wisconsin	5.00%	5.40%
Wyoming	4.00%	5.35%

*Please note the combined rate is an average that may not include all local taxing jurisdictions at your location. These rates are effective January 1, 2009. Source: www.thestc.com/states.stm

AMSOIL TOLL-FREE ORDERING LINE 1-800-777-7094

Exempt Products or Freight

Clothing items are exempt from sales tax in the following states:

Connecticut	- Purchases less than \$50.00 are exempt
Massachusetts	- Purchases less than \$175.00 are exempt
Minnesota	- Total purchase exempt
New Jersey	- Total purchase exempt
New York	- Purchases less than \$110.00 are exempt
Pennsylvania	- Total purchase exempt
Rhode Island	- Total purchase exempt
Vermont	- Purchases less than \$110.00 are exempt

Vitamins are exempt from sales tax in the following states:

Connecticut	District of Columbia	Florida	Maryland
Michigan	New Jersey	New York	Pennsylvania
Texas	Vermont	Wyoming	

The following states pay a reduced tax for vitamins:

Illinois (1% state rate plus local taxes)	Utah (3%)
West Virginia (3%)	

Freight charges, when shipped by common carrier, are exempt from sales tax in the following states:

Alabama	Arizona	California	Colorado
Florida	Idaho	Illinois	Iowa
Kentucky	Maine	Maryland	Massachusetts
Missouri	Nevada	Oklahoma	Utah
Virginia	Wyoming		

Special Taxes

The following information applies to the states listed below in bold print that have excise taxes or other special taxes. Remember to add the excise taxes to the product total before figuring your sales tax. The excise taxes are not exempt from state sales tax.

Alabama:

- There is a 4% sales tax on air and oil filters, mounting kits, fuel additives, Metal Protector, Power Foam and car-care products.
- There is a \$0.06 per-gallon excise tax on Shock Therapy, Natural Gas Engine Oil, gear lube, chaincase lubricant, transmission fluid, bar and chain oil, grease, hydraulic oil, chain and gear oil, compressor oil and foam filter oil.
- There is a \$0.06 per-gallon excise tax plus a \$0.15 per-gallon inspection fee on engine oil, diesel oil and two-cycle oil.

California:

- Effective October 1, 1992 there is a \$0.26 per-gallon tax on all lubricating oil except differential additives, chaincase lubricant, two-cycle oils, bar and chain oil, grease, hydraulic oil, chain and gear oil and compressor oil.

Connecticut:

- Effective February 1, 1997 there is a 7% "Petroleum Tax" on all AMSOIL products except air filters, oil filters, by-pass oil filters, dual-remote oil filtration kits, BP parts, oil analysis kits, antifreeze and car-care products.

Florida:

- Effective June 1, 2011 all lubricating oils, transmission fluids, gear lubes and additives, except ACB, AOB, BF3, PSF and FLSH are charged the following Pollutants Tax depending on package size:

1 qt.	\$0.01	16 gal.	\$0.40
1 gal.	\$0.03	30 gal.	\$0.75
5 lit.	\$0.03	55 gal.	\$1.38
2.5 gal.	\$0.06	275 gal.	\$6.88
5 gal.	\$0.13		

Hawaii:

- Accounts or Dealers with a tax exemption must pay 0.5% on product total.
- Accounts or Dealers without a tax exemption must pay 4.5% on product total.

order online @ www.amsoil.com

Maine:

- Effective May 1, 2010, all gasoline and diesel oils are charged the following tax depending on package size:

<i>Gasoline</i>		<i>Diesel</i>	
1 gal.	\$0.35	1 qt.	\$0.09
5 gal.	\$1.75	1 gal.	\$0.35
16 gal.	\$17.60	5 lit.	\$0.46
30 gal.	\$33.00	5 gal.	\$1.75
55 gal.	\$60.50	30 gal.	\$10.50
275 gal.	\$302.50	55 gal.	\$19.25
		275 gal.	\$96.25

Rhode Island:

- There is a \$0.10 per-gallon tax on the ANT series.
- There is a \$0.05 per-quart tax on the following lubricating oils: engine oil, diesel oil, gear lube, chaincase lubricant, transmission fluid, two-cycle oil, bar and chain oil, hydraulic oil, chain and gear oil and compressor oil.
- There is a \$0.0025 per-gallon tax on products that contain organic solvents. These products include: two-cycle oil, gasoline additives, diesel fuel additives, Metal Protector, Silicone Spray, Power Foam and Engine Flush.

Tennessee:

- Effective April 1, 2011, there is a \$0.02 per-quart tax on all lubricating oils in package sizes of five gallons and under.

Texas:

- There is a \$0.01 per-quart tax on automotive oils. This includes: engine oil, diesel oil, gear lubes, transmission fluid and hydraulic/transmission fluid.

Utah:

- There is a \$0.04 per-quart lubricating oil fee pertaining to all containers except those 55 gallons or bigger on the following lubricants: engine oil, diesel oil, Shock Therapy, gear lube, hydraulic oil, chain and gear oil and compressor oil.

Freight and Handling Information

Freight and Handling Charges

You may order products shipped freight collect OR pre-pay the freight using the schedule included in your account-specific ordering information sheet (Dealer/P.C.: G2604; ROTS: G2603; Commercial: G2602).

Third-party billing is allowed. When third-party billing is requested, the UPS/FEDEX account number of the third party must be supplied at the time of order placement. Parcel Post shipments to military P.O. Boxes will be charged actual freight charges and cannot be shipped freight collect.

Additional Delivery Fees

Carriers may charge an additional fee for delivery to a residence. The consignee pays any ADDITIONAL freight charges in these situations. Allow up to 2-3 days more for rural delivery. Some LTL carriers charge a fee when customers request a call before delivery or lift gate service. The consignee pays for this additional service.

Pick-Up Orders

It is advisable to call the AMSOIL Distribution Center before travelling to pick up product. All orders scheduled for "Pick-Up" **must be picked up within 5 days of the date of the order.** This can also be pre-arranged with the distribution center manager. **Orders that are not picked up within the time-frame will be cancelled.**

Routing

You may include specific routing instructions with your order. However, because the pre-paid freight schedule is based on using the most economical method of transportation, the final decision on routing pre-paid freight orders rests with the AMSOIL Distribution Center Manager. If you need a specific routing guarantee, specify that your order be shipped "Freight Collect." UPS/FEDEX and Parcel Post shipments cannot be shipped Freight Collect. AMSOIL recommends searching for the best rates to your location and specifying Freight Collect for larger shipments.

Please contact your nearest AMSOIL Distribution Center for details when requesting air freight, expedited freight, LTL services or Saturday deliveries. Actual freight charges will apply in these situations, so be sure to ask for estimated delivery times via each shipping method and estimated costs to

AMSOIL DISTRIBUTION CENTERS

Location	Hours	Phone and Fax
Anchorage, Alaska 3020 N. Glenn Highway Palmer, AK 99645	C	Phone: 907/745-3542 Fax: 907/746-6265
Chicago, Illinois 831 Central Ave. Wooddale, IL 60191	A	Phone: 630/595-8385 Fax: 630/595-4601
Columbus, Ohio 707 Hadley Drive Columbus, Ohio 43228	A	Phone: 614/274-9851 Fax: 614/274-9852
Dallas, Texas 2232 Commerce Drive Arlington, TX 76011	A	Phone: 817/640-9923 Fax: 817/633-5160
Lancaster, Pennsylvania 1828 William Penn Way Lancaster, PA 17601	A	Phone: 717-396-0403 Fax: 717-396-0419
Las Vegas, Nevada 4545 N. Lamb Boulevard, Unit C Las Vegas, NV 89115	A	Phone: 702/644-2060 Fax: 702/644-2228
Orlando, Florida 3071 N. Orange Blossom Trail, Unit T Orlando, FL 32804	A	Phone: 407/296-4060 Fax: 407/296-8020
Portland, Oregon 16260 SW 72nd Ave. Building #2 Portland, OR 97224	A	Phone: 503/620-5213 Fax: 503/968-2878
Richmond, Virginia 530 Eastpark Court, Suite C-D Sandston, VA 23150	A	Phone: 804-328-2820 Fax: 804-328-2827
Superior, Wisconsin 1101 Susquehanna Ave. Superior, WI 54880	B	Phone: 715-395-0437 Phone: 715-395-0439 (Literature) Fax: 715-395-0432
Wichita, Kansas 3800 W. 29th St. South Suite 5 Wichita, KS 67217	A	Phone: 316/943-5858 Fax: 316/943-3842
Hours		
A –	Monday, Tuesday, Wednesday, Friday 9 am - 5:30 pm Thursday Noon - 8:30 pm Saturday, Sunday and Statutory Holidays Closed	
B –	Monday, Tuesday, Wednesday, Friday 8 am - 4:30 pm Thursday 8 am - 8:30 pm Saturday, Sunday and Statutory Holidays Closed	
C –	Tuesday through Saturday 9 am - 5:30 pm Sunday, Monday and Statutory Holidays Closed	

Shortages

On shipments with shortages, please note the number of pieces short on the delivery receipt and sign it. Then call the delivering carrier's office and report your shortage. If these efforts fail to complete your shipment within 10 days of receipt, contact your AMSOIL Distribution Center and request assistance.

Overages

On shipments with overages, please note the number of extra pieces on the delivery receipt and sign it. Then, contact your AMSOIL Distribution Center to make further arrangements.

Limited Distribution

Not every distribution center carries a complete inventory of the products listed on this price list. When there is a substantial repeat order for a product not carried by your distribution center, please discuss it with the Distribution Center Manager.

Claims and Damaged Shipments

(NOTE: Claims must be made within 7 days from the time of receipt.)

Items Picked Up at a Distribution Center

If you pick up an order at any distribution center and discover concealed damage when the product is opened, return the damaged product to the same distribution center for exchange at your convenience. Your copy of the invoice or packing slip should accompany such an exchange. The exchange can only be made for exactly the same products.

Parcel Post Shipments from a Distribution Center

1. Claims for damages by Parcel Post must be filed by the purchaser.
 2. Return damaged merchandise and cartons to the local post office when the claim is filed.
 3. All claims are returned to the shipper for verification of mailing date and distributor cost of the damaged items.
 4. If reimbursement is made to AMSOIL INC. as the shipper, AMSOIL will replace the shipment to the purchaser at no charge.
 5. You can also accept reimbursement on your claim. If so, you must place a re-order with the AMSOIL Distribution Center for replacement of your damaged products.
- Please note that some items listed in the price list cannot be shipped via Parcel Post –

United Parcel Service (UPS) & Federal Express (FEDEX) Shipments

Please inspect the shipment before signing for delivery. When there is visible damage, refuse to accept delivery. UPS/FEDEX will return the damaged goods to the AMSOIL Distribution Center and the distribution center will re-ship your order. If UPS/FEDEX delivers a package without a signature and you discover damaged goods inside, contact your local UPS/FEDEX office and refuse the shipment due to damage. When there is concealed damage discovered after you accept delivery, contact the AMSOIL Distribution Center for instructions immediately. NOTE: If you accept delivery of visibly damaged merchandise, you accept all responsibility for filing claims with UPS/FEDEX.

Other Shipments (LTL or Common Carrier)

1. When damaged goods are received, have the driver make note of the damage on the delivery receipt **before you sign it**.
2. Call the carrier's local office and request an inspection of the damaged goods.
3. File a claim with the carrier for the purchaser's cost of the merchandise.
4. Damage claims must be filed within 7 days. The sooner you file, the better.
5. Unlike UPS/FEDEX shipments, you should never refuse a damaged shipment when the products are delivered via a commercial carrier (truck lines). To do so will cost you freight both ways.

Re-Delivery Charges

If a freight carrier is unsuccessful when attempting to deliver to a "ship-to" address, a re-delivery charge may be necessary. This will be charged to the purchaser.

make your best routing decisions.

Expediting and Tracing

If you have not received your order in 5 to 7 days, contact the AMSOIL Distribution Center from which your order was shipped. Be prepared to furnish the following information:

1. Order date
2. Purchaser's name and account number
3. Order number (if known)
4. To whom the product was shipped with an address.

AMSOIL INC. will notify you of the method of shipment, date of shipment and present location as soon as possible.

**AMSOIL TOLL-FREE ORDERING LINE 1-800-777-7094
Lift Gate Service (LTL or Common Carriers)**

Customers can request lift gate service at the time of ordering if they do not have a method of unloading large orders, 30- and 55-gallon drums or totes. Not all carriers offer this service, so when requesting it please allow additional time for delivery. If lift gate service is requested, the consignee pays all costs for the additional service and will be charged the actual cost. Because these costs can vary depending upon the carrier used, it is recommended to contact the AMSOIL Distribution Center from which the order will be shipped prior to placing the order to obtain these costs.

Call Before Delivery Requests (LTL or Common Carriers)

At the time of order, customers can request to be contacted prior to delivery. A **daytime** phone number must be provided, with instructions to call before delivery. The carrier will contact the customer prior to delivery to set up a delivery time. If this service is requested, the consignee pays all costs for the additional service and will be charged the actual cost. Because these costs can vary depending upon the carrier used, it is recommended to contact the AMSOIL Distribution Center from which the order will be shipped prior to placing the order to obtain these costs.

ANY OTHER REQUESTS FOR SPECIAL SERVICES WILL BE CHARGED TO THE CONSIGNEE AT ACTUAL COSTS.

Shipping to APO and FPO Military Post Boxes

AMSOIL INC. ships orders to APO and FPO Military Post Boxes for customers' personal use only. Products may not be resold or redistributed. All APO/FPO orders are shipped from the AMSOIL Distribution Center in Superior, Wis. The United States Postal Service (USPS) will not accept AMSOIL Fuel Additives or Aerosol containers for shipment, or any product marked with "***" in this price list. Your order will be charged actual freight costs, which will be charged at the time the order is shipped. If you require insurance on your order, please specify at the time you place your order. These additional charges will be applied at the time of shipping.

Delays and Special Circumstances when Shipping to APO/FPO Addresses

Due to the challenging nature of distributing packages to these addresses, delays may be experienced which are beyond the control of AMSOIL INC. AMSOIL will ship your order with tracking information requested and/or a signature required for delivery.

Delays can be expected from time-to-time due to airline and customs inspections. AMSOIL makes every attempt to ship and track these orders to its military customers. However, once APO/FPO orders have been tendered for shipment to the USPS, AMSOIL loses control of routing and may or may not be notified of damages or non-deliveries. Customs may refuse and/or

order online @ www.amsoil.com

destroy shipments at their discretion.

AMSOIL CANNOT BE HELD RESPONSIBLE FOR THESE DECISIONS AND CANNOT REPLACE DESTROYED ORDERS.

Shipping to Alaska and Hawaii

Hawaiian orders are shipped from the Portland, Ore. or Superior, Wis. Distribution Centers using the best possible method and are charged actual freight. Most orders are shipped using United States Postal Service (USPS) Priority Flat Rate Boxes. The USPS will not accept AMSOIL fuel additives, aerosol containers or any product marked with "***" in this price list. Contact the Portland, Ore. Distribution Center to arrange surface transportation for large orders and orders with restricted items.

For purchases made from the AMSOIL Distribution Center in Alaska, add 7.5% to the total cost for extra freight expenses from the contiguous U.S. to Alaska. Alaskan orders for Superior-only items are charged actual freight.

Backorders and Invoices

Some orders may require multiple shipments due to products placed on backorder status. Backordered items will be shipped separately. This is also true for items that are not stocked at all distribution centers. These items may also be shipped from an alternate distribution center.

In such situations, each shipment will receive a separate invoice and credit card charge. Credit cards will not be charged until items ship. Although separate invoices are issued, totals for freight charges, taxes and discounts are calculated based upon the whole order.

Backorders receive priority status and will be shipped as soon as they become available. When items on an order are in backorder status and the order is to be picked up at a distribution center, the backordered items can be shipped to a destination of your choosing at the actual freight charge. Questions regarding the status of backordered items should be directed to the appropriate AMSOIL Distribution Center Manager.

Backorders will be shipped to the "ship-to" address on all orders.

AMSOIL® DISTRIBUTION CENTERS



