



UNIVERSITI PUTRA MALAYSIA

**ERGONOMIC CONSIDERATIONS FOR ASSEMBLY AND
DISASSEMBLY OF CNG TANKS ON A VEHICLE**

LO WOON CHEK.

FK 2006 64

**ERGONOMIC CONSIDERATIONS FOR ASSEMBLY AND DISASSEMBLY
OF CNG TANKS ON A VEHICLE**

By

LO WOON CHEK

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Partial Fulfilment of the Requirement for the Degree of Master of Science**

May 2006



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in partial fulfilment of the requirement for the degree of Master of Science

**ERGONOMIC CONSIDERATIONS FOR ASSEMBLY AND DISASSEMBLY
OF CNG TANKS ON A VEHICLE**

By

LO WOON CHEK

May 2006

Chairman: Associate Professor Rosnah Mohd. Yusuff, PhD

Faculty: Engineering

The use of natural gas as an automotive fuel is expanding worldwide, particularly so with the increasing price of petrol and diesel. Natural gas vehicle (NGV) is a relatively new and rapidly evolving technology in Malaysia. As of 2005, there were more than 12,000 NGVs and 38 refuelling stations available in the country. However, the use of natural gas as a vehicle fuel creates challenges in vehicle design. The installation of compressed natural gas (CNG) cylinders into the vehicle requires an analysis of the space availability, mounting system, design to assembly, disassembly and maintenance, fasteners operations, visibility and labelling issues, therefore creating a new impact on the vehicle design. In this study, a petrol fuelled sedan type passenger car has been chosen as a case study by its conversion to bi-fuelled and mono-fuelled NGV. A total of four designs have been introduced: locating the CNG

cylinders in the (i) luggage compartment and (ii) beneath the vehicle floor pan while retaining the original platform, also (iii) placing the cylinder under the backbone and (iv) rear platform by raising the floor. Ergonomics design guidelines and industrial NGV standards have played an important role in the design and design assessment. Many characteristics have been considered and studied to integrate the human into the system. These included equipment accessibility, workspace and operations, and physical accommodation. Virtual reality (VR), which enables the modelling of systems and components, was used for the simulation of assembly, disassembly, maintenance, reachability and visibility operations, and subsequently to evaluate and improve the designs. Concurrently, postural analyses were conducted using Rapid Upper Limb Assessment (RULA) technique. The virtual human contained within the VR software was used to perform the physical work, in an effort to reduce the risk of musculoskeletal disorder.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi sebahagian keperluan untuk ijazah Master Sains

**PERTIMBANGAN ERGONOMI DALAM PEMASANGAN DAN
PEMBUKAAN SILINDER CNG DALAM KERETA**

Oleh

LO WOON CHEK

Mei 2006

Pengerusi: Profesor Madya Rosnah Mohd. Yusuff, PhD

Fakulti: Kejuruteraan

Penggunaan gas asli sebagai bahan bakar kenderaan telah berkembang di serata dunia, terutamanya dengan peningkatan harga petrol dan minyak diesel. Kenderaan gas asli (NGV) merupakan satu teknologi baru yang sedang membangun di Malaysia. Pada tahun 2005, terdapat lebih daripada 12,000 NGV dan 38 stesen pengisian di negara ini. Akan tetapi, penggunaan gas asli telah mendatangkan cabaran kepada rekabentuk kenderaan. Pemasangan silinder gas asli termampat (CNG) pada kenderaan memerlukan analisis ruang, sistem pemasangan, rekabentuk untuk pemasangan, pembukaan dan penyenggaraan, operasi pengancingan, kebolehlihatan serta isu pelabelan, justeru memberikan kesan baru kepada rekabentuk kenderaan. Dalam kajian ini, sebuah kereta sedan yang mengguna petrol sebagai bahan api pada asalnya telah dipilih sebagai kes kajian dalam pengubahsuaian kepada NGV

menggunakan dua dan satu bahan api. Sebanyak empat rekabentuk telah diperkenalkan: pemasangan silinder di (i) tempat bagasi dan (ii) di bawah lantai kenderaan sementara mengekalkan badan asal, serta (iii) bawah backbone and (iv) lantai belakang dengan menaikkan badan kereta. Panduan rekabentuk ergonomi dan piawai NGV perindustrian telah memainkan peranan yang penting dalam rekabentuk dan taksiran rekabentuk. Banyak ciri-ciri telah dipertimbangkan dan dikaji untuk mengintegrasikan manusia ke dalam sistem. Ini termasuklah kebolehsampaian peralatan, ruang kerja serta operasi, dan penempatan fizikal. Realiti maya (VR) yang membolehkan pemodelan sistem dan komponen telah digunakan untuk mensimulasikan operasi pemasangan, pembukaan, penyenggaraan, kebolehcapaian serta kebolehlihatan, dan seterusnya menilai dan memperbaiki rekabentuk. Pada masa yang sama, postur analisis telah dijalankan dengan menggunakan teknik *Rapid Upper Limb Assessment* (RULA). Manusia maya yang terkandung dalam perisian VR telah digunakan untuk melaksanakan kerja fizikal, dalam usaha mengurangkan risiko gangguan kerangka otot.

ACKNOWLEDGEMENTS

There are many people I would like to thank for their help in getting this thesis off the ground. First of all, thanks to Associate Professor Dr. Rosnah Mohd. Yusuff for her guidance and encouragement not only in creating this thesis, but also in advising me since the day I arrived at Universiti Putra Malaysia. At the same time, I would like to thank Professor Ir. Dr. Barkawi Sahari and Associate Professor Dr. Megat Mohamad Hamdan Megat Ahmad for their recommendations and support as a committee. They have provided assistance and most importantly inspiration while pursuing this challenging degree.

This research could not be done without the help and support of my colleagues and friends at UPM: Norwazan Abdul Rahim, Siti Marhainis, Norfaizah, Noranom Said, and Idzwan. Last but not least, thanks to my family and friends who have been so supportive and understanding while I went through the MS program.

I certify that an Examination Committee has met on 16 May 2006 to conduct the final examination of Lo Woon Chek on his Master of Science thesis entitled “Ergonomic Considerations for Assembly and Disassembly of CNG Tanks on a Vehicle” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Jamarei Bin Othman, PhD

Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Chairman)

Wong Shaw Voon, PhD

Associate Professor

Faculty of Engineering

Universiti Putra Malaysia

(Internal Examiner)

Napsiah Ismail, PhD

Associate Professor

Faculty of Engineering

Universiti Putra Malaysia

(Internal Examiner)


Zahari Taha, PhD

Professor

Faculty of Engineering

Universiti Malaya

(External Examiner)


HASANAH MOHD. GHAZALI, PhD
Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 28 AUG 2006

This thesis submitted to the Senate of Universiti Putra Malaysia and has been accepted as partial fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

Rosnah Mohd. Yusuff, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Ir. Barkawi Bin Sahari, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Megat Mohamad Hamdan Megat Ahmad, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)



AINI IDERIS, PhD
Professor/Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 14 SEP 2006

DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



LO WOON CHEK
Date: 20 SEP 2006

TABLE OF CONTENTS

	Page
ABSTRACT	ii
ABSTRAK	iv
ACKNOWLEDGEMENTS	vi
APPROVAL	vii
DECLARATION	ix
LIST OF TABLES	xiii
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xix
 CHAPTER	
 1 INTRODUCTION	1
1.1 Problem Statement	3
1.2 Objectives	6
1.3 Scope of the Study	7
1.4 Significant of the Study	7
1.5 Thesis Outline	8
 2 LITERATURE REVIEW	10
2.1 Natural Gas Vehicles	11
2.1.1 Natural Gas	11
2.1.2 Advantages and Disadvantages of CNG	12
2.1.3 CNG Cylinders	15
2.1.4 Considerations for CNG Cylinder Selection	17
2.1.5 Labelling and Marking of CNG Cylinders	22
2.1.6 Types of NGVs	27
2.1.7 The Trend of NGV	31
2.2 Ergonomics	34
2.2.1 Ergonomics in Automotive Industry	37
2.2.2 RULA Analysis	41
2.2.3 Anthropometry	47
2.2.4 Virtual Human	52



2.3	Design for X	56
2.3.1	Human Factors Engineering in DFX	57
2.3.2	Design for Assembly	58
2.3.3	Design for Disassembly	65
2.3.4	Design for Maintainability	69
2.4	Discussion	73
3	METHODOLOGY	74
3.1	Flow of Project	75
3.2	Anthropometry Survey	77
3.2.1	Apparatus	77
3.2.2	Definition of Measurements	77
3.2.3	Data Processing	78
3.3	Define the Vehicle Characteristics	78
3.3.1	Information on NGV	79
3.3.2	Industrial NGV Standards	80
3.4	Develop and Determine the Design Solution	81
3.4.1	Analysis of Space Availability	82
3.4.2	Ergonomics Design Handbooks	85
3.5	Evaluate and Improve the Designs	86
3.6	Analysis Tools	87
3.6.1	CATIA V5	88
3.6.2	Envision Assembly	91
3.6.3	Envision ERGO	92
3.7	Discussion	93
4	RESULTS AND DISCUSSION	94
4.1	Anthropometric Data	95
4.2	Vehicle Characteristics	96
4.3	Conceptual Designs	97
4.4	Conversion without Modification to the Vehicle Platform	97
4.4.1	Locating the CNG Cylinder in the Luggage Compartment	97
4.4.2	Locating the CNG Cylinders Underneath the Vehicle Platform	109

4.5	Conversion with Modification to the Vehicle Platform	127
4.5.1	Front Platform	127
4.5.2	Rear Platform	142
4.6	Visibility of Label and Marking on CNG Cylinders	161
4.7	Fuel Capacity	163
4.8	Discussion	166
5	CONCLUSION	167
5.1	Recommendations for Further Study	172
	REFERENCES	174
	APPENDICES	182
	BIODATA OF THE AUTHOR	223



LIST OF TABLES

Table		Page
2.1	RULA grand score and action level	45
2.2	Evaluation of assembly design	65
2.3	Maintainability evaluation factors	72
4.1	Vehicle characteristics for the NGV design	96
4.2	Specification of the selected Faber tank	100
4.3	RULA analysis on the virtual human	105
4.4	RULA analysis on the virtual human reaching for the extended valve	106
4.5	Spaces available underneath the vehicle platform after removal of the gasoline fuel tank	112
4.6	Maximum length and diameter for the cylinders underneath the vehicle	112
4.7	Specifications of the Faber tanks underneath the vehicle	113
4.8	RULA analysis on the virtual human (5 th and 95 th percentile)	120
4.9	Specification of the special made cylinder at the new backbone	133
4.10	Specifications of the cylinders underneath the modified rear platform	145
4.11	RULA analysis on the virtual human assembling and disassembling the fasteners	150
4.12	RULA analysis on the virtual human assembling and disassembly the fasteners using the wrench extension	152



4.13	Fuel capacity of the NGVs	139
------	---------------------------	-----



LIST OF FIGURES

Figure		Page
2.1	Basic construction of the four types of CNG fuel cylinders for NGV (Stephens et al., 2002)	16
2.2	The RULA scoring sheet	43
3.1	Process flow chart in this study	76
3.2	Conceptual flow of designing the fuel storage system (Stephens et al., 2002)	82
3.3	Basic chassis frame of the vehicle	83
3.4	The flow of <i>CATIA V5</i> operation	90
4.1	Creating the Malaysian manikin in <i>CATIA V5</i> software	95
4.2	Spaces available in the luggage compartment	98
4.3	Calculation of diameter of the cylinder	99
4.4	CNG system in the luggage compartment	101
4.5	Clearance inspection of the bolt on “V” shape support bar during assembly and disassembly	102
4.6	Clearance inspection of the bolt on mounting bracket during assembly and disassembly	102
4.7	Clearance inspection with 95 th percentile Japanese male forearm	103
4.8	Simulation for reachability for the manual shut-off valve using 5 th percentile Japanese female	104
4.9	Simulation for reachability after extended the valve	106

4.10 (a)	The mannequin is preparing to reach for the spare wheel	107
4.10 (b)	The arms of the mannequin turned into orange during initial lifting	108
4.10 (c)	The arms changed back to yellow after the wheel if lifted	108
4.11	Spaces available underneath the vehicle platform, location A and B	110
4.12	Bottom isometric view of the rear platform after removed the original gasoline fuel tank	110
4.13	CNG cylinders mounted underneath the vehicle for location A and B	113
4.14	Bottom isometric view of the cylinders mounted underneath the vehicle	114
4.15	Bottom view of the cylinders mounted underneath the vehicle	115
4.16	Snug fit mounting of the cylinder	116
4.17	45 degrees slope of the fastener	117
4.18	Simulation of virtual human during assembly and disassembly	119
4.19	Visual span of the virtual human	121
4.20	Free-body diagram of segment one	122
4.21	Free-body diagram of segment two	125
4.22	The backbone at the front platform	128
4.23	The original and modified backbone	129
4.24 (a)	Original backbone with 5 th percentile female (isometric view)	130

4.24 (b)	New backbone with 5 th percentile female (isometric view)	130
4.24 (c)	Original and new backbone (front view)	131
4.25	New backbone with CNG cylinder and mounting	132
4.26	Components of CNG mounting system	134
4.27	Disassembly simulation of the bolt using socket wrench	135
4.28	Disassembly of CNG cylinder mounted under the backbone	137
4.29	In-line type impact wrench	138
4.30	Pistol type impact wrench	139
4.31	Mounting bracket with a hinged unit	140
4.32	Disassembling operation of hinge-mounted cylinder	141
4.33	Comparison between original and modified rear platform	143
4.34	Modified rear seat placed on the new rear platform	144
4.35	Arrangement of the cylinder underneath the rear platform	146
4.36	Continuous flexible straps used for mounting	147
4.37	Tool access for the fasteners	148
4.38	Simulation of maintenance using virtual human	149
4.39	Vision span of the virtual human	150
4.40	Assembling and disassembling the fasteners using wrench extension	151
4.41	Free-body diagram of segment one (without wrench extension)	153

4.42	Free-body diagram of segment one (with wrench extension)	155
4.43	Free-body diagram of segment two (without wrench extension)	157
4.44	Free-body diagram of segment two (with wrench extension)	159

LIST OF ABBREVIATIONS

3D	Three Dimensional
ANSI	American National Standards Institute
CAD	Computer Aided Design
CNG	Compressed Natural Gas
CNG-DI	Compressed Natural Gas Direct Injection
CTD	Cumulative Trauma Disorder
DFA	Design for Assembly
GLE	Gasoline Litre Equivalent
ISO	International Organization for Standardization
MSD	Musculoskeletal Disorder
NASA	National Aeronautics and Space Administration
NFPA	National Fire Protection Association
NGV	Natural Gas Vehicle
NIOSH	National Institute of Occupational Safety and Health
OEM	Original Equipment Manufacturer
OWAS	Ovako Working Posture Analyzing System
PNGV	PETRONAS NGV Sdn. Bhd.

PROTON	Perusahaan Otomobil Nasional Sendirian Berhad
REBA	Rapid Entire Body Assessment
RULA	Rapid Upper Limb Assessment
VR	Virtual Reality



CHAPTER 1

INTRODUCTION

Natural gas vehicle (NGV) technology has a long but sporadic history.

Environmental and energy supply concerns have received increasing attention in the past several decades, natural gas has been promoted as an alternative to petrol and diesel vehicles. The technology, marketing and political activities to support NGV commercialisation have grown substantially, particularly in the period of 1980 - 2000 (IANGV, 1998). Balancing the strengths and weaknesses of the fuel and vehicle technology, the fledgling NGV industry has an opportunity to change from an alternative fuel to a true fuel alternative.

NGV is a relatively new and rapidly evolving technology in Malaysia. As of 2005, there are more than 12,000 NGVs and 38 refuelling stations available in the country, compared to 975 converted NGVs and 8 refuelling stations in February 2000 (IANGV, 2004). These natural gas vehicles are mainly located in Klang Valley and Johor Bahru. Of this, retrofitted bi-fuel vehicles dominate the natural gas vehicle population in Malaysia with majority of the users being city taxis, while others

remain as airport tractors and forklifts. There is a drive to increase the share of natural gas in transportation energy. For this, there are two principal reasons, namely (a) reduction of emissions and (b) diversification of energy sources (Kojima, 2001).

Natural gas, as a cleaner burning fuel, significantly reduced exhaust emissions of other pollutants over all existing petroleum fuels and offers up to 100% reduction in particulate matter. The increase use of NGV can contribute to a reduction in urban air pollution and an improvement in air quality. Besides that, Malaysia has a large indigenous natural gas reserves but limited diversity. At $2.336 \times 10^9 \text{ m}^3$ (82.5 trillion cubic feet), these reserves are two times the amount of oil. Before the introduction of NGV, natural gas is focused on heating, furnaces, cooking and electricity generation only. Because of these, the government is looking to diversity it supply alternatives for energy generation by attempt its use through NGV.

The development of NGV industry in Malaysia is led by PETRONAS NGV Sdn. Bhd, a wholly owned subsidiary of PETRONAS. In order to promote the use of natural gas in the transportation sector, PETRONAS launched the Natural Gas Vehicles program in 1991. During May 1992, 450 NGVs were introduced in Malaysia. Various incentives are provided to encourage the motoring public to use

NGV, while ongoing efforts are being undertaken to expand the NGV refuelling facilities in the country as well as to enhance public awareness on NGV and its benefits. PETRONAS arranges cheap loans for the conversion of vehicles at about RM 2,300.00, and organizes training program for mechanics. The government, through exemptions from import and excise duties, subsidizes the program. The retail price of fuel for natural gas vehicles has been set at half the price of premium petrol. PETRONAS also introduced the *Enviro 2000* NGV taxi in 1996 to further promote the use of NGV. The government is currently targeting buses as the next public transport to convert to NGV.

1.1 Problem Statement

On-board compressed natural gas (CNG) fuel storage presents unique challenges for the commercialization of natural gas vehicles. Vehicle range, storage system, durability, weight and compatibility of component material are all key issues (Haaland and Kunz, 2000). Natural gas has a low volumetric energy density compared to petrol. On average, it takes 0.921 cubic meters (m³) of natural gas to equal the same energy content as one litre (l) of gasoline (Boykiw, 1999; Kojima, 2001).

As of Malaysia, due to the small size of CNG cylinder mounted in the luggage compartment of the converted NGV and lack of refuelling stations, it has resulted in long queues at the refuelling stations. The low CNG cylinder capacity also contributes to low travel distance and hence require constant refuelling. In order to store sufficient natural gas on board, increase the travel range and reduce the refuelling rate, a higher CNG cylinder capacity that can be mounted on the vehicle should be considered. The cheaper price of natural gas compared to the ever increasing price of petrol, also drive the use of higher cylinder capacity. As the more fuel a vehicle can carry, the better the economic payback will be.

Currently, the selections of cylinders to be mounted during conversion for various types of vehicles are based on the range of CNG cylinder sizes available in the market. The cylinders were mostly fitted in the luggage compartment irrespective to the space available in the various car models. These can be clearly seen on the converted saloon type vehicles available in Malaysia. For example, even though the luggage space accessible in *Proton Waja* vehicle is more compared to the *Proton Iswara* vehicle, the size of the CNG cylinders mounted in the luggage compartment are the same, as only one size of cylinder is available for the saloon type vehicle from the conversion company.