UTKARSH INDIA LIMITED

(Formerly Utkarsh Tubes & Pipes Limited)

Registered Office

23A, Netaji Subhas Road, 5th Floor, Suite No. 22, Kolkata 700 001, India, P: 033 2230 9124/25 F: +91 033 2230 5384 E: info@utkarshindia.in

Corporate Office:

Arrjavv Square, 95A, Elliot Road, 4th Floor, Kolkata 700 016, India, P: 033 2264 6666/2265 8888

Factory:

F1: NH6, Vill- Jangalpur, P.O. Andul Mouri, Howrah 711302, India, P: 033 2669 0833/1151/1571 F: 033 2669 3856


F2: NH2, Durgapur Expressway, P.O. Gurap, Hooghly 712303, India, P: 03213 253996

W: www.utkarshindia.in





Metal Beam Crash Barrier | High Mast, Polygonal/ Conical Poles & Steel Tubular Poles | Polymer Products |
Steel Tubes, Pipes & Poles | Railway Electrification Structures | Transmission Line Towers & Substation Structures















Our Product Range

W Beam

- 1. Single Side Single Barrier
- 3. Double Side Single Barrier
- 2. Single Side Double Barrier
- 4. Double Side Double Barrier



- Cold roll formed in thickness 3mm/2.8mrn/2.67mm
- Raw materials conforming to IS 5986/2062/10748 or equivalent of grade
- Fe360/Fe410/Fe510
- Hot deep galvanized to 550 gsm/sq.m
- Overall length 4318mm/3318mm/as per customized drawing
- Effective Length: 4000mm/3000mm
- Width: 311mm

• Thrie Beam

- 1. Single Side Single Barrier
- 3. Double Side Single Barrier
- 2. Single Side Double Barrier
- 4. Double Side Double Barrier
- R POST
- Thickness 3mm/2.8mm/2.67mm
- Raw materials conforming to IS 5986/2062/10748 or equivalent
- Hot deep galvanized to 550 gsm/sq.m
- Overall length 4318mm/3318 mm/as per customized drawings
- Effective Length: 4000mm/3000mm
- Width: 506mm

Anchorage System

- 1. L-Shaped turned down End Terminals
- 2. Fishtail Type End Terminal & U-shaped Median End Terminal
- 3. At Utkarsh, we are manufacturing all the components as per Standard Specification of MORTH







- 3mm/2.67mm/2.8mm thick L-shaped turned down End Terminals
- Fishtail Type End Terminal & U shaped Median End Terminal
- Raw materials conforming to IS 5986/2062/10748 or equivalent of grade Fe360/Fe410/Fe510 or equivalent
- Hot-dip galvanized to 550 gsm/sq.m



Post Spacer

- a) "C" & "I" Channel Section
- b) Raw materials conforming to IS 5986/2062/10748 or equivalent of grade Fe360/Fe410
- c) Dimensions 150mm X 75mm X 5mm thickness (length as per customer requirement)
- d) Post Spacing 2mtrs center to center or as per customer requirement








Fastners

- a) 16mm dia button heads bolts for splice joint and for connection of 'W' and 'Thrie' beam to spacer
- b) 16mm dia Hexagonal heads bolts for connecting Spacer and posts. conforming to IS 1364
- c) Hot-dip galvanized



Why Utkarsh Crash Barrier?

- Robustly constructed from high-quality raw materials
- Conforms to National & International Standards MORTH, India, American (AASHTO M180), Euro norm (EN 1317-1 & 2)
- In-house engineering and production facilities
- In-house quality checking & in-house lab-having UTM,
 Zinc Coating test facilities, etc.
- Raw materials from the highly reputed companies such as TATA and SAIL
- Pedestrian Guard Rail
- High precision in-house roll forming machines
- Strict Quality Control and Quality Systems (ISO 9001: 2015)
- Single source responsibility (Design & engineering, fabrication, Galvanising, Check supply)
- High reputation in govt. and private sectors
- Huge production capacity and strict delivery commitment
- 100% customer satisfaction

