

VEHICULAR RADIO SOLUTIONS

shaping the future in tactical communications



PRC-525 Combat Net Radio

The **PRC-525** high-performance digital radio covers HF, VHF and UHF bands using a single unit.

Thanks to different high-speed data modes and protocols as well as different antijam modes, it perfectly integrates into secure tactical communications networks.

All versions of the PRC-525 family are based on one mechanical platform, with a common logistic concept and the same man machine interface.

The equipment is software defined, so new features and releases can be simply downloaded even in the field.



Technical Characteristics

General

Frequency Range	1.5 to 512MHz	
Channel Spacing	HF	1 Hz
	V/UHF	1 Hz, 5, 6.25, 8.33, 12.5, 25, 50 KHz
Frequency Stability	± 1 ppm	
Pre-set Pages	100 (10 available on rotary switch)	
Modulations	A1A (CW), A3E (AM), J3E (USB, LSB), J2D, F3E (FM), F3E WB, F1D, A3E WB	
Waveforms	Secom H (HF frequency hopping), Secom V (VHF and UHF frequency hopping), OFDM, Stanag 4285, Stanag 4529, Stanag 4539, Stanag 4538, Have Quick	
Operation Modes	Fixed frequency (FF), secured frequency hopping (HF, VHF and UHF) and DDF, GPS mode (time, position), ALE	
Built-In Test (BITE)	Power Up BIT, Manual BIT, Continuous Monitoring	
Power Supply	16 to 30 VDC	
	19 to 30 VDC (fully specified)	
Manpack	Battery	Li Ion (rechargeable)
	Autonomy	>20 h (5 W, FM, 1:1:8 at 25°C)

Receiver

Sensitivity	(for 10dB SINAD)	
	HF-SSB	-115 dBm
	VHF-FM	-115 dBm
	UHF-FM	-112 dBm
Squelch	Syllabic squelch, 150 Hz tone squelch, signal squelch, RSSI (relative signal strength indication)	

Transmitter

RF Power Output		
HV Version	HF	1 mW, 0.5, 1, 2, 5, 10, 20 W
	VHF	1 mW, 0.5, 1, 2, 5, 10 W
VU Version	VHF, UHF	1 mW, 0.5, 1, 2, 5, 10 W

Options

Frequency Hopping	SECOM H, SECOM V, HAVE QUICK II
Data transmission	STANAG 4285, STANAG 4539, STANAG 4529 (HF), OFDM 72 kbps (VHF, UHF, FF)
ALE (HF)	2G: FED-STD-1045/1046/1049
	3G: MIL-STD-141B, STANAG 4538

Environmental

MIL-STD-810E	
Temperature	-40 °C to +70 °C (operating)
	-25 °C to +55 °C (fully specified)
Vibration	method 514.4
Shock	method 516.4
Leakage	method 512.3
	1 m immersion during 2 h

EMC

MIL-STD-461E	
CE102, CE106, CS101, CS103, CS104, CS105, CS114, RE102, RS103, RS105	

Mechanical

(manpack with battery pack)	
Dimensions (WxDxH)	199 x 309 x 74 mm
Weight	5.9 Kg

PRC-525

New generation Combat Net Radio

The **PRC-525** represents a revolution in the digital battlefield, enabling maximum flexibility in terms of frequency bands, waveforms and functions.


The PRC-525 based systems provide data routing, switching capability and interfacing to tactical analogue and digital networks, LAN and WAN networks, as well as PCs and other data terminal equipment connectivity. It is therefore the ideal choice for multiple roles, like network functions and mobile stations for command and control systems.

The tactical radios can be used in portable, vehicular and stationary applications including installations in movable shelters. The rugged hardware complies with the relevant MIL standards for environmental conditions. A great variety of accessories are available from EID and other suppliers for different required applications.

Applications and Systems

Integrated solutions for IP based tactical communications networks

All the accessories and ancillary equipment listed in this brochure are fully compatible with EID's PRC-525 and Rohde & Schwarz M3TR tactical radios.



MT-525

Radio Docking Stations



- Simple and rugged vehicular installation of tactical radios with optional VHF power amplifier (AP-525V)
- Single and double radio versions
- Shock and vibration absorbers
- Power input according to MIL-STD-1275B
- Meets demanding environmental specs MIL-STD-810E
- Ethernet connector in front panel for data access to radio
- Forced air cooling

AP-525V

50W VHF Power Amplifier

The AP-525V is a Linear Power Amplifier integrated on the PRC-525 Tactical Multiband Radio family and designed to be fitted on vehicular docking stations like the MT-525. It allows continuous operation from 30MHz to 108MHz with 50W PEP/CW transmit power supporting voice and data communications either in analogue or digital modes featuring high data rate modem up to 72Kbps and high speed frequency hopping (> 500 hops/s). The control is fully automatic and includes built in protection and monitoring functions.



Technical Characteristics

General

Frequency Range (TX / RX)	VHF: 30 to 108 MHz Bypass HF: 0.1 to 30 MHz Bypass UHF: 108 to 512 MHz
Modulation and Waveform	Same as PRC-525
Power Supply	18 to 32 VDC (MIL-STD-1275B) 22 to 29 VDC (fully specified)
RF Output Power @ 50 Ohms	1mW to 50W (with VSWR protection)
Harmonics level	≤ - 60 dBc @ 50 Ω
Intermodulation	≥ 36 dB referred to PEP

Environmental

Acc. to MIL-STD-1810E

Temperature	-40 °C to +70 °C (operating) -25 °C to +55 °C (fully specified)
Vibration	method 514.4, proc. I
Shock	method 516.4, proc. I
Leakage	IP5.5 (connectors with mating or with covers)
EMI/EMC	MIL-STD-461E CE101, CE102, CS101, CS103, CS104, CS105, CS114, RE102, CE106 RS103
Mechanical	
Dimensions (W x D x H)	290 x 140 x 101 mm
Weight	AP-525V 3.9 Kg AP-525VC 4.2 Kg (with cosite filter)
Colour	RAL9005 Black

Remote Console

CDS-525 / CDD-525

- Radio Remote control
- Voice and Data Services
- Loudspeaker with Volume Control and Mute function
- Field Telephone Set Integration
- Duplex and Relay (Repeater) operation modes




MA-250

Antenna Multicoupler

MA-250 is a VHF wide band antenna multicoupler which allows the connection of 2 VHF transmitters to a single antenna, reducing the number of antennas in radio communication systems. The MA-250A version designed for antennas with VSWR 1:3 or higher, includes an internal attenuator to increase the isolation between the transmitters.

An emergency connection is provided for one transmitter/receiver, bypassing all multicoupler electronics.



Technical Characteristics

General

Frequency Range	30 to 108 MHz
Maximum RF Power (per input)	60 W (PEP, CW)
Impedance	Input and Output: 50 Ω
Transmitter isolation	≥ 20 dB @ 50 Ω ≥ 10 dB with VSWR = 1:3 (MA-250) ≥ 15 dB with VSWR = 1:3 (MA-250A)
Insertion loss	≤ 3.8 dB via coupler (MA-250) ≤ 6.8 dB via coupler (MA-250A) ≤ 0.1 dB via emergency connection

Environmental

	MIL-STD-810F
Temperature	-40 °C to +70 °C (operating) -25 °C to +55 °C (fully specified)
Vibration	method 514.5
Shock	method 516.5
Leakage	EN 60529 IPX5

Mechanical

Dimensions (W x D x H)	160 x 92 x 185 mm
Weight	3.5 kg

SA-525/20

Antenna Tuning Unit

The **HF Antenna Tuning Unit SA-525/20** features automatic matching of electrically short HF antennas, as usually found in vehicular applications.

The SA-525/20 offers two modes of operation, the Active and the Silent tuning. In Active tuning the unit generates RF signal, optimizes VSWR and stores the tuning parameters. In Silent tuning pre-stored parameters are used. Tuning process can be remotely controlled via coaxial or optical interface for optimal NVIS behaviour. Furthermore the SA-525/20 is frequency hopping capable.



Technical Characteristics

General

Frequency Range	1.5 to 30 MHz
Maximum Power Input	25 W (PEP, CW)
Power Supply	MIL-STD-1275B
Matched Antennas	Whip antenna ≥ 3 m Long-wire and broadband antennas ≤ 15 m
Tuning Mode	Active or Silent tuning
Built-In Test	Continuous monitoring of RF level, temperature, supply voltage, etc.

Environmental

	MIL-STD-810F
Temperature range	-40 °C to +70 °C (operating) -25 °C to +55 °C (fully specified)
Vibration	method 514.5
Shock	method 516.5
Leakage	method 512.4

EMC

	MIL-STD-461E
	CE102, CE106, CS101, CS114, RE102, RS103

Mechanical

Dimensions (W x D x H)	147 x 72 x 225 mm
Weight:	2.0 Kg

CC-230

Active Loudspeaker

The CC-230 is an active 15W Class D Audio Amplifier designed to monitor received signals from a radio equipment or Intercom in a compact and rugged design, adaptable to a wide range of installation needs.



Technical Characteristics

General		Environmental	
Functions	Loudspeaker with volume control and Mute function Voice RX/TX via auxiliary handset/headset connector Automatic Current Limit	Temperature	MIL-STD-810F -40 °C to +70 °C (operating) -25 °C to +55 °C (fully specified)
Power Supply	10-33 VDC (MIL-STD-1275B)	Leakage	EN 60529 IPX5
Audio frequency range	350 to 5800 Hz	Mechanical	
Audio Output Power	15W / 8 Ohms Max.	Dimensions (W x D x H)	174 x 72 x 134 mm
		Weight	1.8 Kg
		Colour	RAL 6014 (Nato Green)

ER-525V

50W PRC-525 relay station

- Range extension node and gateway between nets
- Rugged, transportable enclosure
- Two 50W PRC-525 transceivers
- Modes of Operation: Fixed Frequency, Digital Fixed Frequency, Frequency Hopping
- Services: Voice and Data (up to 64Kbps)
- Power supply box: includes gel batteries charged from AC net, diesel generator, or 300W solar panels



HF wire antennas



- 1.5 to 30 MHz frequency range
- Horizontal polarization
- 150W CW input power
- Vehicular and portable applications

TWH-101R Tactical Wireless Headset

The TWH-101 tactical wireless headset provides mobility and freedom to field deployed squads. It features secure voice and data in a small, light, rugged and ergonomic design ready for future soldier programs

Full duplex multiuser conference, secured coding schemes and separated control of communications to the crew members in the vehicle and to the vehicle radios are key features of the TWH-101R.

The main components of TWH-101 system are the TWH-101R, a lightweight, compact and low power wireless radio transceiver compatible with different kinds of headsets; the TWH-101G a gateway from a deployed TWH-101R radio network to an intercom system such as ICC-201 or ICC-251 and the TWH-101C, a charger station for the mobile units.



Technical Characteristics

Standard Units

TWH-101G1	Mobile Gateway Unit for rough-sack
TWH-101G2	Fixed Installation Gateway Unit
TWH-101Rx	Mobile transceiver (options: Only voice, RS232 Data or USB Data)
TWH-101Cx	Battery Charger Unit (option: 3 or 5 Positions)

Electrical

Power Supply

TWH-101R	3VDC max. (2 x AA Alkaline or 2 x NiMH)
TWH-101G	9 to 33VDC (MIL-STD-1275D)
TWH-101C	9 to 33 VDC (MIL-STD-1275D)

Range

500m, open terrain conditions

Autonomy

> 15 hours (continuous operation)

Environmental

Operational Temperature	-40 °C to +70 °C (dependent on battery type)
Storage Temperature	-40 °C to +85 °C
Shock	method 516.6
Vibration	method 514.6
Salt fog	method 509.5
Immersion	method 512.5

Mechanical

Dimensions (W x D x H)

TWH-101G2	95 x 108 x 52 mm
TWH-101R	75 x 28 x 115 mm

Weight


TWH-101G2	680g
TWH-101R	225g (with batteries included)

MIL-STD-810G

Vehicle Installation

EID resources include a qualified and experienced team in radio communications offering fast response to customer specific requirements ranging from system concept definition to system deployment and maintenance support.

Armoured vehicles, fast patrol boats, small vessels and shelters are examples of EID implemented solutions and proved customer satisfaction.



Vehicular Radio Communications Solutions

- PRC-525 multi-band Combat Net Radio
- Docking Stations
- Power Amplifiers
- Remote Consoles
- Active Loudspeaker
- Antenna Multicouplers
- Antenna Tuning Units
- Power Units
- Relay Stations
- HF Wire Antennas
- System Engineering

P.O. Box 535
2821-901 Charneca da Caparica · Portugal
Tel.: (+351) 21 294 86 00 · Fax: (+351) 21 294 87 00
E-mail: eid@eid.pt · www.eid.pt

